

Water Resources Data Puerto Rico and the U.S. Virgin Islands Water Year 1992



U.S. GEOLOGICAL SURVEY WATER-DATA REPORT PR-92-1 Prepared in cooperation with the Commonwealth of Puerto Rico, the Government of the U.S. Virgin Islands and other agencies


		OC	TOB	ER						NO	VEM	BER					DE	CEM	BER		
S	M	Т	W	Т	F	S		S	M	Т	W	Т	F	S	S	M	Т	W	Т	F	S
		1	2	3	4	5							1	2							
6	7	8	9	10	11			3	1	5	6	7	1 8	9	1	2	3	4	5	6	7
13	14	15	16	17	18	19		10	11	12	13	14	15	16	8		10	11	12	13	14
20	21	22	23	24	- 7.			17	18	19		21	22	23	15		17	18	19	20	21
27	28	29			23	20		24		26	-	-	29	30	22		24	25	26		28
2. /	2.0	23	50	JI				27	23	20	21	20	23	30	29			2.0	20	21	20
															23	50	31				
											199	2	-,								•
		J	ANU.	ARY						F	EBR	UAR	Y					MAR	СН		
S	M	T	W	T	F	S		S	M	Т	W	Т	F	S	S	М	T	W	T	F	S
			1	2	3	4								1	1	2	3	4	5	6	7
5	6	7	8	9	10	11		2	3	4	5	6	7	8	8	9	10	11	12	13	14
12	13	14	15	16	17	18			10	11	12	13	14	15	15	16	17	18	19	20	21
19	20	21	22	23	24	25		16	17	18	19	20	21	22	22		24	25	26	27	28
26	27	28	29	30	31			23	24		26					30	31				
			APR	IL							MA	Y						JUNI	Ε		
S	M	Т	W	T	F	S		S	М	Т	W	Т	F	S	S	М	Т	W	T	F	S
			1	2	3	4							1	2		1	2	3	1	5	6
5	6	7	8	9	10	11		3	4	5	6	7	8	9	7	8	9	10	11	12	13
									-	-			-		14						
															21						
26	27	28	29	30		2.0		24	25	26	27	28	29	30	28	29	30	2 1	20	20	die f
								31			~ /	20	- J	00	20	20	00				
			JUL:	Y						Al	UGU:	ST					SEI	PTE	MBEI	3	
S	M	T	W	T	F	S		S	M	T	W	Т	F	S	S	M	T	W	T	F	S
			1	2	3	4								1			1	2	3	4	5
5	6							2	3	4	5	6	7		6	7					
																14					
															20						
															27					- 7	
		= 0						30				- 11			-						

30 31



Water Resources Data Puerto Rico and the U.S. Virgin Islands Water Year 1992

by P.L. Díaz, Z. Aquino, C. Figueroa-Alamo, R.J. Vachier, and A.V. Sánchez



U.S. GEOLOGICAL SURVEY WATER-DATA REPORT PR-92-1 Prepared in cooperation with the Commonwealth of Puerto Rico, the Government of the U.S. Virgin Islands and other agencies

U.S. DEPARTMENT OF THE INTERIOR BRUCE BABBITT, Secretary

U.S. GEOLOGICAL SURVEY Dallas L. Peck, Director

For additional information on the water resources investigation programs in Puerto Rico and the U.S. Virgin Islands write to:

Chief, Caribbean District, Water Resources Division
U.S. Geological Survey
P.O. Box 364424
San Juan, Puerto Rico 00936-4424
(Telephone: (809) 749-4346)

1993

PREFACE

This annual hydrologic data report of Puerto Rico and the U.S. Virgin Islands is one of a series of annual reports that document hydrologic data gathered from the U.S. Geological Survey's surface- and ground-water data-collection networks in each state, Puerto Rico, the U.S. Virgin Islands, and the other Trust Territories. These records of streamflow, ground-water levels, and quality of water provide the hydrologic information needed by state, local and Federal agencies, and the private sector for developing and managing our Nation's land and water resources.

The report is the culmination of a concerted effort by dedicated personnel of the U.S. Geological Survey, Water Resources Division who collected, compiled, analyzed, verified, and organized the data, and who typed, edited, and assembled the report. In addition to the authors, who had primary responsibility for assuring that the information contained herein is accurate, complete and adheres to Geological Survey policy and established guidelines, the following personnel contributed significantly to the collection, processing and tabulations of the data:

José M. Agis Carlos Narvaez George Arroyo Jerry A. Ortíz Angel Class-Cacho Keith Overton Iris M. Concepción Antonio Pagán-Gavino Felix V. Elías David Peyton Angel G. Ferrer Rafael Peña-Cortez Eduardo Figueroa Francisco Pérez-Blair Pedro Galindo Carlos C. Rodríguez José González Julio A. Rodríguez Evelyn S. Guevara Miguel Rodríguez José René Sánchez Senén Guzmán-Ríos

Allen Heaken Luis Santiago-Rivera
Felipe Hernández Carlos Santos
Richard Kessler Luis Soler

Sandra Lagares Heriberto Torres-Sierra

Xevier Maldonado José A. Torres Ernesto Mangual Ahmed Valencia

Ruth I. Guzmán typed the text of the report. Rafael Medina prepared the illustrations.

This report was prepared in cooperation with agencies of the Commonwealth of Puerto Rico, the Government of the U.S. Virgin Islands, and with other federal agencies under the general supervision of Allen L. Zack, District Chief, Caribbean District, San Juan, Puerto Rico.

REPORT DOCUMENTATION 1. REPORT NO. 2.	3. Recipient's Accession No.
PAGE USGS/WRD/HD-93/269	
N. Trile and Subtitle Water Resources Data for Puerto Rico and the U.S. Virgin	5. Report Date April 5, 1993
Islands Water Year 1993	6.
7. Author(s) Pedro L. Díaz, Zaida Aquino, Carlos Figueroa-Alamo, Ricardo J. Vachier, Ana V. Sánchez	8. Performing Organization Rept. No. USGS-WDR-PR-92-1
9. Performing Organization Name and Address	10. Project/Task/Work Unit No.
U.S. Geological Survey, Water Resources Division	11. Contract(C) or Grant(G) No.
P.O. Box 364424	(C)
San Juan, Puerto Rico 00936-4424	(G)
12. Sponsoring Organization Name and Address	13. Type of Report & Period Covered
U.S. Geological Survey, Water Resources Division	Annual-Oct. 1, 1991
P.O. Box 364424	to Sept. 30, 1992
San Juan, Puerto Rico 00936-4424	14.
15. Su plementary Notes	
6. Abstract (Limit: 200 words)	
Water resources data for surface-water, quality-of-water, and ground Rico and the U.S. Virgin Islands, consists of records of discharge, water quality-of-water ground contains discharge records for 74 streamflow-gaging stations; daily sediment or miscellaneous streamflow stations; stage records for 9 reservoirs; water-quality-of-water ground streamsites, 11 lake sites, 2 lagoons, and 1 bay; and water-level records that part of the National Water Data System collected by the U.S. Geologica Puerto Rico and the U.S. Virgin Islands.	lity of streams, and water levels of wells. This report records for 21 streamflow stations; 112 partial-record ality records for 16 streamflow-gaging stations, 42 ords for 91 observation wells. These data represent
Water resources data for surface-water, quality-of-water, and ground Rico and the U.S. Virgin Islands, consists of records of discharge, water qua contains discharge records for 74 streamflow-gaging stations; daily sediment or miscellaneous streamflow stations; stage records for 9 reservoirs; water-quality ungaged streamsites, 11 lake sites, 2 lagoons, and 1 bay; and water-level record part of the National Water Data System collected by the U.S. Geologica Puerto Rico and the U.S. Virgin Islands.	lity of streams, and water levels of wells. This report records for 21 streamflow stations; 112 partial-record ality records for 16 streamflow-gaging stations, 42 ords for 91 observation wells. These data represent I Survey and cooperating local and federal agencies in
Water resources data for surface-water, quality-of-water, and ground Rico and the U.S. Virgin Islands, consists of records of discharge, water qua contains discharge records for 74 streamflow-gaging stations; daily sediment or miscellaneous streamflow stations; stage records for 9 reservoirs; water-qua ungaged streamsites, 11 lake sites, 2 lagoons, and 1 bay; and water-level record that part of the National Water Data System collected by the U.S. Geologica Puerto Rico and the U.S. Virgin Islands. 7. Document Analysis Descriptors *Surface water, *Water quality, *Ground water, Aquifers, Chemical analysis	lity of streams, and water levels of wells. This report records for 21 streamflow stations; 112 partial-record ality records for 16 streamflow-gaging stations, 42 ords for 91 observation wells. These data represent I Survey and cooperating local and federal agencies in
Rico and the U.S. Virgin Islands, consists of records of discharge, water qua contains discharge records for 74 streamflow-gaging stations; daily sediment or miscellaneous streamflow stations; stage records for 9 reservoirs; water-quangaged streamsites, 11 lake sites, 2 lagoons, and 1 bay; and water-level records that part of the National Water Data System collected by the U.S. Geologica Puerto Rico and the U.S. Virgin Islands. 7. Document Analysis • Descriptors *Surface water, *Water quality, *Ground water, Aquifers, Chemical analysis Streamflow, Water analysis, Water Levels, Lakes.	lity of streams, and water levels of wells. This report records for 21 streamflow stations; 112 partial-record ality records for 16 streamflow-gaging stations, 42 ords for 91 observation wells. These data represent I Survey and cooperating local and federal agencies in

c. COSATI Field/Group

18. Availability Statemen;

NO RESTRICTION ON DISTRIBUTIONS

19. Security Class (This Report)

Unclassified

20. Security Class (This Page)

Unclassified

21. No. of Pages

618 22. Price

CONTENTS

	Pag
Preface	. iii
List of surface-water and water-quality stations, in downstream	
order, for which records are published in this volume	vii
List of ground-water wells, by basin, for which records are	
published in this volume	xii
List of discontinued surface-water discharge or stage-only stations	
Introduction	
Cooperation	. 2
Summary of hydrologic conditions	. 3
Precipitation	. 3
Surface water	
Ground water	. 5
Water quality	
Special networks and programs	
Explanation of records	
Station identification numbers	
Downstream order system	
Latitude-longitude system	
Records of stage and water discharge	
Data collection and computation	
Data presentation	
Station manuscript	
Data table of daily mean values	
Statistics of monthly mean data	
Summary statistics	
Identifying estimated daily discharge	
Accuracy of the records	
Records of surface-water quality	
Classification of records	
Arrangement of records	
On-site measurements and sample collection	
Water temperature	
Sediment	
Laboratory measurements	
Data presentation	
Remark codes	
Records of ground-water levels	
Data collection and computation	
Data presentation	
Records of ground-water quality	
Data collection and computation	
Data presentation	
Access to WATSTORE data	
Definition of terms	
Publications on Techniques of Water-Resources Investigations	
Surface- and quality-of-water records for Puerto Rico	
Discharge at partial-record stations in Puerto Rico	
Ground-water records for Puerto Rico	
Surface-water records for the U.S. Virgin Islands	
Ground-water records for the U.S. Virgin Islands	
HIUGA	773

ILLUSTRATIONS

			Page
Eigura	1	Crowle sharping mouthly many discharge of calcutal streams in Directo Disc	4
rigure		Graph showing monthly-mean discharge of selected streams in Puerto Rico	4
	۷.	Virgin Islands	7
	3	Map showing location of fecal coliform bacteria concentration at sampled sites	
		Map showing location of fecal streptococci bacteria concentration at sampled sites	
		Map showing location of surface-water stations in Puerto Rico	
		Map showing location of water-quality stations in Puerto Rico	
		Map showing location of low-flow partial-record stations in Southwest Puerto Rico	
		Map showing location of ground-water stations in Puerto Rico	
		Map showing location of ground water stations in U.S. Virgin Islands	
		Map showing location of ground-water stations in the U.S. Virgin Islands	
		Map showing location of surface-water stations in Vieques and Culebra Islands	
		Grid showing system for numbering wells and miscellaneous site (latitude and longitude)	
		Map showing the Río Guajataca basin	
		Map showing the Rio Camuy basin	
		Map showing the Río Grande de Arecibo basin	
		Map showing the Río Grande de Manatí basin	
		Map showing the Río Cibuco basin	
		Map showing the Río de la Plata basin	
		Map showing the Río Hondo to the Río Puerto Nuevo basins	
		Map showing the Río Grande de Loíza basin	
		Map showing northeastern river basins the Río Herrera to the Río Antón Ruíz basins	
		Map showing southeastern river basins the Río Humacao to the Río Seco basins	
		Map showing south coast river basins the Río Salinas to the Río Jacaguas basins	
		Map showing south coast river basins the Río Inabón to the Río Loco basins	
		Map showing the Río Guanajibo basin	
		Map showing the Río Yagüez and the Río Grande de Añasco basins	
		Map showing the Río Culebrinas basin	
		TABLES	
			Page
Table	1.	Island-wide monthly precipitation and annual averages for 1992 water year and	
		the 30-year reference period, 1951-80	3
	2.	Peak discharges during January 5-6, 1992 and maximums previously recorded	
		at selected streamflow gaging stations in Puerto Rico	5
	3.	Highest water level recorded during 1992 water year and previous high water	
		level (in feet below land-surface datum) at selected ground-water wells in	_
	,	Puerto Rico and the U.S. Virgin Islands	6
	4.	Surface-water quality stations in Puerto Rico with highest concentration of	^
	5.	selected constituents during water year 1992	8
		equivalents per liter	. 34

SURFACE-WATER AND WATER-QUALITY STATIONS, IN DOWNSTREAM ORDER, FOR WHICH RECORDS ARE PUBLISHED IN THIS VOLUME

(Letter after station name designates type of data: (d) discharge, (c) chemical, (b) biological, (s) sediment, (p) pesticide, (e) elevation, gage heights)

	Station number	Page
RIO GUAJATACA BASIN		
Río Guajataca at Lares (d,c,b)	50010500	46
Canal Principal de Diversiones at Lago Guajataca (c,b)		49
Río Guajataca above mouth near Quebradillas (c,b)		51
RIO CAMUY BASIN		
Río Camuy at Tres Pueblos Sinkhole (d)	50014600	54
Río Camuy near Bayaney (d)		55
Río Camuy near Hatillo (d)		56
RIO GRANDE DE ARECIBO BASIN		
Río Grande de Arecibo near Adjuntas (c,b)	50020500	60
Río Grande de Arecibo near Utuado (c,b)		62
Río Saliente at Coabey near Jayuya (d)		64
Río Caonillas above Lago Caonillas near Jayuya (c,b)		65
Lago Caonillas at Caonillas (e)		67
Río Grande de Arecibo below Lago Dos Bocas near Florida (c,b)		68
Río Grande de Arecibo above Arecibo (d)		70
Río Tanamá near Utuado (d,c,b,s)	50028000	72
Río Tanamá at Charco Hondo (d)	50028400	81
Río Grande de Arecibo at Central Cambalache (c,b)	50029000	82
RIO GRANDE DE MANATI BASIN		
Río Orocovis at Orocovis (d)	50030460	86
Río Orocovis near Orocovis (c,b)	50030700	89
Río Grande de Manatí near Morovis (d,c,b)		91
Lago El Guineo at Damsite (e)	50032290	94
Lago Matrullas at Damsite (e)	50032590	95
Río Bauta near Orocovis (d)	50034000	96
Río Grande de Manatí at Ciales (d)	50035000	97
Río Grande de Manatí at Highway 149 at Ciales (c,b)	50035500	98
Río Cialitos at Highway 649 at Ciales (c,b)	50035950	100
Río Grande de Manatí at Highway 2 near Manatí (d,c,b,p)	50038100	102
LAGUNA TORTUGUERO BASIN		
Laguna Tortuguero Outlet near Vega Baja (c,b)	50038200	106
RIO CIBUCO BASIN		
Río Cibuco below Corozal (d,c,b)	50038320	108
Río Cibuco at Vega Baja (d,c,b)		111
RIO DE LA PLATA BASIN		
Lago Carite at Gate Tower (e)	50039990	116
Río de La Plata at Proyecto La Plata (d,c,b)		117
Río de La Plata at Comerio (d)		120
Río de La Plata near Comerio (c,b)		127
Río Guadiana at Guadiana (d)		129
Río Guadiana near Naranjito (c,b)		141
Lago La Plata at Damsite (e)		143
Río de La Plata below La Plata Dam (d)		144
Río de La Plata at Highway 2 near Toa Alta (d,c,b,s,p)	50046000	159

	Station number	Page
RIO HONDO BASIN		
Río Hondo at Flood Channel near Cataño (c,b)	50047530	164
RIO DE BAYAMON BASIN		
Lago de Cidra at Damsite near Cidra (e)	50047550	166
Río de Bayamón below Cidra Dam (d)		167
Río de Bayamón near Aguas Buenas (c,b)		178
Río de Bayamón near Bayamón (d)	50047850	180
Río Guaynabo near Bayamón (c,b)		182
Río de Bayamón at Flood Channel at Bayamón (c,b,p)	50048510	183
RIO PUERTO NUEVO BASIN		
Río Piedras:		
Río Piedras at El Señorial (d,s)	50048770	185
Río Piedras near Río Piedras (c,b,p)		192
Río Piedras at Río Piedras (d,s)		194
Río Piedras at Hato Rey (d,c,b)	50049100	201
Laguna San José:		
Laguna San José No 2 at San Juan (c,b)	50049820	204
Bahía de San Juan:	•	
Bahía de San Juan No 5 at San Juan (c,b)	50049920	205
QUEBRADA BLASINA BASIN		
Quebrada Blasina near Carolina (c,b)	50050300	208
RIO GRANDE DE LOIZA BASIN		
Río Grande de Loíza at Quebrada Arenas (d)		210
Quebrada Blanca at El Jagual (d,s)		212
Quebrada Salvatierra near San Lorenzo (d,s)		219
Río Cayaguas at Cerro Gordo (d)		226
Río Grande de Loíza at Highway 183 near San Lorenzo (d)		227
Río Turabo above Borinquen (d)		241
Río Grande de Loíza at Caguas (d,c,b,s)		255
Río Caguitas near Aguas Buenas (d)		264 278
Río Caguitas at Villa Blanca at Caguas (d)		278
Río Bairoa at Bairoa (d)		291
Río Bairoa near Caguas (c,b)		296
Río Gurabo:	50055400	270
Río Gurabo below El Mangó (d)	50055750	298
Río Valenciano near Juncos (d)		306
Quebrada Mamey near Gurabo (d)		314
Río Gurabo at Gurabo (d,s)		316
Río Gurabo near Gurabo (c,b)		324
Río Cañas at Río Cañas (d,s)		326
Lago Loíza at Damsite (c,b,e)		334
Río Grande de Loíza below Trujillo Alto (c,b)		336
Río Grande de Loíza at Carolina (e)		338
Río Canóvanas near Campo Rico (d)	50061800	340

SURFACE-WATER AND WATER-QUALITY STATIONS, IN DOWNSTREAM ORDER, FOR WHICH RECORDS ARE PUBLISHED IN THIS VOLUME.-Continued

IX

	Station number	Page
RIO ESPIRITU SANTO BASIN		
Quebrada Sonadora near El Verde (d)	50063440	344
Quebrada Toronja at El Verde (d)		346
Río Espíritu Santo near Río Grande (d,c,b)		348
Río Grande near El Verde (d)		351
RIO MAMEYES BASIN		
Río Mameyes near Sabana (d)	50065500	353
RIO SABANA BASIN		
Río Sabana at Sabana (d)	50067000	355
RIO FAJARDO BASIN		
Río Fajardo near Fajardo (d,c,b,p)		357
Río Fajardo below Fajardo (c,b)	50072500	360
RIO BLANCO BASIN		
Río Icacos near Naguabo (d)	50075000	362
RIO HUMACAO BASIN		
Río Humacao at Las Piedras (d)		366
Río Humacao at Highway 3 at Humacao (c,b)	50082000	367
RIO GUAYANES BASIN		
Río Guayanés at Yabucoa (c,b,p)		369
Río Guayanés above mouth at Playa de Guayanés (c,b)	50086500	371
RIO MAUNABO BASIN		
Río Maunabo at Lizas (d)		373
Río Maunabo at Maunabo (c,b)	50091000	374
RIO CHICO BASIN		
Río Chico at Providencia (c,b)	50091800	376
RIO GRANDE DE PATILLAS BASIN		
Río Grande de Patillas near Patillas (c,b)	50092000	378
RIO SALINAS BASIN		
Río Lapas near Rabo del Buey (d)		382
Río Majada at La Plena (d)	50100450	383
RIO COAMO BASIN		
Río Coamo near Coamo (c,b)	50106500	384
RIO DESCALABRADO BASIN		
Río Descalabrado near Los Llanos (d)	50108000	386
RIO JACAGUAS BASIN		
Río Toa Vaca above Lago Toa Vaca (d,s)		387
Río Jacaguas at Juana Díaz (d)	50111500	394
RIO INABON BASIN		
Río Inabón at Real Abajo (d)	50112500	396

X SURFACE-WATER AND WATER-QUALITY STATIONS, IN DOWNSTREAM ORDER, FOR WHICH RECORDS ARE PUBLISHED IN THIS VOLUME--Continued

	Station number	Page
RIO BUCANA BASIN		
Río Bucaná:		
Río Cerrillos above Lago Cerrillos near Ponce (d)		397
Río Cerrillos near Ponce (d,c,b)		398
Río Bucaná at Hwy 14 Bridge near Ponce (d)	50114390	401
RIO PORTUGUES BASIN		
Río Portugués near Ponce (d,c,b)	50115000	402
Río Portugués at Ponce (c,b,p)		405
RIO GUAYANILLA BASIN		
Río Guayanilla near Guayanilla (d)	50124200	407
Río Guayanilla at Central Rufina (c,b,p)		408
DIO VALICO DACIN		
RIO YAUCO BASIN	E012E700	410
Lago Luchetti at Damsite (e)	30123780	410
RIO LOCO BASIN		
Río Loco at Guánica (c,b,p)	50129700	411
RIO GUANAJIBO BASIN		
Río Guanajibo at Highway 119 at San Germán (d)	50131990	414
Río Guanajibo near San Germán (c,b)		415
Río Rosario near Hormigueros (d,c,b,s)	50136400	417
Río Guanajibo near Hormigueros (d,c,b,p)	50138000	426
RIO YAGUEZ BASIN		
Río Yagüez near Mayagüez (c,b)	50138800	430
DIO CHANDE DE AÑACCO DACIN		
RIO GRANDE DE AÑASCO BASIN Lago Guayo near Castañer (e)	501/1500	432
Río Grande de Añasco near Lares (c,b)		433
Río Grande de Añasco near San Sebastián (d,c,b,s)		435
Río Grande de Añasco near Añasco (c,b,p)		438
•		
RIO CULEBRINAS BASIN	501.45400	4.40
Río Culebrinas near San Sebastián (c,b)		442
Río Culebrinas at Highway 404 near Moca (d)		444 445
Río Culebrinas near Aguada (c,b,p)	30149100	443
CULEBRA, P.R.		
Quebrada Resaca near Monte Resaca (e)		447
Drainage Canal at Culebra Airport (e)	50215000	448
VIEQUES, P.R.		
Quebrada Cofresí Tributary near Isabela II (e)	50231000	449
Quebrada La Mina near Esperanza (e)		451
Quebrada Pilón at Colonia Puerto Real (e)	50233000	453
ST THOMAS, US VIRGIN ISLANDS		
Bonne Resolution Gut at Bonne Resolution (d)	50252000	538
Turpentine Run at Mariendal (d)		539
ST JOHN, US VIRGIN ISLANDS	E000#000	<i>-</i>
Guinea Gut at Bethany (d)		540
Cruz Bay Gut at Cruz Bay (e)	50295500	541

SURFACE-WATER AND WATER-QUALITY STATIONS, IN DOWNSTREAM ORDER, FOR WHICH RECORDS ARE PUBLISHED IN THIS VOLUME--Continued

ΧI

	Station number	Page
ST CROIX, US VIRGIN ISLANDS		
River Gut at River (e)	50332000	542
River Gut near Golden Grove (d)	50333500	543
River Gut at Hwy 66 at Fairplanes (d)		544
Bethlehen Gut at Hwy 66 at Fairplanes (d)		547
Gut 4.5 at Cane Valley (e)		550
Jolly Hill Gut at Jolly Hill (d)		551
Salt River at Canaan (e)		552
Gut 10 near Altona (e)		553
Discharge at partial-record stations and miscellaneous sites		455
Low-flow partial-record stations		456
Analyses of samples collected of water-quality partial-record		
stations and miscellaneous sites		469

	Page
RIO GUAJATACA BASIN	
Well 182422067015100 Local number 165	
Well 182647066552400 Local number 202	
70. 70. 70. 70. 70. 70. 70. 70. 70. 70.	
RIO GRANDE DE ARECIBO BASIN	
Well 182737066370900 Local number 204	484
RIO GRANDE DE MANATI BASIN	
Well 182757066325600 Local number 206	485
Well 182710066303700 Local number 207	
Well 182308066260400 Local number 210	
DIO CIRLICO PACIN	
RIO CIBUCO BASIN	400
Well 182647066201700 Local number 70	
Well 182615066235300 Local number 211	
Well 182515066194000 Local number 212	
Well 182330066185700 Local number 213	491
RIO DE LA PLATA BASIN	
Well 182746066170800 Local number 214	492
Well 182530066135400 Local number 216	493
Well 182655066142400 Local number 217	494
RIO HONDO TO RIO PUERTO NUEVO BASINS	
Well 182623066111000 Local number 218	495
Well 182441066082600 Local number 219	
Well 182413066044000 Local number 220	
Well 182511066045401 Local number PN-2	
Well 182435066052701 Local number PN-5	
Well 182445066043401 Local number PN-6	
Well 182437066040501 Local number PN-7	
Well 182443066041502 Local number PN-8c	
Well 182417066042700 Local number PN-10	
Well 182349066032600 Local number PN-13	
Well 182406066034700 Local number PN-19	
RIO GRANDE DE LOIZA BASIN	
Well 181550065593201 Local number 50	
Well 182515065594100 Local number 222	
Well 181513065554601 Local number CJ-TW-3B	
Well 181352066025300 Local number CJ-TW-19A	509
RIO HUMACAO TO RIO SECO BASINS	
Well 175858066100200 Local number 6	510
Well 180415065513900 Local number 96	

	Page
RIO SALINAS TO RIO JACAGUAS BASINS	
Well 175829066232200 Local number 87	512
Well 180002066132200 Local number 67 Well 180002066132200 Local number HW-TW-01	
Well 180001066122002 Local number HW-TW-03C	
Well 175947066130601 Local number HW-TW-05B	
Well 175957066123400 Local number HW-TW-13	
Well 175946066102000 Local number HW-TW-14	
Well 180206066135500 Local number RM-05	
Well 180104066152300 Local number RM-10	519
RIO INABON TO RIO LOCO BASINS	
Well 180133066503300 Local number 132	520
Well 175900066354200 Local number 141	
11 11 11 11 11 11 11 11 11 11 11 11 11	
RIO GUANAJIBO BASIN	
Well 180132067033800 Local number 143	
Well 180627067080600 Local number CR-TW-1	523
Well 180628067075800 Local number CR-TW-2A	524
Well 180628067075801 Local number CR-TW-2B	525
Well 180628067075802 Local number CR-TW-2C	526
Well 180643067080400 Local number CR-TW-3	527
Well 180650067073700 Local number CR-TW-4	528
Well 180557067083100 Local number CR-TW-5	529
Well 180617067083300 Local number CR-TW-6	530
Well 180604067085100 Local number CR-TW-7	531
Well 180547067084800 Local number CR-TW-8	532
Well 180628067084300 Local number CR-TW-9A	
Well 180547067073100 Local number CR-TW-10	
RIO CULEBRINAS BASIN	
Well 182442067091700 Local number 200	535
ST. CROIX, U.S. VIRGIN ISLANDS	
Well 174225064471900 Local number 1	556
Well 174225064472000 Local number 2	557
Well 174243064475100 Local number 3	
Well 174245064475800 Local number 4	
Well 174308064484400 Local number 6	
Well 174525064460600 Local number 7	
Well 174527064460100 Local number 8	
Well 174532064460300 Local number 9	
Well 174329064454700 Local number 10	
Well 174303064481100 Local number 11	
Well 174308064482800 Local number 12	
WEIL 1/4500004402000 LOUR BUILDEL 12	<i></i>

XIV GROUND-WATER WELLS, BY BASIN, FOR WHICH RECORDS ARE PUBLISHED--Continued

	Page
Well 174316064480800 Local number 13	. 567
Well 174247064475701 Local number 14	. 568
Well 174319064454401 Local number 15	
ST. THOMAS, U.S. VIRGIN ISLANDS	
Well 182050064580400 Local number 1	. 570
Well 182138064543100 Local number 2	. 571
Well 182138064542500 Local number 3	. 572
Well 182136064541900 Local number 4	. 573
Well 182038064550300 Local number 6	. 574
Well 182036064545200 Local number 7	. 575
Well 182038064580000 Local number 8	. 576
Well 181917064524600 Local number 9	. 577
Well 182131064541000 Local number 10	. 578
Well 182035064550200 Local number 11	. 579
ST. JOHN, U.S. VIRGIN ISLANDS	
Well 182010064472600 Local number 1	. 580
Well 182109064460300 Local number 2	. 581
Well 182116064451000 Local number 3	. 582
Well 182042064454500 Local number 5	. 583
Well 182044064454600 Local number 6	. 584
Well 182044064454800 Local number 7	. 585
Well 182044064454900 Local number 8	. 586
Well 182044064455000 Local number 9	. 587
Well 182044064455200 Local number 10	. 588
Well 181956064464500 Local number 11	. 589
Well 182110064430000 Local number 12	. 590
Well 181950064422300 Local number 13	. 5 91
Well 182048064430400 Local number 14	592

DISCONTINUED STREAMFLOW STATIONS

The following continuous-record streamflow stations in Puerto Rico and the U.S. Virgin Islands have been discontinued or converted to partial-record stations. Daily streamflow or stage records were collected for the period of record shown for each station.

Station	Station name	Draina ge	Period of
number		area (mi²)	record
50007000 50010600 50011000 50011200	Quebrada de los Cedros near Isabela Río Guajataca above Lago de Guajataca Canal Diversion Lago Guajataca Río Guajataca below Lago Guajataca	6.91	1970 1984-89 1970 1969-70, 1984-87
50011400	Río Guajataca above mouth near Quebradillas		1969-70, 1984-89
50013000	Río Camuy near Lares	7.62	1969-71
50014000	Río Criminales near Lares	4.68	1969-70
50016000	Río Camuy near Camuy		1969-73
50021000	Río Pellejas at Central Pellejas	5.46	1968-70
50021050	Río Pellejas below Central Pellejas	7.89	1972-75
50021500	Río Pellejas near Utuado	9.55	1969-71
50023000	Río Viví near Central Pellejas	5.66	1969-75
50027200	Río Grande de Arecibo blw. Lago dos Bocas	169	1970-71
50029000	Río Grande de Arecibo at Central Cambalache	200	1969-83
50031500	Río Sana Muerto near Orocovis	3.68	1965-70
50035200	Río Grande de Manatí at Hwy 145 at Ciales	132	1972
50035950	Río Cialitos at Hwy 649 at Ciales	17	1970-82
50038360	Río Mavilla near Corozal	9.51	1969-70
50038600	Río Unibón near Morovis	5.29	1969-70
50038700	Río Morovis at Morovis	1.26	1968
50038900 50039600 50043200 50043400 50044600	Río Indio at Vega Baja Río Cibuco at Central San Vicente Río Usabon near Barranquitas Río Aibonito Tributary near Aibonito Río Guadiana near Naranjito	9.15 1.13 1.73	1963,66,71 1969-72 1968-69,71 1968-71 1971
50044650	Quebrada del Toro near Naranjito	0.54	1971
50044800	Quebrada Anones near Naranjito	2.32	1971
50045700	Río Lajas at Toa Alta	8.65	1966-75
50047820	Río de Bayamón at Hwy 174 near Bayamón	31.90	1966
50048000	Río de Bayamón at Bayamón	71.90	1963-67
50049310	Quebrada Josefina at Piñero Avenue	3.84	1988-91
50053050	Río Turabo at Borinquen	7.89	1984-90
50054000	Quebrada de las Quebradillas near Caguas	6.25	1969-71,73
50055650	Quebrada Caimito near Juncos	0.82	1984-87
50056000	Río Valenciano near Las Piedras	6.85	1971
50058300 50061300 50062500 50063300 50065700	Quebrada Arena near Caguas Río Canovanillas near Loíza Río Herrera near Colonia Dolores Río Espíritu Santo near El Verde Río Mameyes at Hwy 191 at Mameyes	14.40 2.75 2.23 11.80	1971 1968-73 1968-72 1968-73 1967-85
50072000	Río Fajardo at Fajardo	21.60	1960-63
50073200	Río Daguao at Daguao	2.26	1966-82
50073400	Quebrada Palma at Daguao	4.84	1972-77
50074000	Río Santiago at Naguabo	4.99	1966-82
50075500	Río Blanco at Florida	11.00	1966-82
50076000	Río Blanco near Florida	12.30	1983-85
50077000	Río Blanco at Río Blanco	17.60	1973-77
50077400	Río Blanco at Colonia La Fe	18.80	1967-70
50078500	Río Anton Ruíz at Central Pasto Viejo	4.33	1968
50081500	Río Humacao near Humacao	9.23	1973
50082000 50082200	Río Humacao at Hwy 3 at Humacao Río Humacao near La Suiza	17.30 19.90	1983-85 1965-66, 1969-71
50082800	Río Guayanés near Colonia Laura	4.69	1969-82
50083500	Río Guayanés near Yabucoa	17.20	1969-71
50084000	Río Limones near Yabucoa	7.89	1969-71
50085100	Río Guayanés at Central Roig	26.60	1965-66, 1968,70
50086100	Río del Ingenio at Comunas	5.50	1965-66, 1968-69
50086500	Río Guayanés at Playa Guayanés	34.00	1965-66, 1968-71
50087200 50091000	Caño Santiago near Central Roig Río Maunabo at Maunabo	6.04 12.40	1965-71 1965,67, 1969-82

WATER RESOURCES DATA FOR PUERTO RICO AND THE U.S. VIRGIN ISLANDS, 1992

DISCONTINUED STREAMFLOW STATIONS--Continued

Station number	Station name	Drainage area (mi²)	Period of record
50091200	Río Maunabo near Maunabo	12.70	1971-72
50091200	Río Jacaboa near Lamboglia	4.13	1965-73
50091700	Río Chico at Patillas	6.82	1965,
30091700	RIO CHICO at Facilias	0.02	1969-72
50091800	Río Chico at Providencia	4.90	1965,
30091800	RIO CHICO at PIOVIGENCIA	4.50	1967-69,
			1971
50094200	Río Grande de Patillas at Patillas	27.90	1967,
30094200	KIO GIANGE GE FACILIAS AC FACILIAS	27.50	1969,
			1971
			13/1
50094300	Río Grande de Patillas at Providencia	29.00	1971
50094400	Río Nigua at Pitahaya	5.86	1965, 1969,
30034400	Nio Nigua ao Ficanaja	3.00	1970-71,
			1973
50095200	Río Guamaní at Guayama	8.22	1969-71
50095500	Río Guamaní near Guayama	12.30	1969-70
50099000	Quebrada Aguas Verdes near Salinas	0.39	1989
30033000	Queblada Aydas Verdes hear Salimas	0.33	2707
50106500	Río Coamo near Coamo	46.00	1967-68
30101300	The country from the country		1984-85,
			1986
50106900	Río Coamo below Lago Coamo near Coamo	65.40	1967-68
50107200	Río Coamo at mouth near Santa Isabel	69.30	1967-68
50108200	Río Descalabrado at Las Ollas	13.90	1965,
30100200	NIO DESCUIADIAGO AC BAS OTTAS	13.30	1967-71
50108500	Río Descalabrado near Santa Isabel	18.10	1966-67
30100300	1130 Bobcarasiado Hoar Banda IBabor		
50111200	Río Toa Vaca near Villalba	21.40	1966-70
50111700	Río Jacaguas near Juana Díaz	53.20	1966-68
50111750	Río Jacaguas below Quebrada Guanábana	56.30	1989
50112100	Río Jacaguas near Arús	59.60	1966-67
50112600	Río Inabón at Coto Laurel		1967-71
50113100	Río Guayo near Coto Laurel	11.80	1965,
	•		1968-71
50113500	Río Inabón near Arús	30.20	1964-65
50114400	Río Bucaná near Ponce	25.60	1965-81
50114700	Río Bucaná near Playa de Ponce	28.40	1964-67
50115900	Río Portugués at Hwy 14 at Ponce		1965-82
50116500	Río Portugués at Highway 2 Bypass at Ponce	20.50	1964-65
50119000	Río Matilde at Ponce	19.40	1965-66
50121000	Río Tallaboa at Peñuelas	24.20	1959-82
50122000	Río Tallaboa at Tallaboa	31.50	1959-63
50124000	Río Guayanilla nr Guayanilla	18.50	1961-69
50101500	-/ - 111 111	0.0.00	1071 00
50124500	Río Guayanilla at Guayanilla	20.80	1971-82
50125900	Río Duey above Diversion near Yauco	8.93	1977-80
50126150	Río Yauco above Diversion Monserrate near Yauco	27.20	1978-85
50128000	Río Yauco near Yauco	45.50	1962-64, 1977-85
F040000	P/- 1 V	8 50	
50129000	Río Loco near Yauco	8.50	1963-67
50129500	Río Loco near Guánica	21.00	1963-69
50129900		21.00	1984-86
50129900	Laguna Cartagena near Boquerón Quebrada Mamey at Joyuda	0.38	1986-88
50136320	Río Rosario at Rosario	16.40	1975-86
50136000	Río Yahuecas near Adjuntas	15.40	1980-85
20141000	KIO Ianuecas near Aujuncas	13.40	1900-03
50145000	Río Grande de Añasco at El Espino	108.00	1959-66,
30143000	120 Status de Midseo de El Espiño	100.00	1961-63
50147000	Río Culebrinas at San Sebastian	16.70	1960-82
50276000	Turpentine Run at Mariendal	2.97	1963-69,
-			1978-86

INTRODUCTION

The Water Resources Division of the U.S. Geological Survey, in cooperation with local and federal agencies obtains a large amount of data pertaining to the water resources of the Commonwealth of Puerto Rico and the Territory of the U.S. Virgin Islands each water year. These data, accumulated during many water years, constitute a valuable data base for developing an improved understanding of the water resources of the area. To make these data readily available to interested parties outside the Geological Survey, the data are published annually in this report series entitled "Water Resources Data for Puerto Rico and the U.S. Virgin Islands, 1992."

This report includes records on both surface and ground water. Specifically, it contains: (1) Discharge records for 74 streamflow-gaging stations, stage only for 11 gaging stations, daily sediment records for 21 streamflow stations, 112 partial-record or miscellaneous streamflow stations, stage records for 9 reservoirs, and (2) water-quality records for 16 streamflow-gaging stations, and for 42 ungaged streamsites, 11 lake sites, 2 lagoons, and 1 bay; and (3) water-level records for 91 observation wells.

Water-resources data for Puerto Rico for calendar years 1958-67 were released in a series of reports entitled "Water Records of Puerto Rico". Water-resources data for the U.S. Virgin Islands for the calendar years 1962-69 were released in a report entitled "Water Records of U.S. Virgin Islands." Included were records of streamflow, ground-water levels, and water-quality data for both surface and ground water.

Beginning with the 1968 calendar year, surface-water records for Puerto Rico were released separately on an annual basis. Ground-water level records and water-quality data for surface and ground water were released in companion reports covering periods of several years. Data for the 1973-74 reports were published under separate covers. Water-resources data reports for 1975-76, 1977, 1978, 1979-80, 1981-82, 1983, 1984, 1985, 1986, 1987, 1988, 1989, 1990, and 1991 water years consist of one volume each and contain data for streamflow, water quality and ground water.

Publications similar to this report are published annually by the Geological Survey for all States. These official Survey reports have an identification number consisting of the two-letter State abbreviation, the last two digits of the water year, and the volume number. For example, this volume is identified as "U.S. Geological Survey Water-Data Report PR-92-1". These water-data reports are for sale in paper copy or in microfiche by the National Technical Information Service, U.S. Department of Commerce, Springfield, Virginia, 22161. Beginning with the 1990 water year, all water-data reports will also be available on Compact Disc-Read Only Memory (CD-ROM). All data reports published for the current water year for the entire Nation, including Puerto Rico and the Trust Territories, will be reproduced on a single CD-ROM disc.

Additional information, including current prices, for ordering specific reports may be obtained from the District Chief at the address given on back of the title page or by telephone (809) 749-4346. A limited number of CD-ROM discs will be available for sale by the Books and Open-File Reports Section, U.S. Geological Survey, Federal Center, Box 25425, Denver, Colorado 80225.

COOPERATION

The U.S. Geological Survey has had cooperative agreements with organizations of the Commonwealth of Puerto Rico and the Territory of the U.S. Virgin Islands for the systematic collections of water resources data since 1958. Organizations that supplied data are acknowledged in the station descriptions. Organizations that assisted in collecting data through cooperative agreements with the Survey are:

Puerto Rico Environmental Quality Board

Puerto Rico Aqueduct and Sewer Authority

Puerto Rico Department of Agriculture

Puerto Rico Industrial Development Company

Puerto Rico Department of Housing

Puerto Rico Highway Authority

Puerto Rico Department of Natural Resources

Puerto Rico Department of Health

Puerto Rico Electric and Power Authority

Puerto Rico Planning Board

Water Resources Research Institute, University of Puerto Rico

Water Resources Research Institute, College of the Virgin Islands

U.S. Virgin Islands Water and Power Authority

U.S. Virgin Islands Energy Office

U.S. Virgin Islands Department of Planning and Natural Resources

Funds were also provided by the Corps of Engineers, U.S. Army, for the collection of records at seven gaging stations published in this report.

SUMMARY OF HYDROLOGIC CONDITIONS

Precipitation

Precipitation throughout Puerto Rico during the 1992 water year (October 1991 to September 1992) averaged about 94 percent of normal. However, precipitation was 84 percent of normal in northern Puerto Rico, 102 percent of normal in southern Puerto Rico, 104 percent of normal in eastern Puerto Rico, and 91 percent of normal in western Puerto Rico. Unusually dry conditions prevailed during most of the 1992 water year except for the months of January and May. May was the wettest month of the 1992 water year. Monthly average precipitation islandwide for the 1992 water year and for the 30-year reference period 1951-1980 used to define normal rainfall, as reported by the National Oceanic and Atmospheric Administration, are listed in table 1.

Table 1. Islandwide monthly precipitation and annual averages for the 1992 water year and the 30-year reference period, 1951-80


Month	1992 Water Year (inches)	30-year normal (inches)
OCT	4.23	7.74
NOV	5.60	5.95
DEC	2.35	4.32
JAN	7.58	3.08
FEB	1.61	2.35
MAR	2.78	2.62
APR	4.38	4.63
MAY	11.30	6.48
JUN	4.37	5.58
JUL	3.97	5.48
AUG	6.08	7.28
SEP	5.43	7.78
TOTAL	59.68	63.29

Surface Water

Streamflow in Puerto Rico was slightly above normal during water year 1992, based on the index stations with monthly-mean discharges about 10 percent greater than the long-term median. The 1992 monthly-mean flow, the long-term monthly median flow, and extreme monthly flows are shown for four index stations in figure 1.

High and low long-term monthly median flows were recorded during water year 1992 (fig. 1). New high long-term monthly flows were recorded at Río Grande de Manatí at Hwy 2 (50038100) during January 1992, and at Río Inabón at Real Abajo (50112500) during January, February, and April 1992. New low long-term monthly flows were recorded at Río Grande de Añasco near San Sebastián (50114000) during November and December 1991, and February 1992; at Río Grande de Manatí at Hwy 2 (50038100) during December 1991 and at Río Fajardo near Fajardo (50071000) during July 1992.

October 1991 was unusually dry with monthly-mean flows less than 60 percent of the long-term October median. Streamflows below the long-term monthly-median flow continued into November and December. January was exceptionally wet with above normal monthly-mean flows and historical maximum-peak flows for many stations in the streamflow network. Heavy precipitation on January 5-6, 1992 caused islandwide flash floods resulting in 23 deaths and total damage estimated in 155 million dollars. Peak discharges for 18 stations in the areas most affected by this flood are listed in table 2.



Unshaded area indicates range between highest and lowest monthly mean discharges for the period of record.

Figure 1.--Monthly mean discharge of selected streams in Puerto Rico.

Two of the most important stations in the network, Río Grande de Loíza below Damsite (50059050) and Río Grande de Patillas near Patillas (50092000), which peak flows are listed in table 2, were not published in this volume because records were questionable and were withheld until additional data have been collected.

During February and March, streamflow declined below the long-term median at the index stations except the Río Inabón at Real Abajo, in the southern part of the island. Streamflows during April, May, and June increased due to excessive rainfall activity. During the last week of May, peak discharges at many stations were as high as those of January 5-6. Streamflow conditions from July to September were variable, but stayed below the islandwide long-term median.

In Vieques, Culebra, and the U.S. Virgin Islands (St. Thomas, St. Croix, and St. John), precipitation and streamflow patterns were similar to those in Puerto Rico. Rainfall in the U.S. Virgin Islands during 1992 water year was 77 percent of normal.

Table 2. Peak discharges during January 5-6, 1992 and maximums previously recorded at selected streamflow gaging stations in Puerto Rico

Station number	Station name	Drainage area (mi²)	Period of record	previous	discharge ly recorded Discharge (ft³/s)		imum for ry 5-6, 1999 Discharge (ft³/s)
50043000	Río de La Plata at Proyecto La Plata	54.8	1960-92	08-27-61	59,600	5	73,600
50043800	Río de La Plata at Comerío	109	1988-92	09-18-89	32,000	5	127,000
50044830	Río Guadiana at Guadiana	9.19	1990-92	02-05-91	4,600	5	6,670
50045010	Río de La Plata below La Plata Dam	173	1989-92	09-18-89	48,800	5	127,000
50046000	Río de La Plata at Hwy 2 near Toa Alta	200	1960-92	09-06-60	95,500	5	118,000
50050900	Río Grande de Loíza at Quebrada Arenas	6.00	1978-92	11-05-83	11,700	5	18,200
50051150	Quebrada Blanca at El Jagual	3.25	1985-92	05-17-85	7,400	5	7,870
50051800	Río Grande de Loíza at Hwy 183 near San Lorenzo	25.0	1990-92	10-20-90	7,510	5	40,700
50055000	Río Grande de Loiza at Caguas	89.8	1960-92	09-06-60	71,500	5	42,800
50055225	Río Cagüitas at Villa Blanca at Caguas	16.9	1991-92	07-16-91	2,060	5	13,300
50055390	Río Bairoa at Bairoa	5.08	1991-92	07-16-91	742	5	1,580
50059050	Río Grande de Loíza below Damsite	209	1987-92	11-27-87	124,300	5	79,500
50067000	Río Sabana at Sabana	3.96	1980-92	04-21-83	9,010	5	9,600
50071000	Río Fajardo near Fajardo	14.9	1962-92	09-18-89	23,500	5	23,300
50092000	Río Grande de Patillas near Patillas	18.3	1966-92	09-16-75	14,800	5	30,900
50100200	Río Lapa near Rabo del Buey	9.92	1989-92	10-20-90	1,750	5	15,700
50100450	Río Majada at La Plena	16.7	1989-92	10-25-90	3,820	5	15,200
50110900	Río Toa Vaca above Lago Toa Vaca	7.64	1989-92	08-24-89	3,740	5	8,710

Ground-Water Levels

Ground-water levels in the major aquifers of Puerto Rico during water year 1992 followed a seasonal trend associated with rainfall. Two significant rainfall events, one in January and the other in May, caused ground-water levels to rise; recharging the major coastal aquifers. Record-high water levels were recorded at several wells in Puerto Rico and the U.S. Virgin Islands (table 3).

In the north coast limestone aquifer, ground-water levels at the Sabana Hoyos index well rose from October 1991 to January 1992 (fig. 2). Thereafter, water levels declined until mid-May, when above normal rainfall reversed the trend. A declining trend was observed during the rest of the water year.

In the south coast alluvial aquifers, the Yauco and Alomar index wells recorded generally declining ground-water levels from October 1991 to January 1992 (fig. 2). In mid-May, ground-water levels rose about 8 and 2 ft at Yauco and Alomar index wells, respectively, due to intense rainfall in the area. From May until the end of the water year 1992 water-levels changed very little at the Yauco index well and declined at the Alomar index well due to ground-water withdrawals for public irrigation and industrial use.

Ground-water levels in the U.S. Virgin Islands in the observation well 11 at Guinea Gut, St. John followed a seasonal trend associated with rainfall (fig. 2). Water-levels were affected by rainfall events during November and December 1991 and on January and May 1992. From January to early-May 1992 the water-level in Guinea Gut well dropped 12.0 ft in response to below normal rainfall in the area.

Table 3. Highest ground-water levels recorded during 1992 water year and previous high ground-water levels at selected wells in Puerto Rico and the U.S. Virgin Islands
[PR, Puerto Rico; St.C, St. Croix; St.T, St. Thomas; St.J, St. John; mm-dd-yy, month-day-year, ft-blsd, feet below land surface datum, mm-yy, month-year]

Well name	Local number	Location	1992 high water (ft-blsd)	Date (mm-dd-yy)	Previous high water (ft-blsd)	Date (mm-dd-yy)	Period recor (mm-yy	d
Saltos 1	165	PR	38.75	09-23-92	38.81	10-05-90	1-82 to	9-92
				09-26-92		10-07-90		
						10-08-90		
La Esperanza	PN-2	PR	8.07	06-08-92	8.12	10-22-90	7-89 to	9-92
2				06-09-92				
				06-10-92				
Jardín Botáni 3	co PN-19	PR	4.04	06-09-92	6.37	09-30-91	6-91 to	9-92
HW-TW-05B	HW-TW-05B	PR	7.89	05-26-92	9.40	08-25-88	4-88 to	9-92
RM 5	RM 5	PR	7.48	05-26-92	8.15	10-26-90	3-89 to	9-92
WAPA-23a	15	St.C	55.29	10-01-91	56.84	02-13-91	2-90 to	9-92
VIEO-1	7	St.T	68.23	02-11-92	71.88	06-16-91	5-91 to	9-92
VIEO-2	12	St.J	21.47	06-05-92	23.48	05-23-91	5-91 to	9-92
				06-06-92		05-24-91		
				06-07-92		05-25-91		
				06-08-92		05-26-91		
VIEO-3	13	St.J	52.04	12-03-91	52.21	09-30-91	5-91 to	9-92
				12-04-91				
				12-05-91				
VIEO-4	14	St.J	9.95	06-05-92	10.50	09-29-91	5-91 to	9-92




Figure 2.—Ground—water levels at selected wells in Puerto Rico and the U.S. Virgin Islands.

Water Quality

In water year 1992, the U.S. Geological Survey, in cooperation with local government agencies, completed the eighth year of sampling for the constituents listed in table 4. These constituents were added to the water quality monitoring program in 1985 and are in addition to the major chemical constituents and physical properties monitored in the continuing water quality monitoring program in Puerto Rico. The highest concentration of selected constituents detected during water year 1992, along with the stations at which these concentrations were detected, are summarized in table 4.

Table 4. Surface-water quality stations in Puerto Rico with highest concentration of selected constituents during water year 1992 [All constituent concentrations are in milligrams per liter; MBAS, Methylene blue active substance]

tation number	Station name	Constituent	Concentration	
50106500	Río Portugués near Ponce	Sulfide	0.8	
50129700	Río Loco at Guánica	Boron	0.7	
50124700	Río Guayanilla at Central Rufina	Manganese	1.2	
50055400	Río Grande de Arecibo near Utuado	Iron	14	
50043000	Río de La Plata at Proyecto La Plata	Iron	14	
50149100	Río Culebrinas near Aguada	Zinc	0.12	
50149100	Río Culebrinas near Aguada	Cyanide	0.06	
50055250	Río Cagüitas at Hwy 30 at Caguas	Phenols	0.011	
50055250	Río Caguitas at Hwy 30 at Caguas	MBAS	1.7	

The presence of high concentrations of fecal coliform (FC) and fecal streptococci (FS) bacteria continued to be the principal surface-water quality problem in Puerto Rico during water year 1992. Bacteria concentration exceeding one million colonies per hundred milliliters of raw water were not observed at any sampling station during this water year as observed in previous years.

The highest concentrations observed during this year were in the San Juan metropolitan area monitoring stations (figs. 3 and 4), which has the highest population density in Puerto Rico. In addition to the effluent from the San Juan metropolitan area, the streams also receive effluent from the upper basin sewage treatment plants servicing urban and suburban zones.

The main sources of contamination in surface-water systems in Puerto Rico are discharges of liquid wastes from industrial and municipal sources. The highest concentration of fecal coliforms and fecal streptococcus bacteria in surface-waters occurred in heavily populated and industrialized areas of the island.

Elevated concentration of suspended sediment are a common problem in many streams in Puerto Rico, especially in the coastal areas. Suspended sediment concentrations are of concern because the deposition of these sediments is rapidly reducing the storage capacities of reservoirs used for water supply. Suspended sediment concentration were monitored at twenty one sites in Puerto Rico during the 1992 water year as part of the cooperative program between the U.S. Geological Survey and various other Commonwealth and Federal agencies.

SPECIAL NETWORKS AND PROGRAMS

National Stream Quality Accounting Network (NASQAN) is a nationwide data-collection network designed by the U.S. Geological Survey to meet many of the information needs of government agencies and other groups involved in natural or regional water-quality planning and management. The 500 or so sites on NASQAN are generally located at the downstream ends of hydrologic accounting units designated by the U.S. Geological Survey Office of Water Data Coordination in consultation with the Water Resources Council. The objectives of NASQAN are (1) to obtain information on the quality and quantity of water moving within and from the United States through a systematic and uniform process of data collection, summarization, analysis, and reporting such that the data may be used for, (2) description of the areal variability of water quality in the Nation's rivers through analysis of data from this and other programs, (3) detection of changes or trends with time in the pattern of occurrence of water-quality characteristics, and (4) providing a nationally consistent data base useful for water-quality assessment and hydrologic research.

EXPLANATION OF RECORDS

The surface-water and ground-water records published in this report are for the 1992 water year that began October 1, 1991 and ended September 30, 1992. A calendar of the water year is provided on the inside of the front cover. The records contain streamflow data, water-quality data for surface and ground water, and ground-water-level data. The locations of the stations and wells where the data were collected are shown in figures 3 to 10. The following sections of the introductory text are presented to provide users with a more detailed explanation of how the hydrologic data published in this report were collected, analyzed, computed, and arranged for presentation.

Station Identification Numbers

Each data station, whether streamsite or well, in this report is assigned a unique identification number. This number is unique in that it applies specifically to a given station and to no other. The number usually is assigned when a station is first established and is retained for that station indefinitely. The systems used by the U.S. Geological Survey to assign identification numbers for surface-water stations and for ground-water well sites differ, but both are based on geographic location. The "downstream order" system is used for regular surface-water stations and the "latitude-longitude" system is used for wells.

Downstream Order System

Since October 1, 1950, the order of listing hydrologic-station records in Survey reports is in a downstream direction along the main stream. All stations on a tributary entering upstream from a main-stream station are listed before that station. A station on a tributary that enters between two main-stream stations is listed between them. A similar order is followed in listing stations in first rank, second rank, and other ranks of tributaries.

As an added means of identification, each hydrologic station and partial-record station has been assigned a station number. These are in the same downstream order used in this report. In assigning station numbers, no distinction is made between partial-record stations and other stations; therefore, the station number for a partial-record station indicates downstream order position in a list made up of both types of stations that may be established; hence, the numbers are not consecutive. The complete 8-digit number for each station such as 50028000, which appears just to the left of the station name, includes the 2-digit part number "50" plus the 6-digit downstream order number "028000."

Latitude-Longitude System

The 8-digit downstream order station numbers are not assigned to wells and miscellaneous sites where only random water-quality samples or discharge measurements are taken.

The well and miscellaneous site numbering system of the U.S. Geological Survey is based on the grid system of latitude and longitude. The system provides the geographic location of the well or miscellaneous site and a unique number for each site. The number consists of 15 digits. The first 6 digits denote the degrees, minutes, and seconds of latitude, the next 7 digits denote degrees, minutes, and seconds of longitude, and the last 2 digits (assigned sequentially) identify the wells or other sites within a 1-second grid. The numbers shown in the grid correspond to the local numbers assigned to each well as visited in the field. An example is well 16 (fig.12).




Figure 3.--Location of fecal coliform bacteria concentration at sampled sites.




Figure 4.--Location of fecal streptococci bacteria concentration at sampled sites.




Figure 5:-Location of surface-water stations in Puerto Rico.




Figure 6.-Location of water-quality stations in Puerto Rico.




Figure 7.--Location of low-flow partial-record stations in southwest Puerto Rico.




Figure 8:-Location of ground-water stations in Puerto Rico.




Figure 9--Location of surface-water stations in the U.S. Virgin Islands.




Figure 10:-Location of ground-water stations in the U.S. Virgin Islands.




Figure 11.--Location of surface-water stations in Vieques and Culebra Islands.




Figure 12.--Grid showing system for numbering wells and miscellaneous sites (latitude and longitude).

Records of Stage and Water Discharge

Records of stage and water discharge may be complete or partial. Complete records of discharge are those obtained using a continuous stage-recording device through which either instantaneous or mean daily discharges may be computed for any time, or any period of time, during the period of record. Complete records of lake or reservoir content, similarly, are those for which stage or content may be computed or estimated with reasonable accuracy for any time, or period of time. They may be obtained using a continuous stage-recording device, but need not be. Because daily mean discharges and end-of-day contents commonly are published for such stations, they are referred to as "daily stations."

By contrast, partial records are obtained through discrete measurements without using a continuous stage-recording device and pertain only to a few flow characteristics, or perhaps only one. The nature of the partial record is indicated by table title such as "Low-flow partial records." Records of miscellaneous discharge measurements or of measurements from special studies, such as low-flow seepage studies, may be considered as partial records, but they are presented separately in this type of report. Location of all complete-record stations for which data are given in this report are shown in figures 5 and 8.

Data Collection and Computation

The data obtained at a complete-record gaging station on a stream or canal consists of a continuous record of stage, individual measurements of discharge throughout a range of stages, and notations regarding factors that may affect the relationships between stage and discharge. These data, together with supplemental information, such as weather records, are used to compute daily discharges. The data obtained at a complete-record gaging station on a lake or reservoir consist of a record of stage and of notations regarding factors that may affect the relationship between stage and lake content. These data are used with stage-area and stage-capacity curves or tables to compute water-surface areas and lake storage.

Continuous records of stage are obtained with analog recorders that trace continuous graphs of stage or with digital recorders that punch stage values on paper tapes at selected time intervals or electronic satellite data collector platforms that receive stage values at selected time intervals. Measurements of discharge are made with current meters using methods adapted by the Geological Survey as a result of experience accumulated since 1880. These methods are described in standard textbooks, in Water-Supply Paper 2175, and in U.S. Geological Survey Techniques of Water-Resources Investigations, Book 3, Chapter A6.

In computing discharge records, results of individual measurements are plotted against the corresponding stages, and stage-discharge relation curves are then constructed. From these curves, rating tables indicating the approximate discharge for any stage within the range of the measurements are prepared. If it is necessary to define extremes of discharge outside the range of the current-meter measurements, the curves are extended using: (1) logarithmic plotting; (2) velocity-area studies; (3) results of indirect measurements of peak discharge, such as slope-area or contracted-opening measurements, and computations of flow-over-dams or weirs; or (4) step-backwater techniques.

Daily mean discharges are computed by applying the daily mean stages (gage heights) to the stage-discharge curves or tables. If the stage-discharge relation is subject to change because of frequent or continual change in the physical features that form the control, the daily mean discharge is determined by the shifting-control method, in which correction factors based on the individual discharge measurements and notes of the personnel making the measurements are applied to the gage heights before the discharges are determined from the curves or tables. This shifting-control method also is used if the stage-discharge relation is changed temporarily because of aquatic growth or debris on the control. At some stations the stage-discharge relation is affected by changing stage; at these stations the rate of change in stage is used as a factor in computing discharge.

In computing records of lake or reservoir contents, it is necessary to have available from surveys, curves or tables defining the relationship of stage and contents. The application of stage to the stage-content curves or tables gives the contents from which daily, monthly or yearly changes then are determined. If the stage-content relationship changes because of deposition of sediment in a lake or reservoir, periodic surveys may be necessary to redefine it. Even when this is done, as time between the last survey increases, the contents computed may increase in error. Discharges over lake or reservoir spillways are computed from stage-discharge relationships much as other stream discharges are computed.

For some gaging stations there are periods when no gage-height record is obtained, or the recorded gage height is so faulty that it cannot be used to compute daily discharge or contents. This happens when the recorder stops or otherwise fails to operate properly, intakes are plugged, the float is loose in the well, or for various other reasons. For such periods, the daily discharges are estimated from the recorded range in stage, previous or following record, discharge measurements, weather records, and comparison with other station records from the same or nearby basins. Likewise, daily contents may be estimated from operator's logs, previous or following record, inflow-outflow studies, and other information. Information explaining how estimated daily-discharge values are identified in station records is included in the next two sections, "Data Presentation" (REMARKS paragraph) and "Identifying Estimated Daily Discharge."

Data Presentation

Steamflow data in this report are presented in a new format that is considerably different from the format in data reports prior to the 1992 water year. The major changes are that statistical characteristics of discharge now appear in tabular summaries following the water-year data table and less information is provided in the text or station manuscript above the table. These changes represent the results of a pilot program to reformat the annual water-data report to meet current user needs and data preferences.

The records published for each continuous-record surface-water discharge station (gaging station) now consist of four parts, the manuscript or station description; the data table of daily mean values of discharge for the current water year with summary data; a tabular statistical summary of monthly mean flow data for a designated period, by water year; and a summary statistics table that includes statistical data of annual, daily, and instantaneous flows as well as data pertaining to annual runoff, 7-day low-flow minimum, and flow duration.

Station manuscript

The manuscript provides, under various headings, descriptive information, such as station location; period of record; historical extremes outside the period of record; record accuracy; and other remarks pertinent to station operation and regulation. The following information, as appropriate, is provided with each continuous record of discharge or lake content. Comments to follow clarify information presented under the various headings of the stations descriptions.

LOCATION.--Information on locations is obtained from the most accurate maps available. The location of the gage with respect to the cultural and physical features in the vicinity and with respect to the reference place mentioned in the station name is given.

DRAINAGE AREA.--Drainage areas are measured using the most accurate maps available. Drainage areas are updated as better maps become available.

PERIOD OF RECORD.--This indicates the period for which there are published records for the station or for an equivalent station. An equivalent station is one that was in operation at a time that the present station was not, and whose location was such that records from it can reasonable be considered equivalent with records from the present station.

REVISED RECORDS.--Because of new information, published records occasionally are found to be incorrect, and revisions are printed in later reports. Listed under this heading are all the reports in which revisions have been published for the station and the water years to which the revisions apply. If a revision did not include daily, monthly, or annual figures of discharge, that fact is noted after the year dates as follows: "(M)" means that only the instantaneous maximum discharge was revised; "(m)" that only the instantaneous minimum was revised; and "(P)" that only peak discharges were revised. If the drainage area has been revised, the report in which the most recently revised figure was first published is given.

GAGE.--The type of gage in current use, the datum of the current gage, and a condensed history of the types, locations, and datums of previous gages are given under this heading.

REMARKS.--All periods of estimated daily-discharge record will either be identified by date in this paragraph of the station description for water-discharge stations or flagged in the daily-discharge table. (See next section, "Identifying Estimated Daily Discharge.") If a remarks statement is used to identify estimated record, the paragraph will begin with this information presented as the first entry. The paragraph is also used to present information relative to the accuracy of the records, to special methods of computations, to conditions that affect natural flow at the station and, possibly, to other pertinent items. For reservoir stations, information is given on the dam forming the reservoir, the capacity, outlet works and spillway, and purpose and use of the reservoir.

COOPERATION.--Records provided by a cooperating organization or obtained for the Geological Survey by a cooperating organization are identified here.

EXTREMES OUTSIDE PERIOD OF RECORD.--Included here is information concerning major floods or unusually low flows that occurred outside the stated period of record. The information may or may not have been obtained by the U.S. Geological Survey.

REVISIONS.--If a critical error in published records is discovered, a revision is included in the first report published following discovery of the error.

Although rare, occasionally the records of a discontinued gaging station may need revision. Because, for these stations, there would be no current or, possibly, future station manuscript published to document the revision in a "Revised Records" entry, users of data for these stations who obtained the record from previously published data reports may wish to contact the District office to determine if the published records were ever revised after the station was discontinued. Of course, if the data were obtained by computer retrieval, the data would be current and there would be no need to check because any published revision of data is always accompanied by revision of the corresponding data in computer storage.

Manuscript information for lake or reservoir stations differs from that for stream stations in the nature of the "Remarks" and in the inclusion of a skeleton stage-capacity table when daily contents are given.

Data table of daily mean value

The daily table of discharge records for stream-gaging stations gives mean discharge for each day of the water year. In the monthly summary for the table, the line headed "TOTAL" gives the sum of the daily figures for each month; the line headed "MEAN" gives the average flow in cubic feet per second for the month; and the lines headed "MAX" and "MIN" give the maximum and minimum daily mean discharges, respectively, for each month. Discharge for the month also is usually expressed in cubic feet per second per square mile (line headed "CFSM"); or in inches (line headed "IN"); or in acre-feet (line headed "AC-FT"). Figures for cubic feet per second per square mile and runoff in inches or in acre-feet may be omitted if there is extensive regulations or diversion or if the drainage area includes large noncontributing areas.

Statistics of monthly mean data

A tabular summary of the mean (line headed "MEAN"), maximum (line headed "MAX"), and minimum (line headed "MIN") of monthly mean flows for each month for a designated period is provided below the mean values table. The water years of the first occurrence of the maximum and minimum monthly flow are provided immediately below those figures. The designated period will be expressed as "FOR WATER YEARS _____, BY WATER YEAR (WY)," and will list the first and last water years of the range of years selected from the PERIOD OF RECORD paragraph in the station manuscript. It will consist of all of the station records within the specified water years, including complete months of record for partial water years, if any, and may coincide with the period of record for the station. The water years for which the statistics are computed will be consecutive, unless a break in the station record is indicated in the manuscript.

Summary statistics

A table titled "SUMMARY STATISTICS" follows the statistics of monthly mean data tabulation. This table consists of four columns, with the first column containing the line headings of the statistics being reported. The table provides a statistical summary of yearly, daily, and instantaneous flows, not only for the current water year but also for the previous calendar year and for a designated period, as appropriate. The designated period selected, "WATER YEARS _______," will consist of all of the station records within the specified water years, inclusive, including complete months of record for partial water years, if any, and may coincide with the period of record for the station. The water years for which the statistics are computed will be consecutive, unless a break in the station record is indicated in the manuscript. All of the calculations for the statistical characteristics designated ANNUAL (see line headings below.), except for the "ANNUAL 7-DAY MINIMUM" statistic, are calculated for the designated period using complete water years. The other statistical characteristics may be calculated using partial water years.

The date or water year, as appropriate, of the first occurrence of each statistic reporting extreme values of discharge is provided adjacent to the statistic. Repeated occurrences may be noted in the REMARKS paragraph of the manuscript or in footnotes. Because the designated period may not be the same as the station period of record published in the manuscript, occasionally the dates of occurrence listed for the daily and instantaneous extremes in the designated-period column may not be within the selected water years listed in the heading. When this occurs, it will be noted in the REMARKS paragraph or in footnotes. Selected streamflow duration curve statistics and runoff data are also given. Runoff data may be omitted if there is extensive regulation or diversion of flow in the drainage basin.

The following summary statistics data, as appropriate, are provided with each continuous record of discharge. Comments to follow clarify information presented under the various line headings of the summary statistics table.

ANNUAL TOTAL.--The sum of the daily mean values of discharge for the year. At some stations the annual total discharge is adjusted for reservoir storage or diversion. The adjusted figures are identified by a symbol and corresponding footnotes.

ANNUAL MEAN.--The arithmetic mean of the individual daily mean discharges for the year noted or for the designated period. At some stations the yearly mean discharge is adjusted for reservoir storage or diversion. The adjusted figures are identified by a symbol and corresponding footnotes.

HIGHEST ANNUAL MEAN .-- The maximum annual mean discharge occurring for the designated period.

LOWEST ANNUAL MEAN .-- The minimum annual mean discharge occurring for the designated period.

HIGHEST DAILY MEAN.--The maximum daily mean discharge for the year or for the designated period.

LOWEST DAILY MEAN .-- The minimum daily mean discharge for the year or for the designated period.

ANNUAL 7-DAY MINIMUM.--The lowest mean discharge for 7 consecutive days for a calendar year or a water year. Note that most low-flow frequency analyses of annual 7-day minimum flows use a climatic year (April 1 - March 31). The date shown in the summary statistics table is the initial date of the 7-day period. (This value should not be confused with the 7-day 10-year low-flow statistics.)

- INSTANTANEOUS PEAK FLOW.--The maximum instantaneous discharge occurring for the water year or for the designated period. Note that secondary instantaneous peak discharges above a selected base discharge are stored in District computer files for stations meeting certain criteria. Those discharge values may be obtained by writing to the District Office. (See address on back of the title page of this report.)
- INSTANTANEOUS PEAK STAGE.--The maximum instantaneous stage occurring for the water year or for the designated period. If the dates of occurrence for the instantaneous peak flow and instantaneous peak stage differ, the REMARKS paragraph in the manuscript or a footnote may be used to provide further information.
- INSTANTANEOUS LOW FLOW.--The minimum instantaneous discharge occurring for the water year or for the designated period.
- ANNUAL RUNOFF.--Indicates the total quantity of water in runoff for a drainage area for the year. Data reports may use any of the following units of measurements in presenting annual runoff data:
 - Acre-foot (AC-FT) is the quantity of water required to cover 1 acre to a depth of 1 foot and is equivalent to 43,560 cubic feet or about 326,000 gallons or 1,233 cubic meters.
 - Cubic feet per second per square mile (CFSM) is the average number of cubic feet of water flowing per second from each square mile of area drained, assuming the runoff is distributed uniformly in time and area.
 - Inches (INCHES) indicates the depth to which the drainage area would be covered if all of the runoff for a given time period were uniformly distributed on it.
- 10 PERCENT EXCEEDS.--The discharge that is exceeded by 10 percent of the flow for the designated period.
- 50 PERCENT EXCEEDS.--The discharge that is exceeded by 50 percent of the flow for the designated period.
- 90 PERCENT EXCEEDS.--The discharge that is exceeded by 90 percent of the flow for the designated period.

Data collected at partial-record stations follow the information for continuous-record sites. Data for partial-record discharge stations are presented in a table of discharge measurements at low-flow partial-record stations. These measurements are generally made in times of drought to give better areal coverage to those events. Those measurements and others collected for some special reason are called measurements at miscellaneous sites.

Identifying Estimated Daily Discharge

Estimated daily-discharge values published in the water-discharge tables are identified by flagging individual daily values with the letter symbol "e" and printing a table footnote, "e Estimated."

Accuracy of the Records

The accuracy of streamflow records depends primarily on: (1) The stability of the stage-discharge relation or, if the control is unstable, the frequency of discharge measurements; and (2) the accuracy of measurements of stage, measurements of discharge, and interpretation of records.

The accuracy attributed to the records is indicated under "REMARKS." "Excellent" means that about 95 percent of the daily discharges are within 5 percent of the true; "good," within 10 percent; and "fair," within 15 percent. Records that do not meet the criteria mentioned, are rated "poor." Different accuracies may be attributed to different parts of a given record.

Daily mean discharges in this report are given to the nearest hundredth of a cubic foot per second for values less than 1 ft³/s; to the nearest tenth between 1.0 and 10 ft³/s; to whole numbers between 10 and 1,000 ft³/s; and to 3 significant figures for more than 1,000 ft³/s. The number of significant figures used is based solely on the magnitude of the discharge value. The same rounding rules apply to discharges listed for partial-record stations and miscellaneous sites.

Information used in the preparation of the records in this publication, such as discharge-measurement notes, gage-height records, temperature measurements, and rating tables are on file in the Caribbean District office. Also, most of the daily mean discharges are in computer-readable form and have been analyzed statistically. Information on the availability of the unpublished information or on the results of statistical analyses of the published records may be obtained from the District office.

Records of Surface-Water Quality

Records of surface-water quality ordinarily are obtained at or near stream-gaging stations because interpretation of records of surface-water quality nearly always requires corresponding discharge data. Records of surface-water quality in this report may involve a variety of types of data and measurement frequencies.

Classification of Records

Water-quality data for surface-water sites are grouped into one of three classifications. A continuing-record station is a site where data are collected on a regularly scheduled basis. Frequency may be once or more times daily, weekly, monthly, or quarterly. A partial-record station is a site where limited water-quality data are collected systematically over a period of years. Frequency of sampling is usually less than quarterly. A miscellaneous sampling site is a location other than a continuing or partial-record station, where random samples are collected to give better areal coverage to define water-quality conditions in the river basin.

A careful distinction needs to be made between "continuing records" as used in this report and "continuous recordings," which refers to a continuous graph or a series of discrete values punched at short intervals on a paper tape. Some records of water quality, such as temperature and specific conductance, may be obtained through continuous recordings; however, because of costs, most data are obtained only monthly or less frequently. Locations of stations for which records on the quality of surface water appear in this report are shown in figure 6.

Arrangement of Records

Water-quality records collected at a surface-water daily record station are published immediately following that record, regardless of the frequency of sample collection. Station number and name are the same for both records. Where a surface-water daily record station is not available or where the water quality differs significantly from that at the nearby surface-water station, the continuing water-quality record is published with its own station number and name in the regular downstream-order sequence. Water-quality data for partial-record stations and for miscellaneous sampling sites appear in separate tables following the table of discharge measurement at miscellaneous sites.

On-site Measurements and Sample Collection

In obtaining water-quality data, a major concern needs to be assuring that the data obtained represent the in situ quality of the water. To assure this, certain measurements, such as water temperature, pH, and dissolved oxygen, need to be made onsite when the samples are taken. To assure that measurements made in the laboratory also represent the in situ water, carefully prescribed procedures need to be followed in collecting the samples, in treating the samples to prevent changes in quality pending analysis, and in shipping the samples to the laboratory. Procedures for onsite measurements and for collecting, treating, and shipping samples are given in publications on "Techniques of Water-Resources Investigations," Book 1, Chap. D2; Book 3, Chap. C2; Book 5, Chap. A1, A3, and A4. Detailed information on collecting, treating, and shipping samples may be obtained from the Geological Survey District office.

One sample can define adequately the water quality at a given time if the mixture of solutes throughout the stream cross section is homogeneous. However, the concentration of solutes at different locations in the cross section may vary widely with different rates of water discharge, depending on the source of material and the turbulence and mixing of the stream. Some streams must be sampled through several vertical sections to obtain a representative sample needed for an accurate mean concentration and for use in calculating load. All samples obtained for the National Stream Quality Accounting Network (see definitions) are obtained from at least several verticals. Whether samples are obtained from the centroid of flow or from several verticals, depends on flow conditions and other factors which must be evaluated by the collector.

Chemical-quality data published in this report are considered to be the most representative values available for the stations listed. The values reported represent water-quality conditions at the time of sampling as much as possible, consistent with available sampling techniques and methods of analysis. In the rare case where an apparent inconsistency exists between a reported pH value and the relative abundance of carbon dioxide species (carbonate and bicarbonate), the inconsistency is the result of a slight uptake of carbon dioxide from the air by the sample between measurement of pH in the field and determination of carbonate and bicarbonate in the laboratory.

For chemical-quality stations equipped with digital monitors, the records consist of daily maximum, minimum, and mean values for each constituent measured and are based upon hourly punches beginning at 0100 hours and ending at 2400 hours for the day of record. More detailed records, when available, (hourly values) may be obtained from the U.S.G.S. District office whose address is given on the back of the title page of this report.

Water Temperature

Water temperatures are measured at most of the water-quality stations. In addition, water temperatures are taken at time of discharge measurements for water-discharge stations. For stations where water temperatures are taken manually once or twice daily, the water temperatures are taken at about the same time each day. Large streams have a small diurnal temperature change; shallow streams may have a daily range of several degrees and may follow closely the changes in air temperature. Some streams may be affected by waste-heat discharges.

At stations where recording instruments are used, either mean temperatures or maximum and minimum temperatures for each day are published. Water temperatures measured at the time of water-discharge measurements are on file in the District office.

Sediment

Suspended-sediment concentrations are determined from samples collected by using depth-integrating and pumping sediment samplers. Samples usually are obtained at several verticals in the cross section, or a single sample may be obtained at a fixed point and a coefficient applied to determine the mean concentration in the cross sections.

During periods of rapidly changing flow or rapidly changing concentration, samples may have been collected more frequently (twice daily or hourly). The published sediment discharges for days of rapidly changing flow or concentration were computed by the subdivided-day method (time-discharge weighted average). Therefore, for those days when the published sediment discharge value differs from the value computed as the product of discharge times mean concentration times 0.0027, the reader can assume that the sediment discharge for that day was computed by the subdivided-day method. For periods when no samples were collected, daily discharges of suspended sediment were estimated on the basis of water discharge, sediment concentrations observed immediately before and after the periods, and suspended-sediment loads for other periods of similar discharge.

At other stations, suspended-sediment samples were collected periodically at many verticals in the stream cross section. Although data collected periodically may represent conditions only at the time of observations, such data are useful in establishing seasonal relations between quality and streamflow and in predicting long-term sediment-discharge characteristics of the stream.

In addition to the records of suspended-sediment discharge, records of the periodic measurements of the particlesize distribution of the suspended sediment and bed material are included for some stations.

Laboratory Measurements

Sediment samples, samples for biochemical-oxygen demand (BOD), samples for indicator bacteria, and daily samples for specific conductance are analyzed locally. All other samples are analyzed in the Geological Survey laboratories in Denver, Co. or Ocala, Fla. Methods used in analyzing sediment samples and computing sediment records are given in TWRI, Book 5, Chap. C1. Methods used by the Geological Survey laboratories are given in TWRI, Book 1, Chap. D2; Book 3, Chap. C2; Book 5, Chap. A1, A3, and A4.

Data Presentation

For continuing-record stations, information pertinent to the history of station operation is provided in descriptive headings preceding the tabular data. These descriptive headings give details regarding location, drainage area, period of record, type of data available, instrumentation, general remarks, cooperation, and extremes for parameters currently measured daily. Tables of chemical, physical, biological, radiochemical data, and so forth, obtained at a frequency less than daily are presented first, and tables of "daily values" of specific conductance, pH, water temperature, dissolved oxygen, and suspended sediment then follow in sequence, when these parameters are studied.

In the descriptive headings, if the location is identical to that of the discharge gaging station, neither the LOCATION nor the DRAINAGE AREA statements are repeated. The following information, as appropriate, is provided with each continuous-record station. Comments that follow clarify information presented under the various headings of the station description.

LOCATION .-- See Data Presentation under "Records of Stage and Water Discharge;" same comments apply.

DRAINAGE AREA.--See Data Presentation under "Records of Stage and Water Discharge;" same comments apply.

PERIOD OF RECORD.--This indicates the periods for which there are published water-quality records for the station. The periods are shown separately for records of parameters measured daily or continuously and those measured less than daily. For those measured daily or continuously, periods of record are given for the parameters individually.

INSTRUMENTATION.--Information on instrumentation is given only if a water-quality monitor temperature record, sediment pumping sampler, or other sampling device is in operation at a station.

REMARKS.--Remarks provide added information pertinent to the collection, analysis, or computation of the records.

COOPERATION.--Records provided by a cooperating organization or obtained for the Geological Survey by a cooperating organization are identified here.

EXTREMES.—Maximums and minimums are given only for parameters measured daily or more frequently. None are given for parameters measured weekly or less frequently, because the true maximums or minimums may not have been sampled. Extremes, when given, are provided for both the period of record and for the current water year.

REVISIONS.--If errors in published water-quality records are discovered after publication, appropriate updates are made to the Water-Quality File in the U.S. Geological Survey's computerized data system, WATSTORE, and subsequently by monthly transfer of update transactions to the U.S. Environmental Protection Agency's STORET system. Because the usual volume of updates makes it impractical to document individual changes in the State data-report series or elsewhere, potential users of U.S. Geological Survey water-quality data are encouraged to obtain all required data from the appropriate computer file to insure the most recent updates.

The surface-water-quality records for partial-record stations and miscellaneous sampling sites are published in separate tables following the table of discharge measurements at miscellaneous sites. No descriptive statements are given for these records. Each station is published with its own station number and name in the regular downstream-order sequence.

Remark Codes

The following remark codes may appear with the water-quality data in this report:

PRINTED OUTPUT	REMARK
E	Estimated value
>	Actual value is known to be greater than the value shown
<	Actual value is known to be less than the value shown
K	Results based on colony count outside the acceptance range (non-ideal colony count)
L	Biological organism count less than 0.5 percent (organism may be observed rather than counted)
D	Biological organism count equal to or greater than 15 percent (dominant)
&	Biological organism estimated as dominant

Records of Ground-Water Levels

Only ground-water level data from a basic network of observation wells are published herein. This basic network contains observation wells so located that the most significant data are obtained from the fewest wells in the most important aquifers.

Data Collection and Computation

Measurements of water levels are made in many types of wells under varying conditions, but the methods of measurement are standardized to the extent possible. The equipment and measuring techniques used at each observation well ensure that measurements at each well are of consistent accuracy and reliability.

Each well is identified by means of (1) a 15-digit number that is based on latitude and longitude and (2) a local number that is provided for local needs. See figure 10.

Water-level records are obtained from direct measurements with a steel tape or from the graph or punched tape of a water-stage recorder. The water-level measurements in this report are given in feet with reference to land-surface datum (lsd). Land-surface datum is a datum plane that is approximately at land surface at each well. If known, the elevation of the land-surface datum is given in the well description. The height of the measuring point (MP) above or below land-surface datum is given in each well description. Water levels in wells equipped with recording gages are reported for every day and as an instantaneous observation at noon.

Water levels are reported to as many significant figures as can be justified by the local conditions. For example, in a measurement of a depth to water of several hundred feet, the error of determining the absolute value of the total depth to water may be a few tenths of a foot, whereas the error in determining the net change of water level between successive measurements may be only a hundredth of a few hundredths of a foot. For lesser depths to water, the accuracy is greater. Accordingly, most measurements reported to a hundredth of a foot, but some are given to a tenth of a foot or a larger unit.

Data Presentation

Each well record consists of three parts, the station description, the data table of water levels observed during the water year and a graph of the water levels for the current water year and other selected period. The description of the well is presented first through use of descriptive headings preceding the tabular data. The comments to follow clarify information presented under the various headings of the well description.

LOCATION.--This paragraph follows the well-identification number and reports the latitude and longitude (given in degrees, minutes, and seconds); a landline location designation; the hydrologic-unit number; the distance and direction from a geographic point of reference; and the owner's name.

AQUIFER.--This entry designates by name (if a name exists) and geologic age the aquifer(s) open to the well.

WELL CHARACTERISTICS.--This entry describes the well in terms of depth, diameter, casing depth and/or screened interval, method of construction, use, and additional information such as casing breaks, collapsed screen, and other changes since construction.

INSTRUMENTATION.--This paragraph provides information on both the frequency of measurment and the collection method used, allowing the user to better evaluate the reported water-level extremes by knowing whether they are based on weekly, monthly, or some other frequency of measurement.

DATUM.--This entry describes both the measuring point and the land-surface elevation at the well. The measuring point is described physically (such as top of collar, notch in top of casing, plug in pump base and so on), and in relation to land surface (such as 1.3 ft above land-surface datum). The elevation of the land-surface datum is described in feet above mean sea level datum, if available. It is reported with precision depending on the method of determination.

REMARKS.--This entry describes factors that may influence the water level in a well or the measurement of the water level. It should identify wells that also are water-quality observation wells, and may be used to acknowledge the assistance of local (non-Survey) observers.

PERIOD OF RECORD.--This entry indicates the period for which there are published records for the well. It reports the month and year of the start of publication of water-level records by the U.S. Geological Survey and the words "to current year" if the records are to be continued into the following year. Periods for which water-level records are available, but are not published by the Geological Survey, may be noted.

EXTREMES FOR PERIOD OF RECORD.--This entry contains the highest and lowest water levels of the period of published record, with respect to land-surface datum, and the dates of their occurrence.

A table of water levels follows the station description for each well. Water levels are reported in feet below land-surface datum and all taped measurements of water level are listed. For wells equipped with recorders, daily values tables are published for the instantaneous water-level observation at noon. The highest and lowest water levels of the water year and their dates of occurrence are shown on a line below the table. Because all values are not published for wells with recorders, the extremes may be values that are not listed in the table. Missing records are indicated by dashes in place of the water level. A hydrograph for a selected period of record follows each water-level table.

Records of Ground-Water Quality

Records of ground-water quality in this type of report differ from other types of records in that for most sampling sites they consist of only one set of measurements for the water year. The quality of ground water ordinarily changes only slowly; therefore, for most general purposes one annual sampling, or only a few samples taken at infrequent intervals during the year, is sufficient. Frequent measurement of the same constituents is not necessary unless one is concerned with a particular problem, such as monitoring for trends in nitrate concentration. In the special cases where the quality of ground water may change more rapidly, more frequent measurements are made to identify the nature of the changes.

Data Collection and Computation

The records of ground-water quality in this report were obtained mostly as a part of special studies in specific areas. Consequently, a number of chemical analyses are presented for some counties but none are presented for others. As a result, the records for this year, by themselves, do not provide a balanced view of ground-water quality Statewide. Such a view can be attained only by considering records for this year in context with similar records obtained for these and other counties in earlier years.

Most methods for collecting and analyzing water samples are described in the "U.S. Geological Survey Techniques of Water-Resources Investigations" manuals listed on a following page. The values reported in this type of report represent water-quality conditions at the time of sampling as much as possible, consistent with available sampling techniques and methods of analysis. All samples are obtained by trained personnel. The wells sampled are pumped long enough to assure that the water collected comes directly from the aquifer and has not stood for a long time in the well casing where it would have been exposed to the atmosphere and to the material, possibly metal, comprising the casings.

Data Presentation

The records of ground-water quality, when available, are published in a section titled QUALITY OF GROUND WATER immediately following the ground-water level records. Data for quality of ground water are listed alphabetically by County, and are identified by well number. The prime identification number for wells sampled is the 15-digit number derived from the latitude-longitude locations. No descriptive statements are given for ground-water-quality records; however, the well number, depth of well, date of sampling, and other pertinent data are given in the table containing the chemical analyses of the ground water. The REMARK codes listed for surface-water-quality records are also applicable to ground-water-quality records.

ACCESS TO WATSTORE DATA

The U.S. Geological Survey is the principal Federal water-data agency and, as such, collects and disseminates about 70 percent of the water data currently being used by numerous State, local, private, and other Federal agencies to develop and manage our water resources. As part of the U.S. Geological Survey's program of releasing water data to the public, a large-scale computerized system has been developed for the storage and retrieval of water data collected through its activities. The National Water-Data Storage and Retrieval System (WATSTORE) was established in 1972 to provide an effective and efficient means for the processing and maintenance of water data collected through the activities of the U.S. Geological Survey and to facilitate release of the data to the public. A variety of useful products, ranging from data tables to complex statistical analyses such as Log Pearson Type III, can be produced using WATSTORE. The system resides on the central computer facilities of the U.S. Geological Survey at its National Center in Reston, Virginia, and consists of related files and data bases.

- * Station Header File Contains descriptive information on over 440,000 sites throughout the United States and its territories where the U.S. Geological Survey collects or has collected data.
- * Daily Values Files Contains over 220 million daily values of streamflow, stages, reservoir contents, water temperatures, specific conductances, sediment concentrations, sediment discharges, and ground-water level.
- * Peak Flow File Contains approximately 500,000 maximum (peak) streamflow and gage-height values at surface-water sites.
- * Water-Quality Data Contains approximately 2 million analyses of water samples that describe the chemical, physical, biological, and radio-chemicals characteristics of both surface and ground water.
- * Ground-Water Site Inventory Data Base Contains inventory data for over 900,000 wells, springs, and other sources of ground water. The data includes site location, geohydrologic characteristics, well-construction history, and one-time field measurements such as water temperature.

In 1976, the U.S. Geological Survey opened WATSTORE to the public for direct access. The signing of a Memorandum of Agreement with the Survey is required to obtain direct access to WATSTORE. The system can be accessed either synchronously or asynchronously. The requestor will be expected to pay all computer costs he/she incurs. Direct access may be obtained by contacting:

U.S. Geological Survey National Water Data Exchange 421 USGS National Center Reston, Virginia 22092

In addition to providing direct access to WATSTORE, data can be provided in various machine-readable formats on magnetic tape or 5-1/4 inch floppy disk; and, as noted in the introduction, on CD-ROM discs. Beginning with the 1990 water year, all water-data reports will also be available on Compact Disc-Read Only Memory (CD-ROM). All data report published for the current water year for the entire Nation, including Puerto Rico and the Trust Territories, will be reproduced on a single CD-ROM disc. Information about the availability of specific types of data or products, and user charges, can be obtained locally from each of the Water Resources Division's offices. (See address on the back of the title page. A limited number of CD-ROM discs will be available for sale by the Books and Open-File Reports Section, U.S. Geological Survey, Federal Center, Box 25425, Denver, Colorado 80225.

DEFINITION OF TERMS

Terms related to streamflow, water-quality, and other hydrologic data as used in this report, are defined below. See also the table for converting inch- pound units to the International System of units (SI) on the inside of the back cover.

Acre-foot (AC-FT, acre-ft) is the quantity of water required to cover 1 acre to a depth of 1 foot and is equal to about 326,000 gallons or 1,233 cubic meters.

Adenosine triphosphate (ATP) is an organic, phosphate-rich, compound important in the transfer of energy in organisms. Its central role in living cells makes it an excellent indicator of the presence of living material in water. A measure of ATP therefore provides a sensitive and rapid estimate of biomass. ATP is reported in micrograms per liter of the original water sample.

Algae growth potential (AGP) is the maximum algal dry weight biomass that can be produced in a natural water sample under standardized laboratory conditions. The growth potential is the algal biomass present a stationary phase and is expressed as milligrams dry weight of algae produced per liter of sample.

Aquifer is a geologic formation, group of formations, or part of a formation that contains sufficient saturated permeable material to yield significant quantities of water to wells and springs.

Artesian means confined and is used to describe a well in which the water level stands above the top of the aquifer, tapped by the well. A flowing artesian well is one in which the water level is above the land surface.

<u>Bacteria</u> are microscopic unicellular organisms, typically spherical, rodlike, or spiral and threadlike in shape, often clumped into colonies. Some bacteria cause disease, while others perform an essential role in nature in the recycling of materials; for example, by decomposing organic matter into a form available for reuse by plants.

Total coliform bacteria are a particular group of bacteria that are used as indicators of possible sewage pollution. They are characterized as aerobic or facultative anaerobic, gram-negative, nonspore-forming, rod-shaped bacteria which ferment lactose with gas formation within 48 hours at 35°C. In the laboratory these bacteria are defined as all the organisms which produce colonies with a golden-green metallic sheen within 24 hours when incubated at 35° C $\pm 1.0^{\circ}$ C on M-Endo medium (nutrient medium for bacterial growth). Their concentrations are expressed as number of colonies per 100 mL of sample.

Fecal coliform bacteria are bacteria that are present in the intestines or feces of warm-blooded animals. They are often used as indicators of the sanitary quality of the water. In the laboratory they are defined as all organisms which produce blue colonies within 24 hours when incubated at $44.5^{\circ}\text{C} \pm 0.2^{\circ}\text{C}$ on M-FC medium (nutrient medium for bacterial growth). Their concentrations are expressed as number of colonies per 100 mL of sample.

Fecal streptococcal bacteria are bacteria found also in intestines of warm-blooded animals. Their presence in water is considered to verify fecal pollution. They are characterized as Gram-positive, cocci bacteria which are capable of growth in brain-heart infusion broth. In the laboratory they are defined as all the organisms which produce red or pink colonies within 48 hours at 35°C ± 1.0°C on KF-streptococcus medium (nutrient medium for bacterial growth). Their concentrations are expressed as number of colonies per 100 mL of sample.

Bed material is the unconsolidated material of which a streambed, lake, pond, reservoir, or estuary bottom is composed.

<u>Biochemical oxygen demand</u> (BOD) is a measure of the quantity of dissolved oxygen, in milligrams per liter, necessary for the decomposition of organic matter by microorganisms, such as bacteria.

Biomass is the amount of living matter present at any given time, expressed as the mass per unit area or volume of habitat.

Ash mass is the mass or amount of residue present after the residue from the dry mass determination has been ashed in a muffle furnace at a temperature of 500° C for 1 hour. The ash mass values of zooplankton and phytoplankton are expressed in grams per cubic meter (g/m³), and periphton and benthic organisms in grams per square meter (g/m²).

<u>Dry mass</u> refers to the mass of residue present after drying in an oven at 105°C for zooplankton and periphyton, until the mass remains unchanged. This mass represents the total organic matter, ash and sediment, in the sample. Dry-mass values are expressed in the same units as ash mass.

Organic mass or volatile mass of the living substance is the difference between the dry mass and the ash mass and represents the actual matter. The organic mass is expressed in the same units as for ash and dry mass.

Wet mass is the mass of living matter plus contained water.

Bottom material: See Bed material.

<u>Cells/volume</u> refers to the number of cells of any organism which is counted by using a microscope and grid or counting cell. Many planktonic organisms are multicelled and are counted according to the number of contained cells per sample, usually milliliters (mL) or liters (L).

<u>Chemical oxygen demand</u> (COD) is a measure of the chemically oxidizable material in the water, and furnishes an approximation of the amount of organic and reducing material present. The determined value may correlate with natural water color or with carbonaceous organic pollution from sewage or industrial wastes.

<u>Clorophyll</u> refers to the green pigments of plants. Chlorophyll <u>a</u> and <u>b</u> are the two most common green pigments in plants.

<u>Color unit</u> is produced by one milligram per liter of platinum in the form of the chloroplatinate ion. Color is expressed in units of the platinum-cobalt scale.

<u>Contents</u> is the volume of water in a reservoir or lake. Unless otherwise indicated, volume is computed on the basis of a level pool and does not include bank storage.

<u>Control</u> designates a feature downstream from the gage that determines the stage-discharge relation at the gage. This feature may be a natural constriction of the channel, an artificial structure, or a uniform cross section over a long reach of the channel.

<u>Control structure</u> as used in this report is a structure on a stream or canal that is used to regulate the flow or stage of the stream or to prevent the intrusion of salt water.

<u>Cubic foot per second</u> (ft³/s) is the rate of discharge representing a volume of 1 cubic foot passing a given point during 1 second and is equivalent to 7.48 gallons per second or 448.8 gallons per minute or 0.02832 cubic meters per second.

Cubic foot per second-day (ft³/s/day) is the volume of water represented by a flow of 1 cubic foot per second for 24 hours. It is equivalent to 86,400 cubic feet, approximately 1.9835 acre-feet, about 646,000 gallons, or 2,445 cubic meters.

<u>Cubic feet per second per square mile</u> (CFSM) is the average number of cubic feet of water flowing per second from each square mile of area drained, assuming that the runoff is distributed uniformly in time and area.

<u>Discharge</u> is the volume of water (or more broadly, volume of fluid plus suspended sediment), that passes a given point within a given period of time.

Instantaneous discharge is the discharge at a particular instant of time.

Mean discharge (MEAN) is the arithmetic mean of individual daily mean discharges during a specific period.

Annual 7-day minimum is the lowest mean discharge for 7 consecutive days for a calendar year or a water year. Note that most low-flow frequency analyses of annual 7-day minimum flows use a climatic year (April 1 - March 31). The date shown in the summary statistics table is the initial date of the 7-day period. (This value should not be confused with the 7-day 10-year low-flow statistic.)

<u>Dissolved</u> refers to that material in a representative water sample which passes through a 0.45 um membrane filter. This is a convenient operational definition used by Federal agencies that collect water data. Determinations of "dissolved" constituents are made on subsamples of the filtrate.

<u>Dissolved-solids concentration</u> of water is determined either analytically by the "residue-on-evaporation" method, or mathematically by totaling the concentrations of individual constituents reported in a comprehensive chemical analysis. During the analytical determination of dissolved solids, the bicarbonate (generally a major dissolved component of water) is converted to carbonate. Therefore, in the mathematical calculations of dissolved-solids concentration, the bicarbonate value, in milligrams per liter, is multiplied by 0.492 to reflect the change.

<u>Diversity index</u> is a numerical expression of evenness of distribution of aquatic organisms. The formula for diversity index is:

$$\frac{1}{d} = -\sum_{i=1}^{n} \log_2 \frac{n_i}{n}$$

Where "i is the number of individuals per taxon, n is the total number of individuals, and s is the total number of taxa in the sample of the community. Diversity index values range from zero, when all the organisms in the sample are the same, to some positive number, when some or all of the organisms in the sample are different.

<u>Drainage area</u> of a stream at a specified location is that area, measured in a horizontal plane, enclosed by a topographic divide from which direct surface runoff from precipitation normally drains by gravity into the stream above the specified point. Figures of drainage area given herein include all closed basins, or noncontribution areas, within the area unless otherwise noted.

<u>Drainage basin</u> is a part of the surface of the earth that is occupied by a drainage system, which consists of a surface stream or a body of impounded surface water together with all tributary surface streams and bodies of impounded surface water.

Gage height (G.H.) is the water-surface elevation referred to some arbitrary gage datum. Gage height is often used interchangeably with the more general term "stage," although gage height is more appropriate when used with a reading on a gage.

Gaging station is a particular site on a stream, canal, lake, or reservoir where systematic observations of hydrologic data are obtained.

<u>Ground-water station</u> is a well at which observations of ground-water level are made, either continuously by recorder, or periodically by hand. In addition, various chemical or physical parameters may be obtained, usually on a periodic basis.

<u>Hardness</u> of water is a physical-chemical characteristic that is commonly recognized by the increased quantity of soap required to produce lather. It is attributable to the presence of alkaline earths (principally calcium and magnesium) and is expressed as equivalent calcium carbonate (CaCO₃).

Hydrologic Bench-Mark Network is a network in small drainage basins around the country whose purpose is to provide consistent data on the hydrology, including water quality, and related factors in representative undeveloped watersheds nationwide, and to provide analyses on a continuing basis to compare and contrast conditions observed in basins more obviously affected by the activities of man.

<u>Hydrologic unit</u> is a geographic area representing part or all of a surface drainage basin or distinct hydrologic feature as delineated by the Office of Water Data Coordination on the State Hydrologic Unit Maps; each hydrologic unit is identified by an eight-digit number.

<u>Land-surface datum</u> (lsd) is a datum plane that is approximately at land surface at each ground-water observation well.

Measuring point (MP) is an arbitrary permanent reference point from which the distance to the water surface in a well is measured to obtain the water level.

Metamorphic stage refers to the stage of development that an organism exhibits during its transformation from an immature form to an adult form. This developmental process exists for most insects, and the degree of difference from the immature stage to the adult form varies from relatively slight to pronounced, with many intermediates. Examples of metamorphic stages of insects are egg-larva-adult or egg-nymph-adult.

Methylene blue active substances (MBAS) are apparent detergents. The determination depends on the formation of a blue color when methylene blue dye reacts with synthetic anionic detergent compounds.

Micrograms per gram (ug/g) is a unit expressing the concentration of a chemical element as the mass (micrograms) of the element per unit mass (gram) of material analyzed.

Micrograms per liter (UG/L, ug/L) is a unit expressing the concentration of chemical constituents in solution as mass (micrograms) of solute per unit volume (liter) of water. One thousand micrograms per liter is equivalent to one milligram per liter.

Milligrams per liter (MG/L, mg/L) is a unit for expressing the concentration of chemical constituents in solution. Milligrams per liter represent the mass of solute per unit volume (liter) of water. Concentration of suspended sediment also is expressed in mg/L, and is based on the mass of sediment per liter of water-sediment mixture. Conversion of chemical concentrations in Mg/L to milliequivalents per liter can be done by using the factors in table 5.

Table 5. Factors for conversion of chemical constituents in milligrams per liter to milliequivalents per liter.

<u>Ion</u>	Multiply by	<u>Ion</u>	Multiply by
Aluminum (Al+3)*	0.11119	Iodide (I-1)	0.00788
Ammonia as NH4+1	.05544	Iron (Fe+3)	.05372
Barium (Ba+2)	.01456	Lead (Pb+2)	.00965
Bicarbonate (HCO3-1)	.01639	Lithium (Li+1)	.14411
Bromide (Br-1)	.01251	Magnesium (Mg+2)	.08226
Calcium (Ca+2)	.04990	Manganese (Mn+2)*	.03640
arbonate (CO3-2)	.03333	Nickel (Ni+2)	.03406
hloride (Cl-1)	.02821	Nitrate (N03-1)	.01613
hromium (Cr+6)*	.11539	Nitrite (NO2-1)	.02174
obalt (Co+2)*	.03394	Phosphate (PO4-3)	.03159
opper (Cu+2)*	.03148	Potassium (K+1)	.02557
yanide (CN-1)	.03844	Sodium (NA+1)	.04350
luoride (F-1)	.05264	Strontium (Sr+2)	.02283
ydrogen (H+1)	.99209	Sulfate (SO4-2)	.02082
Nydroxide (OH-1)	.05880	Zinc $(Zn+2)*$.03060

^{*}Constituent reported in micrograms per liter; multiply by factor and divide results by 1,000.

National Stream Quality Accounting Network (NASQAN) is a nationwide data-collection network designed by the U.S. Geological Survey to meet many of the information needs of government agencies and other groups involved in natural or regional water-quality planning and management. The 500 or so sites in NASQAN are generally located at the downstream ends of hydrologic accounting units designated by the U.S. Geological Survey office of Water Data Coordination in consultation with the Water Resources Council. The objectives of NASQAN are (1) to obtain information on the quality and quantity of water moving within and from the United States through a systematic and uniform process of data collection, summarization, analysis, and reporting such that the data may be used for, (2) description of the areal variability of water quality in the Nation's rivers through analysis of description of the areal variability of water quality in the Nation's rivers through analysis of data from this and other programs, (3) detection of changes or trends with time in the pattern of occurrence of water-quality characteristics, and (4) providing a nationally consistent data base useful for water-quality assessment and hydrologic research.

<u>National Trends Network</u> (NTN) is a network for sampling atmospheric deposition in the United States. The purpose of the network is to determine the variability, both in location and in time, of the composition of atmospheric deposition, which includes snow, rain, dust particles, aerosols, and gases. The core from which the NTN was built was the already-existing deposition-monitoring network of the National Atmospheric Deposition Program (NADP).

Organism is any living entity.

Organism count/area refers to the number of organisms collected and enumerated in a sample and adjusted to the number per unit area habitat, usually square meters (m²), acres, or hectare. Periphyton, benthic organisms, and macrophytes are expressed in these terms.

Organism count/volume refers to the number of organisms collected and enumerated in a sample and adjusted to the number per sample volume, usually milliliters (mL) or liters (L). Numbers of planktonic organisms can be expressed in these terms.

Total organism count is the total number of organisms collected and enumerated in any particular sample.

<u>Parameter Code</u> is a 5-digit number used in the U.S. Geological Survey computerized data system, WATSTORE, to uniquely identify a specific constituent. The codes used in WATSTORE are the same as those used in the U.S. Environmental Protection Agency data system, STORET. The Environmental Protection Agency assigns and approves all requests for new codes.

<u>Partial-record station</u> is a particular site where limited streamflow and/or water-quality data are collected systematically over a period of years for use in hydrologic analyses.

<u>Particle-size</u> is the diameter, in millimeters (mm), of a particle determined by either sieve or sedimentation methods. Sedimentation methods (pipet, bottom-withdrawal tube, visual-accumulation tube) determine fall diameter of particles in either distilled water (chemically dispersed) or in native water (the river water at the time and point of sampling).

<u>Particle-size classification</u> used in this report agrees with recommendations made by the American Geophysical Union Subcommittee on Sediment Terminology. The classification is as follows:

Classification	Size (mm)	Method of analysis
Clay	0.00024 - 0.004	Sedimentation
Silt	.004062	Sedimentation
Sand	.062 - 2.0	Sedimentation or sieve
Gravel	2.0 - 64.0	Sieve

The particle-size distributions given in this report are not necessarily representative of all particles in transport in the stream. Most of the organic matter is removed and the sample is subjected to mechanical and chemical dispersion before analysis in distilled water. Chemical dispersion is not used for native water analysis.

<u>Percent composition</u> is a unit for expressing the ratio of a particular part of a sample or population to the total sample or population, in terms of types, numbers, mass or volume.

<u>Periphyton</u> is the assemblage of microorganisms attached to and living upon submerged solid surfaces. While primarily consisting of algae, they also include bacteria, fungi, protozoa, rotifers, and other small organisms.

<u>Pesticides</u> are chemical compounds used to control undesirable organisms. Major categories of pesticides include insecticides, miticides, fungicides, herbicides, and rodenticides.

<u>Picocurie</u> (PC, pCi) is one trillionth (1 X 10^{-12}) of the amount of ratioactivity represented by a curie (Ci). A curie is the amount of radioactivity that yields 3.7 x 10^{10} radioactive disintegrations per second. A picocurie yields 2.22 dpm (disintegrations per minute).

<u>Plankton</u> is the community of suspended, floating, or weakly swimming organisms that live in the open water of lakes and rivers.

<u>Phytoplankton</u> is the plant part of the plankton. They are usually microscopic and their movement is subject to the water currents. Phytoplankton growth is dependent upon solar radiation and nutrient substances. Because they are able to incorporate as well as release materials to the surrounding water, the phytoplankton have a profound effect upon the quality of the water. They are the primary food producers in the aquatic environment, and are commonly known as algae.

Blue-green algae are a group of phytoplankton organisms having a blue pigment, in addition to the green pigment called chlorophyll. Blue-green algae often cause nuisance conditions in water.

<u>Diatoms</u> are the unicellular or colonial algae having a siliceous shell. Their concentrations are expressed as number of cells per milliliter (cells/mL) of sample.

Green algae have chlorophyll pigments similar in color to thos of higher green plants. Some forms produce algae mats or floating "moss" in lakes. Their concentrations are expressed as number of cells per milliliter (cells/mL) of sample.

Zooplankton is the animal part of the plankton. Zooplankton are capable of extensive movements within the water column and are often large enough to be seen with the unaided eye. Zooplankton are secondary consumers feeding upon bacteria, phytoplankton, and detritus. Because they are the grazers in the aquatic environment, the zooplankton are a vital part of the aquatic food web. The zooplankton community is dominated by small crustaceans and rotifers.

<u>Primary productivity</u> is a measure of the rate at which new organic matter is formed and accumulated through photosynthetic and chemosynthetic activity of producer organisms (chiefly, green plants). The rate of primary production is estimated by measuring the amount of oxygen released (oxygen method) or the amount of carbon assimilated by the plants (carbon method).

Milligrams of carbon per area or volume per unit time [mg C/(m².time)] for periphyton and macrophytes and [mg C/(m³.time)] for phytoplankton are units for expressing primary productivity. They define the amount of carbon dioxide consumed as measured by radioactive carbon (carbon 14). The carbon 14 method is of greater sensitivity than the oxygen light and dark bottle method, and is preferred for use in unenriched waters. Unit time may be either hour or day, depending on the incubation period.

Milligrams of oxygen per area or volume per unit time [mg0 / (m².time)] for periphyton and macrophytes and [mg0 /(m³.time)] for phytoplankton are the units for expressing primary productivity. They define production and respiration rates as estimated from changes in the measured dissolved-oxygen concentration. The oxygen light and dark bottle method is preferred if the rate of primary production is sufficient for accurate measurements to be made within 24 hours. Unit time may be either the hour or day, depending on the incubation period.

<u>Polychlorinated biphenyls</u> (PCBs) are industrial chemicals that are mixtures of chlorinated biphenyl compounds having various percentages of chlorine. They are similar in structure to organochlorine insecticides.

<u>Radiochemical program</u> is a network of regularly sampled water-quality stations where samples are collected to be analyzed for radioisotypes. The streams that are sampled represent major drainage basins in the conterminous United States.

Recoverable from bottom material is the amount of a given constituent that is in solution after a representative sample of bottom material has been digested by a method (usually using an acid or mixture of acids) that results in dissolution of readily soluble substances. Complete dissolution of all bottom material is not achieved by the digestion treatment and thus the determination represents less than the total amount (that is, less than 95 percent) of the constituent in the sample. To achieve comparability of analytical data, equivalent digestion procedures would be required of all laboratories performing such analyses because different digestion procedures are likely to produce different analytical results.

Return period is the average time interval between occurrences of a hydrological event of a given or greater magnitude, usually expressed in years. May also be called recurrence interval.

Runoff in inches (IN, in) shows the depth to which the drainage area would be covered if all the runoff for a given time period were uniformly distributed on it.

<u>Sediment</u> is solid material that originates mostly from disintegrated rocks and is transported by, suspended in, or deposited from water; it includes chemical and biochemical precipitates and decomposed organic material, such as humus. The quantity, characteristics, and cause of the occurrence of sediment in streams are influenced by environmental factors. Some major factors are degree of slope, length of slope, soil characteristics, land usage, and quantity and intensity of precipitation.

<u>Bed load</u> is the sediment that is transported in a stream by rolling, sliding, or skipping along the bed and very close to it. In this report, bed load is considered to consist of particles in transit within 0.25 ft of the streambed.

Bed load discharge (tons per day) is the quantity of bed load measured by dry weight that moves past a section as bed load in a given time.

<u>Suspended sediment</u> is the sediment that at any given time is maintained in suspension by the upward components of turbulent currents or that exists in suspension as a colloid.

<u>Suspended-sediment concentration</u> is the velocity-weighted concentration of suspended sediment in the sampled zone (from the water surface to a point approximately 0.3 ft above the bed) expressed as milligrams of dry sediment per liter of water-sediment mixture (mg/L).

Mean concentration is the time-weighted concentration of suspended sediment passing a stream section during a 24-hour day.

Suspended-sediment discharge (tons/day) is the rate at which dry mass of sediment passes a section of a stream or is the quantity of sediment, as measured by dry mass or volume, that passes a section in a given time. It is calculated in units of tons per day as follows: concentrations (mg/L) x discharge (ft³/s) x 0.0027.

<u>Suspended-sediment load</u> is a general term that refers to material in suspension. It is not synonymous with either discharge or concentration.

<u>Total sediment discharge</u> (tons/day) is the sum of the suspended-sediment discharge and the bed-load discharge. It is the total quantity of sediment, as measured by dry mass or volume, that passes a section during a given time.

<u>Total-sediment load</u> or total load is a term which refers to the total sediment (bed load plus suspended-sediment load) that is in transport. It is not synonymous with total-sediment discharge.

7-day 10-year low flow (7Q10) is the discharge at the 10-year recurrence interval taken from a frequency curve of annual values of the lowest mean discharge for 7 consecutive days (the 7-day low flow).

Sodium-adsorption-ratio (SAR) is the expression of relative activity of sodium ions in exchange reactions within soil and is an index of sodium or alkali hazard to the soil. Waters range in respect to sodium hazard from those which can be used for irrigation on almost all soils to those which are generally unsatisfactory for irrigation.

Solute is any substance that is dissolved in water.

Specific conductance is a measure of the ability of a water to conduct an electric current. It is expressed in microsiemens per centimeter at 25°C. Specific conductance is related to the type and concentration of ions in solution and can be used for approximating the dissolved-solids content of the water. Commonly, the concentration of dissolved solids (in milligrams per liter) is about 65 percent of the specific conductance (in micromhos). This relation is not constant from stream, and it may vary in the same source with changes in the composition of the water.

<u>Stage-discharge relation</u> is the relation between gage height (stage) and volume of water per unit of time, flowing in a channel.

Streamflow is the discharge that occurs in a natural channel. Although the term "discharge" can be applied to the flow of a canal, the word "streamflow" uniquely describes the discharge in a surface stream course. The term "streamflow" is more general than "runoff" as streamflow may be applied to discharge whether or not it is affected by diversion or regulation.

Substrate is the physical surface upon which an organism lives.

<u>Natural substrate</u> refers to any naturally occurring emersed or submersed solid surface, such as a rock or tree, upon which an organism lives.

Artificial substrate is a device which is purposely placed in a stream or lake for colonization of organisms. The artificial substrate simplifies the community structure by standardizing the substrate from which each sample is taken. Examples of artificial substrates are basket samplers (made of wire cages filled with clean streamside rocks) and multiplate samplers (made of hardboard) for benthic organism collection, and plexiglass strips for periphyton.

Surface area of a lake is that area outlined on the latest U.S.G.S. topographic map as the boundary of the lake and measured by a planimeter in acres. In localities not covered by topographic maps, the areas are computed from the best maps available at the time planimetered. All areas shown are those for the stage when the planimetered map was made.

<u>Surficial bed material</u> is that part (0.1 to 0.2 ft) of the bed material that is sampled using U.S. Series Bed-Material Samplers.

<u>Suspended</u> (as used in tables of chemical analyses) refers to the amount (concentration) of the total concentration in a water-sediment mixture. It is associated with the material retained on a 0.45-micrometer filter.

Suspended, recoverable is the amount of a given constituent that is in solution after the part of a representative water-suspended sediment sample that is retained on a 0.45 um membrane filter has been digested by a method (usually using a dilute acid solution) that results in dissolution of only readily soluble substances. Complete dissolution of all the particulate matter is not achieved by the digestion treatment and thus the determination represents something less than the "total" amount (that is, less than 95 percent) of the constituent present in the sample. To achieve comparability of analytical data, equivalent digestion procedures are required of all laboratories performing such analyses because different digestion procedures are likely to produce different analytical results.

Determinations of "suspended, recoverable" constituents are made either by analyzing portions of the material collected on the filter or, more commonly, by difference, based on determinations of (1) dissolved and (2) total recoverable concentrations of the constituent.

Suspended, total is the total amount of a given constituent in the part of representative water-suspended sediment sample that is retained on a 0.45 um membrane filter. This term is used only when the analytical procedure assures measurement of at least 95 percent of the constituent determined. A knowledge of the expected form of the constituent in the sample, as well as the analytical methodology used, is required to determine when the results should be reported as "suspended, total."

Determinations of "suspended, total" constituents are made either by analyzing portions of the material collected on the filter or, more commonly, by difference, based on determinations of (1) dissolved and (2) total concentrations of the constituent.

<u>Taxonomy</u> is the division of biology concerned with the classification and naming of organisms. The classification of organisms is based upon a hierarchial scheme beginning with Kingdom and ending with Species at the base. The higher the classification level, the fewer features the organisms have in common. For example, the taxonomy of a particular mayfly, <u>Hexagenia</u> limbata, is the following:

Kingdom	Animal
Phylum	Arthopoda
Class	-
Order	Ephemeroptera
Family	Ephemeridae
•	Hexagenia
	Hexagenia limbata

<u>Thermograph</u> is an instrument that continuously records variations of temperature on a chart. The more general term "temperature recorder" is used in the table heading and refers to any instrument that records temperature whether on a chart, a tape, or any other medium.

<u>Time-weighted average</u> is computed by multiplying the number of days in the sampling period by the concentrations of individual constituents for the corresponding period and dividing the sum of the products by the total number of days. A time-weighted average represents the composition of water that would be contained in a vessel or reservoir that had received equal quantities of water from the stream each day for the year.

Tons per acre-foot indicates the dry mass of dissolved solids in 1 acre-foot of water. It is computed by multiplying the concentration of the constituent, in milligrams per liter by 0.00136.

Tons per day (T/DAY) is the quantity of a substance in solution or suspension that passes a stream section during a 24-hour period.

Total is the total amount of a given constituent in a representative water-suspended sediment sample, regardless of the constituent's physical or chemical form. This term is used only when the analytical procedure assures measurement of at least 95 percent of the constituent present in both the dissolved and suspended phases of the sample. A knowledge of the expected form of the constituent in the sample, as well as the analytical methodology used, is required to judge when the results should be reported as "total." (Note that the word "total" does double duty here, indicating both that the sample consists of a water-suspended sediment mixture and that the analytical method determined all of the constituent in the sample.)

<u>Total discharge</u> is the total quantity of any individual constituent, as measured by dry mass or volume, that passes through a stream cross-section per unit of time. This term needs to be qualified, such as "total sediment discharge," "total chloride discharge," and so on.

Total, recoverable is the amount of a given constituent that is in solution after a representative water-suspended sediment sample has been digested by a method (usually using a dilute acid solution) that results in dissolution of only readily soluble substances. Complete dissolution of all particulate matter is not achieved by the digestion treatment, and thus the determination represents something less than the "total" amount (that is, less than 95 percent) of the constituent present in the dissolved and suspended phases of the sample. To achieve comparability of analytical data, equivalent digestion procedures are required of all laboratories performing such analyses, because different digestion procedures are likely to produce different analytical results.

<u>Tritium Network</u> is a network of stations which has been established to provide baseline information on the occurrence of tritium in the Nation's surface waters. In addition to the surface-water stations in the network, tritium data are also obtained at a number of precipitations stations. The purpose of the precipitation stations is to provide an estimate sufficient for hydrologic studies of the tritium input to the United States.

Water year in Geological Survey reports dealing with surface water supply is the 12-month period, October 1 through September 30. The water year is designated by the calendar year in which it ends and which includes 9 of the 12 months. Thus, the year ending September 30, 1980, is called the "1980 water year."

<u>WDR</u> is used as an abbreviation for "Water-Data Report" in the REVISED RECORDS paragraph to refer to State annual hydrologic-data reports (WRD was used as an abbreviation for "Water-Resources Data" in reports published prior to 1976).

Weighted average is used in this report to indicate discharge-weighted average. It is computed by multiplying the discharge for a sampling period by the concentrations of individual constituents for the corresponding period and dividing the sum of the products by the sum of the discharges. A discharge-weighted average approximates the composition of water that would be found in a reservoir containing all the water passing a given location during the water year after thorough mixing in the reservoir.

WSP is used as an abbreviation for "Water-Supply Paper" in references to previously published reports.

40 PUBLICATIONS ON TECHNIQUES OF WATER-RESOURCES INVESTIGATIONS

The U.S. Geological Survey publishes a series of manuals describing procedures for planning and conducting specialized work in water-resources investigations. The material is grouped under major subject headings called books and is further divided into sections and chapters. For example, Section A of Book 3 (Applications of Hydraulics) pertains to surface water. The chapter, the unit of publication, is limited to a narrow field of subject matter. This format permits flexibility in revision and publication as the need arises.


The reports listed below are for sale by the U.S. Geological Survey, Books and Open-File Reports Section, Federal Center, Box 25425, Denver, Colorado 80225 (authorized agent of the Superintendent of Documents, Government Printing Office). Prepayment is required. Remittance should be sent by check or money order payable to the U.S. Geological Survey. Prices are not included because they are subject to change. Current prices can be obtained by writing to the above address. When ordering or inquiring about prices for any of these publications, please give the title, book number, chapter number, and "U.S. Geological Survey Techniques of Water-Resources Investigations."

- 1-D1. Water temperature--influential factors, field measurement, and data presentation, by H. H. Stevens, Jr., J. F. Ficken, and G. F. Smoot: USGS--TWRI Book 1, Chapter D1. 1975. 65 pages.
- 1-D2. Guidelines for collection and field analysis of ground-water samples for selected unstable constituents, by W. W. Wood: USGS-TWRI Book 1, Chapter D2. 1976. 24 pages.
- 2-D1. Application of surface geophysics to ground-water investigations, by A. A. R. Zohdy, G. P. Eaton, and D. R. Mabey: USGS--TWRI Book 2, Chapter D1. 1974. 116 pages.
- 2-D2. Application of seismic-refraction techniques to hydrologic studies, by F. P. Haeni: USGS--TWRI Book 2, Chapter D2. 1988. 86 pages.
- 2-E1. Application of borehole geophysics to water-resources investigations, by W. S. Keys and L. M. McCary: USGS--TWRI Book 2, Chapter E1, 1971, 126 pages.
- 2-E2. Borehole geophysics applied to ground-water investigations, by W. S. Keys: USGS--TWRI Book 2, Chapter E2. 1990. 150 pages.
- 2-F1. Application of drilling, coring, and sampling techniques to test holes and wells, by Eugene Shuter and W. E. Teasdale: USGS--TWRI Book 2, Chapter F1. 1989. 97 pages.
- 3-A1. General field and office procedures for indirect discharge measurements, by M. A. Benson and Tate Dalrymple: USGS--TWRI Book 3, Chapter A1, 1967, 30 pages.
- 3-A2. Measurement of peak discharge by the slope-area method, by Tate Dalrymple and M. A. Benson: USGS--TWRI Book 3, Chapter A2. 1967. 12 pages.
- 3-A3. Measurement of peak discharge at culverts by indirect methods, by G. L. Bodhaine: USGS--TWRI Book 3, Chapter A3. 1968. 60 pages.
- 3-A4. *Measurement of peak discharge at width contractions by indirect methods,* by H. F. Matthai: USGS-TWRI Book 3, Chapter A4. 1967. 44 pages.
- 3-A5. *Measurement of peak discharge at dams by indirect methods*, by Harry Hulsing: USGS--TWRI Book 3. Chapter A5. 1967. 29 pages.
- 3-A6. General procedure for gaging streams, by R. W. Carter and Jacob Davidian: USGS--TWRI Book 3, Chapter A6. 1968. 13 pages.
- 3-A7. Stage measurements at gaging stations, by T. J. Buchanan and W. P. Somers: USGS--TWRI Book 3, Chapter A7. 1968. 28 pages.
- 3-A8. Discharge measurements at gaging stations, by T. J. Buchanan and W. P. Somers: USGS--TWRI Book 3, Chapter A8. 1969. 65 pages.
- 3-A9. *Measurement of time of travel in streams by dye tracing,* by F. A. Kilpatrick and J. F. Wilson, Jr.: USGS--TWRI Book 3, Chapter A9. 1989. 27 pages.

- 3-Alo. Discharge ratings at gaging stations, by E. J. Kennedy: USGS--TWRI Book 3, Chapter A10. 1984. 59 pages.
- 3-A11. *Measurement of discharge by moving-boat method*, by G. F. Smoot and C. E. Novak: USGS--TWRI Book 3, Chapter A11, 1969, 22 pages.
- 3-A12. Fluorometric procedures for dye tracing, by J. F. Wilson, Jr., E. D. Cobb, and F. A. Kilpatrick: USGS--TWRI Book 3, Chapter A12. 1986. 41 pages.
- 3-A13. Computation of continuous records of streamflow, by E. J. Kennedy: USGS--TWRI Book 3, Chapter A13, 1983, 53 pages.
- 3-A14. Use of flumes in measuring discharge, by F. A. Kilpatrick and V. R. Schneider: USGS--TWRI Book 3, Chapter A14. 1983. 46 pages.
- 3-A15. Computation of water-surface profiles in open channels, by Jacob Davidian: USGS-TWRI Book 3, Chapter A15. 1984. 48 pages.
- 3-A16. *Measurement of discharge using tracers*, by F. A. Kilpatrick and E. D. Cobb: USGS--TWRI Book 3, Chapter A16. 1985. 52 pages.
- 3-A17. Acoustic velocity meter systems, by Antonius Laenen: USGS--TWRI Book 3, Chapter A17. 1985. 38 pages.
- 3-A18. Determination of stream reaeration coefficients by use of tracers, by F. A. Kilpatrick, R. E. Rathburn, Nobuhiro Yotsukura, G. W. Parker, and L. L. DeLong: USGS--TWRI Book 3, Chapter A18. 1989. 52 pages.
- 3-A19. Levels of streamflow gaging stations, by E.J. Kennedy: USGS--TWRI Book 3, Chapter A19. 1990. 27 pages.
- 3-B1. Aquifer-test design, observation, and data analysis, by R. W. Stallman: USGS--TWRI Book 3, Chapter B1. 1971. 26 pages.
- 3-B2. Introduction to ground-water hydraulics, a programmed text for self-instruction, by G. D. Bennett: USGS-- TWRI Book 3, Chapter B2. 1976. 172 pages.
- 3-B3. Type curves for selected problems of flow to wells in confined aquifers, by J. E. Reed: USGS-TWRI Book 3, Chapter B3. 1980. 106 pages.
- 3-B4. Regression modeling of ground-water flow, by R. L. Cooley and R. L. Naff: USGS--TWRI Book 3, Chapter B4. 1990. 232 pages.
- 3-B5. Definition of boundary and initial conditions in the analysis of saturated ground-water flow systems--An introduction, by O. L. Franke, T. E. Reilly, and G. D. Bennett: USGS--TWRI Book 3, Chapter B5. 1987. 15 pages.
- 3-B6. The principle of superposition and its application in ground-water hydraulics, by T. E. Reilly, O. L. Franke, and G. D. Bennett: USGS--TWRI Book 3, Chapter B6. 1987. 28 pages.
- 3-B7. Analytical solutions for one-, two-, and three-dimensional solute transport in ground-water systems with uniform flow, by E. J. Wexler: USGS--TWRI Book 3, Chapter B7. 1992. 90 pages.
- 3-C1. Fluvial sediment concepts, by H. P. Guy: USGS--TWRI Book 3, Chapter C1. 1970. 55 pages.
- 3-C2. Field methods for measurement of fluvial sediment, by H. P. Guy and V. W. Norman: USGS--TWRI Book 3, Chapter C2. 1970. 59 pages.
- 3-C3. Computation of fluvial-sediment discharge, by George Porterfield: USGS--TWRI Book 3, Chapter C3. 1972. 66 pages.
- 4-A1. Some statistical tools in hydrology, by H. C. Riggs: USGS--TWRI Book 4, Chapter A1. 1968. 39 pages.

PUBLICATIONS ON TECHNIQUES OF WATER-RESOURCES INVESTIGATIONS--Continued

- 4-A2. Frequency curves, by H. C. Riggs: USGS--TWRI Book 4, Chapter A2. 1968. 15 pages.
- 4-B1. Low-flow investigations, by H. C. Riggs: USGS--TWRI Book 4, Chapter B1. 1972. 18 pages.
- 4-B2. Storage analyses for water supply, by H. C. Riggs and C. H. Hardison: USGS--TWRI Book 4, Chapter B2. 1973. 20 pages.
- 4-B3. Regional analyses of streamflow characteristics, by H. C. Riggs: USGS--TWRI Book 4, Chapter B3. 1973. 15 pages.
- 4-D1. Computation of rate and volume of stream depletion by wells, by C. T. Jenkins: USGS--TWRI Book 4, Chapter D1. 1970. 17 pages.
- 5-A1. Methods for determination of inorganic substances in water and fluvial sediments, by M. J. Fishman and L. C. Friedman: USGS--TWRI Book 5, Chapter A1. 1989. 545 pages.
- 5-A2. Determination of minor elements in water by emission spectroscopy, by P. R. Barnett and E. C. Mallory, Jr.: USGS--TWRI Book 5, Chapter A2. 1971. 31 pages.
- 5-A3. Methods for the determination of organic substances in water and fluvial sediments, edited by R. L. Wershaw, M. J. Fishman, R. R. Grabbe, and L. E. Lowe: USGS--TWRI Book 5, Chapter A3. 1987. 80 pages.
- 5-A4. Methods for collection and analysis of aquatic biological and microbiological samples, by L. J. Britton and P. E. Greeson, editors: USGS--TWRI Book 5, Chapter A4. 1989. 363 pages.
- 5-A5. Methods for determination of radioactive substances in water and fluvial sediments, by L. L. Thatcher, V. J. Janzer, and K. W. Edwards: USGS--TWRI Book 5, Chapter A5. 1977. 95 pages.
- 5-A6. Quality assurance practices for the chemical and biological analyses of water and fluvial sediments, by L. C. Friedman and D. E. Erdmann: USGS--TWRI Book 5, Chapter A6. 1982. 181 pages.
- 5-C1. Laboratory theory and methods for sediment analysis, by H. P. Guy: USGS-TWRI Book 5, Chapter C1. 1969. 58 pages.
- 6-A1. A modular three-dimensional finite-difference ground-water flow model, by M. G. McDonald and A. W. Harbaugh: USGS--TWRI Book 6, Chapter A1. 1988. 586 pages.
- 6-A2. Documentation of a computer program to simulate aquifer-system compaction using the modular finite-difference ground-water flow model, by S. A. Leake and D. E. Prudic: USGS--TWRI Book 6, Chapter A2. 1991. 68 pages.
- 7-C1. Finite difference model for aquifer simulation in two dimensions with results of numerical experiments, by P. C. Trescott, G. F. Pinder, and S. P. Larson: USGS--TWRI Book 7, Chapter C1. 1976. 116 pages.
- 7-C2. Computer model of two-dimensional solute transport and dispersion in ground water, by L. F. Konikow and J. D. Bredehoeft: USGS--TWRI Book 7, Chapter C2. 1978. 90 pages.
- 7-C3. A model for simulation of flow in singular and interconnected channels, by R. W. Schaffrannek, R. A. Baltzer, and D. E. Goldberg: USGS--TWRI Book 7, Chapter C3. 1981. 110 pages.
- 8-A1. *Methods of measuring water levels in deep wells*, by M. S. Garber and F. C. Koopman: USGS-TWRI Book 8, Chapter A1. 1968. 23 pages.
- 8-A2. Installation and service manual for U.S. Geological Survey manometers, by J. D. Craig: USGS--TWRI Book 8, Chapter A2. 1983. 57 pages.
- 8-B2. Calibration and maintenance of vertical-axis type current meters, by G. F. Smoot and C. E. Novak: USGS--TWRI Book 8, Chapter B2. 1968. 15 pages.



Surface and Quality-of-Water Records for Puerto Rico THIS PAGE WAS LEFT BLANK INTENTIONALLY




Figure 13.--Río Guajataca basin.

46

RIO GUAJATACA BASIN

50010500 RIO GUAJATACA AT LARES, PR

LOCATION.--Lat 18°18'01", long 66°52'24", Hydrologic Unit 21010001 at bridge on Highway 111, 0.1 mi (0.2 km) upstream from Quebrada Anón, and 0.4 mi (0.6 km) east of Lares.

DRAINAGE AREA . -- 3.16 mi2 (8.18 km2).

WATER-DISCHARGE RECORDS

PERIOD OF RECORD. -- February 1959 to February 1962 (annual low-flow measurements only), January 1963 to April 1969 (monthly measurements only), May 1969 to December 1970 (February to May 1971 and March 1974 to November 1989, monthly measurements only), December 1989 to current year.

GAGE.--Water-stage recorder and crest-stage gage. Elevation of gage is 935 ft (285 m), from topographic map.

REMARKS.--Records poor. Gage-height and precipitation satellite telemetry at station. Small diversion above station for sewage treatment plant; effluent re-enters stream below station.

		DISCHA	RGE, CUBI	C FEET PER		WATER Y MRAN	YEAR OCTOBER VALUES	1991 TO	September	1992		
DAY	OCT	NOA	DEC	JAN	FEB	MAR	APR	MAY	JUN	JUL	AUG	SEP
1	11	23	3.7	e.85	e1.0	e.78	e1.1	e1.5	e2.8	e2.0	e2.3	e18
2	12	17	2.8	e.82	e1.1	e.77		e1.2	e2.1	e2.5	e2.0	e16
3	11	14	2.1	e.81	e1.1	e.76	e.86	e1.0	e1.7	e2.6	e1.8	e15
4	9.6	12	1.8	e.80	e1.1	e.74		e1.0	e1.6	e2.3	e1.8	7.1
5	9.0	12	1.9	e1.0	e1.0	e.80	e.80	e1.0	e4.2	e2.0	e6.0	5.6
6	8.6	11	1.8	e2.4	e1.0	e1.4	e.98	e.93	e5.8	e1.9	e5.4 e3.2	7.1 5.9
7	8.1	9.4	1.7	e1.0 e.83	e.96	e2.0 e.86	e.88 e1.0	e.91 e.84	e13 e5.6	e1.9 e2.1	e2.4	19
9	14	9.0	1.8	e. 81	e.89	e.74		e.94	e4.8	e1.9	e2.3	8.1
10	12	9.1	e1.5	e.82	e.90	e1.2	e3.0	e2.8	e3.7	e1.8	e2.1	14
11	9.4	8.2	e1.4	e1.3	e.89	e.72	e2.2	e9.8	e3.5	e2.5	e1.9	8.5
12	9.3	7.7	e1.3	e1.1	e.90	e.66		e4.5	e3.5	e1.9	e2.8	5.7
13	26	7.7	e1.2	e1.0	e.90	e.66	e1.3	e2.8	e3.3	e1.7	e5.2	5.1
14	11	7.2	e1.2	e.96	e.90	e. 64		e2.1	e3.0	e1.6	e2.7	4.9
15	9.1	7.2	e1.1	e.94	e.94	e. 64	e2.0	e1.9	e2.8	e1.5	e2.2	4.4
16	9.2	5.6	e1.1	e1.0	e.90	e.76		e2.3	e2.7	e1.5	e2.1	6.3
17	7.8	5.6	e1.0	e1.0	e.94	e.81		e2.1	e2.7	e4.2	e2.0	4.8
18	44	5.2	e1.0	e1.3	e.91	e.69		e6.4	e2.5	e3.5	e2.0 e2.1	6.9
19 20	91 32	e4.4	e.96	e1.0 e1.1	e1.0	e. 68		e3.6 e7.0	e2.4 e2.3	e2.6	e2.2	16
0.4		-4.0		-1.0	- 06		-1.0	e4.6	e2.3	e3.2	e2.5	4.9
21	18 17	e4.0 e3.8	e1.5 e.97	e1.0 e1.0	e.96	e. 64		e13	e2.2	e2.0	64.0	5.5
23	13	e3.5	e.95	e.98	e.88	e. 61		e10	e2.3	e1.7	e4.8	11
24	12	e3.3	e.91	e.94	e.88	e2.0	e1.3	e5.8	e2.1	e2.2	e10	5.6
25	18	e3.1	e.89	e1.0	e.88	e2.3	e1.2	e6.6	e2.1	e1.9	e9.4	6.6
26	12	e3.3	e.87	e1.0	e.87	e1.0	e1.1	e3.1	e2.1	e2.2	e7.0	4.9
27	11	e2.8	e.84	e.96	e.84	e2.5	e1.0	e2.6	e2.2	e3.4	e4.8	4.1
28	11	2.6	e.84	e.97	e.83	e15	e.96	e4.6	e2.1	e2.1	e4.0	3.9
29	10	2.5	e.84	e.97	e.80	e5.0	e.94	e4.3	e2.0	e1.6	e3.7	3.5
30 31	18 99	2.6	e.84 e.82	e.96 e.97		e2.5	e1.0	e6.0 e4.5	e1.9	e3.4	e3.6	24
-					52.00		2002					250 6
TOTAL	632.1	221.0	42.93	31.59	27.10	50.64		119.72	95.3 3.18	72.5	116.3 3.75	258.6 8.62
MEAN	20.4	7.37	1.38	2.4	.93	1.63		3.86	13	4.2	10	24
MAX	7.8	2.5	.82	.80	.80	. 61		. 84	1.6	1.5	1.8	3.5
AC-PT	1250	438	85	63	54	100		237	189	144	231	513
CFSM	6.45	2.33	.44	.32	.30	. 52		1.22	1.01	.74	1.19	2.73
IN.	7.44	2.60	.51	.37	.32	.60	.60	1.41	1.12	. 85	1.37	3.04
e E	stimated											
STATIS	TICS OF M	ONTHLY ME	AN DATA E	OR WATER Y	EARS 196	9 - 199	2, BY WATER	YEAR (WY)			
MBAN	19.9	10.6	3.78	2.73	2.31	2.50	3.63	9.13	6.98	4.47	5.34	11.6
MAX	33.7	16.7	7.31	6.83	5.37	6.38		12.3	9.73	9.85	9.88	15.7
(WY)	1991	1971	1971	1971	1971	1971		1991	1970	1969	1991	1990
MIN	11.9	6.51	1.35	.66	.93	1.01		3.86	3.18	2.03	3.34	8.62
(WY)	1971	1991	1991	1991	1992	1970	1970	1992	1992	1990	1970	1992
SUMMAR	Y STATIST	rics	FOR	1991 CALEN	DAR YEAR		FOR 1992 WA	TER YEAR		WATER Y	EARS 1969	- 1992
ANNUAL	TOTAL.			2551.94			1718.78					
ANNUAL		MPAN		6.99			4.70			6.3	-	1991
	ANNUAL M									4.7	0	1991
	T DAILY M			104	May 20		99	Oct 31		216	Oct	7 1990
	DAILY ME			.47	May 20 Jan 13		. 61	Mar 23		. 4	7 Jan	13 1991
		Y MINIMUM		.51	Jan 9		. 67	Mar 17		.5	1 Jan	9 1991
		EAK FLOW						Oct 19		5300		7 1990
		BAK STAGE		5060				Oct 19		21.3 4580		7 1990
	RUNOFF ((AC-FT)		2.21			3410 1.49			2.0		
	RUNOFF			30.04			20.23			27.2		
		REDS		15			11			14		
	CENT EXCE			3.1			2.1			3.7		
	CENT BXCE			.83			. 86			.9		

50010500 RIO GUAJATACA AT LARES, PR

WATER-QUALITY RECORDS

LOCATION.--Lat 18°18'01", long 66°52'24", at bridge on Highway 111 (km 32.9), 0.1 mi (0.2 km) upstream from Quebrada Anón, and 0.4 mi (0.6 km) northeast of Lares plaza.

DRAINAGE AREA. -- 3.16 mi2 (8.18 km2).

PERIOD OF RECORD. -- Water years 1958-71, 1974 to current year.

WATER-QUALITY DATA, WATER YEAR OCTOBER 1991 TO SEPTEMBER 1992

DATE	TIM	CHA IN CU F IB P	IS- RGB, ST. BIC BET ER COND	SPE- CIFIC CON- DUCT- ANCE (US/CM)	PH WATER WHOLE FIELD (STAND- ARD UNITS)	TEMPER ATURE WATER (DEG C	BI R IT	D- Y S	KYGEN, DIS- SOLVED (MG/L)	OXYGEN, DIS- SOLVED (PER- CENT SATUR- ATION)	OXYGEN DEMAND, CHEM- ICAL (HIGH LEVEL) (MG/L)	COLI- FORM, FECAL, 0.7 UM-MF (COLS./ 100 ML)	
OCT 1991 22	085	5	7.6	216	7.4	21.	.0 9	.0	7.6	87	<10	K11000	9300
DEC 17	132	0	0.98	241	7.9	21.	5 3	.3	7.5	86	<10	K90	5300
FEB 1992 20	151		1.1	247	7.9	23.		. 4	8.7	103	<10	490	
APR													
09	080		1.4	268	6.9	21.		. 4	8.1	99	<10	K13000	
02 AUG	101		1.9	235	7.8	24.		.50	8.0	94	<10	700	
27	093	5	5.9	252	6.9	25.	.5 4	.7	5.4	68	<10	630	4100
DATE	HARI NESS TOTA (MG/ AS CACO	O- NE NON L WH L TOT MG/	CARB	CALCIUM DIS- SOLVED (MG/L AS CA)	MAGNE- SIUM, DIS- SOLVED (MG/L AS MG)	SODIUM DIS- SOLVEI (MG/I AS NA	f, A SOR D TI L RAT	D- P- ON S	POTAS- SIUM, DIS- SOLVED (MG/L AS K)	ALKA- LINITY WAT WH TOT FET FIRLD MG/L AS CACO3	SULFIDE TOTAL (MG/L AS S)	SULFATE DIS- SOLVED (MG/L AS SO4)	DIS-
OCT 1991 22 DEC		78	3	23	5.1	9.5	5	0.5	2.5	77	<0.5	6.4	11
17							_	-		84			~-
FEB 1992 20							_	_		100			
APR 09	1	.00	2	32	6.0	12		0.5	3.0	99	<0.5	14	17
JUL 02							-	-		110			
AUG 27	1	.10	0	33	5.8	11		0.5	3.0	110		13	13
	DATE	FLUO- RIDE, DIS- SOLVED (MG/L AS F)	DI SO: (Ma	ICA, SUM S- CON LVED TUE G/L D S SO	STI- D NTS, SC IS- (T LVRD P	IDS, 7 DIS- A DLVED I	RESIDUR TOTAL AT 105 DEG. C, SUS- PENDED (MG/L)	NITRO GEN, NITRAT TOTAI (MG/I AS N)	, G. FR NIT. L. TO L. (M	EN, C RITE NO TAL TO G/L (M	SEN, (PAN) R+NO3 AMI OTAL TO GG/L (PAN)	GEN, MONIA OR STAL T MG/L (IITRO- GEN, GANIC OTAL MG/L .S N)
	1991 2	0.20	2	R	132	2.69	<1	2.29	g n	.010 2	2.30 (0.050	0.15
DEC	· · · · · 7 · · ·			-			1	1.67				0.020	
FBB	1992)						6	1.0/				0.020	
APR													
JUL	9	0.20			171	0.66	13	0.98				0.040	0.16
AUG	2						<1	1.79				0.020	0.28
27	7	<0.10	2	4	168	2.67	1	1.69	9 0	.010 1	1.70	0.040	

K = non-ideal count

50010500 RIO GUAJATACA AT LARES, PR--Continued

WATER-QUALITY DATA, WATER YEAR OCTOBER 1991 TO SEPTEMBER 1992

DATE	NITRO- GEN, AM- MONIA + ORGANIC TOTAL (MG/L AS N)	NITRO- GEN, TOTAL (MG/L AS N)	NITRO- GEN, TOTAL (MG/L AS NO3)	PHOS- PHORUS TOTAL (MG/L AS P)	ARSENIC TOTAL (UG/L AS AS)	BARIUM, TOTAL RECOV- ERABLE (UG/L AS BA)	BORON, TOTAL RECOV- ERABLE (UG/L AS B)	CADMIUM TOTAL RECOV- ERABLE (UG/L AS CD)	CHRO- MIUM, TOTAL RECOV- ERABLE (UG/L AS CR)	COPPER, TOTAL RECOV- ERABLE (UG/L AS CU)
ОСТ 1991										
22 DEC	0.20	2.5	11	0.070	<1	<100	30	<1	<1	<10
17 FEB 1992	<0.20			0.130						
20 APR	<0.20			0.120						
09	0.20	1.2	5.3	0.040	2	<100	30	<1	<1	<10
JUL 02	0.30	2.1	9.3	0.060						
AUG 27	<0.20			0.080						
DATE	IRON, TOTAL RECOV- ERABLE (UG/L AS FE)	LEAD, TOTAL RECOV- ERABLE (UG/L AS PB)	MANGA- NESE, TOTAL RECOV- ERABLE (UG/L AS MN)	MERCURY TOTAL RECOV- ERABLE (UG/L AS HG)	SELE- NIUM, TOTAL (UG/L AS SE)	SILVER, TOTAL RECOV- ERABLE (UG/L AS AG)	ZINC, TOTAL RECOV- ERABLE (UG/L AS ZN)	CYANIDE TOTAL (MG/L AS CN)	PHENOLS TOTAL (UG/L)	METHY- LENE BLUE ACTIVE SUB- STANCE (MG/L)
ОСТ 1991	TOTAL RECOV- ERABLE (UG/L AS FE)	TOTAL RECOV- ERABLE (UG/L AS PB)	NESE, TOTAL RECOV- ERABLE (UG/L AS MN)	TOTAL RECOV- ERABLE (UG/L AS HG)	NIUM, TOTAL (UG/L AS SE)	TOTAL RECOV- ERABLE (UG/L AS AG)	TOTAL RECOV- ERABLE (UG/L AS ZN)	TOTAL (MG/L AS CN)	TOTAL (UG/L)	LENE BLUE ACTIVE SUB- STANCE (MG/L)
OCT 1991 22 DEC	TOTAL RECOV- ERABLE (UG/L	TOTAL RECOV- BRABLE (UG/L	NESE, TOTAL RECOV- ERABLE (UG/L	TOTAL RECOV- ERABLE (UG/L	NIUM, TOTAL (UG/L	TOTAL RECOV- ERABLE (UG/L	TOTAL RECOV- BRABLE (UG/L	TOTAL (MG/L	TOTAL	LENE BLUE ACTIVE SUB- STANCE
OCT 1991 22 DEC 17 FEB 1992	TOTAL RECOV- ERABLE (UG/L AS FE)	TOTAL RECOV- ERABLE (UG/L AS PB)	NESE, TOTAL RECOV- ERABLE (UG/L AS MN)	TOTAL RECOV- BRABLE (UG/L AS HG) <0.10	NIUM, TOTAL (UG/L AS SE) <1	TOTAL RECOV- RRABLE (UG/L AS AG) <1	TOTAL RECOV- ERABLE (UG/L AS ZN) <10	TOTAL (MG/L AS CN) <0.010	TOTAL (UG/L)	LENE BLUE ACTIVE SUB- STANCE (MG/L) 0.03
OCT 1991 22 DEC 17 FEB 1992 20	TOTAL RECOV- ERABLE (UG/L AS FE)	TOTAL RECOV- ERABLE (UG/L AS PB)	NESE, TOTAL RECOV- ERABLE (UG/L AS MN)	TOTAL RECOV- ERABLE (UG/L AS HG)	NIUM, TOTAL (UG/L AS SE)	TOTAL RECOV- ERABLE (UG/L AS AG)	TOTAL RECOV- ERABLE (UG/L AS ZN)	TOTAL (MG/L AS CN)	TOTAL (UG/L)	LENE BLUE ACTIVE SUB- STANCE (MG/L)
OCT 1991 22 DRC 17 FEB 1992 20 APR 09	TOTAL RECOV- ERABLE (UG/L AS FE)	TOTAL RECOV- ERABLE (UG/L AS PB)	NESE, TOTAL RECOV- ERABLE (UG/L AS MN)	TOTAL RECOV- BRABLE (UG/L AS HG) <0.10	NIUM, TOTAL (UG/L AS SE) <1	TOTAL RECOV- RRABLE (UG/L AS AG) <1	TOTAL RECOV- ERABLE (UG/L AS ZN) <10	TOTAL (MG/L AS CN) <0.010	TOTAL (UG/L)	LENE BLUE ACTIVE SUB- STANCE (MG/L) 0.03
OCT 1991 22 DEC 17 FEB 1992 20	TOTAL RECOV- RRABLR (UG/L AS FR) 370	TOTAL RECOV- ERABLE (UG/L AS PB)	NESE, TOTAL RECOV- ERABLE (UG/L AS MN)	TOTAL RECOV- ERABLE (UG/L AS HG)	NIUM, TOTAL (UG/L AS SE)	TOTAL RECOV- RRABLE (UG/L AS AG) <1	TOTAL RECOV- ERABLE (UG/L AS ZN)	TOTAL (MG/L AS CN) <0.010	TOTAL (UG/L) 1	LENE BLUE ACTIVE SUB- STANCE (MG/L) 0.03

50011000 CANAL PRINCIPAL DE DIVERSIONES AT LAGO DE GUAJATACA, PR

WATER-QUALITY RECORDS

LOCATION.--Lat 18°24'02", long 66°55'27", off Highway 476 at Lago Guajataca outlet, 3.0 mi (4.8 km) southwest of Segunda Unidad Baldorioty de Castro, and 5.3 mi (8.5 km) south of Quebradillas Plaza.

DRAINAGE AREA. -- Indeterminate.

PERIOD OF RECORD. -- Water years 1958-64, 1974 to current year.

WATER-QUALITY DATA, WATER YEAR OCTOBER 1991 TO SEPTEMBER 1992

DATE	TIME	DIS- CHARGE, INST. CUBIC FEST PER SECOND	SPE- CIFIC COM- DUCT- ANCE (US/CM)	PH WATER WHOLE FIELD (STAND- ARD UNITS)	TEMPER- ATURE WATER (DEG C)	TUR- BID- ITY (NTU)	OXYGEN, DIS- SOLVED (MG/L)	OXYGEN, DIS- SOLVED (PER- CENT SATUR- ATION)	OXYGEN DEMAND, CHEM- ICAL (HIGH LEVEL) (MG/L)	COLI- FORM, FECAL, 0.7 UM-MF (COLS./ 100 ML)	STREP- TOCOCCI FECAL, KF AGAR (COLS. PER 100 ML)
OCT 1991 22	1345	B105	312	7.3	25.5	3.9	2.3	12	10	20	K13
DEC 17	1545	B100	300	7.4	25.0	1.2	2.9	36	11	K 5	K1
PEB 1992 20	1000	B70	318	7.6	24.5	1.2	2.7	32	<10	K 2	K11
APR 10	1045	R50	282	6.8	25.5	1.2	5.5	67	17	29	20
JUL 07	1050	R50	310	6.9	25.0	1.5	1.7	28	12	10	10
AUG 27	1230	R75	318	6.7	27.5	0.2	2.6	39	<10	330	2500
DATE	HARD- NESS TOTAL (MG/L AS CACO3)	HARD- NESS NONCARB WH WAT TOT FLD MG/L AS CACO3	CALCIUM DIS- SOLVED (MG/L AS CA)	MAGNE- SIUM, DIS- SOLVED (MG/L AS MG)	SODIUM, DIS- SOLVED (MG/L AS NA)	SODIUM AD- SORP- TION RATIO	POTAS- SIUM, DIS- SOLVED (MG/L AS K)	ALKA- LINITY WAT WH TOT FET FIELD MG/L AS CACO3	SULFIDE TOTAL (MG/L AS S)	SULFATE DIS- SOLVED (MG/L AS SO4)	CHLO- RIDE, DIS- SOLVED (MG/L AS CL)
OCT 1991	150	4	54	3.7	7.4	0.3	2.6	140	<0.5	13	12
17								130			
FEB 1992 20								130			
APR 10 JUL	130	5	46	3.6	5.9	0.2	2.1	110	<0.5	7.6	15
07 AUG								150			
27	150	10	53	3.4	5.9	0.2	2.3	160		8.0	9.5
DA OCT 19	RI E SC ATE (M AS	DB, DI DIS- SC DLVED (N	LICA, SUM IS- CON DLVED TUR IG/L D IS SO	STI- E NTS, SC IS- (T LVED F	IDS, TOT. DIS- AT : DLVED DEG ONS SU DER PEN	105 G . C, NIT S- TO OBD (M	EN, G RATE NIT TAL TO G/L (M	EN, G RITE NO2 TAL TO G/L (M	EN, G +NO3 AMM TAL TO G/L (M	EN, G ONIA ORG TAL TO G/L (M	TRO- EN, ANIC TAL G/L N)
22 DRC		0.20	7.5	184		•					0.32
17 FBB 19	92										0.27
20						<1					0.38
10		0.20	4.6	151		6					0.24
07						<1 -				. 130	0.17
27	·	:0.10	5.6	176		2	<0	.010 <0	.050 0	.320	0.28

B = estimate
K = non-ideal count

RIO GUAJATACA BASIN

50011000 CANAL PRINCIPAL DE DIVERSIONES AT LAGO DE GUAJATACA, PR--Continued

WATER-QUALITY DATA, WATER YEAR OCTOBER 1991 TO SEPTEMBER 1992

DATE	NITRO- GEN, AM- MONIA + ORGANIC TOTAL (MG/L AS N)	NITRO- GEN, TOTAL (MG/L AS N)	NITRO- GEN, TOTAL (MG/L AS NO3)	PHOS- PHORUS TOTAL (MG/L AS P)	ARSENIC TOTAL (UG/L AS AS)	BARIUM, TOTAL RECOV- ERABLE (UG/L AS BA)	BORON, TOTAL RECOV- ERABLE (UG/L AS B)	CADMIUM TOTAL RECOV- ERABLE (UG/L AS CD)	CHRO- MIUM, TOTAL RECOV- ERABLE (UG/L AS CR)	COPPER, TOTAL RECOV- ERABLE (UG/L AS CU)
ОСТ 1991										
22 DEC	0.50			0.020	3	<100	30	<1	<1	<10
17	0.30	0.38	1.7	<0.010						
FEB 1992 20	0.40			0.070						
APR 10 JUL	0.40			<0.010	1	<100	30	<1	<1	<10
07	0.30			<0.010						
AUG 27	0.60			0.020						
DATE	IRON, TOTAL RECOV- ERABLE (UG/L AS FE)	LEAD, TOTAL RECOV- ERABLE (UG/L AS PB)	MANGA- NESE, TOTAL RECOV- ERABLE (UG/L AS MN)	MERCURY TOTAL RECOV- ERABLE (UG/L AS HG)	SELE- NIUM, TOTAL (UG/L AS SE)	SILVER, TOTAL RECOV- ERABLE (UG/L AS AG)	ZINC, TOTAL RECOV- ERABLE (UG/L AS ZN)	CYANIDE TOTAL (MG/L AS CN)	PHENOLS TOTAL (UG/L)	METHY- LENE BLUE ACTIVE SUB- STANCE (MG/L)
ОСТ 1991	TOTAL RECOV- ERABLE (UG/L AS FE)	TOTAL RECOV- ERABLE (UG/L AS PB)	NESE, TOTAL RECOV- ERABLE (UG/L AS MN)	TOTAL RECOV- ERABLE (UG/L AS HG)	NIUM, TOTAL (UG/L AS SE)	TOTAL RECOV- ERABLE (UG/L AS AG)	TOTAL RECOV- ERABLE (UG/L AS ZN)	TOTAL (MG/L AS CN)	TOTAL (UG/L)	LENE BLUE ACTIVE SUB- STANCE (MG/L)
	TOTAL RECOV- ERABLE (UG/L	TOTAL RECOV- ERABLE (UG/L	NESE, TOTAL RECOV- ERABLE (UG/L	TOTAL RECOV- ERABLE (UG/L	NIUM, TOTAL (UG/L	TOTAL RECOV- ERABLE (UG/L	TOTAL RECOV- ERABLE (UG/L	TOTAL (MG/L	TOTAL	LENE BLUE ACTIVE SUB- STANCE
OCT 1991 22 DEC 17	TOTAL RECOV- ERABLE (UG/L AS FE)	TOTAL RECOV- ERABLE (UG/L AS PB)	NESE, TOTAL RECOV- ERABLE (UG/L AS MN)	TOTAL RECOV- ERABLE (UG/L AS HG)	NIUM, TOTAL (UG/L AS SE)	TOTAL RECOV- ERABLE (UG/L AS AG)	TOTAL RECOV- ERABLE (UG/L AS ZN)	TOTAL (MG/L AS CN)	TOTAL (UG/L)	LENE BLUE ACTIVE SUB- STANCE (MG/L)
OCT 1991 22 DEC 17 FEB 1992 20	TOTAL RECOV- ERABLE (UG/L AS FE)	TOTAL RECOV- ERABLE (UG/L AS PB)	NESE, TOTAL RECOV- ERABLE (UG/L AS MN)	TOTAL RECOV- ERABLE (UG/L AS HG)	NIUM, TOTAL (UG/L AS SE)	TOTAL RECOV- ERABLE (UG/L AS AG)	TOTAL RECOV- ERABLE (UG/L AS ZN)	TOTAL (MG/L AS CN)	TOTAL (UG/L)	LENE BLUE ACTIVE SUB- STANCE (MG/L)
OCT 1991 22 DBC 17 FEB 1992 20 APR 10	TOTAL RECOV- BRABLE (UG/L AS FE)	TOTAL RECOV- ERABLE (UG/L AS PB)	NESE, TOTAL RECOV- ERABLE (UG/L AS MN)	TOTAL RECOV- ERABLE (UG/L AS HG) <0.10	NIUM, TOTAL (UG/L AS SE)	TOTAL RECOV- ERABLE (UG/L AS AG) <1	TOTAL RECOV- ERABLE (UG/L AS ZN)	TOTAL (MG/L AS CN) <0.010	TOTAL (UG/L)	LENE BLUE ACTIVE SUB- STANCE (MG/L)
OCT 1991 22 DEC 17 FEB 1992 20	TOTAL RECOV- BRABLE (UG/L AS FE)	TOTAL RECOV- BRABLE (UG/L AS PB)	NESE, TOTAL RECOV- ERABLE (UG/L AS MN)	TOTAL RECOV- ERABLE (UG/L AS HG) <0.10	NIUM, TOTAL (UG/L AS SE) <1	TOTAL RECOV- BRABLE (UG/L AS AG) <1	TOTAL RECOV- ERABLE (UG/L AS ZN)	TOTAL (MG/L AS CN) <0.010	TOTAL (UG/L) 2	LENE BLUE ACTIVE SUB- STANCE (MG/L)

50011400 RIO GUAJATACA ABOVE MOUTH NEAR QUEBRADILLAS, PR

WATER-QUALITY RECORDS

LOCATION.--Lat 18°28'31", long 66°57'46", Hydrologic Unit 21010002, on left bank at ford 1.7 mi (2.7 km) upstream from bridge on highway 2, 1.6 mi (2.6 km) west of Quebradillas plaza, 2.1 mi (3.4 km) upstream from Atlantic Ocean, and 6.6 mi (10.6 km) downstream from Lago Guajataca.

DRAINAGE AREA. -- Indeterminate

PERIOD OF RECORD. -- Water years 1969 to current year.

WATER-QUALITY DATA, WATER YEAR OCTOBER 1991 TO SEPTEMBER 1992

		WATE	SR-QUALITY	DATA, WA	TER YEAR	OCTOBER :	1991 TO SE	PTEMBER 1	.992		
DATE	TIME	DIS- CHARGE, INST. CUBIC FEST PER SECOND	SPE- CIFIC CON- DUCT- ANCE (US/CM)	PH WATER WHOLE FIELD (STAND- ARD UNITS)	TEMPER- ATURE WATER (DEG C)	TUR- BID- ITY (NTU)	OXYGEN, DIS- SOLVED (MG/L)	OXYGEN, DIS- SOLVED (PER- CENT SATUR- ATION)	OXYGEN DEMAND, CHEM- ICAL (HIGH LEVEL) (MG/L)	COLI- FORM, FECAL, 0.7 UM-MF (COLS./ 100 ML)	STREP- TOCOCCI FECAL, KF AGAR (COLS. PER 100 ML)
OCT 1991											
22	1630	226	318	8.2	26.0	15	4.1	47	20	K840	880
JAN 1992 10	1230	6.6	556	7.6	24.5	0.70	5.9	68	<10	40	110
FEB											
20 APR	0800	9.3	612	7.5	24.0	0.50	4.5	49	<10	31	54
10 JUL	0905	14	399	6.9	24.5	1.4	5.4	63	<10	2100	3200
20	1030	33	395	7.4	25.0	2.1	6.3	72	13	410	410
SEP 02	1200	250	307	7.9	27.0	3.5	6.2	70	<10	K270	670
DATE	HARD- NESS TOTAL (MG/L AS CACO3)	HARD- NESS NONCARB WH WAT TOT FLD MG/L AS CACO3	CALCIUM DIS- SOLVED (MG/L AS CA)	MAGNE- SIUM, DIS- SOLVED (MG/L AS MG)	SODIUM, DIS- SOLVED (MG/L AS NA)	SODIUM AD- SORP- TION RATIO	POTAS- SIUM, DIS- SOLVED (MG/L AS K)	ALKA- LINITY WAT WH TOT FET FIRLD MG/L AS CACO3	SULFIDE TOTAL (MG/L AS S)	SULFATE DIS- SOLVED (MG/L AS SO4)	CHLO- RIDE, DIS- SOLVED (MG/L AS CL)
OCT 1991 22	160	8	57	3.5	6.1	0.2	1.9	150	<0.5	13	11
JAN 1992 10	**							210			
FBB											
20 APR								230			
10 JUL	180	19	64	5.9	12	0.4	1.7	160	<0.5	8.5	26
20								180			
SEP 02	150	8	56	3.5	5.4	0.2	1.7	150		9.2	11
גם	RI I SC ATE (N	IDE, DI DIS- SC DLVED (N IG/L A	LICA, SUM IS- CON OLVED TUE IG/L D IS SO	STI~ D NTS, SC IS~ (T LVED P	IDS, TOT DIS- AT DLVED DEC PONS SU PER PEN	105 (3. C, NI 18- T(NDED ()	SEN, G TRATE NIT STAL TO 4G/L (M	SEN, G PRITE NO2 STAL TO GG/L (M	BEN, G +NO3 AMM TAL TO G/L (M	EN, G ONIA ORG TAL TO G/L (M	TRO- SEN, ANIC TAL IG/L S N)
OCT 19		0.20	7.4	190 11	.6	<1 ().190 0	0.020 0	.210 0	.070	0.83
JAN 19						7 :	1.98 0	.020 2	.00 0	.030	
FEB 20.						4 2	2.68 0	.020 2	.70 0	.020	
APR 10.		0.20	5.9	220	8.38					. 040	
JUL 20.											۸ 30
SEP						28				.020	0.38
02.	••	0.10	6.0	181 12	2	<1 (0.280	0.040 0	.320 0	.020	0.18

K = non-ideal count

RIO GUAJATACA BASIN

50011400 RIO GUAJATACA ABOVE MOUTH NEAR QUEBRADILLAS, PR--Continued

WATER-QUALITY DATA, WATER YEAR OCTOBER 1991 TO SEPTEMBER 1992

DATE	NITRO- GEN, AM- MONIA + ORGANIC TOTAL (MG/L AS N)	NITRO- GEN, TOTAL (MG/L AS N)	NITRO- GEN, TOTAL (MG/L AS NO3)	PHOS- PHORUS TOTAL (MG/L AS P)	ARSENIC TOTAL (UG/L AS AS)	BARIUM, TOTAL RECOV- ERABLE (UG/L AS BA)	BORON, TOTAL RECOV- BRABLE (UG/L AS B)	CADMIUM TOTAL RECOV- ERABLE (UG/L AS CD)	CHRO- MIUM, TOTAL RECOV- ERABLE (UG/L AS CR)	COPPER, TOTAL RECOV- ERABLE (UG/L AS CU)
OCT 1991										
22 JAN 1992	0.90	1.1	4.9	0.040	3	<100	30	<1	1	10
10	<0.20			<0.010						
20	<0.20			0.020						
APR 10	<0.20			<0.010	<1	<100	30	<1	<1	<10
JUL 20 Sep	0.40			0.020						
02	0.20	0.52	2.3	0.020						
DATE	IRON, TOTAL RECOV- ERABLE (UG/L AS FE)	LEAD, TOTAL RECOV- ERABLE (UG/L AS PB)	MANGA- NESE, TOTAL RECOV- ERABLE (UG/L AS MN)	MERCURY TOTAL RECOV- ERABLE (UG/L AS HG)	SELE- NIUM, TOTAL (UG/L AS SE)	SILVER, TOTAL RECOV- ERABLE (UG/L AS AG)	ZINC, TOTAL RECOV- ERABLE (UG/L AS ZN)	CYANIDE TOTAL (MG/L AS CN)	PHENOLS TOTAL (UG/L)	METHY- LENE BLUE ACTIVE SUB- STANCE (MG/L)
OCT 1991 22	TOTAL RECOV- ERABLE (UG/L	TOTAL RECOV- BRABLE (UG/L	NESE, TOTAL RECOV- ERABLE (UG/L	TOTAL RECOV- BRABLE (UG/L	NIUM, TOTAL (UG/L	TOTAL RECOV- BRABLE (UG/L	TOTAL RECOV- BRABLE (UG/L	TOTAL (MG/L	TOTAL	LENE BLUE ACTIVE SUB- STANCE
OCT 1991 22 JAN 1992 10	TOTAL RECOV- ERABLE (UG/L AS FE)	TOTAL RECOV- ERABLE (UG/L AS PB)	NESE, TOTAL RECOV- ERABLE (UG/L AS MN)	TOTAL RECOV- ERABLE (UG/L AS HG)	NIUM, TOTAL (UG/L AS SE)	TOTAL RECOV- ERABLE (UG/L AS AG)	TOTAL RECOV- ERABLE (UG/L AS ZN)	TOTAL (MG/L AS CN)	TOTAL (UG/L)	LENE BLUE ACTIVE SUB- STANCE (MG/L)
OCT 1991 22 JAN 1992 10 FBB 20	TOTAL RECOV- ERABLE (UG/L AS FE)	TOTAL RECOV- ERABLE (UG/L AS PB)	NESE, TOTAL RECOV- ERABLE (UG/L AS MN)	TOTAL RECOV- BRABLE (UG/L AS HG)	NIUM, TOTAL (UG/L AS SE)	TOTAL RECOV- ERABLE (UG/L AS AG)	TOTAL RECOV- ERABLE (UG/L AS ZN)	TOTAL (MG/L AS CN)	TOTAL (UG/L)	LENE BLUE ACTIVE SUB- STANCE (MG/L)
OCT 1991 22 JAN 1992 10 FEB 20 APR 10	TOTAL RECOV- ERABLE (UG/L AS FE)	TOTAL RECOV- ERABLE (UG/L AS PB)	NESE, TOTAL RECOV- ERABLE (UG/L AS MN)	TOTAL RECOV- ERABLE (UG/L AS HG) <0.10	NIUM, TOTAL (UG/L AS SE) <1	TOTAL RECOV- ERABLE (UG/L AS AG) <1	TOTAL RECOV- ERABLE (UG/L AS ZN)	TOTAL (MG/L AS CN) <0.010	TOTAL (UG/L) <1	LENE BLUE ACTIVE SUB- STANCE (MG/L)
OCT 1991 22 JAN 1992 10 FBB 20	TOTAL RECOV- BRABLE (UG/L AS FE) 450	TOTAL RECOV- BRABLE (UG/L AS PB)	NESE, TOTAL RECOV- BRABLE (UG/L AS MN)	TOTAL RECOV- BRABLE (UG/L AS HG) <0.10	NIUM, TOTAL (UG/L AS SE) <1	TOTAL RECOV- BRABLE (UG/L AS AG) <1	TOTAL RECOV- BRABLE (UG/L AS ZN)	TOTAL (MG/L AS CN) <0.010	TOTAL (UG/L) <1 	LENE BLUE ACTIVE SUB- STANCE (MG/L) 0.03




Figure 14:-Río Camuy basin.

54 RIO CAMUY BASIN

50014600 RIO CAMUY AT TRES PUEBLOS SINKHOLE, PR

LOCATION.--Lat 18°20'42", long 66°49'29", Hydrologic Unit 21010002, at Parque de las Cavernas del Río Camuy, 1.8 mi (2.9 km) southeast from Escuela Segunda Unidad de Santiago Palmer, 4.7 mi (7.6 km) west from Observatorio de Arecibo and 4.8 mi (7.7 km) northeast from Plaza de Lares.

DRAINAGE AREA. -- Indeterminate.

WATER-DISCHARGE RECORDS

PERIOD OF RECORD. -- June 1990 to current year.

GAGE. -- Water-stage recorder and crest-stage gage. Datum of gage is 612.21 ft (186.602 m), above mean sea level.

REMARKS.--Records fair except those for estimated daily discharges, which are poor. Gage-height and precipitation satellite telemetry at station.

satel	Tite tel	emetry at	station.									
	D	ISCHARGE,	CUBIC FRI	T PER SE		R YEAR O	CTOBER 199	1 TO SEPT	EMBER 19	992		
DAY	OCT	NOV	DEC	JAN	FEB	MAR	APR	MAY	JUN	JUL	AUG	SEP
1	56	160	38	28	21	14	41	33	114	37	58	73
2	55	95	37	27	20	15	36	38	88	37	46	57
3	49	77	37	27	21	15	33	34	76	37	38	44
5	47	71 66	36 36	27 27	21 20	15	31	32	69 65	39 38	36 38	42
						15	30	31				
6	45	62 60	35 35	67 35	20 20	15 34	30 33	31 30	115 147	36 35	111 96	41 58
8	141	59	34	30	19	32	33	30	215	36	65	64
9	115	57	34	29	18	21	49	29	130	37	53	53
10	77	55	33	28	18	20	50	31	90	35	50	51
11	59	54	33	33	18	28	47	82	79	41	46	49
12	54	e53	32	39	18	19	38	143	70	38	44	44
13	70	e52	32	30	18	18	38	79	64	35	74	41
14 15	70 54	e50 50	e32 e31	28 26	17 17	17 17	34 32	58 47	59 57	33 33	63 46	40
16 17	51 47	50 49	30 30	26 25	17 17	17	59	49	55 52	32 31	42	41
18	86	48	30	24	16	19 20	71 56	49 58	51	31	41	40
19	116	47	30	24	16	18	85	147	49	32	39	39
20	166	46	33	24	16	18	62	104	47	49	46	70
21	161	45	40	23	16	18	46	128	46	44	46	47
22	117	44	32	23	16	17	41	109	45	41	44	42
23	89	43	31	23	16	17	39	176	44	34	45	57
24 25	79 95	43	30 29	23 23	16 16	17 64	37 36	166 129	43	36 42	69 125	59 49
26 27	89 71	41	29 29	23 22	15 15	62 30	35 34	114 88	41	34 52	103 56	45
28	79	40	29	22	15	72	33	86	40	61	46	39
29	76	39	28	21	14	233	32	123	39	38	44	38
30	74	39	28	21		101	32	114	38	35	41	64
31	274		28	21		49		134		70	39	
TOTAL	2652	1678	1001	849	507	1067	1253	2502	2110	1209	1730	1451
MEAN	85.5 274	55.9 160	32.3	27.4 67	17.5 21	233	41.8 85	80.7	70.3 215	39.0 70	55.8 125	48.4
MIN	44	39	28	21	14	14	30	176 29	38	31	36	38
AC-FT	5260	3330	1990	1680	1010	2120	2490	4960	4190	2400	3430	2880
e Re	timated											
STATIST	TICS OF M	ONTHLY MR	AN DATA FO	R WATER	YEARS 1990	- 1992.	BY WATER	YRAR (WY)				
										24.0	FO 0	
MRAN	98.8 112	53.3 55.9	31.1	24.5	27.0	26.5	43.3	77.5 80.7	47.1	34.2 43.1	50.2 66.0	61.3 70.9
(WY)	1991	1992	1992	1992	1991	1992	1991	1992	1992	1991	1991	1990
MIN	85.5	50.7	29.8	21.6	17.5	18.5	41.8	74.2	32.1	20.7	28.8	48.4
(WY)	1992	1991	1991	1991	1992	1991	1992	1991	1991	1990	1990	1992
SUMMARY	STATIST	ICS	FOR :	1991 CALE	NDAR YEAR	P	OR 1992 WA	TER YEAR		WATER YE	ARS 1990	- 1992
ANNUAL	TOTAL			17258			18009					
	MEAN ANNUAL ANNUAL M			47.3			49.2			49.1 49.2 48.9		1992 1991
	DAILY M			274	Oct 31		274	Oct 31		274		31 1991
	DAILY MR			15	Mar 16		14	Feb 29		14		29 1992
		Y MINIMUM		16	Mar 13		15	Feb 26		15		26 1992
		BAK FLOW BAK STAGE					1030	Oct 31		1030		31 1991 31 1991
	ANEOUS L						14	Feb 28		14		28 1992
	ENT BXCE			88			88	7735.75		89	13/37/3	12 17 17 17
	ENT EXCE			36			40			37		
90 PERC	CENT EXCE	RDS		20			18			19		

50014800 RIO CAMUY NEAR BAYANEY, PR

LOCATION.--Lat 18°23'48", long 66°49'04", Hydrologic Unit 21010002, on left bank at Highway 488, 1.4 mi (2.2 km) southeast of school at Santiago, 0.9 mi (1.4 km) northwest from Rscuela Manuel A. Rivera at Bayaney and 9.1 mi (14.6 km) upstream from Atlantic Ocean.

DRAINAGE AREA. -- Indeterminate.

WATER-DISCHARGE RECORDS

PERIOD OF RECORD. -- May 1984 to current year.

GAGR.--Water-stage recorder. Rlevation of gage is 341 ft (104 m), from topographic map.

REMARKS.--Records fair except those for estimated daily discharges, which are poor. Gage-height and precipitation satellite telemetry at station.

		DISCHAR	GE, CUBIC	FEET PE		ATBR YE. MEAN VA	AR OCTOBER	1991 TO	srpte m be	R 1992		
DAY	ост	NOV	DEC	JAN	FEB	MAR	APR	МУЛ	JUN	JUL	λŪG	SRP
1	92	458	71	39	33	26	65	36	261	e 66	112	126
2	96	208	70	39	33	25	47	52	193	e67	80	111
3	83	160	68	39	36	25	40	42	155	e86	68	80
4	80	146	68	39	36	25	35	36	133	e89	63	74
5	77	134	65	39	35	25	35	34	132	e79	61	71
6	73	126	64	124	34	25	33	35	217	e70	202	70
7 8	71 314	149 133	63 61	71 48	33 30	52 86	40 38	32 31	306 e520	e66 e66	187 110	98 158
9	303	113	61	45	29	35	71	30	e295	73	82	119
10	195	107	60	44	28	30	85	31	e188	66	77	93
11	122	104	58	46	28	48	104	100	e166	65	71	93
12	98	99	56	73	28	30	75	304	e131	85	64	81
13	124	96	55	54	28	27	54	163	e120	66	95	75
14	129	93	55	45	28	27	45	99 74	e115	59 56	173 90	73 72
15	92	90	55	41	28	26	40		e107			
16	84	89	53	39	29	26	77	68	e96	54	74	77
17 18	80 157	87 84	53	38 37	28	31	133	79 78	e93	53 139	72 71	77 75
19	157 235	81	52 51	36	28 28	33 28	102 215	319	e91 e84	101	69	75 79
20	395	78	55	36	29	27	110	224	e83	92	71	191
21	356	77	77	36	29	26	75	329	e80	123	73	104
22	234	75	54	35	28	26	59	258	e78	109	81	86
23	163	75	46	35	26	26	49	549	e76	70	127	153
24	137	77	45	35	26	25	45	465	e77	60 77	158	145
25	170	77	43	34	26	97	43	311	e73	77	254	109
26	173	77	42	35	26	134	40	336	e72	64	229	102
27 28	128	77	41	35	26	49	38	210 179	e71	75 116	121 91	95 90
29	152 150	76 75	40 40	34 34	26 26	140 541	37 35	257	e73 e71	63	82	81
30	141	73	40	33		239	34	253	e68	55	74	118
31	620		39	34		87		305		117	71	
TOTAL	5324	3394	1701	1352	848	2047	1899	5319	4225	2427	3253	2976
MEAN	172	113	54.9	43.6	29.2	66.0	63.3	172	141	78.3	105	99.2
MAX	620	458	77	124	36	541	215	549	520	139	254	191
MIN	71	73	39	33	26	25	33	30	68	53	61	70
e Ra	stimated											
STATIST	TICS OF MC	DMTHLY MEY	N DATA F	OR WATER	YEARS 1984	- 1992,	BY WATER Y	TEAR (WY)				
MBAN	220	127	67.4	48.5	46.7	48.2	106	196	109	82.5	96.4	151
MAX	427	244	97.4	80.9	78.3	66.0	202	624	141	109	135	273
(WY)	1986	1986	1988	1988	1987	1992	1986	1986	1992	1989	1989	1984
MIN	81.6	74.9	49.7	33.1	29.2	35.7	61.4	43.2	79.9	58.4	54.2	99.2
(WY)	1988	1989	1989	1991	1992	1991	1990	1989	1989	1984	1987	1992
SUMMARY	STATIST	CS	FOR :	1991 CALE	NDAR YEAR	F	OR 1992 WAT	TER YEAR		WATER YE	ARS 1984	- 1992
ANNUAL				35824			34765					
ANNUAL				98.1			95.0			108		
	r annual i									179		1986
	ANNUAL M			620	Ont 31		620	Oct 31		89.3 3820	Oat	1989 7 1985
	DAILY ME DAILY ME			26	Oct 31 Feb 2		25	Mar 2		25		27 1989
	SEVEN-DAY			27	Jan 28		25	Feb 29		25		29 1992
	CANBOUS PI						2500	Oct 31		6450		7 1985
Instant	TANEOUS PI	RAK STAGE					12.61	Oct 31		17.66	Oct	7 1985
	TANBOUS LA						25	Mar 2		25	Apr	26 1989
	CENT BXCBI			197			189			210		
	CENT EXCE			74			73 29			70 35		
JU PERC	CENT EXCE	202		31			29			35		

RIO CAMUY BASIN

50015700 RIO CAMUY NEAR HATILLO, PR

LOCATION.--Lat 18°27'44", long 66°49'56", Hydrologic Unit 21010002, 1.8 mi (2.9 km) southwest of Hatillo plaxa, and 1.8 mi (2.9 km) southeast of Camuy plaxa, 1.2 mi (1.9 km) south of Planta de Purificación, and 3.3 mi (5.5 km) upstream from Atlantic Ocean.

DRAINAGE AREA. -- Indeterminate.

WATER-DISCHARGE RECORDS

PERIOD OF RECORD. -- June 1984 to current year.

GAGE .-- Water-stage recorder. Elevation of gage is 13 ft (4 m), from topographic map.

REMARKS.--Records fair except those for estimated daily discharges, which are poor. Gage-height and precipitation satellite telemetry at station.

		DI SCHARGE	, cubic	FEET PER		ATER YI MEAN V	BAR OCTOBER ALUES	1991 TO	September	1992		
DAY	OCT	NOV	DEC	JAN	Feb	MAR	APR	MAY	JUN	JUL	AUG	SEP
1	103	1220	59	44	37	31	77	41	569	e 70	180	124
2	119	284	58	44	37	31	57	60	390	e71	87	181
3 4	96 89	176 151	57 57	42 42	38 41	31 31	48 43	48 41	306 266	e91 e94	68 63	88 82
5	86	135	56	43	38	31	40	38	371	e86	64	76
6	81	124	55	147	37	31	38	38	274	e76	133	75
7	78	147	54	80	37	35	45	37	578	e70	390	91
8 9	302 655	168 113	54 53	52 47	36 35	108	44 77	35 34	795 645	e70 e78	126 79	223 177
10	391	105	53 52	46	34	41 36	89	34	280	e71	73	77
	331	103		40	34	30	0,	34	200	0,1	,,,	• • •
11	207	102	51	45	34	49	127	59	251	e 69	66	105
12	155	97	50	75	34	36	111	454	173	e91	62	76
13 14	148 188	92 88	49	59	34	33	62	310	144	e70	58 290	67 65
15	113	85	51 50	47 43	34 34	33 33	49 43	112 77	130 e110	e64 e 60	128	64
	113	03	30	4.5	3.	33	•	• • •	4110	400	120	•
16	99	85	49	42	33	32	42	73	e100	e58	79	76
17	92	83	48	41	33	33	171	95	e99	e56	73	71
18 19	161 270	81 78	48	40	33	40	143	71 354	e97 e91	e150 e110	71	67 64
20	579	75 75	47 50	40 40	33 32	36 34	162 153	508	e89	e110	69 75	326
••	3,3	,,,	50	•0	32	34	155	300	907	970	, ,	3.0
21	615	74	80	39	32	34	78	464	e 86	e1 30	76	133
22	416	72	56	39	32	33	64	568	e83	e120	82	84
23	305	71	49	39	32	32	53	1250	e82	e74	138	164
24 25	196 241	69 68	47 46	39 38	32 32	32 50	49 46	1090 636	e81 e78	e62 e82	365 340	223 126
45	241	00	40	30	32	50	40	636	470	604	340	120
26	267	66	45	39	32	236	43	838	e 76	e66	531	112
27	183	64	45	38	32	40	42	565	e76	e58	181	159
28	183	64	45	38	31	60	40	302	e78	176	127	157
29 30	262	62	45	38	31	688	39	425	e76	74	100	80
30 31	178 634	61	44 44	38 38		660 102	39	484 508	e72	63 107	88 83	101
31	034		**	30		102		300		107	03	
TOTAL	7492		1594	1482	990	2732	2114	9649	6546	2615	4345	3514
MBAN	242		51.4	47.8	34.1	88.1	70.5	311	218	84.4	140	117
MAX	655	1220	80	147	41	688	171	1250	795	176	531	326
MIN	78	61	44	38	31	31	38	34	72	56	58	64
e Es	timated											
STATIST	ICS OF MC	ONTHLY MEAN	DATA FO	R WATER Y	BARS 1984	- 1992	, BY WATER Y	MEAR (WY)				
MEAN	381		83.1	62.9	68.1	69.0	190	394	150	111	124	206
MAX	735		151	131	134	88.1	411	1586	218	161	180	376
(WY)	1986		1988	1988	1987	1992	1986	1986	1992	1990	1989	1989
MIN (WY)	116 1988		51.4 1992	46.2 19 8 9	34.1	49.2	70.5	59.5	105 1991	65.6 1984	71.6 1990	117
(#1)	1308	1909	1992	1989	1992	1988	1992	1989	1991	1304	1330	1992
SUMMARY	STATISTI	CS	FOR 1	991 CALEN	DAR YEAR	1	FOR 1992 WAT	TER YEAR		WATER YE	ARS 1984	- 1992
ANNUAL	TOTAL			49447			47233					
ANNUAL	MRAN			135			129			170		
	ANNUAL M									335		1986
	ANNUAL ME			1600			4050	62		129	0-1	1992
	DAILY ME			1600 37	Apr 26 Feb 2		1250 31	May 23 Feb 28		8150 25		7 1985 80 1990
	SEVEN-DAY			38	Mar 11		31	Feb 28		30		9 1990
	ANBOUS PE				2001 11		4430	Nov 1		10700		7 1985
INSTANT	ANEOUS PE	RAK STAGE					18.16			24.75		7 1985
	ENT EXCEE			288			303			321		
	ENT EXCES			75			72			82		
An BRKC	ENT EXCEE	รบร		42			34			42		

RIO CAMUY BASIN

50015700 RIO CAMUY NEAR HATILLO, PR--Continued

WATER QUALITY RECORDS

PERIOD OF RECORD. -- WATER YEARS AUGUST 1984 TO CURRENT YEAR

DATE	TIME	STREAMFLOW, INSTANTANEOUS (CFS)	SPECIFIC CON- DUCTANCE (UMHOS)	TEMPERA- TURE (DEG C)	DATE	TIME	STREAMFLOW, INSTANTANEOUS (CFS)	SPECIFIC CON- DUCTANCE (UMHOS)	TEMPERA- TURE (DEG C)
FEB. 21 AUG. 19		32 69	320 220	21.5 26.0	SEP. 19	1250	114	180	28.0

THIS PAGE WAS LEFT BLANK INTENTIONALLY




Figure 15.-Río Grande de Arecibo basin.

50020500 RIO GRANDE DE ARECIBO NEAR ADJUNTAS, PR

WATER-QUALITY RECORDS

LOCATION.--Lat 18°10'54", long 66°44'12", at Highway 135 bridge, 1.0 mi (1.6 km) upstream from Lago Adjuntas, and 1.5 mi (2.4 km) northwest of Adjuntas plaza.

DRAINAGE AREA.--12.7 mi² (32.9 km²) this does not include 6.0 mi² (15.6 km²) above Lago Garzas.

PERIOD OF RECORD. -- Water years 1969-74, 1979 to current year.

WATER-QUALITY DATA, WATER YEAR OCTOBER 1991 TO SEPTEMBER 1992

			****	IBN-QUAL	JIII DAI	.,	I Mai	unit o	CIODE) SEFIE	1221	2226				
			DIS- CHARGE INST. CUBIC	CIF	C WHO	TER OLE SLD	TEMP		TUR		OXYGE	50; (P)	GEN, LS- LVED ER-	OXYGE DEMAN CHEM ICAL	ID, I-	FORM, FECAL 0.7	TOC FE	CREP- COCCI CAL, AGAR
DATE		TIME	PER PER SECON	ANCI D (US/	A Al	AND- RD (TS)	WAT:	BR	BID ITY (NTU		SOLVE (MG/I	D SA	ENT TUR- LON)	(HIC LEVEL (MG/I	(۵)	UM-MF (COLS. 100 ML	/ E	PER ML)
NOV 1991																		
06 JAN 1992		1230	22	119	117	7.7	2	4.0	13		7.	5	81		48	410	0	9200
07		1545	48		333	7.4	2	3.0	12		7.	4	83	<	10	K130	0	3500
27		1030	11	- 3	335	7.7	2	1.0	0.	50	8.	5	100		16	25	0	5100
03		1000	41	113	265	7.4	2	2.0	4.	3	9.	0	105		12	K160	0	4700
11		1025	27		280	7.5	2	4.0	1.	2	9.	6	109		18	7	0	260
AUG 21		0950	18		515	7.4		3.5	1.		6.		70		16	490		24000
22		0330	10		,13	/. 4	4	3.5	1.	•	0.	4	70		10	430	0 2	84000
			HARD-									AL	KA-					
		HARD- NESS	NESS	B CALC		INE-	SODI	TIM	SODI		POTAS					SULFAT		IDB,
		TOTAL	WH WAT	DIS	D:	S-	DIS	-	SORP	-	DIS-	TOT	FET	SULFI		DIS-	DI	g-
DATE		(MG/L AS	TOT FL			LVED	SOLV.		TIO		SOLVE (MG/I		LAS	TOTA		SOLVE (MG/L		IG/L
		CACO3)	CAC03	AS (CA) AS	MG)	AS	NA)			AS K)	CA	203	AS S	(1)	AS SO4) AS	CL)
NOV 1991																		
06 JAN 1992		110	2	29	1.5	0.0	53		2		3.6		94	<0	.5	9.3	8	36
07						-	-	-					77					
27			22	-	9	-	-	-					110					
03		98	2	26		3.0	15		0	.7	3.5		100	<0	.5	14	2	4
11							_						100					
21		120	6	33		8.6	46		2		2.9		120			11	7	3
		120		33					•				120					-
					SOLIDS,			RESI										
				ILICA, DIS-	SUM OF CONSTI-		IDS, IS-	TOTA		NIT		MITRO- GEN,		TRO-		rro- En,	NITRO- GEN,	
		I	IS-	SOLVED	TUENTS,	SC	LVED	DEG.	C, 1	NITE	ATE N	TTRITE	NO2	+NO3	AMM	O AIMC	RGANIC	2
	DATE		LVED G/L	(MG/L AS	DIS- SOLVED		ONS	PRND		TOT		TOTAL (MG/L		TAL G/L		TAL 3/L	TOTAL (MG/L	
		AS	F)	S102)	(MG/L)	E	(YAC	(MG	/L)	AS	N)	AS N)	AS	N)	AS	N)	AS N)	
NOV	1991																	
	1992		0.10	29	275	1	6.2		10	1.	12	0.080	1	.20	0	.170	1.0	
07									7	1.	37	0.030	1	.40	0	160	0.34	l .
			44						1	1.	14	0.060	1	.20	0.	.040	0.16	5
			0.10	23	174	1	9.0		1	1.	08	0.020	1	.10	0.	.110	0.09	
JUN 11					122				3	0 -	740	0.050	0	.790	0	.020		
AUG				27	202													
21			0.20	41	273	1	3.3		8	U.	650	0.080	U	.730	U.	.070	0.33	

K = non-ideal count

RIO GRANDE DE ARECIBO BASIN 50020500 RIO GRANDE DE ARECIBO NR ADJUNTAS, PR--Continued WATER QUALITY DATA, WATER YEAR OCTOBER 1991 TO SEPTEMBER 1992

DATE	NITRO- GEN, AM- MONIA + ORGANIC TOTAL (MG/L AS N)	NITRO- GEN, TOTAL (MG/L AS N)	NITRO- GEN, TOTAL (MG/L AS NO3)	PHOS- PHORUS TOTAL (MG/L AS P)	ARSENIC TOTAL (UG/L AS AS)	BARIUM, TOTAL RECOV- ERABLE (UG/L AS BA)	BORON, TOTAL RECOV- ERABLE (UG/L AS B)	CADMIUM TOTAL RECOV- ERABLE (UG/L AS CD)	CHRO- MIUM, TOTAL RECOV- ERABLE (UG/L AS CR)	COPPER, TOTAL RECOV- ERABLE (UG/L AS CU)
NOV 1991										
06 JAN 1992	1.2	2.4	11	0.220	1	<100	20	<1	<1	50
07	0.50	1.9	8.4	0.110						
FRB 27	0.20	1.4	6.2	0.170						
APR 03	0.20						-10	∢1	<1	<10
JUN	0.20	1.3	5.8	0.080	<1	<100	<10	<1	<1	<10
11	<0.20			0.080						
21	0.40	1.1	5.0	0.190						
DATE	IRON, TOTAL RECOV- ERABLE (UG/L AS FE)	LEAD, TOTAL RECOV- ERABLE (UG/L AS PB)	MANGA- NESE, TOTAL RECOV- ERABLE (UG/L AS MN)	MERCURY TOTAL RECOV- ERABLE (UG/L AS HG)	SELE- NIUM, TOTAL (UG/L AS SE)	SILVER, TOTAL RECOV- ERABLE (UG/L AS AG)	ZINC, TOTAL RECOV- ERABLE (UG/L AS ZN)	CYANIDE TOTAL (MG/L AS CN)	PHENOLS TOTAL (UG/L)	METHY- LENE BLUE ACTIVE SUB- STANCE (MG/L)
NOV 1991	TOTAL RECOV- ERABLE (UG/L AS FE)	TOTAL RECOV- ERABLE (UG/L AS PB)	NESE, TOTAL RECOV- ERABLE (UG/L AS MN)	TOTAL RECOV- ERABLE (UG/L AS HG)	NIUM, TOTAL (UG/L AS SE)	TOTAL RECOV- ERABLE (UG/L AS AG)	TOTAL RECOV- ERABLE (UG/L AS ZN)	TOTAL (MG/L AS CN)	TOTAL (UG/L)	LENE BLUE ACTIVE SUB- STANCE (MG/L)
NOV 1991 06 JAN 1992	TOTAL RECOV- ERABLE (UG/L	TOTAL RECOV- ERABLE (UG/L	NESE, TOTAL RECOV- ERABLE (UG/L	TOTAL RECOV- ERABLE (UG/L	NIUM, TOTAL (UG/L	TOTAL RECOV- ERABLE (UG/L	TOTAL RECOV- ERABLE (UG/L	TOTAL (MG/L	TOTAL	LENE BLUE ACTIVE SUB- STANCE
NOV 1991 06 JAN 1992 07	TOTAL RECOV- ERABLE (UG/L AS FE)	TOTAL RECOV- ERABLE (UG/L AS PB)	NESE, TOTAL RECOV- ERABLE (UG/L AS MN)	TOTAL RECOV- ERABLE (UG/L AS HG)	NIUM, TOTAL (UG/L AS SE)	TOTAL RECOV- ERABLE (UG/L AS AG)	TOTAL RECOV- ERABLE (UG/L AS ZN)	TOTAL (MG/L AS CN)	TOTAL (UG/L)	LENE BLUE ACTIVE SUB- STANCE (MG/L)
NOV 1991 06 JAN 1992 07 FRB 27	TOTAL RECOV- ERABLE (UG/L AS FE)	TOTAL RECOV- ERABLE (UG/L AS PB)	NESE, TOTAL RECOV- ERABLE (UG/L AS MN)	TOTAL RECOV- BRABLE (UG/L AS HG)	NIUM, TOTAL (UG/L AS SE)	TOTAL RECOV- BRABLE (UG/L AS AG)	TOTAL RECOV- ERABLE (UG/L AS ZN)	TOTAL (MG/L AS CN)	TOTAL (UG/L)	LENE BLUE ACTIVE SUB- STANCE (MG/L)
NOV 1991 06 JAN 1992 07 FRB 27 APR 03	TOTAL RECOV- ERABLE (UG/L AS FE)	TOTAL RECOV- ERABLE (UG/L AS PB)	NESE, TOTAL RECOV- ERABLE (UG/L AS MN)	TOTAL RECOV- BRABLE (UG/L AS HG) <0.10	NIUM, TOTAL (UG/L AS SE)	TOTAL RECOV- BRABLE (UG/L AS AG)	TOTAL RECOV- ERABLE (UG/L AS ZN)	TOTAL (MG/L AS CN) <0.010	TOTAL (UG/L)	LENE BLUR ACTIVE SUB- STANCE (MG/L)
NOV 1991 06 JAN 1992 07 FRB 27 APR 03 JUN	TOTAL RECOV- ERABLE (UG/L AS FE) 1400	TOTAL RECOV- BRABLE (UG/L AS PB)	NESE, TOTAL RECOV- ERABLE (UG/L AS MN)	TOTAL RECOV- BRABLE (UG/L AS HG) <0.10	NIUM, TOTAL (UG/L AS SE) <1	TOTAL RECOV- BRABLE (UG/L AS AG)	TOTAL RECOV- ERABLE (UG/L AS ZN)	TOTAL (MG/L AS CN) <0.010	TOTAL (UG/L) <1	LENE BLUE ACTIVE SUB- STANCE (MG/L)
NOV 1991 06 JAN 1992 07 FRB 27 APR 03	TOTAL RECOV- ERABLE (UG/L AS FE) 1400	TOTAL RECOV- BRABLE (UG/L AS PB)	NESE, TOTAL RECOV- ERABLE (UG/L AS MN)	TOTAL RECOV- BRABLE (UG/L AS HG) <0.10	NIUM, TOTAL (UG/L AS SE) <1	TOTAL RECOV- BRABLE (UG/L AS AG)	TOTAL RECOV- ERABLE (UG/L AS ZN)	TOTAL (MG/L AS CN) <0.010	TOTAL (UG/L) <1	LENE BLUE ACTIVE SUB- STANCE (MG/L)

50025000 RIO GRANDE DE ARECIBO NEAR UTUADO, PR

WATER-QUALITY RECORDS

LOCATION.--Lat 18°18'11", long 66°41'59", at bridge near Highway 10 at km 56.4, 0.5 mi (0.8 km) downstream from Río de Caguana, and 2.5 mi (4.0 km) north of Utuado plaza.

DRAINAGE AREA.--66.0 mi $^{\circ}$ (170.9 km $^{\circ}$) this excludes 6.0 mi $^{\circ}$ (15.5 km $^{\circ}$) upstream from Lago Garzas to Río Guayanés in the Río Tallaboa basin.

PERIOD OF RECORD. -- Water years 1959-74, 1979 to current year.

WATER-QUALITY DATA, WATER YEAR OCTOBER 1991 TO SEPTEMBER 1992

DATE	TIME	DIS- CHARGE, INST. CUBIC FEET PER SECOND	SPE- CIFIC CON- DUCT- ANCE (US/CM)	PH WATER WHOLE FIELD (STAND- ARD UNITS)	TEMPER- ATURE WATER (DEG C)	TUR- BID- ITY (NTU)	DIS- SOLVI	CENT ED SATU	DEMAND CHEM- ICAL (HIGH C- LEVEL)	COLI- FORM, FECAL, 0.7 UM-MF (COLS./ 100 ML)	
OCT 1991 30	1140	158	141	7.7	24.5	250	7	.5 84	1 4	0 K69000	30000
DEC	1000	39									
30 FEB 1992			308	7.9	20.0	10	9.				
27 APR	1140	35	310	8.0	22.5	2.1	L 8	.5 96			3900
15 JUN	1055	55	291	7.7	26.5	5.0	8.	.0 100) 1	2 K800	300
24	0940	77	280	8.4	25.0	2.4	10	.0 112	2 <1	0 K110	380
20	1035	60	299	7.5	26.0	1.9	5 7	. 0 81	L 1	7 410	230
DATE	HARD- NESS TOTAL (MG/L AS CACO3)	HARD- NESS NONCARB WH WAT TOT FLD MG/L AS CACO3	CALCIUM DIS- SOLVED (MG/L AS CA)	MAGNE- SIUM, DIS- SOLVED (MG/L AS MG)	SODIUM, DIS- SOLVED (MG/L AS NA)	SODIU AD- SORP- TION RATIO	SIUI DIS- SOLVI	M, WAT WE TOT FE ED FIRLE L MG/L I	(H BT SULFID D TOTAL AS (MG/L		DIS- SOLVED (MG/L
OCT 1991 30	66	0	18	5.2	9.7	0.	.5 3.0		55 <0.	5 17	12
DEC 30								10			
FEB 1992 27									98		
APR											
15 JUN	110	21	31	8.5	16	0.			92 <0.		18
24 AUG								10	00		
20	110	13	30	8.4	16	0.	.7 2.3	3 9	98	20	20
OCT 30 DRC 30 FRB	R: SI SI DATE (1 A: 1991 	IDB, DI DIS- SC DILVED (N MG/L J S F) SI <0.10 1	LICA, SUM LICA, SUM LICA CON DLVED TUE LICA DO LICA SO LICA	STI- I NTS, SG IS- (T LVED F G/L) I	IDS, TOT DIS- AT DLVED DEG CONS SU PER PEN	105	NITROGEN, NITRATE I TOTAL (MG/L AS N) 1.15 0.970 1.12	NITRO-GEN, NITRITE PATOTAL (MG/L AS N) 0.050 0.030 0.080	GEN, NO2+NO3 A TOTAL (MG/L	GEN, MMONIA OR FOTAL T (MG/L (IITRO- GEN, GANIC OTAL MG/L S N) 0.79 0.17 0.26 0.09
	•••					10	0.940	0.050	0.990	0.080	0.12
AUG 20	• • •	0.20 2	18	184 3	10	16	0.970	0.030	1.00	0.020	
K = 1	non-ideal	count									

K = non-ideal count

50025000 RIO GRANDE DE ARECIBO NEAR UTUADO, PR--Continued WATER-QUALITY DATA, WATER YEAR OCTOBER 1991 TO SEPTEMBER 1992

DATE	NITRO- GEN, AM- MONIA + ORGANIC TOTAL (MG/L AS N)	NITRO- GEN, TOTAL (MG/L AS N)	NITRO- GEN, TOTAL (MG/L AS NO3)	PHOS- PHORUS TOTAL (MG/L AS P)	ARSENIC TOTAL (UG/L AS AS)	BARIUM, TOTAL RECOV- ERABLE (UG/L AS BA)	BORON, TOTAL RECOV- ERABLE (UG/L AS B)	CADMIUM TOTAL RECOV- ERABLE (UG/L AS CD)	CHRO- MIUM, TOTAL RECOV- ERABLE (UG/L AS CR)	COPPER, TOTAL RECOV- ERABLE (UG/L AS CU)
ост 1991										
30	0.90	2.1	9.3	0.320	<1	200	50	<1	12	100
30 FRB 1992	0.20	1.2	5.3	0.180						
27	0.50	1.7	7.5	0.230						
APR 15	0.20	0.87	3.9	0.100	<1	<100	<10	<1	<1	20
JUN 24	0.20	1.2	5.3	0.170						
AUG 20	<0.27			0.070						
DATE	IRON, TOTAL RECOV- ERABLE (UG/L AS FE)	LEAD, TOTAL RECOV- ERABLE (UG/L AS PB)	MANGA- NESE, TOTAL RECOV- ERABLE (UG/L AS MN)	MERCURY TOTAL RECOV- ERABLE (UG/L AS HG)	SELE- NIUM, TOTAL (UG/L AS SE)	SILVER, TOTAL RECOV- ERABLE (UG/L AS AG)	ZINC, TOTAL RECOV- BRABLE (UG/L AS ZN)	CYANIDE TOTAL (MG/L AS CN)	PHENOLS TOTAL (UG/L)	METHY- LENE BLUE ACTIVE SUB- STANCE (MG/L)
ост 1991	TOTAL RECOV- BRABLE (UG/L AS FR)	TOTAL RECOV- BRABLE (UG/L AS PB)	NESE, TOTAL RECOV- ERABLE (UG/L AS MN)	TOTAL RECOV- ERABLE (UG/L AS HG)	NIUM, TOTAL (UG/L AS SR)	TOTAL RECOV- ERABLE (UG/L AS AG)	TOTAL RECOV- BRABLE (UG/L AS ZN)	TOTAL (MG/L AS CN)	TOTAL (UG/L)	LENE BLUR ACTIVE SUB- STANCE (MG/L)
	TOTAL RECOV- ERABLE (UG/L	TOTAL RECOV- BRABLE (UG/L	NESE, TOTAL RECOV- ERABLE (UG/L	TOTAL RECOV- BRABLE (UG/L	NIUM, TOTAL (UG/L	TOTAL RECOV- BRABLE (UG/L	TOTAL RECOV- BRABLE (UG/L	TOTAL (MG/L	TOTAL	Lene Blur Active Sub- Stance
ост 1991 30	TOTAL RECOV- BRABLE (UG/L AS FR)	TOTAL RECOV- BRABLE (UG/L AS PB)	NESE, TOTAL RECOV- ERABLE (UG/L AS MN)	TOTAL RECOV- ERABLE (UG/L AS HG)	NIUM, TOTAL (UG/L AS SR)	TOTAL RECOV- ERABLE (UG/L AS AG)	TOTAL RECOV- BRABLE (UG/L AS ZN)	TOTAL (MG/L AS CN)	TOTAL (UG/L)	LENE BLUR ACTIVE SUB- STANCE (MG/L)
OCT 1991 30 DBC 30 FRB 1992 27	TOTAL RECOV- ERABLE (UG/L AS FE)	TOTAL RECOV- BRABLE (UG/L AS PB)	NESE, TOTAL RECOV- ERABLE (UG/L AS MN)	TOTAL RECOV- BRABLE (UG/L AS HG)	NIUM, TOTAL (UG/L AS SR)	TOTAL RECOV- ERABLE (UG/L AS AG)	TOTAL RECOV- BRABLE (UG/L AS ZN)	TOTAL (MG/L AS CN)	TOTAL (UG/L)	LENE BLUE ACTIVE SUB- STANCE (MG/L) 0.06
OCT 1991 30 DEC 30 FEB 1992 27 APR 15	TOTAL RECOV- ERABLE (UG/L AS FE)	TOTAL RECOV- ERABLE (UG/L AS PB)	NESE, TOTAL RECOV- ERABLE (UG/L AS MN)	TOTAL RECOV- ERABLE (UG/L AS HG)	NIUM, TOTAL (UG/L AS SR)	TOTAL RECOV- RRABLE (UG/L AS AG) <1	TOTAL RECOV- BRABLE (UG/L AS ZN)	TOTAL (MG/L AS CN) <0.010	TOTAL (UG/L) <1	LENE BLUR ACTIVE SUB- STANCE (MG/L)
OCT 1991 30 DEC 30 FEB 1992 27	TOTAL RECOV- RRABLE (UG/L AS FE) 14000	TOTAL RECOV- BRABLE (UG/L AS PB)	NESE, TOTAL RECOV- BRABLE (UG/L AS MN)	TOTAL RECOV- BRABLE (UG/L AS HG) 0.10	NIUM, TOTAL (UG/L AS SR) <1	TOTAL RECOV- BRABLB (UG/L AS AG) <1	TOTAL RECOV- BRABLE (UG/L AS ZN) 50	TOTAL (MG/L AS CN) <0.010	TOTAL (UG/L) <1 	LENE BLUE ACTIVE SUB- STANCE (MG/L) 0.06

50025155 RIO SALIENTE AT COABEY NEAR JAYUYA, PR

LOCATION.--Lat 18°12'48", long 66°33'49", Hydrologic Unit 21010002, 2.0 mi (3.2 km) southeast of Jayuya, 1.4 mi (2.2 km) northeast of Hacienda Gripiñas.

DRAINAGE ARRA. -- 9.25 mi2 (23.96 km2).

WATER-DISCHARGE RECORDS

PERIOD OF RECORD. -- October 1989 to current year.

GAGE.--Water-stage recorder. Elevation of gage is 1,706 ft (520 m), from topographic map.

REMARKS.--Records fair except those for estimated daily discharges, which are poor. Gage-height and precipitation satellite telemetry at station.

		_										
	DI	SCHARGE,	CUBIC FEE				TOBER 1991	TO SEPTE	MBER 199	2		
				Ι	AILY MEAN	VALUES						
DAY	OCT	NOV	DRC	JAN	FEB	MAR	APR	MAY	JUN	JOL	AUG	SEP
1	10	e 16	7.5	e 7.0	e 13	e9.4	e 26	e 35	e150	e17	18	14
2	9.6	e15	7.3	e6.9	e13	e9.4	e 20	e 22	e74	e15	14	13
3	9.1	e 13	7.4	e6.9	e12	e9.2	e12	e 17	e50	e 13	12	13
4	8.2	e11	8.7	e35	e12	e 9.1	e10	e15	e42	e12	16	15
5	7.9	e 10	8.9	e450	e15	e 9.0	e 15	e 17	e 37	e12	42	17
6	8.0	e11	8.7	e300	e32	e9.1	e 26	e15	e34	e12	35	15
7	14	e 13	7.7	e120	e32	e 9.6	e24	e12	e32	e15	17	88
8	17	e15	6.7	e 60	e30	e 10	e 56	e 11	e 31	e 13	15	36
9	16	e13	6.6	e40	e21	e12	e45	e11	e30	e12	23	22
10	18	e12	6.6	e34	e 17	e9.0	e19	e 13	e 38	e 11	60	18
11	16	e11	6.5	e 39	e15	e8.4	e14	e 26	e 30	e11	34	17
12	13	e 11	6.3	e39	e14	e8.2	e11	e2 7	e 26	e 11	23	16
13	10	e1 0	6.3	e 31	e 16	e8. 0	e12	e4 9	e24	e 11	18	15
14	9.2	e1 0	6.3	e27	e 16	e 7.8	e25	e64	e23	e10	17	14
15	8.8	10	€6.3	e 24	e 14	e8.4	e72	e4 5	e 23	e 11	17	38
16	8.6	10	5.6	e25	e13	e 10	e 55	e96	e22	e 10	16	21
17	8.1	9.4	6.0	e26	e12	e10	e77	e 76	e22	e10	15	18
18	11	9.2	6.0	e21	e11	e 7.6	e 180	e123	e21	e9.8	14	15
19	12	8.8	5.8	e 19	e11	e 7.1	e135	e72	e 20	e9.5	13	14
20	8.8	8.7	e 19	e 17	e10	e 6.9	e 66	e4 8	e 2 0	e 8.9	13	19
21	9.9	8.5	e21	e16	e10	e8.6	e 33	e 38	e2 0	e8.8	55	20
22	16	8.5	e10	e16	e10	e 6.6	e24	e120	e19	e15	25	16
23	15	8.2	e8.6	e15	e10	e7.4	e19	e170	e18	22	18	45
24	12	11	e8.2	e 16	e9.6	e9.0	e16	e 120	e 17	10	16	26
25	8.5	10	e7.8	e15	e11	e7.8	e14	e80	e 16	11	15	27
26	8.3	7.9	e7.4	e15	e9.4	e12	e 13	e140	e 16	9.8	27	25
27	7.5	8.2	e7.6	e14	e10	e20	e12	e80	e15	9.6	21	18
28	7.4	9.8	e 7.6	e14	e11	e52	e12	e 50	e14	9.8	16	18
29	17	8.7	e7.4	e14	e 10	e25	e 15	e40	e14	9.6	15	18
30	19	7.9	e7.2	e14		e 15	e21	e38	e13	30	14	35
31	e 17		e7.2	e14		e 20		e14 0		40	15	
TOTAL	360.9	315.8	250.2	1490.8	420.0	361.6	1079	1810	911	409.8	669	686
MEAN	11.6	10.5	8.07	48.1	14.5	11.7	36.0	58.4	30.4	13.2	21.6	22.9
MAX	19	16	21	450	32	52	180	170	150	40	60	88
MIN	7.4	7.9	5.6	6.9	9.4	6.6	10	11	13	8.8	12	13
AC-FT	716	626	496	2960	833	717	2140	3590	1810	813	1330	1360
CFSM IN.	1.26 1.45	1.14	. 87	5.20	1.57	1.26	3.89	6.31	3.28 3.66	1.43	2.33	2.47 2.76
TM.	1.45	1.27	1.01	6.00	1.69	1.45	4.34	7.28	3.00	1.65	2.69	2.70
e B	stimated											
STATIST	TICS OF M	CONTHLY M	BAN DATA F	OR WATER Y	TRARS 1989	9 - 1992,	BY WATER Y	MBAR (WY)				
MEAN	36.8	23.6	12.0	22.6	11.2	11.5	18.8	26.2	17.2	11.8	17.8	27.5
MAX	70.5	40.0	17.9	48.1	14.5	13.0	36.0	58.4	30.4	15.3	21.6	45.2
(WY)	1991	1991	1991	1992	1992	1991	1992	1992	1992	1991	1992	1990
MIN	11.6	10.5	8.07	7.19	6.00	9.90	7.01	5.35	10.1	6.85	13.8	14.4
(WY)	1992	1992	1992	1990	1990	1990	1990	1990	1991	1990	1990	1991
SUMMARY	Y STATIST	ICS	FOR	1991 CALE	DAR YEAR	F	OR 1992 WAT	ER YEAR		WATER YE	ARS 1989	- 1992
ANNUAL				4700.2			8764.1			10.0		
ANNUAL	MBAN T ANNUAL	MPAN		12.9			23.9			19.8 23.9		1992
	ANNUAL M									14.3		1990
	T DAILY M			75	Mar 26		450	Jan 5		450	Jan	5 1992
LOWEST	DAILY ME	RAN			Aug 12			Dec 16		2.4 3.4	Jul 2	3 1990
	SEVEN-DA			6.0	Dec 13		6.0					2 1990
	TANEOUS P		1				2900			2900	Jan	5 1992
	TANBOUS I RUNOFF (9320			5.5 17380	Dec. 12		14330		
	RUNOFF (1.3	9		2.59			2.14		
ANNUAL	RUNOFF (INCHES)		18.90			35.25			29.06		
	CENT BXCE			21			43			38		
	CENT EXCE			10			14			12		
SO PER	CENT EXCE	ಆಗುತ		7.2			7.9			5.6		

50026050 RIO CAONILLAS ABOVE LAGO CAONILLAS NEAR JAYUYA, PR

WATER-QUALITY RECORDS

LOCATION.--Lat 18°13'26", long 66°38'22", 300 ft (91 m) off Highway 531, 700 ft (213 m) upstream from Lago Caonillas, 3.3 mi (5.3 km) northwest of Jayuya plaza.

DRAINAGE AREA. -- 40.4 mi 2 (104.6 km2).

PERIOD OF RECORD. -- Water years 1979 to current year.

WATER-QUALITY DATA, WATER YEAR OCTOBER 1991 TO SEPTEMBER 1992

גם	ATB	TIME	DIS- CHARGE, INST. CUBIC FEST PER SECOND	SPE- CIFIC CON- DUCT- ANCE (US/CM)	PH WATER WHOLE FIELD (STAND- ARD UNITS)	TEMPER ATURE WATER (DEG C	BI IT	D- Y	OXYGEN, DIS- SOLVED (MG/L)	OXYGE DIS SOLV (PER CEN SATU	red (Tro (- Tr (r Li	CYGEN EMAND, CHEM- ICAL (HIGH EVEL) MG/L)	COLI- FORM, FECAL 0.7 UM-MF (COLS. 100 ML	TOCOCCI FECAL, KF AGAR (COLS. PER
OCT 19		1200	82	146	7.4	23.	0 17		8.6	82		21	360	0 2100
JAN 19		1315	B300	132	7.3	22.	0 18		9.5	100		<10	230	0 4100
FEB 27 APR	•	0845	23	184	7.9	21.	0 0	.40	9.3	98		14	K 3	6 82
02 JUN	•	0950	39	201	7.6	23.	5 7	.5	9.0	95		12	K74	5 360
04	•	1105	171	170	7.7	25.	0 5	.1	8.2	78		13	K130	0 360
25	•	0940	38	204	7.2	24.	0 69		6.2	58		10	K970	0 4300
K.D	LTB	HARD- NESS TOTAL (MG/L AS CACO3)	HARD- NESS NONCARB WH WAT TOT FLD MG/L AS CACO3	CALCIUM DIS- SOLVED (MG/L AS CA)	MAGNE- SIUM, DIS- SOLVED (MG/L AS MG)	SODIUM DIS- SOLVED (MG/L AS NA	, A Sor Ti Rat	ON	POTAS- SIUM, DIS- SOLVED (MG/L AS K)	ALKA LINIT WAT W TOT F FIRL MG/L CACO	y h et si d ' as	LFIDE TOTAL (MG/L AS S)	SULFAT DIS- SOLVR (MG/L AS SO4	DIS- D SOLVED (MG/L
OCT 19	•	53	4	14	4.5	8.1		0.5	1.8		48	<0.5	11	9.4
JAN 19							_	-			32			
FRB 27 APR	•						-	-			75			
02 JUN	•	73	6	19	6.2	11		0.6	3.1		69	<0.5	14	12
04 AUG	•						-	-			53			
25	•	79	7	21	6.5	14		0.7	1.8		70		13	9.3
c	DATI	R] I S() } A\$	IDE, DI DIS- SI DLVED (I	LICA, SUM IS- CON OLVED TUE MG/L E AS SO	ISTI- I INTS, SC DIS- (7 DLVED I	LIDS, TO DIS- A'DLVED DI CONS CONS	RSIDUR OTAL T 105 EG. C, SUS- ENDED (MG/L)	NITE GEI NITE TOTE (MG. AS I	N, C ATB NIT AL TC /L ()	ITRO- SEN, FRITE STAL 4G/L S N)	NITRO GEN, NO2+NO TOTAI (MG/I AS N))3 AMN L TO	SEN, SONIA O STAL SG/L	NITRO- GEN, RGANIC TOTAL (MG/L AS N)
	31 IAN 1992		(0.10	20	98 2	1.7	12	0.	660 (0.010	0.6	70 0	0.030	0.27
	07 BB	:					17	1.	17 (.030	1.2) (0.030	0.27
	27 APR				~-		1		- <(0.010	0.3	50 0	.020	
	02 TUN	•	(0.10	22	129 1	.3.5	1		- <(0.010	0.5	0 0	0.020	
	04						12		- <0	0.010	1.1	(0	.010	

82

0.510

0.070

0.580

0.090

AUG 25...

<0.10

23

133

13.6

R = estimate
K = non-ideal count

50026050 RIO CAONILLAS ABOVE LAGO CAONILLAS NEAR JAYUYA, PR--Continued WATER-QUALITY DATA, WATER YEAR OCTOBER 1991 TO SEPTEMBER 1992

DATE	NITRO- GEN, AM- MONIA + ORGANIC TOTAL (MG/L AS N)	NITRO- GEN, TOTAL (MG/L AS N)	NITRO- GEN, TOTAL (MG/L AS NO3)	PHOS- PHORUS TOTAL (MG/L AS P)	ARSENIC TOTAL (UG/L AS AS)	BARIUM, TOTAL RECOV- ERABLE (UG/L AS BA)	BORON, TOTAL RECOV- ERABLE (UG/L AS B)	CADMIUM TOTAL RECOV- EPABLE (UG/L AS CD)	CHRO- MIUM, TOTAL RECOV- ERABLE (UG/L AS CR)	COPPER, TOTAL RECOV- ERABLE (UG/L AS CU)
OCT 1991										
31 JAN 1992	0.30	0.97	4.3	0.070	<1	<100	20	<1	<1	40
07 FBB	0.30	1.5	6.6	0.070						
27 APR	<0.20			0.060						
02 JUN	<0.20	~-		0.060	<1	<100	<10	<1	<1	<10
04 AUG	<0.20			0.050						
25	<0.20			0.080						
DATE	IRON, TOTAL RECOV- ERABLE (UG/L AS FE)	LEAD, TOTAL RECOV- ERABLE (UG/L AS PB)	MANGA- NESE, TOTAL RECOV- ERABLE (UG/L AS MN)	MERCURY TOTAL RECOV- ERABLE (UG/L AS HG)	SELE- NIUM, TOTAL (UG/L AS SE)	SILVER, TOTAL RECOV- BRABLE (UG/L AS AG)	ZINC, TOTAL RECOV- ERABLE (UG/L AS ZN)	CYANIDE TOTAL (MG/L AS CN)	PHENOLS TOTAL (UG/L)	METHY- LENE BLUE ACTIVE SUB- STANCE (MG/L)
OCT 1991	TOTAL RECOV- ERABLE (UG/L AS FE)	TOTAL RECOV- ERABLE (UG/L AS PB)	NESE, TOTAL RECOV- ERABLE (UG/L AS MN)	TOTAL RECOV- ERABLE (UG/L AS HG)	NIUM, TOTAL (UG/L AS SE)	TOTAL RECOV- BRABLE (UG/L AS AG)	TOTAL RECOV- ERABLE (UG/L AS ZN)	TOTAL (MG/L AS CN)	TOTAL (UG/L)	LENE BLUE ACTIVE SUB- STANCE (MG/L)
OCT 1991 31 JAN 1992	TOTAL RECOV- ERABLE (UG/L AS FE)	TOTAL RECOV- ERABLE (UG/L AS PB)	NESE, TOTAL RECOV- ERABLE (UG/L	TOTAL RECOV- ERABLE (UG/L AS HG)	NIUM, TOTAL (UG/L	TOTAL RECOV- BRABLE (UG/L	TOTAL RECOV- ERABLE (UG/L AS ZN)	TOTAL (MG/L	TOTAL	LENE BLUE ACTIVE SUB- STANCE (MG/L)
OCT 1991 31	TOTAL RECOV- ERABLE (UG/L AS FE)	TOTAL RECOV- ERABLE (UG/L AS PB)	NESE, TOTAL RECOV- ERABLE (UG/L AS MN)	TOTAL RECOV- ERABLE (UG/L AS HG)	NIUM, TOTAL (UG/L AS SE)	TOTAL RECOV- BRABLE (UG/L AS AG)	TOTAL RECOV- ERABLE (UG/L AS ZN)	TOTAL (MG/L AS CN)	TOTAL (UG/L)	LENE BLUE ACTIVE SUB- STANCE (MG/L)
OCT 1991 31 JAN 1992 07 FEB 27	TOTAL RECOV- ERABLE (UG/L AS FE)	TOTAL RECOV- ERABLE (UG/L AS PB)	NESE, TOTAL RECOV- ERABLE (UG/L AS MN)	TOTAL RECOV- ERABLE (UG/L AS HG)	NIUM, TOTAL (UG/L AS SE)	TOTAL RECOV- BRABLE (UG/L AS AG)	TOTAL RECOV- ERABLE (UG/L AS ZN)	TOTAL (MG/L AS CN)	TOTAL (UG/L)	LENE BLUE ACTIVE SUB- STANCE (MG/L)
OCT 1991 31 JAN 1992 07 FEB 27 APR 02	TOTAL RECOV- ERABLE (UG/L AS FE)	TOTAL RECOV- ERABLE (UG/L AS PB) <1	NESE, TOTAL RECOV- ERABLE (UG/L AS MN)	TOTAL RECOV- ERABLE (UG/L AS HG)	NIUM, TOTAL (UG/L AS SE)	TOTAL RECOV- ERABLE (UG/L AS AG)	TOTAL RECOV- ERABLE (UG/L AS ZN) <10	TOTAL (MG/L AS CN) <0.010	TOTAL (UG/L) <1	LENE BLUE ACTIVE SUB- STANCE (MG/L)
OCT 1991 31 JAN 1992 07 FEB 27 APR	TOTAL RECOV- BRABLE (UG/L AS FE) 1200	TOTAL RECOV- BRABLE (UG/L AS PB)	NESE, TOTAL RECOV- ERABLE (UG/L AS MN)	TOTAL RECOV- BRABLE (UG/L AS HG) <0.10	NIUM, TOTAL (UG/L AS SE) <1	TOTAL RECOV- BRABLE (UG/L AS AG)	TOTAL RECOV- BRABLE (UG/L AS ZN) <10	TOTAL (MG/L AS CN) <0.010	TOTAL (UG/L) <1 	LENE BLUE ACTIVE SUB- STANCE (MG/L) 0.03

50026140 LAGO CAONILLAS AT CAONILLAS, PR

LOCATION.--Lat 18°16'43", long 66°39'43", Hydrologic Unit 21010001, at Lago Caonillas Dam on Río Caonillas, 2.92 mi (4.7 km) northeast of Plaza de Utuado, 0.34 mi (0.55 km) west from Iglesia Santa María del Monte Carmelo, and 1.85 mi (3.0 km) nothwest from Hacienda Carbonell.

DRAINAGE AREA. -- 48.4 mi 2 (125.4 km2).

RLEVATION RECORDS

PERIOD OF RECORD. -- March 1991 to current year.

GAGE. -- Water stage recorder. Datum of gage is mean sea level.

REMARKS.--Lago Caonillas was completed in 1948. The dam is a concrete gravity structure with a total length of 815 ft (248 m), a maximum height of 235 ft (72 m), and a maximum base width of 195 ft (59 m). Nonoverflow sections on each abutment have a total length of 603 ft (184 m). The dam is the main unit of Caonillas Hidroelectric Project, and provides 49,000 acre-feet (60 hm³) of usable storage for power generation at Caonillas Power Plant No. 1 located 2.5 mi (4.0 km) downstream from the dam. The dam is owned by Puerto Rico Electric Power Authority. Gage-height and precipitation satellite telemetry at station.

EXTREMES FOR PERIOD OF RECORD.--Maximum elevation 824.46 ft (286.91 m), June 3; minimum elevation, less than 771.00 ft (235.00 m), many days.

Capacity Table (based on data from Puerto Rico Electric Power Authority)

Elevation, in feet	Contents, in acre-feet	Blevation, in feet	Contents, in acre-feet
705	0	800	27,982
750	8,421	830	46,161

ELEVATION (FERT NGVD), WATER YEAR OCTOBER 1991 TO SEPTEMBER 1992 DAILY OBSERVATION AT 24:00 VALUES

DAY	oct	NOV	DEC	Jan	Feb	MAR	APR	MAY	JUN	JUL	AUG	SEP
1	780.74	785.97	787.65	788.05	805.98	805.97	λ	804.83	823.23	809.95	791.88	784.62
2	780.98	786.32	787.17	787.92	806.02	805.84	805.66	804.93	824.22	809.41	791.29	784.85
3	781.17	786.54	787.26	787.78	806.12	805.82	806.35	804.76	824.11	808.89	790.17	784.97
4	781.28	786.71	787.28	787.82	806.16	805.81	806.39	804.54	824.12	808.67	788.83	785.11
5	781.45	786.93	787.27	790.71	806.19	805.74	806.51	803.86	824.20	808.32	788.87	784.50
6	781.62	786.98	787.26	804.60	806.13	805.73	806.42	803.28	823.87	807.53	788.11	784.72
7	781.76	787.16	787.27	805.85	806.44	805.72	806.57	802.90	822.56	807.11	787.04	786.55
8	781.99	787.38	787.28	805.75	806.53	806.17	806.69	802.27	823.18	806.38	787.13	787.28
9	782.00	787.59	787.37	805.96	806.61	806.31	807.06	802.27	822.76	805.35	787.27	787.63
10	782.14	787.09	787.44	805.44	806.69	806.02	807.45	802.26	822.39	804.20	788.04	787.90
11	782.28	787.17	787.50	805.52	806.47	805.99	807.41	801.70	822.10	803.48	788.25	787.21
12	782.19	787.35	787.57	805.57	806.34	805.32	807.52	801.79	821.33	802.83	788.54	787.17
13	782.18	786.28	787.65	805.59	806.36	804.63	807.61	801.84	820.83	802.33	788.50	787.35
14	782.31	786.21	787.57	805.82	806.41	804.41	807.62	800.84	820.48	801.61	788.64	787.52
15	782.44	786.37	787.63	805.59	806.47	803.25	807.75	800.10	819.76	800.98	788.61	788.53
16	782.57	786.52	787.72	805.59	806.51	803.38	807.68	800.31	819.07	800.23	788.37	789.12
17	782.69	786.48	787.73	805.78	806.48	802.84	807.77	800.80	818.32	799.65	788.15	788.75
18	783.12	786.53	787.75	805.79	806.48	802.90	807.68	801.14	817.39	799.04	787.97	788.95
19	783.48	786.63	787.82	805.77	806.48	801.98	808.31	801.00	816.79	798.67	787.40	788.64
20	783.64	786.55	788.01	805.78	806.48	800.75	809.16	801.86	814.89	798.28	786.52	789.12
21	783.76	786.51	788.40	805.85	806.43	801.17	808.71	801.79	814.22	797.71	785.66	789.12
22	783.97	786.62	788.57	805.91	806.44	801.17	807.96	801.40	814.66	797.06	784.72	789.21
23	783.56	786.73	788.71	805.43	806.44	801.09	807.66	809.65	813.70	796.49	784.71	790.07
24	782.93	786.88	788.81	805.47	806.30	801.09	807.09	812.88	813.21	795.91	784.49	790.58
25	782.67	787.00	788.91	805.53	806.19	801.52	807.00	814.67	812.70	795.95	784.64	790.61
26	782.77	787.12	788.72	805.58	806.18	801.60	807.06	817.10	812.11	795.95	784.73	790.87
27	782.85	787.24	788.61	805.63	806.18	801.25	806.46	818.25	811.67	795.58	784.72	791.01
28	782.71	787.34	788.48	805.76	806.17	801.60	805.88	818.65	811.51	794.58	784.93	791.40
29	783.45	787.44	788.18	805.90	806.10	801.92	805.37	819.53	810.83	793.48	785.10	791.69
30	784.48	787.55	788.09	806.03		A	805.13	820.16	810.47	792.62	785.24	792.23
31	785.20	707133	787.91	806.05		y		821.56		792.56	784.39	
TOTAL	24260.38	23605.19	24423.59	24889.82	23383.78			25002.92	24550.68	24830.80	24402.91	23647.28
MRAN	782.59	786.84	787.86	802.90	806.34			806.55	818.36	800.99	787.19	788.24
MAX	785.20	787.59	788.91	806.05	806.69			821.56	824.22	809.95	791.88	792.23
MIN	780.74	785.97	787.17	787.78	805.98			800.10	810.47	792.56	784.39	784.50

A No gage-height record.

50027250 RIO GRANDE DE ARECIBO BELOW LAGO DOS BOCAS NEAR FLORIDA, PR

WATER-QUALITY RECORDS

LOCATION.--Lat 18°20'50", long 66°40'02", at pedestrian bridge, 0.7 mi (1.1 km) downstream from Lago Dos Bocas and 6.6 mi (10.6 km) west of Florida plaza.

DRAINAGE AREA.--169 mi² (436 km²) does not include 6.0 mi² (15.6 km²) above Lago Gargas.

PERIOD OF RECORD. -- Water years 1970-71, 1974 to current year.

WATER-QUALITY DATA, WATER YEAR OCTOBER 1991 SEPTEMBER 1992

DATE	TIME	DIS- CHARGE, INST. CUBIC FEET PER SECOND	SPE- CIFIC COM- DUCT- ANCE (US/CM)	PH WATER WHOLE FIBLD (STAND- ARD UNITS)	TEMPER- ATURE WATER (DEG C)	TUR- BID- ITY (NTU)	OXYGEN, DIS- SOLVED (MG/L)	OXYGEN, DIS- SOLVED (PER- CENT SATUR- ATION)	OXYGEN DEMAND, CHEM- ICAL (HIGH LEVEL) (MG/L)	COLI- FORM, FECAL, 0.7 UM-MF (COLS./ 100 ML)	STREP- TOCOCCI FECAL, KF AGAR (COLS. PER 100 ML)
NOV 1991 05	1030	26	193	7.4	25.5	54	5.4	60	13	200	400
DEC 30	0815	20	244	7.6	23.0	1.3	6.3	78	<10	64	85
FEB 1992											
28 APR	0840	20	244	7.6	23.0	1.4	6.3	79	16	K8	K4
15 Jun	0900	18	197	6.5	24.5	13	6.0	71	22	54	270
24 AUG	0835	16	173	6.8	25.5	7.3	5.6	64	29	K10	37
20	0845	19	200	6.7	26.0	1.6	4.0	52	12	K40	K120
DATE	HARD- NESS TOTAL (MG/L AS CACO3)	HARD- NESS NONCARB WH WAT TOT FLD MG/L AS CACO3	CALCIUM DIS- SOLVED (MG/L AS CA)	MAGNE- SIUM, DIS- SOLVED (MG/L AS MG)	SODIUM, DIS- SOLVED (MG/L AS NA)	SODIUM AD- SORP- TION RATIO	f POTAS- SIUM, DIS- SOLVED (MG/L AS K)	ALKA- LINITY WAT WH TOT FET FIRLD MG/L AS CACO3	SULFIDE TOTAL (MG/L AS S)	SULFATE DIS- SOLVED (MG/L AS SO4)	CHLO- RIDE, DIS- SOLVED (MG/L AS CL)
NOV 1991 05	68	2	19	5.1	8.8	0.9	2.5	64	<0.5	11	11
DEC 30								85			
FEB 1992 28								85			
APR						/					
15 JUN	76	5	21	5.7	9.7	0.9		66	<0.5	14	14
24 AUG								62			
20	81	7	22	6.3	11	0.5	2.3	80		13	13
	RI E SC ATR (M AS	DB, DI DIS- SC DLVED (M IG/L A	ICA, SUM SS- CON DLVED TUE IG/L D SS SO	STI- D NTS, SO IS- (T LVED P	IDS, TOT IS- AT LVED DEG ONS SU ER PEN	105 . C, N] S- 7 DED (GEN, CITRATE NIT	BEN, G TRITE NO2 DTAL TO AG/L (M	EN, G +NO3 AMM TAL TO G/L (M	EN, G ONIA ORG TAL TO G/L (M	TRO- BEN, BANIC OTAL IG/L S N)
NOV 1		0.10 2	0	116	8.07	14	0.660	0.040 0	.700 0	.060	0.34
DEC 30.						1	0.500	0.010 0	.510 0	.020	
FEB 1 28.						1	<(0.010 0	.350 0	. 04 0	0.46
APR 15.		0.20 1	.8	125	6.1	30				.040	
JUN 24.						12				.090	0.11
AUG 20.		0.10 2	1	135	6.92	10				.080	0.42
	on-ideal c		-	300							- /

K = non-ideal count

RIO GRANDE DE ARECIBO BASIN

50027250 RIO GRANDE DE ARECIBO BELOW LAGO DOS BOCAS NEAR FLORIDA, PR--Continued WATER-QUALITY DATA, WATER YEAR OCTOBER 1991 TO SEPTEMBER 1992

DATE	NITRO- GEN, AM- MONIA + ORGANIC TOTAL (MG/L AS N)	NITRO- GEN, TOTAL (MG/L AS N)	NITRO- GEN, TOTAL (MG/L AS NO3)	PHOS- PHORUS TOTAL (MG/L AS P)	ARSENIC TOTAL (UG/L AS AS)	BARIUM, TOTAL RECOV- ERABLE (UG/L AS BA)	BORON, TOTAL RECOV- ERABLE (UG/L AS B)	CADMIUM TOTAL RECOV- BRABLE (UG/L AS CD)	CHRO- MIUM, TOTAL RECOV- ERABLE (UG/L AS CR)	COPPER, TOTAL RECOV- ERABLE (UG/L AS CU)
NOV 1991										
05 DBC	0.40	1.1	4.9	0.070	<1	<100	50	<1	4	70
30 FBB 1992	<0.20			0.030						
28 APR	0.50	0.85	3.8	0.030						
15 JUN	<0.20			0.030	<1	<100	20	<1	<1	10
24 AUG	0.20	0.36	1.6	0.020						
20	0.40	0.60	2.7	0.020						
DATE	IRON, TOTAL RECOV- ERABLE (UG/L AS FE)	LEAD, TOTAL RECOV- BRABLE (UG/L AS PB)	MANGA- NESE, TOTAL RECOV- ERABLE (UG/L AS MN)	MERCURY TOTAL RECOV- ERABLE (UG/L AS HG)	SELE- NIUM, TOTAL (UG/L AS SR)	SILVER, TOTAL RECOV- BRABLE (UG/L AS AG)	ZINC, TOTAL RECOV- ERABLE (UG/L AS ZN)	CYANIDE TOTAL (MG/L AS CN)	PHENOLS TOTAL (UG/L)	METHY- LENE BLUE ACTIVE SUB- STANCE (MG/L)
NOV 1991	TOTAL RECOV- ERABLE (UG/L AS FE)	TOTAL RECOV- BRABLE (UG/L AS PB)	NESE, TOTAL RECOV- ERABLE (UG/L AS MN)	TOTAL RECOV- ERABLE (UG/L AS HG)	NIUM, TOTAL (UG/L AS SR)	TOTAL RECOV- BRABLE (UG/L AS AG)	TOTAL RECOV- BRABLE (UG/L AS ZN)	TOTAL (MG/L AS CN)	TOTAL (UG/L)	LENE BLUB ACTIVE SUB- STANCE (MG/L)
NOV 1991 05 DEC 30	TOTAL RECOV- ERABLE (UG/L	TOTAL RECOV- BRABLE (UG/L	NESE, TOTAL RECOV- BRABLE (UG/L	TOTAL RECOV- ERABLE (UG/L	NIUM, TOTAL (UG/L	TOTAL RECOV- BRABLE (UG/L	TOTAL RECOV- BRABLE (UG/L	TOTAL (MG/L	TOTAL	LENE BLUE ACTIVE SUB- STANCE
NOV 1991 05 DBC 30 FBB 1992 28	TOTAL RECOV- ERABLE (UG/L AS FE)	TOTAL RECOV- BRABLE (UG/L AS PB)	NESE, TOTAL RECOV- ERABLE (UG/L AS MN)	TOTAL RECOV- ERABLE (UG/L AS HG)	NIUM, TOTAL (UG/L AS SR)	TOTAL RECOV- BRABLE (UG/L AS AG)	TOTAL RECOV- BRABLE (UG/L AS ZN)	TOTAL (MG/L AS CN)	TOTAL (UG/L)	LENE BLUE ACTIVE SUB- STANCE (MG/L)
NOV 1991 05 DEC 30 FEB 1992 28 APR 15	TOTAL RECOV- ERABLE (UG/L AS FE)	TOTAL RECOV- BRABLE (UG/L AS PB)	NESE, TOTAL RECOV- ERABLE (UG/L AS MN)	TOTAL RECOV- ERABLE (UG/L AS HG) <0.10	NIUM, TOTAL (UG/L AS SR)	TOTAL RECOV- BRABLE (UG/L AS AG) <1	TOTAL RECOV- BRABLE (UG/L AS ZN)	TOTAL (MG/L AS CN) <0.010	TOTAL (UG/L)	LENE BLUE ACTIVE SUB- STANCE (MG/L)
NOV 1991 05 DEC 30 FBB 1992 28	TOTAL RECOV- BRABLE (UG/L AS FE) 3600	TOTAL RECOV- BRABLE (UG/L AS PB)	NESE, TOTAL RECOV- BRABLE (UG/L AS MN)	TOTAL RECOV- ERABLE (UG/L AS HG) <0.10	NIUM, TOTAL (UG/L AS SR)	TOTAL RECOV- BRABLE (UG/L AS AG) <1	TOTAL RECOV- ERABLE (UG/L AS ZN)	TOTAL (MG/L AS CN) <0.010	TOTAL (UG/L) 1	LENE BLUE ACTIVE SUB- STANCE (MG/L)

50027750 RIO GRANDE DE ARECIBO ABOVE ARECIBO, PR

LOCATION.--Lat 18°25'22", long 66°41'58", Hydrologic Unit 21010002, 0.5 mi (0.8 km) upstream from Río Tanamá, 3.6 mi (5.8 km) south of Arecibo and 4.9 mi (7.9 km) above mouth, and 10.4 mi (16.7 km) downstream from Lago Dos Bocas.

DRAINAGE AREA.--200 mi² (520 km²), approximately, of which an undetermined amount does not contribute directly to surface runoff.

WATER-DISCHARGE RECORDS

PERIOD OF RECORD. -- April 1982 to current year.

GAGE. -- Water-stage recorder. Elevation of gage is 30 ft (9 m), from topographic map.

REMARKS.--Records fair except those for estimated daily discharges, which are poor. Flow regulated by Lago Dos Bocas Dam 10.4 mi (16.7 km) upstream from gage. Gage-height and precipitation satellite telemetry at station.

Dam 1	0.4 mi (1	16.7 km)	upstream :	from gage.	. Gage-he	ight and	precipit	ation sate	llite te	lemetry a	t station	•
	DIS	SCHARGE,	CUBIC FRE	T PER SECO		YEAR OC		1 TO SEPTE	MBER 199	2		
DAY	OCT	NOA	DEC	JAN	FEB	MAR	APR	MAY	JUN	JUL	AUG	SEP
1	87	e210	188	191	e 99	141	34	241	722	422	611	65
2	217	e2 30	51	162	e96	e4 0	35	83	1210	407	597	101
3	446	e420	99	181	e4 0	e37	66	262	737	350	367	436
4	382	e450	62	154	e33	e34	109	185	618	199	478	293
5	94	e320	72	95	e233	e560	162	281	519	222	427	311
6 7	61	536	111	614	337	e45	295	282	377 574	595 236	351 397	67 38
8	49 165	609 532	113 93	542 536	406 e130	e38 e34	120 74	278 432	680	256 257	89	84
ğ	114	219	84	634	e47	e40	346	95	638	271	186	440
10	137	422	44	516	e130	87	805	51	665	214	548	666
11	312	328	36	307	223	112	748	358	669	358	468	653
12	96	231	34	121	453	e560	245	292	674	378	123	129
13	237	502	38	448	135	e740	55	248	643	591	151	68
14	333	656	43	214	e35	e160	46	405 120	388 625	98 61	133 46	64 89
15	136	284	176	334	e33	e250	132					
16	230	114	43	159	e34	e540	130	84	658	391	255	115
17	47	76	39	78	e120	157	134	80 566	692 727	408 301	e110 e98	316 130
18 19	42 41	339 139	37 35	225 132	e45 e41	58 57	49 300	730	825	314	e200	313
20	112	175	38	134	e39	836	543	576	113	361	e300	247
21	419	83	53	124	e37	e1200	745	618	302	450	e580	145
22	516	182	46	40	e35	219	862	828	719	324	e480	359
23	266	52	63	228	e34	46	565	1650	674	341	e58	210
24	229	42	54	e173	e170	93	541	2030	242	360	e 400	513
25	415	42	51	e 60	e 80	42	196	993	120	90	608	593
26	99	39	77	e47	e52	37	81	811	78	51	485	304
27	86	38	113	e2 12	e34	350	409	906	64	216	354	92
28	168	37	164	e66	34	80	354	690	148	420	81	201
29	313	36	135	e181	38	91	463	588 476	199	447 482	38 33	403 526
30 31	344 658	58	178 430	e460 e251		39 35	191	569	511	126	143	
TOTAL	6851	7401	2800	7619	3223	6758	8835	15808	15811	9741	9195	7971
MRAN	221	247	90.3	246	111	218	294	510	527	314	297	266
MAX	658	656	430	634	453	1200	862	2030	1210	5 9 5	611	666
MIN	41	36	34	40	33	34	34	51	64	51	33	38
AC-FT	13590	14680	5550	15110	6390	13400	17520	31360	31360	19320	18240	15810
CFSM IN.	1.10 1.27	1.23 1.38	.45 .52	1.23 1.42	.56 .60	1.09 1.26	1.47 1.64	2.55 2.94	2.64 2.94	1.57 1.81	1.48 1.71	1.33 1.48
e Ri	stimated											
STATIST	TCS OF M	омтит.У в	RAN DATA B	OR WATER	VRARS 1982	- 1992	RY WATER	YEAR (WY)				
MEAN	726 1984	642 1413	309 570	255 437	241 428	227 351	418 617	699 2000	398 683	280 374	275 474	498 1080
MAX (WY)	1986	1986	1988	1988	1988	1985	1986	1986	1987	1987	1988	1984
MIN	221	247	90.3	167	111	114	207	185	195	161	154	266
(WY)	1992	1992	1992	1989	1992	1987	1984	1989	1990	1990	1990	1992
SUMMARY	Y STATIST	ICS	FOR	1991 CALE	ndar year	I	FOR 1992 V	VATER YEAR		WATER Y	RARS 1982	- 1992
ANNUAL				97499			102013					
YNNUYT				267			279			415 729		1986
	r annual Annual M									279		1992
	DAILY M			1030	May 11		2030	May 24		14800	Mav	18 1985
	DAILY ME			34	Dec 12		33	Feb 4		33		4 1992
	SEVEN-DA		TM.	41	Nov 23		41	Nov 23		41		23 1991
Instant	PANEOUS P	EAR FLOW	ī				3880	May 23		45800		18 1985
	PANEOUS P		E				9.0	3 May 23		18.2		18 1985
	PANEOUS L			400						30	Mar	30 1986
	RUNOFF (193400 1.3			202300 1.3			300700 2.0		
	RUNOFF (18.1			18.9			28.2		
	CENT EXCE			535	_		620			838	-	
	CENT EXCE			219			199			275		
	CENT EXCE			58			40			63		

50027750 RIO GRANDE DE ARECIBO ABOVE ARECIBO, PR--Continued

WATER QUALITY RECORDS

PERIOD OF RECORD. -- WATER YEARS APRIL 1982 TO CURRENT YEAR

DATE	TIME	STREAMFLOW, INSTANTANEOUS (CFS)	SPECIFIC CON- DUCTANCE (UMHOS)	TEMPERA- TURE (DEG C)	DATE	TIME	STREAMFLOW, INSTANTANEOUS (CFS)	SPECIFIC CON- DUCTANCE (UMHOS)	TEMPERA- Ture (Deg C)
APR. 22	1125	121	230	26.0	AUG. 16	0930	92	242	22.5
JUN. 25	1145	43	273	28.0					

50028000 RIO TANAMA NEAR UTUADO, PR

LOCATION.--Lat 18°18'02", long 66°46'58", Hydrologic Unit 21010001, on downstream side of left abutment of bridge on Highway 111, 1.2 mi (1.9 km) upstream from natural tunnel, 1.5 mi (2.4 km) northeast of Angeles, and 5.8 mi (9.3 km) northwest of Utuado.

DRAINAGE AREA. -- 18.4 mi 2 (47.7 km2).

WATER-DISCHARGE RECORDS

PERIOD OF RECORD.--June 1944 to June 1958 (daily stage and two to four measurements per month by Puerto Rico Water Resources Authority), November 1959 to current year.

GAGE.--Water-stage recorder and crest-stage gage. Datum of gage is 938.32 ft (286.000 m) above mean sea level.

Datum of gage was lowered 3.00 ft (0.914 m) on Oct. 1978. Prior to Nov. 17, 1966, non-recording gage and

Nov. 17, 1966 to Sept. 30, 1978 recording gage, both at present site.

REMARKS. -- Records fair except those for estimated daily discharges, which are poor.

Name No Notice Late except those for estimated daily discharges, which are poor.												
DISCHARGE, CUBIC FEET PER SECOND, WATER YEAR OCTOBER 1991 TO SEPTEMBER 1992 DAILY MEAN VALUES												
DAY	OCT	NOV	DEC	JAN	FEB	MAR	APR	MAY	JUN	JUL	AUG	SEP
1	52	73	26	21	18	12	41	27	223	22	47	124
. 2	40	57	26	20	17	12	e28	37	99	22	36	e61
3 4	36 35	51 48	26 26	19 19	16 16	12 11	e24 e20	26 24	74 e66	23 22	32 69	42 39
5	34	45	25	25	16	11	18	23	e58	23	55	43
6 7	34 34	44 43	24 24	203 e34	17 19	11 18	21 29	23 23	55 72	25 26	92 57	45 85
8	91	41	24	26	17	26	25	22	133	34	59	75
9 10	49 40	39 38	24 24	25 23	16 15	21 20	59 65	21 21	e65 91	28 26	52 45	47 74
11	36	37	23	25	14	19	35	45	63	45	41	48
12	34	36	23	26	15	13	30	80	51	31	37	44
13	36	36	22	24	15	12	27	37	45	27	44	43
14 15	34 34	35 35	24 22	22 21	15 15	12 12	23 24	28 26	41 40	33 32	39 35	43 42
16	32	35	22	21	14	11	47	58	38	27	34	42
17 18	30 76	34 33	22 22	21 20	14 14	15 14	40 27	49 99	37 35	27 30	35 33	42 41
19	118	33	21	19	14	12	88	194	34	38	32	42
20	103	32	37	19	14	11	45	e 85	34	78	34	84
21	109	32	35	18	13	10	33	e84	33	46	55	45
22 23	139 82	32 31	24 23	18 18	13 13	10 9.9	31 28	54 199	32 30	36 30	63 72	46 48
24	e63	32	22	19	13	9.6	26	132	29	57	42	41
25	e 56	31	21	18	13	33	25	101	27	46	72	38
26	50	30	21	19	13	22	24	100	27	32	49	37
27 28	46 59	31 28	21 21	18 19	13 12	15 74	24 23	7 4 62	26 25	66 38	42 36	36 52
29	71	28	21	19	12	180	23	76	24	32	34	52
30 31	80 124	27	21 22	19 19		e50 47	25	59 91	23	41 101	33 32	135
TOTAL	1857	1127	739	837	426	745.5	978	1980	1630	1144	1438	1636
MEAN	59.9	37.6	23.8	27.0	14.7	24.0	32.6	63.9	54.3	36.9	46.4	54.5
MAX MIN	139 30	73 27	37 21	203 18	19 12	180 9.6	88 18	199 21	223 23	101 22	92 32	135 36
AC-FT	3680	2240	1470	1660	845	1480	1940	3930	3230	2270	2850	3250
CFSM IN.	3.26 3.75	2.04 2.28	1.30 1.49	1.47 1.69	.80 .86	1.31 1.51	1.77 1.98	3.47 4.00	2.95 3.30	2.01 2.31	2.52 2.91	2.96 3.31
		2.20	1.17	1.03	.00	1.31	1.70	4.00	3.30	2.51	2.31	3.31
	timated			n Wimpn	WHARE 4050	1000	ny wimph					
			EAN DATA FO			•						
MBAN MAX	80.7 195	70.5 159	43.3 121	29.4 50.1	25.2 40.5	24.8 71.2	37.4 142	59.2 193	43.2 116	37.9 65.7	47.6 110	74.7 177
(WY)	1990	1969	1966	1966	1961	1972	1969	1963	1979	1981	1979	1961
MIN	25.4	29.3	21.5	18.0	13.2	11.0	9.70	12.4	16.5	19.5	24.3	27.6
(WY)	1963	1979	1965	1974	1965	1984	1984	1977	1977	1976	1976	1986
SUMMARY	STATIST	CS	FOR 1	1991 CALE	NDAR YEAR	F	OR 1992 WA	TER YEAR		WATER YE	ARS 1960	- 1992
ANNUAL				15176			14537.5			47.9		
ANNUAL HIGHEST	ANNUAL N	ŒAN		41.6			39.7			71.1		1969
LOWEST	ANNUAL ME	BAN								29.9		1983
	DAILY ME			338 11	May 5 Mar 15		223 9.6	Jun 1 Mar 24		2170 6.5		l7 1963 l2 1984
	SEVEN-DAY		IM .	11 12	Mar 13		11			7.4	May	6 1984
	ANEOUS PE						3490	Jan 6		12200	May 1	L8 1985
	'ANBOUS PE						12.46 9.4	Jan 6 Mar 24		17.45 6.6		l8 1985 l2 1977
ANNUAL	RUNOFF ()	C-FT)		30100			28840			34710		
	RUNOFF (C			2.2			2.16			2.60 35.38		
	RUNOFF ()			30.6 74	0		29.39 74			35.38 84		
50 PERC	ENT EXCE	BDS		34			32			33		
90 PERC	ENT EXCE	SDS		17			15			17		

50028000 RIO TANAMA NEAR UTUADO, PR--Continued

WATER-QUALITY RECORDS

PERIOD OF RECORD .-- Water years 1958 to current year.

PERIOD OF DAILY RECORD. --

SUSPENDED SEDIMENT DISCHARGE: January 1968 to current year.

INSTRUMENTATION .-- US D-49 SEDIMENT SAMPLER SINCE OCTOBER 1968. AUTOMATIC SEDIMENT SAMPLER SINCE 1990

RRMARKS.--Sediment samples were collected by a local observer on a wee.:ly basis and during high flow events.

Estimates for period of missing daily record were made from a sediment transport curve developed from a period of record over 5 years.

EXTREMES FOR PERIOD OF DAILY RECORD.-SEDIMENT CONCENTRATIONS: Maximum daily mean, 20,400 mg/L November 27, 1968; minimum daily mean, 0 mg/L
during water year 1985.
SEDIMENT LOADS: Maximum daily, 167,000 tons (152,000 tonnes) May 18, 1985, minimum daily, 0.0 ton
(0.0 tonne) several days during many years.

EXTREMES FOR CURRENT YEAR.--SEDIMENT CONCENTRATIONS: Maximum daily mean, 1,900 mg/L October 1, 1990; minimum daily mean,

3.0 mg/L several days.

SEDIMENT LOADS: Maximum daily, 16,500 tons (15,000 tonnes) October 17, 1989; minimum daily 0.14 ton (0.13 tonne) several days.

WATER-QUALITY DATA, WATER YEAR OCTOBER 1991 TO SEPTEMBER 1992

DATE	TIMB	DIS- CHARGE, INST. CUBIC FEET PER SECOND	SPB- CIFIC CON- DUCT- ANCB (US/CM)	PH WATER WHOLE FIELD (STAND- ARD UNITS)	TEMPER- ATURE WATER (DEG C)	TUR- BID- ITY (NTU)	OXYGEN, DIS- SOLVED (MG/L)	OXYGEN, DIS- SOLVED (PER- CENT SATUR- ATION)	OXYGEN DEMAND, CHEM- ICAL (HIGH LEVEL) (MG/L)	COLI- FORM, FECAL, 0.7 UM-MF (COLS./ 100 ML)	STREP- TOCOCCI FECAL, KF AGAR (COLS. PER 100 ML)
OCT 1991											
21 DBC	1310	55	142	7.5	22.5	24	8.9	102	<10	2000	1000
17	1030	23	146	7.8	20.5	1.9	6.4	80	<10	97	220
FEB 1992 18	1200	13	175	7.7	22.0	1.2	8.8	99	<10	22	110
APR 09	1020	22	156	7.5	23.0	5.9	9.8	106	<10	K16000	K2000
JUL 08	0840	26	167	6.8	24.5	2.1	8.4	90	<10	270	
SEP											2440
03	1055	43	154	7.1	27.0	10	7.1	84	<10	K590	K110
DATE	HARD- NESS TOTAL (MG/L AS CACO3)	HARD- NESS NONCARB WH WAT TOT FLD MG/L AS CACO3	CALCIUM DIS- SOLVED (MG/L AS CA)	MAGNE- SIUM, DIS- SOLVED (MG/L AS MG)	SODIUM, DIS- SOLVED (MG/L AS NA)	SODIUM AD- SORP- TION RATIO	POTAS- SIUM, DIS- SOLVED (MG/L AS K)	ALKA- LINITY WAT WH TOT PET FIELD MG/L AS CACO3	SULFIDE TOTAL (MG/L AS 8)	SULFATE DIS- SOLVED (MG/L AS SO4)	CHLO- RIDE, DIS- SOLVED (MG/L AS CL)
OCT 1991	NESS TOTAL (MG/L AS CACO3)	NESS NONCARB WH WAT TOT FLD MG/L AS CACO3	DIS- SOLVED (MG/L AS CA)	SIUM, DIS- SOLVED (MG/L AS MG)	DIS- SOLVED (MG/L AS NA)	AD- SORP- TION RATIO	SIUM, DIS- SOLVED (MG/L AS K)	LINITY WAT WH TOT FET FIELD MG/L AS CACO3	TOTAL (MG/L AS S)	DIS- SOLVED (MG/L AS SO4)	RIDE, DIS- SOLVED (MG/L AS CL)
	NESS TOTAL (MG/L AS	NESS NONCARB WH WAT TOT FLD MG/L AS	DIS- SOLVED (MG/L	SIUM, DIS- SOLVED (MG/L	DIS- SOLVED (MG/L	AD- SORP- TION	SIUM, DIS- SOLVED (MG/L	LINITY WAT WH TOT PET FIELD MG/L AS	TOTAL (MG/L	DIS- Solved (MG/L	RIDE, DIS- SOLVED (MG/L
OCT 1991 21 DEC 17	NESS TOTAL (MG/L AS CACO3)	NESS NONCARB WH WAT TOT FLD MG/L AS CACO3	DIS- SOLVED (MG/L AS CA)	SIUM, DIS- SOLVED (MG/L AS MG)	DIS- SOLVED (MG/L AS NA)	AD- SORP- TION RATIO	SIUM, DIS- SOLVED (MG/L AS K)	LINITY WAT WH TOT FET FIELD MG/L AS CACO3	TOTAL (MG/L AS S)	DIS- SOLVED (MG/L AS SO4)	RIDE, DIS- SOLVED (MG/L AS CL)
OCT 1991 21 DEC 17 FRB 1992 18	NESS TOTAL (MG/L AS CACO3)	NESS NONCARB WH WAT TOT FLD MG/L AS CACO3	DIS- SOLVED (MG/L AS CA)	SIUM, DIS- SOLVED (MG/L AS MG)	DIS- SOLVED (MG/L AS NA)	AD- SORP- TION RATIO	SIUM, DIS- SOLVED (MG/L AS K)	LINITY WAT WH TOT PET FIELD MG/L AS CACO3	TOTAL (MG/L AS S)	DIS- SOLVED (MG/L AS SO4)	RIDE, DIS- SOLVED (MG/L AS CL)
OCT 1991 21 DRC 17 FEB 1992 18 APR 09	NESS TOTAL (MG/L AS CACO3)	NESS NONCARB WH WAT TOT FLD MG/L AS CACO3	DIS- SOLVED (MG/L AS CA)	SIUM, DIS- SOLVED (MG/L AS MG)	DIS- SOLVED (MG/L AS NA)	AD- SORP- TION RATIO	SIUM, DIS- SOLVED (MG/L AS K)	LINITY WAT WH TOT FET FIRLD MG/L AS CACO3	TOTAL (MG/L AS 8)	DIS- SOLVED (MG/L AS SO4)	RIDE, DIS- SOLVED (MG/L AS CL)
OCT 1991 21 DEC 17 FEB 1992 18	NESS TOTAL (MG/L AS CACO3)	NESS NONCARB WH WAT TOT FLD MG/L AS CACO3	DIS- SOLVED (MG/L AS CA)	SIUM, DIS- SOLVED (MG/L AS MG)	DIS- SOLVED (MG/L AS NA) 7.5	AD- SORP- TION RATIO	SIUM, DIS- SOLVED (MG/L AS K)	LINITY WAT WH TOT FET FIRLD MG/L AS CACO3	TOTAL (MG/L AS 8)	DIS- SOLVED (MG/L AS SO4) 12	RIDE, DIS- SOLVED (MG/L AS CL)

K = non-ideal count

50028000 RIO TANAMA NEAR UTUADO, PR--Continued

WATER-QUALITY DATA, WATER YEAR OCTOBER 1991 TO SEPTEMBER 1992

DATE	FLUO- RIDE, DIS- SOLVED (MG/L AS F)	SILICA, DIS- SOLVED (MG/L AS SIO2)	SOLIDS, SUM OF CONSTI- TUENTS, DIS- SOLVED (MG/L)	SOLIDS, DIS- SOLVED (TONS PER DAY)	RESIDUE TOTAL AT 105 DEG. C, SUS- PENDED (MG/L)	NITRO- GEN, NITRATE TOTAL (MG/L AS N)	NITRO- GEN, NITRITE TOTAL (MG/L AS N)	NITRO- GEN, NO2+NO3 TOTAL (MG/L AS N)	NITRO- GEN, AMMONIA TOTAL (MG/L AS N)	NITRO- GEN, ORGANIC TOTAL (MG/L AS N)
OCT 1991										
21	<0.10	20	89	13.2	19	0.780	0.020	0.800	0.040	
DEC 17					1	0.670	0.010	0.680	0.010	
FRB 1992					_					
18 APR					7		<0.010	0.590	0.020	
09	0.20	24	111	6.59	14	0.650	0.020	0.670	0.040	
JUL 08					16	0.690	0.010	0.700	0.020	0.18
SEP					16	0.690	0.010	0.700	0.020	0.10
03	<0.10	22	105	12.2	<1		<0.010	0.890	0.010	
DATE	NITRO- GEN, AM- MONIA + ORGANIC TOTAL (MG/L AS N)	NITRO- GEN, TOTAL (MG/L AS N)	NITRO- GEN, TOTAL (MG/L AS NO3)	PHOS- PHORUS TOTAL (MG/L AS P)	ARSENIC TOTAL (UG/L AS AS)	BARIUM, TOTAL RECOV- ERABLE (UG/L AS BA)	BORON, TOTAL RECOV- ERABLE (UG/L AS B)	CADMIUM TOTAL RECOV- ERABLE (UG/L AS CD)	CHRO- MIUM, TOTAL RECOV- ERABLE (UG/L AS CR)	COPPER, TOTAL RECOV- ERABLE (UG/L AS CU)
OCT 1991										
21	<0.20			0.040	<1	<100	10	<1	3	20
DEC 17 FEB 1992	<0.20			0.020						
18	0.20	0.90	4.0	0.040						
APR 09					_			_		
JUL	<0.20			<0.010	<1	<100	<10	<1	<1	10
08 SRP										
03	<0.20			0.020						
DATE	IRON, TOTAL RECOV- ERABLE (UG/L AS FE)	LRAD, TOTAL RECOV- ERABLE (UG/L AS PB)	MANGA- NESE, TOTAL RECOV- ERABLE (UG/L AS MN)	MERCURY TOTAL RECOV- ERABLE (UG/L AS HG)	SELE- NIUM, TOTAL (UG/L AS SE)	SILVER, TOTAL RECOV- ERABLE (UG/L AS AG)	ZINC, TOTAL RECOV- ERABLE (UG/L AS ZN)	CYANIDE TOTAL (MG/L AS CN)	PHENOLS TOTAL (UG/L)	METHY- LENE BLUE ACTIVE SUB- STANCE (MG/L)
OCT 1991		_								
21 DEC	2200	2	100	<0.10	<1	<1	<10	<0.010	2	0.02
17 FEB 1992										
18										
09	490	<1	40	<0.10	<1	<1	<10	<0.010	2	0.03
JUL 08 SEP					***					
03				~ ~						

RIO GRANDE DE ARECIBO BASIN
50028000 RIO TANAMA NEAR UTUADO, PR--Continued

DAY	MEAN DISCHARGE (CFS)	MEAN CONCEN- TRATION (MG/L)	SEDIMENT DISCHARGE (TONS/DAY)	MEAN DISCHARGE (CFS)	MEAN CONCEN- TRATION (MG/L)	SEDIMENT DISCHARGE (TONS/DAY)	MEAN DISCHARGE (CFS)	MEAN CONCEN- TRATION (MG/L)	SEDIMENT DISCHARGE (TONS/DAY)
		OCTOBER		P	IOVEMBER		1	DECEMBER	
1	52	65	18	73	97	21	26	6	. 42
2	40	27	3.1	57	40	6.7	26	6	.45
3	36	21	2.0	51	12	1.7	26	7	.51
4	35	20	1.9	48	7	. 92	26	7	. 47
5	34	17	1.5	45	5	.63	25	5	. 33
6	34	11	1.0	44	4	.49	24	4	.26
7	34	9	. 85	43	5	.58	24	3	.22
8	91	315	404	41	6	.66	24	3	.22
9	49	38	5.7	39	7	.75	24	4	. 25
10	40	21	2.4	38	7	.71	24	4	.24
11	36	20	1.9	37	6	. 64	23	4	.24
12	34	19	1.7	36	6	.58	23	4	.24
13	36	14	1.4	36	6	.58	22	4	. 24
14	34	10	. 92	35	6	.57	24	4	.24
15	34	8	. 75	35	6	.56	22	4	.24
16	32	6	. 56	35	6	.56	22	4	. 24
17	30	5	.40	34	6	.55	22	4	. 27
18	76	279	243	33	6	.53	22	5	.30
19	118	448	499	33	5	.43	21	5	. 29
20	103	515	273	32	3	.30	37	29	4.8
21	109	360	387	32	3	.26	35	28	3.6
22	139	492	598	32	3	.29	24	8	. 55
23	82	114	27	31	4	.33	23	5	.31
24	e63	38	e 6.9	32	4	.34	22	4	. 27
25	e 56	30	e4.4	31	4	.37	21	6	.39
26	50	38	4.9	30	5	.40	21	9	.52
27	46	35	4.4	31	5	.39	21	11	. 62
28	59	83	25	28	5	.43	21	12	. 68
29	71	140	64	28	6	.46	21	12	. 66
30	80	141	46	27	6	.43	21	10	.57
31	124	393	362				22	7	. 43
TOTAL	1857		2992.68	1127		43.14	739		19.07

e Estimated

RIO GRANDE DE ARECIBO BASIN

50028000 RIO TANAMA NEAR UTUADO, PR--Continued

DAY	MEAN DISCHARGE (CFS)	MEAN CONCEN- TRATION (MG/L)	SEDIMENT DISCHARGE (TONS/DAY)	MEAN DISCHARGE (CFS)	MEAN CONCEN- TRATION (MG/L)	SEDIMENT DISCHARGE (TONS/DAY)	MEAN DISCHARGE (CFS)	MEAN CONCEN- TRATION (MG/L)	SEDIMENT DISCHARGE (TONS/DAY)
		JAN UARY		1	BBRUARY			MARCH	
1	21	5	.31	18	7	.36	12	2	.06
2	20	4	. 23	17	7	.32	12	2	.06
3	19	4	. 23	16	5	.24	12	2	. 06
4	19	5	.28	16	5	.22	11	2	. 07
5	25	12	1.0	16	5	.22	11	3	.10
6	203	481	1190	17	5	.24	11	4	. 13
7	e34	29	e3.0	19	5	.27	18	9	. 62
8	26	12	. 83	17	6	.29	26	29	6.9
9	25	10	. 63	16	7	.32	21	11	. 67
10	23	8	.51	15	8	.32	20	7	. 60
11	25	7	.48	14	7	.29	19	9	. 52
12	26	10	.70	15	6	.25	13	6	.21
13	24	12	.74	15	5	.21	12	6	.20
14	22	13	.79	15	4	.18	12	5	. 18
15	21	12	. 67	15	4	.16	12	4	. 14
16	21	8	. 46	14	4	.16	11	4	. 12
17	21	5	. 29	14	4	.16	15	4	. 15
18	20	4	.21	14	4	.15	14	4	. 15
19	19	4	.20	14	4	.14	12	3	. 11
20	19	4	.21	14	25	.86	11	3	. 09
21	18	4	.21	13	4	.14	10	3	. 08
22	18	4	.20	13	5	.18	10	2	.06
23	18	4	.20	13	6	.22	9.9	2	.06
24	19	4	.20	13	6	.22	9.6	2	.06
25	18	3	. 18	13	5	.20	33	47	16
26	19	3	. 15	13	5	.18	22	8	.58
27	18	3	. 14	13	4	.15	15	5	. 25
28	19	2	. 12	12	3	.11	74	293	252
29	19	2	. 13	12	2	.08	180	868	2810
30	19	4	.21				e50	86	e12
31	19	6	.30				47	77	20
TOTAL	837		1203.81	426		6.84	745.5		3122.23

e Estimated

50028000 RIO TANAMA NEAR UTUADO, PR--Continued

	MEAN DI SCHARGE	MEAN CONCEN- TRATION	SEDIMENT DISCHARGE	MEAN DISCHARGE	MRAN CONCEN- TRATION	Sediment Discharge	MEAN DI SCHARGE	MEAN CONCEN- TRATION	SEDIMENT DISCHARGE
DAY	(CFS)	(MG/L)	(TONS/DAY)	(CFS)	(MG/L)	(TONS/DAY)	(CFS)	(MG/L)	(TONS/DAY)
		APRIL			MAY			JUNE	
1	41	35	5.0	27	10	.75	223	1010	4060
2	e28	19	e1.4	37	10	.97	99	257	80
3	e24	17	el.1	26	10	.70	74	56	11
4	e20	13	e.66	24	10	.63	e66	28	e5.0
5	18	10	.49	23	10	. 62	e58	18	e2.8
6	21	8	.48	23	10	.59	55	12	1.8
7	29	8	.58	23	8	.49	72	100	46
8	25	8	. 57	22	6	.36	133	517	1030
9	59	129	62	21	4	.26	e65	79	e16
10	65	96	24	21	4	.27	91	217	114
11	35	25	2.8	45	67	21	63	69	14
12	30	13	1.1	80	451	372	51	29	4.1
13	27	11	. 85	37	33	3.9	45	27	3,2
14	23	10	. 59	28	16	1.2	41	24	2.6
15	24	11	.78	26	14	.94	40	21	2.2
16	47	75	30	58	85	23	38	17	1.8
17	40	31	4.7	49	64	18	37	14	1.4
18	27	13	1.0	99	561	546	35	12	1.1
19	88	301	321	194	1070	1820	34	10	.86
20	45	45	6.0	e 85	124	e35	34	8	.72
21	33	21	1.9	e84	143	e56	33	7	. 65
22	31	19	1.6	54	54	8.6	32	7	.58
23	28	22	1.7	199	1070	827	30	8	. 63
24	26	23	1.6	132	309	129	29	10	.74
25	25	20	1.3	101	185	55	27	10	.75
26	24	15	. 94	100	176	56	27	10	.70
27	24	11	. 67	74	40	8.4	26	10	. 64
28	23	9	. 55	62	19	3.1	25	8	. 53
29	23	8	. 52	76	105	38	24	7	. 44
30	25	9	. 56	59	87	16	23	7	.45
31				91	229	161			
TOTAL	978		476.44	1980		4204.78	1630		5404.69

e Estimated

RIO GRANDE DE ARECIBO BASIN

50028000 RIO TANAMA NEAR UTUADO, PR--Continued

DAY	MEAN DISCHARGE (CFS)	MEAN CONCEN- TRATION (MG/L)	SEDIMENT DISCHARGE (TONS/DAY)	MEAN DI S CHARGE (CFS)	MEAN CONCEN- TRATION (MG/L)	SEDIMENT DISCHARGE (TONS/DAY)	MRAN DISCHARGE (CFS)	MEAN CONCEN- TRATION (MG/L)	SEDIMENT DISCHARGE (TONS/DAY)
		JULY			August		S	eptember	
1 2 3 4 5	22 22 23 22 23	8 9 11 14 17	.48 .52 .62 .77	47 36 32 69 55	38 22 20 179 65	5.2 2.2 1.8 124 14	124 e61 42 39 43	731 71 30 27 26	1150 e14 3.5 2.8 3.0
6 7 8 9 10	25 26 34 28 26	18 18 25 14 13	1.2 1.2 2.7 1.1	92 57 59 52 45	229 74 81 51 25	124 12 25 8.2 3.3	45 85 75 47 74	32 386 123 41 205	4.1 275 39 5.6 149
11 12 13 14 15	45 31 27 33 32	55 23 17 22 31	15 2.1 1.2 3.0 3.0	41 37 44 39 35	20 14 35 40 28	2.2 1.4 9.1 4.5 2.7	48 44 43 43	44 29 22 20 17	6.2 3.4 2.6 2.3 1.8
16 17 18 19 20	27 27 30 38 78	23 14 17 30 200	1.6 .95 1.4 4.6 133	34 35 33 32 34	16 17 20 21 21	1.4 1.6 1.8 1.8	42 42 41 42 84	14 21 48 66 293	1.5 3.2 5.6 16 160
21 22 23 24 25	46 36 30 57 46	33 12 12 106 53	4.4 1.1 .91 49 8.3	55 63 72 42 72	118 190 121 46 906	39 55 41 5.7 442	45 46 48 41 38	48 41 34 31 25	6.6 6.5 4.0 3.4 2.5
26 27 28 29 30 31	32 66 38 32 41 101	22 183 24 18 38 341	1.9 144 2.7 1.5 7.0 351	49 42 36 34 33 32	47 27 19 17 17	7.8 3.0 1.8 1.6 1.5	37 36 52 52 135	15 10 78 61 1030	1.5 .98 33 12 1140
TOTAL YBAR	1144 14537.5		748.17 22228.63	1438		947.7	1636		3059.08

e Estimated

50028000 RIO TANAMA NEAR UTUADO, PR--Continued

WATER QUALITY DATA, WATER YEAR OCTOBER 1991 TO SEPTEMBER 1992

PARTICLE-SIZE DISTRIBUTION OF SUSPENDED SEDIMENT

DATE	TIME	DIS- CHARGE, INST. CUBIC FEET PER SECOND	SEDI - MENT, SUS- PENDED (MG/L)	SEDI- MENT, DIS- CHARGE, SUS- PENDED (T/DAY)	SED. SUSP. FALL DIAM. PERCENT FINER THAN .002 MM	SED. SUSP. FALL DIAM. PERCENT FINER THAN .004 MM	SED. SUSP. FALL DIAM. PERCENT FINER THAN .008 MM
ост 1991							
18	1610	292	7490	5900	7	12	17
20	1900	197	3780	2010	12	24	32
31	1543	240	3220	2090	19	26	37
JAN 1992							
06	0220	1330	16000	56300	3	7	11
MAY							
12	1630	545	4070	5990	28	39	48
23 JUN	0915	289	1830	1430	42	48	42
01	1645	3400	7830	71900	24	35	42
JUL	1013	3400	7030	71300	••	33	
31	1445	535	3720	5370	30	36	44
SEP							
01	1550	988	7160	19100	21	23	32
07	1728	300	3700	3000	36	41	48
19	2355	254	2320	1590	36	43	50
30	1610	821	10100	22400	20	29	37
DATE	SED. SUSP. FALL DIAM. PERCENT FINER THAN .016 MM	SED. SUSP. FALL DIAM. PERCENT FINER THAN .031 MM	SED. SUSP. SIEVE DIAM. PERCENT FINER THAN .062 MM	SED. SUSP. SIEVE DIAM. PERCENT FINER THAN .125 MM	SED. SUSP. SIEVE DIAM. PERCENT FINER THAN .250 MM	SED. SUSP. SIEVE DIAM. PERCENT FINER THAN .500 MM	SED. SUSP. SIEVE DIAM. PERCENT FINER THAN 1.00 MM
OCT 1991							
18 20	27 47	39 62	58 81	75 92	89 97	98	99
31	53	64	83	92	97 98	99 99	99.5
JAN 1992	33	0.6	63	93	30	33	99.6
06	17	25	39	54	77	93	99
MAY					• •		
12	63	73	87	95	98	99	100
23	59	64	92	97	99	99.7	99.8
JUN							
01	53	65	80	90	96	99	99.8
JUL							
31 Sep	55	66	77	83	97	99	99.8
01	39	50	60	72	84	94	99
07	61	72	91	97	98	99	100
19	58	65	79	91	97	99	100
30	50	56	70	85	93	97	99

50028000 RIO TANAMA NEAR UTUADO--Continued

WATER QUALITY DATA, WATER YEAR OCTOBER 1991 TO SEPTEMBER 1992

SILT AND CLAY PERCENT OF SUSPENDED SEDIMENT

DATE	TIME	STREAM- FLOW, INSTAN- TANEOUS (CFS)	SEDI- MENT, SUS- PENDED (MG/L)	SEDI- MENT, DIS- CHARGE, SUS- PENDED (T/DAY)	SED. SUSP. SIEVE DIAM. PERCENT FINER THAN .062 MM
OCT 1991					
18	1625	457	3340	4120	83
20	1716	361	911	888	86
20	2015	130	3240	1140	94
22	1638	353	2500	2390	80
31	1618	661	3070	5480	72
31	1808	246	1440	957	84
DEC					
02	1310	23	30	1.9	85
MAR 1992					
30	1256	79	70	15	91
APR					
09	0816	22	131	7.8	96
15	1920	231	1770	1100	91
MAY					
12	1610	389	2610	2740	85
18	1028	40	255	27.6	98
18	1840	471	2410	3070	84
18	1920	540	4830	7050	81
18	2020	290	2690	2100	93
23	0800	215	4430	2572	74
23	0855	274	1660	1230	84
JUN					
02	0837	102	268	101	69
JUL					
31	1340	272	2550	1870	58
AUG					
25	1623	255	1540	1060	72
25	1648	493	3100	4120	81
25	1928	107	3900	1130	93
SEP	4554			4 4 5 6	
01	1550	330	1650	1470	79
01	1730	419	4290	4860	90
07 20	2100	253	2100	1430	79
	0115	210	1800	1020	92
30	0802 1520	46	368	46	99 81
30	1240	455	3610	4440	81

50028400 RIO TANAMA AT CHARCO HONDO, PR

LOCATION.--Lat 18°24'52", long 66°42'52", Hydrologic Unit 21010002 on right bank at abandoned power house at Charco Hondo, 1.5 mi (2.4 km) upstream from mouth, and 4 mi (6 km) south of Arecibo.

DRAINAGE ARRA. -- 57.6 mi 2 (149.2 km2).

WATER-DISCHARGE RECORDS

PERIOD OF RECORD. -- April 1969 to June 1971, October 1981 to current year.

GAGE. -- Water-stage recorder and crest-stage gage. Elevation of gage is 60 ft (18 m), from topographic map.

REMARKS.--Records poor. Diversion 0.8 mi (1.3 km) upstream for municipal supply of Arecibo.

	DIS	SCHARGE,	CUBIC FEET		OND, WATER		TOBER 1991	TO SEPTE	MBER 199	2		
DAY	OCT	NOV	DEC	JAN	FEB	MAR	APR	MAY	JUN	JUL	AUG	. SEP
1	95	283	53	49	41	33	e 97	e 60	412	67	325	165
2	95	176	54	46	40	32	e70	€80	236	67	117	123
3	83	e 110	53	44	42	32	e 54	e 62	e 150	67	68	68
4	79	e 98	53	43	51	32	e4 5	e53	e130	74	87	61
5	76	e92	52	106	42	32	e4 3	e 50	e120	85	102	58
6	74	e87	51	e288	41	31	e47	e50	e115	67	126	66
7	77	e96	50	e150	43	34	e64	e50	e150	65	102 69	104 152
8 9	131 119	e125 e94	50 50	e70 e58	41 39	40 55	e56 e120	e48 e47	e270 e140	67 71	93	104
10	106	e82	50	e55	39	33	166	e47	e190	67	70	111
11	90	e 78	49	55	38	42	272	e 90	e150	76	58	102
12	84	e74	49	65	38	32	e120	e170	e120	80	51	6 6
13	82	e71	48	56	37	30	e70	e101	e110	68	43	59
14	110	e.69	50	52	37	29	e 60	e 62	e100	68	62	e78
15	82	e 68	48	49	37	29	e 90	e 57	e 90	73	44	e 90
16	77	e 68	47	48	37	30	77	e75	e 86	70	44	107
17	74	e67	49	4.8	37	32	89	90	e82	70	e45	73
18	112	e65	47	47	36	36	82	148	73 70	69 73	49	67 63
19 20	195 213	e64 e63	46 52	46 45	36 36	30 31	144 e115	366 239	68	132	45 43	207
21	229	e62	100	44	34	31	€80	e212	67	110	57	116
22	234	e62	56	44	34	31	e70	229	66	96	73	69
23	181	e61	51	44	34	31	e63	483	65	71	115	101
24	113	e 60	4.8	44	35	31	e58	407	66	e58	144	127
25	96	e 62	47	44	35	48	e 55	235	68	112	106	76
26	91	e58	46	45	36	98	e54	273	67	63	96	83
27	91	57	46	43	35	36	e52	198	6 6	92	100	63
28	95	57	4.6	43	34	73	e50	148	66	89	70	59
29	100	57	46	43	34	358	e50	166	66	61	58	94
30 31	164 257	5 4	45 45	42 42		209 76	e 55	148 224	65 	58 251	52 49	180
TOTAL	3705	2520	1577	1898	1099	1697	2468	4668	3524	2537	2563	2892
MBAN	120	84.0	50.9	61.2	37.9	54.7	82.3	151	117	81.8	82.7	96.4
MAX	257	283	100	288	51	358	272	483	412	251	325	207
MIN	74	54	45	42	34	29	43	47	65	58	43	58
AC-FT	7350	5000	3130	3760	2180	3370	4900	9260	6990	5030	5080	5740
CFSM IN.	2.07 2.39	1.46 1.63	.88 1.02	1.06 1.23	.66 .71	.95 1.10	1.43 1.59	2.61 3.01	2.04 2.28	1.42 1.64	1.44 1.66	1.67 1.87
	stimated											
STATIST	rics of M	ONTHLY M	BAN DATA F	OR WATER	YEARS 1969	- 1992,	BY WATER	YBAR (WY)	1			
MEAN	171	144	79.2	53.0	44.9	39.2	70.9	139	89.1	70.0	76.6	114
MAX	335	260	219	90.8	85.1	70.0	141	371	179	120	125	216
(WY)	1990	1982	1982	1982	1971	1971	1986	1986	1970	1969	1991	1984
MIN (WY)	72.1 1983	71.5 1988	36.4 1989	22.3 1989	16.7 1989	16.6 1988	25.9 1989	15.8 1989	23.3 1989	22.0 1989	37.4 1987	59.7 1986
GIIMMADA	Y STATIST	тса	POD 1	1991 CATE	NDAR YEAR		OR 1992 WA	700 VV10		WATED VE	ARS 1969	- 1992
		ics	FOR .		MUAR IBAK	F		NAGE NGE		WALLA ID	ARB 1303	- 1336
ANNUAL				32091 87.9			31148 85.1			88.1		
	r annual i									124		1986
	ANNUAL M									51.3		1989
	DAILY M			479	May 5		483	May 23		2500		7 1985
	DAILY ME		M	35 36	Apr 22 Apr 18		29 31	Mar 14 Mar 13		4.2 5.4		28 1989 22 1989
	FANEOUS P			30	Wht 19		2920	Mar 29		15000		18 1985
	TANEOUS P							Mar 29		17.95		18 1985
	FANBOUS LA						29	Mar 14		3.3		28 1989
ANNUAL	RUNOFF (AC-FT)		63650			61780			63820	_	
	RUNOFF (1.5			1.48			1.53		
	RUNOFF (20.7	3		20.12			20.78		
	CENT EXCE: CENT EXCE:			154			151			180		
	CENT BYCE			69 41			66 37			65 27		
JU PAR	COMI BACE	200		41			31			41		

50029000 RIO GRANDE DE ARECIBO AT CENTRAL CAMBALACHE, PR

WATER-QUALITY RECORDS

LOCATION.--Lat 18°27'20", long 66°42'10", Hydrologic Unit 21010002, at bridge on unimproved road, about 500 ft (152 m) upstream from Central Cambalache, near Highway 2, 8.3 mi (13.4 km) downstream from Dos Bocas Reservoir, 1.9 mi (3.1 km) downstream from Río Tanamá, and 1.6 mi (2.6 km) southeast of Arecibo.

DRAINAGE AREA. -- 200 mi² (520 km²), approximately.

PERIOD OF RECORD. -- Water years 1963-66, 1969 to current year.

WATER-QUALITY DATA, WATER YEAR OCTOBER 1991 TO SEPTEMBER 1992

		MALI	PK-GOVUT1.1	DATA, WA	MAGI NGT	OCTOBER	1991 10 56	FIEMDER I	. 334		
DATE	TIME	DIS- CHARGE, INST. CUBIC FERT PER SECOND	SPB- CIFIC CON- DUCT- ANCE (US/CM)	PH WATER WHOLE FIELD (STAND- ARD UNITS)	TEMPER- ATURE WATER (DEG C)	TUR- BID- ITY (NTU)	OXYGEN, DIS- SOLVED (MG/L)	OXYGEN, DIS- SOLVED (PER- CENT SATUR- ATION)	OXYGEN DEMAND, CHEM- ICAL (HIGH LEVEL) (MG/L)	COLI- FORM, FECAL, 0.45 UM-MF (COLS./ 100 ML)	STREP- TOCOCCI FECAL, (COLS. PER 100 ML)
OCT 1991											
29 JAN 1992	1045	202	240	7.9	25.0	12	7.2	84	<10	K1200	310
08	1115	157	258	7.6	23.5	96	6.8	78	14	K1200	740
FRB											
28 Jun	0945	63	299	7.8	23.5	1.3	8.8	96	12	230	500
26	0945	148	276	7.7	27.5	5.0	7.0	80	<10	650	K180
AUG	0313	240	2,0		27.3	3.0	,		120	020	
19	1035	112	281	7.8	26.5	4.3	6.3	72	<10	K7200	900
DATE	HARD- NESS TOTAL (MG/L AS CACO3)	HARD- NESS NONCARB WH WAT TOT FLD MG/L AS CACO3	CALCIUM DIS- SOLVED (MG/L AS CA)	MAGNE- SIUM, DIS- SOLVED (MG/L AS MG)	SODIUM, DIS- SOLVED (MG/L AS NA)	SODIU AD- SORP- TION RATIO	SIUM, DIS-	ALKA- LINITY WAT WH TOT FET FIELD MG/L AS CACO3	SULFIDE TOTAL (MG/L AS S)	SULFATE DIS- SOLVED (MG/L AS SO4)	CHLO- RIDE, DIS- SOLVED (MG/L AS CL)
OCT 1991											
29	110		35	5.0	8.7	0.	4 1.9	94	<0.5	11	12
JAN 1992											
08								90			
FEB 28								120			
JUN								120			
26	120		40	5.9	8.7	0.	3 1.7	110	<0.5	11	10
AUG											
19	120		40	5.8	8.9	0.	3 1.5	120		11	12
	R S	IDE, DI DIS- SO OLVED (1	LICA, SUM IS- CON DLVED TUR MG/L D	STI- I NTS, SC IS- (T	IDS, TOT DIS- AT DLVED DEG ONS SU	105 . C, N s-	GEN, G ITRATE NIT TOTAL TO	EN, G RITE NO2 TAL TO	EN, G +NO3 AMM TAL TO	EN, C KONIA ORC TAL TO	ITRO- GEN, GANIC OTAL 4G/L
											3 N)
			. ,			•		•	•		-
	1991)	0.10	18	148 8	0.8	8	0.520 0	.010 0	.530 0	.030	
Jan	1992					-					
FEB	3					83	0.840 0	.070 0	.910 0	.120	0.28
	3					1	<0	.010 0	.280 0	.010	
26 AUG	5	0.30	16	160 6	3.8	20	<0	.010 0	.560 0	.030	
	·	0.20	16	166 5	0.2	11	<0	.010 0	.350 0	.030	

K = non-ideal count

50029000 RIO GRANDE DE ARECIBO AT CENTRAL CAMBALACHE, PR--Continued WATER-QUALITY DATA, WATER YEAR OCTOBER 1991 TO SEPTEMBER 1992

DATE	NITRO- GEN, AM- MONIA + ORGANIC TOTAL (MG/L AS N)	NITRO- GEN, TOTAL (MG/L AS N)	NITRO- GEN, TOTAL (MG/L AS NO3)	PHOS- PHORUS TOTAL (MG/L AS P)	ARSENIC TOTAL (UG/L AS AS)	BARIUM, TOTAL RECOV- ERABLE (UG/L AS BA)	BORON, TOTAL RECOV- ERABLE (UG/L AS B)	CADMIUM TOTAL RECOV- ERABLE (UG/L AS CD)	CHRO- MIUM, TOTAL RECOV- ERABLE (UG/L AS CR)	COPPER, TOTAL RECOV- ERABLE (UG/L AS CU)
OCT 1991										
29 JAN 1992	<0.20	~-		0.040	<1	<100	40	<1	1	30
08 FRB	0.40	1.3	5.8	0.120						
28 JUN	<0.20	~-		0.030						
26	<0.20			0.020	<1	<100	20	<1	<1	<10
AUG 19	<0.20	~-		<0.010						
DATE	IRON, TOTAL RECOV- ERABLE (UG/L AS FE)	LEAD, TOTAL RECOV- BRABLE (UG/L AS PB)	MANGA - NESE, TOTAL RECOV- BRABLE (UG/L AS MN)	MERCURY TOTAL RECOV- BRABLE (UG/L AS HG)	SELE- NIUM, TOTAL (UG/L AS SE)	SILVER, TOTAL RECOV- ERABLE (UG/L AS AG)	ZINC, TOTAL RECOV- ERABLE (UG/L AS ZN)	CYANIDE TOTAL (MG/L AS CN)	PHENOLS TOTAL (UG/L)	METHY- LENE BLUE ACTIVE SUB- STANCE (MG/L)
OCT 1991										
29	530	4	30	<0.10	<1	<1	20	<0.010	<1	0.03
JAN 1992 08										
FRB 28										
JUN 26	330	<1	60	<0.10	∢1	<1	<10	<0.010	<1	0.01
AUG 19										
				PRSTICI	DE ANALYS	ES				
DATE	TIME	PCB,	ALDRIN,	CHLOR- DANE,				DI-		
		TOTAL (UG/L)	TOTAL (UG/L)	TOTAL (UG/L)	DDD, TOTAL (UG/L)	DDE, TOTAL (UG/L)	DDT, TOTAL (UG/L)	AZINON, TOTAL (UG/L)	DI- BLDRIN TOTAL (UG/L)	ENDO- SULFAN, TOTAL (UG/L)
JUN 1992	0045	TOTAL (UG/L)	TOTAL (UG/L)	TOTAL (UG/L)	TOTAL (UG/L)	TOTAL (UG/L)	TOTAL (UG/L)	AZINON, TOTAL (UG/L)	BLDRIN TOTAL (UG/L)	SULFAN, TOTAL (UG/L)
JUN 1992 26	0945	TOTAL	TOTAL	TOTAL	TOTAL	TOTAL	TOTAL	AZINON, TOTAL	BLDRIN TOTAL	SULFAN, TOTAL
	ENDR WAT UNFL TE RE (UG/	TOTAL (UG/L) <0.1 IN ER TRD ETHI C TOT	TOTAL (UG/L) <0.010 HBP ON, CHL	TOTAL (UG/L) <0.1 TA- CHL OR, BPOX AL TOT	TOTAL (UG/L) <0.010 TA- OR IDE LIND AL TOT	TOTAL (UG/L) <0.010 MALL AND THIC	TOTAL (UG/L) <0.010 MET A- OX ON, CHL	AZINON, TOTAL (UG/L) <0.01 H- MET Y- PAR OR, THI AL TOT	ELDRIN TOTAL (UG/L) <0.010 HYL A- ON, MIR AL TO	SULFAN, TOTAL (UG/L)
26 DA	ENDR WAT UNFL TE RE (UG/	TOTAL (UG/L) <0.1 IN ER TRD ETHI C TOT L) (UG	TOTAL (UG/L) <0.010 HBP ON, CHL AL TOT /L) (UG	TOTAL (UG/L) <0.1 HEP TA- CHL OR, BPOX AL TOT /L) (UG	TOTAL (UG/L) <0.010 TA- OR IDE LIND (AL TOT (/L) (UG	TOTAL (UG/L) <0.010 **ANAL ANR THI AL TOT; //L) (UG,	TOTAL (UG/L) <0.010 A- OX ON, CHL AL TOT/L) (UG	AZINON, TOTAL (UG/L) <0.01 H- MET Y- PAR OR, THI AL TOT /L) (UG	ELDRIN TOTAL (UG/L) <0.010 HYL A- ON, MIR AL TO /L) (UG	SULFAN, TOTAL (UG/L) <0.010 EX, TAL
DA DA	ENDR WAT UNFL TE RE (UG/ 92 . <0.	TOTAL (UG/L) <0.1 IN ER TRD ETHI C TOT L) (UG 010 <0 NAF TE LEN A- POI ON, CHIL AL TOT	TOTAL (UG/L) <0.010 HBP ON, CHI AL TOT /L) (UG .01 <0. H- A- BS, Y- PE OR. THA AL TOT	TOTAL (UG/L) <0.1 TA- CHL OR, BPOX AL TOT /L) (UG 010 <0. R- TO NE APHE AL TOT AL TOTAL	TOTAL (UG/L) <0.010 TA- OR IDE LIND (AL TOT (/L) (UG 010 <0.	TOTAL (UG/L) <0.010 MALL ANE THICAL TOTAL (UG, UG, UG, UG, UG, UG, UG, UG, UG, UG,	TOTAL (UG/L) <0.010 .0.010 MBT A- OX ON, CHL AL TOT /L) (UG .01 <0	AZINON, TOTAL (UG/L) <0.01 H- MET Y- PAR OR, THI AL TOT /L) (UG .01 <0	ELDRIN TOTAL (UG/L) <0.010 HYL A- ON, MIR AL TOT CUG .01 <0	SULFAN, TOTAL (UG/L) <0.010 EX, TAL /L) .01
26 DA JUN 19 26	ENDR WAT UNFL TE RE (UG/ 92 . <0. PAR THI TE TOT (UG	TOTAL (UG/L) <0.1 IN ER TRD ETHI C TOT L) (UG 010 <0 NAF TE LEN A- POI ON, CHI AL TOT /L) (UG/	TOTAL (UG/L) <0.010 HEP ON, CHL AL TOT /L) (UG .01 <0. H- A- ES, Y- PE OR. THA AL L) (UG	TOTAL (UG/L) <0.1 HEP TA - CHL OR, BPOX AL TOT /L) (UG 010 <0. R- TO NE APHE AL TOT /L) (UG	TOTAL (UG/L) <0.010 TA- OR IDR LIND AL TOT //L) (UG 010 <0.	TOTAL (UG/L) <0.010 MALL ANR THICAL TOTAL (UG/L) 010 <0 AL TOTAL (UG/L) 1- 2,4 ON TOTAL (UG/L) (UG/L) (UG/L)	TOTAL (UG/L) <0.010 A- OX ON, CHL AL TOT /L) (UG .01 <0	AZINON, TOTAL (UG/L) <0.01 H- MRT Y- PAR OR, THI AL TOT /L) (UG .01 <0	ELDRIN TOTAL (UG/L) <0.010 HYL A- ON, MIR AL TO /L) (UG .01 <0 -DP SILV AL TOT L) (UG	SULFAN, TOTAL (UG/L) <0.010 EX, TAL /L) .01

THIS PAGE WAS LEFT BLANK INTENTIONALLY




Figure 16 -- Río Grande de Manatí basin.

50030460 RIO OROCOVIS AT OROCOVIS, PR

LOCATION.--Lat 18°13'25", long 66°23'34", Hydrologic Unit 21010001, on right bank, 0.4 mi (0.6 km) south of junction of Highways 155 and 156 in Orocovis, 600 ft (183 m) upstream from Río Batijas, and 250 ft (76 m) upstream from bridge on Highway 599.

DRAINAGE AREA .-- 5.03 mi2 (13.03 km2).

WATER-DISCHARGE RECORDS

PERIOD OF RECORD. -- April 1981 to September 1982, October 1988 to current year.

GAGE. -- Water-stage recorder. Elevation of gage is 500 ft (152 m), from topographic map.

REMARKS.--Records poor. Low flow affected by diversions for water supply. Gage-height and precipitation satellite telemetry at station.

reten	etry at	station.										
		DISCHARG	E, CUBIC	C FERT PER		WATER YE MEAN VA	AR OCTOBER	R 1989 TO	septembe	R 1990		
DAY	OCT	NOV	DEC	JAN	FEB	MAR	APR	MAY	JUN	JUL	AUG	SEP
1	e185	13	6.9	3.8	1.6	1.9	1.6	. 97	2.6	e1.6	1.6	e1.4
2	e247	11	6.7	3.5	1.7	1.8	1.6	1.1	2.4	e1.5	1.7	e1.3
3	e253	10	6.7	3.4	1.7	1.8	1.8	1.1	2.1	e1.4	1.8	e1.7
4	e105	10	6.9	3.7	1.6	2.0	1.7	.89	2.4	e1.5	1.7	e1.5
5	e32	9.7	7.2	3.7	1.7	1.9	1.7	.89	3.5	e1.4	1.6	1.6
6	18	9.0	6.6	3.8	2.1	1.6	1.7	.94	2.7	e1.5	1.7	42 15
7 8	16 17	8.9	7.0 6.9	3.7	3.2	1.8	1.8	1.6	2.6	e1.5 e1.4	1.6	2.8
9	15	8.3	7.1	3.4	3.6	3.5	2.3	2.1	1.4	e1.4	1.6	7.6
10	14	8.5	7.0	3.4	2.6	2.9	2.2	4.4	1.9	1.9	1.8	7.2
11	13	8.0	6.8	2.1	2.2	1.9	1.9	3.4	2.2	2.3	2.1	3.7
12	12	7.9	7.2	2.5	2.4	3.2	2.6	2.5	2.3	1.9	1.7	4.0
13	12	9.0	7.2	1.7	2.8	8.4	2.9	2.5	2.2	2.2	40	169
14	12	8.8	6.9	1.6	8.4	13	2.5	2.3	1.4	2.6	6.9	31
15	22	7.9	6.8	1.8	2.1	3.3	2.3	2.1	6.3	2.2	1.7	15
16	51	7.6	6.6	2.0	1.7	2.3	2.3	2.0	2.0	1.9	1.8	4.5
17	40	7.7	6.9	2.1	1.4	1.9	3.1	2.2	1.6	2.9	1.7	e2.4
18	29	7.9	6.8	2.1	1.5	1.5	5.2	2.3	2.1	1.3	1.5	e2.1
19 20	19 48	7.5	6.5	2.4	1.5	1.5	12	1.9	2.0	1.8	1.4	e1.9
										1.7	1.9	e1.5
21	54 148	7.0	6.5	2.1	1.5	1.5	2.7	1.8	2.0	1.2	1.9	e1.3
23	162	7.1	6.2	2.0	1.6	1.6	1.7	1.4	2.3	1.3	1.9	1.7
24	57	6.9	5.8	1.6	1.6	1.5	1.5	1.6	5.4	2.0	e1.5	56
25	29	6.9	4.8	1.6	1.8	1.4	1.5	1.6	3.3	2.0	e1.3	24
26	43	7.2	3.6	2.0	2.2	1.5	1.6	1.7	2.4	e1.8	e1.2	7.1
27	39	7.2	3.6	2.2	1.6	1.6	1.3	2.0	e1.9	e1.8	e1.5	3.5
28	44	6.7	3.8	1.8	1.6	1.5	1.0	1.9	e1.7	e1.6	1.8	3.2
29	31	6.8	4.2	1.5		1.6	1.0	1.8	e1.7	e1.4	36	2.5
30 31	18 14	6.7	4.2	1.5		1.6	.86	1.6	e1.6	e1.2	e2.0	8.1
TOTAL	1799	246.1	190.1	76.2	62.8	76.2	72.56	57.79	72.5	53.6	129.9	426.3
MEAN	58.0	8.20	6.13	2.46	2.24	2.46	2.42	1.86	2.42	1.73	4.19	14.2
MAX	253	13	7.2	3.8	8.4	13	12	4.4	6.3	2.9	40	169
MIN	12 3570	6.7 488	3.6	1.5	1.3	1.4	.86	. 89 115	1.4	1.2	1.2 258	1.3 846
AC-FT CFSM	11.5	1.63	1.22	151 .49	125 .45	151	.48	. 37	.48	.34	.83	2.83
IN.	13.30	1.82	1.41	.56	.46	.56	.54	.43	.54	.40	.96	3.15
e E	timated											
STATIST	TCS OF M	ONTHLY MEAN	I DATA FO	OR WATER Y	RARS 1981	- 1990	BY WATER	YRAR (WY)				
									2 06	9 70	F 0F	10.5
MEAN	28.1	7.05	7.89	2.66	2.36	1.85	3.21	10.2	3.96	2.78	5.05 12.3	18.5 39.6
MAX	58.0	9.57 1982	15.8	4.06	2.92	2.46	7.78	31.8	10.4	5.68	1989	1989
(WY)	1990	3.38	1982	1982	1982	1990	1981	1981	1981	1981	1.03	9.83
MIN (WY)	7.40 1989	1989 .	1.69	1.47 1989	1.92	1.47	1.32 1982	1.42 1989	1.16	1982	1982	1981
CTIMAL D.	. cmamtcm	Ton	ROD 1	1000 CALEN	DAD VEAD		OR 1990 W	AMPD VELD		WATER YE	ADC 1001	- 1000
	STATIST	ics	FOR .	1989 CALEN						MAIAN IL	AND 190	1 - 1990
ANNUAL				4162.80			3263.05 8.94			7,15		
ANNUAL	MEAN L	MEAN		11.4			8.94	•		8.94		1990
	ANNUAL M									6.17		1982
	DAILY M			420	Sep 18		253	Oct 3		420		18 1989
	DAILY ME			1.0				6 Apr 30		.74		4 1982
		Y MINIMUM		1.1				Apr 30		.80		25 1982
INSTANT	TANBOUS P	BAK FLOW					1800	Sep 13				e e . 5157,
	RUNOFF (BAK STAGE		8260			6470	7 Sep 13		5180		
	RUNOFF (2.27			1.78	В		1.42		
	RUNOFF (30.79			24.13			19.31		
10 PERC	CENT BXCE	EDS		22			13			13		
	CENT EXCE			2.0			2.2			2.2		
90 PER	CENT EXCE	EDS		1.2			1.5			1.1		

50030460 RIO OROCOVIS AT OROCOVIS, PR--Continued

DISCHARGE, CUBIC FERT PER SECOND, WATER YEAR OCTOBER 1990 TO SEPTEMBER 1991 DAILY MEAN VALUES

				D.	AILY MEAN	VALUES						
DAY	OCT	NOV	DRC	JAN	FRB	MAR	APR	MAY	JUN	JUL	AUG	SRP
1	3.7	12	10	9.5	1.7	1.1	1.7	55	2.7	. 94	2.0	2.5
2	2.8	11	10	6.2	1.5	1.1	1.7	9.2	2.3	1.3	5.7	2.7
3	3.0	11	27	4.8	1.4	1.1	1.9	4.5	2.3	1.3	10	1.6
4	3.5	10	15	4.1	1.3	.98	2.1	3.6	2.3	e.90	11	1.4
5	5.0	10	11	3.8	2.1	1.2	1.9	3.3	2.7	e.9 0	5.0	e1.4
6	3.7	9.7	9.3	4.4	4.3	1.2	1.9	2.6	2.7	.94	e1.4	e1.3
7 8	3.1	8.8	8.8	4.2	2.4	1.3	2.0	8.2	1.5	1.2	1.6	29
9	2.9 3.1	8.0 8.0	8.1 8.8	4.5 3.8	1.6 1.3	1.2 1.3	2.2 1.8	6.2 2.7	1.2 .87	30 12	3.1 3.4	19 9.6
10	4.8	7.1	8.3	3.9	3.7	1.5	1.9	4.6	1.3	2.0	2.8	6.2
11	4.0	6.9	8.0	3.1	3.1	1.6	1.8	4.6	.98	. 95	e1.3	e1.9
12	3.3	7.0	7.9	3.2	6.6	1.5	2.2	41	.89	e1.0	1.1	e1.8
13	10	6.4	7.4	3.2	5.7	1.5	3.0	104	1.0	e1. 0	1.4	e1.8
14	82	6.3	7.3	2.5	2.9	1.4	2.3	42	.70	e1.1	20	e 1.6
15	110	6.2	7.8	2.5	2.3	1.2	2.5	23	. 95	e1.3	9.2	e1.5
16	130	6.5	7.1	2.8	2.7	1.2	2.2	11	. 92	139	2.7	e1.5
17 18	88 76	6.1 5.9	6.1	2.5 2.0	1.8 2.5	1.1	1.8 2.2	7.2 6.6	.84 .87	24 8.7	10 6.6	3.7 2.4
19	68	5.8	6.1 5.7	1.9	5.1	1.4 1.3	2.3	5.0	.95	4.1	2.0	1.1
20	24	106	6.4	2.0	2.3	1.3	2.0	3.5	1.6	2.5	2.8	1.9
21	209	38	5.1	1.7	2.5	1.4	1.4	3.2	2.8	2.0	2.7	3.0
22	54	47	6.1	1.8	1.7	3.8	1.5	3.2	2.0	1.7	12	1.8
23	30	26	6.5	2.2	1.4	2.4	1.6	3.5	1.0	1.8	17	2.3
24	34	16	6.1	1.7	1.4	1.6	1.5	3.4	1.0	1.8	4.9	1.8
25	92	13	4.7	1.8	1.4	1.4	1.4	2.9	.95	3.2	3.2	e1.3
26	111	12	4.8	1.6	1.3	19	1.6	2.9	.93	3.2	1.5	e1.4
27	53	12	4.5	1.7	1.3	7.6	1.6	3.5	1.0	1.5	34	13
28 29	38 25	11 10	4.7	1.5 1.5	1.2	3.7 2.7	1.6 1.8	4.3 3.5	.98 1.0	5.3 2.1	22 7.0	9.9 4.0
30	19	11	6.0	1.6		2.2	12	3.6	.96	1.5	3.6	3.5
31	15		26	1.8		1.8		3.7		1.3	2.8	
TOTAL	1310.9	454.7	264.8	93.8	68.5	73.08	67.4	385.5	42.19	260.53	213.8	135.9
MEAN	42.3	15.2	8.54	3.03	2.45	2.36	2.25	12.4	1.41	8.40	6.90	4.53
MAX	209	106	27	9.5	6.6	19	12	104	2.8	139	34	29
MIN	2.8	5.8	4.2	1.5	1.2	. 98	1.4	2.6	.70	.90	1.1	1.1
ac-ft CFSM	2600 8.41	902 3.01	525 1.70	186	136 .49	145	134 .45	765 2.47	84 .28	517 1.67	424 1.37	270 .90
IN.	9.69	3.36	1.96	. 60 . 69	.51	.47 .54	.50	2.85	.31	1.93	1.58	1.01
e E	Setimated											
STATIS	STICS OF M	CONTHLY ME	AN DATA F	OR WATER Y	EARS 198:	1 - 1991	, BY WATER	YEAR (WY))			
MBAN	31.6	9.08	8.05	2.75	2.38	1.97	3.02	10.7	3.45	3.90	5.42	15.7
MAX	58.0	15.2	15.8	4.06	2.92	2.46	7.78	31.8	10.4	8.40	12.3	39.6
(WY)	1990	1991	1982	1982	1982	1990	1981	1981	1981	1991	1989	1989
MIN	7.40	3.38	1.69	1.47	1.92	1.47	1.32	1.42	1.16	1.45	1.03	4.53
(WY)	1989	1989	1989	1989	1989	1982	1982	1989	1982	1982	1982	1991
SUMMAR	NY STATIST	rics	FOR :	1990 CALEN	DAR YEAR	;	FOR 1991 WA	TER YEAR		WATER	YEARS 1981	- 1991
ANNUAL	TOTAL			3058.25			3371.10					
ANNUAL				8.38			9.24				67	4004
	ST ANNUAL NANNUAL B										24 17	1991 1982
	T DAILY M			209	Oct 21		209	Oct 21		420		18 1989
	DAILY ME			.86	Apr 30		.70	Jun 14			70 Jun	14 1991
		MUMINIM YA		.96	Apr 30			Jun 12			80 Apr	25 1982
		PEAK PLOW					803					
	TANKOUS E RUNOFF (PEAK STAGE		6070			8.81 6690	Nov 20		5560		
	RUNOFF (1.67			1.84			1.		
	RUNOFF			22.62			24.93			20.	72	
	CENT EXCE			13			19			13		
	RCENT EXCE			2.2 1.5			2.9 1.2			2. 1.		
JU PAR	CENT BACE	3400		1.5			1.4			1.	•	

50030460 RIO OROCOVIS AT OROCOVIS, PR--Continued

DISCHARGE, CUBIC FEET PER SECOND, WATER YEAR OCTOBER 1991 TO SEPTEMBER 1992 DAILY MEAN VALUES

				Ē	AILY MEAN	VALUES						
DAY	OCT	NOV	DEC	JAN	FRB	MAR	APR	MAY	JUN	JUL	AUG	SEP
1	2.2	7.8	e1.0	1.0	1.9	1.3	2.4	3.0	158	2.5	1.5	2.1
2	2.2	6.9	1.3	. 97	1.5	1.2	4.5	7.2	51	11	1.9	2.6
3	1.9	3.7	1.2	. 92	1.7	1.7	2.2	3.2	29	4.5	.93	2.9
4 5	1.6 1.7	1.8 3.1	1.4 1.3	.98 415	1.8 1.9	1.4 1.2	1.5 1.6	2.3 1.5	21 17	3.1 2.3	1.4 3.0	2.8 2.5
•	•••	3.1	1.5	415	1.7	1	1.0	1.5		2.5		
6	1.7	3.3	1.3	358	12	1.2	1.5	7.4	15	3.5	4.5	2.9
7	20	3.6	1.3	48	14	1.1	2.4	3.4	13	2.8	1.3 1.3	2.2 5.7
8 9	9.7 4.3	3.3 2.4	1.3 1.5	41 32	12 5.1	1.4 1.5	1.7 71	1.8 1.5	12 11	4.1 2.4	1.3	2.5
10	3.9	2.2	1.3	25	2.9	1.9	26	1.5	12	3.8	1.4	1.3
11	3.1	1.7	1.2	19	2.1	1.2	13	1.4	10	2.6	1.6	e.90
12	3.4	e1.3	1.5	15	2.0	1.0	13	2.2	9.6	1.9	1.7	e.86
13	3.1	e1.2	1.2	18	2.3	. 90	11	1.2	12	1.6	e1.4	1.5
14 15	2.5 1.7	e1.2 1.2	1.4 1.8	14 11	1.8 1.7	. 92	8.4 9.6	5.6 8.5	8.2 7.3	1.8 1.9	e1.3 e1.3	1.2 .86
						1.1						
16 17	1.7 1.3	1.3	1.0	8.7	1.6 2.5	1.0	32 24	3.1 7.2	7.4 6.6	2.6 1.9	1.5 1.4	. 83 e. 88
18	1.3	.99 2.0	.98 1.1	7.6 5.5	1.5	2.7 2.1	14	5.0	6.0	2.1	1.4	e1.2
19	2.3	2.6	1.1	5.0	1.4	1.2	86	4.3	5.6	1.6	1.3	e1.6
20	6.9	2.6	9.1	3.6	1.5	. 91	40	35	5.6	1.8	1.2	e1.8
21	5.9	2.0	13	3.0	1.2	. 92	15	17	6.3	1.4	e1.0	e2.1
22	3.0	e1.3	1.8	2.7	1.2	1.1	7.7	7.4	4.7	1.5	e.96	e1.4
23	5.3	e1.2	1.4	3.9	1.3	1.2	5.3	213	4.3	1.4	e.93	e.86
24 25	1.8 1.8	e1.1 .93	1.2 1.1	3.7 2.9	1.4 1.7	e1.0 e1.6	4.0 2.6	131 56	3.9 3.6	1.2 1.2	1.0 1.1	e.94 e1.7
26	1.3	.86	1.3	2.9	1.6	e1.8	2.5	160 37	3.3 3.2	2.2 1.9	1.2 1.2	e.88 e.88
27 28	e1.3 e1.2	1.0 1.1	.97 .94	2.7 3.3	1.5 1.5	6. 8 7.7	2.0 1.8	21	3.1	1.0	1.3	e.88
29	8.4	1.1	.89	2.6	1.5	6.6	1.8	16	2.7	1.0	1.5	e.80
30	19	e.96	1.1	2.5		3.1	2.9	44	3.0	. 85	1.5	e2.0
31	17		1.2	2.8		1.9		99	-	1.1	1.7	
TOTAL	142.4	65.74	58.18	1063.27	86.1	60.65	411.4	907.7	455.4	74.55	46.02	51.57
WRYN	4.59	2.19	1.88	34.3	2.97	1.96	13.7	29.3	15.2	2.40	1.48	1.72
MAX MIN	20 1.2	7.8	13	415	14 1.2	7.7	.86	213 1.2	158 2.7	. 85	4.5 .93	5.7 .80
AC-FT	282	.86 130	.89 115	.92 2110	171	.90 120	1.5 816	1800	903	148	91	102
CFSM	.91	. 44	.37	6.82	.59	.39	2.73	5.82	3.02	.48	.30	.34
IN.	1.05	. 49	.43	7.86	. 64	. 45	3.04	6.71	3.37	. 55	.34	.38
e R	stimated											
STATIS	TICS OF M	IONTTHT.Y MR	AN DATA	FOR WATER Y	/RARS 1981	- 1992.	RY WATER	YRAR (WY)			
												40.0
mban Max	26.2 58.0	7.70 15.2	6.82 15.8	9.06 34.3	2.50 2.97	1.97 2.46	4.80 13.7	13.8 31.8	5.40 15.2	3.65 8.40	4.76 12.3	13.3 39.6
(WY)	1990	1991	1982	1992	1992	1990	1992	1981	1992	1991	1989	1989
MIN	4.59	2.19	1.69	1.47	1.92	1.47	1.32	1.42	1.16	1.45	1.03	1.72
(WY)	1992	1992	198 9	1989	1989	1982	1982	1989	1982	1982	1982	1992
SUMMAR	Y STATIST	rics	FOR	1991 CALE	NDAR YEAR	F	OR 1992 W	ATER YEAR		WATER Y	TARS 1981	- 1992
ANNUAL	TOTAL			1607.02	2		3422.9	В				
ANNUAL	MRAN T ANNUAL	MPAN		4.40)		9.3	5		8.0 9.3		1992
	ANNUAL M									6.1		1982
	T DAILY M				Jul 16			Jan 5		420	Sep	18 1989
	DAILY ME			.70	Jun 14			Sep 29		.7	0 Jun	14 1991
		Y MINIMUM		.86	3 Jun 12			9 Sep 23				25 1982
		BAK FLOW BAK STAGE					2320 11.5	Jan 5 3 Jan 5		2320 11.5		5 1992 5 1992
	RUNOFF (1	3190			6790			5800		
ANNUAL	RUNOFF (CFSM)		. 88	3		1.8	5		1.5	9	
	RUNOFF (11.88			25.3			21.6		
	CENT EXCE			8.3 1.9			14 1.9			13 2.2		
	CENT EXCE			1.9			1.9			1.1		
		-		•								

50030700 RIO OROCOVIS NEAR OROCOVIS, PR

WATER-QUALITY RECORDS

LOCATION.--Lat 18°14'20", long 66°22'58", at flat low bridge about 300 ft (91 m) northwest of Highway 568, 1.0 mi (1.6 km) north of Orocovis plaza.

DRAINAGE AREA. -- 10.1 mi2 (26.2 km2).

PERIOD OF RECORD .-- Water year 1979 to current year.

WATER-QUALITY DATA, WATER YEAR OCTOBER 1991 TO SEPTEMBER 1992

DATE	TIME	DIS- CHARGE, INST. CUBIC FEBT PER SECOND	SPR- CIFIC CON- DUCT- ANCR (US/CM)	PH WATER WHOLE FIELD (STAND- ARD UNITS)	TEMPER- ATURE WATER (DEG C)	TUR- BID- ITY (NTU)	OXYGEN, DIS- SOLVED (MG/L)	OXYGEN, DIS- SOLVED (PER- CENT SATUR- ATION)	OXYGEN DEMAND, CHEM- ICAL (HIGH LEVEL) (MG/L)	COLI- FORM, FECAL, 0.7 UM-MF (COLS./	STREP- TOCOCCI FECAL, KF AGAR (COLS. PER 100 ML)
OCT 1991 10	1300	6.4	316	8.2	24.0	10	7.9	84	15	K 7200	900
16	1100	4.5	229	8.3	20.5	1.7	8.3	99	27	K140	K200
FEB 1992 26	1145	8.3	284	8.1	22.5	3.0	8.2	98	16	230	220
MAY 29 JUN	1010	24	235	7.4	22.5	2.7	8.0	92	<10	K7800	870
30 AUG	0915	15	275	7.8	24.0	2.0	8.4	102	<10	K 1900	K550
11	0915	7.9	312	7.8	24.5	2.2	8.0	93	18	24000	360
DATE	HARD- NESS TOTAL (MG/L AS CACO3)	HARD- NESS NONCARB WH WAT TOT FLD MG/L AS CACO3	CALCIUM DIS- SOLVED (MG/L AS CA)	MAGNE- SIUM, DIS- SOLVED (MG/L AS MG)	SODIUM, DIS- SOLVED (MG/L AS NA)	SODIUM AD- SORP- TION RATIO	POTAS- SIUM, DIS- SOLVED (MG/L AS K)	WAT WH TOT FET	SULFIDE TOTAL (MG/L AS S)	SULFATE DIS- SOLVED (MG/L AS SO4)	CHLO- RIDE, DIS- SOLVED (MG/L AS CL)
OCT 1991 10	130	5	33	12	13	0.5	1.7	120	<0.5	16	20
DEC 16								140			
FEB 1992 26								110			
МАҮ 29	90	0	22	8.6	12	0.5	2.0	82	<0.5	7.5	14
JUN 30								120			
AUG 11	130	13	34	12	14	0.5	1.9	110		8.3	17
ם	RI I SC DATE ()	IDR, DI DIS- SC DLVED (M	ICA, SUM IS- CON DLVED TUE IG/L D IS SO	STI- ENTS, SC DIS- (T DLVED P	IDS, TOT DIS- AT DLVED DEG CONS SU PER PEN	105 . C, NI S- T	GEN, TRATE NI OTAL T MG/L (GEN, C TRITE NO. OTAL TO MG/L (1	SEN, C S+NO3 AMB STAL TO AG/L (M	EEN, G NONIA ORG TAL TO G/L (M	TRO- EN, ANIC TAL G/L
OCT 1		9 2 / 31	(M	ا زنا/ فا	AI) (E	IG/LI) A	5 M/ A	o Nj	,		
10.	991			•							
DEC	991	cO.10 3	12	200	3.44	11	0.680	0.010).690 (0.020	
DEC 16. FRB 1	991	<0.10 3	22	200	3.44	11	0.680	0.010).690 ().360 (0.020	5.6
DEC 16. FEB 1 26. MAY		<0.10 3 	 	200	3.44	11 1 1	0.680 0.350 0.860	0.010 (0.010 (0.020 (0.690 C).020).030).050	 5.6
DEC 16. FEB 1 26.		<0.10 3 	22	200	3.44	11 1 1 17	0.680 0.350 0.860 0.830	0.010 (0.010 (0.020 (0.690 C 0.360 C 0.880 C	0.020 0.030 0.050	5.6

K = non-ideal count

50030700 RIO OROCOVIS NEAR OROCOVIS, PR--Continued

WATER-QUALITY DATA, WATER YEAR OCTOBER 1991 TO SEPTEMBER 1992

DATE	NITRO- GEN, AM- MONIA + ORGANIC TOTAL (MG/L AS N)	NITRO- GEN, TOTAL (MG/L AS N)	NITRO- GEN, TOTAL (MG/L AS NO3)	PHOS- PHORUS TOTAL (MG/L AS P)	ARSENIC TOTAL (UG/L AS AS)	BARIUM, TOTAL RECOV- ERABLE (UG/L AS BA)	BORON, TOTAL RECOV- ERABLE (UG/L AS B)	CADMIUM TOTAL RECOV- ERABLE (UG/L AS CD)	CHRO- MIUM, TOTAL RECOV- ERABLE (UG/L AS CR)	COPPER, TOTAL RECOV- ERABLE (UG/L AS CU)
OCT 1991										
10	<0.20			0.070	<1	<100	50	<1	<1	10
DEC 16	5.6	6.0	26	0.060						
FEB 1992 26	<0.20			0.000						
MAY	₹0.20			0.220						
29 JUN	<0.20			0.090	<1	<100	10	<1	<1	<10
30	0.40	1.0	4.5	0.120						
AUG 11	<0.20			0.150						
DATE	IRON, TOTAL RECOV- ERABLE (UG/L AS FE)	LEAD, TOTAL RECOV- ERABLE (UG/L AS PB)	MANGA- NESE, TOTAL RECOV- ERABLE (UG/L AS MN)	MERCURY TOTAL RECOV- ERABLE (UG/L AS HG)	SRLE- NIUM, TOTAL (UG/L AS SE)	SILVER, TOTAL RECOV- ERABLE (UG/L AS AG)	ZINC, TOTAL RECOV- ERABLE (UG/L AS ZN)	CYANIDE TOTAL (MG/L AS CN)	PHENOLS TOTAL (UG/L)	METHY- LENE BLUE ACTIVE SUB- STANCE (MG/L)
DATE	TOTAL RECOV- ERABLE (UG/L	TOTAL RECOV- ERABLE (UG/L	NESE, TOTAL RECOV- ERABLE (UG/L	TOTAL RECOV- ERABLE (UG/L	NIUM, TOTAL (UG/L	TOTAL RECOV- BRABLE (UG/L	TOTAL RECOV- ERABLE (UG/L	TOTAL (MG/L	TOTAL	LENE BLUE ACTIVE SUB- STANCE
ост 1991 10	TOTAL RECOV- ERABLE (UG/L	TOTAL RECOV- ERABLE (UG/L	NESE, TOTAL RECOV- ERABLE (UG/L	TOTAL RECOV- ERABLE (UG/L	NIUM, TOTAL (UG/L	TOTAL RECOV- BRABLE (UG/L	TOTAL RECOV- ERABLE (UG/L	TOTAL (MG/L	TOTAL	LENE BLUE ACTIVE SUB- STANCE
OCT 1991 10 DEC 16	TOTAL RECOV- ERABLE (UG/L AS FE)	TOTAL RECOV- ERABLE (UG/L AS PB)	NESE, TOTAL RECOV- ERABLE (UG/L AS MN)	TOTAL RECOV- BRABLE (UG/L AS HG)	NIUM, TOTAL (UG/L AS SE)	TOTAL RECOV- ERABLE (UG/L AS AG)	TOTAL RECOV- ERABLE (UG/L AS ZN)	TOTAL (MG/L AS CN)	TOTAL (UG/L)	LENE BLUE ACTIVE SUB- STANCE (MG/L)
OCT 1991 10 DEC 16 FEB 1992	TOTAL RECOV- ERABLE (UG/L AS FE)	TOTAL RECOV- ERABLE (UG/L AS PB)	NESE, TOTAL RECOV- ERABLE (UG/L AS MN)	TOTAL RECOV- ERABLE (UG/L AS HG) <0.10	NIUM, TOTAL (UG/L AS SE)	TOTAL RECOV- ERABLE (UG/L AS AG)	TOTAL RECOV- ERABLE (UG/L AS ZN)	TOTAL (MG/L AS CN)	TOTAL (UG/L)	LENE BLUE ACTIVE SUB- STANCE (MG/L)
OCT 1991 10 DEC 16	TOTAL RECOV- ERABLE (UG/L AS FE)	TOTAL RECOV- ERABLE (UG/L AS PB)	NESE, TOTAL RECOV- ERABLE (UG/L AS MN)	TOTAL RECOV- BRABLE (UG/L AS HG)	NIUM, TOTAL (UG/L AS SE)	TOTAL RECOV- ERABLE (UG/L AS AG)	TOTAL RECOV- ERABLE (UG/L AS ZN)	TOTAL (MG/L AS CN)	TOTAL (UG/L)	LENE BLUE ACTIVE SUB- STANCE (MG/L)
OCT 1991 10 DRC 16 FEB 1992 26 MAY 29	TOTAL RECOV- ERABLE (UG/L AS FE)	TOTAL RECOV- ERABLE (UG/L AS PB)	NESE, TOTAL RECOV- ERABLE (UG/L AS MN)	TOTAL RECOV- ERABLE (UG/L AS HG) <0.10	NIUM, TOTAL (UG/L AS SE)	TOTAL RECOV- ERABLE (UG/L AS AG)	TOTAL RECOV- ERABLE (UG/L AS ZN)	TOTAL (MG/L AS CN)	TOTAL (UG/L)	LENE BLUE ACTIVE SUB- STANCE (MG/L)
OCT 1991 10 DEC 16 FEB 1992 26 MAY 29 JUN	TOTAL RECOV- RRABLE (UG/L AS FE) 1100	TOTAL RECOV- BRABLE (UG/L AS PB)	NESE, TOTAL RECOV- ERABLE (UG/L AS MN)	TOTAL RECOV- ERABLE (UG/L AS HG) <0.10	NIUM, TOTAL (UG/L AS SE)	TOTAL RECOV- BRABLB (UG/L AS AG) <1	TOTAL RECOV- BRABLE (UG/L AS ZN) <10	TOTAL (MG/L AS CN) <0.010	TOTAL (UG/L) 1	LENE BLUE ACTIVE SUB- STANCE (MG/L) 0.02
OCT 1991 10 DRC 16 FEB 1992 26 MAY 29	TOTAL RECOV- RRABLE (UG/L AS FE) 1100	TOTAL RECOV- ERABLE (UG/L AS PB) 6 <1	NESE, TOTAL RECOV- ERABLE (UG/L AS MN)	TOTAL RECOV- ERABLE (UG/L AS HG) <0.10	NIUM, TOTAL (UG/L AS SE)	TOTAL RECOV- BRABLB (UG/L AS AG) <1	TOTAL RECOV- BRABLE (UG/L AS ZN) <10	TOTAL (MG/L AS CN) <0.010	TOTAL (UG/L) 1	LENE BLUE ACTIVE SUB- STANCE (MG/L) 0.02

50031200 RIO GRANDE DE MANATI NEAR MOROVIS, PR

LOCATION.--Lat 18°17'45", long 66°24'47", Hydrologic Unit 21010001, on right bank , 0.1 mi (0.2 km) downstream from Quebrada Perchas, 0.8 mi (1.3 km) upstream from Río Sana Muerto, and 2.2 mi (3.5 km) south of Morovis.

DRAINAGE AREA. -- 55.2 mi 2 (143.0 km2).

WATER-DISCHARGE RECORDS

PERIOD OF RECORD. -- January 1965 to current year.

GAGE.--Water-stage recorder and concrete control. Elevation of gage is 440 ft (134 m), from topographic map. Feb. 2, 1966 to Apr. 27, 1967, staff gage read twice daily.

REMARKS.--Records fair except those for estimated daily discharges, which are poor. Public water-supply pumpage, about 300 ft (91 m) above the station, influences low-flow discharges. Gage-height and precipitation satellite telemetry at station.

	DIS	CHARGE,	CUBIC PERT		OND, WATER DAILY MEAN		CTOBER 1991	TO SEPTE	MBER 199	2		
DAY	OCT	NOA	DEC	JAN	FEB	MAR	APR	MAY	JUN	JUL	AUG	SEP
1	24	211	26	27	37	e33	35	223	283	41	35	24
2	24	190	25	26	36	e 30	143	289	191	41	32	21
3	22	114	26	25	35	e 30	95	135	138	67	33	23
4	19	75	29	24	37	e 30	62	92	122	43	63	26
5	20	57	30	2480	35	e 29	42	70	113	41	69	42
6	21	53	28	1530	37	e28	38	187	99	39	119	45
7	34	58	26	246	74	e29	69	120	91	38	54	31
8	92	60	25	147	65	e 30	73	76	92	54	42	27
9	48	49	27	116	4.4	e33	293	62	106	56	37	63
10	28	41	34	117	39	e35	220	55	145	42	36	29
11	23	35	29	e 86	38	e28	101	49	124	39	34	22
12	23	32	27	e82	95	e27	70	47	92	42	35	21
13	21	32	25	e88	47	e26	58	48	91	39	32	20
14	20	32	25	e84	37	e25	48	46	87	54	30	19
15	19	34	25	e70	35	e25	57	66	71	41	46	19
16	18	31	25	e70	33	e25	180	54	68	48	34	19
17	17	30	25	e 76	30	31	190	100	66	41	29	21
18	17	29	24	e62	31	49	129	156	62	40	28	22
19 20	49 44	28 28	24 43	e55 e51	31 32	39 32	e580 e450	233 305	59 58	35 35	26 119	29 69
21	26	28	176	e47	32	27	e200	248	56	33	97	31
22	25	33	69	e46	32	28	96	130	55	32	39	24
23 24	39 25	32	46	e44	e33	27	73	457	52	34	29 27	24 23
25	23	52 38	34	46 44	e32 e32	24	62 54	599 261	50 48	43 37	35	20
			30	**	4 32	23	34		*0			
26	30	31	29	44	e33	22	50	474	46	34	27	20
27 28	20	28	33	41	e30	128	46	246	45	33 32	26	20
29	19 49	33 29	33 31	40 41	e33 e36	62 71	43 64	165 135	45 42	32	24 23	17 17
30	224	26	27	38		42	141	144	41	31	23	56
31	216		27	38		39		231		30	25	
TOTAL	1279	1549	1083	5931	1141	1107	3762	5503	2638	1247	1308	844
MEAN	41.3	51.6	34.9	191	39.3	35.7	125	178	87.9	40.2	42.2	28.1
MAX	224	211	176	2480	95	128	580	599	283	67	119	69
MIN	17	26	24	24	30	22	35	46	41	30	23	17
AC-FT	2540	3070	2150	11760	2260	2200	7460	10920	5230	2470	2590	1670
CFSM	.75	. 94	.63	3.47	.71	. 65	2.27	3.22	1.59	.73	.76	.51
IN.	.86	1.04	.73	4.00	.77	.75	2.54	3.71	1.78	. 84	.88	. 57
e Ba	timated											
STATIST	ICS OF M	ONT HILY M	RAN DATA FO	R WATER	YRARS 1965	- 1992	, BY WATER	YRAR (WY)				
							•	-				
MEAN	168	158	118	83.9	66.5	70.4	114	170	65.2	48.4	59.0	93.2
MAX	1037	491	522	191	179	226	412	915	173	157 1979	435 1979	386 1979
MIN MIN	1971 24.0	1971 28.3	1966 27.9	1992 24.7	1969 23.4	1972 12.7	1969 10.6	1985 23.6	1987 16.9	18.5	9.70	25.0
(WY)	1978	1974	1984	1984	1984	1984	1984	1977	1977	1977	1984	1977
SUMMARY	STATIST	CS	FOR 1	1991 CALE	NDAR YEAR		FOR 1992 WA	TER YEAR		WATER YEA	RS 1965	- 1992
ANNUAL	TOTAL			19164			27392					
ANNUAL				52.5			74.8			102		
	'ANNUAL E									248		1971
	ANNUAL ME							.		40.3	30 4	1974
	DAILY MEA			605 15	Jul 16 Sep 6		2480 17	Jan 5 Oct 17		17100 5.7		L8 1985 20 1984
	SEARN-DY		M	19	Sep 6 Aug 31		17	Oct 17		6.8		L8 1984
	ANEOUS PE			13	wan at		19000	Jan 5		48000		1985
	ANBOUS PI						11.27			17.89		18 1985
	ANBOUS LO						16	Sep 28		4.4		15 1984
	RUNOFF (A			38010			54330			73880		
	RUNOFF (9			1.36			1.85		
	RUNOFF (1			12.9	1		18.46			25.10		
IN BRKC	ENT EXCE	ED2		98			139			179		

50031200 RIO GRANDE DE MANATI NEAR MOROVIS, PR--Continued

WATER-QUALITY RECORDS

PERIOD OF RECORD. -- Water years 1968 to current year.

WATER-QUALITY DATA, WATER YEAR OCTOBER 1991 TO SEPTEMBER 1992

			WAT	RK-GOYPIL	DATA, W	ATER YEA	R OCTOB	BR 1991	TO SEE	LEWBER I	992		
DATI	В	TIME	DIS- CHARGE, INST. CUBIC FRET PER SECOND	SPB- CIFIC CON- DUCT- ANCE (US/CM)	PH WATER WHOLE FIELD (STAND- ARD UNITS)	TEMPER ATURE WATER (DEG C	BI	D- E	(GEN,)IS-)LVED IG/L)	OXYGEN, DIS- SOLVED (PER- CENT SATUR- ATION)	OXYGEN DEMAND, CHEM- ICAL (HIGH LEVEL) (MG/L)	COLI- FORM, FECAL, 0.7 UM-MF (COLS./ 100 ML)	STREP- TOCOCCI FECAL, KF AGAR (COLS. PER 100 ML)
OCT 199:	1	1115	43	222	7.8	24.	5 110		8.0	93	31	23000	9500
DEC 12 FRB 1992	•	1415	25	298	8.5	24.	5 5	. 5	8.3	98	15	K10	90
26 APR	4	0945	34	281	8.0	23.	0 1	.3	8.3	100	14	130	100
21 JUN		0945	140	199	7.0	24.	0 67		8.7	104	17	2800	2000
30		1105	40	250	8.3	24.	0 1	.5	7.5	99	<10	110	450
11		1125	33	230	8.2	27.	0 3	.1	7.0	86	17	270 0	60
Dati	B	HARD- NESS TOTAL (MG/L AS CACO3)	HARD- NESS NONCARE WH WAT TOT FLD MG/L AS CACO3	DIS- SOLVED	MAGNE- SIUM, DIS- SOLVED (MG/L AS MG)	SODIUM DIS- SOLVED (MG/L AS NA	, A Sor Ti Rat	D- S P- D ON SC IO (M	OTAS- BIUM, DIS- DLVED G/L B K)	ALKA- LINITY WAT WH TOT PET FIELD MG/L AS CACO3	SULFIDE TOTAL (MG/L AS S)	SULFATE DIS- SOLVED (MG/L AS SO4)	CHLO- RIDE, DIS- SOLVED (MG/L AS CL)
OCT 199:	1	83	6	20	8.1	11		0.5	2.4	79	<0.5	7.7	14
DEC 12	_						_	_		110			
FEB 1992	2						-	-		110			
APR 21		76	0	18	7.6	10		0.5	3.6	57	<0.5	11	16
30							-	-		120			
AUG 11		120	3	29	12	14		0.6	2.1	120		7.4	17
		RI D	DE, D	LICA, SUI IS- COI OLVED TUI	nsti- 1 Ents, sc	LIDS, TO DIS- A DLVED D	ESIDUE OTAL T 105 EG. C,	NITRO- GEN, NITRATE TOTAL	GE	N, G	EN, C	EN, G	TRO- SEN, SANIC TAL
	DATE						ENDED (MG/L)	(MG/L AS N)	(MC AS				G/L N)
	T 1991 09	l	0.20	21	132	15.1	33	0.560	0.	070 0	.630	.080	0.42
:	12 B 1992	ì					17		<0.	010 0	.360	.020	
	26						1		<0.	010 0	.300	.020	
	21		0.10	22	122	16.1	64	1.25	0.	050 1	.30 (.070	0.53
	30						<1		<0.	010 0	.170	.080	0.72
	11		0.20	25	175	15.6	<1		<0.	010 0	.270	.030	
K :	= non-	ideal c	ount										

RIO GRANDE DE MANATI BASIN

50031200 RIO GRANDE DE MANATI NEAR MOROVIS, PR--Continued WATER-QUALITY DATA, WATER YEAR OCTOBER 1991 TO SEPTEMBER 1992

DATE	NITRO- GEN, AM- MONIA + ORGANIC TOTAL (MG/L AS N)	NITRO- GEN, TOTAL (MG/L AS N)	NITRO- GEN, TOTAL (MG/L AS NO3)	PHOS- PHORUS TOTAL (MG/L AS P)	ARSENIC TOTAL (UG/L AS AS)	BARIUM, TOTAL RECOV- ERABLE (UG/L AS BA)	BORON, TOTAL RECOV- BRABLE (UG/L AS B)	CADMIUM TOTAL RECOV- ERABLE (UG/L AS CD)	CHRO- MIUM, TOTAL RECOV- BRABLE (UG/L AS CR)	COPPER, TOTAL RECOV- ERABLE (UG/L AS CU)
OCT 1991										
09 DBC	0.50	1.1	5.0	0.160	<1	<100	30	<1	8	20
12 FEB 1992	<0.20			0.070						
26	<0.20			0.060			~-			
APR 21 JUN	0.60	1.9	8.4	0.130	<1	<100	20	1	12	20
30	0.80	0.97	4.3	0.040			~-			
AUG 11	<0.20			0.040						
	IRON, TOTAL RECOV-	LEAD, TOTAL	MANGA - NESE, TOTAL	MERCURY TOTAL	SELE-	SILVER, TOTAL	ZINC, TOTAL			METHY- LENE BLUE ACTIVE
DATE	ERABLE (UG/L AS FE)	RECOV- BRABLE (UG/L AS PB)	RECOV- ERABLE (UG/L AS MN)	RECOV- ERABLE (UG/L AS HG)	NIUM, TOTAL (UG/L AS SE)	RECOV- ERABLE (UG/L AS AG)	RECOV- BRABLE (UG/L AS ZN)	CYANIDE TOTAL (MG/L AS CN)	PHENOLS TOTAL (UG/L)	SUB- STANCE (MG/L)
OCT 1991	BRABLE (UG/L AS FE)	ERABLE (UG/L AS PB)	ERABLE (UG/L AS MN)	ERABLE (UG/L AS HG)	TOTAL (UG/L AS SE)	ERABLE (UG/L AS AG)	ERABLE (UG/L AS ZN)	TOTAL (MG/L AS CN)	TOTAL (UG/L)	SUB- STANCE (MG/L)
	BRABLE (UG/L	RRABLE (UG/L	ERABLE (UG/L	ERABLE (UG/L	TOTAL (UG/L	ERABLE (UG/L	BRABLE (UG/L	TOTAL (MG/L	TOTAL	SUB- STANCE
OCT 1991 09 DBC 12	BRABLE (UG/L AS FE)	ERABLE (UG/L AS PB)	ERABLE (UG/L AS MN)	ERABLE (UG/L AS HG)	TOTAL (UG/L AS SE)	ERABLE (UG/L AS AG)	ERABLE (UG/L AS ZN)	TOTAL (MG/L AS CN)	TOTAL (UG/L)	SUB- STANCE (MG/L)
OCT 1991 09 DEC 12 FEB 1992 26	BRABLE (UG/L AS FE)	ERABLE (UG/L AS PB)	ERABLE (UG/L AS MN)	ERABLE (UG/L AS HG)	TOTAL (UG/L AS SE)	ERABLE (UG/L AS AG)	ERABLE (UG/L AS ZN)	TOTAL (MG/L AS CN)	TOTAL (UG/L)	SUB- STANCE (MG/L)
OCT 1991 09 DEC 12 FEB 1992 26 APR 21	ERABLE (UG/L AS FE) 7100	ERABLE (UG/L AS PB)	ERABLE (UG/L AS MN)	ERABLE (UG/L AS HG) <0.10	TOTAL (UG/L AS SE)	ERABLE (UG/L AS AG)	ERABLE (UG/L AS ZN)	TOTAL (MG/L AS CN)	TOTAL (UG/L)	SUB- STANCE (MG/L) 0.01
OCT 1991 09 DEC 12 FEB 1992 26	RRABLE (UG/L AS FE) 7100	ERABLE (UG/L AS PB) 3	ERABLE (UG/L AS MN) 140	ERABLE (UG/L AS HG) <0.10	TOTAL (UG/L AS SE) <1	ERABLE (UG/L AS AG) <1	ERABLE (UG/L AS ZN) 20	TOTAL (MG/L AS CN)	TOTAL (UG/L) 2 	SUB- STANCE (MG/L) 0.01

50032290 LAGO RL GUINEO AT DAMSITE, PR

LOCATION.--Lat 18°09'41", long 66°51'48", Hydrologic Unit 21010001, at damsite on Río Toro Negro, 3.0 mi (4.8 km) northwest from Villalba plaza and 1.9 mi (3.1 km) northeast of Cerro Maravillas. The reservoir itself fixes the territorial limits between the Municipality of Ciales and Orocovis.

DRAINAGE AREA. -- 1.64 mi 2 (4.25 km2).

ELEVATION RECORDS

PERIOD OF RECORD. -- May 1988 to current year.

GAGE. -- Water-stage recorder. Datum of gage is mean sea level.

REMARKS.--Lago Guineo was completed in 1931. It provides a maximum storage of approximately 2,180 ac-ft (2.688 hm²) for power and irrigation. Waters are discharged through an outlet power tunnel into the Río Toro Negro and coveyed to the head water works of Toro Negro Hydroelectric Plant No.2, for energy generation at Toro Negro Hydroelectric plant No.1, and are discharged into the Guayabal Reservoir to be later used for irrigation at South Coast Irrigation System. The dam is rockfill with a vertical concrete corewall, rock toes, and riprap facing of upstream slope, with a total length of 565 ft (172 m), a maximum structural height of 125 ft (38 m) to top of corewall. At a maximum reservoir water surface elevation the uncontrolled morning-glory tunnel spillway crest has an elevation of 2,966 ft (904 m) above mean sea level and a design capacity of 7,000 ft³/s. The dam is owned by Puerto Rico Electric Power Authority. Gage-height and precipitation satellite telemetry at station.

EXTREMES OBSERVED FOR PERIOD OF RECORD. -- Maximum elevation 2,961.70 ft (902.73 m), Oct. 21, 1990; minimum elevation, 2,919.79 ft (899.95 m), May 27, 1988.

EXTREMES OBSERVED FOR CURRENT YEAR.--Maximum elevation, 2,961.11 ft (902.55 m), Jan. 6; minimum elevation, 2,941.60 ft (896.60 m), Jan. 3.

Capacity Table (based on data from Puerto Rico Electric Power Authority)

Elevation, in feet	Contents, in acre-feet	Elevation, in feet	Contents, in acre-feet
2,872	0	2,943	1,029
2,919	361	2,950	1,308
2,925	491	2,961	1,852

ELEVATION (FRET NGVD), WATER YEAR OCTOBER 1991 TO SEPTEMBER 1992 DAILY OBSERVATION AT 24:00 VALUES

DAY	OCT	NOA	DEC	JAN	FEB	MAR	APR	MAY	JUN	JUL	AUG	SEP
1	2949.48	2947.21	2946.06	2942.88	2952.29	2949.59	2952.14	2952.32	2960.80	2958.39	2954.16	2951.52
2	2949.20	2947.33	2945.67	2942.50	2952.39	2949.52	2952.88	2952.44	2960.20	A	2954.24	2951.31
3	2948.86	2947.41		2942.06	2952.19	2949.58	2953.07	2952.54	2960.38	Ä	2953.80	2951.09
4	2948.46		2945.04		2952.06		2953.17	2952.18	2960.33	λ	2953.74	
5	2948.52		2944.80		2951.93	2949.72	2953.25	2951.92	2960.17	λ.	2954.21	
				-,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,	-,,,,,,	-,,,,,,	-,,,,,,					-,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,
6	2948.57	2947.31	2944.48	2961.03	2953.03	2949.79	2952.97	2951.94	2959.97	A	2954.13	2950.93
7	2948.86	2947.23	2944.52	2960.40	2953.29	2949.86	2952.71	2951.81	2960.19	λ	2953.90	2953.49
8	2948.72	2947.33	2944.56	2959.90	2953.04	2949.94	2952.77	2951.74	2960.41	λ	2953.99	2953.41
9	2948.66	2947.54	2944.21	2959.38	2953.21	2950.09	2953.12	2951.83	2960.20	A	2954.15	2953.25
10	2948.32	2947.65	2944.23	2958.83	2953.03	2950.17	2952.99	2951.91	2960.00	λ	2956.42	2953.09
11	2948.06	2947.73	2944.29	2958.34	2953.15	2950.23	2952.55	2951.38	2959.86	λ	2956.34	2952.95
12	2947.49	2947.41		λ	2952.59	2950.14	2952.68	2951.58	2959.88	A	2956.24	2952.37
13	2946.92	2946.90	2943.96	A	2952.26	2949.90	2952.43	2951.70	2960.15	A	2956.10	2952.43
14	2946.76	2946.44	2944.00	λ	2952.08	2949.94	2952.15	2952.20	2960.37	λ	2955.98	2952.25
15	2946.44	2946.49	2944.02	λ	2951.87	2950.00	2951.99	2952.12	2959.85	λ	2955.50	2952.14
16	2946.52	2946.55		λ	2951.96	2949.84	2952.23	2952.47	2959.47	A	2955.58	2952.02
17	2946.60	2946.61	2944.11	λ	2952.05	2949.94	2952.43	2952.64	2959.27	λ	2955.42	2951.54
18	2946.72	2946.10	2944.13	λ	2951.83	2949.98	2952.57	2952.34	2959.31	λ	2955.25	2950.96
19	2946.80	2946.16	2944.17	λ	2951.43	2950.03	2953.58	2952.10	2959.25	λ	2954.85	2950.48
20	2946.88	2946.21	2944.34	A	2951.23	2950.12	2954.88	2950.83	2959.58	A	2954.65	2950.10
21	2947.00	2946.12	2944.43	A	2951.02	2950.19	2954.64	2950.57	2959.46	λ	2954.53	2950.00
22	2947.04	2945.88	2944.47	λ	2950.38	2950.25	2954.02	2950.35	2959.32	A	2954.05	2949.86
23	2946.74	2945.92	2944.50	λ	2950.46	2950.31	2953.54	2956.76	2959.08	λ	2953.61	2950.32
24	2946.46	2945.99	2944.54	2955.00	2949.92	2950.10	2953.24	2958.06	2959.01	λ	2953.38	2950.48
25	2946.45	2945.86	2944.56	2955.19	2950.00	2950.15	2953.38	2959.10	2958.86	λ	2953.22	2950.66
26	2946.52	2945.74	2944.60	2955.29	2950.11	2950.21	2953.52	2960.74	2958.66	λ	2953.06	2950.82
27	2946.65	2945.84	2944.40	2954.85	2950.20	2950.16	2953.00	2960.43	2958.37	2954.39	2952.82	2950.94
28	2946.56	2945.93	2943.34	2954.47	2950.30	2950.25	2952.40	2960.03	2958.50	2954.10	2952.66	2951.28
29	2947.33	2945.97	2943.36	2953.87	2949.52	2950.61	2952.38	2959.85	2958.40	2954.21	2952.14	2951.50
30	2947.23	2946.01	2942.96	2953.17		2950.44	2952.40	2959.74	2958.48	2954.02	2952.22	2951.75
31	2947.25		2942.65	2952.83		2952.01		2960.80		2954.10	2951.72	
MBAN	2947.49	2946.65	2944.31		2951.68	2950.09	2952.97	2954.08	2959.59		2954.26	2951.49
MAX	2949.48	2947.73	2946.06		2953.29	2952.01	2954.88	2960.80	2960.80		2956.42	2953.49
MIN	2946.44	2945.74	2942.65		2949.52	2949.52	2951.99	2950.35	2958.37		2951.72	2949.86

A No gage-height record.

50032590 LAGO DE MATRULLAS AT DAMSITE, PR

LOCATION.--Lat 18°12'46", long 66°28'50", Hydrologic Unit 21010001, in concrete house at damsite, and 5.8 mi (9.3 km) southwest of Orocovis.

DRAINAGE AREA. -- 4.46 mi 2 (11.55 km2).

RIRVATION RECORDS

PERIOD OF RECORD .-- May 1988 to current year.

GAGE .-- Water-stage recorder. Datum of gage is mean sea level.

REMARKS.--Lago Matrullas was completed in 1934. The dam is an earthfill structure about 120 ft (37 m) height, a top width of 30 ft (9 m) and a length of 710 ft (216 m), and has a maximum storage capacity of about 4,274 ac-ft (5.220 hm³) at top of dam elevation. The Matrullas Dam is owned by the Puerto Rico Electric Power Authority and is part of the Toro Negro Hydroelectric Project, a project developed by the P.R.B.P.A. for the primary purpose of generating electric power. Discharges from the Power Plants are collected by the Jacaguas River which flows into Guayabal Dam, at which dam they are regulated for irrigation of lands served by the Juana Días Canal. Gage-height and precipitation satellite telemetry at station.

EXTREMES OBSERVED FOR PERIOD OF RECORD. -- Maximum elevation 2,413.56 ft (735.65 m), Jan. 6, 1992; minimum elevation, 2,392.81 ft (729.33 m), Sept. 10, 1989.

EXTREMES OBSERVED FOR CURRENT YEAR.--Maximum elevation, 2,413.56 ft (735.65 m), Jan. 6; minimum elevation, 2,408.23 ft (734.03 m), Oct. 19.

Capacity Table (based on data from Puerto Rico Electric Power Authority)

Blevation, in feet	Contents, in acre-feet	Elevation, in feet	Contents, in acre-feet
2,338	2	2,399	1,845
2,360	302	2,415	2,945

ELEVATION (FEET NGVD), WATER YEAR OCTOBER 1991 TO SEPTEMBER 1992 DAILY OBSERVATION AT 24:00 VALUES

DAY	ост	NOV	DEC	JAN	FEB	MAR	APR	MAY	JUN	JOL	AUG	SEP
1	2409.81	2409.26	2408.84	2410.46	2408.80	2409.58	2409.88	2411.34	2412.46	2411.77	2411.77	2410.46
2	2409.60	2409.41	2408.69	2410.29	2408.81	2409.73	2410.20	2411.53	2411.96	2411.80	2411.81	2410.38
3	2409.37	2409.55	2408.57	2410.03	2408.85	2409.86	2410.64	2411.52	2411.90	2411.77	2411.70	2410.32
4	2409.13	2409.53	2408.51	2409.81	2408.87	2409.90	2410.82	2411.32	2411.89	2411.75	2411.66	2410.24
5	2409.15	2409.49	2408.43	2412.87	2408.86	2409.92	2410.97	2411.22	2411.90	2411.79	2411.70	2410.30
6	2409.25	2409.49	2408.33	2412.55	2409.40	2409.99	2410.86	2411.26	2411.88	2411.75	2411.73	2410.42
7	2409.52	2409.50	2408.39	2412.04	2409.74	2409.97	2410.98	2411.30	2411.95	2411.72	2411.74	2410.53
8	2409.80	2409.54	2408.48	2411.72	2409.76	2410.08	2411.02	2411.30	2411.95	2411.78	2411.75	2411.24
9	2409.92	2409.64	2408.33	2411.54	2409.93	2410.12	2411.24	2411.42	2411.88	2411.76	2411.76	2411.53
10	2410.06	2409.75	2408.32	2411.38	2409.88	2410.18	2411.20	2411.48	2411.86	2411.72	2411.77	2411.49
11	2410.03	2409.87	2408.40	2411.18	2409.78	2410.00	2410.98	2411.25	2411.88	A	2411.72	2411.44
12	2409.77	2409.75	2408.48	2411.45	2409.60	2409.76	2411.06	2411.58	2411.88	λ	2411.70	2411.27
13	2409.41	2409.45	2408.55	2411.40	2409.40	2409.56	2410.95	2411.54	2411.90	λ	2411.66	2411.29
14	2409.11	2409.07	2408.64	2411.20	2409.28	2409.27	2410.78	2411.69	2411.89	2411.75	2411.66	2411.24
15	2408.84	2408.92	2408.72	2410.96	2409.24	2409.23	2410.74	2411.64	2411.82	2411.74	2411.57	2411.17
16	2408.65	2408.99	2408.80	2410.92	2409.35	2409.06	2411.27	2411.91	2411.80	2411.73	2411.61	2411.11
17	2408.47	2409.07	2408.88	2410.98	2409.52	2409.00	2411.42	2412.38	2411.81	2411.73	2411.60	2410.99
18	2408.27	2409.05	2408.96	2410.78	2409.49	2409.00	2411.43	2411.80	2411.84	2411.76	2411.54	2410.76
19	2408.28	2409.13	2409.03	2410.58	2409.34	2408.98	2411.93	2411.64	2411.80	2411.79	2411.42	2410.46
20	2408.39	2409.03	2409.29	2410.56	2409.30	2408.94	2412.18	2411.56	2411.82	2411.78	2411.52	2410.19
21	2408.38	2408.89	2409.71	2410.42	2409.28	2409.03	2411.56	2411.50	2411.86	2411.74	2411.62	2410.02
22	2408.54	2408.65	2409.87	2410.27	2409.08	2409.18	2411.34	2411.56	2411.82	2411.67	2411.49	2409.95
23	2408.53	2408.66	2409.97	2410.12	2409.11	2409.30	2411.27	2412.80	2411.78	2411.69	2411.29	2410.01
24	2408.36	2408.77	2410.04	2409.98	2409.14	2409.26	2411.30	2412.48	2411.78	2411,67	2411.14	2410.15
25	2408.31	2408.69	2410.13	2409.88	2409.14	2409.16	2411.42	2412.28	2411.76	2411.73	2411.01	2410.14
26	2408.45	2408.61	2410.23	2410.02	2409.16	2409.05	2411.44	2412.51	2411.75	2411.76	2410.93	2410.03
27	2408.57	2408.61	2410.32	2409.94	2409.19	2409.00	2411.38	2412.12	2411.74	2411.77	2410.87	2410.07
28	2408.58	2408.70	2410.41	2409.78	2409.32	2409.18	2411.45	2411.91	2411.79	2411.69	2410.85	2410.09
29	2408.84	2408.68	2410.49	2409.58	2409.44	2409.52	2411.34	2411.86	2411.78	2411.66	2410.67	2410.09
30	2409.16	2408.76	2410.45	2409.28		2409.66	2411.34	2411.81	2411.78	2411.64	2410.66	2410.14
31	2409.21		2410.41	2409.06		2409.77		2412.07		2411.69	2410.57	
MBAN	2409.02	2409.15	2409.18	2410.68	2409.31	2409.49	2411.15	2411.73	2411.86		2411.43	2410.58
MAX	2410.06	2409.87	2410.49	2412.87	2409.93	2410.18	2412.18	2412.80	2412.46		2411.81	2411.53
MIN	2408.27	2408.61	2408.32	2409.06	2408.80	2408.94	2409.88	2411.22	2411.74		2410.57	2409.95

A No gage-height record.

50034000 RIO BAUTA NEAR OROCOVIS, PR

LOCATION.--Lat 18°14'10", long 66°27'18", Hydrologic Unit 21010001, on left bank, at bridge on Highway 157 (12.1 km), and 4.2 mi (6.8 km) west of Orocovis.

DRAINAGE AREA. -- 16.7 mi2 (43.3 km2).

WATER-DISCHARGE RECORDS

PERIOD OF RECORD.--February 1959 to April 1966 (annual low-flow measurements only), February to September 1969 (occasional measurements only), October 1969 to September 1982, October 1988 to current year.

GAGE.--Water-stage recorder and crest-stage gage. Datum of gage is 772.82 ft (235.556 m) above mean sea level.

REMARKS.--Records fair except those for estimated daily discharges, which are poor. Gage-height and precipitation satellite telemetry at station.

		DISCHARGE	, CUBIC	FEET PER		WATER YEAR Y MRAN VALU		1991 TO	september	1992		
DAY	OCT	NOV	DEC	JAN	FEB	MAR	APR	MAY	JUN	JUL	λUG	SEP
1	11	43	7.7	7.3	14	11	23	23	e 160	19	15	7.7
2	11	32	7.9	7.2	14	9.8	35	56	e260	24	13	7.7
3	10	19	8.1	7.2	13	9.9	30	32	e110	20	12	7.8
4 5	9.9	14 12	8.3	7.2	13	9.7	17	23	e70	19	11	8.4 8.7
3	10	14	8.2	904	13	9.5	13	19	e56	18	14	0.7
6	9.9	13	7.8	922	34	9.3	13	23	e50	17	23	9.5
7	54	16	7.4	149	34	9.4	38	22	e45	17	14	8.9
8 9	30 20	24 14	7.4 8.0	66 43	32 22	10 9.8	23 74	17 15	e43 e43	21 19	14 13	26 23
10	16	12	8.3	36	18	13	71	14	e41	17	17	11
11	14	••		20			••		e52	17	17	9.0
12	12	11 10	8.3 7.8	30 30	16 15	9.5 8.8	29 19	14 37	e39	16	15	8.5
13	îi	9.9	7.7	33	e28	8.6	15	32	e35	16	14	8.1
14	10	9.7	7.9	30	e18	8.4	13	59	e33	17	14	8.1
15	9.9	9.7	7.5	25	e15	8.3	27	94	e 31	15	15	7.8
16	9.8	10	7.5	26	e14	8.1	99	48	e30	16	13	8.0
17	9.5	9.4	7.7	28	e13	11	89	135	e 30	15	12	8.5
18	9.2	9.0	7.8	22	e12	11	53	94	e 29	15	11	8.3
19	9.3	8.7	7.4	20	e12	9.4	276	177	29	15	11	8.1
20	10	8.5	17	18	e 11	8.6	195	103	28	15	15	8.4
21	9.8	8.6	28	17	e11	8.3	101	68	28	14	21	8.8
22	13		11	17	e 11	9.1	48	43	28	e13	12	8.2
23	14	8.6	9.3	16	e11	8.3	33	315	26	e 16	10	8.2
24	11	8.6	8.5	17	e10	7.9	27	e671	24	e15	9.3	10
25	10	9.4	8.4	16	11	11	22	e200	23	e13	8.7	8.3
26	10	8.6	7.7	16	9.9	9.0	20	e410	23	e12	8.4	7.8
27	9.8	8.5	7.9	15	9.9	15	18	e220	22	e12	8.5	7.5
28 29	9.2 35	8.5 7.9	7.9 7.7	15 15	12 12	17 91	16	e110 e70	21 20	e12 e11	8.6 8.1	7.2 9.2
30	44	7.6	7.6	15		37	16 18	e60	19	e11	7.9	18
31	63		7.6	15		19		e50		014	8.0	
TOTAL	515.3	380.0 2	77.3	2584.9	458.8	425.7	1471	3254	1448	491	393.5	294.7
MEAN	16.6		8.95	83.4	15.8	13.7	49.0	105	48.3	15.8	12.7	9.82
MAX	63	43	28	922	34	91	276	671	260	24	23	26
MIN	9.2	7.6	7.4	7.2	9.9	7.9	13	14	19	11	7.9	7.2
AC-FT	1020	754	550	5130	910	844	2920	6450	2870	974	781	585
CFSM	1.00	.76	.54	4.99	.95	. 82	2.94	6.29	2.89	. 95	.76	. 59
IN.	1.15	. 85	. 62	5.76	1.02	. 95	3.28	7.25	3.23	1.09	.88	. 66
e Ra	stimated											
STATIST	CICS OF M	ONTHLY MEAN	DATA FO	R WATER Y	RARS 196	9 - 1992. I	Y WATER Y	TRAR (WY)	,			
						•				40 4		F4 2
MRAN MAX	99.3 392	59.2 205	29.8 108	20.9 83.4	14.1 30.9	16.3 59.9	27.2 80.2	49.8 179	20.4 78.6	17.1 104	22.7 152	54.3 149
(WY)	1971		1971	1992	1971	1972	1980	1981	1979	1979	1979	1979
MIN	15.8		8.95	6.62	6.26	5.57	6.23	7.05	4.10	5.22	6.76	9.82
(WY)	1976		1992	1973	1977	1977	1977	1973	1977	1974	1976	1992
STIMMADA	Y STATIST	TCS	ROP 1	991 CALEN	NID VOID	POL	R 1992 WAS	MPD VP1D		WATER YE	ADG 1969	1 - 1992
			FOR I		WAR IBAR	FUF		And: nu		WAL MELAN	1703	
ANNUAL				6282.0 17.2			11994.2 32.8			35.8		
	P ANNUAL :	MRAN		17.2			34.0			79.3		1979
	ANNUAL M									13.2		1977
Highest	r DAILY M	RAN		362			922	Jan 6		3870		9 1970
	DAILY ME			6.1			7.2			3.0		23 1977
		Y MINIMUM		7.1	Jul 1			Dec 29		3.4		20 1977
		Bak Flow Bak Stage					5920 15 72	Jan 5 Jan 5		17800 21.90		9 1970 9 1970
	TANBOUS L						7.2			21.90		23 1977
	RUNOFF (12460			23790	'		25950		
ANNUAL	RUNOFF (CFSM)		1.03			1.96			2.14		
	RUNOFF (13.99			26.72			29.14		
	CENT EXCE			26			52			66		
DU PER(CENT EXCE	PUS		11			14			13		

50035000 RIO GRANDE DE MANATI AT CIALES, PR

LOCATION.--Lat 18°19'26", long 66°27'36", Hydrologic Unit 21010001, on left bank, 1.6 mi (2.6 km) upstream from Hwy 145 bridge, 0.8 mi (1.3 km) downstream from Quebrada Saliente, 0.9 mi (1.4 km) upstream from Quebrada Cojo Vales, and 1.2 mi (1.9 km) southeast of Ciales.

DRAINAGE AREA.--128 mi² (332 km²), excludes 6.0 mi² (15.5 km²), the runoff from which is diverted through El Guineo and de Matrullas reservoirs.

WATER-DISCHARGE RECORDS

PERIOD OF RECORD.--September 1946 to September 1953, May 1956 to December 1957 (unpublished, available in files of Caribbean District Office and in the National Water Data Storage and Retrieval System, Washington, D.C.), February 1959 to September 1960 (monthly discharge measurements only), October 1960 to current year. Equivalent record from January 1971 to December 1972 published as 50035200 Río Grande de Manatí at Highway 145 at Ciales at site 1.6 mi (2.6 km) downstream, drainage area 132 mi² (342 km²).

GAGE.--Water-stage recorder. Elevation of gage is 140 ft (43 m), from topographic map. Prior to Apr. 1, 1962, staff gage, read twice daily, at site 100 ft (30 m) upstream at same datum. January 1971 to December 1972 at site 1.6 mi (2.6 km) downstream at different datum.

REMARKS.--Records fair except those for estimated daily discharges, which are poor. Gage-height and precipitation satellite telemetry at station.

EXTREMES OUTSIDE PERIOD OF RECORD.--Approximate gage heights of major floods, pointed out by local residents are as follows: August 1899, 50 ft (15 m), September 1928, 36 ft (11 m), and September 1932, 34 ft (10 m) at site 1.6 mi (2.6 km) upstream.

		DISCHAR	GE, CUBIC	FEET PER		WATER Y	EAR OCTOBE	R 1991 TO	September	1992		
DAY	ост	NOV	DEC	JAN	PEB	MAR MAR	APR	MAY	JUN	JUL	AUG	SEP
1	66	e1300	54	52	79	61	e150	e180	1710	102	114	93
2	64	e940	54	51	76	57	e84	e1600	965	102	81	90
3	61	e320	54	48	75	56	e580	e410	480	143	78	88
4	55	e210	54	45	78	56	e130	e220	376	105	112	105
5	52	e160	54	5110	79	56	e88	e150	328	99	120	151
6	52	130	54	e5240	110	56	e74	316	284	98	216	155
7	59	119	52	e616	237	54	e84	198	275	95	108	153
8	272	148	52	e385	178	89	e110	137	272	122	86	173
9	129	116	52	265	134	98	e1000	109	263	131	79	237
10	78	94	61	235	111	124	e2200	104	326	102	86	124
11	74	80	55	193	100	92	e350	97	273	95	168	95
12	64	73	52	236	149	68	e200	e 90	228	94	93	85
13	56	72	51	204	96	58	e140	e190	213	93	80	75
14	52	67	50	195	88	55	99	e130	204	122	72	72
15	50	67	49	160	82	54	90	e190	181	101	96	72
16	47	68	47	153	77	54	e130	e160	169	102	88	70
17	45	66	47	235	72	61	e390	e250	149	99	76	84
18	43	62	47	158	71	100	e180	e660	142	94	69	92
19	106	60	47	132	71	81	e450	e500	145	91	69	118
20	116	57	66	119	69	67	e1800	e1200	141	91	169	238
21	70	57	302	110	69	58	e640	e880	145	90	248	105
22	56	55	122	105	69	57	e240	e390	144	86	196	83
23	85	54	80	100	67	61	e160	e1400	131	83	119	76
24	60	73	64	97	64	55	e130	e4500	129	101	108	107
25	63	69	57	97	64	57	e120	e2300	125	89	122	86
26	59	62	52	97	65	117	e110	e3500	118	77	103	7 7
27	54	57	52	88	65	324	e100	1030	117	75	138	73
28	47	57	53	83	64	265	e96	529	114	75	110	75
29 30	206 e1100	57 56	59 53	81	62	e200 e320	e94 e170	373 208	109 106	70 67	99 93	83 106
31	e920		52	81 81		e110	e1/U	894		67	93	100
TOTAL	4261	4806	1998	14852	2621	3021	10189	22895 739	8362	2961 95.5	3489	3241 108
MBAN MAX	137 1100	160 1300	64.5 302	479 5240	90.4 237	97.5 324	340 2200	4500	279 1710	143	113 248	238
MIN	43	54	47	45	62	54	74	90	106	67	69	70
AC-PT	8450	9530	3960	29460	5200	5990	20210	45410	16590	5870	6920	6430
CFSM	1.07	1.25	.50	3.74	.71	.76	2.65	5.77	2.18	.75	.88	.84
IN.	1.24	1.40	.58	4.32	.76	.88	2.96	6.65	2.43	.86	1.01	.94
e Bi	stimated											
STATIST	TICS OF M	ONTHLY MEA	N DATA FO	R WATER Y	BARS 1961	- 1992	, BY WATER	YEAR (WY)				
MEAN	482	382	276	174	138	151	283	472	162	110	154	286
MAX	2422	1006	1296	479	424	477	1174	2293	458	438	1212	994
(WY)	1971	1971	1966	1992	1969	1969	1969	1985	1979	1979	1979	1979
MIN	97.8	67.6	64.5	64.1	47.9	36.5	28.5	71.4	40.2	40.2	33.6	77.7
(WY)	1987	1974	1992	1984	1984	1984	1984	1989	1977	1974	1984	1977
	Y STATIST	ICS	FOR 1	991 CALEN	DAR YEAR		FOR 1992 W	VATER YEAR		WATER	YEARS 1961	- 1992
ANNUAL				48803			82696					
ANNUAL				134			226			256		4054
	r annual Annual M									520 118		1971 1974
	DAILY M			2030	Jul 16		5240	Jan 6		42700	May 1	8 1985
	DAILY ME			43	Oct 18		43	Oct 18		5.		9 1971
		MINIMUM Y		47	Aug 8		48	Dec 13		22	Apr 1	6 1984
	TANEOUS P				-		38100	Jan 6		125000		9 1970
		BAK STAGE						II Jan 6		24.		9 1970
	raneous l Runoff (96800			43 164000	Oct 17		20 185800	Apr 2	0 1984
	RUNOFF (1.04			1.7	17		2.	00	
	RUNOFF (14.18			24.0			27.		
10 PBR	CENT EXCE	RDS		217			327			458		
	CENT EXCE			81			96			118		•
90 PERC	CENT BXCE	RNZ		53			54			55		

50035500 RIO GRANDE DE MANATI AT HIGHWAY 149 AT CIALES, RP

WATER-QUALITY RECORDS

LOCATION.--Lat 18°20'46", long 66°28'06", at bridge on Highway 149, about 800 ft (244 m) upstream from confluence with Río Cialitos, 0.5 mi (0.8 km) north of Ciales plaza.

DRAINAGE AREA.--136 mi² (352 km²) this excludes the 6 mi² (15.5 km²) upstream from Lago El Guineo and Lago de Matrullas, flow from which is diverted to Río Jacaguas.

PERIOD OF RECORD .-- Water years 1979 to current year.

WATER-QUALITY DATA, WATER YEAR OCTOBER 1991 TO SEPTEMBER 1992

D ATE	TIME	DIS- CHARGE, INST. CUBIC FEBT PER SECOND	SPB- CIFIC CON- DUCT- ANCE (US/CM)	PH WATER WHOLE FIELD (STAND- ARD UNITS)	TEMPER- ATURE WATER (DEG C)	TUR- BID- ITY (NTU)	OXYGEN, DIS- SOLVED (MG/L)	OXYGEN, DIS- SOLVED (PER- CENT SATUR- ATION)	OXYGEN DEMAND, CHEM- ICAL (HIGH LEVEL) (MG/L)	COLI- FORM, FECAL, 0.45 UM-MP (COLS./ 100 ML)	STREP- TOCOCCI FECAL, (COLS. PER 100 ML)
ост 1991											
21	1130	96	240	7.0	26.0	17	5.5	67	<10	53000	410
DEC											
30	1055	47	265	8.5	24.0	4.9	<24.0	98	<10	K72	K170
FEB 1992											
20	1005	55	250	8.1	25.0	6.4	7.6	84	<10	36	K100
MAY											
15	1045	B4 00	134	6.8	23.5	57	6.8	79	22	430	210
JOL											
02	0930	93	330	8.0	29.0	2.2	6.6	74	<10	200	30
AUG											
29	1145	87	443	7.5	29.0	0.50	7.8	86	<10	200	K150

DATE	HARD- NESS TOTAL (MG/L AS CACO3)	CALCIUM DIS- SOLVED (MG/L AS CA)	MAGNE- SIUM, DIS- SOLVED (MG/L AS MG)	SODIUM, DIS- SOLVED (MG/L AS NA)	SODIUM AD- SORP- TION RATIO	POTAS- SIUM, DIS- SOLVED (MG/L AS K)	ALKA- LINITY WAT WH TOT FET FIELD MG/L AS CACO3	SULFIDE TOTAL (MG/L AS S)	SULFATE DIS- SOLVED (MG/L AS SO4)	CHLO- RIDE, DIS- SOLVED (MG/L AS CL)
OCT 1991										
21	95	24	8.6	13	0.6	1.9	100	<0.5	9.7	10
DEC										
30 FRB 1992							110			
20							95			
MAY										
15	64	16	5.8	9.1	0.5	1.7	64	<0.5	7.2	12
JUL 02							87			
AUG							0,			
29	91	23	8.1	12	0.5	1.9	90		9.0	14
DATE	FLUO- RIDE, DIS- SOLVED (MG/L AS F)	SILICA, DIS- SOLVED (MG/L AS SIO2)	SOLIDS, SUM OF CONSTI- TUENTS, DIS- SOLVED (MG/L)	SOLIDS, DIS- SOLVED (TONS PER DAY)	RESIDUE TOTAL AT 105 DEG. C, SUS- PENDED (MG/L)	NITRO- GEN, NITRATE TOTAL (MG/L AS N)	NITRO- GEN, NITRITB TOTAL (MG/L AS N)	NITRO- GEN, NO2+NO3 TOTAL (MG/L AS N)	NITRO- GEN, AMMONIA TOTAL (MG/L AS N)	NITRO- GEN, ORGANIC TOTAL (MG/L AS N)
OCT 1991										
21 DEC	0.30	22	149	38.9	3	0.360	0.020	0.380	0.040	0.26
30			~ -		1	0.200	0.010	0.210	0.020	
FBB 1992					_					
20					12		<0.010	0.200	0.010	
MAY 15 JUL	0.20	20	110		24	0.190	0.050	0.240	0.080	
02 AUG					8	0.480	0.010	0.490	0.030	0.57

K = non-ideal count
B = estimate

50035500 RIO GRANDE DE MANATI AT HIGHWAY 149 AT CIALES, PR--Continued

WATER-QUALITY DATA, WATER YEAR OCTOBER 1991 TO SEPTEMBER 1992

DATE	NITRO- GEN, AM- MONIA + ORGANIC TOTAL (MG/L AS N)	NITRO- GEN, TOTAL (MG/L AS N)	NITRO- GEN, TOTAL (MG/L AS NO3)	PHOS- PHORUS TOTAL (MG/L AS P)	ARSENIC TOTAL (UG/L AS AS)	BARIUM, TOTAL RECOV- ERABLE (UG/L AS BA)	BORON, TOTAL RECOV- ERABLE (UG/L AS B)	CADMIUM TOTAL RECOV- ERABLE (UG/L AS CD)	CHRO- MIUM, TOTAL RECOV- ERABLE (UG/L AS CR)	COPPER, TOTAL RECOV- ERABLE (UG/L AS CU)
OCT 1991										
21 DBC	0.30	0.68	3.0	0.110	<1	<100	<10	<1	1	10
30 FEB 1992	<0.20			0.070						
20 MAY	<0.20			0.050						
15 JUL	<0.20			0.140	<1	<100	20	<1	<1	10
02 AUG	0.30	0.38	1.7	0.070						
29	<0.20			0.050						
DATE	IRON, TOTAL RECOV- ERABLE (UG/L AS FE)	LEAD, TOTAL RECOV- ERABLE (UG/L AS PB)	MANGA - NESE, TOTAL RECOV - ERABLE (UG/L AS MN)	MERCURY TOTAL RECOV- ERABLE (UG/L AS HG)	SELE- NIUM, TOTAL (UG/L AS SE)	SILVER, TOTAL RECOV- ERABLE (UG/L AS AG)	ZINC, TOTAL RECOV- ERABLE (UG/L AS ZN)	CYANIDE TOTAL (MG/L AS CN)	PHENOLS TOTAL (UG/L)	METHY- LENE BLUE ACTIVE SUB- STANCE (MG/L)
OCT 1991 21	TOTAL RECOV- ERABLE (UG/L	TOTAL RECOV- ERABLE (UG/L	NESE, TOTAL RECOV- ERABLE (UG/L	TOTAL RECOV- ERABLE (UG/L	NIUM, TOTAL (UG/L	TOTAL RECOV- ERABLE (UG/L	TOTAL RECOV- ERABLE (UG/L	TOTAL (MG/L	TOTAL	Lene Blue Active Sub- Stance
OCT 1991 21 DEC 30	TOTAL RECOV- ERABLE (UG/L AS FE)	TOTAL RECOV- ERABLE (UG/L AS PB)	NESE, TOTAL RECOV- ERABLE (UG/L AS MN)	TOTAL RECOV- ERABLE (UG/L AS HG)	NIUM, TOTAL (UG/L AS SE)	TOTAL RECOV- ERABLE (UG/L AS AG)	TOTAL RECOV- ERABLE (UG/L AS ZN)	TOTAL (MG/L AS CN)	TOTAL (UG/L)	LENE BLUE ACTIVE SUB- STANCE (MG/L)
OCT 1991 21 DEC 30 FEB 1992 20	TOTAL RECOV- ERABLE (UG/L AS FE)	TOTAL RECOV- ERABLE (UG/L AS PB)	NESE, TOTAL RECOV- ERABLE (UG/L AS MN)	TOTAL RECOV- ERABLE (UG/L AS HG)	NIUM, TOTAL (UG/L AS SE)	TOTAL RECOV- ERABLE (UG/L AS AG)	TOTAL RECOV- ERABLE (UG/L AS ZN)	TOTAL (MG/L AS CN)	TOTAL (UG/L)	LENE BLUE ACTIVE SUB- STANCE (MG/L)
OCT 1991 21 DEC 30 FEB 1992 20 MAY 15	TOTAL RECOV- ERABLE (UG/L AS FE)	TOTAL RECOV- ERABLE (UG/L AS PB)	NESE, TOTAL RECOV- ERABLE (UG/L AS MN)	TOTAL RECOV- ERABLE (UG/L AS HG) <0.10	NIUM, TOTAL (UG/L AS SE)	TOTAL RECOV- ERABLE (UG/L AS AG)	TOTAL RECOV- ERABLE (UG/L AS ZN) <10	TOTAL (MG/L AS CN) <0.010	TOTAL (UG/L)	LENE BLUE ACTIVE SUB- STANCE (MG/L)
OCT 1991 21 DEC 30 FEB 1992 20	TOTAL RECOV- BRABLE (UG/L AS FE) 1300	TOTAL RECOV- ERABLE (UG/L AS PB)	NESE, TOTAL RECOV- ERABLE (UG/L AS MN)	TOTAL RECOV- ERABLE (UG/L AS HG) <0.10	NIUM, TOTAL (UG/L AS SE)	TOTAL RECOV- ERABLE (UG/L AS AG)	TOTAL RECOV- ERABLE (UG/L AS ZN)	TOTAL (MG/L AS CN) <0.010	TOTAL (UG/L)	LENE BLUE ACTIVE SUB- STANCE (MG/L)

50035950 RIO CIALITOS AT HIGHWAY 649 AT CIALBS, PR

WATER-QUALITY RECORDS

LOCATION.--Lat 18°20'18", long 66°28'28", 100 ft (30 m) upstream from bridge on Highway 649, 0.7 mi (1.1 km) upstream from mouth, and about 0.4 mi (0.6 km) west of Ciales plaza.

DRAINAGE AREA. -- 17.0 mi 2 (44.0 km2).

PERIOD OF RECORD. -- Water years 1969-71, 1974 to current year.

WATER-QUALITY DATA, WATER YEAR OCTOBER 1991 TO SEPTEMBER 1992

DATE	TIME	DI CHAR INS CUB FE PE SEC	GE, SPI T. CII CIC CON	PIC WHO N- PIE CT- (STA CB AF	'ER OLE OLD TEMI ND- ATO	ire Ter	TUR- BID- ITY (NTU)	OXYG DI: SOL' (MG	Soi En, (Pi S- Ci VED SAT	S- DE LVED C ER- I ENT (TUR- LE	MAND, HEM- CAL HIGH VEL) (COLI- FORM, FRCAL, 0.45 UM-MF COLS./ 00 ML)	STREP- TOCOCCI FECAL, (COLS. PER 100 ML)
OCT 1991 21	1240	4	.0	194	7.2	23.5	82		6.0	70	22	K60000	6800
DEC 30 FEB 1992	1200	0	.70	232	8.4	1.0	2.4	:	9.4	109	<10	K850	340
20 MAY	1110	3	.0	236	8.1	22.5	1.7		8.8	101	<10	330	520
15 JUL	1245	3	. 6	225	7.1	26.0	2.0	•	7.8	95	<10	350	220
02	1045	5	.0	420	8.3	26.5	13	;	8.5	86	<10	460	K870
29	1300	3	. 6	213	7.7	26.5	12	;	8.2	81	<10	K900	250
DATE	N T	ARD- IESS OTAL MG/L AS	CALCIUM DIS- SOLVED (MG/L AS CA)	MAGNE- SIUM, DIS- SOLVED (MG/L AS MG)	SODIUM, DIS- SOLVED (MG/L AS NA)	SODIU AD- SORP- TIOI RATIO	- N :	POTAS- SIUM, DIS- SOLVED (MG/L AS K)	ALKA- LINITY WAT WH TOT FET FIELD MG/L AS CACO3	SULFID TOTAL (MG/L AS S)	SOLV (MG/	TR RI DI RD SO L (M	LO- DE, S- LVED (G/L (CL)
OCT 1991 21 DRC		75	22	4.8	9.7	0	. 5	2.8	70	<0.	5 9.	0	9.7
30 FEB 1992									100				 -
20 MAY									100				
15 JUL		80	23	5.5	9.8	0	. 5	2.0	75	<0.	5 6.	3 1	.2
02 AUG									98				
29		84	24	5.8	9.9	0.	. 5	1.8	81		6.	2 1	.1
DATE	R S	LUO- RIDE, DIS- ROLVED MG/L RS F)	SILICA, DIS- SOLVED (MG/L AS SIO2)	SOLIDS, SUM OF CONSTI- TUENTS, DIS- SOLVED (MG/L)	SOLIDS, DIS- SOLVED (TONS PER DAY)	RESIDE TOTAL AT 10: DEG. (SUS- PENDE)	5 C, N;	NITRO- GEN, ITRATE IOTAL (MG/L AS N)	NITRO- GEN, NITRITE TOTAL (MG/L AS N)	NITRO GEN, NO2+NO TOTAL (MG/L AS N)	GEN 3 AMMON TOTA (MG/	, GIA ORG L TO L (M	TRO- EN, ENIC TAL G/L
OCT 1991 21		<0.10	19	119	1.29	,	49	1.34	0.060	1.40	0.0	80	0.62
DEC 30						•	1	0.540	0.010	0.55			
FRB 1992 20							9		<0.010	0.48			
MAY 15		0.20	27	135	1.31		3	0.530	0.010	0.54	0 0.0	30	
JUL 02 AUG						:	19	0.420	0.010	0.43	0 0.0	20	
AUG 29		0.10	25	137	1.33	:	16	0.590	0.010	0.60	0.0	50	

RIO GRANDE DE MANATI BASIN

50035950 RIO CIALITOS AT HIGHWAY 649 AT CIALES, PR--Continued

WATER-QUALITY DATA, WATER YEAR OCTOBER 1991 TO SEPTEMBER 1992

DATE	NITRO- GEN, AM- MONIA + ORGANIC TOTAL (MG/L AS N)	NITRO- GEN, TOTAL (MG/L AS N)	NITRO- GEN, TOTAL (MG/L AS NO3)	PHOS- PHORUS TOTAL (MG/L AS P)	ARSENIC TOTAL (UG/L AS AS)	BARIUM, TOTAL RECOV- ERABLE (UG/L AS BA)	BORON, TOTAL RECOV- ERABLE (UG/L AS B)	CADMIUM TOTAL RECOV- ERABLE (UG/L AS CD)	CHRO- MIUM, TOTAL RECOV- ERABLE (UG/L AS CR)	COPPER, TOTAL RECOV- ERABLE (UG/L AS CU)
OCT 1991					_				_	
21 Dec	0.70	2.1	9.3	0.150	<1	<100	20	<1	2	10
30 FBB 1992	<0.20			0.070						
20 MAY	<0.20			0.060						
15	<0.20			0.050	<1	<100	20	<1	<1	<10
JUL 02 Aug	<0.20			0.080						
29	<0.20			0.140						
DATE	IRON, TOTAL RECOV- ERABLE (UG/L AS FE)	LEAD, TOTAL RECOV- ERABLE (UG/L AS PB)	MANGA- NESE, TOTAL RECOV- ERABLE (UG/L AS MN)	MERCURY TOTAL RECOV- ERABLE (UG/L AS HG)	SELE- NIUM, TOTAL (UG/L AS SE)	SILVER, TOTAL RECOV- ERABLE (UG/L AS AG)	ZINC, TOTAL RECOV- ERABLE (UG/L AS ZN)	CYANIDE TOTAL (MG/L AS CN)	PHENOLS TOTAL (UG/L)	METHY- LENE BLUE ACTIVE SUB- STANCE (MG/L)
OCT 1991	TOTAL RECOV- ERABLE (UG/L AS FE)	TOTAL RECOV- ERABLE (UG/L AS PB)	NESE, TOTAL RECOV- ERABLE (UG/L AS MN)	TOTAL RECOV- ERABLE (UG/L AS HG)	NIUM, TOTAL (UG/L AS SE)	TOTAL RECOV- ERABLE (UG/L AS AG)	TOTAL RECOV- ERABLE (UG/L AS ZN)	TOTAL (MG/L AS CN)	TOTAL (UG/L)	LENE BLUE ACTIVE SUB- STANCE (MG/L)
	TOTAL RECOV- ERABLE (UG/L	TOTAL RECOV- ERABLE (UG/L	NESE, TOTAL RECOV- ERABLE (UG/L	TOTAL RECOV- ERABLE (UG/L	NIUM, TOTAL (UG/L	TOTAL RECOV- BRABLE (UG/L	TOTAL RECOV- BRABLE (UG/L	TOTAL (MG/L	TOTAL	LENE BLUE ACTIVE SUB- STANCE
OCT 1991 21 DEC 30	TOTAL RECOV- ERABLE (UG/L AS FE)	TOTAL RECOV- ERABLE (UG/L AS PB)	NESE, TOTAL RECOV- ERABLE (UG/L AS MN)	TOTAL RECOV- ERABLE (UG/L AS HG)	NIUM, TOTAL (UG/L AS SE)	TOTAL RECOV- ERABLE (UG/L AS AG)	TOTAL RECOV- ERABLE (UG/L AS ZN)	TOTAL (MG/L AS CN)	TOTAL (UG/L)	LENE BLUE ACTIVE SUB- STANCE (MG/L)
OCT 1991 21 DEC 30 FEB 1992 20	TOTAL RECOV- ERABLE (UG/L AS FE)	TOTAL RECOV- ERABLE (UG/L AS PB)	NESE, TOTAL RECOV- ERABLE (UG/L AS MN)	TOTAL RECOV- ERABLE (UG/L AS HG)	NIUM, TOTAL (UG/L AS SE)	TOTAL RECOV- ERABLE (UG/L AS AG)	TOTAL RECOV- ERABLE (UG/L AS ZN)	TOTAL (MG/L AS CN)	TOTAL (UG/L)	LENE BLUE ACTIVE SUB- STANCE (MG/L)
OCT 1991 21 DEC 30 FEB 1992 20 MAY 15	TOTAL RECOV- ERABLE (UG/L AS FE)	TOTAL RECOV- ERABLE (UG/L AS PB)	NESE, TOTAL RECOV- ERABLE (UG/L AS MN)	TOTAL RECOV- ERABLE (UG/L AS HG) <0.10	NIUM, TOTAL (UG/L AS SE)	TOTAL RECOV- ERABLE (UG/L AS AG)	TOTAL RECOV- ERABLE (UG/L AS ZN) 10	TOTAL (MG/L AS CN)	TOTAL (UG/L)	LENE BLUE ACTIVE SUB- STANCE (MG/L)
OCT 1991 21 DEC 30 FEB 1992 20	TOTAL RECOV- BRABLE (UG/L AS FE) 4000	TOTAL RECOV- ERABLE (UG/L AS PB)	NESE, TOTAL RECOV- ERABLE (UG/L AS MN)	TOTAL RECOV- BRABLE (UG/L AS HG) <0.10	NIUM, TOTAL (UG/L AS SE) <1	TOTAL RECOV- RRABLE (UG/L AS AG) <1	TOTAL RECOV- ERABLE (UG/L AS ZN)	TOTAL (MG/L AS CN) <0.010	TOTAL (UG/L) 2 	LENE BLUE ACTIVE SUB- STANCE (MG/L) 0.02

50038100 RIO GRANDE DE MANATI AT HIGHWAY 2 NEAR MANATI, PR

LOCATION.--Lat 18°25'52", long 66°31'37", Hydrologic Unit 21010002, at bridge on Highway 2, and 2.3 mi (3.7 km) west of Manatí.

DRAINAGE AREA.--197 mi² (510 km²), approximately, of which about 38 mi² (98 km²) is partly or entirely noncontributing, excludes 6.0 mi² (15.5 km²) upstream from Lago El Guineo and Lago de Matrullas.

WATER-DISCHARGE RECORDS

PERIOD OF RECORD. -- 1963-68 (annual maximum discharge only), February 1970 to current year.

REVISED RECORDS.--WRD PR-86-1: 1970-71 (M), 1975, 1979, 1982-85 (P).

GAGE.--Water-stage recorder. Elevation of gage is 14 ft (4 m), from topographic map. Prior to 1968 crest-stage gage at same site and datum 3.57 ft (1.09 m) lower.

REMARKS.--Records fair except those for estimated daily discharges, which are poor. Gage-height and precipitation satellite telemetry at station.

EXTREMES OUTSIDE PERIOD OF RECORD. --Approximate gage heights to gage datum of major floods, pointed out by local residents, are as follows: Sept. 13, 1928, 36.6 ft (11.16 m), Sept. 27, 1932, 36.3 ft (11.06 m), and Aug. 4, 1945, 34.3 ft (10.45 m).

		DISCHAR	R, CUBIC	FEET PER		WATER MEAN	YEAR OCTOBI	ER 1991 TO	sept em ber	1992		
DAY	OCT	NOA	DRC	JAN	FRB	MAR	APR	MAY	JUN	JUL	AUG	SRP
1	105	1540	96	e82	e127	95	246	246	2770	156	131	85
2	101	1170	96	e78	e123	91		1920	2340	153	123	78
3	98	457	98	e74	179	91		547	847	194	112	84
ă	91	297	97	e74	168	89		301	629	173	112	86
5	91	222	97	e8400	151	89		217	509	154	167	102
6	94	199	96	e8410	139	88		333	442	148	220	139
7	88	173	93	e940	252	85		275	400	143	175	118
8	203	190	93	e560	206	83		192	433	160	124	158
9	255	169	92	e44 0	184	148		160	e4 00	197	114	216
10	128	150	100	e360	155	126	2130	150	e620	157	108	155
11	114	135	97	e350	144	120	472	141	459	145	188	108
12	106	125	92	e360	162	107	283	136	33 7	142	136	93
13	97	122	90	e320	151	90	219	240	313	142	114	85
14	93	117	91	e290	135	85	184	170	291	165	105	76
15	90	117	90	e250	126	82	165	243	267	151	112	72
16	86	116	87	e370	123	81	221	210	248	149	119	69
17	83	115	87	e340	117	84		316	236	151	108	78
18	80	110	85	e240	114	112		803	223	136	93	90
19	100	106	82	e200	111	116		624	213	133	87	90
20	211	104	82	e180	111	100		1300	206	131	93	656
21	172	107	277	e170	108	89	866	1060	200	129	296	176
22	108	109	e174	e154	108	84		482	204	122	196	119
23	124	108	e130	e155	105	87		2520	195	119	130	106
24	113	118	e100	e154	102	84		6280	192	133	106	181
25	101	121	e90	e154	101	77		1660	186	138	111	168
2 3	101	121	670	6134	101	,,	100	1660	100	130	111	100
26	133	108	e86	e140	103	123		3250	179	116	127	167
27	165	104	e 86	e137	101	111		2050	175	108	126	115
28	110	103	e 90	e130	9 9	509		979	173	107	112	103
29	396	104	e92	e130	95	282	139	705	16 6	106	101	91
30	1320	99	e92	e130		509	235	540	162	98	91	98
31	1120		e88	e128		168		1440		95	88	
TOTAL	6176	6815	3146	23900	3900	4085	12677	29490	14015	4351	4025	3962
MEAN	199	227	101	771	134	132		951	467	140	130	132
MAX	1320	1540	277	8410	252	509		6280	2770	197	296	656
MIN	80	99	82	74	95	77		136	162	95	87	69
AC-FT	12250	13520	6240	47410	7740	8100		58490	27800	8630	7980	7860
CFSM	1.01	1.15	.52	3.91	.68	. 67		4.83	2.37	.71	.66	. 67
IN.	1.17	1.29	.59	4.51	.74	.77		5.57	2.65	. 82	.76	.75
e Es	timated			•								
STATIST	CICS OF M	ONTHLY MEAL	N DATA FO	R WATER YI	BARS 1970	- 199	2, BY WATE	R YBAR (WY)	ı			
MBAN	818	589	388	260	205	198	364	686	251	165	229	438
MAX	2958	1803	388 1498	771	444	198 521		3178	747	105 577	1644	1510
(WY)	1971	1971	1971	19 92	1988	1972		1985	1987	1979	1979	1979
MIN	161	123	101	105	87.6	68.4		93.7	78.7	75.2	67.9	127
(WY)	1987	1974	1992	1984	1984	1984		1989	1977	1984	1984	1983
	STATIST			991 CALENI		1304		WATER YEAR	13//	WATER YE		
330W737	moma r			70004			446540					
ANNUAL				79921			116542			204		
ANNUAL				219			318			381		1001
	ANNUAL									756		1971 1974
	ANNUAL M			2020	T. 1 C.		0.44.5	7		17/2	Was- 1	
	DAILY M			3020	Jul 16		8410	Jan 6		55900	May 1	18 1985
	DAILY ME			80	Oct 18		69	Sep 16		34		12 1984 7 1984
		Y MINIMUM		86	Dec 14		80	Sep 13		38	May	
		RAK FLOW					13600	May 24		97200	Oct	7 1985 7 1985
		EAK STAGE					28.			33.79	Oct	
	NANEOUS L			150500			43	Jan 16		33 276000	may .	L2 1984
	RUNOFF (158500			231200	60		1.93		
	RUNOFF (1.11			1.					
ANNUAL	RUNOFF (TMCHR2)		15.09			22.	ΛŢ		26.28		

50038100 RIO GRANDE DE MANATI AT HIGHWAY 2 NEAR MANATI, PR--Continued (National stream-quality accounting network station)

WATER-QUALITY RECORDS

PERIOD OF RECORD. -- Water years 1969 to current year.

WATER-QUALITY DATA, WATER YEAR OCTOBER 1991 TO SEPTEMBER 1992

			_	·				_			
DATE	TIME	DIS- CHARGE, INST. CUBIC FEET PER SECOND	SPE- CIFIC CON- DUCT- ANCE (US/CM)	PH WATER WHOLE FIELD (STAND- ARD UNITS)	TEMPER- ATURE WATER (DEG C)	TUR- BID- ITY (NTU)	OXYGEN, DIS- SOLVED (MG/L)	COLI- FORM, FECAL, 0.45 UM-MF (COLS./ 100 ML)	STREP- TOCOCCI FECAL, (COLS. PER 100 ML)	HARD- NESS TOTAL (MG/L AS CACO3)	CALCIUM DIS- SOLVED (MG/L AS CA)
OCT 1991											
04 DEC	0950	108	309	7.6	27.5	15	7.0	21000	K1500	130	40
31 FEB 1992	0920	90	328	7.7	23.0		3.8	4700	K11000		
25 APR	1025	100	325	7.5	25.0	6.3	8.0	3500	4700	140	44
22 JUN	1000	370	280	6.7	25.0	55	6.3	4 60 0	3600	100	27
23	1005	186	286	7.2	28.0	10	5.2	K18000	2100	120	35
10	0935	108	3 02	7.2	27.0	7.6	5.4	27000	1700	130	38
DATE	MAGNE- SIUM, DIS- SOLVED (MG/L AS MG)	SODIUM, DIS- SOLVED (MG/L AS NA)	SODIUM AD- SORP- TION RATIO	POTAS- SIUM, DIS- SOLVED (MG/L AS K)	ALKA- LINITY WAT WH TOT FET FIELD MG/L AS CACO3	SULFATE DIS- SOLVED (MG/L AS SO4)	CHLO- RIDE, DIS- SOLVED (MG/L AS CL)	FLUO- RIDE, DIS- SOLVED (MG/L AS F)	SILICA, DIS- SOLVED (MG/L AS SIO2)	SOLIDS, RESIDUR AT 180 DRG. C DIS- SOLVED (MG/L)	SOLIDS, SUM OF CONSTI- TUENTS, DIS- SOLVED (MG/L)
OCT 1991 04	7.6	11	0.4	1.8	130	9.3	12	0.10	20	187	183
DEC						_					
31 FEB 1992	8.2	11	0.4	1.7	140	8.2	13	0.10	20	178	190
25 APR	8.4	12	0.4	1.9	140	14	17	<0.10	16	189	200
22 JUN	8.6	8.5	0.4	2.1	130	15	8.7	<0.10	28	166	142
23	7.8	11	0.4	2.0	110	7.4	14	0.10	20	170	165
10	8.0	11	0.4	2.5	120	6.8	15	0.10	20	174	180
DATE	SOLIDS, DIS- SOLVED (TONS PER DAY)	NITRO- GEN, NO2+NO3 DIS- SOLVED (MG/L AS N)	NITRO- GEN, AMMONIA DIS- SOLVED (MG/L AS N)	NITRO- GEN, AMMONIA DIS- SOLVED (MG/L AS NH4)	NITRO- GEN, AM- MONIA + ORGANIC TOTAL (MG/L AS N)	PHOS- PHORUS TOTAL (MG/L AS P)	PHOS- PHORUS DIS- SOLVED (MG/L AS P)	PHOS- PHORUS ORTHO, DIS- SOLVED (MG/L AS P)	PHOS- PHATE, ORTHO, DIS- SOLVED (MG/L AS PO4)	ALUM- INUM, DIS- SOLVED (UG/L AS AL)	BARIUM, DIS- SOLVED (UG/L AS BA)
OCT 1991											
04 DEC	54.5	0.640	0.030	0.04	0.60	0.200	0.130	0.120	0.37	20	40
31 FRB 1992	46.2	0.580	0.090	0.12	0.50	0.140	0.140	0.090	0.28		
25 APR	51.0	0.500	0.030	0.04	0.40	0.100	0.060	0.060	0.18	<10	43
22 Jun	166	0.970	0.040	0.05	<0.20	0.040	0.040	0.040	0.12		
23 AUG	85.4	0.260	0.070	0.09	0.30	0.090	0.080	0.090	0.28	10	41
10	52.5	0.480	0.400	0.52	0.60	0.130	0.090	0.070	0.21	20	48

50038100 RIO GRANDE DE MANATI AT HIGHWAY 2 NEAR MANATI, PR--Continued (National stream-quality accounting network station)

WATER-QUALITY DATA, WATER YEAR OCTOBER 1991 TO SEPTEMBER 1992

DATE	COBALT, DIS- SOLVED (UG/L AS CO)	IRON, DIS- SOLVED (UG/L AS FE)	LITHIUM DIS- SOLVED (UG/L AS LI)	MANGA- NESE, DIS- SOLVED (UG/L AS MN)	MOLYB- DENUM, DIS- SOLVED (UG/L AS MO)	NICKEL, DIS- SOLVED (UG/L AS NI)	SELE- NIUM, DIS- SOLVED (UG/L AS SE)	SILVER, DIS- SOLVED (UG/L AS AG)	STRON- TIUM, DIS- SOLVED (UG/L AS SR)	VANA- DIUM, DIS- SOLVED (UG/L AS V)
OCT 1991	r									
04 DBC	<3	14	<4	25	<10	1	<1	<1.0	190	8
31 FEB 1992										
25 APR	<3	<3	4	27	<10	<1	<1	<1.0	210	<6
22 JUN										
23 AUG	<3	9	<4	27	<10	1	<1	<1.0	170	<6
10	<3	12	<4	25	<10	<1	<1	<1.0	190	9

50038100 RIO GRANDE DE MANATI AT HIGHWAY 2 NEAR MANATI, PR--Continued (National stream-quality accounting network station)

WATER-QUALITY DATA, WATER YEAR OCTOBER 1991 TO SEPTEMBER 1992

PARTICLE-SIZE DISTRIBUTION OF SUSPENDED SEDIMENT

D ATE	TIME	STREAM- FLOW, INSTAN- TANEOUS (CFS)	SEDI- MENT, SUS- PENDED (MG/L)	SEDI- MENT, DIS- CHARGE, SUS- PENDED (T/DAY)	SED. SUSP. SIEVE DIAM. PERCENT FINER THAN .062 MM
OCT 1991					
04 DRC 1992	0950	108	86	25	96
31 FRB	0920	90	65	16	93
25 APR	1025	100	68	18	86
22	1000	370	123	123	91
JUN 23	1005	186	35	18	89
AUG 10	0935	108	38	11	87

PESTICIDE ANALYSES

DATE	TIME	PCB, TOTAL (UG/L)	ALDRIN, TOTAL (UG/L)	CHLOR- DANE, TOTAL (UG/L)	DDD, TOTAL (UG/L)	DDR, TOTAL (UG/L)	DDT, TOTAL (UG/L)	DI- AZINON, TOTAL (UG/L)	DI- BLDRIN TOTAL (UG/L)	ENDO- SULFAN, TOTAL (UG/L)
JUN 1992 23	1005	<0.1	<0.010	<0.1	<0.010	<0.010	<0.010	<0.01	<0.010	<0.010

DATE	ENDRIN WATER UNFLTRD REC (UG/L)	ETHION, TOTAL (UG/L)	HEPTA- CHLOR, TOTAL (UG/L)	HEPTA- CHLOR EPOXIDE TOTAL (UG/L)	LINDANE TOTAL (UG/L)	MALA- THION, TOTAL (UG/L)	METH- OXY- CHLOR, TOTAL (UG/L)	METHYL PARA- THION, TOTAL (UG/L)	MIREX, TOTAL (UG/L)
JUN 1992 23	<0.010	<0.01	<0.010	<0.010	<0.010	<0.01	<0.01	<0.01	<0.01
DATE	PARA- THION, TOTAL (UG/L)	NAPH- THA- LENES, POLY- CHLOR. TOTAL (UG/L)	PER- THANE TOTAL (UG/L)	TOX- APHENE, TOTAL (UG/L)	TOTAL TRI- THION (UG/L)	2,4-D, TOTAL (UG/L)	2,4,5-T TOTAL (UG/L)	2, 4-DP TOTAL (UG/L)	SILVEX, TOTAL (UG/L)
JUN 1992 23	<0.01	<0.10	<0.1	<1	<0.01	<0.01	<0.01	<0.01	<0.01

LAGUNA TORTUGUERO BASIN

50038200 LAGUNA TORTUGUERO OUTLET NEAR VEGA BAJA, PR

WATER-QUALITY RECORDS

LOCATION.--Lat 18°28'29", long 66°26'50", at bridge on Highway 686, 4.2 mi (6.8 km) northeast of Manatí, and 4.4 mi (7.1 km) northwest of Vega Baja plaza.

DRAINAGE AREA. -- Indeterminate.

PERIOD OF RECORD. -- Water years 1964-66, 1969-71, 1974 to current year.

WATER-QUALITY DATA, WATER YEAR OCTOBER 1991 TO SEPTEMBER 1992

		MATER-OUA	LITY DATA	, WATER Y	EAR OCTOR	ER 1991 T	O SEPTEMB	BR 1992		
DATE	TIME	DIS- CHARGE, INST. CUBIC FEET PER SECOND	SPE- CIFIC CON- DUCT- ANCE (US/CM)	PH WATER WHOLE FIELD (STAND- ARD UNITS)	TEMPER- ATURE WATER (DEG C)	OXYGEN, DIS- SOLVED (MG/L)	OXYGEN DEMAND, CHEM- ICAL (HIGH LEVEL) (MG/L)	COLI- FORM, FECAL, 0.45 UM-MF (COLS./ 100 ML)	STREP- TOCOCCI FECAL, (COLS. PER 100 ML)	ALKA- LINITY WAT WH TOT FET FIELD MG/L AS CACO3
OCT 1991										
10	1600	17	1400	8.2	30.0	8.3	38	K30	23	98
DEC										
06 FEB 1992	0840	15	1480	7.7	25.5	6.9	34	K12	K4 0	120
21	1015	8.8	1370	7.9	26.0	6.9	32	K4	K16	120
APR						•				
13	1000	6.0	1520	7.7	27.5	6.6	40	K 56	310	110
JUN 09	0835	17	1400	7.9	29.5	6.4	36	10	50	100
AUG	0055	Δ,	1400	,.,	27.3	0.4	30	10	30	200
14	0745	2.8	1380	7.1	29.0	3.8	31	430	110	100
	SULFIDE TOTAL	RESIDUE TOTAL AT 105 DEG. C, SUS-	NITRO- GEN, NITRATE TOTAL	NITRO- GEN, NITRITE TOTAL	NITRO- GEN, NO2+NO3 TOTAL	NITRO- GEN, AMMONIA TOTAL	NITRO- GEN, ORGANIC TOTAL	NITRO- GEN, AM- MONIA + ORGANIC TOTAL	NITRO- GEN, TOTAL	NITRO- GEN, TOTAL
DATE	(MG/L	PENDED	(MG/L	(MG/L	(MG/L	(MG/L	(MG/L	(MG/L	(MG/L	(MG/L
	AS S)	(MG/L)	AS N)	AS N)	AS N)	AS N)	AS N)	AS N)	AS N)	AS NO3)
OCT 1991										
10	<0.5	2	0.390	0.010	0.400	0.230	0.67	0.90	1.3	5.8
DEC									4.0	
06 FRB 1992		10	0.540	0.020	0.560	0.360	0.74	1.1	1.7	7.3
21		6	0.460	0.020	0.480	0.240	0.56	0.80	1.3	5.7
APR										
13 Jun	<0.5	22	0.370	0.010	0.380	0.260	0.84	1.1	1.5	6.6
09		8	0.310	0.010	0.320	0.160	0.74	0.90	1.2	5.4
AUG										
14		6	0.220	0.010	0.230	0.230	0.87	1.1	1.3	5.9
		BOR			N NES				L	'HY -
	PHO							TDD		UE
	PHOR TOT						OV- CYAN BLE TOT.			IVE B-
DAT										NCE
	AS						ZN) AS		L) (MC	(/L)
ост 199										
10		010	150	10	<10	<10	<10 <0.	010	3 (.10
DEC	•••	010	130		~~~	~~~	120 10.		•	
06	<0.	010 -					-			· -
FEB 199 21		010 -							_	, <u>.</u>
APR	<0.	010 -	-	-	-	-	-	-	-	_
13	0.	010	90	30	70	10	<10 <0.	010	2 (.09
JUN	_									
AUG	<0.	U10 -		-	-		-			-
14	<0.	010 -								
K = non	-ideal co	unt								




Figure 17,--Río Cibuco basin.

50038320 RIO CIBUCO BELOW COROZAL, PR

LOCATION.--Lat 18°21'13", long 66°20'07", Hydrologic Unit 21010001, on right bank, 150 ft (46 m) downstream from Río Corozal, and 1.4 mi (2.3 km) northwest of Corozal.

DRAINAGE AREA .-- 15.1 mi2 (39.1 km2).

WATER-DISCHARGE RECORDS

PERIOD OF RECORD .-- May 1969 to current year.

GAGE. -- Water-stage recorder. Elevation of gage is 195 ft (59 m), from topographic map.

REMARKS.--Records fair. Gage-height and precipitation satellite telemetry at station.

	DIS	SCHARGE, (CUBIC FE	T PER SECO	ND, WATER		TOBER 1991	TO SEPTE	MBER 199	2		
DAY	OCT	NOV	DEC	JAN	PRB	MAR	APR	MAY	JUN	JUL	AUG	SEP
1	10	164	11	9.9	11	9.2	17	113	18	7.9	10	7.6
2	8.0	84	12	10	11	9.2	22	91	17	7.7	12	9.1
3	7.2	55	13	10	27	9.0	17	23	16	7.8	12	11
4	8.8	50	13	9.9	16	9.3	12	14	14	7.7	147	12
5	12	48	11	1260	13	9.8	12	12	13	8.2	61	19
6	8.8	36	10	278	12	8.9	12	56	13	7.5	46	20
7	7.4	24	10	58	11	9.2	18	18	13	7.5	20	14
8	26	21	11	30	11	15	14	13	14	16	15	13
9 10	19 11	16 14	14	25 38	9.3	9.6	12 14	11 11	15 17	16 12	13 11	12 11
11	9.0	13	10	28	10	8.8	12	11	15	12	9.9	10
12	8.2	14	10	27	15	8.5	11	10	14	11	9.4	10
13	7.2	14	9.8	33	11	7.7	11	10	13	15	9.6	9.4
14	7.3	12	12	27	11	7.1	11	9.5	13	24	21	10
15	6.4	12	9.4	23	12	8.0	11	9.9	13	15	13	10
16	4.9	13	11	39	11	7.3	9.6	20	12	13	14	11
17	4.6	12	9.9	36	11	9.3	10	11	12	13	9.6	13
18	4.6	11	9.3	25	10	13	9.6	15	11	12	9.3	12
19 20	10 8.9	11 12	9.2	22 19	11 11	12 8.3	9.4	106 38	11 9.1	18 14	8.8 15	77 59
21	6.2	14	18	16	11	7.7	9.1	83	9.5	12	11	19
22	7.4	16	12	17	12	8.0	8.8	36	9.7	11	9.1	13
23	11	14	11	16	10	8.2	8.9	92	9.4	11	8.6	16
24 25	7.0	36	11	15	11	7.2	9.2	120	8.8	15	7.9 8.2	11 16
45	79	16	10	13	12	7.3	8.9	40	8.5	11		
26	21	13	10	13	12	6.9	8.9	89	8.5	10	8.8	12
27	13	13	11	12	11	133	9.0	60	8.2	9.5	9.1	9.4
28	15	21	13	14	10	45	8.7	34	8.2	9.8	8.6	9.0
29	159	13	13	12	9.8	29	9.6	30	8.1	11	9.0	8.6
30 31	153 109	12	12 11	12 11		18 20	31	23 20	8.1	10 10	8.0 9.8	9.6
MOMAT	769.9	004			242.0		200 1	1220 4	360.1	365.6	564.7	473.7
TOTAL MEAN	24.8	804	361.6	2158.8	343.0	480.5	366.1	1229.4	12.0	11.8	18.2	15.8
MAX	159	26.8 164	11.7 21	69.6 1260	11.8 27	15.5 133	12.2 31	39.7 120	18	24	147	77
MIN	4.6	11	9.2	9.9	9.3	6.9	8.7	9.5	8.1	7.5	7.9	7.6
AC-FT	1530	1590	717	4280	680	953	726	2440	714	725	1120	940
CFSM	1.64	1.77	.77	4.61	.78	1.03	.81	2.63	.79	.78	1.21	1.05
IN.	1.90	1.98	.89	5.32	.85	1.18	.90	3.03	.89	.90	1.39	1.17
STATIS	TICS OF M	ONTHLY ME	AN DATA	FOR WATER 3	EARS 1969	- 1992,	BY WATER	YEAR (WY)				
									15.2	11.0	17.1	26.5
MEAN	43.6	46.6	37.1 169	25.7	22.0	23.7	33.6	46.2	44.4	11.9 34.6	50.8	73.2
(WY)	135 1991	155 1971	1971	69.6 1992	51.3 1988	65.1 1981	111 1973	157 1986	1987	1979	1979	1979
MIN	8.05	8.15	6.86	8.36	8.11	4.36	3.32	3.20	2.26	2.93	3.44	6.54
(WY)	1979	1974	1979	1978	1984	1984	1984	1977	1977	1977	1978	1978
omaan.	V OMANTON		200	1001 (1) (1)	man vara		on 1002 W	AMED VELD		WATER YE	106	- 1002
	Y STATIST	ics	FOR	1991 CALER	WAR IEAR		OR 1992 W	ATER IEAR		WAIRN ID	ARS 1902	1336
ANNUAL				7238.0			8277.4					
ANNUAL				19.8			22.6			29.2		4004
	T ANNUAL									56.5		1971
	ANNUAL M			200			4050			13.6	Marr	1984
	T DAILY ME			290 4.6			1260			2370		18 1985 24 1977
	SEVEN-DA			5.6			6.2			1.4		20 1977
	TANEOUS P			3.0	sep 3		11900			13600		7 1979
	TANBOUS P						19.3			19.80		7 1979
INSTAN	TANBOUS L	OW FLOW					3.8					
ANNUAL	RUNOFF (AC-FT)		14360			16420			21180		
	RUNOFF (1.31			1.5			1.94		
	RUNOFF (17.83	3		20.3	9		26.31		
	CENT EXCE			32			35			50		
	CENT EXCE			13			12			13		
90 PER	CENT EXCE	RDS		6.8			8.2			5.9		

50038320 RIO CIBUCO BELOW COROZAL, PR--Continued

WATER-QUALITY RECORDS

PERIOD OF RECORD. -- Water years 1969-76, 1979 to current year.

WATER-QUALITY DATA, WATER YEAR OCTOBER 1991 TO SEPTEMBER 1992

				.,			V DDI 1818	- L		
DATE	TIME	DIS- CHARGE, INST. CUBIC FEET PER SECOND	SPE- CIFIC CON- DUCT- ANCE (US/CM)	PH WATER WHOLE FIELD (STAND- ARD UNITS)	TEMPER- ATURE WATER (DRG C)	TUR- BID- ITY (NTU)	OXYGEN, DIS- SOLVED (MG/L)	OXYGEN DEMAND, CHEM- ICAL (HIGH LEVEL) (MG/L)	COLI- FORM, FECAL, 0.45 UM-MF (COLS./ 100 ML)	STREP- TOCOCCI FECAL, (COLS. PER 100 ML)
OCT 1991										
17	1015	4.6	426	7.9	25.5	3.0	7.6	14	410	280
DRC										
09	1345	15	367	8.0	24.0	9.6	7.9	19	K80000	30000
FRB 1992										
26	1025	10	360	7.7	25.0	1.1	8.6	18	6900	870
JUN 22	1100	10	200		A7 F				0400	#0.4.0
AUG	1100	10	366	7.8	27.5	1.8	7.5	<10	2400	K210
14	0835	11	365	7.4	25.0	1.5	6.2	<10	8700	740
24	0055		303	, . .	23.0	1.3	0.2	410	0,00	/40
DATE	HARD- NESS TOTAL (MG/L AS CACO3)	CALCIUM DIS- SOLVED (MG/L AS CA)	MAGNE- SIUM, DIS- SOLVED (MG/L AS MG)	SODIUM, DIS- SOLVED (MG/L AS NA)	SODIUM AD- SORP- TION RATIO	POTAS- SIUM, DIS- SOLVED (MG/L AS K)	ALKA- LINITY WAT WH TOT FET FIELD MG/L AS CACO3	SULFIDE TOTAL (MG/L AS S)	SULFATR DIS- SOLVED (MG/L AS SO4)	CHLO- RIDE, DIS- SOLVED (MG/L AS CL)
OCT 1991										
17	160	41	13	27	0.9	4.4	130	<0.5	17	30
DEC										
09.,.							110			
FRB 1992										
26 JUN							120			
22	140	36	12	18	0.7	3.2	120	<0.5	19	29
AUG	140	36	14	10	0.,	3.4	140	30.5	19	49
14	140	35	12	18	0.7	3.5	120		16	26
DATE	FLUO- RIDE, DIS- SOLVED (MG/L AS F)	SILICA, DIS- SOLVED (MG/L AS SIO2)	SOLIDS, SUM OF CONSTI- TUENTS, DIS- SOLVED (MG/L)	SOLIDS, DIS- SOLVED (TONS PER DAY)	RESIDUE TOTAL AT 105 DEG. C, SUS- PENDED (MG/L)	NITRO- GEN, NITRATE TOTAL (MG/L AS N)	NITRO- GEN, NITRITE TOTAL (MG/L AS N)	NITRO- GEN, NO2+NO3 TOTAL (MG/L AS N)	NITRO- GEN, AMMONIA TOTAL (MG/L AS N)	NITRO- GEN, ORGANIC TOTAL (MG/L AS N)
OCT 1991					_					
17 Dec	0.10	33	243	3.06	<1	3.71	0.090	3.80	0.150	0.45
09 FEB 1992					24	3.67	0.030	3.70	0.040	0.36
26					1	2.78	0.020	2.80	0.030	0.17
JUN 22	0.20	29	218	6.07	4	2.28	0.020	2.30	0.050	0.35
AUG 14	0.20	32	220	6.53	2	0.990	0.110	1.10	0.090	0.21

50038320 RIO CIBUCO BELOW COROZAL, PR--Continued

WATER-QUALITY DATA, WATER YEAR OCTOBER 1991 TO SEPTEMBER 1992

DATE	NITRO- GEN, AM- MONIA + ORGANIC TOTAL (MG/L AS N)	NITRO- GEN, TOTAL (MG/L AS N)	NITRO- GEN, TOTAL (MG/L AS NO3)	PHOS- PHORUS TOTAL (MG/L AS P)	ARSENIC TOTAL (UG/L AS AS)	BARIUM, TOTAL RECOV- ERABLE (UG/L AS BA)	BORON, TOTAL RECOV- ERABLE (UG/L AS B)	CADMIUM TOTAL RECOV- ERABLE (UG/L AS CD)	CHRO- MIUM, TOTAL RECOV- ERABLE (UG/L AS CR)	COPPER, TOTAL RECOV- ERABLE (UG/L AS CU)
OCT 1991										
17	0.60	4.4	19	1.00	<1	<100	40	<1	<1	<10
DEC 09	0.40	4.1	18	0.810						
FEB 1992										
26 JUN	0.20	3.0	13	0.540						
22	0.40	2.7	12	0.520	<1	<100	30	<1	<1	<10
AUG 14	0.30	1.4	6.2	0.370						
	IRON, TOTAL	LEAD, TOTAL	MANGA- NESE,	MERCURY		SILVER,	ZINC,			METHY- LENE BLUE
DATE	RECOV- ERABLE (UG/L AS FE)	RECOV- ERABLE (UG/L AS PB)	TOTAL RECOV- ERABLE (UG/L AS MN)	TOTAL RECOV- ERABLE (UG/L AS HG)	SELE- NIUM, TOTAL (UG/L AS SE)	TOTAL RECOV- ERABLE (UG/L AS AG)	TOTAL RECOV- ERABLE (UG/L AS ZN)	CYANIDE TOTAL (MG/L AS CN)	PHENOLS TOTAL (UG/L)	ACTIVE SUB- STANCE (MG/L)
OCT 1991	ERABLE (UG/L AS FE)	RECOV- ERABLE (UG/L AS PB)	RECOV- ERABLE (UG/L AS MN)	RECOV- ERABLE (UG/L AS HG)	NIUM, TOTAL (UG/L AS SE)	RECOV- ERABLE (UG/L AS AG)	RECOV- ERABLE (UG/L AS ZN)	TOTAL (MG/L AS CN)	TOTAL (UG/L)	ACTIVE SUB- STANCE (MG/L)
OCT 1991 17	ERABLE (UG/L	RECOV- ERABLE (UG/L	RECOV- ERABLE (UG/L	RECOV- ERABLE (UG/L	NIUM, TOTAL (UG/L	RECOV- ERABLE (UG/L	RECOV- ERABLE (UG/L	TOTAL (MG/L	TOTAL	active sub- stance
OCT 1991 17 DEC 09	ERABLE (UG/L AS FE)	RECOV- ERABLE (UG/L AS PB)	RECOV- ERABLE (UG/L AS MN)	RECOV- ERABLE (UG/L AS HG)	NIUM, TOTAL (UG/L AS SE)	RECOV- ERABLE (UG/L AS AG)	RECOV- ERABLE (UG/L AS ZN)	TOTAL (MG/L AS CN)	TOTAL (UG/L)	ACTIVE SUB- STANCE (MG/L)
OCT 1991 17 DEC 09 FRB 1992	ERABLE (UG/L AS FE) 80	RECOV- ERABLE (UG/L AS PB)	RECOV- ERABLE (UG/L AS MN)	RECOV- ERABLE (UG/L AS HG) <0.10	NIUM, TOTAL (UG/L AS SE)	RECOV- ERABLE (UG/L AS AG)	RECOV- ERABLE (UG/L AS ZN)	TOTAL (MG/L AS CN) <0.010	TOTAL (UG/L)	ACTIVE SUB- STANCE (MG/L) 0.07
OCT 1991 17 DEC 09 FEB 1992 26 JUN	ERABLE (UG/L AS FE) 80	RECOV- ERABLE (UG/L AS PB)	RECOV- ERABLE (UG/L AS MN)	RECOV- ERABLE (UG/L AS HG)	NIUM, TOTAL (UG/L AS SE)	RECOV- ERABLE (UG/L AS AG)	RECOV- ERABLE (UG/L AS ZN) <10	TOTAL (MG/L AS CN) <0.010	TOTAL (UG/L) 3	ACTIVE SUB- STANCE (MG/L) 0.07
OCT 1991 17 DEC 09 FRB 1992 26	ERABLE (UG/L AS FE) 80	RECOV- ERABLE (UG/L AS PB)	RECOV- ERABLE (UG/L AS MN)	RECOV- ERABLE (UG/L AS HG) <0.10	NIUM, TOTAL (UG/L AS SE)	RECOV- ERABLE (UG/L AS AG)	RECOV- ERABLE (UG/L AS ZN)	TOTAL (MG/L AS CN) <0.010	TOTAL (UG/L)	ACTIVE SUB- STANCE (MG/L) 0.07

50039500 RIO CIBUCO AT VEGA BAJA, PR

LOCATION.--Lat 18°26'53", long 66°22'29", Hydrologic Unit 21010002, on left bank, at bridge on Hwy 2, 0.6 mi (1.0 km) downstream from Río Indio, and 0.8 mi (1.3 km) east of Vega Baja.

DRAINAGE AREA. -- 99.1 mi² (256.7 km²), of which 25.4 mi² (65.8 km²), does not contribute directly to surface

WATER-DISCHARGE RECORDS

PERIOD OF RECORD. -- January 1973 to current year.

GAGE.--Water-stage recorder. Datum of gage is 7.79 ft (2.374 m) above mean sea level.

REMARKS.--Records fair except those for estimated daily discharges, which are poor. Gage-height and precipitation satellite telemetry at station.

EXTREMES OUTSIDE PERIOD OF RECORD.--Flood of Dec. 11, 1965 reached a stage of 26.2 ft (7.99 m), datum unknown, discharge about 28,000 ft³/s (793 m³/s).

				• - • -								
		DI SCHAF	GB, CUBIC	FERT PER		WATER YEA MRAN VAL	R OCTOBER JES	1991 TO	sep tem ber	1992		
DAY	OCT	VOV	DEC	JAN	FEB	MAR	APR	MAY	JUN	JUL	AUG	SEP
1	40	280	32	34	42	28	120	91	282	29	24	25
2	28	424	32	32	42	26	45	630	222	27	23	e25
3 4	23 20	174	37 52	31 30	43 127	28 29	166 49	115 52	155 103	29 28	26 187	e29 e31
5	26	129 136	42	381	58	26	34	34	74	27	312	e42
6	20				45		31	122	61	28	314	e4 5
7	32 20	99 66	38 36	2930 355	45 43	25 23	46	74	70	25	99	e35
8	22	58	43	201	42	23	53	37	64	35	70	e31
9	73	45	46	138	38	43	43	28	67	78	71	e 30
10	30	37	65	205	36	27	51	25	68	52	62	31
11	22	31	44	156	36	24	46	23	75	40	43	33
12 13	20	28 29	40	113 120	41 37	23	34 31	21 20	57 48	37 43	36 37	30 29
14	18 17	28	39 45	100	35	22 22	29	20	43	92	32	28
15	17	26	43	83	35	23	26	19	40	98	71	27
16	17	25	36	78	35	22	26	33	39	58	42	28
17	15	26	38	199	32	25	29	61	38	50	35	28
18	16	24	35	106	30	38	28	39	38	42	30	40 77
19 20	22 30	22 23	33 37	78 6 8	31 31	38 30	58 31	191 363	37 36	71 107	27 26	1210
21	22	26	140	64	31	25	29	250	35	41	60	186
22	18	74	58	60	34	24	25	307	36	32	31	79
23	28	32	46	58	32	23	25	240	35	30	27	64
24	26	132	41	54	29	24	23	642	33	44	25	77
25	43	53	38	54	31	22	23	252	31	48	29	66
26	134	34	36	58	30	22	23	382	29	29	28	100
27 28	33 43	31 29	36 42	52 48	31 30	128 296	23 23	e490 e250	28 31	27 31	28 25	47 38
29	365	51	51	49	29	106	28	e163	28	27	25	34
30	785	34	39	45		63	136	158	28	25	26	32
31	321		36	43		116		380		24	32	
TOTAL	2326	2206	1376	6023	1136	1394	1334	5512	1931	1354	1903	2577
MBAN	75.0	73.5	44.4	194	39.2	45.0	44.5	178	64.4	43.7	61.4	85.9
MAX MIN	785 15	424 22	140 32	2930 30	127 29	296 22	166 23	642 19	282 28	107 24	314 23	1210 25
AC-FT	4610	4380	2730	11950	2250	2760	2650	10930	3830	2690	3770	5110
CFSM	.76	.74	.45	1.96	.40	.45	.45	1.79	.65	. 44	. 62	. 87
IN.	. 87	. 83	.52	2.26	.43	. 52	.50	2.07	.72	.51	.71	. 97
e Ba	stimated											
STATIST	TICS OF M	ONTHLY ME	N DATA F	OR WATER Y	EARS 1973	- 1992,	BY WATER	YEAR (WY)				
MEAN	171	189	184	96.5	92.3	95.9	160	210	76.9	53.9	85.3	121
MAX	559	523	1316	209	190	339	671	655	245	162	461	450
(WY)	1986	1980	1982	1988	1988	1990	1987	1985	1987	1979	1979	1979
MIN (WY)	45.9 1974	40.0 1974	30.5 1979	36.3 19 84	32.6 1977	24.3 19 84	16.2 1984	24.7 1977	12.8 1977	15.5 1977	21.2 1978	27.3 1991
()	22.0	25.0	25.5			2,00	2,00					
SUMMARY	Y STATIST	ICS	FOR	1991 CALEN	DAR YEAR	FC	OR 1992 WA	TER YEAR		WATER YE	ARS 1973	- 1992
ANNUAL				29965			29072			100		
ANNUAL	MKAN PANNUAL I	MPAN		82.1			79.4			129 236		1982
	ANNUAL M									49.3		1974
Highest	r DAILY M	BAN		1030	Jul 16		2930	Jan 6		14600		13 1981
	DAILY ME			15	Oct 17		15	Oct 17		7.4		24 1977
	RANBOUS PI	Y MINIMUM		17	Oct 12		17 7710	Oct 12 Jan 6		8.5 34000		21 1977 12 1987
		BAK STAGE						Jan 6		19.10		12 1987
Instant	TANEOUS L	OW FLOW					14	Oct 17		6.1		24 1977
	RUNOFF (59440 .83	,		57660 .80			93220 1.30		
	RUNOFF (11.2			.80 10.91			17.64		
10 PERG	CENT BXCE	RDS		168			155			227		
	CENT BXCE			48			36			60		
90 PBR	CENT BXCE	RD2		22			23			25		

50039500 RIO CIBUCO AT VEGA BAJA, PR--Continued

WATER-QUALITY RECORDS

PERIOD OF RECORD. -- Water years 1972 to current year.

WATER QUALITY DATA, WATER YEAR OCTOBER 1991 TO SEPTEMBER 1992

DATE	TIME	DIS- CHARGE, INST. CUBIC FEET PER SECOND	SPE- CIFIC CON- DUCT- ANCE (US/CM)	PH WATER WHOLE FIELD (STAND- ARD UNITS)	TEMPER- ATURE WATER (DEG C)	TUR- BID- ITY (NTU)	OXYGEN, DIS- SOLVED (MG/L)	OXYGEN DEMAND, CHEM- ICAL (HIGH LEVEL) (MG/L)	COLI- FORM, FECAL, 0.45 UM-MF (COLS./ 100 ML)	STREP- TOCOCCI FECAL, (COLS. PER 100 ML)
OCT 1991										
01 DBC	1630	44	427	8.0	26.5	1.7	7.1	<10	2400	2700
06 FEB 1992	1145	37	445	7.9	25.0	3.4	6.6	11	390	330
21	1245	35	404	7.9	24.5	2.1	8.0	<10	290	K150
JUN 09	1100	73	441	7.9	26.5	6.6	6.6	14	400	380
AUG 14	0940	32	451	7.5	28.0	2.7	3.8	<10	28000	400
14	0940	32	421	7.5	28.0	2.7	3.8	<10	28000	400
DATE	HARD- NESS TOTAL (MG/L AS CACO3)	CALCIUM DIS- SOLVED (MG/L AS CA)	MAGNE- SIUM, DIS- SOLVED (MG/L AS MG)	SODIUM, DIS- SOLVED (MG/L AS NA)	SODIUM AD- SORP- TION RATIO	POTAS- SIUM, DIS- SOLVED (MG/L AS K)	ALKA- LINITY WAT WH TOT FET FIELD MG/L AS CACO3	SULFIDE TOTAL (MG/L AS S)	SULFATE DIS- SOLVED (MG/L AS SO4)	CHLO- RIDE, DIS- SOLVED (MG/L AS CL)
OCT 1991										
01	190	56	12	42	1	4.7	160	<0.5	11	32
06 FRB 1992							170			
21							160			
JUN 09 AUG	180	57	9.4	18	0.6	4.1	170	<0.5	16	26
14	190	58	10	18	0.6	4.0	180		17	27
DATE	FLUO- RIDE, DIS- SOLVED (MG/L AS F)	SILICA, DIS- SOLVED (MG/L AS SIO2)	SOLIDS, SUM OF CONSTI- TUENTS, DIS- SOLVED (MG/L)	SOLIDS, DIS- SOLVED (TONS PER DAY)	RESIDUE TOTAL AT 105 DEG. C, SUS- PENDED (MG/L)	NITRO- GEN, NITRATE TOTAL (MG/L AS N)	NITRO- GEN, NITRITE TOTAL (MG/L AS N)	NITRO- GEN, NO2+NO3 TOTAL (MG/L AS N)	NITRO- GEN, AMMONIA TOTAL (MG/L AS N)	NITRO- GEN, ORGANIC TOTAL (MG/L AS N)
OCT 1991										
01	0.20	19	273	32.5	4	1.48	0.020	1.50	0.040	0.16
06 FEB 1992					14	1.78	0.020	1.80	0.050	0.15
21					7	1.75	0.050	1.80	0.020	0.18
JUN 09 AUG	0.10	19	252	49.3	<1	1.27	0.030	1.30	0.030	0.17
14	0.10	20	260	22.5	7	1.36	0.040	1.40	0.030	
K = non-ide	al count									

RIO CIBUCO BASIN

50039500 RIO CIBUCO AT VEGA BAJA, PR--Continued

WATER-QUALITY DATA, WATER YEAR OCTOBER 1991 TO SEPTEMBER 1992

DATE	NITRO- GEN, AM- MONIA + ORGANIC TOTAL (MG/L AS N)	NITRO- GEN, TOTAL (MG/L AS N)	NITRO- GEN, TOTAL (MG/L AS NO3)	PHOS- PHORUS TOTAL (MG/L AS P)	ARSENIC TOTAL (UG/L AS AS)	BARIUM, TOTAL RECOV- ERABLE (UG/L AS BA)	BORON, TOTAL RECOV- ERABLE (UG/L AS B)	CADMIUM TOTAL RECOV- ERABLE (UG/L AS CD)	CHRO- MIUM, TOTAL RECOV- ERABLE (UG/L AS CR)	COPPER, TOTAL RECOV- ERABLE (UG/L AS CU)
OCT 1991										
01 DBC	0.20	1.7	7.5	0.380	<1	<100		1	1	<10
06 FBB 1992	0.20	2.0	8.9	0.390						
21 Jun	0.20	2.0	8.9	0.370						
09	0.20	1.5	6.6	0.230	<1	<100	30	<1	<1	<10
14	<0.20			0.260						
DATE	IRON, TOTAL RECOV- BRABLE (UG/L AS FE)	LRAD, TOTAL RECOV- ERABLE (UG/L AS PB)	MANGA- NESE, TOTAL RECOV- ERABLE (UG/L AS MN)	MERCURY TOTAL RECOV- ERABLE (UG/L AS HG)	SELE- NIUM, TOTAL (UG/L AS SE)	SILVER, TOTAL RECOV- ERABLE (UG/L AS AG)	ZINC, TOTAL RECOV- ERABLE (UG/L AS ZN)	CYANIDE TOTAL (MG/L AS CN)	PHENOLS TOTAL (UG/L)	METHY- LENE BLUE ACTIVE SUB- STANCE (MG/L)
OCT 1991	TOTAL RECOV- BRABLE (UG/L AS FE)	TOTAL RECOV- BRABLE (UG/L	NESE, TOTAL RECOV- BRABLE (UG/L	TOTAL RECOV- ERABLE (UG/L	NIUM, TOTAL (UG/L	TOTAL RECOV- ERABLE (UG/L	TOTAL RECOV- BRABLE (UG/L	TOTAL (MG/L	TOTAL	LENE BLUE ACTIVE SUB- STANCE
OCT 1991 01	TOTAL RECOV- BRABLE (UG/L	TOTAL RECOV- BRABLE (UG/L	NESE, TOTAL RECOV- BRABLE (UG/L	TOTAL RECOV- ERABLE (UG/L	NIUM, TOTAL (UG/L	TOTAL RECOV- ERABLE (UG/L	TOTAL RECOV- BRABLE (UG/L	TOTAL (MG/L	TOTAL	LENE BLUE ACTIVE SUB- STANCE
OCT 1991 01 DEC 06	TOTAL RECOV- BRABLE (UG/L AS FE)	TOTAL RECOV- BRABLE (UG/L AS PB)	NESE, TOTAL RECOV- ERABLE (UG/L AS MN)	TOTAL RECOV- ERABLE (UG/L AS HG)	NIUM, TOTAL (UG/L AS SE)	TOTAL RECOV- ERABLE (UG/L AS AG)	TOTAL RECOV- BRABLE (UG/L AS ZN)	TOTAL (MG/L AS CN)	TOTAL (UG/L)	LENE BLUE ACTIVE SUB- STANCE (MG/L)
OCT 1991 01 DBC 06 FBB 1992 21	TOTAL RECOV- BRABLE (UG/L AS FE)	TOTAL RECOV- BRABLE (UG/L AS PB)	NESE, TOTAL RECOV- ERABLE (UG/L AS MN)	TOTAL RECOV- ERABLE (UG/L AS HG)	NIUM, TOTAL (UG/L AS SE)	TOTAL RECOV- ERABLE (UG/L AS AG)	TOTAL RECOV- BRABLE (UG/L AS ZN)	TOTAL (MG/L AS CN)	TOTAL (UG/L)	LENE BLUE ACTIVE SUB- STANCE (MG/L)
OCT 1991 01 DEC 06 FEB 1992	TOTAL RECOV- BRABLE (UG/L AS FE)	TOTAL RECOV- BRABLE (UG/L AS PB)	NESE, TOTAL RECOV- ERABLE (UG/L AS MN)	TOTAL RECOV- ERABLE (UG/L AS HG)	NIUM, TOTAL (UG/L AS SE)	TOTAL RECOV- ERABLE (UG/L AS AG)	TOTAL RECOV- BRABLE (UG/L AS ZN)	TOTAL (MG/L AS CN)	TOTAL (UG/L)	LENE BLUE ACTIVE SUB- STANCE (MG/L)

THIS PAGE WAS LEFT BLANK INTENTIONALLY




Figure 18--Río de la Plata basin.

50039990 LAGO CARITE AT GATE TOWER

LOCATION.--Lat 18°03'46", long 66°05'58", Hydrologic Unit 21010005, on top of a concrete tower at diversion tunnel on Carite Reservoir, 0.7 mi (1.1 km) northwest from Escuela Carite Chino, 1.2 mi (1.9 km) northeast from Central Hidroeléctrica de Carite Num. 1 and 1.8 mi (2.9 km) northeast from Escuela Segunda Unidad.

DRAINAGE AREA. -- 8.20 mi 2 (21.24 km2).

ELEVATION RECORDS

PERIOD OF RECORD .-- May 1989 to current year.

GAGE. -- Water stage recorder. Datum of gage is mean sea level.

REMARKS.--Lago Carite Dam was completed in 1913. The operation of the reservoir is controlled by the utilisation of water to meet the demands for domestic, industrial and agricultural purposes in the Guayama Area. The dam is an earthfill with crest elevation of 1,806 ft (550 m) above mean sea level, with a structural height of 104 ft (32 m) and a length of 500 ft (152 m). The dam has a capacity of approximately 11,310 acre-feet (13.9 hm²). The Dam is operated by the Puerto Rico Electric and Power Authority. Gage-height and precipitation satellite telemetry at station.

EXTREMES OBSERVED FOR PERIOD OF RECORD. -- Maximum elevation 1,787.61 ft (544.86 m), Jan. 5, 1992; minimum elevation, 1,761.48 ft (536.90 m), June 13, 14, 1990.

EXTREMES FOR CURRENT YEAR. -- Maximum elevation 1,787.61 ft (544.86 m), Jan. 5; minimum elevation, 1,776.26 ft (541.40 m), Oct. 1.

Capacity Table

(based on Data from Puerto Rico Electric Power Authority)

Elevation, in feet	Contents, in acre-feet	Elevation, in feet	Contents, in acre-feet
1,746	0	1,775	6, 194
1,760	2,471	1,780	7,704
1,769	4,561	1,790	11,048

ELEVATION (FRET NGVD), WATER YEAR OCTOBER 1991 TO SEPTEMBER 1992 DAILY OBSERVATION AT 24:00 VALUES

2 1776.88 1776.86 1780.93 1780.96 1781.61 1781.38 1780.74 1779.15 1780.55 1781.53 1781.33 1779.75 1776.75 1776.82 1780.94 1781.89 1781.55 1781.35 1780.64 1779.03 1780.40 1781.52 1781.33 1779.6 1776.80 1776.81 1781.03 1780.90 1781.57 1781.31 1780.50 1788.0 1780.42 1781.52 1781.33 1779.6 1776.84 1776.87 1781.05 1786.50 1781.57 1781.31 1780.50 1788.77 1780.02 1781.53 1782.68 1779.4 1776.88 1777.73 1781.07 1782.49 1781.75 1781.31 1780.50 1788.69 1780.42 1781.53 1782.68 1779.4 1776.88 1777.73 1781.06 1781.89 1781.30 1780.47 1778.69 1780.29 1781.55 1781.71 1779.2 1776.88 1777.73 1781.08 1781.84 1781.77 1781.26 1780.36 1778.68 1780.10 1781.50 1781.71 1779.2 1776.90 1778.84 1781.08 1781.84 1781.77 1781.26 1780.13 1778.50 1780.02 1781.55 1781.61 1779.2 1776.95 1779.32 1781.08 1781.86 1781.74 1781.24 1780.01 1778.50 1780.02 1781.55 1781.61 1779.0 1776.95 1779.32 1781.06 1781.86 1781.72 1781.20 1779.85 1783.35 1780.78 1781.52 1781.52 1778.9 1776.99 1779.32 1781.06 1781.86 1781.72 1781.20 1779.85 1783.35 1780.78 1781.52 1781.52 1778.6 13 1777.01 1779.27 1781.02 1781.82 1781.61 1781.14 1779.90 1778.04 1781.54 1781.55 1781.49 1778.6 13 1777.01 1779.27 1781.02 1781.82 1781.60 1781.10 1779.77 1778.04 1781.54 1781.46 1778.3 1779.40 1779.29 1781.04 1781.80 1781.55 1781.50 1781.47 1778.3 1779.04 1779.29 1781.04 1781.80 1781.55 1781.50 1781.70 1779.80 1779.29 1781.04 1781.80 1781.55 1781.50 1781.47 1778.3 1781.64 1778.3 1777.04 1779.29 1781.04 1781.80 1781.55 1781.50 1781.47 1778.3 1777.06 1779.29 1781.04 1781.79 1781.55 1781.07 1779.69 1778.04 1781.64 1781.40 1778.3 1791.40 1779.29 1781.04 1781.79 1781.55 1781.07 1779.69 1778.04 1781.64 1781.40 1778.3 1791.40 1779.29 1781.04 1781.50 1781.50 1781.50 1781.40 1778.3 1791.50 1779.20 1781.00 1781.79 1781.50 1781.50 1781.47 1781.60 1781.47 1781.60 1781.47 1781.60 1781.47 1781.60 1781.47 1781.60 1781.40 1779.20 1781.00 1779.20 1781.00 1781.79 1781.50 1781.40 1779.79 1779.80 1779.20 1781.00 1781.75 1781.40 1781.40 1779.40 1779.90 1779.20 1781.00 1781.70 1781.40 1781.40 1781.40 1781.40 17	DAY	OCT	NOV	DEC	JAN	FEB	MAR	APR	MAY	JUN	JUL	AUG	SEP
1776.75 1776.82 1780.94 1780.94 1781.59 1781.35 1781.35 1780.64 1791.03 1780.40 1781.52 1781.30 1779.55 1776.80 1776.81 1781.03 1780.90 1781.57 1781.33 1780.57 1778.77 1780.29 1781.53 1782.68 1777.56 1776.80 1776.77 1781.05 1786.50 1781.57 1781.31 1780.50 1778.77 1780.29 1781.53 1782.68 1779.40 1776.88 1777.73 1781.06 1781.84 1781.07 1781.84 1781.08 1781.84 1781.77 1781.36 1778.68 1780.20 1781.55 1781.61 1779.13 1776.90 1778.84 1781.08 1781.84 1781.77 1781.66 1780.13 1778.65 1780.01 1781.55 1781.61 1779.10 1776.94 1779.20 1781.08 1781.86 1781.77 1781.26 1780.13 1778.69 1780.00 1781.55 1781.61 1779.10 1776.95 1779.32 1781.07 1781.87 1781.72 1781.20 1778.49 1780.40 1781.54 1781.55 1778.97 1776.99 1779.32 1781.07 1781.87 1781.72 1781.20 1779.85 1778.89 1781.52 1781.52 1781.52 1781.52 1778.99 1776.99 1779.32 1781.09 1781.87 1781.72 1781.20 1779.79 1778.13 1781.84 1781.55 1781.85 1778.85 1776.99 1779.27 1781.07 1781.07 1781.60 1781.57 1781.60 1781.57 1781.60 1781.57 1781.60 1781.55 1781	1	1776.37	1776.89	1780.79	1780.98	1781.63	1781.38	1780.78	1779.20	1780.68	1781.53	1781.27	1779.87
4 1776.80 1776.81 1781.03 1780.90 1781.57 1781.33 1780.57 1781.05 1780.42 1781.52 1781.33 1779.55 1776.84 1776.77 1781.05 1786.50 1781.57 1781.31 1780.50 1778.77 1780.29 1781.53 1782.68 1779.46 1776.87 1776.84 1781.07 1782.49 1781.75 1781.30 1780.47 1778.69 1780.20 1781.53 1782.68 1777.9 1776.88 1777.73 1781.06 1781.89 1781.31 1780.36 1778.68 1780.10 1781.50 1781.71 1779.2 1776.94 1779.20 1781.08 1781.84 1781.77 1781.26 1780.13 1778.00 1780.02 1781.55 1781.61 1779.10 1776.94 1779.20 1781.08 1781.87 1781.72 1781.20 1779.85 1778.35 1780.78 1781.52 1781.55 1779.00 1776.95 1779.32 1781.07 1781.87 1781.72 1781.20 1779.85 1778.35 1780.78 1781.52 1781.52 1778.9 1776.98 1779.32 1781.08 1781.84 1781.64 1781.17 1779.72 1781.06 1781.84 1781.55 1779.06 1779.79 1779.32 1781.07 1781.84 1781.64 1781.14 1779.90 1778.13 1781.84 1781.55 1781.49 1778.66 1777.02 1779.27 1781.07 1781.82 1781.60 1781.10 1779.77 1778.04 1781.97 1781.47 1781.46 1778.35 1777.04 1779.27 1781.02 1781.82 1781.60 1781.10 1779.77 1778.04 1781.97 1781.47 1781.46 1778.35 1777.04 1779.22 1781.04 1781.80 1781.59 1781.07 1779.69 1778.17 1781.47 1781.40 1778.37 1777.04 1779.23 1781.04 1781.80 1781.59 1781.07 1779.69 1778.17 1781.65 1781.49 1778.40 1777.08 1779.22 1781.04 1781.87 1781.59 1781.07 1779.69 1778.17 1781.65 1781.49 1778.34 1781.50 1781.47 1778.34 1781.50 1781.47 1778.34 1781.50 1781.47 1778.34 1781.50 1781.47 1778.34 1781.50 1781.47 1778.34 1781.50 1781.47 1778.34 1781.50 1781.47 1778.34 1777.08 1779.20 1781.00 1781.75 1781.00 1781.50 1781.60 1781.60 1781.60 1781.60 1781.60 1781.60 1781.70 1779.90 1779.21 1781.00 1781.75 1781.00 1781.50 1781.60	2	1776.68	1776.86	1780.83	1780.96	1781.61	1781.38	1780.74	1779.15	1780.55	1781.53	1781.33	1779.75
5 1776.84 1776.77 1781.05 1786.50 1781.57 1781.31 1780.50 1777.77 1780.29 1781.53 1782.68 1779.46 6 1776.87 1776.84 1781.07 1782.49 1781.75 1781.30 1780.47 1778.69 1780.20 1781.52 1781.89 1779.37 1776.88 1777.37 1781.06 1781.33 1781.78 1781.31 1780.36 1778.69 1780.10 1781.50 1781.71 1779.28 1781.89 1779.30 1776.90 1778.84 1781.08 1781.84 1781.77 1781.26 1780.13 1778.69 1780.10 1781.55 1781.61 1779.19 1776.94 1779.20 1781.08 1781.86 1781.74 1781.24 1780.13 1778.49 1780.40 1781.55 1781.61 1779.10 1776.95 1779.32 1781.07 1781.87 1781.72 1781.20 1779.85 1778.35 1780.78 1781.52 1781.55 1779.00 1776.95 1779.32 1781.06 1781.84 1781.66 1781.14 1779.90 1778.35 1780.78 1781.55 1781.49 1778.60 13 1777.01 1779.27 1781.07 1781.82 1781.61 1781.14 1779.90 1778.13 1781.84 1781.55 1781.49 1778.66 13 1777.02 1779.27 1781.07 1781.82 1781.65 1781.60 1781.10 1779.87 1778.04 1781.27 1781.07 1781.82 1781.60 1781.10 1779.87 1778.04 1781.25 1781.40 1781.80 1781.80 1781.80 1781.50 1781.40 1778.51 1777.08 1779.28 1781.04 1781.80 1781.59 1781.07 1779.69 1778.17 1781.67 1781.47 1781.47 1781.47 1781.18 1777.08 1779.26 1781.04 1781.79 1781.50 1781.04 1781.79 1781.05 1781.04 1781.17 1781.17 1781.05 1781.14 1777.08 1779.20 1781.00 1781.75 1781.40 1781.50 1781.40 1778.11 1777.08 1779.20 1781.00 1781.75 1781.40 1781.50 1781.40 1778.11 1777.08 1779.20 1781.00 1781.75 1781.40 1781.40 1778.11 1777.08 1779.20 1781.00 1781.75 1781.40 1781.40 1779.50 1779.60 1779.80 1779.20 1781.00 1781.75 1781.40 1781.40 1779.50 1779.60 1779.90 1779.90 1779.90 1779.80 1779.90 1779.90 1779.90 1779.90 1779.90 1779.90 1779.90 1781.10 1781.70 1781.40 1779.10 1779.90 1779.90 1779.90 1781.00 1781.70 1781.40 1781.40 1779.10 1779.90 1781.00 1781.70 1781.50 1781.40 1779.50 1781.60 1781.40 1779.10 1779.90 1781.00 1781.70 1781.50 1781.40 1779.50 1781.60 1781.70 1781.50 1781.40 1781.40 1779.40 1779.90 1781.60 1781.40 1781.40 1781.40 1779.50 1781.60 1781.70 1779.80 1779.90 1781.00 1781.70 1781.40 1781.70 1781.40 1781.40 1781.40 1781.40 1779.50 1781.40 1781.40 1781.40 1781.40 1781	3	1776.75	1776.82	1780.94	1780.94	1781.59	1781.35	1780.64	1779.03	1780.40	1781.52	1781.30	1779.65
6 1776.87 1776.84 1781.07 1782.49 1781.75 1781.30 1780.47 1778.69 1780.20 1781.52 1781.89 1779.37 1776.88 1777.73 1781.06 1781.93 1781.78 1781.31 1780.36 1778.68 1780.10 1781.50 1781.71 1779.22 8 1776.94 1779.20 1781.08 1781.84 1781.77 1781.26 1780.13 1778.50 1780.02 1781.55 1781.61 1779.10 1776.94 1779.20 1781.08 1781.87 1781.72 1781.26 1780.13 1778.95 1780.04 1781.54 1781.55 1779.00 1776.95 1779.32 1781.07 1781.87 1781.72 1781.20 1779.85 1778.35 1780.04 1781.52 1781.55 1779.00 1776.99 1779.32 1781.06 1781.87 1781.72 1781.20 1779.85 1778.35 1780.78 1781.55 1781.61 1779.01 1776.99 1779.32 1781.06 1781.86 1781.64 1781.14 1779.90 1778.13 1781.84 1781.55 1781.49 1778.60 13 1777.01 1779.27 1781.02 1781.82 1781.61 1781.10 1779.77 1778.04 1781.87 1781.49 1778.65 1777.04 1779.27 1781.02 1781.82 1781.60 1781.10 1779.77 1778.04 1781.82 1781.40 1781.85 1781.50 1781.47 1778.15 1777.04 1779.29 1781.04 1781.80 1781.59 1781.07 1781.55 1781.49 1778.15 1777.04 1779.29 1781.04 1781.80 1781.59 1781.07 1781.50 1781.47 1781.14 1781.50 1781.47 1778.15 1777.08 1779.28 1781.04 1781.79 1781.54 1781.04 1779.69 1778.25 1781.69 1781.40 1778.14 1781.70 1777.08 1779.29 1781.00 1781.79 1781.55 1781.09 1779.69 1778.10 1781.47 1781.40 1778.14 1781.70 1779.00 1779.29 1781.00 1781.79 1781.50 1781.07 1781.60 1781.40 1778.14 1781.70 1779.00 1779.29 1781.00 1781.79 1781.50 1781.07 1781.60 1781.40 1778.14 1781.70 1781.70 1781.70 1789.20 1781.00 1781.70 1781.70 1781.00 1781.70	4	1776.80	1776.81	1781.03	1780.90	1781.57	1781.33	1780.57	1778.90	1780.42	1781.52	1781.33	1779.56
7 1776.88 1777.73 1781.06 1781.93 1781.70 1781.31 1780.36 1778.68 1780.10 1781.50 1781.71 1779.28 1776.89 1777.84 1781.08 1781.84 1781.77 1781.26 1780.31 1778.50 1780.02 1781.55 1781.61 1779.10 1776.94 1779.20 1781.08 1781.84 1781.72 1781.20 1779.85 1778.49 1780.40 1781.54 1781.52 1778.09 1776.95 1779.32 1781.07 1781.87 1781.87 1781.20 1779.85 1778.35 1780.78 1781.52 1781.52 1778.90 1776.99 1779.32 1781.06 1781.84 1781.64 1781.14 1779.95 1778.26 1781.66 1781.55 1781.55 1778.90 1776.99 1779.32 1781.08 1781.84 1781.64 1781.14 1779.90 1778.13 1781.84 1781.55 1781.49 1778.61 1777.01 1779.27 1781.02 1781.82 1781.60 1781.10 1779.77 1778.04 1781.87 1781.49 1778.51 1777.04 1779.29 1781.02 1781.82 1781.60 1781.50 1781.10 1779.87 1778.25 1781.82 1781.46 1781.40 1778.51 1777.04 1779.29 1781.04 1781.80 1781.59 1781.07 1779.69 1778.17 1781.74 1781.50 1781.47 1778.11 1777.08 1779.28 1781.04 1781.80 1781.59 1781.07 1779.69 1778.17 1781.64 1781.40 1778.11 1777.08 1779.28 1781.04 1781.79 1781.54 1781.08 1779.28 1781.46 1781.40 1778.11 1777.08 1779.20 1781.04 1781.79 1781.55 1781.49 1778.11 1777.08 1779.20 1781.04 1781.79 1781.50 1781.40 1779.97 1781.62 1781.49 1781.40 1778.11 1777.08 1779.20 1781.00 1781.75 1781.49 1779.69 1779.80 1781.69 1781.49 1781.40 1778.11 1777.08 1779.20 1781.01 1781.77 1781.50 1781.40 1777.97 1781.65 1781.49 1781.40 1778.11 1777.08 1779.20 1781.00 1781.75 1781.49 1781.60 1779.60 1777.08 1779.20 1781.10 1781.74 1781.47 1780.98 1779.54 1777.08 1779.20 1781.10 1781.77 1781.45 1780.98 1779.54 1777.47 1781.63 1781.49 1781.36 1781.00 1781.75 1781.49 1781.40 1778.10 1779.99 1781.01 1781.70 1781.45 1780.96 1779.50 1779.99 1781.65 1781.49 1781.10 1781.70 1781.45 1780.96 1779.50 1779.99 1781.65 1781.49 1781.11 1781.40 1780.96 1779.50 1780.97 1781.45 1780.96 1781.47 1781.45 1780.96 1779.50 1780.97 1781.45 1781.49 1781.40 1780.97 1781.45 1780.96 1781.47 1781.45 1780.96 1781.47 1781.45 1780.96 1781.47 1781.46 1780.97 1781.45 1780.97 1780.98 1780.99 1781.55 1781.49 1781.50 1780.99 1781.55 1781.49 1781.50 1780.99 1781	5	1776.84	1776.77	1781.05	1786.50	1781.57	1781.31	1780.50	1778.77	1780.29	1781.53	1782.68	1779.40
8 1776.90 1778.84 1781.08 1781.84 1781.77 1781.26 1780.13 1778.50 1780.02 1781.55 1781.61 1779.19 1776.94 1779.20 1781.08 1781.86 1781.74 1781.24 1780.01 1778.8.9 1780.40 1781.55 1781.55 1778.04 1779.32 1781.07 1781.87 178		1776.87	1776.84	1781.07	1782.49	1781.75	1781.30	1780.47	1778.69	1780.20	1781.52	1781.89	1779.36
9 1776.94 1779.20 1781.08 1781.86 1781.74 1781.24 1780.01 1778.49 1780.40 1781.54 1781.55 1779.00 1776.95 1779.32 1781.07 1781.87 1781.72 1781.20 1779.85 1778.35 1780.78 1781.52 1781.52 1778.91 1776.98 1779.32 1781.06 1781.86 1781.84 1781.54 1781.55 1778.89 1778.35 1780.78 1781.52 1781.52 1778.90 1776.98 1779.32 1781.06 1781.86 1781.84 1781.55 1778.80 1781.84 1781.55 1781.89 1778.80 1779.01 1779.27 1781.07 1781.82 1781.60 1781.10 1779.77 1778.04 1781.97 1781.47 1781.46 1781.46 1781.51 1777.04 1779.29 1781.02 1781.02 1781.82 1781.60 1781.10 1779.77 1778.04 1781.97 1781.47 1781.40 1778.31 1777.04 1779.29 1781.04 1781.80 1781.59 1781.17 1779.69 1778.17 1781.47 1781.40 1781.40 1778.31 1781.47 1781.40 1779.39 1778.01 1799.29 1781.04 1781.50 1781.47 1781.40 1778.31 1781.47 1781.40 1779.39 1778.04 1781.50 1781.47 1781.40 1778.31 1781.47 1781.40 1779.39 1778.01 1781.70 1799.29 1781.04 1781.50 1781.47 1781.40 1778.31 1781.47 1781.40 1781.40 1778.31 1777.08 1779.26 1781.04 1781.79 1781.54 1781.08 1779.48 1778.08 1781.69 1781.52 1781.44 1778.31 1777.08 1779.20 1781.00 1781.75 1781.40 1781.50 1781.60 1779.48 1779.08 1779.20 1781.00 1781.75 1781.40 1781.50 1781.60 1779.40 1777.09 1781.65 1781.40 1781.47 1781.49 1781.40 1778.31 1777.08 1779.20 1781.00 1781.75 1781.40 1781.60 1779.54 1777.47 1781.63 1781.49 1781.40 1778.31 1781.60 1781.40 1781.47 1780.98 1779.54 1777.47 1781.63 1781.49 1781.30 1781.50 1781.40 1781.47 1780.98 1779.55 1781.40 1781.47 1780.98 1779.56 1781.49 1781.31 1781.31 1781.31 1781.31 1781.31 1781.31 1781.31 1781.31 1781.31 1781.31 1781.31 1781.31 1781.31 1781.31 1781.31 1781.31 1781.31 1781.31 1781.32 1781.40 1781.40 1781.43 1780.82 1779.50 1781.49 1781.45 1780.60 1780.90 1781.53 1781.45 1780.60 1780.90 1781.53 1781.45 1780.95 1781.45 1780.95 1781.45 1780.95 1781.45 1780.95 1781.45 1780.95 1781.45 1780.95 1781.45 1780.95 1781.45 1780.95 1781.45 1780.95 1781.45 1780.95 1781.45 1780.95 1781.45 1780.95 1781.45 1780.95 1781.45 1780.95 1781.45 1780.95 1781.45 1780.95 1781.45 1780.95 1781.45 1780.95 1781.45 1780		1776.88	1777.73	1781.06	1781.93	1781.78	1781.31	1780.36	1778.68	1780.10	1781.50	1781.71	1779.21
10 1776.95 1779.32 1781.07 1781.87 1781.72 1781.20 1779.85 1778.35 1780.78 1781.52 1781.52 1778.95 11 1776.98 1779.32 1781.06 1781.86 1781.86 1781.17 1779.72 1778.26 1781.06 1781.58 1781.55 1778.86 12 1776.99 1779.32 1781.08 1781.84 1781.64 1781.14 1779.90 1778.13 1781.84 1781.55 1781.49 1778.66 13 1777.01 1779.27 1781.07 1781.82 1781.61 1781.10 1779.77 1778.04 1781.97 1781.47 1781.46 1778.56 14 1777.02 1779.27 1781.02 1781.82 1781.60 1781.10 1779.77 1778.04 1781.97 1781.47 1781.46 1778.57 15 1777.04 1779.29 1781.04 1781.80 1781.59 1781.07 1779.69 1778.17 1781.74 1781.50 1781.47 1778.31 16 1777.06 1779.28 1781.03 1781.80 1781.56 1781.04 1779.62 1778.20 1781.69 1781.47 1781.47 1778.31 17 1777.08 1779.20 1781.01 1781.77 1781.50 1781.06 1779.40 1777.79 1781.65 1781.49 1781.40 1778.14 18 1777.08 1779.20 1781.00 1781.77 1781.50 1781.06 1779.40 1777.79 1781.65 1781.49 1781.40 1778.14 19 1777.08 1779.20 1781.12 1781.74 1781.49 1781.02 1779.57 1777.63 1781.62 1781.49 1781.40 1778.14 20 1777.08 1779.20 1781.12 1781.74 1781.47 1780.98 1779.57 1777.63 1781.62 1781.48 1781.39 1778.44 21 1777.08 1779.20 1781.12 1781.74 1781.45 1780.98 1779.62 1777.77 1781.88 1781.49 1781.36 1781.05 21 1777.08 1779.29 1781.00 1781.73 1781.45 1780.92 1779.64 1777.77 1781.88 1781.49 1781.36 1781.30 22 1777.08 1779.28 1781.06 1781.73 1781.45 1780.92 1779.64 1777.77 1781.88 1781.49 1781.15 1781.34 1781.34 1780.92 1779.62 1779.99 1781.65 1781.49 1781.11 1781.11 1781.11 1781.11 1781.11 1781.11 1781.11 1781.12 1781.79 1781.40 1781.89 1779.99 1781.65 1781.49 1781.10 1781.79 1781.40 1781.89 1779.99 1781.65 1781.49 1781.07 1781.49 1781.50 1781.49	8	1776.90	1778.84	1781.08	1781.84	1781.77	1781.26	1780.13	1778.50	1780.02	1781.55	1781.61	1779.10
11 1776.98 1779.32 1781.06 1781.86 1781.68 1781.17 1779.72 1778.26 1781.06 1781.58 1781.55 1778.81 12 1776.99 1779.32 1781.08 1781.84 1781.64 1781.14 1779.90 1778.13 1781.84 1781.55 1781.49 1778.66 13 1777.01 1779.27 1781.02 1781.82 1781.61 1781.10 1779.77 1778.04 1781.97 1781.47 1781.46 1778.55 1777.02 1779.27 1781.02 1781.82 1781.60 1781.10 1779.77 1778.04 1781.92 1781.47 1781.40 1778.55 1777.04 1779.29 1781.04 1781.80 1781.59 1781.07 1779.69 1778.17 1781.74 1781.50 1781.47 1778.15 1777.04 1779.29 1781.04 1781.80 1781.55 1781.04 1779.69 1778.17 1781.74 1781.50 1781.47 1778.17 1777.08 1779.26 1781.04 1781.79 1781.54 1781.08 179.48 1778.08 1781.69 1781.47 1781.44 1778.15 1777.08 1779.20 1781.00 1781.75 1781.40 1779.40 1779.79 1781.65 1781.49 1781.44 1778.15 1777.08 1779.20 1781.00 1781.75 1781.49 1781.06 1779.40 1777.97 1781.65 1781.49 1781.40 1778.14 1777.08 1779.20 1781.00 1781.75 1781.49 1781.00 1779.75 1777.63 1781.65 1781.49 1781.40 1778.41 1781.70 1777.08 1779.20 1781.00 1781.75 1781.49 1781.02 1779.57 1777.63 1781.62 1781.48 1781.39 1788.40 1777.08 1779.20 1781.10 1781.74 1781.47 1780.98 1779.54 1777.47 1781.63 1781.49 1781.30 1781.40 1788.14 1781.30 1777.08 1779.25 1781.06 1781.71 1781.45 1780.92 1779.64 1777.14 1781.73 1781.53 1781.49 1781.30 1781.40 1779.19 1781.65 1781.49 1781.43 1780.92 1779.64 1777.14 1781.73 1781.53 1781.18 1781.30 1777.08 1779.28 1781.05 1781.49 1781.43 1780.92 1779.64 1777.14 1781.73 1781.53 1781.18 1781.30 1777.08 1779.28 1781.05 1781.49 1781.43 1780.92 1779.64 1777.14 1781.55 1781.49 1781.13 1781.50 1781.49 1781.65 1781.49 1781.00 1781.73 1781.43 1780.82 1779.65 1779.89 1781.67 1781.46 1780.84 1781.00 1781.75 1781.49 1781.00 1781.75 1781.49 1781.00 1781.75 1781.49 1781.00 1781.75 1781.49 1781.00 1781.75 1781.49 1781.00 1781.75 1781.49 1781.00 1781.75 1781.49 1781.00 1781.75 1781.49 1781.00 1781.75 1781.49 1781.00 1781.75 1781.49 1781.00 1781.75 1781.49 1781.00 1781.75 1781.49 1781.00 1781.75 1781.49 1781.00 1781.75 1781.49 1781.00 1781.75 1781.49 1781.00 1781.75 1781.49 1781.0	9	1776.94	1779.20	1781.08	1781.86	1781.74	1781.24	1780.01	1778.49	1780.40	1781.54	1781.55	1779.04
12 1776.99 1779.32 1781.08 1781.84 1781.64 1781.14 1779.90 1778.13 1781.84 1781.55 1781.49 1778.66 13 1777.01 1779.27 1781.07 1781.82 1781.61 1781.10 1779.77 1778.04 1781.97 1781.47 1781.46 1778.56 14 1777.02 1779.27 1781.02 1781.82 1781.60 1781.10 1779.77 1778.04 1781.97 1781.46 1781.46 1778.56 15 1777.04 1779.29 1781.04 1781.80 1781.59 1781.07 1779.69 1778.17 1781.74 1781.50 1781.47 1778.31 16 1777.06 1779.28 1781.03 1781.80 1781.56 1781.04 1779.62 1778.20 1781.69 1781.47 1781.47 1778.16 17 1777.08 1779.26 1781.04 1781.79 1781.54 1781.08 1779.48 1778.08 1781.69 1781.52 1781.44 1778.17 18 1777.08 1779.20 1781.01 1781.77 1781.50 1781.06 1779.40 1777.97 1781.65 1781.49 1781.40 1778.17 19 1777.08 1779.20 1781.00 1781.75 1781.49 1781.02 1779.57 1777.63 1781.62 1781.48 1781.39 1778.44 20 1777.08 1779.20 1781.12 1781.74 1781.47 1780.98 1779.54 1777.47 1781.63 1781.49 1781.40 1778.47 21 1777.08 1779.29 1781.01 1781.72 1781.45 1780.96 1779.62 1777.27 1781.88 1781.49 1781.36 1781.02 21 1777.08 1779.25 1781.06 1781.71 1781.45 1780.96 1779.62 1777.27 1781.88 1781.49 1781.36 1781.02 21 1777.08 1779.25 1781.06 1781.71 1781.45 1780.96 1779.62 1777.27 1781.88 1781.47 1781.25 1781.44 1781.32 1777.08 1779.25 1781.03 1781.69 1781.43 1780.92 1779.64 1777.14 1781.73 1781.53 1781.18 1781.31 1781.32 1777.08 1779.28 1781.05 1781.69 1781.43 1780.86 1779.59 1779.99 1781.62 1781.46 1780.84 1781.00 1781.77 1779.86 1781.01 1781.73 1781.43 1780.86 1779.59 1779.99 1781.62 1781.45 1780.84 1781.00 1781.73 1781.44 1780.75 1780.94 1781.11 1781.45 1780.78 1779.57 1780.48 1781.55 1781.49 1780.72 1781.00 1780.79 1780.94 1781.17 1781.44 1780.77 1779.46 1781.15 1781.45 1780.45 1780.70 1780.94 1780.94 1781.17 1781.44 1780.77 1779.46 1781.15 1781.35 1780.22 1780.57 1780.94 1780.75 1780.94 1781.15 1780.67 1779.44 1781.00 1781.55 1781.35 1780.22 1780.57 1780.94 1780.69 1780.69 1780.69 1781.65 1780.70 1780.70 1780.99 1781.55 1781.55 1781.35 1780.22 1780.57 1779.40 1780.99 1781.55 1781.35 1780.22 1780.57 1779.40 1780.78 1780.70 1780.70 17	10	1776.95	1779.32	1781.07	1781.87	1781.72	1781.20	1779.85	1778.35	1780.78	1781.52	1781.52	1778.94
13 1777.01 1779.27 1781.07 1781.82 1781.61 1781.10 1779.77 1778.04 1781.97 1781.47 1781.46 1778.55 14 1777.02 1779.27 1781.02 1781.82 1781.60 1781.10 1779.87 1778.04 1781.97 1781.47 1781.46 1778.55 15 1777.04 1779.29 1781.04 1781.80 1781.59 1781.07 1779.69 1778.17 1781.47 1781.46 1781.47 1778.16 16 1777.06 1779.28 1781.03 1781.80 1781.56 1781.04 1779.62 1778.20 1781.69 1781.47 1781.43 1778.16 17 1777.08 1779.26 1781.04 1781.79 1781.54 1781.08 1779.48 1778.08 1781.69 1781.52 1781.44 1778.17 18 1777.08 1779.23 1781.01 1781.77 1781.50 1781.06 1779.40 1777.97 1781.65 1781.49 1781.40 1778.16 19 1777.08 1779.20 1781.00 1781.75 1781.49 1781.02 1779.57 1777.63 1781.62 1781.48 1781.39 1778.44 20 1777.08 1779.20 1781.12 1781.74 1781.47 1780.98 1779.54 1777.47 1781.63 1781.49 1781.36 1781.01 21 1777.08 1779.29 1781.10 1781.72 1781.45 1780.98 1779.64 1777.47 1781.83 1781.49 1781.36 1781.01 22 1777.08 1779.29 1781.05 1781.69 1781.43 1780.92 1779.64 1777.14 1781.73 1781.53 1781.18 1781.34 1781.34 1781.34 1779.09 1779.79 1781.65 1781.49 1781.11 1781.14 1780.92 1779.69 1779.99 1781.62 1781.46 1780.84 1781.05 1779.07 1779.79 1781.03 1781.72 1781.43 1780.92 1779.62 1778.93 1781.65 1781.46 1780.84 1781.05 1777.07 1779.86 1781.01 1781.73 1781.43 1780.92 1779.62 1778.93 1781.65 1781.46 1780.84 1781.05 1777.07 1779.79 1781.03 1781.73 1781.43 1780.92 1779.65 1781.39 1781.65 1781.46 1780.84 1781.05 1777.07 1779.86 1781.01 1781.73 1781.43 1780.92 1779.57 1780.48 1781.59 1781.46 1780.84 1781.05 1781.65 1781.79 1780.96 1781.71 1781.46 1780.78 1779.59 1781.59 1781.45 1780.72 1781.06 1780.96 1781.71 1781.46 1780.78 1779.59 1781.39 1781.55 1781.35 1780.62 1780.65 1780.65 1780.95 1780.95 1780.95 1781.35 1781.35 1780.92 1780.65 1780.65 1780.95		1776.98	1779.32	1781.06	1781.86	1781.68	1781.17	1779.72	1778.26	1781.06	1781.58	1781.55	1778.80
14 1777.02 1779.27 1781.02 1781.82 1781.60 1781.10 1779.87 1778.25 1781.82 1781.46 1781.40 1778.31 15 1777.04 1779.29 1781.04 1781.80 1781.59 1781.07 1779.69 1778.17 1781.74 1781.50 1781.47 1778.15 16 1777.06 1779.28 1781.04 1781.79 1781.54 1781.08 1779.62 1778.08 1781.69 1781.47 1781.43 1778.16 17 1777.08 1779.20 1781.01 1781.77 1781.50 1781.00 1779.40 1777.97 1781.65 1781.44 1778.14 19 1777.08 1779.20 1781.00 1781.75 1781.49 1781.40 1777.63 1781.62 1781.48 1781.49 1781.40 20 1777.08 1779.20 1781.10 1781.72 1781.45 1780.96 1777.47 1781.63 1781.49 1781.49 1781.30 1781.49 1781.40 1781.40 1781.44 1781.49 1781.44 1781.44 1781.49 1781.44 1781.49		1776.99	1779.32	1781.08	1781.84	1781.64	1781.14	1779.90	1778.13	1781.84	1781.55	1781.49	1778.64
15 1777.04 1779.29 1781.04 1781.80 1781.59 1781.07 1779.69 1778.17 1781.74 1781.50 1781.47 1778.18 16 1777.06 1779.28 1781.04 1781.80 1781.56 1781.04 1779.62 1778.20 1781.69 1781.47 1781.43 1778.18 17 1777.08 1779.26 1781.04 1781.79 1781.54 1781.08 1779.48 1778.08 1781.69 1781.52 1781.44 1778.18 18 1777.08 1779.23 1781.01 1781.77 1781.50 1781.06 1779.40 1777.97 1781.65 1781.49 1781.40 1778.18 19 1777.08 1779.20 1781.00 1781.75 1781.49 1781.02 1779.57 1777.63 1781.62 1781.48 1781.39 1778.44 20 1777.08 1779.20 1781.01 1781.74 1781.47 1780.98 1779.54 1777.47 1781.63 1781.49 1781.36 1781.05 21 1777.08 1779.19 1781.10 1781.72 1781.45 1780.92 1779.64 1777.47 1781.63 1781.49 1781.36 1781.05 22 1777.08 1779.25 1781.06 1781.71 1781.45 1780.92 1779.64 1777.14 1781.73 1781.53 1781.15 1781.45 1781.32 1777.08 1779.28 1781.05 1781.69 1781.43 1780.92 1779.64 1777.14 1781.73 1781.54 1781.11 1781.11 1781.12 24 1777.07 1779.79 1781.03 1781.72 1781.43 1780.86 1779.59 1779.99 1781.62 1781.46 1780.84 1781.01 1781.72 1781.43 1780.86 1779.59 1779.99 1781.62 1781.46 1780.84 1781.00 1777.06 1779.90 1780.99 1781.73 1781.43 1780.82 1779.57 1780.48 1781.55 1781.45 1780.72 1781.06 1787.06 1780.27 1780.96 1781.71 1781.44 1780.78 1779.59 1781.55 1781.45 1780.72 1781.06 1780.79 1777.06 1780.27 1780.96 1781.71 1781.44 1780.78 1779.59 1781.55 1781.45 1780.72 1781.06 1780.79 1777.06 1780.27 1780.96 1781.71 1781.44 1780.71 1779.49 1781.55 1781.57 1781.40 1780.45 1780.79 1777.06 1780.57 1780.96 1781.71 1781.44 1780.74 1779.49 1781.55 1781.57 1781.40 1780.45 1780.79 1777.06 1780.57 1780.96 1781.71 1781.44 1780.71 1779.44 1781.00 1781.55 1781.35 1780.32 1780.57 1780.96 1780.79 1780.99 1781.65 1780.67 1779.44 1781.00 1781.55 1781.35 1780.22 1780.57 1770.09 1780.99 1781.68 1780.70 1780.78 1780.79 1779.99 1780.79 1779.99	13	1777.01	1779.27	1781.07	1781.82	1781.61	1781.10	1779.77	1778.04	1781.97	1781.47	1781.46	1778.52
16 1777.06 1779.28 1781.03 1781.80 1781.56 1781.04 1779.62 1778.20 1781.69 1781.47 1781.43 1778.11 17 1777.08 1779.26 1781.04 1781.79 1781.54 1781.08 1779.48 1778.08 1781.69 1781.44 1778.14 18 1777.08 1779.23 1781.01 1781.77 1781.50 1781.06 1779.40 1777.97 1781.65 1781.49 1781.40 1778.14 19 1777.08 1779.20 1781.00 1781.75 1781.49 1781.02 1779.57 1777.63 1781.62 1781.48 1781.39 1778.44 20 1777.08 1779.19 1781.10 1781.72 1781.47 1780.98 1779.54 1777.47 1781.63 1781.49 1781.36 1781.40 21 1777.08 1779.19 1781.10 1781.72 1781.45 1780.98 1779.62 1777.27 1781.88 1781.47 1781.42 1781.42 1781.43 1780.93 1781.41 1781.43 1780.93 1781.63 1781.44 1781.45	14	1777.02	1779.27	1781.02	1781.82	1781.60	1781.10	1779.87	1778.25	1781.82	1781.46	1781.40	1778.37
17 1777.08 179.26 1781.04 1781.79 1781.54 1781.08 1779.48 1778.08 1781.69 1781.52 1781.44 1778.1 18 1777.08 1779.23 1781.01 1781.77 1781.50 1781.06 1779.40 1777.97 1781.65 1781.49 1781.40 1778.1 19 1777.08 179.20 1781.00 1781.75 1781.49 1781.02 1779.57 1777.63 1781.48 1781.49 1781.49 20 1777.08 179.20 1781.12 1781.74 1781.47 1780.98 1779.54 1777.47 1781.63 1781.48 1781.49 1781.40 21 1777.08 179.19 1781.10 1781.72 1781.45 1780.98 1779.62 1777.47 1781.63 1781.49 1781.40 1781.40 21 1777.08 1779.25 1781.06 1781.71 1781.45 1780.92 1779.62 1777.14 1781.73 1781.53 1781.49 1781.49 1781.49 1781.49 1781.49 1781.49 1781.49 1781.49 1781.41 1781.49 1	15	1777.04	1779.29	1781.04	1781.80	1781.59	1781.07	1779.69	1778.17	1781.74	1781.50	1781.47	1778.18
18 1777.08 179.23 1781.01 1781.77 1781.50 1781.06 1779.40 1777.97 1781.65 1781.49 1781.40 1778.14 19 1777.08 1779.20 1781.00 1781.75 1781.49 1781.02 1777.63 1781.62 1781.48 1781.39 1778.44 20 1777.08 1779.20 1781.12 1781.74 1781.47 1780.98 1779.54 1777.47 1781.63 1781.49 1781.36 1781.03 21 1777.08 1779.19 1781.10 1781.72 1781.45 1780.96 1779.62 1777.27 1781.88 1781.47 1781.45 1780.92 1779.64 1777.14 1781.53 1781.18 1781.45 1780.92 1779.64 1777.14 1781.53 1781.18 1781.45 1780.92 1779.64 1777.14 1781.53 1781.18 1781.45 1780.92 1779.64 1777.14 1781.67 1781.44 1781.45 1780.92 1779.64 1777.14 1781.67 1781.44 1781.45 1780.92 1779.62 1777.14 1781.67 1781.44 1781.41 1		1777.06		1781.03	1781.80	1781.56	1781.04	1779.62	1778.20	1781.69	1781.47	1781.43	1778.16
19 1777.08 1779.20 1781.00 1781.75 1781.49 1781.02 1779.57 1777.63 1781.62 1781.48 1781.39 1778.40 1777.08 1779.20 1781.12 1781.74 1781.47 1780.98 1779.54 1777.47 1781.63 1781.49 1781.36 1781.00 1781.01 1781.72 1781.45 1780.96 1779.62 1777.27 1781.88 1781.47 1781.25 1781.46 1781.71 1781.45 1780.92 1779.64 1777.14 1781.73 1781.53 1781.18 1781.39 1777.08 1779.25 1781.06 1781.71 1781.45 1780.92 1779.64 1777.14 1781.73 1781.53 1781.18 1781.30 1777.08 1779.28 1781.05 1781.69 1781.43 1780.92 1779.62 1778.93 1781.67 1781.49 1781.11 1781.12 1777.07 1779.79 1781.03 1781.72 1781.43 1780.86 1779.59 1779.99 1781.62 1781.46 1780.84 1781.00 1781.73 1781.43 1780.82 1779.57 1780.48 1781.59 1781.45 1780.72 1781.00 1781.73 1781.43 1780.82 1779.57 1780.48 1781.59 1781.45 1780.72 1781.00 1781.73 1781.44 1780.78 1779.59 1781.58 1781.42 1780.60 1780.90 1777.06 1780.27 1780.96 1781.71 1781.46 1780.78 1779.49 1781.52 1781.57 1781.40 1780.45 1780.72 1781.00 1781.73 1781.45 1780.74 1779.46 1781.13 1781.55 1781.37 1780.36 1780.75 1780.96 1780.97 1780.98 1780.92 1781.69 1780.92 1781.69 1780.92 1781.69 1780.92 1781.69 1780.92 1781.69 1780.92 1781.69 1780.92 1781.40 1780.67 1779.40 1781.53 1781.55 1781.37 1780.36 1780.57 1780.94 1781.71 1781.44 1780.67 1779.46 1781.13 1781.56 1781.37 1780.36 1780.57 1780.94 1781.71 1781.44 1780.67 1779.46 1781.13 1781.55 1781.35 1780.22 1780.57 1777.02 1780.69 1780.92 1781.69 1781.42 1780.67 1779.44 1781.00 1781.55 1781.35 1780.22 1780.57 1760.98 1780.72 1780.96 1781.68 1780.60 1779.42 1780.90 1781.53 1781.32 1780.10 1780.77 1770.69 1780.96 1781.65 1780.70 1780.78 1781.29 1779.99 1780.70 1780.78 1780.78 1781.29 1779.99 1780.78 1780.78 1780.78 1781.29 1779.99 1780.78 1780.78 1780.78 1780.78 1780.78 1781.29 1779.99 1780.78 1780.78 1780.78 1780.78 1780.78 1780.78 1780.78 1780.79 1780.78 1780.79 1780.78 1780.78 1780.78 1780.79 1780.78 1780.79 1780.78 1780.78 1780.78	17	1777.08	1779.26	1781.04	1781.79	1781.54	1781.08	1779.48	1778.08	1781.69	1781.52	1781.44	1778.17
20 1777.08 1779.20 1781.12 1781.74 1781.47 1780.98 1779.54 1777.47 1781.63 1781.49 1781.36 1781.01 21 1777.08 1779.19 1781.10 1781.72 1781.45 1780.96 1779.62 1777.27 1781.88 1781.47 1781.25 1781.42 22 1777.08 1779.25 1781.06 1781.71 1781.45 1780.92 1779.64 1777.14 1781.73 1781.53 1781.18 1781.31 23 1777.08 1779.28 1781.05 1781.69 1781.43 1780.92 1779.62 1778.93 1781.67 1781.49 1781.11 1781.11 24 1777.07 1779.79 1781.03 1781.72 1781.43 1780.86 1779.59 1779.99 1781.62 1781.46 1780.84 1781.00 25 1777.07 1779.86 1781.01 1781.73 1781.43 1780.82 1779.57 1780.48 1781.59 1781.45 1780.72 1781.00 26 1777.06 1779.90 1780.99 1781.72 1781.47 1780.78 1779.50 1781.39 1781.58 1781.42 1780.60 1780.91 27 1777.06 1780.27 1780.96 1781.71 1781.46 1780.74 1779.49 1781.25 1781.57 1781.40 1780.45 1780.76 28 1777.05 1780.57 1780.94 1781.71 1781.44 1780.71 1779.46 1781.13 1781.56 1781.37 1780.36 1780.56 29 1777.02 1780.69 1780.92 1781.69 1781.42 1780.67 1779.44 1781.00 1781.55 1781.35 1780.32 1780.56 29 1777.02 1780.69 1780.92 1781.69 1781.42 1780.67 1779.44 1781.00 1781.55 1781.35 1780.22 1780.57 30 1776.98 1780.72 1780.93 1781.68 1780.62 1779.42 1780.90 1781.53 1781.32 1780.10 1780.73 31 1776.92 1780.96 1781.65 1780.70 1780.78 1781.29 1779.99	18	1777.08	1779.23	1781.01	1781.77	1781.50	1781.06	1779.40	1777.97	1781.65	1781.49	1781.40	1778.14
21 1777.08 1779.19 1781.10 1781.72 1781.45 1780.96 1779.62 1777.27 1781.88 1781.47 1781.25 1781.44 1787.08 1779.25 1781.06 1781.71 1781.45 1780.92 1779.64 1777.14 1781.73 1781.53 1781.18 1781.32 1777.08 1779.28 1781.05 1781.69 1781.43 1780.92 1779.62 1778.93 1781.67 1781.49 1781.11 1781.11 1781.12 1777.07 1779.79 1781.03 1781.72 1781.43 1780.86 1779.59 1779.99 1781.62 1781.46 1780.84 1781.00 1779.70 1779.86 1781.01 1781.73 1781.43 1780.82 1779.57 1780.48 1781.59 1781.45 1780.72 1781.00 1781.70 1779.86 1781.01 1781.73 1781.47 1780.78 1779.50 1781.39 1781.58 1781.42 1780.60 1780.90 1777.06 1779.90 1780.99 1781.72 1781.47 1780.78 1779.50 1781.39 1781.58 1781.42 1780.60 1780.90 1777.06 1780.27 1780.96 1781.71 1781.46 1780.74 1779.49 1781.25 1781.57 1781.40 1780.45 1780.75 1780.45 1780.75 1780.46 1780.75 1780.76 178	19	1777.08	1779.20	1781.00	1781.75	1781.49	1781.02	1779.57	1777.63	1781.62	1781.48	1781.39	1778.40
22 1777.08 1779.25 1781.06 1781.71 1781.45 1780.92 1779.64 1777.14 1781.73 1781.53 1781.18 1781.36 1777.08 1779.28 1781.05 1781.69 1781.43 1780.92 1779.62 1778.93 1781.67 1781.49 1781.11 1781.12 1777.07 1779.79 1781.03 1781.72 1781.43 1780.86 1779.59 1779.99 1781.62 1781.46 1780.84 1781.06 1779.70 1779.86 1781.01 1781.73 1781.43 1780.82 1779.57 1780.48 1781.59 1781.45 1780.72 1781.00 1780.70 1779.86 1781.01 1781.73 1781.43 1780.82 1779.57 1780.48 1781.59 1781.45 1780.72 1781.00 1780.79 1777.06 1780.27 1780.96 1781.71 1781.46 1780.74 1779.50 1781.39 1781.58 1781.42 1780.60 1780.90 1780.90 1780.90 1781.71 1781.46 1780.74 1779.49 1781.25 1781.57 1781.40 1780.45 1780.70 1780.48 1781.71 1780.48 1780.70 1780.50 178	20	1777.08	1779.20	1781.12	1781.74	1781.47	1780.98	1779.54	1777.47	1781.63	1781.49	1781.36	1781.03
23 1777.08 1779.28 1781.05 1781.69 1781.43 1780.92 1779.62 1778.93 1781.67 1781.49 1781.11 1781.11 24 1777.07 1779.79 1781.03 1781.72 1781.43 1780.86 1779.59 1779.99 1781.62 1781.46 1780.84 1781.00 25 1777.07 1779.86 1781.01 1781.73 1781.43 1780.82 1779.57 1780.48 1781.59 1781.45 1780.72 1781.00 27 1777.06 1780.99 1781.72 1781.47 1780.78 1779.50 1781.39 1781.58 1781.42 1780.60 1780.91 1777.06 1780.27 1780.96 1781.71 1781.46 1780.74 1779.49 1781.25 1781.57 1781.40 1780.45 1780.72 1781.00 28 1777.05 1780.57 1780.94 1781.71 1781.44 1780.71 1779.46 1781.13 1781.56 1781.37 1780.36 1780.79 1780.90 1781.92 1780.90 1781.92 1780.90 1781.59 1781.55 1781.35 1780.22 1780.50 1776.98 1780.69 1780.92 1781.68 1781.42 1780.67 1779.44 1781.00 1781.55 1781.35 1780.22 1780.50 1776.98 1780.72 1780.93 1781.68 1780.62 1779.42 1780.90 1781.53 1781.32 1780.10 1780.73 1776.92 1780.96 1781.65 1780.70 1780.78 1781.29 1779.99					1781.72	1781.45	1780.96	1779.62	1777.27	1781.88	1781.47	1781.25	1781.44
24 1777.07 1779.79 1781.03 1781.72 1781.43 1780.86 1779.59 1779.99 1781.62 1781.46 1780.84 1781.04 1781.05 1777.07 1779.86 1781.01 1781.73 1781.43 1780.82 1779.57 1780.48 1781.59 1781.45 1780.72 1781.01 1781.73 1781.44 1780.82 1779.57 1780.48 1781.59 1781.45 1780.72 1781.01 1781.74 1780.78 1779.50 1781.39 1781.58 1781.42 1780.60 1780.94 1781.71 1781.44 1780.74 1779.49 1781.25 1781.57 1781.40 1780.45 1780.75 1780.57 1780.94 1781.71 1781.44 1780.71 1779.46 1781.13 1781.56 1781.37 1780.36 1780.75 1780.59 1781.59 1781.59 1781.37 1780.36 1780.55 1780.59 178			1779.25	1781.06	1781.71	1781.45	1780.92	1779.64	1777.14	1781.73	1781.53	1781.18	1781.30
25 1777.07 1779.86 1781.01 1781.73 1781.43 1780.82 1779.57 1780.48 1781.59 1781.45 1780.72 1781.00 26 1777.06 1779.90 1780.99 1781.72 1781.47 1780.78 1779.50 1781.39 1781.58 1781.42 1780.60 1780.99 27 1777.06 1780.27 1780.96 1781.71 1781.46 1780.74 1779.49 1781.25 1781.57 1781.40 1780.45 1780.79 28 1777.05 1780.57 1780.94 1781.71 1781.44 1780.71 1779.46 1781.13 1781.56 1781.37 1780.36 1780.67 29 1777.02 1780.69 1780.92 1781.69 1781.42 1780.67 1779.44 1781.00 1781.55 1781.35 1780.22 1780.57 30 1776.98 1780.72 1780.93 1781.68 1780.62 1779.42 1780.90 1781.53 1781.32 1780.10 1780.79 31 1776.92 1780.96 1781.65 1780.70 1780.78 1781.29 1779.99				1781.05	1781.69	1781.43	1780.92	1779.62	1778.93	1781.67	1781.49	1781.11	1781.18
26 1777.06 1779.90 1780.99 1781.72 1781.47 1780.78 1779.50 1781.39 1781.58 1781.42 1780.60 1780.99 27 1777.06 1780.27 1780.96 1781.71 1781.46 1780.74 1779.49 1781.25 1781.57 1781.40 1780.45 1780.75 1777.05 1780.57 1780.94 1781.71 1781.44 1780.71 1779.46 1781.13 1781.56 1781.37 1780.36 1780.76 1780.96 1780.92 1781.69 1781.42 1780.67 1779.46 1781.13 1781.55 1781.35 1780.22 1780.57 1776.98 1780.72 1780.93 1781.68 1780.62 1779.42 1780.90 1781.53 1781.32 1780.10 1780.73 1776.92 1780.96 1781.65 1780.70 1780.78 1781.29 1779.99		1777.07	1779.79	1781.03	1781.72	1781.43	1780.86	1779.59	1779.99	1781.62	1781.46	1780.84	1781.04
27 1777.06 1780.27 1780.96 1781.71 1781.46 1780.74 1779.49 1781.25 1781.57 1781.40 1780.45 1780.79 28 1777.05 1780.57 1780.94 1781.71 1781.44 1780.71 1779.46 1781.13 1781.56 1781.37 1780.36 1780.69 29 1777.02 1780.69 1780.92 1781.69 1781.42 1780.67 1779.44 1781.00 1781.55 1781.35 1780.22 1780.57 30 1776.98 1780.72 1780.93 1781.68 1780.62 1779.42 1780.90 1781.53 1781.32 1780.10 1780.79 31 1776.92 1780.96 1781.65 1780.70 1780.78 1781.29 1779.99	25	1777.07	1779.86	1781.01	1781.73	1781.43	1780.82	1779.57	1780.48	1781.59	1781.45	1780.72	1781.00
28 1777.05 1780.57 1780.94 1781.71 1781.44 1780.71 1779.46 1781.13 1781.56 1781.37 1780.36 1780.66 1777.02 1780.69 1780.92 1781.69 1781.42 1780.67 1779.44 1781.00 1781.55 1781.35 1780.22 1780.55 1776.98 1780.72 1780.93 1781.68 1780.62 1779.42 1780.90 1781.53 1781.32 1780.10 1780.76 1776.92 1780.96 1781.65 1780.70 1780.78 1781.29 1779.99						1781.47	1780.78	1779.50	1781.39				1780.90
29 1777.02 1780.69 1780.92 1781.69 1781.42 1780.67 1779.44 1781.00 1781.55 1781.35 1780.22 1780.57 30 1776.98 1780.72 1780.93 1781.68 1780.62 1779.42 1780.90 1781.53 1781.32 1780.10 1780.73 1776.92 1780.96 1781.65 1780.70 1780.78 1781.29 1779.99				1780.96	1781.71	1781.46	1780.74	1779.49	1781.25	1781.57	1781.40	1780.45	1780.79
30 1776.98 1780.72 1780.93 1781.68 1780.62 1779.42 1780.90 1781.53 1781.32 1780.10 1780.78 31 1776.92 1780.96 1781.65 1780.70 1780.78 1781.29 1779.99		1777.05	1780.57	1780.94	1781.71	1781.44	1780.71	1779.46	1781.13	1781.56	1781.37	1780.36	1780.67
31 1776.92 1780.96 1781.65 1780.70 1780.78 1781.29 1779.99		1777.02	1780.69	1780.92	1781.69	1781.42	1780.67	1779.44	1781.00	1781.55	1781.35	1780.22	1780.57
	30	1776.98	1780.72	1780.93	1781.68		1780.62	1779.42	1780.90	1781.53	1781.32	1780.10	1780.78
MPAN 1775 OF 1770 OF 1701 OF 1701 OF 1701 OF 1701 OF 1770 OF 1770 OF 1770 OF 1701 OF 1701 OF 1701 OF	31	1776.92		1780.96	1781.65		1780.70		1780.78		1781.29	1779.99	
ENDIG ALIVO, DE ALICO, DE ALICALUL ALOLOS ALOLOS ALOLOS ALOLOS ALICANDO ALOLOS	MBAN	1776.96	1778.94	1781.01	1781.84	1781.56	1781.05	1779.86	1778.97	1781.23	1781.48	1781.21	1779.67
	MAX	1777.08	1780.72	1781.12	1786.50	1781.78				1781.97	1781.58	1782.68	1781.44
	MIN	1776.37	1776.77	1780.79	1780.90					1780.02	1781.29	1779.99	1778.14

CAL YR 1991 MEAN 1777.75 MAX 1782.01 MIN 1772.93 WTR YR 1992 MEAN 1780.31 MAX 1786.50 MIN 1776.37

50043000 RIO DE LA PLATA AT PROYECTO LA PLATA, PR

LOCATION.--Lat 18°09'37", long 66°13'44", Hydrologic Unit 21010005, at upstream side of bridge on Highway 173, 0.4 mi (0.6 km) northeast of Proyecto La Plata, and 2.5 mi (4.0 km) upstream from Rio Usabón.

DRAINAGE AREA.--63.0 mi² (163.2 km²), excludes 8.2 mi² (21.1 km²) upstream from Carite Reservoir, the flow of which is diverted to Río Guamaní.

WATER-DISCHARGE RECORDS

PERIOD OF RECORD. -- 1958 (occasional measurements only), February 1959 to March 1960 (monthly measurements only), April 1960 to current year.

GAGE.--Water-stage recorder. Elevation of gage is 850 ft (259 m), from topographic map. Prior to Mar. 29, 1961, wire-weight gage read twice daily at same site and datum.

REMARKS.--Records poor. The Puerto Rico Aqueduct and Sewer Authority operates a pumping plant about 5 mi (8 km) upstream which can divert as much as 23 ft³/s (0.65 m³/s) into Cidra Reservoir. Gage-height and precipitation satellite telemetry at station.

satel	lite tel	emetry at	station	•								
		DI SCHA	RGE, CUB	IC FERT PER		WATER Y Y MEAN V	rear october /Alues	1991 TO	September	1992		
DAY	OCT	NOV	DEC	JAN	FEB	MAR	APR	MAY	JUN	JOL	AUG	SEP
1	e 16	e49	e11	e9.8	e14	e9.3	e19	e150	e25	e9.2	e9.2	e9.6
2	e17	e38	e13	e9.8	e15	e9.4	e600	e185	e23	e9.2	69.4	e11
3	e12	e28	e1 6	e9.4	045	e9.0	e40	e31	e22	e8.8	e22	e19
4	e11	e19	e22	e28	e49	e11	e18	e21	e21	e8.6	e100	e28
5	e17	e13	e24	e 8000	e27	e12	e14	e19	e19	e9.2	e220	e 16
6	ell	e24	e20	e5230	e2 6	e9.5	e17	e34	e19	e8. 6	e50	e15
7	e55	e32	e 18	e1740	e23	69.2	e21	e18	e20	e14	e22	e12
8	e25	e35	e18	e49	e18	e4 5	e17	e20	e21	e31	e19	e9.5
9	e13	e23	e21	e47	e17	e 15	e15	e13	e21	e16	e25	e8.7
10	e11	e14	e 18	e 66	e20	e11	014	e13	e20	e11	e 20	e8.3
11	e10	e12	e15	e 36	e 19	e9.8	e14	e12	e19	e10	e1 7	e8.1
12	e97	e11	e 16	e29	e 25	e9.2	e1 3	e12	e1 7	e11	e2 0	e7.5
13	e 9.0	e9.4	e14	e 66	e16	e 9.0	e13	e13	e15	e16	e16	e7.1
14	e8.8	e9.6	619	e36	e15	e8.8	e13	e13	e14	e23	e56	e7.1
15	e 9.0	e8.6	e13	e 29	e15	e8.5	e12	e31	e14	e25	e21	e7.3
16	e8.8	e14	e12	e230	e14	e8.4	e13	e74	e14	e13	e17	e15
17	e7.8	e11	e1 0	e 110	e 13	e 24	e13	e22	e13	e 11	e15	e26
18	e 8.6	e9. 0	e 9.6	e 56	e14	e15	e13	e120	e 13	e 10	e15	e45
19	e9.4	69.0	e 9.0	e38	e14	e12	e13	e180	e12	e16	e16	e97
20	e9.2	e10	e 46	e 31	e 14	e 10	e13	e74	e13	e 9.6	e 16	e45
21	e9.2	e17	e 31	e28	e15	e9.6	e12	e170	e 16	e8.8	e14	e20
22	e8.2	e20	e17	e27	e14	e19	e12	e78	e12	e12	e13	e15
23	e8.4	e45	e14	e26	e13	e11	e11	e400	e11	e23	e12	e12
24	e7.6	e 88	e12	e24	e13	e9.6	e11	e280	e10	e34	e11	e11
25	e7.8	e23	e11	e24	e1 3	e9.2	e 11	e130	e10	e11	e12	e 9.9
26	e8.4	e19	e 12	e23	e14	e8 .6	e11	e120	e 9.8	e9.7	e13	e8.8
27	e7.8	e14	e17	e21	e13	e300	e10	e100	e9.8	e9.4	e11	e8.2
28	e 10	e1 2	e13	e19	e12	e530	e28	e56	e9.6	e9.4	e10	e8.4
29	e25	e 17	e 11	e18	e11	e28	e60	e4 0	e9.4	6 9.0	e9.8	e9.4
30	e27	e13	e10	e16		e13	e4 6	e31	e9.4	e8.6	e10	e10
31	e13		e9.8	e15		e34		e27		e8.7	e11	
TOTAL	498.0	646.6	502.4	16091.0	531	1227.1	1117	2487	462.0	413.8	832.4	514.9
MRAN	16.1	21.6	16.2	519	18.3	39.6	37.2	80.2	15.4	13.3	26.9	17.2
MAX	97	88	46	8000	49	530	600	400	25	34	220	97
MIN	7.6	8.6	9.0	9.4	11	8.4	10	12	9.4	8.6	9.2	7.1
AC-FT	988	1280	997	31920	1050	2430	2220	4930	916	821	1650	1020
CFSM	.29	. 39	.30	9.47	.33	.72	. 68	1.46	. 28	. 24	.49	.31
IN.	.34	.44	.34	10.92	.36	. 83	.76	1.69	.31	.28	.57	.35
e Bi	stimated											
STATIST	TICS OF M	ONTHLY ME	AN DATA	FOR WATER Y	BARS 196	0 - 1992	2, BY WATER Y	RAR (WY)			
								-	•			
MEAN MAX	212	184	102	66.8	46.6	34.7	50.7	106	95.3	83.8	137	157
	2164 1971	831	565	519	195	120	323	594	629	489	642	975
(WY) MIN	7.82	1978 12.1	1971 9.16	1992 7.78	1989 7.65	1972 4.72	1971 6.61	1985 6.66	1970 4.93	1961 5.30	1961 9.45	1960 11.9
(WY)	1969	1982	1990	1990	1990	1977	1977	1968	1977	1977	1967	1967
(41)	1303	1702	1370	1990	1330	1977	19//	1700	13//	1911	1307	1301
SUMMARY	Y STATIST	ric s	FOR	1991 CALEN	DAR YEAR	1	FOR 1992 WAT	TER YEAR		WATER 3	TEARS 1960	- 1992
ANNUAL				8590.2			25323.2					
ANNUAL				23.5			69.2			105		
	r annual									368		1971
	ANNUAL M					-				31.3		1968
	T DAILY ME DAILY ME			900	Jul 16		8000	Jan 5		20300		6 1960
		AM Y NINIMUM	1	3.1 3.9			7.1 7.7	Sep 13		3.2		25 1974 6 1977
		EAR FLOW		3.9	Aug 8	•	73600	Sep 9 Jan 5		73600		5 1992
		BAK STAGE						Jan 5		36.3		5 1992
	RUNOFF (•	17040			50230			75790		
	RUNOFF (.43			1.26			1.9	91	
	RUNOFF (5.83			17.19			25.9		
10 PER	CENT EXCE	EDS		45			49			160		
	CENT BXCE			11			14			29		
90 PER	CENT BXCE	RDS		5.4			9.0			8.9	•	

50043000 RIO DE LA PLATA AT PROYECTO LA PLATA, PR--Continued

WATER-QUALITY RECORDS

PERIOD OF RECORD. -- Water years 1958 to current year.

WATER-QUALITY DATA, WATER YEAR OCTOBER 1991 TO SEPTEMBER 1992

DATE	TIME	DIS- CHARGE, INST. CUBIC FRET PER SECOND	SPR- CIFIC CON- DUCT- ANCE (US/CM)	PH WATER WHOLE FIELD (STAND- ARD UNITS)	TEMPER- ATURE WATER (DEG C)	TUR- BID- ITY (NTU)	OXYGEN, DIS- SOLVED (MG/L)	OXYGEN DEMAND, CHEM- ICAL (HIGH LEVEL) (MG/L)	COLI- FORM, FECAL, 0.45 UM-MF (COLS./ 100 ML)	STREP- TOCOCCI FECAL, (COLS. PER 100 ML)
OCT 1991 08	1200	24	437	8.1	27.5	13	7.5	20	K 650	520
DRC										
05 FRB 1992	0930	31	396	7.7	23.5	5.0	6.8	19	K600	570
22 APR	1100	12	440	8.2	24.5	0.50	8.3	<10	140	320
20	0905	300	395	7.7	25.0	280	6.3	36	K73000	65000
JUN 10	0950	19	428	8.3	27.5	0.60	8.2	<10	K80	K170
AUG 07	0925	142	175	6.9	26.5	26	6.2	25	21000	3500
	HARD- NES S TOTAL	CALCIUM DIS-	MAGNE- SIUM, DIS-	SODIUM, DIS-	SODIUM AD- SORP-	POTAS- SIUM, DIS-	ALKA- LINITY WAT WH TOT FET	SULFIDE	SULFATE DIS-	CHLO- RIDE, DIS-
	(MG/L	SOLVED	SOLVED	SOLVED	TION	SOLVED	FIELD	TOTAL	SOLVED	SOLVED
DATE	AS CACO3)	(MG/L AS CA)	(MG/L AS MG)	(MG/L	RATIO	(MG/L	MG/L AS CACO3	(MG/L AS S)	(MG/L AS SO4)	(MG/L AS CL)
	CACOS)	AS CA)	AS MG)	AS NA)		AS K)	CACOS	AS S)	AS SUE)	MS CE)
OCT 1991 08	160	39	14	33	1	2.8	140	<0.5	26	34
DEC								10.5		
05 PBB 1992							130			
22 APR							170			
20	80	20	7.3	15	0.7	3.4	130	<0.5	7.4	17
JUN 10							150			
AUG 07	56	14	5.1	14	0.8	1.7	60		8.4	14
•/	30	••	3.1		•••	•••	•		-	
	FLUO- RIDE, DIS- SOLVED	SILICA, DIS- SOLVED (MG/L	SOLIDS, SUM OF CONSTI- TURNTS, DIS-	SOLIDS, DIS- SOLVED (TONS	RBSIDUR TOTAL AT 105 DEG. C, SUS-	NITRO- GEN, NITRATE TOTAL	NITRO- GEN; NITRITE TOTAL	NITRO- GEN, NO2+NO3 TOTAL	NITRO- GEN, AMMONIA TOTAL	NITRO- GEN, ORGANIC TOTAL
DATE	(MG/L	AS	SOLVED	PER	PRNDRD	(MG/L	(MG/L	(MG/L	(MG/L	(MG/L
	AS F)	SIO2)	(MG/L)	DAY)	(MG/L)	AS N)	AS N)	AS N)	AS N)	AS N)
OCT 1991					_					
08	0.10	24	257	16.4	23	1.87	0.030	1.90	0.050	0.45
05 FRB 1992					22	2.47	Ó.130	2.60	0.130	0.57
22					4		<0.010	0.290	0.010	0.19
APR 20	0.10	17	165	134	291	1.08	0.020	1.10	0.020	0.58
JUN 10					<1	0.690	0.010	0.700	<0.010	
AUG		17	100	41.0				_		0.33
07	0.10	17	109	41.8	39	0.480	0.030	0.510	0.070	0.33
K = non-ide	al count									

RIO DE LA PLATA BASIN

50043000 RIO DE LA PLATA AT PROYECTO LA PLATA, PR--Continued
WATER-QUALITY DATA, WATER YEAR OCTOBER 1991 TO SEPTEMBER 1992

DATE	NITRO- GEN, AM- MONIA + ORGANIC TOTAL (MG/L AS N)	NITRO- GEN, TOTAL (MG/L AS N)	NITRO- GEN, TOTAL (MG/L AS NO3)	PHOS- PHORUS TOTAL (MG/L AS P)	ARSENIC TOTAL (UG/L AS AS)	BARIUM, TOTAL RECOV- ERABLE (UG/L AS BA)	BORON, TOTAL RECOV- ERABLE (UG/L AS B)	CADMIUM TOTAL RECOV- ERABLE (UG/L AS CD)	CHRO- MIUM, TOTAL RECOV- ERABLE (UG/L AS CR)	COPPER, TOTAL RECOV- ERABLE (UG/L AS CU)
OCT 1991										
08 Dec	0.50	2.4	11	0.710	<1	<100	30	<1	2	<10
05 FEB 1992	0.70	3.3	15	0.930						
22 APR	0.20	0.49	2.2	0.170						
20 JUN	0.60	1.7	7.5	0.360	<1	<100	30	<1	20	30
10	0.20	0.90	4.0	0.370						
07	0.40	0.91	4.0	0.140						
DATE	IRON, TOTAL RECOV- ERABLE (UG/L AS FE)	LEAD, TOTAL RECOV- ERABLE (UG/L AS PB)	MANGA - NESE, TOTAL RECOV- ERABLE (UG/L AS MN)	MERCURY TOTAL RECOV- BRABLE (UG/L AS HG)	SELE- NIUM, TOTAL (UG/L AS SE)	SILVER, TOTAL RECOV- ERABLE (UG/L AS AG)	ZINC, TOTAL RECOV- ERABLE (UG/L AS ZN)	CYANIDE TOTAL (MG/L AS CN)	PHENOLS TOTAL (UG/L)	MBTHY- LENE BLUE ACTIVE SUB- STANCE (MG/L)
OCT 1991	TOTAL RECOV- ERABLE (UG/L AS FE)	TOTAL RECOV- ERABLE (UG/L AS PB)	NESE, TOTAL RECOV- ERABLE (UG/L AS MN)	TOTAL RECOV- ERABLE (UG/L AS HG)	NIUM, TOTAL (UG/L AS SE)	TOTAL RECOV- ERABLE (UG/L AS AG)	TOTAL RECOV- ERABLE (UG/L AS ZN)	TOTAL (MG/L AS CN)	TOTAL (UG/L)	LENE BLUE ACTIVE SUB- STANCE (MG/L)
OCT 1991 08 DEC	TOTAL RECOV- ERABLE (UG/L	TOTAL RECOV- ERABLE (UG/L	NESE, TOTAL RECOV- ERABLE (UG/L	TOTAL RECOV- BRABLE (UG/L	NIUM, TOTAL (UG/L	TOTAL RECOV- ERABLE (UG/L	TOTAL RECOV- ERABLE (UG/L	TOTAL (MG/L	TOTAL	LENE BLUE ACTIVE SUB- STANCE
OCT 1991 08	TOTAL RECOV- ERABLE (UG/L AS FE)	TOTAL RECOV- ERABLE (UG/L AS PB)	NESE, TOTAL RECOV- ERABLE (UG/L AS MN)	TOTAL RECOV- ERABLE (UG/L AS HG)	NIUM, TOTAL (UG/L AS SE)	TOTAL RECOV- ERABLE (UG/L AS AG)	TOTAL RECOV- ERABLE (UG/L AS ZN)	TOTAL (MG/L AS CN)	TOTAL (UG/L)	LENE BLUE ACTIVE SUB- STANCE (MG/L)
OCT 1991 08 DEC 05 FEB 1992 22	TOTAL RECOV- ERABLE (UG/L AS FE)	TOTAL RECOV- ERABLE (UG/L AS PB)	NESE, TOTAL RECOV- ERABLE (UG/L AS MN)	TOTAL RECOV- BRABLE (UG/L AS HG)	NIUM, TOTAL (UG/L AS SE)	TOTAL RECOV- ERABLE (UG/L AS AG)	TOTAL RECOV- ERABLE (UG/L AS ZN)	TOTAL (MG/L AS CN)	TOTAL (UG/L)	LENE BLUE ACTIVE SUB- STANCE (MG/L)
OCT 1991 08 DEC 05 FEB 1992 22 APR 20	TOTAL RECOV- ERABLE (UG/L AS FE)	TOTAL RECOV- ERABLE (UG/L AS PB)	NESE, TOTAL RECOV- ERABLE (UG/L AS MN)	TOTAL RECOV- ERABLE (UG/L AS HG) <0.10	NIUM, TOTAL (UG/L AS SR)	TOTAL RECOV- ERABLE (UG/L AS AG) <1	TOTAL RECOV- ERABLE (UG/L AS ZN)	TOTAL (MG/L AS CN) <0.010	TOTAL (UG/L)	LENE BLUE ACTIVE SUB- STANCE (MG/L) 0.07
OCT 1991 08 DEC 05 FEB 1992 22	TOTAL RECOV- ERABLE (UG/L AS FE)	TOTAL RECOV- ERABLE (UG/L AS PB)	NESE, TOTAL RECOV- ERABLE (UG/L AS MN)	TOTAL RECOV- ERABLE (UG/L AS HG)	NIUM, TOTAL (UG/L AS SE)	TOTAL RECOV- ERABLE (UG/L AS AG) <1	TOTAL RECOV- ERABLE (UG/L AS ZN)	TOTAL (MG/L AS CN) <0.010	TOTAL (UG/L)	LENE BLUE SUB- STANCE (MG/L)

50043800 RIO DE LA PLATA AT COMERIO, PR

LOCATION.--Lat 18°13'23", long 66°13'30", Hydrologic Unit 21010005, on right bank 50 ft (15 m) upstream from bridge off Highway 167 in the Town of Comerío, 0.4 ml (0.6 km) southwest of Comerío High School, and 0.2 mi (0.3 km) northeast of Plaza de Comerío.

DRAINAGE AREA. -- 109 mi2 (282 km2).

WATER-DISCHARGE RECORDS

PERIOD OF RECORD. -- December 1988 to current year.

GAGE. -- Water-stage recorder and crest-stage gage. Datum of gage is 604.2 ft (184.160 m) above mean sem level.

REMARKS.--Records fair except those for estimated daily discharges, which are poor. Gage-height and precipitation satellite telemetry at station.

540011												
		DI SCHAF	IGE, CUB	C FEET PE	R SECOND, T	WATER YE MRAN VA	AR OCTOBER LUES	1991 TO	Septembe	R 1992		
DAY	OCT	NOV	DEC	JAN	FEB	MAR	APR	MAY	JUN	JUL	AUG	SEP
1	60	49	46	19	e27	e21	36	17	96	30	29	37
2	37	50	34	21	e27	e22	216	30	e115	28	32	37
3 4	56 32	50 31	30	21	e80	e21	35 21	30 20	e63 51	27 26	35 36	36 38
5	23	30	36 46	18 e14600	e90 e50	e23 e25	19	17	49	25	55	39
6	22	30	34	e5630	e50	e23	18	17	43	25	424	44
7	83	313	28	e330	e4 0	e22	17	22	39	25	163	38
8	47	367	24	e100	e35	e21	18	20	42 44	25 25	108 84	35 37
9 10	46 25	332 123	25 22	e90 e120	e34 e37	e25 e60	29 43	17 16	57	27	75	46
11	24	68	22	⊕ 70	e 36	e55	21	14	128	27	69	37
12	22	e45	26	e 60	e4 5	e35	18	14	161	27	73	34
13	19	e35	20	e120	e 30	e25	27	15	167	29	69	33
14 15	18 17	e30 27	18 17	e70 e60	e29 e28	e22 e21	27 23	15 37	224 113	28 23	61 62	33 33
16	16	29	17	e4 00	e25	e 20	43	33	85	22	63	33
17	16	42	17	e250	e24	e50	55	52	71	25	60	45
18	15	36	18	e110	e25	e33	25	29	75	36	54	63
19	15	26	17	e85	e25	30	127	20	55	30	51	63
20	33	21	19	e 70	e25	25	213	31	48	25	47	642
21	21	23	64	e 60	e26	23	60	79	96	26	46	562
22	19	37	49	e55	e27	24	30 23	29 832	116 72	26 49	45 41	152 91
23 24	21 20	38 32	27 21	e50 e45	e25 e25	24 22	19	1930	54	33	40	64
25	18	202	19	e42	e24	22	18	432	45	28	40	52
26	18	62	19	e38	e27	22	17	3380	40	25	40	47
27	18	90	20	e35	e25	20	16	463	37	26	45	44
28 29	21 25	187 118	20 19	e33 e31	e24 e23	21 21	16 16	184 132	34 34	22 22	46 43	41 39
30	282	73	19	e29	5 23	22	17	109	34	27	41	73
31	171		19	e28		20		106		28	40	
TOTAL	1260	2596	812	22690	988	820	1263	8142	2288	847	2117	2568
MBAN	40.6	86.5	26.2	732	34.1	26.5	42.1	263	76.3	27.3	68.3	85.6 642
MAX MIN	282 15	367 21	6 4 17	14600 18	90 23	60 20	216 16	3380 14	224 34	49 22	424 29	33
AC-FT	2500	5150	1610	45010	1960	1630	2510	16150	4540	1680	4200	5090
CFSM	.37	. 80	.24	6.75	.31	.24	.39	2.42	.70	. 25	.63	.79
IN.	.43	. 89	.28	7.78	.34	.28	.43	2.79	.78	.29	.73	.88
e Ba	stimated											
STATIST	rics of M	ONTHLY MR	AN DATA	FOR WATER	YEARS 1989	- 1992,	BY WATER	YEAR (WY))			
MEAN	342	74.0	40.2	221	110	48.6	32.4	92.0	40.5	52.5	53.4	235
MAX	866	92.7	70.4	732	247	75.7	42.1	263	76.3	119	76.1	729
(WY) MIN	1991	1991	1991	1992	1989	1989	1992	1992 25.3	1992 16.0	1991 19.0	1989 26.5	1989 51.2
(MA)	40.6 1992	42.6 1990	23.9 1990	22.8 1990	24.4 1990	26.5 1992	22.3 1991	1989	1991	1989	1991	1991
						_						1000
SUMMARY	Y STATIST	ICS	FOR	1991 CALE	NDAR YEAR	F	OR 1992 W	ATER YEAR		WATER Y	BARS 1989	- 1992
ANNUAL				20781 56.9			46391 127			101		
	r annual i	MRAN		30.9			147			131		1991
LOWEST	ANNUAL M	BAN								45.0		1990
	r daily m			2500 11	Jul 16		14600	Jan 5 May 11		14600 10		5 1992 17 1989
	DAILY ME	Y MINIMUM		13	Jul 14 Jun 16		14 16	May 8		11		25 1989
	TANEOUS P						127000	Jan 5		127000	Jan	5 1992
Instant	TANEOUS P	BAK STAGE						Jan 5		29.2		5 1992
	TANEOUS L RUNOFF ()			41220			14 92020	May 10		10 73200	Mug	28 1990
	RUNOFF (.5	2		1.1	7		.9:	3	
ANNUAL	RUNOFF (INCHES)		7.1			15.9	1		12.6		
	CENT BYCE			96 29			115 33			130 32		
	CENL EXCE CENL EXCE			28 16			33 19			16		
EM(

50043800 RIO DE LA PLATA AT COMERIO, PR--Continued

WATER-QUALITY RECORDS

PERIOD OF RECORDS .-- Water years 1989 to current year.

INSTRUMENTATION. -- USD-77 and automatic sediment sampler.

REMARKS. -- Sediment samples were collected by a local observer on a week basis and during high flow events.

PERIOD OF DAILY RECORD. --

SUSPENDED-SEDIMENT DISCHARGE: October 1989 to September 1992

EXTREMES FOR PERIOD OF DAILY RECORD.--SEDIMENT CONCENTRATION: Maximum daily mean, 8,800 mg/L Jan. 05, 1992; Minimum daily mean, 2 mg/L few days.

SEDIMENT LOADS: Maximum daily mean, 950,000 tons (862,000 tonnes) Jan. 05, 1992; Minimum daily mean, 0.06 ton (0.05 tonne) Aug 20, 1990.

EXTREMES FOR WATER YEARS 1992. --

SEDIMENT CONCENTRATION: Maximun daily mean, 8,800 mg/l Jan. 05, 1992; Minimun daily mean, 2 mg/L Feb. 23, 1992.

SEDIMENT LOADS: Maximum daily mean, 950,000 tons (862,000 tonnes) Jan. 05, 1992; Minimum daily mean .23 tons (.21 tonnes) May 12, 1992.

SEDIMENT DISCHARGE, SUSPENDED (TONS/DAY), WATER YEAR OCTOBER 1991 TO SEPTEMBER 1992

DAY	MEAN DISCHARGE (CFS)	MBAN CONCEN- TRATION (MG/L)	SEDIMENT DISCHARGE (TONS/DAY)	MEAN DISCHARGE (CFS)	MEAN CONCEN- TRATION (MG/L)	SEDIMENT DISCHARGE (TONS/DAY)	MEAN DISCHARGE (CFS)	MEAN CONCEN- TRATION (MG/L)	SEDIMENT DISCHARGE (TONS/DAY)
		OCTOBER		1	NOVEMBER		i	DECEMBER	
1	60	42	7.1	49	89	12	46	17	2.1
2	37	28	3.0	50	40	5.5	34	18	1.6
3	56	38	6.2	50	3 0	3.9	30	20	1.7
4	32	21	1.8	31	29	2.5	36	19	1.8
5	23	17	1.1	30	26	2.2	46	17	1.9
6	22	15	. 94	30	23	1.9	34	14	1.3
7	83	48	25	313	148	278	28	12	. 92
8	47	35	5.4	367	184	209	24	12	. 81
9	46	35	4.6	332	171	158	25	12	.78
10	25	29	2.1	123	40	17	22	12	.73
11	24	24	1.5	68	15	2.8	22	12	.75
12	22	20	1.2	e45	e14	1.6	26	16	1.0
13	19	20	1.0	e35	e12	1.0	20	20	1.1
14	18	21	.99	e 30	e12	.91	18	20	. 95
15	17	22	. 98	27	12	.86	17	20	. 92
16	16	21	.91	29	12	.88	17	20	. 92
17	16	19	. 79	42	22	3.0	17	20	. 95
18	15	18	.72	36	17	1.7	18	17	. 83
19	15	18	.72	26	15	1.0	17	14	. 64
20	33	27	2.6	21	15	.90	19	15	. 81
21	21	27	1.6	23	16	1.1	64	41	7.3
22	19	25	1.3	37	27	2.8	49	17	2.7
23	21	22	1.2	38	28	2.9	27	18	1.3
24	20	20	1.1	32	24	1.8	21	26	1.4
25	18	17	. 82	202	113	76	19	33	1.7
26	18	13	. 60	62	45	8.4	19	35	1.8
27	18	9	.43	90	54	23	20	34	1.8
28	21	14	1.0	187	58	35	20	32	1.7
29	25	19	1.4	118	23	7.8	19	33	1.7
30	282	127	384	73	19	3.9	19	35	1.8
31	171	173	100				19	35	1.8
TOTAL	1260		562.10	2596		867.35	812		47.51

e Estimated

RIO DE LA PLATA BASIN

50043800 RIO DE LA PLATA AT COMERIO, PR--Continued

SEDIMENT DISCHARGE, SUSPENDED (TONS/DAY), WATER YEAR OCTOBER 1991 TO SEPTEMBER 1992

DAY	MEAN DISCHARGE (CFS)	MBAN CONCEN- TRATION (MG/L)	SEDIMENT DISCHARGE (TONS/DAY)	MEAN DISCHARGE (CFS)	MRAN CONCEN- TRATION (MG/L)	SEDIMENT DISCHARGE (TONS/DAY)	MEAN DISCHARGE (CFS)	MEAN CONCEN- TRATION (MG/L)	SEDIMENT DISCHARGE (TONS/DAY)
		JANUARY		:	FEBRUARY			MARCH	
1	19	28	1.4	e27	8	e.58	e21	14	e.77
2	21	20	1.1	e27	8	e.58	e22	15	e. 90
3	21	20	1.2	e80	8	e1.7	e21	21	e1.2
4	18	20	1.0	e 90	11	e2.6	e2 3	43	e2.6
5	e14600	8800	e950000	e50	23	e3.0	e25	73	e4.9
6	e5630	3560	e86600	e50	40	e5.4	e2 3	90	e5.6
7	e330	921	e1190	e4 0	51	e5.5	e22	492	e2 9
8	e100	153	e41	e35	50	e4. 7	e21	48	e2.7
9	e90	22	e5.4	e34	44	e4.0	e25	28	e1.8
10	e120	15	e4 .9	e37	37	e3.7	e60	351	. e57
11	e70	12	e2.2	e36	30	e2.9	e55	355	e62
12	e6 0	11	e1.8	e45	21	e2.5	e35	29	e2.7
13	e120	10	e3.2	e30	15	e1.2	e25	28	e1.9
14	e 70	7	e1.4	e29	19	e1.5	e22	27	e1.6
15	e 60	8	e1.3	e28	33	e2.5	e21	26	e1.5
16	e400	16	e17	e25	40	e2.7	e2 0	24	e1.3
17	e250	27	e18	e24	36	e2.3	e50	23	e3.1
18	e110	31	e9.1	e25	26	e1.7	e33	17	e1.4
19	e85	25	e5.6	e25	16	e1.0	30	8	. 67
20	e 70	20	e3.8	e25	10	e.64	25	8	. 57
21	e60	11	e1.8	e 26	6	e.46	23	10	. 63
22	e55	8	e1.3	e27	5	e.36	24	11	.71
23	e50	5	e.74	e25	2	e.17	24	11	.70
24	e45	3	e. 42	e25	3	e.24	22	11	. 67
25	e42	3	e.34	e24	6	e.39	22	10	. 60
26	e38	3	e.30	e27	8	e.62	22	8	.46
27	e35	3	e.28	e25	11	e.75	20	29	1.6
28	e33	3	e.26	e24	12	e.78	21	143	9.0
29	e31	3	e.30	e23	12	e.74	21	170	9.4
30	e29	5	e.39				22	185	11
31	e28	7	e.53				20	113	6.4
TOTAL	22690		1037916.06	988		55.21	820		224.38

e Estimated

RIO DE LA PLATA BASIN
50043800 RIO DE LA PLATA AT COMERIO, PR--Continued

SEDIMENT DISCHARGE, SUSPENDED (TONS/DAY), WATER YEAR OCTOBER 1991 TO SEPTEMBER 1992

DAY	MEAN DISCHARGE (CFS)	MBAN CONCEN- TRATION (MG/L)	SEDIMENT DISCHARGE (TONS/DAY)	MEAN DISCHARGE (CFS)	MEAN CONCEN- TRATION (MG/L)	SEDIMENT DISCHARGE (TONS/DAY)	MEAN DISCHARGE (CFS)	MEAN CONCEN- TRATION (MG/L)	SEDIMENT DISCHARGE (TONS/DAY)
		APRIL			MAY			JUNE	
1	36	33	7.1	17	35	1.6	96	14	3.8
2 3	216	121	179	30	18	1.1	e115	24	e7.5
3	35	73	7.6	30	13	.94	e63	30	e 5.3
4	21	49	3.0	20	15	.80	51	25	3.4
5	19	39	2.0	17	8	.35	49	20	2.8
6	18	34	1.7	17	5	.25	43	21	2.6
7	17	30	1.4	22	8	.51	39	23	2.4
8	18	53	2.5	20	13	.64	42	23	2.6
9	29	62	4.6	17	27	1.1	44	22	2.6
10	43	101	10	16	18	.77	57	33	7.4
11	21	192	11	14	9	.32	128	82	31
12	18	133	6.1	14	6	.23	161	94	50
13	27	132	9.8	15	6	. 25	167	81	39
14	27	155	11	15	8	.31	224	127	88
15	23	155	10	37	17	2.0	113	74	25
16	43	133	15	33	26	2.6	85	57	14
17	55	194	27	52	64	15	71	48	9.3
18	25	333	21	29	126	9.9	75	42	8.9
19	127	421	146	20	63	3.2	55	38	5.7
20	213	429	258	31	43	4.3	48	33	4.2
21	60	296	55	79	264	107	96	49	19
22	30	98	8.9	29	111	10	116	28	8.7
23	23	25	1.5	832	504	4940	72	53	10
24	19	18	. 87	1930	884	7600	54	79	11
25	18	25	1.2	432	95	128	45	56	7.0
26	17	29	1.4	3380	1350	27000	40	22	2.3
27	16	23	1.0	463	198	276	37	16	1.6
28	16	17	. 69	184	47	27	34	13	1.2
29	16	25	1.0	132	10	3.7	34	13	1.2
30	17	28	1.3	109	9	2.7	34	13	1.1
31				106	9	2.5			
TOTAL	1263		806.66	8142		40143.07	2288		378.6

e Estimated

RIO DE LA PLATA BASIN

50043800 RIO DE LA PLATA AT COMERIO, PR--Continued

SEDIMENT DISCHARGE, SUSPENDED (TONS/DAY), WATER YEAR OCTOBER 1991 TO SEPTEMBER 1992

DAY	MEAN DISCHARGE (CFS)	MBAN CONCEN- TRATION (MG/L)	SEDIMENT DISCHARGE (TONS/DAY)	MEAN Discharge (CFS)	MEAN CONCEN- TRATION (MG/L)	SEDIMENT DISCHARGE (TONS/DAY)	MEAN DISCHARGE (CFS)	MEAN CONCEN- TRATION (MG/L)	SEDIMENT DISCHARGE (TONS/DAY)
		JULY			AUGUST		S	ep tem ber	
1	30	14	1.1	29	10	.77	37	19	1.9
2	28	15	1.1	32	10	.86	37	21	2.1
3	27	16	1.2	35	11	.99	36	22	2.1
4	26	19	1.3	36	11	1.1	38	24	2.4
5	25	24	1.6	55	32	6.5	39	25	2.6
6	25	29	2.0	424	204	332	44	25	2.9
7	25	32	2.2	163	81	41	38	23	2.3
8	25	31	2.1	108	30	9.1	35	21	2.0
9	25	24	1.7	84	19	4.3	37	18	1.9
10	27	20	1.5	75	17	3.3	46	15	1.7
11	27	16	1.2	69	14	2.6	37	14	1.4
12	27	17	1.3	73	13	2.4	34	14	1.3
13	29	19	1.4	69	12	2.2	33	13	1.2
14	28	30	2.2	61	11	1.8	33	13	1.2
15	23	33	2.1	62	11	1.9	33	13	1.2
16	22	16	. 93	63	12	2.0	33	13	1.2
17	25	7	.48	60	12	1.9	45	31	4.4
18	36	8	.77	54	12	1.7	63	44	7.6
19	30	9	.73	51	15	2.0	63	46	9.2
20	25	10	. 66	47	19	2.4	642	193	1360
21	26	8	. 55	46	20	2.5	562	244	434
22	26	7	. 50	45	20	2.3	152	90	43
23	49	33	4.6	41	19	2.1	91	50	13
24	33	20	1.8	40	16	1.7	64	39	6.8
25	28	10	.70	40	12	1.2	52	36	5.0
26	25	7	. 53	40	9	.96	47	33	4.1
27	26	9	. 60	45	8	. 96	44	32	3.7
28	22	10	.60	46	9	1.1	41	30	3.3
29	22	10	. 58	43	66	7.7	39	28	2.9
30	27	10	. 68	41	14	1.6	73	47	13
31	28	10	.76	40	17	1.8			
TOTAL	847		39.47	2117		444.74	2568		1939.4
YBAR	46391		1083424.55						

50043800 RIO DE LA PLATA AT COMERIO, PR--Continued

WATER QUALITY DATA, WATER YEAR OCTOBER 1991 TO SEPTEMBER 1992

PARTICLE-SIZE DISTRIBUTION OF SUSPENDED SEDIMENT

DATE	TIME	DIS- CHARGE, INST. CUBIC FEET PER SECOND	SEDI- MENT, SUS- PENDED (MG/L)	SEDI- MENT, DIS- CHARGE, SUS- PENDED (T/DAY)	SED. SUSP. FALL DIAM. PERCENT FINER THAN .002 MM	SED. SUSP. FALL DIAM. PERCENT FINER THAN .004 MM	SED. SUSP. FALL DIAM. PERCENT FINER THAN .008 MM
JAN 1992							
05	1745	11300	10700	327000	22	32	41
05	1630	6960	23100	434000	15	25	43
APR							
10 May	1630	29	582	46	69	77	81
24	0010	4950	2680	35800	37	39	49
26	0618	10780	6000	175000	23	27	29
DATE	SED. SUSP. FALL DIAM. PERCENT FINER THAN .016 MM	SED. SUSP. FALL DIAM. PERCENT FINER THAN .031 MM	SED. SUSP. SIEVE DIAM. PERCENT FINER THAN .062 MM	SED. SUSP. SIEVE DIAM. PERCENT FINER THAN .125 MM	SED. SUSP. SIEVE DIAM. PERCENT FINER THAN .250 MM	SED. SUSP. SIEVE DIAM. PERCENT FINER THAN .500 MM	SED. SUSP. SIEVE DIAM. PERCENT FINER THAN 1.00 MM
JAN 1992							
05	51	63	77	93	97	99	99.9
05	64	76	90	96	99.8	99.8	99.9
APR 10 MAY			98	98	98	100	100
24		71	92	98	99	100	100
26	36	44	59	73	85	97	99

50043800 RIO DE LA PLATA AT COMERIO--Continued WATER QUALITY DATA, WATER YEAR OCTOBER 1991 TO SEPTEMBER 1992

SILT AND CLAY PERCENT OF SUSPENDED SEDIMENT

DATE	TIME	STREAM- FLOW, INSTAN- TANEOUS (CFS)	SEDI- MENT, SUS- PENDED (MG/L)	SEDI - MENT, DIS - CHARGE, SUS - PENDED (T/DAY)	SED. SUSP. SIEVE DIAM. PERCENT FINER THAN .062 MM
OCT 1991					
03	1733	50	49	6.7	91
31	1905	74	693	138	99
JAN 1992					
05	1550	1700	70100	320000	35
06	2200	2460	762	5060	98
APR					
02	2006	18	545	26	98
13	0800	18	402	19	98
MAY					
23	2020	4310	3530	41000	88
24	0050	4590	2280	28200	95
26	0710	8720	2080	48990	99
JUN					
09	1452	39	153	16	96
JUL					
03	1730	27	327	24	97
AUG					
06	1030	719	1280	2480	97
SEP					
20	2115	570	570	877	98

RIO DE LA PLATA BASIN

50044000 RIO DE LA PLATA NEAR COMERIO, PR

WATER-QUALITY RECORDS

LOCATION.--Lat 18714'33", long 66712'28", at bridge on Highway 156, 0.56 mi (0.9 km) upstream from dam, about 2.0 mi (3.2 km) northeast of Comerio plaza.

DRAINAGE AREA.--139 mi' (360 km'), excludes 8.2 mi' (21.1 km') upstream from Carite Reservoir, the flow of which is diverted to Rio Guamani.

PERIOD OF RECORD. -- Water years 1979 to current year.

DATE	TIME	DIS CHARC INS CUB: FBI PBI SECC	GB, SPE F. CIF IC CON GT DUC R ANC	PIC WHO I- FIE T- (STA EB AF	PER DLE ELD TEN AND- AT RD WA	iper- Ture Ater 3G C)	TUR BII ITY (NTC)- D:	GEN, IS- LVED G/L)	OXYGE DIS SOLV (PER CEN SATU ATIO	- DEMA BD CHE - ICA T (HI R- LEVE	ND, FOR MARKET PROPERTY OF THE	LI- RM, CAL, 45 -MF LS./	STREP- TOCOCCI FECAL, (COLS. PER 100 ML)
OCT 1991 15	1200	26		427	8.5	27.0	6.	.1 :	10.0	12	0	14	540	K100
DEC 10	1300	35		425	8.3	24.5	2.	. 5	9.2	11	0	19	K92	K150
FBB 1992 24	1515	37		420	7.8	25.0	1.	3	8.1	9	8	17	240	310
APR 01	1010	27		431	8.0	26.0	1.	1	8.8	1	08	14	K850	K200
JUN 08	0950	55		389	8.7	27.0	0.	90	9.5	1	02	12	K650	K100
AUG 05	1005	68		372	8.1	27.0	1.		7.4	_	91	16	2800	2600
DATE	NE To ()	ARD- ISS OTAL MG/L AS ACO3)	CALCIUM DIS- SOLVED (MG/L AS CA)	MAGNE- SIUM, DIS- SOLVED (MG/L AS MG)	SODIUM, DIS- SOLVED (MG/L AS NA)	SO T RA'	DIUM AD- RP- ION TIO	POTAS- SIUM, DIS- SOLVED (MG/L AS K)	ALK LINI WAT TOT FIB MG/L CAC	TY WH FET LD AS	SULFIDE TOTAL (MG/L AS S)	SULFATE DIS- SOLVED (MG/L AS SO4)	RI DI SO (M	LO- DB, S- LVED G/L CL)
OCT 1991		350	26	15	26			2.0		F40	-O E	22	2	•
DEC		150	36	15	26		0.9	3.0		540	<0.5	22		0
10 FEB 1992										140				
24 Apr										160				
01 Jun		160	39	16	28		1	4.7		170	<0.5	21	3	7
08 Aug										130				
05		130	32	13	26		1	2.6		120		20	3	0
DATE	R] S((1	LUO- IDB, DIS- DLVED MG/L S F)	SILICA, DIS- SOLVED (MG/L AS SIO2)	SOLIDS, SUM OF CONSTI- TUENTS, DIS- SOLVED (MG/L)	SOLIDS, DIS- SOLVEI (TONS PER DAY)	TOT. AT DEG SU PEN	105 . C, s-	NITRO- GEN, NITRATE TOTAL (MG/L AS N)	NIT GE NITR TOT (MG AS	N, ITB AL /L	NITRO- GEN, NO2+NO3 TOTAL (MG/L AS N)	NITRO- GEN, AMMONIA TOTAL (MG/L AS N)	G ORG TO (M	TRO- EN, ANIC TAL G/L N)
OCT 1991							_		_					
15 DEC		0.10	29	485	34.4		8	0.660		010	0.670	0.040		0.26
10 FEB 1992							35	0.870		010	0.880	0.020		0.28
24 Apr								0.360	0.	010	0.370	0.040		0.26
01 Jun		0.20	20	268	19.5		2			010	0.260	0.020		
0.0		_					•		- 0	010	0 200	0 010		A 10

--

229

--

42

1

--

22

<0.010

<0.010

0.290

0.200

0.010

0.040

0.19

0.36

K = non-ideal count

0.10

24

08...

AUG 05...

RIO DE LA PLATA BASIN
50044000 RIO DE LA PLATA NEAR COMERIO, PR--Continued

WATER-QUALITY DATA, WATER YEAR OCTOBER 1991 TO SEPTEMBER 1992

DATE	NITRO- GEN, AM- MONIA + ORGANIC TOTAL (MG/L AS N)	NITRO- GEN, TOTAL (MG/L AS N)	NITRO- GEN, TOTAL (MG/L AS NO3)	PHOS- PHORUS TOTAL (MG/L AS P)	ARSENIC TOTAL (UG/L AS AS)	BARIUM, TOTAL RECOV- ERABLE (UG/L AS BA)	BORON, TOTAL RECOV- ERABLE (UG/L AS B)	CADMIUM TOTAL RECOV- ERABLE (UG/L AS CD)	CHRO- MIUM, TOTAL RECOV- ERABLE (UG/L AS CR)	COPPER, TOTAL RECOV- ERABLE (UG/L AS CU)
OCT 1991										
15 DBC	0.30	0.97	4.3	0.370	<1	<100	90	<1	<1	<10
10 FEB 1992	0.30	1.2	5.2	0.370						
24 APR	0.30	0.67	3.0	0.210						
01 JUN	<0.20			0.110	1	<100	60	<1	<1	20
08 AUG	0.20	0.49	2.2	0.140						
05	0.40	0.60	2.7	0.290						
DATE	IRON, TOTAL RECOV- ERABLE (UG/L AS FE)	LEAD, TOTAL RECOV- ERABLE (UG/L AS PB)	MANGA- NESE, TOTAL RECOV- ERABLE (UG/L AS MN)	MERCURY TOTAL RECOV- ERABLE (UG/L AS HG)	SELE- NIUM, TOTAL (UG/L AS SE)	SILVER, TOTAL RECOV- ERABLE (UG/L AS AG)	ZINC, TOTAL RECOV- ERABLE (UG/L AS ZN)	CYANIDE TOTAL (MG/L AS CN)	PHENOLS TOTAL (UG/L)	METHY- LENE BLUE ACTIVE SUB- STANCE (MG/L)
OCT 1991 15 DEC	440	1	40	<0.10	<1	<1	<10	<0.010	1	0.04
10 FRB 1992										
24 APR										
01 Jun	170	1	30	<0.10	<1	<1	<10	<0.010	3	0.03
08 AUG										
05										

50044830 RIO GUADIANA AT GUADIANA, PR

LOCATION.--Lat 18°18'08", long 66°13'24", Hydrologic Unit 21010005, at left bank downstream side of river, 1.3 mi (2.1 km) East of Plaza de Naranjito, 0.9 mi (1.4 km) west from intersection of roads 167 and 164 at km 8.9 and 2.9 mi (4.7 km) northwest from Represa Comerio.

DRAINAGE AREA. -- 9.19 mi 2 (23.80 km2).

WATER-DISCHARGE RECORDS

PERIOD OF RECORD. -- July 1990 to current year.

GAGE.--Water-stage recorder and crest-stage gage. Elevation of gage is 230 ft (70 m), from topographic map.

REMARKS.--Records fair except those for estimated daily discharges, which are poor. Gage-height and precipitation satellite telemetry at station.

sacet	TILE COL	emerth #	t station.									
	DI	SCHARGE,	CUBIC FEET		OND, WATER DAILY MEAN		TOBER 199	1 TO SEPTE	MBER 199	2		
DAY	OCT	NOA	DEC	JAN	PEB	MAR	APR	MAY	JUN	JUL	AUG	SEP
1	5.3	17	3.8	3.4	5.1	3.2	6.4	45	9.1	3.2	3.1	3.4
2	5.9	13	4.3	3.4	5.1	3.3	217	66	8.2	3.2	3.3	3.3
3	3.9	9.8	5.0	3.2	15	3.1	22	15	7.8	3.2	3.3	4.5
4	3.8	6.0	7.7	3.2	17	3.7	7.2	8.4	7.8	2.9	19	10
5	5.7	e4.5	8.4	536	9.3	4.0	4.8	6.5	6.8	3.2	78	6.1
6												
7	3.6	7.6	7.2	342	9.4	3.3	5.0	12	6.4	3.0	30	5.3
	19	11	6.4	43	8.4	3.2	7.3	6.8	6.9	3.0	9.4	5.2
8	8.7	12	6.3	17	6.5	16	6.1	5.4	7.4	11	6.7	3.6
9	4.2	8.4	7.4	16	6.1	6.3	e 6.0	4.9	7.1	7.2	8.7	3.2
10	3.7	5.0	6.3	23	6.9	3.8	e 5.0	4.6	7.3	3.9	7.6	3.0
11	3.5	3.9	5.1	13	6.7	3.5	e4 .9	4.4	6.9	3.5	6.0	2.9
12	3.3	3.8	5.7	10	8.9	3.3	e4.8	4.2	6.0	3.5	7.3	2.8
13	3.0	3.2	4.8	23	5.7	3.1	4.7	4.2	5.4	4.4	5.7	2.5
14	3.0	3.3	6.7	13	5.5	3.1	4.6	4.6	5.1	7.0	20	2.5
15	3.0	2.9	4.4	9.9	5.2	3.0	4.3	4.3	5.0	8.8	7.9	2.5
16	3.0	4.7	4.2	81	5.0	2.9	4.3	26	5.2	5.1	6.7	2.6
17	2.6	4.0	3.7	48	4.6	8.3	4.7	7.5	4.8	4.2	5.4	9.4
18	2.9	3.1	3.4	20	4.8	5.3	4.5	29	4.5	3.5	5.2	
19	3.2	3.1	3.1	14	4.8	4.4	4.5	65	4.3	5.5	5.2	3.4 33
20	3.1	3.1	16	11	4.7	3.7	4.4	26	4.1	3.6	5.4	29
21	3.1	5.9	••	••			4.5	c 0			5.0	
22			12	10	5.3	3.3	4.5	60	5.6	3.0		9.3
23	2.8	6.1	6.1	9.5	5.2	6.6	4.1	27	4.1	3.1	4.6	4.7
	2.9	13	4.9	9.2	4.6	3.8	4.0	145	3.9	5.4	4.3	4.1
24	2.6	31	4.2	8.5	4.7	3.4	3.9	130	3.7	12	4.2	3.2
25	2.6	8.0	3.7	8.3	4.3	3.3	3.8	45	3.5	3.9	4.0	3.1
26	2.9	6.8	3.7	8.3	5.0	3.0	3.7	42	3.4	3.5	4.6	2.8
27	2.6	5.1	5.8	7.2	4.2	81	3.7	42	3.4	3.3	4.2	2.5
28	3.6	3.9	4.5	6.9	3.8	197	3.4	23	3.4	3.3	3.7	2.5
29	8.6	5.8	4.0	6.5	3.6	17	21	15	3.2	3.3	3.4	2.7
30	9.2	4.6	3.6	5.6		4.6	16	12	3.3	3.0	3.4	3.1
31	4.4		3.4	5.5		12		9.6		3.0	3.7	
TOTAL	139.7	219.6	175.8	1318.6	185.4	425.5	400.6	900.4	163.6	139.7	289.2	176.2
MEAN	4.51	7.32	5.67	42.5	6.39	13.7	13.4	29.0	5.45	4.51	9.33	5.87
MAX	19	31	16	536	17	197	217	145	9.1	12	78	33
MIN	2.6	2.9	3.1	3.2	3.6	2.9	3.4	4.2	3.2	2.9	3.1	2.5
AC-FT	277	436	349	2620	368	844	795	1790	325	277	574	349
CFSM	.49	. 80	. 62	4.63	.70	1.49	1.45	3.16	.59	.49	1.02	. 64
IN.	. 57	. 89	.71	5.34	.75	1.72	1.62	3.64	.66	.57	1.17	.71
e Br	stimated											
OT LTT OF	TTCG OF M	OMBET V M	BAN DATA PO			- 1902	DV WIMED	V010 /WV				
DINITO	IICS OF M	ONINDI E	PUM DUIV E	N WAIRK	EARS 1990	- 1992,	DI WATER	IBAR (WI	1			
MBAN	51.6	10.7	12.7	28.9	18.8	13.3	12.5	18.3	5.33	9.25	7.22	8.65
MAX	98.7	14.1	19.7	42.5	31.7	13.7	13.4	29.0	5.45	14.0	9.33	16.1
(WY)	1991	1991	1991	1992	1991	1992	1992	1992	1992	1991	1992	1990
MIN	4.51	7.32	5.67	15.2	6.39	12.9	11.6	7.49	5.21	4.51	5.76	3.95
(WY)	1992	1992	1992	1991	1992	1991	1991	1991	1991	1992	1991	1991
SUMMARY	Y STATIST	ICS	FOR :	1991 CALEI	MDAR YEAR	1	OR 1992 W	ATER YEAR		WATER Y	EARS 1990	- 1992
ANNUAL	TOTAL			3757.4			4534.3					
	T ANNUAL			10.3			12.4			16.2 20.0		1991
	ANNUAL M DAILY M			225	Bak "		F3.	7		12.4		1992
	DAILY MR			335	Feb 5 Jun 27		536	Jan 5 Sep 13		536		5 1992
			n.c	2.6						2.5		13 1992
	SEVEN-DA			2.8	Oct 21		2.7			2.7		10 1992
	l'anbous p L'anbous p						6670			6670		5 1992
								6 Jan 5		13.3	o Jan	5 1992
	RUNOFF (7450			8990			11750	-	
	RUNOFF (1.1			1.3			1.7		
	RUNOFF (15.2	L		18.3	3		23.9	,	
	CENT BXCE			18			17			25		
	CENT BYCE			5.9			4.8			6.5		
JU PERC	CENT EXCE	272		3.0			3.1			3.2		

50044830 RIO GUADIANA AT GUADIANA, PR--Continued

WATER-QUALITY RECORDS

PERIOD OF RECORDS. -- Water years 1990 to current year.

INSTRUMENTATION .-- USD-77 and automatic sediment sampler.

PERIOD OF DAILY RECORD.--SUSPENDED-SEDIMENT DISCHARGE: August 01, 1990 to September 1992

EXTREMES FOR PERIOD OF DAILY RECORD.-SEDIMENT CONCENTRATION: Maximum daily mean, 1,300 mg/L Oct. 16, 1990; Minimum daily mean, 2 mg/L few days.

SEDIMENT LOADS: Maximum daily mean, 18,000tons (16,300tonnes) Jan. 05, 1992; Minimum daily mean, 0.00 ton (0.0 tonne) several days.

EXTREMES FOR WATER YEARS 1990-92.--

Water Year	Suspended-sediment meximum	concentration (mg/L) minimum	Suspended-sediment discharge maximum	(tons per day) minimum
1990	259 (Sep. 25)	2 (Aug. 20)	185 (Sep. 03)	.05 (Aug. 04)
1991	1,430 (Feb. 05)	1 (Several days)	8.650 (Feb. 05)	.00 (Several days)
1992	2,690 (Jan. 05)	2 (Several days)	18,000 (Jan. 05)	.02 (Several days)

SEDIMENT DISCHARGE, SUSPENDED (TONS/DAY), WATER YEAR OCTOBER 1989 TO SEPTEMBER 1990

	MBAN				MRAN		MEAN			
	MRAN	CONCEN-	SEDIMENT	Mean	CONCEN-	Sediment	mran	CONCEN-	SEDIMENT	
	DISCHARGE	TRATION	DISCHARGE	DISCHARGE	TRATION	DISCHARGE	DISCHARGE	TRATION	DISCHARGE	
DAY	(CFS)	(MG/L)	(TONS/DAY)	(CFS)	(MG/L)	(TONS/DAY)	(CFS)	(MG/L)	(TONS/DAY)	
		MLY			August		Si	PTEMBER		
1				e4.1	6	e.06	6.6	11	.31	
2				e5.8	9	e.18	5.7	8	.15	
3				e5.4	6	e.08	66	231	185	
4				e4.3	5	e.05	22	50	5.3	
5				e5.0	5	e.08	38	115	49	
•				63.0	-	4.00	30			
6				e6.8	9	e.16	15	31	1.7	
7				e8.8	13	e.30	59	188	114	
8				e6.2	9	e.16	28	62	6.1	
9				e6.0	9	e.14	13	28	1.0	
10				e8.2	12	e.26	9.8	17	.47	
11				e6.4	7	e.12	13	26	2.0	
12				e7.0	10	e.18	8.4	14	. 34	
13				e10	17	e.46	7.3	10	.20	
14				9.0	15	.36	30	72	17	
15				6.0	9	.14	14	25	1.0	
16				5.1	6	.08	8.6	14	.33	
17				4.6	6	.08	7.2	10	. 17	
18				4.6	6	.07	13	27	2.8	
19				4.2	6	.06	8.4	15	.38	
20				4.2	š	.06	7.0	10	.16	
					•					
21				4.0	5	.06	6.5	10	. 16	
22				5.8	7	.12	6.7	10	. 16	
23				4.9	7	.10	14	27	2.0	
24				4.3	6	. 07	7.9	13	. 29	
25				6.2	11	.30	23	63	25	
26				4.5	6	.07	11	21	.77	
27				4.1	5	.06	9.2	17	. 56	
28				24	69	30	8.2	15	. 34	
29				14	74	3.6	8.5	12	.27	
30				5.5	20	.31	8.5	14	.41	
31				4.8	8	.10				
TOTAL				203.8		37.87	483.5		417.37	

e Estimated

RIO DE LA PLATA BASIN

50044830 RIO GUADIANA AT GUADIANA, PR--Continued

SEDIMENT DISCHARGE, SUSPENDED (TONS/DAY), WATER YEAR OCTOBER 1990 TO SEPTEMBER 1991

DAY	MEAN DISCHARGE (CFS)	MEAN CONCEN- TRATION (MG/L)	SEDIMENT DISCHARGE (TONS/DAY)	MEAN DISCHARGE (CFS)	MRAN CONCEN- TRATION (MG/L)	SEDIMENT DISCHARGE (TONS/DAY)	MRAN DISCHARGE (CFS)	MEAN CONCEN- TRATION (MG/L)	SEDIMENT DISCHARGE (TONS/DAY)
		OCTOBER		1	OVEMBER		1	DECEMBER	
1	7.9	13	.31	16	5	.24	25	55	4.3
2	5.7	8	. 12	15	4	.18	38	98	19
3	15	62	3.7	15	4	.16	105	281	147
4	56	156	38	16	4	.17	40	22	2.8
5	33	75	7.7	15	4	.17	21	11	.70
6	19	36	1.9	14	4	.17	16	7	.30
7	108	430	599	13	5	.18	14	5	.20
8	46	94	16	13	4	.14	13	4	. 15
9	194	790	2080	13	3	.10	12	4	. 12
10	186	699	906	12	3	.10	12	4	. 12
11	68	211	47	12	3	.11	12	4	. 14
12	30	68	6.3	12	4	.12	14	6	.20
13	20	38	2.1	11	ā	.12	11	8	.27
14	146	593	1100	11	4	.11	11	10	.28
15	234	955	2750	10	4	.12	11	10	.28
16	225	900	2070	13	5	.17	10	9	.24
17	208	828	1490	11	5 5	.15	9.5	8	.22
18	306	1250	3370	11	5	.14	9.4	7	.17
19	281	1160	2060	11	5	.15	9.3	5	. 12
20	102	218	88	12	12	.53	9.3	3	.09
21	322	1090	1430	12	23	.80	9.3	3	.08
22	81	59	15	27	56	5.4	11	5	. 14
23	44	35	4.2	14	16	.61	13	6	.21
24	38	42	7.4	11	8	.26	13	6	.22
25	73	265	245	10	7	.19	9.9	7	.19
26	87	255	114	11	7	.19	9.2	6	. 15
27	40	65	8.3	14	20	.93	9.2	5	. 12
28	27	20	1.6	11	8	.26	10	5	.13
29	22	8	.49	33	93	46	18	39	5.6
30	19	6	.32	25	56	4.9	42	116	28
31	17	6	.29				66	157	41
TOTAL	3060.6		18462.73	424		62.87	613.1		252.54

RIO DE LA PLATA BASIN

50044830 RIO GUADIANA AT GUADIANA, PR--Continued

SEDIMENT DISCHARGE, SUSPENDED (TONS/DAY), WATER YEAR OCTOBER 1990 TO SEPTEMBER 1991

DAY	MEAN DISCHARGE (CFS)	CONCEN- TRATION (MG/L) JANUARY	SEDIMENT DISCHARGE (TONS/DAY)	MEAN DISCHARGE (CFS)	CONCEN- TRATION	SEDIMENT DISCHARGE	MBAN DISCHARGB	CONCEN- TRATION	SEDIMENT DISCHARGE
1		(MG/L)				DISCHARGE	DISCHARGE	TOATION	DISCHARGE
1		(MG/L)							
			•		(MG/L)	(TONS/DAY)	(CFS)	(MG/L)	(TONS/DAY)
		TARMITON				•	•		
		UANUARI		1	FBBRUARY			MARCH	
2	58	158	28	9.6	12	.29	11	13	.39
	29	36	3.1	8.5	12	.26	11	6	. 18
3	19	20	1.0	8.3	12	.25	10	5	. 14
4	15	20	. 81	23	60	18	12	4	. 12
5	21	42	4.8	335	1430	8650	10	5	. 13
6	25	55	3.7	58	164	37	11	4	.11
7	21	41	2.4	23	37	2.6	11	2	. 05
8	18	22	1.0	16	15	. 67	10	3	. 09
9	19	15	.71	14	11	.39	9.5	5	. 12
10	20	15	.81	15	20	1.1	9.1	5	. 13
11	18	12	. 59	14	24	.88	10	7	. 17
12	16	7	.28	17	32	2.3	8.8	7	. 18
13	14	5	.19	18	38	2.0	9.2	Ź	.17
14	13	6	.20	14	22	.84	8.9	Ś	.11
15	12	10	.34	12	10	.31	8.1	3	. 07
								_	
16	12	12	.40	13	11	.54	7.3	3	.06
17	11	9	.27	12	22	.72	7.2	3	.07
18	11	4	. 13	45	136	58	10	14	. 43
19	11	4	. 11	59	166	34	7.6	4	.10
20	10	4	.11	44	127	18	7.0	4	.08
21	9.7	5	. 12	30	61	6.2	8.1	6	. 14
22	9.2	5	. 12	20	18	.97	101	346	158
23	9.5	7	. 18	16	9	.38	24	47	4.4
24	8.9	12	.29	14	6	.23	12	6	.22
25	8.9	16	. 37	12	5	.16	9.7	6	. 17
26	8.9	16	. 38	11	5	.15	11	13	. 64
27	8.6	13	. 29	11	5	.16	12	11	. 42
28	7.9	8	. 18	14	19	1.5	9.3	5	. 14
29	7.9	7	.15				8.3	4	.09
30	7.9	ģ	. 18				7.9	ā	. 09
31	10	10	. 29				7.6	2	. 05
TOTAL	470.4		51.50	886.4		8837.90	399.6		167.26

RIO DE LA PLATA BASIN
50044830 RIO GUADIANA AT GUADIANA, PR--Continued

SEDIMENT DISCHARGE, SUSPENDED (TONS/DAY), WATER YEAR OCTOBER 1990 TO SEPTEMBER 1991

DAY	MRAN DISCHARGE (CFS)	MEAN CONCEN- TRATION (MG/L)	SEDIMENT DISCHARGE (TONS/DAY)	MEAN DISCHARGE (CFS)	MEAN CONCEN- TRATION (MG/L)	SEDIMENT DISCHARGE (TONS/DAY)	MRAN DI SCHARGE (CFS)	MEAN CONCEN- TRATION (MG/L)	SEDIMENT DISCHARGE (TONS/DAY)
		APRIL			MAY			JUNE	
1	7.6	4	.08	5.8	9	.14	5.1	8	. 12
2	8.7	7	. 16	7.2	13	.28	3.9	8	.08
3	7.5	6	.11	7.1	9	.19	3.6	8	. 08
4	7.1	5	. 09	6.0	6	.11	3.6	7	. 07
5	7.1	5	.10	5.9	6	.10	3.5	7	.06
6	7.0	5	.09	5.9	6	.10	3.8	8	. 07
7	9.1	14	.42	7.6	10	.28	3.7	10	.09
8	21	21	1.3	19	43	4.6	3.3	7	.06
9	11	15	. 47	9.5	72	2.6	3.1	4	.03
10	8.9	15	.36	7.1	8	.14	3.0	4	.04
11	10	16	.41	7.6	9	,28	3.0	4	.02
12	16	35	3.7	11	12	.47	3.0	3	. 03
13	24	57	7.1	11	15	.88	2.8	3	. 02
14	19	47	4.5	9.7	16	.45	2.8	4	.03
15	56	379	292	7.1	14	.25	2.8	6	.05
16	18	38	2.1	6.1	15	.23	2.7	10	. 07
17	12	21	.68	5.7	15	.22	2.7	ĩi	. 07
18	11	17	.48	6.8	14	.25	3.0	13	. 09
19	9.6	14	. 34	9.5	23	.68	3.3	15	. 13
20	8.6	12	.26	7.6	17	.36	3.2	15	. 13
21	8.0	11	.22	5.8	16	.25	3.1	12	.10
22	7.7	7	. 15	5.1	16	.21	3.1	7	.06
23	7.4	5	.10	4.8	11	.15	29	389	184
24	6.9	5	.09	4.8	8	.11	4.4	17	.21
25	6.7	6	.10	18	40	5.4	3.3	17	. 16
26	6.5	7	. 13	5.9	8	.13	2.8	19	. 15
27	6.4	8	. 13	4.9	6	.09	2.6	20	. 14
28	6.3	ž	.13	4.5	5	.07	2.6	15	.11
29	5.8	'n	.11	4.3	5	.06	7.5	16	.90
30	5.8	8	, 12	5.7	9	.26	32	94	30
31				5.2	ž	.10			
TOTAL	346.7		316.03	232.2		19.44	156.3		217.17

RIO DE LA PLATA BASIN

50044830 RIO GUADIANA AT GUADIANA, PR--Continued

SEDIMENT DISCHARGE, SUSPENDED (TONS/DAY), WATER YEAR OCTOBER 1990 TO SEPTEMBER 1991

DAY	MRAN DISCHARGE (CFS)	MEAN CONCEN- TRATION (MG/L)	SEDIMENT DISCHARGE (TONS/DAY)	MEAN DISCHARGE (CFS)	MRAN CONCEN- TRATION (MG/L)	SEDIMENT DISCHARGE (TONS/DAY)	MRAN Discharge (CFS)	MEAN CONCEN- TRATION (MG/L)	SEDIMENT DISCHARGE (TONS/DAY)
		JULY			august		SI	RPTEMBER	
1 2 3 4 5	6.4 3.7 4.6 4.0 3.3	16 12 10 13 13	.31 .12 .13 .13 .11	7.1 5.1 4.4 4.1 4.0	11 5 5 4 3	.27 .06 .06 .05 .03	3.5 3.6 3.2 3.0 3.1	2 3 2 1 1	.02 .02 .01 .00 .00
7 8 9 10	7.4 4.4 3.2 2.9	20 10 11 11	.57 .12 .09 .08	3.8 4.1 3.7 3.5	1 1 1	.01 .01 .01 .00	3.5 3.1 3.0 3.0	1 1 1	.01 .00 .00 .00
11 12 13 14 15	3.0 2.9 2.9 2.7 27	9 9 8 8 78	.08 .08 .07 .06	3.5 3.6 3.7 e3.6 e3.4	1 1 1 1	.00 .00 .00 e.01 e.00	2.8 6.9 3.7 2.9 2.7	2 12 7 5	.01 .79 .08 .05
16 17 18 19 20	250 22 9.0 6.5 5.3	1010 55 15 12 12	2010 4.5 .40 .24 .16	e3.9 4.6 4.0 3.2 3.7	1 1 1 1 17	e.01 .01 .01 .00	3.3 6.8 4.0 3.3 3.3	3 11 4 3 2	.03 .28 .04 .02
21 22 23 24 25	4.7 4.4 4.1 4.3 3.9	10 8 5 5 5	.12 .09 .05 .05	3.5 41 9.6 5.1 4.4	20 147 79 10 1	.19 92 2.4 .15 .02	3.3 4.8 5.2 3.9 3.4	2 2 2 2 2	.02 .02 .04 .02
26 27 28 29 30 31	4.0 4.2 4.5 4.0 4.2	5 5 5 5 5	.06 .05 .06 .05 .05	4.1 11 6.7 4.6 4.0 3.9	1 21 9 3 2 2	.01 1.2 .19 .04 .02	3.3 3.3 3.2 4.3	2 4 12 15 34	.01 .03 .10 .18 5.6
TOTAL YBAR	433.5 7320.0		2056.00 30547.92	178.7		97.03	118.5		7.45

RIO DE LA PLATA BASIN 50044830 RIO GUADIANA AT GUADIANA, PR--Continued SEDIMENT DISCHARGE, SUSPENDED (TONS/DAY), WATER YEAR OCTOBER 1991 TO SEPTEMBER 1992

DAY	MEAN DISCHARGE (CFS)	MEAN CONCEN- TRATION (MG/L)	SEDIMENT DISCHARGE (TONS/DAY)	MEAN DISCHARGE (CFS)	MRAN CONCEN- TRATION (MG/L)	SEDIMENT DISCHARGE (TONS/DAY)	MEAN DISCHARGE (CFS)	MEAN CONCEN- TRATION (MG/L)	SEDIMENT DISCHARGE (TONS/DAY)
		OCTOBER		1	NOVEMBER		1	DECEMBER	
1	5.3	12	.20	17	69	13	3.8	20	.20
2	5.9	14	. 25	13	104	3.7	4.3	16	. 17
3	3.9	7	.09	9.8	79	2.3	5.0	11	. 14
4	3.8	8	.09	6.0	38	. 64	7.7	8	. 16
5	5.7	12	. 19	e4. 5	22	e.27	8.4	8	. 17
6	3.6	12	.11	7.6	23	.48	7.2	8	. 15
7	19	79	15	11	21	. 65	6.4	8	. 13
8	8.7	124	3.5	12	13	.40	6.3	8	. 14
9	4.2	48	.54	8.4	17	.39	7.4	8	. 15
10	3.7	104	1.2	5.0	14	.22	6.3	7	. 13
11	3.5	13	. 12	3.9	10	.11	5.1	5	.06
12	3.3	10	. 09	3.8	10	.09	5.7	5	.09
13	3.0	10	. 07	3. 2	10	.09	4.8	5	. 07
14	3.0	10	.08	3.3	8	.08	6.7	5	. 09
15	3.0	10	.08	2.9	8	.06	4.4	5	.06
16	3.0	10	.08	4.7	8	.10	4.2	5	.06
17	2.6	10	. 07	4.0	8	.09	3.7	5	. 05
18	2.9	10	. 07	3.1	7	.07	3.4	5	. 04
19	3.2	10	.08	3.1	8	.07	3.1	5	. 04
20	3.1	8	. 07	3.1	10	.08	16	57	8.6
21	3.1	8	.06	5.9	17	. 68	12	30	1.3
22	2.8	9	.06	6.1	14	.30	6.1	5	.08
23	2.9	10	.08	13	49	5.2	4.9	5	.06
24	2.6	10	. 07	31	85	13	4.2	5	. 06
25	2.6	15	.10	8.0	14	.30	3.7	5	. 05
26	2.9	19	. 15	6.8	12	.22	3.7	5	. 05
27	2.6	17	. 12	5.1	12	.15	5.8	5	.08
28	3.6	11	. 13	3.9	11	.11	4.5	5	. 06
29	8.6	25	2.1	5.8	16	.50	4.0	5	. 05
30	9.2	33	1.2	4.6	18	.24	3.6	5	. 04
31	4.4	12	. 14				3.4	5	. 05
TOTAL	139.7		26.19	219.6		43.59	175.8		12.58

e Estimated

RIO DE LA PLATA BASIN 50044830 RIO GUADIANA AT GUADIANA, PR--Continued

SEDIMENT DISCHARGE, SUSPENDED (TONS/DAY), WATER YEAR OCTOBER 1991 TO SEPTEMBER 1992

		MBAN			MRAN			MRAN	
DAY	MEAN DISCHARGE (CFS)	CONCEN- TRATION (MG/L)	SEDIMENT DISCHARGE (TONS/DAY)	MEAN Discharge (CFS)	CONCEN- TRATION (MG/L)	SEDIMENT DISCHARGE (TONS/DAY)	MEAN DISCHARGE (CFS)	CONCEN- TRATION (MG/L)	SEDIMENT DISCHARGE (TONS/DAY)
	(5.5)	JANUARY	(101,0,011)		BBRUARY	(2010,2111,	(012)	MARCH	,,
1	3.4	5	. 05	5.1	21	.27	3.2	5	. 05
2	3.4	5	.04	5.1	19	.24	3.3	3	. 02
3	3.2	5	.04	15	47	7.3	3.1	3	.02
4	3.2	5	.04	17	55	3.3	3.7	3	. 03
5	536	2690	18000	9.3	20	.55	4.0	7	.08
6	342	1800	2710	9.4	6	.14	3.3	28	. 22
7	43	148	21	8.4	6	.13	3.2	53	.42
8	17	43	1.9	6.5	10	.18	16	111	20
9	16	59	3.5	6.1	9	.14	6.3	88	1.8
10	23	66	5.3	6.9	8	.14	3.8	26	.28
11	13	22	.75	6.7	13	.32	3.5	6	.06
12	10	22	.58	8.9	15	.50	3.3	2	. 02
13	23	70	5.1	5.7	5	.07	3.1	2	.02
14	13	35	1.3	5.5	5	.06	3.1	2	. 02
15	9.9	24	. 64	5.2	5	.06	3.0	3	. 02
16	81	594	663	5.0	5	.07	2.9	3	.03
17	48	182	33	4.6	4	.04	8.3	15	.74
18	20	42	2.3	4.8	4	.05	5.3	8	. 12
19	14	17	. 63	4.8	7	.10	4.4	5	.06
20	11	10	.28	4.7	6	.08	3.7	3	.03
21	10	10	. 25	5.3	4	.06	3.3	2	. 02
22	9.5	10	.25	5.2	7	.09	6.6	13	.31
23	9.2	10	.27	4.6	9	.11	3.8	10	. 09
24	8.5	10	. 23	4.7	10	.11	3.4	9	. 08
25	8.3	10	.22	4.3	7	.08	3.3	6	. 06
26	8.3	10	.22	5.0	6	.09	3.0	4	. 04
27	7.2	10	.20	4.2	7	.08	81	416	659
28	6.9	12	.20	3.8	8	.08	197	914	4580
29	6.5	16	.28	3.6	8	.08	17	77	5.0
30	5.6	20	.28				4.6	9	. 12
31	5.5	21	.31				12	42	4.8
TOTAL	1318.6		21452.16	185.4		14.52	425.5		5273.56

RIO DE LA PLATA BASIN

50044830 RIO GUADIANA AT GUADIANA, PR--Continued

SEDIMENT DISCHARGE, SUSPENDED (TONS/DAY), WATER YEAR OCTOBER 1991 TO SEPTEMBER 1992

		MEAN			MEAN			MRAN	
DAY	MEAN DISCHARGE (CFS)	CONCEN- TRATION (MG/L)	SEDIMENT DISCHARGE (TONS/DAY)	MBAN Discharge (CFS)	CONCEN- TRATION (MG/L)	SEDIMENT DI SCHARGE (TONS/DAY)	MEAN DISCHARGE (CFS)	CONCEN- TRATION (MG/L)	SEDIMENT DISCHARGE (TONS/DAY)
	(355)	APRIL	(100.0, 1.1.1,	(512)	MAY	(10110)	(512)	JUNE	(22)
						25			
1	6.4	15	.28	45	191	85	9.1	2	. 04
2	217	1070	4200	66	109	38	8.2	3	. 07
3	22	99	6.1	15	12	.51	7.8	7	.15
4	7.2	26	. 55	8.4	12	.27	7.8	10	.20
5	4.8	15	.18	6.5	12	.20	6.8	6	.11
6	5.0	15	.22	12	35	1.5	6.4	5	.09
7	7.3	15	. 27	6.8	9	.17	6.9	5	.10
8	6.1	14	.24	5.4	6	.09	7.4	5	.10
9	e 6.0	14	e.22	4.9	3	.04	7.1	5	.10
10	e 5.0	13	e. 17	4.6	2	.02	7.3	5	.10
11	e4.9	11	e. 15	4.4	2	.02	6.9	5	. 09
12	e4 .8	8	e.11	4.2	2	.02	6.0	5	.08
13	4.7	5	. 07	4.2	2	.02	5.4	6	.08
14	4.6	4	. 05	4.6	2	. 03	5.1	8	. 11
15	4.3	4	.06	4.3	4	.05	5.0	10	. 13
16	4.3	5	.06	26	99	30	5.2	11	. 14
17	4.7	5	. 06	7.5	19	.45	4.8	9	. 11
18	4.5	5	. 06	29	112	23	4.5	7	.08
19	4.5	4	. 05	65	300	256	4.3	6	.06
20	4.4	3	. 04	26	79	6.8	4.1	6	.07
21	4.5	5	. 06	60	263	133	5.6	17	.36
22	4.1	5	.06	27	90	9.0	4.1	8	.08
23	4.0	6	.06	145	552	702	3.9	ž	.08
24	3.9	Š	. 05	130	241	110	3.7	é	.08
25	3.8	5	. 04	45	125	16	3.5	12	.11
26	3.7	7	. 07	42	143	18	3.4	18	.16
27	3.7	8	.08	42	110	14	3.4	15	.13
28	3.4	11	.09			6.7	3.4	9	.09
29				23	110				
	21	83	23	15	105	4.3	3.2	6	. 05
30	16	91	6.1	12	46	1.5	3.3	5	.04
31				9.6	6	.15			
TOTAL	400.6		4238.55	900.4		1456.84	163.6		3.19

e Estimated

RIO DE LA PLATA BASIN

50044830 RIO GUADIANA AT GUADIANA, PR--Continued

SEDIMENT DISCHARGE, SUSPENDED (TONS/DAY), WATER YEAR OCTOBER 1991 TO SEPTEMBER 1992

	Mean				MBAN		MRAN		
DAY	MEAN DISCHARGE (CFS)	CONCEN- TRATION (MG/L)	SEDIMENT DISCHARGE (TONS/DAY)	MEAN Discharge (CFS)	CONCEN- TRATION (MG/L)	SEDIMENT DISCHARGE (TONS/DAY)	MEAN DISCHARGE (CFS)	CONCEN- TRATION (MG/L)	SEDIMENT DISCHARGE (TONS/DAY)
		JULY			august		SI	ep tembe r	
1	3.2	5	. 04	3.1	4	.03	3.4	10	· .09
2	3.2	5	.04	3.3	5	.07	3.3	10	. 09
3	3.2	6	. 05	3.3	6	.06	4.5	14	.17
4	2.9	6	.04	19	67	11	10	27	1.7
5	3.2	6	.05	78	614	534	6.1	14	.26
6	3.0	6	. 05	30	522	77	5.3	11	.18
7	3.0	6	.04	9.4	12	.30	5.2	14	. 32
8	11	32	1.8	6.7	6	.12	3.6	8	.08
9	7.2	17	.38	8.7	18	. 65	3.2	5	. 05
10	3.9	7	.09	7.6	18	.44	3.0	3	. 03
11	3.5	7	- 07	6.0	11	.19	2.9	3	. 02
12	3.5	7	.06	7.3	14	.38	2.8	2	. 02
13	4.4	8	.09	5.7	11	.17	2.5	2	. 02
14	7.0	15	.49	20	67	14	2.5	3	.02
15	8.8	22	. 91	7.9	16	.42	2.5	6	.04
16	5.1	11	. 18	6.7	10	.17	2.6	8	.05
17	4.2	8	. 09	5.4	10	.13	9.4	31	3.6
18	3.5	7	. 07	5.2	9	.12	3.4	6	. 07
19	5.5	15	.51	5.2	8	.11	33	134	37
20	3.6	17	. 17	5.6	8	.13	29	126	27
21	3.0	11	.08	5.0	7	.09	9.3	29	1.2
22	3.1	7	. 05	4.6	4	.06	4.7	14	.21
23	5.4	13	. 42	4.3	3	.04	4.1	14	.16
24	12	34	2.6	4.2	3	.04	3. 2	12	. 12
25	3.9	6	.06	4.0	3	.04	3.1	12	.11
26	3.5	5	.04	4.6	9	.16	2.8	10	.08
27	3.3	4	. 03	4.2	5	.05	2.5	7	.05
28	3.3	3	. 02	3.7	6	.06	2.5	5	.04
29	3.3	3	. 03	3.4	8	.07	2.7	5	.04
30	3.0	3	. 03	3.4	8	.07	3.1	5	.04
31	3.0	3	. 03	3.7	8	.08			
TOTAL	139.7		8.61	289.2		640.25	176.2		72.86
YEAR	4534.3		33242.90						

50044830 RIO GUADIANA AT GUADIANA , PR--Continued

WATER QUALITY DATA, WATER YEARS OCTOBER 1990 TO SEPTEMBER 1992

PARTICLE-SIZE DISTRIBUTION OF SUSPENDED SEDIMENT

DATE	TIMB	DIS- CHARGE, INST. CUBIC FERT PER SECOND	SEDI - MENT, SUS- PENDED (MG/L)	SEDI- MENT, DIS- CHARGE, SUS- PENDED (T/DAY)	SED. SUSP. FALL DIAM. PERCENT FINER THAN .002 MM	SED. SUSP. FALL DIAM. PERCENT FINER THAN .004 MM	SED. SUSP. FALL DIAM. PERCENT FINER THAN .008 MM
OCT 1990							
17	1601	704	3370	6400	33	38	46
APR 1991	4045			F000		• •	
15 Jun	1317	403	4940	5370	26	36	46
23	1015	208	4920	2760	40	52	61
JAN 1992	1015	200	4320	2,00	••	32	01
05	1727	1190	7370	23700	17	23	31
05	1917	1850	8200	41000	21	28	37
16	1832	512	3840	5310	25	36	41
MAY	4.050					_	_
23 AUG	1852	578	3030	4730	1	3	6
05	2127	344	3860	3580	35	44	54
	SED.	SED.	SED.	SED.	SED.	SED.	SED.
	SUSP.	SUSP.	SUSP.	SUSP.	SUSP.	SUSP.	SUSP.
	PALL	FALL	SIEVE	SIEVE	SIEVE	SIEVE	SIEVE
	DIAM.	DIAM.	DIAM.	DIAM.	DIAM.	DIAM.	DIAM.
	PERCENT	PERCENT	PERCENT	PERCENT	PERCENT	PERCENT	PERCENT
	FINER	FINER	PINER	FINER	PINER	PINER	FINER
DATE	THAN .016 MM	THAN .031 MM	THAN	THAN .125 MM	THAN	THAN .500 MM	THAN 1.00 MM
	. UIU FAFE	.VJI MM	. VOZ FAM	. Is J mm	.ajv ma	.500 AA	1.00 22
OCT 1990							
17	56	67	82	91	978	99.4	100
APR 1991							
15	60	68	86	94	96	97	98
JUN 23	74	0.5	96	98	99	99.6	100
JAN 1992	/4	86	30	36	33	99.0	100
05	39	47	60	72	79	87	94
05	46	53	66	75	84	94	99
16	55	65	84	90	93	98	99
MAY						_	
23	15	24	63	51	67	83	95
AUG							
05	68	78	95	98	99	99.7	100

50044830 RIO GUADIANA AT GUADIANA, PR--Continued WATER QUALITY DATA, WATER YEAR OCTOBER 1991 TO SEPTEMBER 1992 SILT AND CLAY PERCENT OF SUSPENDED SEDIMENT

DATE	TIME	STREAM- FLOW, INSTAN- TANEOUS (CFS)	SEDI- MENT, SUS- PENDED (MG/L)	SEDI- MENT, DIS- CHARGE, SUS- PENDED (T/DAY)	SED. SUSP. SIEVE DIAM. PERCENT FINER THAN .062 MM
OCT 1991					
08 NOV	1500	6.4	113	2	100
06 DEC	1215	7.8	55	1.2	98
17	1152	3.6	23	0.2	96
JAN 1992					
05	1607	423	3500	4000	96
05	1657	562	4250	6450	91
16	1917	500	2560	3460	89
16	2127	205	1140	633	91
MAR					
31	1805	45	779	95	62
MAY					
21	1830	126	929	316	94
23	1827	400	2940	3170	60
23	2222	342	1030	956	81
JUL					
08 Aug	1635	20	91	5	94
05 SEP	2027	443	4540	5430	94
17	1620	11	270	8	98

50044850 RIO GUADIANA NEAR NARANJITO, PR

WATER-QUALITY RECORDS

LOCATION.--Lat 18°18'39", long 66°13'28", at steel-cross-bridge 0.8 mi (1.3 km) northwest of Highway 164, 1.2 mi (1.9 km) upstream from mouth and about 2.0 mi (3.2 km) northeast of Naranjito plaza.

DRAINAGE AREA. -- 4.0 mi 2 (10.3 km²).

PERIOD OF RECORD. -- Water year 1979 to current year.

WATER-QUALITY DATA, WATER YEAR OCTOBER 1991 TO SEPTEMBER 1992

		WATE	SK-OOYTITY	DATA, WA	TER YEAR	OCTOB	KK 1991 T	O SELLEME	IEK 1997	2		
DATE	TIME	DIS- CHARGE, INST. CUBIC FEST PER SECOND	SPE- CIFIC CON- DUCT- ANCE (US/CM)	PH WATER WHOLE FIBLD (STAND- ARD UNITS)	TEMPER- ATURE WATER (DEG C)	BI IT	D- DI Y S OL	SOI EN, (PE S- CE VED SAT	S- DI VBD (IR- : INT UR- LI	XYGEN EMAND, CHEM- ICAL (HIGH EVEL) MG/L)	COLI- FORM, FECAL, 0.45 UM-MF (COLS./ 100 ML)	STREP- TOCOCCI FECAL, (COLS. PER 100 ML)
OCT 1991												
15	0930	3.7	384	8.0	24.5	1	.7	7.6 8	3	12	K1800	K1300
10 PEB 1992	1100	6.5	374	8.1	23.0	2	. 6	8.2 9	8	<10	700	940
25 APR	0945	4.9	315	8.1	22.5	0	.50	7.0 7	7	12	190	470
01 JUN	0840	12	299	7.5	22.5	25		8.8 10	1	22	K7300	5500
08	0810	17	364	8.0	24.5	0	. 80	8.0 9	4	10	K910	2300
05	0820	19	250	7.4	25.0	17		6.0	1	27	2000	52000
DATE	HARD- NESS TOTAL (MG/L AS CACO3)	HARD- NESS NONCARB WH WAT TOT FLD MG/L AS CACO3	CALCIUM DIS- SOLVED (MG/L AS CA)	MAGNE- SIUM, DIS- SOLVED (MG/L AS MG)	SODIUM, DIS- SOLVED (MG/L AS NA)	SOR TI RAT	D- SI P- DI ON SOL	UM, WAT S- TOT VED FIE /L MG/I	TY WH FRT SI	ULFIDE TOTAL (MG/L AS S)	SULFATE DIS- SOLVED (MG/L AS SO4)	CHLO- RIDE, DIS- SOLVED (MG/L AS CL)
OCT 1991								_				•
15 D R C	150		34	15	21		0.8 3	. 0	120	<0.5	18	29
10 FEB 1992			~ ~			-		-	130			
25 APR			~-			-		-	120			
01 JUN	120		27	13	15		0.6 4	. 4	110	<0.5	18	26
08	180		47	14	24		0.8 2	. 6	130	<0.5	20	33
05	110		25	11	14		0.6 2	. 4	100		17	21
			S OL:			SIDUR						
	R DATE (IDE, DI DIS- SC OLVED (1 MG/L	DLVED TURE MG/L DI AS SOI	STI- D NTS, SO IS- (T LVED P	IS- AT LVED DE ONS S ER PE	TAL 105 G. C, US- NDED MG/L)	NITRO- GEN, NITRATE TOTAL (MG/L AS N)	NITRO- GEN, NITRITE TOTAL (MG/L AS N)	NITRO GEN NO2+NO TOTAL (MG/) AS N	, GE O3 AMM L TO L (M	RN, G ONIA ORG FAL TO G/L (N	TRO- SEN, SANIC STAL GG/L S N)
15	1991 	0.10	26	218	2.17	1	1.57	0.030	1.6	0 0	. 080	0.22
)			- -		15	1.49	0.010	1.5	0 0	.010	0.19
25	1992					9	1.59	0.010	1.6	0 0	.020	
	ı .	0.20	20	190	6.04	11	1.18	0.020	1.2	0 0	.040	0.16
	3	0.20	26	269 1	2.3	9	0.990	0.010	1.0	0 0	.010	
AUG 05	i	0.10	19	169	8.67	224	0.820	0.020	0.8	40 0	.030	0.67

K = non-ideal count

RIO DE LA PLATA BASIN 50044850 RIO GUADIANA NEAR NARANJITO, PR--Continued

WATER-QUALITY DATA, WATER YEAR OCTOBER 1991 TO SEPTEMBER 1992

DATE	NITRO- GEN, AM- MONIA + ORGANIC TOTAL (MG/L AS N)	NITRO- GEN, TOTAL (MG/L AS N)	NITRO- GEN, TOTAL (MG/L AS NO3)	PHOS- PHORUS TOTAL (MG/L AS P)	ARSENIC TOTAL (UG/L AS AS)	BARIUM, TOTAL RECOV- ERABLE (UG/L AS BA)	BORON, TOTAL RECOV- ERABLE (UG/L AS B)	CADMIUM TOTAL RECOV- ERABLE (UG/L AS CD)	CHRO- MIUM, TOTAL RECOV- ERABLE (UG/L AS CR)	COPPER, TOTAL RECOV- ERABLE (UG/L AS CU)
OCT 1991										
15	0.30	1.9	8.4	0.470	<1	<100	60	<1	1	<10
10 FRB 1992	0.20	1.7	7.5	0.320						
25	<0.20			0.280						
APR 01	0.20	1.4	6.2	0.160	1	<100	20	<1	8	10
JUN 08	<0.20			0.180						
AUG 05	0.70	1.5	6.8	0.410						
DATE	IRON, TOTAL RECOV- ERABLE (UG/L AS FE)	LEAD, TOTAL RECOV- ERABLE (UG/L AS PB)	MANGA- NESE, TOTAL RECOV- ERABLE (UG/L AS MN)	MERCURY TOTAL RECOV- ERABLE (UG/L AS HG)	SELE- NIUM, TOTAL (UG/L AS SE)	SILVER, TOTAL RECOV- BRABLE (UG/L AS AG)	ZINC, TOTAL RECOV- ERABLE (UG/L AS ZN)	CYANIDE TOTAL (MG/L AS CN)	PHENOLS TOTAL (UG/L)	METHY- LENE BLUE ACTIVE SUB- STANCE (MG/L)
ОСТ 1991	TOTAL RECOV- BRABLE (UG/L AS FE)	TOTAL RECOV- BRABLE (UG/L AS PB)	NESE, TOTAL RECOV- ERABLE (UG/L AS MN)	TOTAL RECOV- ERABLE (UG/L AS HG)	NIUM, TOTAL (UG/L AS SE)	TOTAL RECOV- ERABLE (UG/L AS AG)	TOTAL RECOV- ERABLE (UG/L AS ZN)	TOTAL (MG/L AS CN)	TOTAL (UG/L)	LENE BLUE ACTIVE SUB- STANCE (MG/L)
	TOTAL RECOV- ERABLE (UG/L	TOTAL RECOV- BRABLE (UG/L	NESE, TOTAL RECOV- ERABLE (UG/L	TOTAL RECOV- ERABLE (UG/L	NIUM, TOTAL (UG/L AS SE)	TOTAL RECOV- BRABLE (UG/L	TOTAL RECOV- BRABLE (UG/L	TOTAL (MG/L	TOTAL	Lene Blue Active Sub- Stance
OCT 1991 15 DBC 10	TOTAL RECOV- BRABLE (UG/L AS FE)	TOTAL RECOV- BRABLE (UG/L AS PB)	NESE, TOTAL RECOV- ERABLE (UG/L AS MN)	TOTAL RECOV- ERABLE (UG/L AS HG)	NIUM, TOTAL (UG/L AS SE)	TOTAL RECOV- ERABLE (UG/L AS AG)	TOTAL RECOV- ERABLE (UG/L AS ZN)	TOTAL (MG/L AS CN)	TOTAL (UG/L)	LENE BLUE ACTIVE SUB- STANCE (MG/L)
OCT 1991 15 DEC 10 FEB 1992 25	TOTAL RECOV- BRABLE (UG/L AS FE)	TOTAL RECOV- BRABLE (UG/L AS PB)	NESE, TOTAL RECOV- ERABLE (UG/L AS MN)	TOTAL RECOV- ERABLE (UG/L AS HG)	NIUM, TOTAL (UG/L AS SE)	TOTAL RECOV- ERABLE (UG/L AS AG)	TOTAL RECOV- ERABLE (UG/L AS ZN)	TOTAL (MG/L AS CN)	TOTAL (UG/L)	LENE BLUE ACTIVE SUB- STANCE (MG/L)
OCT 1991 15 DEC 10 FEB 1992 25 APR 01	TOTAL RECOV- ERABLE (UG/L AS FE)	TOTAL RECOV- BRABLE (UG/L AS PB)	NESE, TOTAL RECOV- ERABLE (UG/L AS MN)	TOTAL RECOV- ERABLE (UG/L AS HG) <0.10	NIUM, TOTAL (UG/L AS SE)	TOTAL RECOV- ERABLE (UG/L AS AG)	TOTAL RECOV- ERABLE (UG/L AS ZN)	TOTAL (MG/L AS CN) <0.010	TOTAL (UG/L)	LENE BLUR ACTIVE SUB- STANCE (MG/L)
OCT 1991 15 DEC 10 FEB 1992 25	TOTAL RECOV- ERABLE (UG/L AS FE) 140	TOTAL RECOV- ERABLE (UG/L AS PB)	NESE, TOTAL RECOV- BRABLE (UG/L AS MN)	TOTAL RECOV- ERABLE (UG/L AS HG) <0.10	NIUM, TOTAL (UG/L AS SE)	TOTAL RECOV- RRABLE (UG/L AS AG) <1	TOTAL RECOV- ERABLE (UG/L AS ZN) <10	TOTAL (MG/L AS CN) <0.010	TOTAL (UG/L) 1 	LENE BLUE ACTIVE SUB- STANCE (MG/L) 0.05

50045000 LAGO LA PLATA AT DAMSITE, PR

LOCATION.--Lat 18°20'40", long 66°14'10", Hydrologic Unit 21010005, 2.9 mi (4.7 km) at northeast of Plaza de Naranjito, 2.7 mi (4.3 km) West of Road 167, km 15.3, Buena Vista, Bayamón, 5.2 mi (8.4 km) east of Plaza de Corozal.

DRAINAGE AREA. -- 181 mi2 (469 km2).

RLEVATION RECORDS

PERIOD OF RECORD. -- February 1989 to current year.

GAGE. -- Water-stage recorder. Datum of gage is mean sea level.

REMARKS.--Lago La Plata first construction phase was completed in 1974 and the second construction phase to provide the spillway with bascule gates was completed in October 1989. The maximum storage is 37,000 ac-ft (45.6 hm²) and its purpose is the supply of water for domestic and industrial use. The Plata Dam is a concrete gravity structure located across the Río de la Plata, the dam has an overall length of 774 ft (236 m) and a maximum height of about 131 ft (40 m). The dam spillway is provided with 6 bascule gates. The spillway crest has a total clear length of 690 ft (210 m), an elevation of 155 ft (47 m). The Dam is owned and operated by Puerto Rico Aqueduct and Sewer Authority. Gage-height and precipitation satellite telemetry at station.

EXTREMES OBSERVED FOR PERIOD OF RECORD. -- Maximum elevation, 167.02 ft (50.91 m), Jan. 5, 1992; minimum elevation, 144.88 ft (44.16 m), Oct. 29, 1991.

EXTREMES FOR CURRENT YEAR.--Maximum elevation, 167.02 ft (50.91 m), Jan. 5; minimum elevation, 144.88 ft (44.16 m), Oct. 29.

Capacity Table (based on data from Puerto Rico Aqueduct and Sewer Authority)

Elevation, in feet	Contents, in acre-feet	Elevation, in feet	Contents, in acre-feet
98.43	2,760	164.05	28,550
131.24	11,360	170.61	33,160
154.60	22,720	175.52	37,040

ELEVATION (FEET NGVD), WATER YEAR OCTOBER 1991 TO SEPTEMBER 1992 DAILY OBSERVATION AT 24:00 VALUES

DAY	OCT	NOA	DEC	JAN	FBB	MAR	APR	MAY	JUN	JUL	λUG	SEP
1	148.72	146.45	151.12	147.57	154.68	153.25	152.10	154.65	154.92	153.88	149.93	152.72
2	148.88	146.72	151.06	147.39	154.64	153.10	154.50	154.92	154.96	153.73	149.80	152.55
3	148.87	146.83	151.02	147.22	154.76	152.93	154.87	154.83	154.92	153.55	149.67	152.42
4	148.83	146.82	151.00	147.04	154.88	152.82	154.78	154.73	154.88	153.36	149.66	152.31
5	148.75	146.81	151.01	166.92	154.82	152.69	154.67	154.63	154.85	153.17	150.56	152.33
6	148.58	146.79	150.95	λ	154.77	152.53	154.50	154.78	154.80	152.97	155.14	152.44
7	148.45	147.43	150.83	155.21	154.85	152.39	154.46	154.71	154.79	152.79	155.11	152.34
8	148.51	148.76	150.73	155.13	154.87	152.30	154.33	154.66	154.79	152.70	155.02	152.18
9	148.43	149.76	150.66	155.05	154.81	152.16	154.21	154.56	154.81	152.68	155.15	152.04
10	148.32	150.06	150.52	155.04	154.77	152.14	154.30	154.49	154.81	152.56	154.95	151.98
11	148.16	150.12	150.36	154.97	154.72	152.12	154.19	154.45	154.88	152.45	154.84	151.87
12	148.04	150.11	150.23	154.95	154.77	152.00	154.06	154.28	154.96	152.30	154.85	151.70
13	147.83	150.12	150.08	154.99	154.75	151.93	153.92	154.09	154.92	152.16	154.81	151.53
14	147.64	150.01	149.93	154.96	154.69	151.81	153.89	153.89	154.95	152.05	154.81	151.33
15	147.42	149.90	149.78	154.90	154.64	151.68	153.76	153.68	154.91	151.96	154.75	151.16
16	147.21	149.81	149.16	155.36	154.54	151.50	153.66	153.97	154.90	151.86	154.71	151.02
17	146.97	149.73	149.30	154.94	154.47	151.39	153.95	154.19	154.87	151.77	154.67	150.98
18	146.79	149.70	149.09	154.88	154.38	151.35	153.88	154.76	154.89	151.67	154.58	150.99
19	146.58	149.53	148.89	154.84	154.26	151.28	153.76	155.12	154.82	151.60	154.47	151.41
20	146.41	149.38	148.84	154.84	154.16	151.13	154.83	154.93	154.76	151.45	154.33	153.83
21	146.23	149.28	148.97	154.83	154.06	150.99	154.97	155.37	154.81	151.31	154.21	155.37
22	146.01	149.31	149.02	154.82	153.98	150.92	154.82	155.02	155.00	151.17	154.07	155.04
23	145.82	149.41	148.91	154.81	153.85	150.79	154.67	156.83	154.92	151.14	153.94	154.92
24	145.64	149.87	148.77	154.81	153.76	150.65	154.50	155.29	154.82	151.23	153.77	154.81
25	145.50	150.27	148.56	154.81	153.67	150.48	154.31	155.16	154.72	151.08	153.60	154.72
26	145.41	150.35	148.39	154.82	153.60	150.31	154.14	155.48	154.62	150.95	153.46	154.58
27	145.22	150.33	148.22	154.80	153.52	150.87	153.95	155.03	154.47	150.84	153.35	154.46
28	145.01	150.83	148.15	154.80	153.44	152.29	153.74	154.92	154.33	150.65	153.21	154.29
29	144.96	151.07	147.99	154.79	153.33	152.41	153.88	154.90	154.18	150.42	153.09	154.10
30	145.23	151.14	147.85	154.74		152.29	153.96	154.86	154.06	150.23	152.96	153.99
31	146.15		147.71	154.70		152.22		154.95		150.10	152.85	
MEAN	147.12	149.22	149.58		154.36	151.83	154.19	154.78	154.78	151.93	153.56	152.85
MAX	148.88	151.14	151.12		154.88	153.25	154.97	156.83	155.00	153.88	155.15	155.37
MIN	144.96	146.45	147.71		153.33	150.31	152.10	153.68	154.06	150.10	149.66	150.98

A No gage-height record.

50045010 RIO DE LA PLATA BELOW LA PLATA DAM, PR

LOCATION.--Lat 18°20'45", long 66°14'17", Hydrologic Unit 21010005, 2.8 mi (4.5 km) west of Road 167, km 15.3, Buena Vista, Bayamón, 5.0 mi (8.0 km) east of Plaza de Corozal, 3.0 mi (4.8 km) northeast of Plaza de Naranjito.

DRAINAGE AREA. -- 173 mi2 (448 km2).

WATER-DISCHARGE RECORDS

PERIOD OF RECORD. -- July 1989 to current year.

GAGE.--Water-stage recorder. Elevation of gage is 164 ft (30 m), from topographic map.

REMARKS.--Records poor. Regulation at all stages by Puerto Rico Aqueduct and Sewer Authority reservoir upstream from gage. Gage-height satellite telemetry at station.

	DIS	CHARGE,	CUBIC PRI	et per sec	OND, WATER		TOBER 19	91 TO SEP	TRMBER 199	2		
DAY	OCT	NOV	DEC	JAN	FEB	MAR	APR	MAY	JUN	JUL	AUG	SEP
1	.01	.16	.15	.10	2.4	.00	.01	.27	105	.02	.01	.00
2	.00	.35	.15	. 09	.78	.00	.00	209	108	. 02	.00	.00
3 4	.00	.40	.18	.06	2.1	.00	29	91 13	91 42	. 02 . 02	.00 .12	.00
5	.00	. 25 . 15	.23	.04 16300	50 53	.00	20 2.9	1.3	24	. 02	.49	.00
			•	20200	33		•	2.5				
6	.00	. 10		27400	26	.00	.36	10	15	.01	112	. 01
7 8	.00	. 02 . 00	.08 .12	1500 576	30 61	.00	.08	12 2.9	8.8 7.5	.01 .02	295 160	.01 .00
و	.00	.01	.21	360	43	.00	.02	.36	10	. 25	154	.00
10	.00	.01	.21	374	24	.00	.00	.07	8.6	. 12	148	.00
11	00	00	10	270	12			01	160	.16	57	.00
12	.00	. 02 . 02	.15 .12	279 201	13 17	.00	.00	.01 .01	160 183	. 19	30	.00
13	.00	.06	.12	220	19	.00	.00	.00	294	.11	29	. 00
14	.00	.06	.25	213	7.4	.00	.00	.00	309	. 11	17	.00
15	.00	.06	.14	137	1.7	.00	.00	.00	172	.08	14	. 00
16	.00	. 04	.12	226	.42	.00	.00	1.5	112	. 12	9.1	.00
17	.00	. 04	.10	531	.17	.00	.00	.47	78	. 14	3.8	. 00
18	.00	. 02	.10	207	.09	.00	.00	4.6	48	. 12	. 93	.00
19	.00	. 02	.02	109	.06	. 00	.00	158	37	. 09	.13	. 07
20	.00	. 02	.20	63	.03	.00	6.7	154	18	. 12	.03	. 34
21	.00	. 13	.38	47	.02	.00	95	430	11	.09	.01	350
22	.00	. 49	.17	41	.03	.01	46	305	104	. 14	.00	e371
23	.00	. 26	.12	33	.02	.00	10	1020	99	.10	.00	149
24 25	.00 .01	.78 .31	.10 .08	27 28	.01 .01	.00	.54 .05	3840 705	50 18	. 13 . 14	.00	44 9.0
•	.01		.00	20	.01	. 00		703	10	. 14		5.0
26	.11	. 18	.06	30	.00	.00	.00	4520	2.7	. 14	.13	. 69
27	.13	. 15	.06	26	.00	.46	.00	796	.37	.10	.07	. 03
28 29	.12 .43	.24 .28	.17 .25	23 24	.00 .00	1.7 .85	.00	365 209	.14	.11	.01	.01 .01
30	.46	. 18	.15	14		.16	.36	140	.03	.04	.00	.01
31	.22		.11	7.6		. 03		86		.02	.00	
TOTAL	1.49	4.81	4 55	48996.89	351.24	3.21	211 07	13074.49	2116.20	2.85	1030.83	924.18
MEAN	.048	. 16	.15	1581	12.1	.10	7.04	422	70.5	.092	33.3	30.8
MAX	.46	.78	.38	27400	61	1.7	95	4520	309	. 25	295	371
MIN	.00	. 00	. 02	.04	.00	.00	.00	. 00	.03	.01	.00	.00
ac-ft Cfsm	3.0 .00	9.5 .00	9.0 .00	97190 9.15	697 .07	6.4 .00	419 .04	25930 2.44	4200 .41	5.7 .00	2040 .19	1830 .18
IN.	.00	.00	.00	10.55	.08	.00	.05	2.81	.46	.00	.22	.20
e Ra	timated											
STATIST	rics of Mc	NTHLY M	BAN DATA	FOR WATER	YEARS 1989	- 1992	, BY WATI	SR YBAR (W	Y)			
MEAN	437	47.5	28.4	550	77.5	44.8	14.9	162	30.0	21.8	8.34	273
MAX	1107	107	84.8	1581	222	83.2	27.7	422	70.5	64.7	33.3	1047
(WY)	1991	1991	1991	1992	1991	1990	1990	1992	1992	1991	1992	1989
MIN (WY)	.048 1992	.16 1992	.14 1990	.19 1990	.27 1990	.10 1992	7.04 1992	2.00 1991	.16 1991	.092 1992	.020 1989	.001 1991
	STATISTI				ENDAR YEAR			WATER YEA			YEARS 198	
SUPPLIE	DIMITOI		FOR			,	FUR 1992	MAIDY INS		WALDIN	IMARO IJO	.,
				12317.1 33.7			66721. 182			121 182 37.		1992 1990
HI GHEST	DAILY ME	BAN			Jul 16		27400			27400	Jan	6 1992
	DAILY MEA				00 Jun 17			.00 Oct	2	•	00 Jul	14 1989
	SEVEN-DAY NAMBOUS PE			. (00 Aug 7		127000	.00 Oct Jan		127000		14 1989 5 1992
	TANBOUS PE							.76 Jan		34.		5 1992
ANNUAL	RUNOFF (A	C-FT)	-	24430			132300			87900		
	RUNOFF (.:				. 05			70	
	RUNOFF (]			2.0			14.			9. 174		
	CENT EXCES			83	23		148	. 12			49	
	CENT BACE				00			. 00			00	

50045010 RIO DE LA PLATA AT BELOW LA PLATA DAM, PR--Continued

WATER-QUALITY RECORDS

PERIOD OF RECORDS. -- Water years 1990 to current year.

INSTRUMENTATION. -- Automatic sediment sampler and DH-48.

PERIOD OF DAILY RECORD.--SUSPENDED-SEDIMENT DISCHARGE: October 1989 to September 1992

EXTREMES FOR PERIOD OF DAILY RECORD.-SEDIMENT CONCENTRATION: Maximum daily mean, 2,180 mg/L Jan. 06, 1992; Minimum daily mean,
<.05 mg/L several days.

SEDIMENT LOADS: Maximum daily mean, 362,000tons (328,000tonnes) Jan. 06, 1992; Minimum daily mean, 0.00 ton (0.00 tonne) several days.

EXTREMES FOR WATER YEARS 1990-92.--

Water Year	Suspended-sediment maximum	concentration (mg/L) minimum	Suspended-sediment discha maximum	rge (tons per day) minimum
1990	848 (Mar. 14)	<.05 (Several days)	259 (Oct. 23)	.00 (Several days)
1991 1992	243 (Oct. 21) 2.180 (Jan. 06)	<.05 (Several days)	5,760 (Oct. 21) 362,000 (Jan. 06)	.00 (Several days)

SEDIMENT DISCHARGE, SUSPENDED (TONS/DAY), WATER YEAR OCTOBER 1989 TO SEPTEMBER 1990

		MBAN			mban			MRAN	
	MEAN DI SCHARGE	CONCEN- TRATION	SEDIMENT DISCHARGE	MEAN DISCHARGE	CONCEN- TRATION	Sediment Discharge	mean Discharge	CONCEN- TRATION	Sediment Discharge
DAY	(CFS)	(MG/L)	(TONS/DAY)	(CFS)	(MG/L)	(TONS/DAY)	(CFS)	(MG/L)	(TONS/DAY)
		OCTOBER		1	NOVEMBER		1	DECEMBER	
1	159	17	7.5	114	14	4.4	.10	٧.	5 .00
2	246	24	16	77	11	2.3	.07	<.	
3	196	21	11	50		1.1	.04	۷.	5 .00
4	223	22	13	37	7	.66	.03	٧.	5 .00
5	234	22	14	40	7	.76	.03	≺.	5 .00
6	170	19	8.5	90	12	3	.02	∢.	5 .00
7	109	14	4	87	12	2.8	.02	₹.	
8	89	12	2.9	87	12	2.8	.01	ζ.	
9	76	11	2.3	92	12	3.1	.01	₹.	
10	68	10	1.9	55	- 9	1.3	.01	₹.	
11	62	10	1.6	38	7	.69	.01	۷.	5 .00
12	54	9	1.3	34	Ź	.61	.02	₹.	
13	45	8	.93	33	6	.54	.02	∢.	
14	56	9	1.4	33	6	.54	.02	₹.	
15	47	8	i	28	6	.42	.04	<.	
• •	36	6	. 63	24	5	.32	.09	۷.	5 .00
16 17	275	26	19	20	4	.24	.13	ζ,	
18	170	19	8.5	17	1	.19	.13	₹.	
	74		2.2	29	6	.44	.13	ζ.	
19 20	65	11 10	1.8	25	5	.34	.18	₹.	
20	65	10	1.6	45	3	.34	.10	``	
21	263	25	18	17	4	.19	.18	<.	5 .00
22	503	38	52	10	4	.10	.17	<.	
23	1310	73	259	6.2	4	.06	.16	<.	
24	687	48	89	4.1	3	.00	. 15	<.	
25	184	20	9.7	3.1	2	.02	.12	<٠	5 .00
26	290	27	21	1.8	2	.01	.10	∢.	
27	204	22	12	. 81	<.	.5 .00	.10	<.	
28	94	13	3.2	.38	<.	.5 .00	.16	3	.00
29	.84	13	3.2	. 25	<.	.5 .00	1.1	<.	
30	152	17	7.1	. 15	<.	.5 .00	.74	<.	
31	103	13	3.7				.39	<.	5 .00
TOTAL	6328		597.36	1053.79		26.93	4.48		0.01

RIO DE LA PLATA BASIN 50045010 RIO DE LA PLATA BELOW LA PLATA DAM, PR--Continued SEDIMENT DISCHARGE, SUSPENDED (TONS/DAY), WATER YEAR OCTOBER 1989 TO SEPTEMBER 1990

	MRAN	MEAN CONCEN-	Sediment	MRAN	MRAN CONCEN-	Sediment	mran	MEAN CONCEN-	SEDIMENT
DAY	DISCHARGE (CFS)	TRATION (MG/L)	DISCHARGE (TONS/DAY)	DISCHARGE (CFS)	TRATION (MG/L)	DISCHARGE (TONS/DAY)	DISCHARGE (CFS)	TRATION	DISCHARGE (TONS/DAY)
		JANUARY		1	FEBRUARY			MARCH	
1	.31	۷,	5 .00	.18	۷,	5 .00	.34	٠.!	5 .00
2	.27	∢,		.11	٧.		.33	<.	
3	.22	۷.		. 15	<.		.28	<.	
4	.19	۷.		. 13	<٠		.33	۷٠.	
5	.15	<.	5 .00	. 12	۷.		.20	<. !	5 .00
6	.15	۷.		. 05	۷,		.13	<.!	
7	.15	<.		. 09	<.		.08	<.!	
8	.13	<.		.28	<.		.04	<.!	
9	.13	<.		.26	<.		.22	<.!	
10	. 13	۷.	5 .00	. 15	<.	5 .00	.31	<. ∶	5 .00
11	.12	۷.	5 .00	.08	۷.	5 .00	1.7	2	.01
12	.11	۷.		. 03	<.		2.8	3	.02
13	.10	<.	5 .00	.01	۷.	5 .00	511	38	53
14	.07	<.	5 .00	. 95	٧.	5 .01	848	55	126
15	.12	<.	5 .00	. 62	۷٠	5 .00	51	9	1.5
16	.10	۷,	5 .00	.44	۷.	5 .00	178	19	9.2
17	. 17	۷٠		.30	<.		269	25	18
18	.15	۷.		.23	٧.		187	20	10
19	.11	<.		.48	<.		104	13	3.7
20	.53	۷.	5 .00	. 32	۷.	5 .00	56	9	1.4
21	.50	۷.		. 22	۷.		54	9	1.3
22	.27	<.		. 28	۷.		48	8	1
23	.17	<.		.50	<.		44	7	. 89
24	.31	<.		.58	<.		41	7	.79
25	.20	۷.	5 .00	. 34	۷.	5 .00	36	6	. 63
26	.12	۷.		.26	۷.		31	6	.49
27	.10	۷.		.21	۷.		28	6	.42
28	.11	٠.		.20	<.		25	5	. 34
29	.17	<٠					22	5	. 28
30	.28	٧.					20	4	.24
31	.34	<.	5 .00				18	4	.10
TOTAL	5.98		0.00	7.57		0.01	2577.76		

50045010 RIO DE LA PLATA BELOW LA PLATA DAM, PR--Continued

147

SEDIMENT DISCHARGE, SUSPENDED (TONS/DAY), WATER YEAR OCTOBER 1989 TO SEPTEMBER 1990

DAY	MEAN DISCHARGE (CFS)	TRATION D	EDIMENT ISCHARGE ONS/DAY)	MEAN DISCHARGE (CFS)	MRAN CONCEN- TRATION (MG/L)	SEDIMENT DISCHARGE (TONS/DAY)	MEAN DISCHARGE (CFS)	MEAN CONCEN- TRATION (MG/L)	SEDIMENT DISCHARGE (TONS/DAY)
		APRIL			MAY			JUNE	
1	16	4	. 17	45	8	.93	3.4	2	.02
2	14	4	. 15	42	7	.82	3.1	2	. 02
3	12	4	. 12	36	6	. 63	2.5	3	.02
4	10	4	. 10	30	6	.47	2.4	3	.02
5	8.2	4	.08	26	5	.37	2.7	3	. 02
6	6.5	3	.06	22	5	.28	2.3	3	.02
7	5.3	3	.04	22	5	.28	1.7	3	.01
8	4.2	3	. 03	257	24	17	1.4	3	.01
9	3.4	2	.02	663	46	82	1.1	3	.01
10	3.0	2	.02	71	10	2	1.2	3	.01
11	2.0	2	.01	76	11	2.3	1.1	3	.01
12	1.7	2	.01	74	11	2.2	.96	4	.01
13	1.0	4	.01	71	10	2	.90	۷۰!	5 .01
14	.67	<.5	.00	71	10	2	1.3	3	.01
15	.36	<.5	.00	67	10	1.8	168	18	8.4
16	.25	<.5	.00	61	10	1.6	260	24	17
17	1.8	2	.01	50	8	1.1	89	12	2.9
18	12	4	. 12	40	7	.76	26	6	.40
19	16	4	. 17	31	6	.49	5.7	3	. 05
20	58	9	31.4	25	5	.34	1.4	3	.01
21	98	13	3.4	30	6	.47	.80	٧. ١	
22	92	12	3.1	24	5	.32	. 67	<.!	
23	58	9	1.4	20	4	.24	. 67	<.!	
24	31	6	.49	17	4	.19	. 62	<.!	
25	32	6	. 52	14	4	.15	.81	<. !	5 .00
26	76	11	2.3	11	4	.11	. 66	<.!	
27	81	11	2.5	9.7	4	.10	.58	<.!	
28	73	11	2.1	8.2	4	.08	.55	<.!	
29	64	10	1.7	6.0	3	.05	.51	<.!	
30	51	9	1.2	5.0	3	.04	.52	<. !	
31				4.0	3	.03		***	
TOTAL	832.38		51.23	1928.9		121.15	582.55		

RIO DE LA PLATA BASIN 50045010 RIO DE LA PLATA BELOW LA PLATA DAM, PR--Continued

SEDIMENT DISCHARGE, SUSPENDED (TONS/DAY), WATER YEAR OCTOBER 1989 TO SEPTEMBER 1990

DAY	MEAN DISCHARGE (CFS)	MEAN CONCEN- TRATION (MG/L)	SEDIMENT DISCHARGE (TONS/DAY)	MEAN DISCHARGE (CFS)	MEAN CONCEN- TRATION (MG/L)	Sediment Discharge (Tons/Day)	Mran Discharge (CFS)	MEAN CONCEN- TRATION (MG/L)	SEDIMENT DISCHARGE (TONS/DAY)
		JULY			August		s	eptember	
1	. 63	<.		.16	∢.		.00	۷۰!	
2	.64	٧.		. 14	٧.		.00	<.!	
3	.57	٧.		. 17	٧.		.01	<.!	
4	.35	٧.		.08	۷.		.08	<. !	
5	.29	۷٠	5 .00	.04	<٠	5 .00	.41	<.!	5 .00
6	.20	<.		.02	٧.		.40	٧٠!	
7	.15	٧٠		.06	٧٠		1.2	<٠!	
8	.12	٧.		.10	٧٠		.91	۷۰!	
9	.13	۷.		. 06	۷٠		.53	<٠!	
10	.28	۷.	5 .00	. 24	٧.	5 .00	.43	۷۰!	5 .00
11	.12	٧.	5 .00	. 27	٧.	5 .00	.83	<.!	5 .00
12	.03	٧.	5 .00	.13	٧.	5 .00	.92	<.!	5 .00
1.3	.00	۷.	5 .00	. 14	٧.	5 .00	.59	۷۰!	
14	.00	<.		.23	۷٠		.73	<.!	
15	.00	٧.	5 .00	.12	<.	5 .00	1.2	3	.01
16	.31	<.		. 05	∢,		1.3	3	.01
17	1.4	5	.01	. 02	۷.		1.1	3	.01
18	.79	<.		.01	<.		1.2	3	.01
19	.82	٧.		.01	<.		1.7	2	.01
20	2.0	2	.01	.00	٧٠	5 .00	1.7	2	.01
21	.98	4	.01	.00	<.		1.4	3	.01
22	. 67	<.		.00	30	.00	. 82	<.!	
23	.36	<.		.00	٧.		.48	<.!	
24	. 43	<.		.00	٧.		.33	<.!	
25	.39	٧٠	5 .00	.08	٧.	5 .00	.31	٠.١	5 .00
26	.28	<.		.11	<.	5 .00	171	19	8.6
27	.20	<.		. 02	٧.		154	17	7.2
28	.14	<.		.00	۷.		80	12	2.5
29	1.0	<.		.00	۷.		29	6	.44
30	. 66	۷.		.00	<.		8.2	4	. 08
31	.30	<٠	5 .00	. 00	٧.	5 .00			
TOTAL	14.24		0.03	2.26		0.00	460.78		18.89
YRAR	13798.69		1073.58						

149

50045010 RIO DE LA PLATA BELOW LA PLATA DAM, PR--Continued

SEDIMENT DISCHARGE, SUSPENDED (TONS/DAY), WATER YEAR OCTOBER 1990 TO SEPTEMBER 1991

DAY	MRAN DISCHARGE (CFS)	MEAN CONCEN- TRATION (MG/L)	SEDIMENT DISCHARGE (TONS/DAY)	Mean Discharge (CFS)	MEAN CONCEN- TRATION (MG/L)	SEDIMENT DISCHARGE (TONS/DAY)	MEAN DISCHARGE (CFS)	MEAN CONCEN- TRATION (MG/L)	SEDIMENT DISCHARGE (TONS/DAY)
		OCTOBER		1	NOVEMBER		1	DECEMBER	
1	110	14	4.1	218	22	13	166	18	8.2
2	140	16	6.2	182	20	10	152	17	7.1
3	88	12	2.9	178	19	9.2	377	31	32
4	107	13	3.9	154	17	7.2	298	27	22
5	95	12	3.2	155	17	7.3	152	17	7.1
6	65	10	1.8	171	17	8.6	86	12	2.8
7	629	13	73	149	17	6.8	53	8	1.2
8	218	22	13	124	15	5	37	7	. 66
9	579	42	65	125	15	5.1	28	6	.42
10	1060	65	186	120	15	4.8	22	5	.28
11	410	33	37	101	13	3.6	18	4	.20
12	145	17	6.5	92	12	3.1	16	4	. 17
13	417	34	38	82	12	2.7	19	4	.22
14	521	39	55	69	11	2	16	4	. 17
15	1180	69	220	62	10	1.6	16	4	.17
16	2720	115	840	63	10	1.7	31	6	.49
17	1500	79	320	70	11	2	35	6	.60
18	2050	94	522	67	11	1.9	26	5	. 37
19	3470	134	1260	90	12	3	13	4	. 14
20	484	37	48	65	10	1.8	5.6	33	.05
21	8790	243	5760	78	11	2.4	2.1	2	.01
22	1010	63	173	110	14	4.1	1.5	2	.01
23	391	32	34	102	13	3.6	1.3	3	.01
24	308	28	23	102	13	3.6	1.5	2	.01
25	845	55	126	84	12	2.7	1.7	2	.01
26	3810	142	1460	51	9	1.2	1.4	3	.01
27	1670	84	378	55	9	1.3	1.2	3	.01
28	572	41	64	54	9	1.3	5.3	3	.04
29	374	32	32	55	9	1.3	52	8	1.2
30	254	25	17	185	20	9.8	182	19	9.5
31	302	27	22				813	53	117
TOTAL	34314		11794.6	3213		131.7	2629.6		212.15

RIO DE LA PLATA BASIN

50045010 RIO DE LA PLATA BELOW LA PLATA DAM, PR--Continued

SEDIMENT DISCHARGE, SUSPENDED (TONS/DAY), WATER YEAR OCTOBER 1990 TO SEPTEMBER 1991

		MRAN			MEAN				
DAY	MEAN DISCHARGE (CFS)	CONCEN- TRATION (MG/L)	SEDIMENT DISCHARGE (TONS/DAY)	MEAN Discharge (CFS)	CONCEN- TRATION (MG/L)	SEDIMENT DISCHARGE (TONS/DAY)	MRAN DISCHARGE (CFS)	MBAN CONCEN- TRATION (MG/L)	SEDIMENT DISCHARGE (TONS/DAY)
		JANUARY		1	FEBRUARY			MARCH	
1	686	46	86	2.2	2	.01	75	11	2.2
2	224	23	14	2.1	2	.01	91	12	3
3	123	15	5	2.0	2	.01	92	12	3.1
4	81	11	2.5	3.3	2	.02	54	9	1.3
5	56	- 9	1.4	1020	64	175	37	7	. 66
6	108	14	4	452	35	43	34	6	.57
7	121	15	4.8	337	29	26	38	7	. 69
8	69	11	2	202	20	11	44	7	. 89
9	71	10	2	117	15	4.6	47	8	1
10	101	13	3.6	77	11	2.3	35	6	. 60
11	88	12	2.9	180	19	9.4	33	6	. 54
12	72	11	2.1	291	27	21	34	6	. 57
13	55	9	1.3	1070	65	189	31	6	.49
14	48	8	1	329	28	2 5	29	6	.44
15	41	7	.79	207	21	12	24	5	.32
16	39	7	.72	109	14	4	15	4	.16
17	32	6	. 52	96	13	3.3	7.3	4	. 07
18	26	5	. 37	165	18	8.1	4.1	3	. 03
19	21	5	.26	350	30	28	1.6	2	.01
20	15	4	. 16	289	27	21	1.2	3	.01
21	10	4	.10	246	24	16	.50	1	.00
22	6.7	3	.06	192	19	10	217	22	13
23	5.3	3	. 04	135	16	5.8	267	25	18
24	6.3	3	. 06	91	12	3	123	15	5
25	7.1	4	. 07	68	10	1.9	38	7	. 69
26	6.3	3	. 06	60	9	1.5	9.4	.4	. 09
27	2.5	3	. 02	62	10	1.6	86	12	2.8
28	1.9	2	.01	72	11	2.1	74	11	2.2
29	1.9	2	.01				28	6	. 42
30	1.7	3	.01				8.7	3	. 08
31	2.1	2	.01				2.8	3	. 02
TOTAL	2128.8		135.87	6226.6		624.65	1581.60		58.95

50045010 RIO DE LA PLATA BELOW LA PLATA DAM, PR--Continued

151

SEDIMENT DISCHARGE, SUSPENDED (TONS/DAY), WATER YEAR OCTOBER 1990 TO SEPTEMBER 1991

	Mean				MRAN		mean			
DAY	MEAN DISCHARGE (CFS)	CONCEN- TRATION (MG/L)	SEDIMENT DISCHARGE (TONS/DAY)	MEAN DISCHARGE (CFS)	CONCEN- TRATION	Sediment Discharge (Tons/Day)	MRAN Discharge (CFS)	CONCEN- TRATION (MG/L)	SEDIMENT DISCHARGE (TONS/DAY)	
		APRIL			MAY			JUNE		
1	2.0	2	.01	1.1	3	.01	.46	۷.	5 .00	
2	1.9	2	.01	1.1	33	.01	.41	۷.		
3	2.7	3	.02	1.2	3	.01	.29	<.		
4	2.9	3	. 02	1.6	3	.01	.23	۷.		
5	3.0	2	. 02	1.2	3	.01	. 17	۷.	5 .00	
6	2.9	3	. 02	1.1	3	.01	.15	۷.		
7	2.9	3	. 02	1.0	4	.01	.15	۷.		
8	3.8	3	. 03	2.5	3	.02	.12	<.	5 .00	
9	4.2	3	. 03	1.5	2	.01	.10	۷.		
10	3.2	2	. 02	. 68	<.	5 .00	.07	۷.	5 .00	
11	3.4	2	. 02	. 49	<.		.04	۷.		
12	3.5	2	.02	.48	٧.		.04	<.		
13	4.5	3	.04	. 62	۷.		.03	۷.		
14	3.6	3	.03	14	4	.15	.02	<.		
15	68	10	1.9	22	5	.28	.01	٠.	5 .00	
16	107	13	3.9	5.7	3	.05	.01	<.		
17	38	7	. 69	.77	۷٠		.00	<.		
18	11	4	.11	. 33	<.		.45	<.		
19	3.9	3	.03	. 29	۷.		.47	۷.		
20	3.3	3	. 03	. 26	۷.	5 .00	.28	۷.	5 .00	
21	3.3	2	. 02	.25	۷.		.17	۷.		
22	3.1	2	. 02	. 17	۷.		.10	۷.		
23	2.3	3	. 02	. 14	<.		.19	۷.		
24	1.9	2	.01	. 12	٧.		.17	<٠		
25	1.8	2	.01	1.4	3	.01	.12	۷.	5 .00	
26	1.7	2	.01	. 62	<.		.08	۷.		
27	1.5	2	. 01	. 42	۷.		.03	۷.		
28	1.4	3	.01	.29	<٠		.02	۷٠		
29	1.3	3	.01	.23	<٠		.02	۷.		
30	1.2	3	.01	. 19	۷.		.41	<.		
31				. 26	٠.	5 .00				
TOTAL	295.2		7.10	62.01		0.59	4.81		0.00	

RIO DE LA PLATA BASIN

50045010 RIO DE LA PLATA BELOW LA PLATA DAM, PR--Continued

SEDIMENT DISCHARGE, SUSPENDED (TONS/DAY), WATER YEAR OCTOBER 1990 TO SEPTEMBER 1991

	MEAN			MRAN		Mean			
DAY	MRAN DISCHARGE (CFS)		SEDIMENT DISCHARGE (TONS/DAY)	Mean Discharge (CFS)	CONCEN- TRATION (MG/L)	SEDIMENT DISCHARGE (TONS/DAY)	MEAN DISCHARGE (CFS)	CONCEN- TRATION (MG/L)	SEDIMENT DISCHARGE (TONS/DAY)
		JULY			AUGUST		SI	eptember	
1	.45	<.5	.00	.39	۷,	5 .00	e.00	۷. !	s e.00
2	.27	<.5		.17	<.		e.00	<.!	
3	.20	<.5		.08	₹.		e.00	۷. ا	
4	.21	<.5		. 03	<.		e.00	<.!	e.00
5	.16	<.5		.01	۷.		e.00	٠.!	
6	.09	<.5		.01	۷.		e.00	٠.!	
7	.25	<.5		.00	<٠		e.00	<.!	
8	.44	<.5		.00	۷.		e.00	<.!	
9	.31	<.5		.00	<.		e.00	<.!	
10	.20	<.5	.00	.00	٧.	5 .00	e. 02	<.!	e. 00
11	.13	<.5	.00	.00	۷.	5 .00	e.00	<.!	5 e. 00
12	.07	<.5		. 00	₹.		e.00	<.!	
13	. 05	<.5		.00	<.		e.00	<.!	
14	.02	<.5	.00	. 00	<.		e.00	<.!	e.00
15	.05	<.5	.00	.00	٧.	5 .00	e.00	<. !	•. 00
16	1330	74	265	.00	۷.		e.00	٠.١	
17	507	38	52	.00	<.		e.00	<.!	
18	121	15	4.8	.00	۷.	5 .00	e.00	<.!	
19	36	6	. 63	.00	<.		e.00	<.!	
20	7.0	3	. 06	.00	۷.	5 .00	e. 00	٠٠!	5 e. 00
21	1.0	4	.01	.00	۷.		•.00	٠.١	
22	.38	<.5		.00	<.		e.00	٠.١	
23	.18	<.5		.00	<.		e.00	<.!	
24	.11	<.5		. 00	<.		e.00	<.!	
25	.08	<.5	.00	.00	۷.	5 .00	€.00	<.!	5 e.00
26	.04	<.5	.00	. 00	۷.	5 .00	e.00	٠.!	5 e.00
27	.03	<.5	.00	e. 02	۷.		.00	<.!	5 .00
28	.10	<.5	.00	e. 03	۷.	5 e.00	.00	<.!	5 .00
29	.15	<.5		e. 02	۷.	5 e.00	.01	<.!	
30	.07	<.5		e. 03	۷.		.01	<.!	
31	.39	<. <u>!</u>	.00	e. 02	۷.	5 e.00			
TOTAL	2006.43		322.50	0.81		0.00	0.04		0.00
YEAR	52462.90		13288.11						

e Estimeted

RIO DE LA PLATA BASIN
50045010 RIO DE LA PLATA BELOW LA PLATA DAM, PR--Continued

SEDIMENT DISCHARGE, SUSPENDED (TONS/DAY), WATER YEAR OCTOBER 1991 TO SEPTEMBER 1992

		MEAN			mran			MEAN	
DAY	Mean Discharge (CFS)	CONCEN- TRATION (MG/L)	Sediment Discharge (Tons/Day)	Mean Discharge (CFS)	CONCEN- TRATION (MG/L)	SEDIMENT DISCHARGE (TONS/DAY)	MEAN Discharge (CFS)	CONCEN- TRATION (MG/L)	SEDIMENT DISCHARGE (TONS/DAY)
		OCTOBER		1	NOVEMBER		1	December	
1	.01	5	.00	. 16	4	.00	.15	5	.00
2	.00	5	.00	. 35	4	.00	.15	5	.00
3	.00	5	.00	.40	4	.00	.18	5	.00
4	.00	5	.00	. 25	4	.00	.23	5	.00
5	.00	5	. 00	. 15	4	.00	.14	5	.00
6	.00	5	.00	.10	4	.00	.11	5	.00
7	.00	5	.00	. 02	4	.00	.08	5	.00
8	.00	5	.00	.00	5	.00	.12	5	.00
9	.00	5	. 00	. 01	4	.00	.21	5	.00
10	.00	5	.00	.01	5	.00	.21	5	.00
11	.00	5	.00	. 02	4	.00	.15	5	.00
12	.00	5	.00	.02	5	.00	.12	5	.00
13	.00	5	.00	. 06	6	.00	.12	5	.00
14	.00	5	.00	.06	6	.00	.25	5	.00
15	.00	4	. 00	.06	5	.00	.14	5	.00
16	.00	4	.00	.04	5	.00	.12	7	.00
17	.00	4	.00	.04	5	.00	.10	10	.00
18	.00	4	. 00	.02	5	.00	.10	14	.00
19	.00	4	.00	. 02	5	.00	.02	13	. 00
20	.00	4	. 00	. 02	5	.00	.20	11	.00
21	.00	5	. 00	. 13	5	.00	.38	10	.01
22	.00	5	.00	. 49	5	.01	.17	9	.00
23	.00	5	.00	.26	5	.01	.12	10	.00
24	.00	5	. 00	.78	5	.01	.10	10	.00
25	.01	4	.00	.31	5	.00	.08	10	.00
26	.11	4	.00	. 18	5	.00	.06	10	.00
27	. 13	4	.00	. 15	5	.00	.06	10	.00
28	.12	3	.00	. 24	5	.00	.17	10	.00
29	.43	4	.01	.28	5	.00	.25	10	.00
30 31	.46	•	.00	. 18	5	.00	.15	10	. 00
31	.22	4	.00				.11	10	.00
TOTAL	1.49		0.01	4.81		0.03	4.55		0.01

RIO DE LA PLATA BASIN

50045010 RIO DE LA PLATA BELOW LA PLATA DAM, PR--Continued

SEDIMENT DISCHARGE, SUSPENDED (TONS/DAY), WATER YEAR OCTOBER 1991 TO SEPTEMBER 1992

	MBAN				MRAN		MRAN			
DAY	MEAN DISCHARGE (CFS)	CONCEN- TRATION (MG/L)	SEDIMENT DISCHARGE (TONS/DAY)	mean Discharge (CFS)	CONCEN- TRATION (MG/L)	SEDIMENT DISCHARGE (TONS/DAY)	MRAN Discharge (CFS)	CONCEN- TRATION (MG/L)	SEDIMENT DISCHARGE (TONS/DAY)	
		JANUARY		1	FEBRUARY			MARCH		
1	.10	10	.00	2.4	1	.01	.00	1	.00	
2	.09	10	.00	.78	ī	.00	.00	ī	.00	
3	.06	10	.00	2.1	ī	.03	.00	ī	.00	
4	.04	10	.00	50	12	1.8	.00	ī	.00	
5	16300	1870	305000	53	13	1.8	.00	1	.00	
6	27400	2180	362000	26	7	. 63	.00	1	.00	
7	1500	199	965	30	7	.71	.00	1	.00	
8	576	89	141	61	14	2.1	.00	1	.00	
9	360	63	62	43	11	1.3	.00	1	.00	
10	374	60	58	24	6	.42	.00	1	.00	
11	279	126	113	13	4	.15	.00	1	.00	
12	201	40	22	17	4	.21	.00	1	.00	
13	220	40	22	19	5	.23	.00	1	.00	
14	213	39	22	7.4	3	.07	.00	1	.00	
15	137	30	13	1.7	3	.01	.00	1	.00	
16	226	39	50	. 42	4	.00	.00	1	.00	
17	531	82	138	. 17	5	.00	.00	1	.00	
18	207	38	21	. 09	12	.00	.00	1	.00	
19	109	28	9.0	.06	14	.00	.00	1	.00	
20	63	25	4.4	. 03	8	.00	.00	1	.00	
21	47	25	3.2	. 02	5	.00	.00	1	.00	
22	41	25	2.7	. 03	5	.00	.01	1	.00	
23	33	25	2.1	. 02	4	.00	.00	1	.00	
24	27	24	1.7	.01	2	.00	.00	1	.00	
25	28	22	1.6	.01	1	.00	.00	1	.00	
26	30	21	1.6	.00	1	.00	.00	1	.00	
27	26	17	1.2	.00	1	.00	.46	1	. 00	
28	23	13	. 83	.00	1	.00	1.7	1	. 00	
29	24	8	. 52	.00	1	.00	.85	1	.00	
30	14	5	.21				.16	1	.00	
31	7.6	3	.06				.03	1	.00	
TOTAL	48996.89		668656.12	351.24		9.47	3.21		0.00	

RIO DE LA PLATA BASIN

50045010 RIO DE LA PLATA BELOW LA PLATA DAM, PR--Continued

SEDIMENT DISCHARGE, SUSPENDED (TONS/DAY), WATER YEAR OCTOBER 1991 TO SEPTEMBER 1992

DAY	MEAN DISCHARGE (CPS)	MEAN CONCEN- TRATION (MG/L)	SEDIMENT DISCHARGE (TONS/DAY)	MEAN Discharge (CFS)	MRAN CONCEN- TRATION (MG/L)	SEDIMENT DISCHARGE (TONS/DAY)	Mran Discharge (CFS)	MEAN CONCEN- TRATION (MG/L)	SEDIMENT DISCHARGE (TONS/DAY)
		APRIL			MAY			JUNE	
1	.01	1	.00	. 27	1	.00	105	91	26
2 3	.00	1	.00	209	12	7.0	108	55	15
4	29 20	8 5	. 84 . 37	91 13	13	3.9	91	61 56	14 6.5
5	2.9		.02	1.3	4	.22	42	45	
3	4.9	1	. 02	1.3	1	.00	24		2.9
6	.36	1	.00	10	3	.13	15	39	1.5
7	.08	1	.00	12	5	.16	8.8	37	.90
8	.02	1	.00	2.9	2	.03	7.5	37	.77
9	.00	1	.00	.36	1	.00	10	36	. 84
10	.00	<.	05 .00	. 07	1	.00	8.6	34	.88
11	.00	1	.00	.01	1	.00	160	44	16
12	.00	1	.00	.01	1	.00	183	29	17
13	.00	1	.00	.00	1	.00	294	27	18
14	.00	1	.00	.00	1	.00	309	24	20
15	.00	1	.00	.00	1	.00	172	21	12
16	.00	1	.00	1.5	1	.01	112	20	5.8
17	.00	1	.00	.47	1	.00	78	20	4.0
18	.00	1	.00	4.6	2	.07	48	20	2.9
19	.00	1	.00	158	15	12	37	20	2.0
20	6.7	3	. 15	154	20	8.2	18	18	. 92
21	95	20	5.2	430	64	148	11	16	.70
22	46	15	2.0	305	33	48	104	23	6.9
23	10	3	. 13	1020	91	1250	99	19	5.0
24	.54	1	.00	3840	411	6160	50	16	2.1
25	.05	1	.00	705	105	209	18	12	. 69
26	.00	1	.00	4520	461	10200	2.7	10	.08
27	.00	1	.00	796	105	256	.37	10	.01
28	.00	1	.00	365	62	63	.14	9	.00
29	.05	1	.00	209	44	25	.06	7	.00
30	.36	1	.00	140	40	15	.03	6	.00
31				86	39	11			
TOTAL	211.07		8.71	13074.49		18416.72	2116.20		183.39

RIO DE LA PLATA BASIN

50045010 RIO DE LA PLATA BELOW LA PLATA DAM, PR--Continued

SEDIMENT DISCHARGE, SUSPENDED (TONS/DAY), WATER YEAR OCTOBER 1991 TO SEPTEMBER 1992

DAY	MRAN Discharge (CFS)	MEAN CONCEN- TRATION (MG/L)	SEDIMENT DISCHARGE (TONS/DAY)	MEAN DISCHARGE (CFS)	MEAN CONCEN- TRATION (MG/L)	SEDIMENT DISCHARGE (TONS/DAY)	MRAN DISCHARGE (CFS)	MEAN CONCEN- TRATION (MG/L)	SEDIMENT DISCHARGE (TONS/DAY)
		JULY			August		81	PTEMBER	
1	.02	6	.00	.01	12	.00	.00	2	.00
2 3	.02 .02	5 5	.00	.00	10	.00	.00	2	.00
4	.02	5	.00	.00 .12	10 10	.00 .00	.00	2 2	.00
5	.02	5	.00	.49	9	.01	.00	2	.00
6	.01	5	.00	112	10	3.7	.01	2	.00
7	.01	5	.00	295	6	5.3	.01	2	.00
8	.02	5	.00	160	7	3.1	.00	2	.00
9	.25	5	.00	154	9	3.7	.00	2	.00
10	.12	5	.00	148	10	4.1	.00	2	.00
11	.16	5	.00	57	14	2.8	.00	2	.00
12	.19	5	.00	30	8	.70	.00	2	.00
13	.11	5	.00	29	6	.49	.00	2	.00
14 15	.11	5 5	.00	17	5	.22	.00	2	.00
13	.08	5	.00	14	5	.20	.00	2	.00
16	.12	5	.00	9.1	5	.11	.00	2	.00
17	. 14	2	.00	3.8	5 5 5	.05	.00	2	.00
18	. 12	3	.00	. 93	5	.01	.00	2	.00
19	.09	5	.00	. 13	5	.00	.07	2	.00
20	.12	5	.00	. 03	5	.00	.34	4	.00
21	.09	5 5	.00	.01	5	.00	350	6	4.6
22 23	.14	5	. 00	.00	4	.00	e371	5	e5.9
24	.10	5 5	.00	.00	3	.00	149	3	1.5
25	.13 .14	6	.00 .00	.00	3	.00	44	2	.24
	.14	•	.00	.00	2	.00	9.0	2	.06
26	.14	8	.00	. 13	2	.00	.69	2	.00
27	.10	11	.00	. 07	2	.00	.03	2	.00
28	.11	14	.00	.01	2	.00	.01	2	.00
29	.09	15	.00	.00	2	.00	.01	2	.00
30	.04	15	.00	.00	2	.00	.01	2	.00
31	.02	14	.00	.00	2	.00			
TOTAL	2.85		0.00	1030.83		24.49	924.18		12.30
YEAR	66721.81		687311.25						

....

e Estimated

50045010 RIO DE LA PLATA BELOW LA PLATA DAM, PR--Continued NATER QUALITY DATA, WATER YEAR OCTOBER 1991 TO SEPTEMBER 1992

PARTICLE-SIZE DISTRIBUTION OF SUSPENDED SEDIMENT

DATE	TIME	DIS- CHARGE, INST. CUBIC FEET PER SECOND	SEDI- MENT, SUS- PENDED (MG/L)	SEDI- MENT, DIS- CHARGE, SUS- PENDED (T/DAY)	SED. SUSP. FALL DIAM. PERCENT FINER THAN .002 MM	SED. SUSP. FALL DIAM. PERCENT FINER THAN .004 MM	SED. SUSP. FALL DIAM. PERCENT FINER THAN .008 MM
JAN 1992							
05	1909	5530	7460	111000	39	53	59
05	2219	12400	6680	230000	48	69	82
06	0359	41200	10800	1200000	31	39	43
DATE	SED. SUSP. FALL DIAM. PERCENT FINER THAN .016 MM	SED. SUSP. FALL DIAM. PERCENT FINER THAN .031 MM	SED. SUSP. SUSP. SIEVE DIAM. PERCENT FINER THÂN .062 MM	SED. SUSP. SIEVE DIAM. PERCENT FINER THAN .125 MM	SED. SUSP. SIEVE DIAM. PERCENT FINER THAN .250 MM	SED. SUSP. SIEVE DIAM. PERCENT FINER THAN .500 MM	SED. SUSP. SIEVE DIAM. PERCENT FINER THAN 1.00 MM
JAN 1992							
05	69	80	97	99	99.7	99.1	100
05	87	92	98	99	99.6	99.1	100
06	51	63	86	97	99.3	99.6	100

50045010 RIO DE LA PLATA BELOW LA PLATA DAM, PR--Continued WATER QUALITY DATA, WATER YEAR OCTOBER 1991 TO SEPTEMBER 1992 SILT AND CLAY PERCENT OF SUSPENDED SEDIMENT

DATE	TIME	STREAM- FLOW, INSTAN- TANEOUS (CFS)	SEDI- MENT, SUS- PENDED (MG/L)	SEDI- MENT, DIS- CHARGE, SUS- PENDED (T/DAY)	SED. SUSP. SIEVE DIAM. PERCENT FINER THAN .062 MM
JAN 1992					
05	1849	1280	12800	44100	86
05	2359	123000	6380	2120000	98
MAY					
26	1744	2440	218	1430	97
26	1944	2150	226	1310	96

LOCATION.--Lat 18°24'41", long 66°15'39", Hydrologic Unit 21010005, on left bank, at downstream side of bridge on Highway 2, 1.3 mi (2.1 km) downstream from Río Lajas, and 1.6 mi (2.6 km) northwest of Toa Alta, 11.3 mi (18.2 km) downstream from Puerto Rico Aqueduct and Sewer Authority reservoir.

50046000 RIO DE LA PLATA AT HIGHWAY 2 NEAR TOA ALTA, PR

DRAINAGE AREA.--208 mi² (539 km²), excludes 8.2 mi² (21.2 km²) upstream from Lago Carite, flow from which is diverted to Río Guamaní. Area at site used prior to September 25, 1984, 200 mi² (518 km²).

WATER-DISCHARGE RECORDS

PERIOD OF RECORD. -- November 1959 (measurement only), January 1960 to current year. Prior to October 1984, published as Río de la Plata at Toa Alta, PR; October 1984 to September 1988 published as 50046900.

GAGE.--Water-stage recorder. Datum of gage is 9.15 ft (2.789 m), above mean sea level. Prior to October, 1984, at site about 1.0 mi (1.6 km) upstream at mean sea level datum.

REMARKS.--Records fair except those for estimated daily discharges, which are poor. Regulation at all stages by Puerto Rico Aqueduct and Sewer Authority reservoir upstream from gage. Gage-height and precipitation satellite telemetry at station.

EXTREMES OUTSIDE PERIOD OF RECORD.--Approximate discharges and elevations of major floods, as pointed out by local residents are as follows: Sept. 13, 1928, 120,000 ft³/s (3,400 m³/s), gage height, 37.4 ft (11.40 m); June 16, 1943, 82,000 ft³/s (2,322 m³/s), gage height, 34.4 ft (10.48 m), at site 1.0 mi upstream and different datum.

		DISCHARGE	, CUBIC	FERT PER			YEAR OC	TOBER	1991 TO	sep tembe r	1992		
DAY	ост	NOV	DEC	JAN	FEB	MAF		PR	MAY	JUN	ஶ	AUG	SEP
		**		40					••		45	• •	
1 2	44 29	55 69	22 22	18 17	23 19	12 11		19 17	29 253	92 95	17 17	14 14	14 11
3	17	83	34	15	19	12		18	156	85	16	18	13
4	14	55	46	16	80	12		13	59	61	16	71	17
5	25	59	25	5850	63	12		19	29	45	17	132	18
6 7	18	27	22	15900	48	11		18	90	45	17	93	48
8	15 13	19 26	16 27	2130 766	35 38	11 15		17 15	41 27	53 55	15 23	259 163	44 19
9	14	28	33	475	49	21		14	21	50	23	163	15
10	15	24	31	569	41	13		18	20	39	18	186	22
11	13	21	21	370	30	12		23	17	73	59	85	34
12	13	24	24	246	24	11		16	15	151	33	45	17
13	13	21	23	275	22	9.3		19	13	232	29	47	15
14 15	13 15	22	29	236	24	9.3		14	14	246	35 10	116	15 14
15	15	21	21	192	20	11		12	12	186	19	63	14
16	15	24	21	151	17	11		14	248	90	30	38	18
17	14	23	24	588	15	12		13	83	70	24	29	22
18	454	23	18	233	13	16		13	67	45	19	22	17
19	92	23	18	146	14	13		13	150	43	65	21	31
20	26	29	21	104	12	12		13	276	36	155	19	311
21	19	57	37	78	10	10		13	345	43	56	19	153
22	17	232	20	57	13	11		52	542	41	25	18	429
23	14	86	19	57	12	11		43	431	86	20	17	189
24	21	160	17	51	11	8.7		22	5060	62	60	18	95
25	67	54	16	45	11	7.9)	15	805	40	37	15	51
26	45	35	16	45	9.5	8.5	;	13	4800	28	20	14	34
27	27	26	19	40	11	19		11	1010	24	29	16	24
28	3 9	23	18	38	11	133		11	444	21	35	13	22
29	61	25	19	38	11	121		12	402	19	19	12	19
30	76	24	20	e32		33		64	206	17	15	12	18
31	35		27	e29		21	-		117		14	26	
TOTAL	1293	1398	726	28807	705.5	630.7	, ,	74	15782	2173	977	1778	1749
MEAN	41.7		23.4	929	24.3	20.3			509	72.4	31.5	57.4	58.3
MAX	454	232	46	15900	80	133		64	5060	246	155	259	429
MIN	13	19	16	15	9.5	7.9		11	12	17	14	12	11
AC-FT	2560		1440	57140	1400	1250		40	31300	4310	1940	3530	3470
CFSM	.21	.23	. 12	4.65	. 12	.10		10	2.55	.36	. 16	.29	.29
IN.	.24	.26	. 14	5.36	. 13	. 12	· .	11	2.94	.40	. 18	.33	.33
e Est	timated												
STATIST	ICS OF MC	NTHLY MEAN	DATA FO	R WATER Y	BARS 1960	- 199	92, BY W	ATER	YEAR (WY))			
Mar.		466	246	4.05	400			0.7	200	100	4.45	266	200
MEAN	515	460	346	195	136	109		97	369	172	147	266 1677	329 1691
MAX (WY)	4813		1352	929 1993	409	468		22	1939	847 1970	690 1961	1979	1960
MIN	1971 35.1		1971 23. 4	1992 16.9	1989 16.0	1969 8.31			1985 7.63	11.4	13.9	16.5	19.2
(WY)	1974		23. 4 1992	1984	1983	1986			1984	1977	1976	1976	1991
SUMMARY	STATIST	CS	FOR 1	991 CALEN	DAR YEAR		FOR 19	92 WA	TER YEAR		WATER YEA	RS 1960	- 1992
ANNUAL '	TOTAL			26717			565	93.2					
ANNUAL I	MRAN			73.2				55			268		
Highest	ANNUAL B	ŒAN									824		1971
	ANNUAL ME										36.3		1977
	DAILY ME			2020	Jul 16		159	00	Jan 6		40000		9 1970
	DAILY MEA			13	Sep 11			7.9	Mar 25		2.7		7 1984
		MINIMUM		13	Oct 8		4400	9.9	Mar 20		2.9		5 1984
	ANBOUS PE						1180	00 26.39	Jan 5 Jan 5		118000 26.39		5 1992 5 1992
	ANEOUS LA	RAK STAGE						40.39	UEII 5		26.39		5 1984
	ANEOUS LA RUNOFF (A			52990			1123	00			194200	Apr 2	.J 1704
	RUNOFF (.37			1123	.77			1.34		
	RUNOFF (4.97				10.54			18.23		
	ENT EXCE			132				70			510		
50 PERC	ENT EXCE	BDS		28				23			94		
ON DEDC	DATE DYCE	ene ene		16				12			19		

12

16

90 PERCENT EXCERDS

19

50046000 RIO DE LA PLATA AT HWY 2 NR TOA ALTA, PR--Continued (National stream-quality accounting network station)

WATER-QUALITY RECORDS

PERIOD OF RECORD. -- Water years 1958 to current year

WATER-QUALITY DATA, WATER YEAR OCTOBER 1991 TO SEPTEMBER 1992

DATE	TIME	DIS- CHARGE, INST. CUBIC FEET PER SECOND	SPE- CIFIC CON- DUCT- ANCE (US/CM)	PH WATER WHOLE FIELD (STAND- ARD UNITS)	TEMPER- ATURE WATER (DEG C)	TUR- BID- ITY (NTU)	OXYGEN, DIS- SOLVED (MG/L)	OXYGEN, DIS- SOLVED (PER- CENT SATUR- ATION)	COLI- FORM, FECAL, 0.45 UM-MF (COLS./ 100 ML)	STREP- TOCOCCI FECAL, (COLS. PER 100 ML)	HARD- NESS TOTAL (MG/L AS CACO3)
OCT 1991 02 DEC	1000	30	422	7.0	26.5	4.0	6.0	86	3100	790	170
17 FRB 1992	1045	24	541	7.0	24.0	1.4	7.6	71	270	320	220
21 APR	0915	11	505	7.6	25.5	3.3	6.6	89	K91	K60	210
14 Jun	0910	14	510	7.1	26.5	2.4	6.2	77	200	K20	190
29 A UG	0930	20	414	7.6	29.0	3.2	7.0	89	K680	27	170
17	1055	31	432	7.3	29.0	10	3.3	74	K280	45	180
DATE	CALCIUM DIS- SOLVED (MG/L AS CA)	MAGNE- SIUM, DIS- SOLVED (MG/L AS MG)	SODIUM, DIS- SOLVED (MG/L AS NA)	SODIUM AD- SORP- TION RATIO	POTAS- SIUM, DIS- SOLVED (MG/L AS K)	ALKA- LINITY WAT WH TOT FET FIBLD MG/L AS CACO3	SULFATE DIS- SOLVED (MG/L AS SO4)	CHLO- RIDE, DIS- SOLVED (MG/L AS CL)	FLUO- RIDB, DIS- SOLVED (MG/L AS F)	SILICA, DIS- SOLVED (MG/L AS SIO2)	SOLIDS, RRSIDUR AT 180 DEG. C DIS- SOLVED (MG/L)
OCT 1991 02	52	9.4	20	0.7	3.4	150	18	27	0.10	14	245
DRC 17	70	11	24	0.7	2.5	200	23	34	0.20	17	313
FBB 1992 21	64	12	21	0.6	3.3	190	27	34	<0.10	15	300
APR 14	58	12	22	0.7	3.5	180	26	40	0.20	17	298
JUN 29 AUG	50	12	20	0.7	2.7	150	24	29	0.20	18	234
17	55	10	18	0.6	3.1	160	21	28	0.40	16	255
DATE	SOLIDS, SUM OF CONSTI- TUENTS, DIS- SOLVED (MG/L)	SOLIDS, DIS- SOLVED (TONS PER DAY)	NITRO- GEN, NO2+NO3 DIS- SOLVED (MG/L AS N)	NITRO- GEN, AMMONIA DIS- SOLVED (MG/L AS N)	NITRO- GEN, AMMONIA DIS- SOLVED (MG/L AS NH4)	NITRO- GEN,AM- MONIA + ORGANIC TOTAL (MG/L AS N)	PHOS- PHORUS TOTAL (MG/L AS P)	PHOS- PHORUS DIS- SOLVED (MG/L AS P)	PHOS- PHORUS ORTHO, DIS- SOLVED (MG/L AS P)	PHOS- PHATE, ORTHO, DIS- SOLVED (MG/L AS PO4)	ALUM- INUM, DIS- SOLVED (UG/L AS AL)
OCT 1991	220	10.7	0.700			2.52	0.050			0.67	10
02 DEC 17	238 304	19.7 20.5	0.790	0.080 <0.010	0.10	0.50	0.250 0.190	0.240	0.220	0.67	
FRB 1992	293	8.83	0.510	0.100	0.13	1.0	0.170	0.120	0.100	0.31	20
APR 14	291	11	0.870	0.070	0.09	0.60	0.230	0.190	0.170	0.52	
JUN 29	248	12.8	0.290	0.030	0.04	0.60	0.080	0.080	0.060	0.18	60
AUG 17	255	21.3	0.490	0.140	0.18	0.40	0.120	0.090	0.090	0.28	10

K = non-ideal count

50046000 RIO DE LA PLATA AT HWY 2 NR TOA ALTA, PR--Continued (National stream-quality accounting network station)

WATER-QUALITY DATA, WATER YEAR OCTOBER 1991 TO SEPTEMBER 1992

DATE	BARIUM, DIS- SOLVED (UG/L AS BA)	COBALT, DIS- SOLVED (UG/L AS CO)	IRON, DIS- SOLVED (UG/L AS FE)	LITHIUM DIS- SOLVED (UG/L AS LI)	MANGA- NESE, DIS- SOLVED (UG/L AS MN)	MOLYB- DENUM, DIS- SOLVED (UG/L AS MO)	NICKEL, DIS- SOLVED (UG/L AS NI)	SKLE- NIUM, DIS- SOLVED (UG/L AS SE)	SILVER, DIS- SOLVED (UG/L AS AG)	STRON- TIUM, DIS- SOLVED (UG/L AS SR)	VANA- DIUM, DIS- SOLVED (UG/L AS V)
OCT 1991											
02 DEC	53	<3	11	<4	60	<10	<1	<1	<1.0	210	<6
17 FEB 1992											
21 APR	54	<3	<3	5	24	<10	3	<1	<1.0	270	<6
14 JUN											
29 AUG	51	<3	4	<4	99	<10	<1	<1	<1.0	220	10
17	62	<3	10	<4	130	<10	2	<1	<1.0	220	<6

50046000 RIO DE LA PLATA AT HWY 2 NR TOA ALTA, PR--Continued (National stream-quality accounting network station)

WATER-QUALITY DATA, WATER YEAR OCTOBER 1990 TO SEPTEMBER 1991

PARTICLE-SIZE DISTRIBUTION OF SUSPENDED SEDIMENT

DATE	TIME	STREAM- FLOW, INSTAN- TANEOUS (CFS)	SEDI- MENT, SUS- PENDED (MG/L)	SEDI- MENT, DIS- CHARGE, SUS- PENDED (T/DAY)	SED. SUSP. SIEVE DIAM. PERCENT FINER THAN .062 MM
OCT 1991					
02	1000	30	32.7	2.65	92
DEC 1992 17	1045	24	113	7.32	64
FEB					
21	0915	11	61.8	1.84	90
APR 14	0910	14	68	2.57	91
JUN	0310	14	68	2.57	31
29	0930	20	17	0.92	96
AUG					
17	1055	31	28	2.34	100

PESTICIDE ANALYSES

DATE	TIME	PCB, TOTAL (UG/L)	ALDRIN, TOTAL (UG/L)	CHLOR- DANE, TOTAL (UG/L)	DDD, TOTAL (UG/L)	DDE, TOTAL (UG/L)	DDT, TOTAL (UG/L)	DI- AZINON, TOTAL (UG/L)	DI- BLDRIN TOTAL (UG/L)	ENDO- SULFAN, TOTAL (UG/L)
JUN 1992 29	0930	<0.1	<0.010	<0.1	<0.010	<0.010	<0.010	<0.01	<0.010	<0.010

DATE	ENDRIN WATER UNFLTRD REC	ETHION, TOTAL	HEPTA- CHLOR, TOTAL	HEPTA- CHLOR BPOXIDE TOTAL	LINDANE TOTAL	MALA- THION, TOTAL	MRTH- OXY- CHLOR, TOTAL	MRTHYL PARA- THION, TOTAL	MIREX, TOTAL
	(UG/L)	(UG/L)	(UG/L)	(UG/L)	(UG/L)	(UG/L)	(UG/L)	(UG/L)	(UG/L)
JUN 1992									
29	<0.010	<0.01	<0.010	<0.010	<0.010	<0.01	<0.01	<0.01	<0.01
DATE	PARA- THION, TOTAL (UG/L)	NAPH- THA- LENES, POLY- CHLOR. TOTAL (UG/L)	PER- THANE TOTAL (UG/L)	TOX- APHENE, TOTAL (UG/L)	TOTAL TRI- THION (UG/L)	2,4-D, TOTAL (UG/L)	2,4,5-T TOTAL (UG/L)	2, 4-DP TOTAL (UG/L)	SILVEX, TOTAL (UG/L)
JUN 1992 29	<0.01	<0.10	<0.1	<1	<0.01	<0.01	<0.01	<0.01	<0.01
	-0.01	-0.IV	40.1	*1	~0.01	-0.01	-0.01	-0.01	-0.01




Figure 19.-Río Hondo to Río Puerto Nuevo basins.

RIO HONDO BASIN

50047530 RIO HONDO AT FLOOD CHANNEL NEAR CATAÑO, PR

WATER-QUALITY RECORDS

LOCATION.--Lat 18°26'13", long 66°09'36", at Río Hondo Channel, 800 ft (245 m) below junction with Río Hondo, 0.9 mi (1.5 km) downstream from bridge on de Diego Expressway and 1.1 mi (1.8 km) above mouth.

DRAINAGE ARRA. -- Indeterminate.

PERIOD OF RECORD .-- Water years 1979 to current year.

WATER-QUALITY DATA, WATER YEAR OCTOBER 1991 TO SEPTEMBER 1992

			W	ATER-QU	ALITY	DATA, W	ATER Y	YBAR	OCTOB	ER 1	991 T	O SE	PTRMB	ER 1	992				
DATE		TIME	DIS CHARG INST CUBI FEE PER SECO	E, SPI	FIC N- CT-	PH WATER WHOLE FIELD (STAND- ARD UNITS)	WAT		TO BI IT (NT	Y	OXYG DI SOL' (MG	S-	OXYG DI SOL (PE CE SAT	S- VED R- NT UR-	OXYG DEMA CHE ICA (HI LEVE (MG/	ND, M- L GH L)	COLI FORM FECA 0.45 UM-M (COLS 100 M	L,	STREP- TOCOCCI FECAL, (COLS. PER 100 ML)
NOV 1991																			
01 JAN 1992		0805	25		3900	7.6		24.5	24			1.7		34		24	320	00	47000
02		0810		1	7000	7.5		23.0	3	.1		4.4		30		250	590	00	31000
MAR 02		1030			5600	7.9		27.5		. 5		B.O		68		620	260	00	4900
MAY		1030		3.	3600	7.3		47.5		. 5		0.0		0.0		020	200	00	4300
32 JUL		0845	34		1300	7.1		27.0	27			2.5		32		68	820	00	35000
10		1005			9900	7.6		30.0	6	.2		6.0		47		120	270	00	8900
DATE		HARD- NESS TOTAL (MG/L AS CACO3)	HARD NESS NONCA WH WA TOT F MG/L CACO	RB CALC	CIUM S- LVED 3/L CA)	MAGNE- SIUM, DIS- SOLVED (MG/L AS MG)	(MC	5 -	SOR	ON	POT. SI DI: SOL: (MG	UM, S- VRD /L	ALK LINI WAT TOT FIR MG/L CAC	TY WH FET LD AS	SULF TOT (MG AS	AL /L	SULFA DIS- SOLV (MG/ AS SO	ED L	CHLO- RIDE, DIS- SOLVED (MG/L AS CL)
NOV 1991																			
01 JAN 1992		260	17	0	14	37		300		8	1	5		100	<0	.5	8	7	520
02							-		- 2	_	-	-		200	_	_			
MAR 02										_	_			150	_				
MAY			- 77						-					130					-
22 JUL		440	30	0 !	59	72		540		14	2	8		140	<0	. 5	17	0	980
10					-				-	-	-	-		140	-	-			
		R	LUO- IDE, DIS- OLVED	SILICA, DIS- SOLVED (MG/L	CON	STI- NTS, S	LIDS, DIS- OLVED TONS	AT DEC	IDUE AL 105 L. C,	NIT	TRO- EN, RATE	NIT	TRO- EN, RITE	NO2	TRO- EN, +NO3 TAL			NIT GE ORGA TOT	N, NIC
	DATE		MG/L S F)	AS SIO2)			PER DAY)		IDED IG/L)	(M	G/L N)		G/L N)		G/L N)	(MC		(MG AS	
NOV	1991	L																	
	1		0.10	8.8		1070	72		28	0	.410	0	.060	0	.470	0.	340	0	.76
	1992								19	0	.090	0	. 070	0	.160	2.	00	0	. 50
MAR																			
MAY	2					:			30	0	.100	0	.090	0	.190	1.	20	0	.0
	2		0.30	12		1960	180		18	0	.500	0	.070	0	.570	0.	220	0	. 58
10	0				10				26			0	.020	<0	.050	0.	400	0	. 80

RIO HONDO BASIN
50047530 RIO HONDO AT FLOOD CHANNEL NEAR CATAÑO, PR--Continued

WATER-QUALITY DATA, WATER YEAR OCTOBER 1991 TO SEPTEMBER 1992

DATE	NITRO- GEN, AM- MONIA + ORGANIC TOTAL (MG/L AS N)	NITRO- GEN, TOTAL (MG/L AS N)	NITRO- GEN, TOTAL (MG/L AS NO3)	PHOS- PHORUS TOTAL (MG/L AS P)	ARSENIC TOTAL (UG/L AS AS)	BARIUM, TOTAL RECOV- ERABLE (UG/L AS BA)	BORON, TOTAL RECOV- ERABLE (UG/L AS B)	CADMIUM TOTAL RECOV- ERABLE (UG/L AS CD)	CHRO- MIUM, TOTAL RECOV- ERABLE (UG/L AS CR)	COPPER, TOTAL RECOV- ERABLE (UG/L AS CU)	
NOV 1991											
01 JAN 1992	1.1	1.6	6.9	0.330	7	80	120	<1	<1	12	
02 MAR	2.5	2.7	12	0.660							
02 May	1.2	1.4	6.2	0.410							
22 Jul	0.80	1.4	6.1	0.220	4	100	220	1	3	10	
10	1.2			0.500							
DATE	IRON, TOTAL RECOV- ERABLE (UG/L	LEAD, TOTAL RECOV- ERABLE (UG/L	MANGA - NESE, TOTAL RECOV- ERABLE (UG/L	MERCURY TOTAL RECOV- ERABLE (UG/L	SELE- NIUM, TOTAL (UG/L	SILVER, TOTAL RECOV- ERABLE (UG/L	ZINC, TOTAL RECOV- ERABLE (UG/L	CYANIDE TOTAL (MG/L	PHENOLS TOTAL	METHY- LENE BLUE ACTIVE SUB- STANCE	
	AS FB)	AS PB)	AS MON)	AS HG)	AS SE)	AS AG)	AS ZN)	AS CN)	(UG/L)	(MG/L)	
NOV 1991	-		AS MN)	AS HG)	AS SR)	AS AG)	AS ZN)	AS CN)	(UG/L)	(MG/L)	
NOV 1991 01 JAN 1992	AS FR)	AS PB)									
01 JAN 1992 02	-		AS MN)	AS HG)	AS SR)	AS AG)	AS ZN)	AS CN)	(UG/L)	(MG/L)	
01 JAN 1992 02 MAR 02	1500	8	AS MN)	AS HG)	AS SB)	AS AG)	AS ZN)	AS CN)	(UG/L)	(MG/L)	
01 JAN 1992 02 MAR	1500	8	AS MON)	0.20	AS SR)	AS AG) <1	AS ZN)	AS CN) <0.010	(UG/L) 2 	(MG/L) 0.12	s

50047550 LAGO CIDRA AT DAMSITE NEAR CIDRA, PR

LOCATION. -- Lat 18°11'57", long 66°08'29", Hydrologic Unit 21010005, at Lago de Cidra Dam on Río de Bayamón, 1.9 mi (3.0 km) northeast of Plaza de Cidra and 1.8 mi (2.9 km) northwest of Escuela Segunda Unidad de Bayamón.

DRAINAGE AREA. -- 8.26 mi2 (21.39 km2).

RIRVATION RECORDS

PERIOD OF RECORD. -- January 1988 to current year.

GAGE .-- Water-stage recorder. Datum of gage is mean sea level.

REMARKS.--Lago de Cidra was completed in 1946. The maximum storage is 5,300 ac-ft (6.53 hm²) and provides supplemental water to metropolitan San Juan. The dam is a concrete gravity and earthfill structure approximately 541 ft (165 m) long between abutments with a maximum structural height of about 78.7 ft (24.0 m). The spillway portion of the dam, length 131 ft (40 m) and crest elevation 1,322 ft (403 m), is an ungated ogee crest located 131 ft (40 m) from the right abutment. This dam is owned by Puerto Rico Aqueduct and Sewer Authority. Gage-height and precipitation satellite telemetry at station.

EXTREMES OBSERVED FOR PERIOD OF RECORD.--Maximum elevation 1,323.99 ft (403.55 m), Feb. 3, 1988; minimum elevation 1,305.18 ft (397.82 m), Sept. 30, 1990.

EXTREMES OBSERVED FOR CURRENT YEAR. -- Maximum elevation, 1,322.29 ft (403.03 m), Jan. 14; minimum elevation, 1,311.00 ft (399.59 m), Sept. 19.

Capacity Table (based on data from Puerto Rico Electric Power Authority)

Elevation, in feet	Contents, in acre-feet	Elevation, in feet	Contents, in acre-feet
1,305	1,970	1,319	4,400
1,309	2,610	1,322	5,200
1,312	3,100	1,324	5,800

ELEVATION (FRET NGVD), WATER YEAR OCTOBER 1991 TO SEPTEMBER 1992 DAILY OBSERVATION AT 24:00 VALUES

DAY	OCT	NOV	DEC	JAN	FEB	MAR	APR	MAY	JUN	JUL	AUG	SEP
1	1311.73	1311.40	λ	1314.51	1321.49	1319.83	1316.36	1313.46	1316.44	1317.34	1315.44	1312.92
2	1311.92	1311.33	λ	1314.37	1321.31	1319.66	1316.51		1316.45	1317.40	1315.37	1312.68
3	1312.08	1311.32	λ	1314.21	1321.12	1319.53	1316.40	1313.54	1316.48	1317.43	1315.27	1312.48
4	1312.16	1311.21	À	1314.04	1321.05	1319.41	1316.28	1313.50	1316.54	1317.38	1315.25	1312.32
5	1312.21	1311.15	λ	A	1321.01	1319.29	1316.15	1313.43	1316.52	1317.36	1315.76	1312.30
						2020120	2020123					
6	1312.27	1311.13	λ	λ	1320.99	1319.16	1315.98	1313.38	1316.41	1317.33	1316.34	1312.30
7	1312.31	1311.81	À	A	1320.96	1319.05	1315.78	1313.29	1316.35	1317.32	1316.51	1312.17
8	λ	A	λ	À	1320.92	1318.92	1315.62	1313.21	1316.45	1317.33	1316.53	1312.06
9	λ	À	À	À	1320.89	1318.78	1315.45	1313.15		1317.29	1316.50	1312.09
10	λ	À	À	À	1320.88	1318.67	1315.27	1313.09	1316.76	1317.20	1316.41	1311.96
					101000	2020.07	1010.1.	1010.00	1010170			1011.70
11	λ	λ	λ	λ	1320.85	1318.59	1315.15	1313.01	1316.98	1317.14	1316.22	1311.82
12	À	λ	1314.56	λ	1320.81	1318.51	1315.07	1312.97		1317.01	1316.11	1311.67
13	Ä	λ	1314.81	λ	1320.77	1318.40	1315.05	1312.96	1317.37	1316.97	1316.01	1311.49
14	À	λ	1314.67	1322.22	1320.73	1318.33	1315.03	1312.95	1317.52	1316.90	1315.92	1311.31
15	Ä	Ä	1314.56	1322.02	1320.66	1318.26	1315.01	1312.96	1317.59	1316.84	1315.83	1311.15
			1514.50	1322.02	1520.00	1510.20	1313.01	1312.70	1317.33	1510.04	1313.63	1311.13
16	1312.28	λ	1314.63	1321.92	1320.62	1318.21	1314.95	1312.98	1317.67	1316.93	1315.67	1311.09
17	1312.23	λ	1314.72	1321.89	1320.58	1318.18	1314.89	1313.01	1317.76	1316.97	1315.45	1311.12
18	1312.19	Ä	1314.78	1321.84	1320.52	1318.14	1314.81	1312.99	1317.85	1316.87	1315.30	1311.07
19	1312.17	λ	1314.84	1321.79	1320.47	1318.17	1314.89	1312.96	1317.86	1316.80	1315.20	1311.27
20	1312.10	Ä	1315.08	1321.74	1320.43	1318.04	1314.85	1312.95	1317.78	1316.72	1315.09	1311.99
	10120110	••	1313.00	1321.74	1320.43	1310.04	1314.03	1312.93	1317.70	1310.72	1313.03	1311.33
21	1312.00	λ	1315.17	1321.66	1320.36	1317.87	1314.78	1313.35	1317.90	1316.61	1314.94	1312.75
22	1311.94	λ	1315.27	1321.56	1320.39	1317.72	1314.74	1313.42		1316.54	1314.77	1313.11
23	1311.84	λ	A	1321.46	1320.43	1317.58	1314.61	1314.25	1317.92	1316.58	1314.61	1313.44
24	1311.78	λ	A A	1321.37	1320.36	1317.42	1314.39	1314.92	1317.91	1316.68	1314.41	1313.67
25	1311.74	1312.93	Ä	1321.36	1320.25	1317.25	1314.15	1315.35	1317.95	1316.64	1314.19	1313.83
	2022174	1312.73		1321.30	1320.23	1317.23	1314.13	1313.33	1317.33	1310.04	1314.19	1313.03
26	1311.68	1313.12	λ	1321.35	1320.22	1317.09	1313.92	1315.83	1317.89	1316.60	1314.05	1313.88
27	1311.61	1313.33	λ	1321.32	1320.15	1316.93	1313.70	1315.99	1317.81	1316.55	1313.91	1313.85
28	1311.43	A	λ	1321.32	1320.07	1316.90	1313.60	1316.09	1317.64	1316.32	1313.74	1313.83
29	1311.31	λ	1315.07	1321.40	1319.95	1316.75	1313.50	1316.19	1317.54	1316.03	1313.50	1313.86
30	1311.38	Ä	1314.89	1321.45		1316.60	1313.46	1316.30	1317.43	1315.78	1313.31	1313.90
31	1311.36		1314.73	1321.50		1316.47	1313.40	1316.37		1315.60	1313.17	7313.30
						1310.4/		1310.37		1313.00	1313.17	
MEAN					1320.66	1318.18	1315.01	1313.91	1317.28	1316.85	1315.19	1312.45
MAX					1321.49	1319.83	1316.51	1316.37	1317.99	1317.43	1316.53	1313.90
MIN					1319.95	1316.47	1313.46	1312.95	1316.35	1315.60	1313.17	1311.07
						,						

A No gage-height record.

50047560 RIO DE BAYAMON BELOW LAGO CIDRA, PR

LOCATION.--Lat 18°12'04", long 66°08'26", Hydrologic Unit 21010005, 0.2 mi (0.3 km) downstream of Lago Cidra Dam on right bank, 2.1 mi (3.4 km) northwest of Plaza de Cidra.

DRAINAGE AREA. -- 8.31 mi 2 (21.5 km2).

WATER-DISCHARGE RECORDS

PERIOD OF RECORD. -- November 1990 to current year.

GAGE.--Water-stage recorder. Elevation of gage is 1,279 ft (390 m), from topographic map.

REMARKS.--Records poor. Regulation at all stages by Puerto Rico Aqueduct and Sewer Authority reservoir upstream from gage. Gage-height and precipitation satellite telemetry at station.

	DI	SCHARGE,	CUBIC FEE		OND, WATER DAILY MEAN		rober 1991	l TO SEPTI	EMBRR 199	2		
DAY	OCT	NOA	DEC	JAN	FEB	MAR	APR	MAY	JUN	JUL	AUG	SEP
1	22	32	4.3	84	e27	28	19	7.5	e12	28	9.2	33
2	23	32	103	74	41	35	20	7.8	17	2.8	1.9	39
3	24	32	36	63	28	29	19	7.6	e9. 9	14	1.8	30
4	23	33	7.5	77	22	27	19	7.6	e 6.8	20	1.8	13
5	24	21	7.6	154	19	26	18	7.5	e25	20	5.6	10
6	23	4.7		981		0.0	27		37	• •	60	10
7	31	9.8	7.5 7.6	119	19 19	26 26	35	11 24	31	14 11	.60 .65	9.5
8	17	8.7	7.8	23	20	26	30	21	8.6	11	.64	10
ğ	17	5.6	7.9	12	20	27	28	9.3	8.3	20	.72	10
10	17	6.2	7.9	24	21	22	28	9.6	8.7	24	12	9.8
11 12	18 18	7.6 9.5	8.2 8.5	12 9.2	21 21	16 16	29 28	9.6 9.3	8.2 8.2	28 32	28 6.3	9.6 9.6
13	18	85	64	9.8	21	15	24	9.1	8.0	26	6.3	18
14	18	119	116	22	22	16	21	9.6	7.8	23	6.8	24
15	18	128	88	41	22	15	21	9.5	7.6	23	7.0	11
16	18	125	3.6	30	23	15	24	12	7.5	12	17	12
17	18	122	3.5	12	23	15	17	27	7.2	9.5	28	11
18	18	111	3.6	7.1	24	15	17	16	6.6	27	15	15
19 20	19 20	104 82	3.6 5.1	7.0 7.1	24 25	e10 27	28 27	14 11	28 36	27 26	4.5	22 11
20	20	64	3.1	7.1	45	41	21	11	30	20	4.7	
21	19	85	4.1	12	e24	38	22	12	17	27	12	5.4
22	19	42	4.2	13	e 3.6	34	10	10	11	27	15	1.9
23	12	3.0	4.4	13	e11	27	19	15	35	8.1	15	1.6
24	2.5	4.0	4.1	e21	40	27	31	e9.0	14	2.9	23	1.6
25	2.9	3.4	4.7	e2.7	32	27	31	e 3,8	16	19	26	11
26	2.7	3.4	3.7	e3.3	27	26	30	e4 . 4	27	14	14	25
27	7.7	3.9	21	e2. 6	26	26	30	64.1	34	14	13	32
28	61	4.1	106	e2.9	26	26	16	64.4	34	31	40	18
29	43	4.0	100	e2.7	26	26	14	e4 . 4	23	31	40	7.9
30	33 29	4.0	97	e2.6		26	7.2	e3.8	34	21 15	24 16	8.1
31	49		91	e2.6		21		e4 . 4		15	10	
TOTAL	635.8	1234.9	941.4	1846.6	677.6	736	689.2	315.3	534.4	608.3	396.51	430.0
MBAN	20.5	41.2	30.4	59.6	23.4	23.7	23.0	10.2	17.8	19.6	12.8	14.3
MAX	61	128	116	981	41	38	35	27	37	32	40	39
MIN	2.5	3.0	3.5	2.6	3.6	10	7.2	3.8	6.6	2.8	.60	1.6
AC-FT	1260	2450	1870	3660	1340	1460	1370	625	1060	1210	786	853
CFSM	2.47	4.95	3.65	7.16	2.81	2.85	2.76	1.22	2.14	2.36	1.54	1.72
IN.	2.84	5.52	4.21	8.26	3.03	3.29	3.08	1.41	2.39	2.72	1.77	1.92
e Ba	stimated											
STATIST	CICS OF 1	MONTHLY ME	AN DATA I	FOR WATER	YBARS 1991	- 1992,	BY WATER	YBAR (WY)			
MEAN	20.5	40.8	21.4	37.3	29.8	18.5	17.6	11.2	15.0	15.6	20.2	15.2
MAX	20.5	41.2	30.4	59.6	36.5	23.7	23.0	12.2	17.8	19.6	27.5	16.0
(WY)	1992	1992	1992	1992	1991	1992	1992	1991	1992	1992	1991	1991
MIN	20.5	40.5	12.4	14.9	23.4	13.4	12.2	10.2	12.1	11.7	12.8	14.3
(WY)	1992	1991	1991	1991	1992	1991	1991	1992	1991	1991	1992	1992
SUMMARY	estatis:	rics	FOR	1991 CALE	NDAR YEAR	F	OR 1992 W	ATER YEAR		WATER 1	TEARS 1991	- 1992
ANNUAL	TOTAL			7515.0			9046.0	1				
ANNUAL	MEAN LANNUAL	MRAN		20.6			24.7			24.7		1992
	ANNUAL									24.		1992
	DAILY			193	Feb 6		981	Jan 6		981		6 1992
	DAILY M			2.5				0 Aug 6				6 1992
ANNUAL	SEABN-D	MUMINIM YA		3.7			1.7	Aug 3		1.) Aug	3 1992
		PEAK FLOW					1540	Jan 6		1540		6 1992
		PEAK STAGE	3				15.3			15.3		6 1992
		LOW FLOW		440				0 Aug 6		47040		6 1992
	RUNOFF			14910	2		17940			17910		
	RUNOFF			2.4			2.9			40.3		
	RUNOFF CENT BXC			33.6 37	v		40.49 36	•		35	,•	
	CENT EXC			13			17			13		
	CENT BXC			8.4			4.0			7.9	5	
											-	

50047560 RIO DE BAYAMON BELOW LAGO CIDRA, PR--Continued

WATER-QUALITY RECORDS

PERIOD OF RECORDS. -- Water years 1991 to current year.

INSTRUMENTATION. -- DH-48 and automatic sediment sampler.

PERIOD OF DAILY RECORD. --

SUSPENDED-SEDIMENT DISCHARGE: November 1990 to September 1992

EXTREMES FOR PERIOD OF DAILY RECORD. -SEDIMENT CONCENTRATION: Maximum daily mean, 3,670 mg/L Jan. 05, 1992; Minimum daily mean,
6 mg/L Sep. 01, 1991.

SEDIMENT LOADS: Maximum daily mean, 9,830tons (8,920tonnes) Jan. 05, 1992; Minimum daily mean, 0.04 ton (0.03 tonne) Aug 09-10, 1992.

EXTREMES FOR WATER YEARS 1991-92.--

Water Year	Suspended-sediment maximum	concentration (mg/L) minimum	Suspended-sediment discharge maximum	(tons per day) minimum
1991	778 (Feb. 12)	6 (Sep. 01)	338 (Feb. 05)	.19 (Sep. 10)
1992	3,670 (Jan. 06)	8 (Sep. 11)	9,830 (Jan. 06)	.04 (Aug. 09-10)

DAY	MRAN DISCHARGE (CFS)	MEAN CONCEN- TRATION (MG/L)	SEDIMENT DISCHARGE (TONS/DAY)	MEAN DISCHARGE (CFS)	MEAN CONCEN- TRATION (MG/L)	SEDIMENT DISCHARGE (TONS/DAY)	MEAN DISCHARGE (CFS)	MEAN CONCEN- TRATION (MG/L)	SEDIMENT DISCHARGE (TONS/DAY)
		OCTOBER		1	NOVEMBER		I	DECEMBER	
1				13	33	1.2	e12	56	e1.8
2				12	33	1.1	e13	51	e1.7
3				13	33	1.2	e13	51	e1.8
4				28	33	2.8	e13	48	e1.6
5				28	45	3.5	13	46	1.6
6				28	55	4.2	13	51	1.8
7				26	62	4.4	13	61	2.1
8				28	62	4.7	13	63	2.2
9				28	62	4.7	13	65	2.3
10				29	62	4.9	13	65	2.2
11				29	62	4.9	13	67	2.3
12				29	62	4.9	12	66	2.1
13				52	62	8.7	13	71	2.4
14				60	62	10	13	71	2.4
15				60	60	9.7	12	65	2.1
16				62'	60	10	12	55	1.8
17				e55	60	e8.9	12	46	1.4
18				e55	60	e8. 9	12	43	1.3
19				e 60	60	e9. 7	11	45	1.3
20				₩60	60	e 9.7	11	53	1.5
21				e55	60	e8.9	12	54	1.7
22				e 60	60	e 9.7	12	44	1.4
23				e60	60	e 9.7	12	44	1.4
24				e60	60	e 9.7	12	49	1.5
25				e55	60	e8.9	11	45	1.3
26				e55	60	e8.9	10	41	1.1
27				e55	60	e8.9	11	40	1.2
28				e35	60	e5.7	11	32	.90
29				e13	60	e2.1	12	25	. 80
30				e12	60	e1. 9	12	26	.79
31							20	524	42
TOTAL				1215		192.5	385		91.79

e Estimated

169

50047560 RIO DE BAYAMON BELOW LAGO CIDRA, PR--Continued

DAY	MRAN DISCHARGE (CFS)	MEAN CONCEN- TRATION (MG/L)	SEDIMENT DISCHARGE (TONS/DAY)	MEAN DISCHARGE (CFS)	MEAN CONCEN- TRATION (MG/L)	SEDIMENT DISCHARGE (TONS/DAY)	MEAN DISCHARGE (CFS)	MRAN CONCEN- TRATION (MG/L)	SEDIMENT DISCHARGE (TONS/DAY)
		JANUARY		1	FRBRUARY			MARCH	
1	12	189	5.9	14	38	1.4	12	75	2.5
2	20	109	6.3	13	32	1.1	13	64	2.3
3	18	7 7	3.7	12	25	.82	13	54	2.0
4	16	54	2.3	13	24	.83	17	50	2.2
5	16	44	1.8	143	423	388	16	48	2.2
6	16	43	1.8	193	47	26	17	44	2.1
7	16	41	1.8	73	45	9.1	18	36	1.8
8	18	34	1.5	38	45	4.8	19	23	1.2
9	19	22	1.1	25	45	3.1	19	11	.57
10	19	12	.60	17	44	2.1	14	10	.38
11	18	8	.40	30	42	3.5	11	10	.31
12	17	9	.39	64	778	337	11	14	.41
13	15	10	. 37	120	426	199	11	21	. 63
14	15	13	.49	50	19	2.9	11	27	. 81
15	16	18	.74	26	27	2.0	12	34	1.1
16	15	20	.84	17	42	2.1	12	38	1.2
17	15	18	. 69	13	54	2.1	12	38	1.2
18	14	14	. 53	14	54	2.2	13	35	1.2
19	14	13	.46	20	49	2.9	13	33	1.1
20	12	13	.40	19	47	2.6	13	34	1.1
21	12	11	.35	18	45	2.3	13	39	1.4
22	12	11	. 35	16	46	2.2	14	40	1.3
23	12	13	.40	15	48	2.1	13	38	1.3
24	12	15	. 47	14	48	2.0	13	32	1.1
25	13	17	. 58	14	54	2.1	13	24	.81
26	13	18	. 64	11	65	2.0	12	16	. 50
27	13	18	.61	10	74	2.2	12	11	.34
28	13	19	. 67	11	79	2.6	12	23	.73
29	14	25	. 93				12	48	1.5
30	14	33	1.3				11	61	1.8
31	14	39	1.4				12	53	1.7
TOTAL	463		39.81	1023		1011.05	414		38.79

RIO DE BAYAMON BASIN

50047560 RIO DE BAYAMON BELOW LAGO CIDRA, PR--Continued

SEDIMENT DISCHARGE, SUSPENDED (TONS/DAY), WATER YEAR OCTOBER 1990 TO SEPTEMBER 1991

		MEAN			MRAN			MBAN	
DAY	MEAN DISCHARGE (CFS)	CONCEN- TRATION (MG/L)	SEDIMENT DISCHARGE (TONS/DAY)	MEAN Discharge (CFS)	CONCEN- TRATION (MG/L)	SEDIMENT DISCHARGE (TONS/DAY)	MEAN DISCHARGE (CFS)	CONCEN- TRATION (MG/L)	SEDIMENT DISCHARGE (TONS/DAY)
		APRIL			MAY			JUNE	
1	11	45	1.3	13	34	1.1	13	22	. 69
2	11	22	.61	13	20	.70	13	18	.56
3	11	32	.91	13	20	.68	13	18	. 59
4	10	49	1.3	13	21	.68	13	20	. 67
5	10	61	1.6	13	29	.99	13	20	. 67
6	12	61	1.8	13	29	.98	13	25	. 84
7	12	53	1.7	14	26	. 92	12	54	1.7
8	12	50	1.6	14	22	.78	12	70	2.1
9	12	53	1.7	13	19	.59	12	54	1.7
10	12	55	1.8	11	17	.50	12	37	1.2
11	12	57	1.8	11	15	.44	12	24	.77
12	12	57	2.0	11	14	.37	12	26	. 82
13	13	53	1.8	11	13	.37	13	38	1.2
14	13	49	1.7	11	12	.34	13	46	1.6
15	13	47	1.6	11	11	.32	12	47	1.5
16	12	45	1.5	11	11	.31	12	46	1.4
17	13	41	1.4	12	10	.30	11	43	1.3
18	13	38	1.2	12	10	.33	12	31	. 92
19	12	26	. 85	11	10	.28	12	22	. 64
20	12	21	. 68	12	10	.32	12	21	. 67
21	13	26	. 92	11	15	.43	12	20	.61
22	13	31	1.1	12	25	.75	12	19	.60
23	13	25	. 81	12	40	1.3	12	17	. 55
24	13	22	.74	12	55	1.8	12	57	1.7
25	13	27	.91	15	48	2.0	12	57	1.7
26	13	33	1.1	12	35	1.1	11	81	2.4
27	13	39	1.3	11	23	. 69	11	76	2.3
28	13	45	1.6	12	20	.61	11	49	1.4
29	13	49	1.6	13	25	.79	12	25	.76
30	12	48	1.5	12	29	.94	12	15	. 45
31				12	27	. 86			
TOTAL	367		40.43	377		22.57	364		34.01

171

50047560 RIO DE BAYAMON BELOW LAGO CIDRA, PR--Continued

DAY	MEAN DISCHARGE (CFS)	MEAN CONCEN- TRATION (MG/L)	SEDIMENT DISCHARGE (TONS/DAY)	MBAN Discharge (CPS)	MEAN CONCEN- TRATION (MG/L)	SEDIMENT DISCHARGE (TONS/DAY)	MEAN DISCHARGE (CFS)	MEAN CONCEN- TRATION (MG/L)	SEDIMENT DISCHARGE (TONS/DAY)
		JULY			AUGUST		Si	EPTEMBER	
1	11	14	.42	14	19	.70	13	6	. 22
2	11	13	.39	14	21	.75	14	7	.26
3	11	12	. 36	15	28	1.1	13	8	.27
4	11	12	. 36	16	35	1.6	13	7	.27
5	11	12	. 37	15	40	1.6	12	7	. 26
6	11	13	. 37	16	39	1.6	12	7	. 23
7	11	13	. 37	16	34	1.4	11	6	.20
8	11	13	. 37	17	30	1.3	12	7	.21
9	11	14	.40	16	33	1.4	12	7	.21
10	11	16	.46	17	38	1.7	12	6	.19
11	11	16	.46	17	41	1.9	12	7	.22
12	11	16	.46	19	38	1.9	32	20	2.3
13	10	14	.36	30	31	2.6	23	18	1.3
14	11	12	.34	49	25	3.3	11	11	.31
15	14	21	1.0	49	37	4.6	12	11	. 32
16	21	103	27	41	30	3.3	12	13	.43
17	9.4	41	. 97	23	30	2.0	26	373	164
18	9.5	43	1.1	18	28	1.3	14	49	1.9
19	10	39	1.1	47	22	2.8	15	34	1.4
20	11	35	. 99	45	18	2.2	15	31	1.2
21	11	30	. 89	46	17	2.1	16	22	. 97
22	11	26	.80	55	27	4.6	17	14	. 67
23	11	22	. 66	43	25	2.9	17	11	. 52
24	11	19	. 57	37	18	1.8	18	14	. 63
25	11	17	. 52	37	18	1.8	18	16	.71
26	12	15	. 52	28	17	1.4	18	17	.79
27	14	15	.56	24	13	.84	19	19	. 95
28	13	16	.56	20	15	.81	20	20	1.0
29	14	16	.56	29	7	.52	20	20	1.0
30	13	17	. 62	26	5	.37	21	20	1.2
31	13	18	. 65	14	5	.20			
TOTAL	361.9		44.56	853		56.39	480		184.14

RIO DE BAYAMON BASIN
50047560 RIO DE BAYAMON BELOW LAGO CIDRA, PR--Continued

DAY	MRAN DISCHARGE (CFS)	MEAN CONCEN- TRATION (MG/L)	SEDIMENT DISCHARGE (TONS/DAY)	MEAN DISCHARGE (CFS)	MRAN CONCEN- TRATION (MG/L)	SEDIMENT DISCHARGE (TONS/DAY)	MEAN DISCHARGE (CFS)	MEAN CONCEN- TRATION (MG/L)	SEDIMENT DISCHARGE (TONS/DAY)
		OCTOBER			OVEMBER	• • • • •		DECEMBER	
_									
1 2	22	29	1.6	32	22	1.8	4.3	30 28	.33 7.6
	23	28	1.7	32	22	1.8	103 36	28 30	2.8
3 4	24	28	1.8	32	22	1.8	7.5	30 39	.76
5	23 24	27 26	1.6 1.7	33 21	22 25	1.9 1.3	7.5	40	. 82
5	24	26	1.7	21	25	1.3	7.0	40	.04
6	23	26	1.6	4.7	20	.23	7.5	40	.80
7	31	232	82	9.8	29	.98	7.6	38	.79
8	17	31	1.4	8.7	28	.68	7.8	32	. 66
9	17	25	1.1	5.6	28	.43	7.9	29	. 62
10	17	26	1.1	6.2	28	.46	7.9	28	. 59
11	18	27	1.2	7.6	31	. 63	8.2	30	. 66
12	18	29	1.3	9.5	32	.93	8.5	30	.70
13	18	30	1.3	85	38	8.2	64	49	12
14	18	30	1.4	119	40	13	116	20	6.2
15	18	30	1.4	128	42	14	88	20	4.8
16	18	30	1.4	125	45	15	3.6	20	.20
17	18	30	1.4	122	100	32	3.5	20	.19
18	18	30	1.4	111	52	15	3.6	25	.23
19	19	29	1.5	104	50	14	3.6	27	.23
20	20	27	1.4	82	44	10	5.1	26	. 33
21	19	24	1.2	85	39	8.8	4.1	34	.39
22	19	25	1.3	42	37	3.9	4.2	59	. 62
23	12	30	.98	3.0	38	.30	4.4	72	.88
24	2.5	37	.26	4.0	47	.53	4.1	61	. 68
25	2.9	40	. 32	3.4	51	.44	4.7	50	. 60
26	2.7	38	.31	3.4	56	.51	3.7	50	.51
27	7.7	35	. 67	3.9	59	.57	21	53	2.9
28	61	35	5.7	4.1	55	.55	106	56	16
29	43	35	3.8	4.0	44	.46	100	55	15
30	33	272	44	4.0	40	.42	97	53	14
31	29	30	2.3				91	51	12
TOTAL	635.8		170.14	1234.9		150.62	941.4		104.89

50047560 RIO DE BAYAMON BELOW LAGO CIDRA, PR--Continued

DAY	MRAN DISCHARGE (CFS)	MEAN CONCEN- TRATION (MG/L)	SEDIMENT DISCHARGE (TONS/DAY)	MEAN DISCHARGE (CFS)	MRAN CONCEN- TRATION (MG/L)	SEDIMENT DISCHARGE (TONS/DAY)	MEAN DISCHARGE (CFS)	MEAN CONCEN- TRATION (MG/L)	SEDIMENT DISCHARGE (TONS/DAY)
		JANUARY		I	BBRUARY			MARCH	
1	84	49	11	e2 7	102	e7.1	28	63	4.6
2	74	50	9.7	41	100	10	35	61	5.8
3	63	52	8.8	28	98	7.2	29	58	4.8
4	77	51	10	22	92	5.7	27	53	3.7
5	154	1170	976	19	84	4.3	26	53	3.7
6	981	3670	9830	19	83	4.2	26	58	4.0
7	119	1140	600	19	92	4.7	26	61	4.3
8	23	111	7.1	20	104	5.5	26	60	4.2
9	12	102	3.6	20	107	5.8	27	54	3.8
10	24	94	5.7	21	96	5.3	22	48	2.7
11	12	92	3.0	21	80	4.4	16	47	2.0
12	9.2	91	2.1	21	67	3.6	16	47	1.9
13	9.8	90	2.5	21	62	3.4	15	45	1.8
14	22	91	5.3	22	62	3.5	16	48	1.9
15	41	135	15	22	62	3.6	15	53	2.1
16	30	183	15	23	62	3.7	15	58	2.3
17	12	184	6.3	23	61	3.8	15	55	2.2
18	7.1	177	3.2	24	60	3.8	15	49	2.1
19	7.0	173	3.2	. 24	63	4.0	e 10	45	e1.2
20	7.1	166	3.0	25	68	4.5	27	53	3.7
21	12	156	4.8	e24	70	e4 .6	38	83	8.3
22	13	149	5.2	e 3.6	75	e.68	34	97	8.3
23	13	146	5.1	e11	76	e2. 5	27	79	5.7
24	e21	145	e8.6	40	77	8.4	27	63	4.4
25	e2. 7	145	e1.1	32	71	5.8	27	49	3.4
26	e3.3	148	e1.3	27	68	4.9	26	41	2.9
27	e 2.6	151	e1.1	26	64	4.5	26	39	2.7
28	e 2.9	151	e1.2	26	63	4.3	26	36	2.5
29	e 2.7	134	e. 98	26	64	4.4	26	38	2.6
30	e 2.6	113	e.79				26	41	2.9
31	e2. 6	107	e.75				21	44	2.6
TOTAL	1846.6		11551.42	677.6		138.18	736		109.1

e Estimated

RIO DE BAYAMON BASIN

50047560 RIO DE BAYAMON BELOW LAGO CIDRA, PR--Continued

SEDIMENT DISCHARGE, SUSPENDED (TONS/DAY), WATER YEAR OCTOBER 1991 TO SEPTEMBER 1992

DAY	MEAN DISCHARGE (CFS)	MEAN CONCEN- TRATION (MG/L)	SEDIMENT DISCHARGE (TONS/DAY)	MEAN DISCHARGE (CFS)	MEAN CONCEN- TRATION (MG/L)	SEDIMENT DISCHARGE (TONS/DAY)	MEAN DISCHARGE (CFS)	MBAN CONCEN- TRATION (MG/L)	SEDIMENT DISCHARGE (TONS/DAY)
		APRIL			MAY			JUNE	
1	19	46	2.2	7.5	63	1.3	e12	52	e1.6
2	20	46	2.5	7.8	68	1.4	17	43	2.0
3	19	46	2.3	7.6	62	1.2	e 9.9	32	e.86
4	19	45	2.3	7.6	49	.94	e6.8	26	e.43
5	18	45	2.2	7.5	41	.78	e25	21	e1.4
6	27	43	3.3	11	43	1.3	37	20	1.9
7	35	42	3.9	24	50	3.2	31	18	1.5
8	30	41	3.4	21	57	3.3	8.6	19	.42
9	28	43	3.2	9.3	52	1.3	8.3	20	. 44
10	28	53	4.0	9.6	45	1.1	8.7	27	. 66
11	29	67	5.2	9.6	40	.97	8.2	45	.94
12	28	75	5.8	9.3	39	.96	8.2	75	1.6
13	24	71	4.6	9.1	40	.99	8.0	73	1.5
14	21	60	3.3	9.6	42	1.0	7.8	63	1.3
15	21	51	2.8	9.5	46	1.2	7.6	52	. 99
16	24	45	2.7	12	52	1.6	7.5	42	.87
17	17	41	1.9	27	59	4.5	7.2	33	. 65
18	17	40	1.8	16	61	2.8	6.6	33	. 54
19	28	40	2.8	14	70	2.9	28	32	2.3
20	27	41	2.9	11	62	1.7	36	30	2.9
21	22	42	2.4	12	46	1.6	17	31	1.4
22	10	44	1.2	10	30	.82	11	31	. 97
23	19	42	2.1	15	38	1.6	35	29	2.7
24	31	40	3.3	e9.0	63	e1.5	14	29	1.1
25	31	40	3.2	e3.8	117	e1.2	16	26	1.1
26	30	30	2.4	e4.4	108	e1.3	27	23	1.7
27	30	34	2.7	e4.1	71	e.78	34	21	1.9
28	16	36	1.6	e4.4	62	e.73	34	18	1.6
29	14	44	1.7	e4.4	60	e.72	23	15	1.0
30	7.2	53	1.0	e3.8	61	e.63	34	15	1.3
31				e4.4	60	e.71			
TOTAL	689.2		84.7	315.3		46.03	534.4		39.57

e Estimated

175

50047560 RIO DE BAYAMON BELOW LAGO CIDRA, PR--Continued

	MEAN DISCHARGE	MEAN CONCEN- TRATION	SEDIMENT DISCHARGE	MEAN DISCHARGE	MEAN CONCEN- TRATION	SEDIMENT DISCHARGE	MEAN DISCHARGE	MEAN CONCEN- TRATION	SEDIMENT DISCHARGE
DAY	(CFS)	(MG/L)	(TONS/DAY)	(CFS)	(MG/L)	(TONS/DAY)	(CFS)	(MG/L)	(TONS/DAY)
		JULY			AUGUST		SI	SP TEMBE R	
1	28	15	1.1	9.2	31	.57	33	32	2.8
2	2.8	15	.11	1.9	94	.45	39	38	3.9
3	14	15	.58	1.8	94	.43	30	36	3.1
4 5	20	14	.76	1.8	42	.20	13	28	1.1
5	20	14	.74	5.6	36	.56	10	20	.53
6	14	13	.54	.60	35	.05	10	30	.76
7	11	12	.34	. 65	29	.05	9.5	47	1.1
8	11	12	. 35	. 64	25	.04	10	47	1.3
9	20	16	. 86	.72	21	.04	10	12	.37
10	24	16	. 98	12	21	. 62	9.8	9	. 23
11	28	16	1.1	28	22	1.7	9.6	8	.21
12	32	14	1.2	6.3	23	.38	9.6	9	.23
13	26	12	. 86	6.3	23	.36	18	9	.41
14	23	12	.72	6.8	20	.36	24	9	. 57
15	23	12	.72	7.0	20	. 37	11	9	.25
16	12	14	.41	17	18	.84	12	10	.31
17	9.5	31	. 87	28	17	1.2	11	10	.30
18	27	50	3.6	15	16	.68	15	29	1.5
19	27	59	4.1	4.5	18	.22	22	45	3.3
20	26	51	3.6	4.7	18	.22	11	37	1.3
21	27	37	2.6	12	18	.56	5.4	47	. 68
22	27	26	1.8	15	18	.68	1.9	45	.22
23	8.1	19	.50	15	18	.68	1.6	45	.20
24	2.9	14	. 09	23	15	. 85	1.6	40	.18
25	19	11	. 60	26	13	. 82	11	38	1.1
26	14	8	.28	14	10	.41	25	35	2.3
27	14	7	.26	13	9	.28	32	32	2.8
28	31	4	.31	40	9	. 95	18	28	1.4
29	31	5	.39	40	10	1.1	7.9	25	.50
30	21	6 6	.34	24	10	. 68	8.1	25	.52
31	15	6	. 23	16	18	.73			
TOTAL	608.3		30.94	396.51		17.08	430.0		33.47
YEAR	9046.01		12476.14						

50047560 RIO DE BAYAMON BELOW LAGO CIDRA PR--Continued

WATER QUALITY DATA, WATER YEARS JANUARY 1991 TO SEPTEMBER 1992

PARTICLE-SIZE DISTRIBUTION OF SUSPENDED SEDIMENT

DATE	TIMB	DIS- CHARGE, INST. CUBIC FEBT PER SECOND	SRDI - MENT, SUS- PENDED (MG/L)	SEDI- MENT, DIS- CHARGE, SUS- PENDED (T/DAY)	SED. SUSP. FALL DIAM. PERCENT FINER THAN .002 MM	SED. SUSP. FALL DIAM. PERCENT FINER THAN .004 MM	SED. SUSP. FALL DIAM. PERCENT FINER THAN .008 MM
JAN 1991							
04	1753	15	2930	119	38	46	51
13	1730	14	405	15	62		75
FEB							
05	1640	310	7700	64500	35	54	65
JUL							
16 SRP	0750	78	1530	322	55	59	67
17	0859	238	7370	4730	37	52	63
OCT	0037	230	7370	4730	3,	34	63
07	1640	215	4990	2900	49	61	67
30	1500	93	5080	1280		13	15
	SED.	SED.	SED.	SED.	SED.	SED.	SED.
	SUSP.	SUSP.	SUSP.	SUSP.	SUSP.	SUSP.	SUSP.
					_ 352.		

	SED.						
	SUSP.						
	FALL	FALL	SIEVE	SIRVE	SIEVE	SIEVE	SIEVE
	DIAM.						
	PERCENT						
	FINER						
DATE	THAN						
	.016 MM	.031 MM	.062 MM	.125 MM	.250 MM	.500 MM	1.00 MM
JAN 1991							
04	64	75	96	99	99.5	100	100
13		85	95	97	98	99	99
FEB							
05	73	81	94	98	99.4	99.6	99.8
JUL							
16	77	80	99	99.2	99.5	99.7	100
SRP							
17	71	78	98	99.4	99.6	99.7	100
OCT							
07	76	86	99	99.5	99.7	100	100
30	~ -	17	25	25	99	100	100

50047560 RIO DE BAYAMON BELOW LAGO CIDRA , PR--Continued WATER QUALITY DATA, WATER YEAR OCTOBER 1991 TO SEPTEMBER 1992 SILT AND CLAY PERCENT OF SUSPENDED SEDIMENT

DATE	TIME	STREAM- PLOW, INSTAN- TANEOUS (CFS)	SEDI- MENT, SUS- PENDED (MG/L)	SEDI- MENT, DIS- CHARGE, SUS- PENDED (T/DAY)	SED. SUSP. SIEVE DIAM. PERCENT FINER THAN .062 MM
OCT 1991					
04	1520	12	389	13	87
07	1800	60	330	53	99
30	1400	276	2320	1730	99
NOV					
21	1606	100	53	14	95
21	1846	113	197	60	97
DEC					
13	1215	120	118	38	84
JAN 1992					
07	1605	26	130	9	90
28	1722	6	156	3	92
MAY					
16	1505	16	423	18	58
SRP					
17	1420	10	725	20	96

50047600 RIO DE BAYAMON NEAR AGUAS BUENAS, PR

WATER-QUALITY RECORDS

LOCATION.--Lat 18°14'39", long 66°08'39", at bridge on Highway 156, and 2.9 mi (4.7 km) west of Aguas Buenas plaza.

DRAINAGE ARRA. -- 18.5 mi 2 (47.9 km2).

PERIOD OF RECORD. -- Water years 1958-65, 1974 to current year.

WATER-QUALITY DATA, WATER YEAR OCTOBER 1991 TO SEPTEMBER 1992

DATE	TIME	DIS- CHARGE, INST. CUBIC FEET PER SECOND	SPR- CIFIC CON- DUCT- ANCE (US/CM)	PH WATER WHOLE FIELD (STAND- ARD UNITS)	TEMPER- ATURE WATER (DEG C)	TUR- BID- ITY (NTU)	OXYGEN, DIS- SOLVED (MG/L)	OXYGEN, DIS- SOLVED (PER- CENT SATUR- ATION)	OXYGEN DEMAND, CHEM- ICAL (HIGH LEVEL) (MG/L)	COLI- FORM, FECAL, 0.45 UM-MF (COLS./ 100 ML)	STREP- TOCOCCI FECAL, (COLS. PER 100 ML)
OCT 1991											
15	1430	17	297	8.2	25.5	3.0	8.5	106	16	340	410
DEC 11	1100	11	329	8.0	21.0	1.7	6.5	79	11	K10	330
FEB 1992	1100	11	349	8.0	21.0	1.7	0.5	13	11	KIU	330
24	1315	49	233	7.9	22.0	25	8.3	101	10	6000	17000
APR											
20	1120	36	218	7.1	23.0	180	7.3	86	27	54000	53000
JUN 10	1145	20	205		25.0					400	K1300
AUG	1142	20	295	8.1	25.0	7.9	8.1	99	<10	490	K1300
06	0940	30	213	6.9	23.0	200	6.9	83	31	1300	130000

DATE	HARD- NESS TOTAL (MG/L AS CACO3)	CALCIUM DIS- SOLVED (MG/L AS CA)	MAGNE- SIUM, DIS- SOLVED (MG/L AS MG)	SODIUM, DIS- SOLVED (MG/L AS NA)	SODIUM AD- SORP- TION RATIO	POTAS- SIUM, DIS- SOLVED (MG/L AS K)	ALKA- LINITY WAT WH TOT FET FIELD MG/L AS CACO3	SULFIDE TOTAL (MG/L AS S)	SULFATE DIS- SOLVED (MG/L AS SO4)	CHLO- RIDE, DIS- SOLVED (MG/L AS CL)
OCT 1991										
15 DEC	110	26	11	17	0.7	2.3	110	<0.5	12	20
11 FBB 1992							130			
24 APR							120			
20	140	37	12	29	1	3.2	140	<0.5	25	32
JUN 10 AUG							110			
06	77	18	7.8	10	0.5	3.1	59		17	24
	FLUO-	SILICA,	SOLIDS,	solids,	RESIDUE TOTAL	NITRO-	NITRO-	NITRO-	NITRO-	NITRO-
DATE	RIDE, DIS- SOLVED (MG/L AS F)	DIS- SOLVED (MG/L AS SIO2)	CONSTI- TUENTS, DIS- SOLVED (MG/L)	DIS- SOLVED (TONS PER DAY)	AT 105 DEG. C, SUS- PENDED (MG/L)	GEN, NITRATE TOTAL (MG/L AS N)	GEN, NITRITE TOTAL (MG/L AS N)	GEN, NO2+NO3 TOTAL (MG/L AS N)	GEN, AMMONIA TOTAL (MG/L AS N)	GEN, ORGANIC TOTAL (MG/L AS N)
ОСТ 1991 15	RIDE, DIS- SOLVED (MG/L	SOLVED (MG/L AS	TUENTS, DIS- SOLVED	SOLVED (TONS PER	DEG. C, SUS- PENDED	GEN, NITRATE TOTAL (MG/L	NITRITE TOTAL (MG/L	NO2+NO3 TOTAL (MG/L	AMMONIA TOTAL (MG/L	ORGANIC TOTAL (MG/L
OCT 1991 15 DEC 11	RIDE, DIS- SOLVED (MG/L AS F)	SOLVED (MG/L AS SIO2)	TUENTS, DIS- SOLVED (MG/L)	SOLVED (TONS PER DAY)	DEG. C, SUS- PENDED (MG/L)	GEN, NITRATE TOTAL (MG/L AS N)	NITRITE TOTAL (MG/L AS N)	NO2+NO3 TOTAL (MG/L AS N)	AMMONIA TOTAL (MG/L AS N)	ORGANIC TOTAL (MG/L AS N)
OCT 1991 15 DEC 11 FEB 1992 24	RIDE, DIS- SOLVED (MG/L AS F)	SOLVED (MG/L AS SIO2)	TUENTS, DIS- SOLVED (MG/L)	SOLVED (TONS PER DAY)	DEG. C, SUS- PENDED (MG/L)	GEN, NITRATE TOTAL (MG/L AS N)	NITRITE TOTAL (MG/L AS N)	NO2+NO3 TOTAL (MG/L AS N)	AMMONIA TOTAL (MG/L AS N)	ORGANIC TOTAL (MG/L AS N)
OCT 1991 15 DRC 11 FEB 1992 24 APR 20	RIDE, DIS- SOLVED (MG/L AS F)	SOLVED (MG/L AS SIO2)	TUENTS, DIS- SOLVED (MG/L)	SOLVED (TONS PER DAY) 8.47	DEG. C, SUS- PENDED (MG/L)	GEN, NITRATE TOTAL (MG/L AS N)	NITRITE TOTAL (MG/L AS N) <0.010	NO2+NO3 TOTAL (MG/L AS N) 0.360 0.620	AMMONIA TOTAL (MG/L AS N) 0.020 0.010	ORGANIC TOTAL (MG/L AS N) 0.18
OCT 1991 15 DEC 11 FEB 1992 24	RIDE, DIS- SOLVED (MG/L AS F)	SOLVED (MG/L AS SIO2) 27	TUENTS, DIS- SOLVED (MG/L) 181	SOLVED (TONS PER DAY) 8.47	DEG. C, SUS- PENDED (MG/L) <1 10	GEN, NITRATE TOTAL (MG/L AS N)	NITRITE TOTAL (MG/L AS N) <0.010 <0.010 0.020	NO2+NO3 TOTAL (MG/L AS N) 0.360 0.620 0.290	AMMONIA TOTAL (MG/L AS N) 0.020 0.010 0.030	ORGANIC TOTAL (MG/L AS N) 0.18 0.19 0.27

K = non-ideal count

RIO DE BAYAMON BASIN

50047600 RIO DE BAYAMON NEAR AGUAS BUENAS, PR--Continued WATER-QUALITY DATA, WATER YEAR OCTOBER 1991 TO SEPTEMBER 1992

DATE	NITRO- GEN, AM- MONIA + ORGANIC TOTAL (MG/L AS N)	NITRO- GEN, TOTAL (MG/L AS N)	NITRO- GEN, TOTAL (MG/L AS NO3)	PHOS- PHORUS TOTAL (MG/L AS P)	ARSENIC TOTAL (UG/L AS AS)	BARIUM, TOTAL RECOV- ERABLE (UG/L AS BA)	BORON, TOTAL RECOV- ERABLE (UG/L AS B)	CADMIUM TOTAL RECOV- ERABLE (UG/L AS CD)	CHRO- MIUM, TOTAL RECOV- ERABLE (UG/L AS CR)	COPPER, TOTAL RECOV- ERABLE (UG/L AS CU)
OCT 1991										
15 DEC	0.20	0.56	2.5	0.050	<1	<100	60	<1	2	<10
11 FEB 1992	0.20	0.82	3.6	0.050						
24 APR	0.30	0.59	2.6	0.060						
20 JUN	0.70	1.5	6.5	0.100	<1	<100	60	<1	13	40
10 A UG	0.20	0.50	2.2	0.020						
06	0.80	2.4	11	0.170						
DATE	IRON, TOTAL RECOV- ERABLE (UG/L AS FE)	LEAD, TOTAL RECOV- ERABLE (UG/L AS PB)	MANGA- NESE, TOTAL RECOV- ERABLE (UG/L AS MN)	MERCURY TOTAL RECOV- ERABLE (UG/L AS HG)	SELE- NIUM, TOTAL (UG/L AS SE)	SILVER, TOTAL RECOV- ERABLE (UG/L AS AG)	ZINC, TOTAL RECOV- ERABLE (UG/L AS ZN)	CYANIDE TOTAL (MG/L AS CN)	PHENOLS TOTAL (UG/L)	MRTHY- LENR BLUE ACTIVE SUB- STANCE (MG/L)
OCT 1991	TOTAL RECOV- ERABLE (UG/L AS FE)	TOTAL RECOV- ERABLE (UG/L AS PB)	NESE, TOTAL RECOV- ERABLE (UG/L AS MN)	TOTAL RECOV- ERABLE (UG/L AS HG)	NIUM, TOTAL (UG/L AS SE)	TOTAL RECOV- ERABLE (UG/L AS AG)	TOTAL RECOV- ERABLE (UG/L AS ZN)	TOTAL (MG/L AS CN)	TOTAL (UG/L)	LENR BLUR ACTIVE SUB- STANCE (MG/L)
OCT 1991 15 DEC	TOTAL RECOV- ERABLE (UG/L	TOTAL RECOV- ERABLE (UG/L	NESR, TOTAL RECOV- ERABLE (UG/L	TOTAL RECOV- ERABLE (UG/L AS HG)	NIUM, TOTAL (UG/L AS SE)	TOTAL RECOV- BRABLE (UG/L	TOTAL RECOV- ERABLE (UG/L	TOTAL (MG/L	TOTAL	LENR BLUR ACTIVR SUB- STANCE
OCT 1991 15 DEC 11 FEB 1992	TOTAL RECOV- ERABLE (UG/L AS FE)	TOTAL RECOV- ERABLE (UG/L AS PB)	NESE, TOTAL RECOV- ERABLE (UG/L AS MN)	TOTAL RECOV- ERABLE (UG/L AS HG)	NIUM, TOTAL (UG/L AS SE)	TOTAL RECOV- ERABLE (UG/L AS AG)	TOTAL RECOV- ERABLE (UG/L AS ZN)	TOTAL (MG/L AS CN)	TOTAL (UG/L)	LENR BLUR BLUR ACTIVE SUB- STANCE (MG/L) 0.03
OCT 1991 15 DEC 11 FEB 1992 24	TOTAL RECOV- ERABLE (UG/L AS FE)	TOTAL RECOV- ERABLE (UG/L AS PB)	NESE, TOTAL RECOV- ERABLE (UG/L AS MN)	TOTAL RECOV- ERABLE (UG/L AS HG)	NIUM, TOTAL (UG/L AS SE)	TOTAL RECOV- ERABLE (UG/L AS AG)	TOTAL RECOV- ERABLE (UG/L AS ZN)	TOTAL (MG/L AS CN)	TOTAL (UG/L)	LENR BLUR ACTIVE SUB- STANCE (MG/L)
OCT 1991 15 DEC 11 FEB 1992	TOTAL RECOV- ERABLE (UG/L AS FE)	TOTAL RECOV- ERABLE (UG/L AS PB)	NESE, TOTAL RECOV- ERABLE (UG/L AS MN)	TOTAL RECOV- ERABLE (UG/L AS HG) <0.10	NIUM, TOTAL (UG/L AS SE)	TOTAL RECOV- ERABLE (UG/L AS AG)	TOTAL RECOV- ERABLE (UG/L AS ZN)	TOTAL (MG/L AS CN) <0.010	TOTAL (UG/L)	LENR BLUR BLUR ACTIVE SUB- STANCE (MG/L) 0.03
OCT 1991 15 DBC 11 FEB 1992 24 APR 20	TOTAL RECOV- ERABLE (UG/L AS FE)	TOTAL RECOV- ERABLE (UG/L AS PB)	NESE, TOTAL RECOV- ERABLE (UG/L AS MN)	TOTAL RECOV- ERABLE (UG/L AS HG)	NIUM, TOTAL (UG/L AS SE)	TOTAL RECOV- RRABLE (UG/L AS AG) <1	TOTAL RECOV- ERABLE (UG/L AS ZN)	TOTAL (MG/L AS CN) <0.010	TOTAL (UG/L)	LENE BLUR ACTIVE SUB- STANCE (MG/L) 0.03

50047850 RIO BAYAMON NR BAYAMON, PR

LOCATION.--Lat 18°20'08", long 66°08'13", Hydrologic Unit 21010005, on left bank, at rock quarry near Highway 174, 1.3 mi (2.1 km) south of colonia Santa Rosa and 4.7 mi (7.6 km) south of Bayamón.

DRAINAGE AREA. --41.8 mi 2 (108.3 km2).

WATER-DISCHARGE RECORDS

PERIOD OF RECORD. -- September 1964 to October 1970, June 1988 to current year.

GAGE. -- Water-stage recorder and crest-stage gage. Elevation of gage is 98 ft (30 m), from topografic map.

REMARKS.--Records fair except those for estimated daily discharges, which are poor. Diversion to the Guaynabo water treatment plant, for municipal supply, made upstream from station (at Represa de San Juan). Flow is regulated by storage and release of water at Lago de Cidra (capacity 5,220 acre-ft), 10.5 mi (16.9 km) upstream. Gage-height and precipitation satellite telemetry at station.

•		DISCHA	RGE, CUB	C FEET PER			YEAR OCTOBER VALUES	1991 TO	SEPTEMBER	1992		
DAY	OCT	NOV	DEC	JAN	FEB	MAR	APR	MAY	JUN	JOL	AUG	SEP
1 2 3 4 5	15 12 9.8 7.6 9.2	47 35 19 20 17	10 10 16 23 14	8.8 8.0 7.6 7.5	e8.6 e8.4 e8.6 e8.8 e8.4	e8.5 e8.5 e8.4 e8.4	19 18 8.6	123 87 19 12	19 16 15 14 13	7.4 7.5 7.5 7.6 7.8	7.0 7.0 7.2 9.2 71	19 18 18 21 26
6 7 8 9 10	7.3 29 59 7.5 6.0	17 29 121 67 17	11 10 10 10 9.8	811 69 23 17 25	e8.4 e8.4 e8.4 e8.8	e8.4 e8.4 e8.3 e8.3	8.1 8.8 8.8	13 11 9.0 8.8 9.2	13 15 17 18 14	7.6 7.2 11 14 9.5	103 19 19 271 89	37 25 17 15
11 12 13 14 15	5.8 5.7 5.6 5.8 6.5	12 10 10 9.5 9.0	8.8 11 9.4 13 e10	17 15 15 14 14	e8.8 e8.2 e8.2 e8.4 e8.0	e8.2 8.2 8.0 7.8 7.8	8.8 8.8 8.1	8.2 8.1 8.1 7.9 7.4	15 12 12 12 11	9.5 9.1 8.8 9.6	52 46 41 48 41	13 11 30 16 11
16 17 18 19 20	5.7 5.6 8.3 7.1 6.7	13 11 9.4 8.8 8.5	8.8 8.8 8.4 15	32 38 14 e13 e12	e8.0 e8.0 e8.0 e8.4 e8.0	7.8 8.4 9.2 8.6 8.0	7.9 8.0 8.1	57 22 25 29 25	10 10 9.6 9.4 9.1	8.5 8.3 7.8 8.3 7.9	36 32 30 29 30	12 15 12 78 105
21 22 23 24 25	7.0 6.4 6.3 6.2 6.2	23 56 34 103 19	61 12 11 8.9 8.4	e11 e11 e10 e10	e8.0 e9.4 e8.4 e9.0 e8.4	8.0 8.0 8.0 7.8	7.6 7.5 7.5	38 39 66 181 33	16 11 9.3 8.6 8.4	7.6 7.2 7.4 17 8.3	28 27 25 23 23	58 15 18 9.9 8.9
26 27 28 29 30 31	6.2 11 7.7 6.4 51 39	16 15 18 14 13	8.2 10 9.7 9.0 8.6 8.6	e10 e9.8 e9.9 e9.2 e9.2 e8.8	e8.8 e8.5 e8.5 e8.5	7.8 8.8 75 19 9.1 8.3	7.4 7.5 24 26	122 51 30 23 20 18	8.2 8.2 8.0 7.7 7.4	6.9 9.4 7.5 6.5 6.0 6.4	23 24 21 20 20 24	8.5 8.3 7.5 7.1 7.2
TOTAL MEAN MAX MIN AC-FT CFSM IN.	378.6 12.2 59 5.6 751 .29	801.2 26.7 121 8.5 1590 .64	381.2 12.3 61 8.2 756 .29	2539.8 81.9 1270 7.5 5040 1.96 2.26	245.1 8.45 9.4 8.0 486 .20	333.8 10.8 75 7.8 662	300.8 10.0 26 7.4 597	1120.7 36.2 181 7.4 2220 .86 1.00	356.9 11.9 19 7.4 708 .28	266.1 8.58 17 6.0 528 .21	1245.4 40.2 271 7.0 2470 .96 1.11	662.4 22.1 105 7.1 1310 .53
	timated	. /1	.34	2.20	.22	. 30	.27	1.00	.34	.24	1.11	
STATIST	ICS OF M	ONTHLY ME.	AN DATA	FOR WATER Y	EARS 1964	- 199	2, BY WATER	YBAR (WY)			
MBAN MAX (WY) MIN (WY)	37.7 129 1991 4.30 1969	50.3 174 1970 7.91 1965	49.5 263 1966 5.19 1968	40.2 159 1969 5.30 1968	23.7 75.3 1989 4.75 1965	20.3 52.9 1990 3.58 1965	72.7 1971 5.36	48.1 131 1966 6.88 1967	21.2 60.8 1970 4.26 1967	21.3 46.6 1970 5.98 1967	46.1 137 1970 15.0 1991	44.2 146 1989 6.02 1967
SUMMARY	STATIST	ics	FOR	1991 CALEN	DAR YEAR		FOR 1992 WA	TER YEAR		WATER Y	TEARS 1964	- 1992
LOWEST		BAN		7003.7 19.2 750	Jul 16		8632.0 23.6	Jan 5		35.2 59.7 12.1 5500	, L	1966 1968 9 1970
Lowest Annual Instant Instant Annual	DAILY ME SEVEN-DA ANEOUS P	AN Y MINIMUM BAK FLOW BAK STAGE AC-FT)		5.2 5.8 13890 .46	Sep 15 Oct 11		5.6 5.8 6980 14.18 17120	Oct 13 Oct 11 Jan 5 Jan 5		2.2 2.4 28000 20.2 25480	April April Oct	19 1965 14 1965 9 1970 9 1970
ANNUAL 10 PERC 50 PERC	RUNOFF (ENT EXCE ENT EXCE	inches) Eds Eds		6.23 28 10 7.1			7.68 36 9.5 7.5			11.4 61 13 4.8		

50047990 RIO GUAYNABO NEAR BAYAMON, PR

WATER-QUALITY RECORDS

LOCATION.--Lat 18°22'32", long 66°07'59", at bridge on Highway 833, 0.2 mi (0.3 km) upstream from Río de Bayamón, and 2.3 mi (3.7 km) southeast of Bayamón plaza.

DRAINAGE AREA. -- 73.2 mi2 (189.6 km2).

PERIOD OF RECORD. -- Water years 1958, 1964, 1971-73, 1976, 1979 to current year.

WATER-QUALITY DATA, WATER YEAR OCTOBER 1991 TO SEPTEMBER 1992

			WAT	RK-OOVTIL	DATA, WA	TEK ARWE	C OCTOB	RK 1991 1	O SEPTEM	BEK 19:	92		
DATE		TIMB	DIS- CHARGE, INST. CUBIC FEET PER SECOND	SPE- CIFIC CON- DUCT- ANCE (US/CM)	PH WATER WHOLE FIELD (STAND- ARD UNITS)	TEMPER- ATURE WATER (DEG C)	BI: IT	D- DI Y SOL	D: SOI EN, (PI S- CI VED SA'	is- i Lved ER- Ent Tur- i	DXYGEN DEMAND, CHEM- ICAL (HIGH LEVEL) (MG/L)	COLI- FORM, FECAL, 0.7 UM-MF (COLS./ 100 ML)	STREP- TOCOCCI FECAL, KF AGAR (COLS. PER 100 ML)
OCT 1991													
17		1400	25	461	7.7	28.0) 13		4.8	70	22	3500	K200
31 FRB 1992		1115	28	420	7.5	22.5	19		5.0	79	13	2200	6100
25 APR		1200	41	438	7.6	23.9	5 6	. 4	5.4	82	16	5300	23000
23 JUN		1250	20	506	7.1	29.0) 3	. 2	3.3	43	37	3000	716
25		0815	30	470	7.3	28.0) 3	. 2	3.1	42	11	K1100	K200
AUG 06		1150	75	278	7.2	27.5	22		4.0	54	15	4800	13000
DATE	N T (IARD- IESS OTAL (MG/L AS (ACO3)	HARD- NESS NONCARB WH WAT TOT FLD MG/L AS CACO3	CALCIUM DIS- SOLVED (MG/L AS CA)	MAGNE- SIUM, DIS- SOLVED (MG/L AS MG)	SODIUM, DIS- SOLVED (MG/L AS NA)	SOR: TI RAT:	D- SI P- DI ON SOL	VED FIR	TTY WH	SULFIDE TOTAL (MG/L AS S)	SULFATE DIS- SOLVED (MG/L AS SO4)	CHLO- RIDB, DIS- SOLVED (MG/L AS CL)
OCT 1991 17		170	4	46	13	30		1 3	. 7	160	<0.5	12	40
DEC 31					~-		-	_	_	150			
FRB 1992 25					~-		_		_	150			
APR													
23 JUN		160	7	44	13	30		1 4	. 5	170	<0.5	21	43
25							-		-	150			~-
AUG 06		180	12	49	13	30		1 3	. 4	180		17	39
17 DBC 31 FBB 25 APR 23 JUN 25 AUG	1 1992 5 3	RI E SO (M AS	DE, DIS- SI	LICA, SUNIS- CON DLVED TUE MG/L I AS SO	STI -	JIDS, TO DIS- AT DLVRD DE CONS S PER PE	SSIDUE DTAL 105 8G. C, SUS- SNDED (MG/L) 5 35 10 17	NITRO- GEN, NITRATE TOTAL (MG/L AS N) 0.440 0.450 0.460 0.350 0.240	NITRO- GEN, NITRITE TOTAL (MG/L AS N) 0.030 0.040 0.030 0.050 0.060	TOTA (MG, AS 1 0.4 0.4 0.4	N, G NO3 AMM AL TO /L (M N) AS 170 0 190 0 190 0 100 1	EN, C ONIA ORC TAL TO G/L ()	OTRO- SEN, SANIC DTAL GC/L 3 N) 0.89 0.31 0.30 0.70 0.70
•	. • • •							7.520					·

K = non-ideal count

RIO DE BAYAMON BASIN 50047990 RIO GUAYNABO NEAR BAYAMON, PR--Continued

WATER-QUALITY DATA, WATER YEAR OCTOBER 1991 TO SEPTEMBER 1992

DATE	NITRO- GEN, AM- MONIA + ORGANIC TOTAL (MG/L AS N)	NITRO- GEN, TOTAL (MG/L AS N)	NITRO- GEN, TOTAL (MG/L AS NO3)	PHOS- PHORUS TOTAL (MG/L AS P)	ARSENIC TOTAL (UG/L AS AS)	BARIUM, TOTAL RECOV- ERABLE (UG/L AS BA)	BORON, TOTAL RECOV- ERABLE (UG/L AS B)	CADMIUM TOTAL RECOV- ERABLE (UG/L AS CD)	CHRO- MIUM, TOTAL RECOV- BRABLE (UG/L AS CR)	COPPER, TOTAL RECOV- ERABLE (UG/L AS CU)
ОСТ 1991										
17 DBC	1.0	1.5	6.5	0.290	<1	<100	30	5	3	30
31	0.40	0.89	3.9	0.310						
FEB 1992 25	0.40	0.89	3.9	0.270						
APR 23	2.5	2.9	13	0.750	2	200	10	<1	4	10
JUN 25	3.1	3.4	15	1.30						
AUG 06	0.60	1.2	5.4	0.310	<1	<100	50	<1	∢1	<10
DATE	IRON, TOTAL RECOV- ERABLE (UG/L AS FE)	LEAD, TOTAL RECOV- ERABLE (UG/L AS PB)	MANGA- NESE, TOTAL RECOV- BRABLB (UG/L AS MN)	MERCURY TOTAL RECOV- ERABLE (UG/L AS HG)	SELE- NIUM, TOTAL (UG/L AS SE)	SILVER, TOTAL RECOV- ERABLE (UG/L AS AG)	ZINC, TOTAL RECOV- BRABLE (UG/L AS ZN)	CYANIDE TOTAL (MG/L AS CN)	PHENOLS TOTAL (UG/L)	METHY- LENE BLUE ACTIVE SUB- STANCE (MG/L)
ОСТ 1991	TOTAL RECOV- BRABLE (UG/L	TOTAL RECOV- ERABLE (UG/L AS PB)	NESE, TOTAL RECOV- ERABLE (UG/L AS MN)	TOTAL RECOV- ERABLE (UG/L AS HG)	NIUM, TOTAL (UG/L AS SE)	TOTAL RECOV- ERABLE (UG/L	TOTAL RECOV- BRABLE (UG/L	TOTAL (MG/L	TOTAL	LENE BLUE ACTIVE SUB- STANCE
OCT 1991 17 DBC	TOTAL RECOV- BRABLB (UG/L AS FE)	TOTAL RECOV- ERABLE (UG/L	NESE, TOTAL RECOV- BRABLE (UG/L	TOTAL RECOV- ERABLE (UG/L	NIUM, TOTAL (UG/L	TOTAL RECOV- ERABLE (UG/L AS AG)	TOTAL RECOV- BRABLE (UG/L AS ZN)	TOTAL (MG/L AS CN)	TOTAL (UG/L)	LENE BLUE ACTIVE SUB- STANCE (MG/L)
ОСТ 1991 17	TOTAL RECOV- BRABLB (UG/L AS FE)	TOTAL RECOV- ERABLE (UG/L AS PB)	NESE, TOTAL RECOV- ERABLE (UG/L AS MN)	TOTAL RECOV- ERABLE (UG/L AS HG)	NIUM, TOTAL (UG/L AS SE)	TOTAL RECOV- ERABLE (UG/L AS AG)	TOTAL RECOV- BRABLE (UG/L AS ZN)	TOTAL (MG/L AS CN)	TOTAL (UG/L)	LENE BLUE ACTIVE SUB- STANCE (MG/L)
OCT 1991 17 DEC 31 FEB 1992 25	TOTAL RECOV- BRABLB (UG/L AS FE)	TOTAL RECOV- ERABLE (UG/L AS PB)	NESE, TOTAL RECOV- ERABLE (UG/L AS MN)	TOTAL RECOV- ERABLE (UG/L AS HG)	NIUM, TOTAL (UG/L AS SE)	TOTAL RECOV- ERABLE (UG/L AS AG)	TOTAL RECOV- BRABLE (UG/L AS ZN)	TOTAL (MG/L AS CN)	TOTAL (UG/L)	LENE BLUE ACTIVE SUB- STANCE (MG/L)
OCT 1991 17 DBC 31 FEB 1992 25 APR 23	TOTAL RECOV- BRABLB (UG/L AS FE)	TOTAL RECOV- ERABLE (UG/L AS PB)	NESE, TOTAL RECOV- ERABLE (UG/L AS MN)	TOTAL RECOV- ERABLE (UG/L AS HG)	NIUM, TOTAL (UG/L AS SE)	TOTAL RECOV- ERABLE (UG/L AS AG)	TOTAL RECOV- BRABLE (UG/L AS ZN)	TOTAL (MG/L AS CN)	TOTAL (UG/L)	LENE BLUE ACTIVE SUB- STANCE (MG/L)
OCT 1991 17 DBC 31 FEB 1992 25	TOTAL RECOV- BRABLB (UG/L AS FE)	TOTAL RECOV- ERABLE (UG/L AS PB)	NESE, TOTAL RECOV- BRABLE (UG/L AS MN)	TOTAL RECOV- ERABLE (UG/L AS HG)	NIUM, TOTAL (UG/L AS SE)	TOTAL RECOV- BRABLE (UG/L AS AG) <1	TOTAL RECOV- BRABLE (UG/L AS ZN)	TOTAL (MG/L AS CN) <0.010	TOTAL (UG/L) 2	LENE BLUE ACTIVE SUB- STANCE (MG/L)

50048510 RIO DE BAYAMON AT FLOOD CHANNEL AT BAYAMON, PR

WATER-QUALITY RECORDS

LOCATION.--Lat 18°24'29", long 66°09'04", at bridge on Highway 890, 1.0 (1.6 km) downstream from bridge on Highway 2, and 3.2 mi (5.1 km) above mouth.

DRAINAGE AREA. -- 71.9 mi 2 (186.2 km2).

PERIOD OF RECORD. -- Water years 1974 to current year.

REMARKS.--Prior to 1979 sampling site was 0.8 mile (1.3 km) downstream but was changed because of flood channel construction.

WATER-QUALITY DATA, WATER YEAR OCTOBER 1991 TO SEPTEMBER 1992

			•	WIDK- GOW	DITT DAT	A, W/	AI NAI'	AR OCTOR	BR 1331	10 35	PIBADA	R 1992			
DATE		TIME	DISCHARGINST CUBIC FEE PER SECO	E, SPE CIF CON T DUC ANC	- WA IC WH - PI T- (SI B A	H Ter Ole Eld And- Rd Its)	TEMPE ATUR WATE (DEG	B BI R II	:D- 'Y \$	KYGEN, DIS- SOLVED (MG/L)	OXYGE DIS SOLV (PER CEN SATU ATIO	- DEM ED CH - IC T (H R- LEV	AND, EM- AL IGH EL)	COLI- PORM, PECAL, 0.7 UM-MF (COLS./ 100 ML)	KF AGAR (COLS. PER
OCT 1991		1215	22		432	7.8	30	.0 10)	7.2	89		19	40000	K1300
DEC 11		1415	24		442	7.8	27	.0 3	. 8	5.8	72		21	K17000	K100
FEB 1992 25		1330	43		407	7.2	26	.0 1	6	7.0	52		18	K800	23000
APR 23		0940	42		485	7.2	26	.0 20)	4.4	54		17	K20000	R1600
JUN 25		1050	19		451	7.6	28	.0 1	. 2	7.5	94		22	K1100	K200
AUG 07		1240	48		377	7.0	28	.7 46	i	3.7	60		27	4100	2100
DATE	1	HARD- NESS FOTAL (MG/L AS CACO3)	HARD NESS NONCA WH WA TOT F MG/L CACO	RB CALC T DIS LD SOI AS (MG	IUM S - I VED SC /L (N	GNE- IUM, IS- DLVED IG/L MG)	SODIU DIS- SOLVE (MG/ AS N	M, A SOF D TI L RAT	ID- IP- ION S	POTAS- SIUM, DIS- SOLVED (MG/L AS K)	ALKA LINIT WAT W TOT P FIBL MG/L CACO	Y H ET SUL D TO AS (M	FIDE TAL G/L S)	SULFATE DIS- SOLVEI (MG/L AS SO4)	DIS~ SOLVED (MG/L
OCT 1991		140	6	44	1	.3	26		0.9	2.6	1	60	<0.5	18	31
DEC 11				_	-			-	-		1	60			
FEB 1992 25				-	-			-	-		1	40			
APR 23		150	7	39	. 1	.3	24		0.9	3.6	1	70	<0.5	19	34
JUN 25				-	_			_			1	80			
AUG 07		140	0	37	1	.1	19		0.7	2.7	1	60		19	27
07	DATE 1991	RI D SC (M	JUO- IDE, IIS- ILVED IG/L F)	SILICA, DIS- SOLVED (MG/L AS SIO2)	SOLIDS, SUM OF CONSTI- TUENTS, DIS- SOLVED (MG/L)	1 SC (7) 1	LIDS, DIS- DLVED TONS	RESIDUE TOTAL AT 105 DEG. C, SUS- PENDED (MG/L)	NITRO GEN, NITRAT TOTAL (MG/I AS N)	, G FB NIT L TO L (M	TRO- IRN, RITE TAL G/L N)	NITRO- GEN, NO2+NO3 TOTAL (MG/L AS N)	G AMM TO (M AS	EN, ONIA OF TAL T G/L (IITRO- GEN, IGANIC OTAL MG/L S N)
DEC 11	١							17	0.38	80 0	. 070	0.450	0	.750	0.45
	1992 5							6	0.31	10 0	.040	0.350	0	.450	0.55
	3		0.20	24	240	. :	27	48	0.47		. 130	0.600		. 20	0.70
	5							18	0.26	60 0	.030	0.290	0	.060	0.34
AUG 07	7		0.10	23	224		29	79	0.60	00 0	. 020	0.620	0	.090	0.41
¥ -	non-	ideal c	ount												

K = non-ideal count

RIO DE BAYAMON BASIN

50048510 RIO DE BAYAMON AT FLOOD CHANNEL AT BAYAMON, PR--Continued WATER-QUALITY DATA, WATER YEAR OCTOBER 1991 TO SEPTEMBER 1992

DATE	NITRO- GEN, AM- MONIA + ORGANIC TOTAL (MG/L AS N)	NITRO- GEN, TOTAL (MG/L AS N)	NITRO- GEN, TOTAL (MG/L AS NO3)	PHOS- PHORUS TOTAL (MG/L AS P)	ARSENIC TOTAL (UG/L AS AS)	BARIUM, TOTAL RECOV- ERABLE (UG/L AS BA)	BORON, TOTAL RECOV- ERABLE (UG/L AS B)	CADMIUM TOTAL RECOV- ERABLE (UG/L AS CD)	CHRO- MIUM, TOTAL RECOV- ERABLE (UG/L AS CR)	COPPER, TOTAL RECOV- ERABLE (UG/L AS CU)
OCT 1991										
07	0.70	1.1	4.7	0.210	<1	100	<10	<1	2	<10
11 FRB 1992	1.2	1.7	7.3	0.270						
25 APR	1.0	1.3	6.0	0.260						
23 JUN	1.9	2.5	11	0.480	2	200	30	<1	20	10
25	0.40	0.69	3.1	0.110						
07	0.50	1.1	5.0	0.160						
	TOTAL	TOTAL	MANGA - TOTAL	TOTAL	SELE-	TOTAL	TOTAL			METHY- BLUE
DATE	RECOV- BRABLE (UG/L AS FE)	RECOV- ERABLE (UG/L AS PB)	RECOV- ERABLE (UG/L AS MN)	RECOV- ERABLE (UG/L AS HG)	NIUM, TOTAL (UG/L AS SE)	RECOV- ERABLE (UG/L AS AG)	RECOV- ERABLE (UG/L AS ZN)	CYANIDE TOTAL (MG/L AS CN)	PHENOLS TOTAL (UG/L)	ACTIVE SUB- STANCE (MG/L)
OCT 1991	RECOV- ERABLE (UG/L AS FE)	RECOV- ERABLE (UG/L AS PB)	ERABLE (UG/L AS MN)	ERABLE (UG/L AS HG)	TOTAL (UG/L AS SE)	RECOV- ERABLE (UG/L AS AG)	ERABLE (UG/L AS ZN)	TOTAL (MG/L AS CN)	TOTAL (UG/L)	SUB- STANCE (MG/L)
OCT 1991 07 DEC	RECOV- ERABLE (UG/L	RECOV- ERABLE (UG/L	ERABLE (UG/L	ERABLE (UG/L	TOTAL (UG/L	RECOV- ERABLE (UG/L	ERABLE (UG/L	TOTAL (MG/L	TOTAL	SUB- STANCE
OCT 1991 07 DEC 11	RECOV- ERABLE (UG/L AS FE)	RECOV- ERABLE (UG/L AS PB)	ERABLE (UG/L AS MN)	ERABLE (UG/L AS HG)	TOTAL (UG/L AS SE)	RECOV- ERABLE (UG/L AS AG)	ERABLE (UG/L AS ZN)	TOTAL (MG/L AS CN)	TOTAL (UG/L)	SUB- STANCE (MG/L)
OCT 1991 07 DBC 11 FEB 1992 25	RECOV- ERABLE (UG/L AS FE)	RECOV- ERABLE (UG/L AS PB)	ERABLE (UG/L AS MN)	ERABLE (UG/L AS HG) <0.10	TOTAL (UG/L AS SE)	RECOV- ERABLE (UG/L AS AG)	ERABLE (UG/L AS ZN)	TOTAL (MG/L AS CN)	TOTAL (UG/L)	SUB- STANCE (MG/L)
OCT 1991 07 DEC 11 FEB 1992 25 APR 23	RECOV- ERABLE (UG/L AS FE) 850	RECOV- ERABLE (UG/L AS PB)	ERABLE (UG/L AS MN)	ERABLE (UG/L AS HG) <0.10	TOTAL (UG/L AS SE)	RECOV- ERABLE (UG/L AS AG) <1	ERABLE (UG/L AS ZN)	TOTAL (MG/L AS CN)	TOTAL (UG/L)	SUB- STANCE (MG/L) 0.06
OCT 1991 07 DEC 11 FEB 1992 25 APR	RECOV- ERABLE (UG/L AS FE) 850	RECOV- ERABLE (UG/L AS PB)	ERABLE (UG/L AS MN) 280	ERABLE (UG/L AS HG) <0.10	TOTAL (UG/L AS SR)	RECOV- ERABLE (UG/L AS AG) <1	ERABLE (UG/L AS ZN) <10	TOTAL (MG/L AS CN) <0.010	TOTAL (UG/L) 1	SUB- STANCE (MG/L) 0.06

PESTICIDE ANALYSES

WATER-QUALITY DATA

DATE TIME

JUN 1992 25...

1050

185

50048770 RIO PIRDRAS AT BL SENORIAL, PR

LOCATION.--Lat 18°21'51", long 66°03'56", Hydrologic Unit 21010005, on right bank, in the Riberas of Señorial Housing area, 0.6 mi (1.0 km) west of Highway 176 and 2.7 mi (4.3 km) southwest of Río Piedras Plaza.

DRAINAGE AREA. -- 7.49 mi2 (19.40 km2).

WATER-DISCHARGE RECORDS

PERIOD OF RECORDS .-- March 1988 to current year.

GAGE.--Water-stage recorder. Elevation of gage is 98.4 ft (30.0 m), from topographic map.

REMARKS.--Records poor. Gage-height and precipitation satellite telemetry at station.

DATE No. DATE No. DATE DATE NA. APR NA. DATE			DI SCHA	RGB, CUBI	C FRET PER		WATER YE	EAR OCTOBER	1991 TO	Sep tem be	R 1992		
2 6.3 31 10 0 efc.0 els 4.4 4.3 148 31 4.0 e28 e7.6 3 5.7 17 20 e4.5 e11 5.0 4.5 20 12 3.9 e17 e8.6 4 5 3.9 e17 e8.6 6 6.4 12 12 255 e7.2 5.4 4.4 3.1 11 6.5 11.9 e17 3.6 6 6.4 12 12 255 e7.2 4.4 3.1 11 6.5 11.9 e17 3.6 6 6.4 12 12 255 e7.2 4.4 3.1 11 6.5 11.9 e17 3.6 6 6.4 12 22 5.5 e7.2 4.4 3.1 11 6.5 11.9 e17 3.6 6 6.4 12 22 6.7 4.4 3.1 11 6.5 11.9 e17 3.6 6 6.7 4.4 1.7 12 22 6.7 4.4 2.5 1.0 6.7 12 1.0 6.1 6.7 4.4 1.0 1.0 1.0 1.0 1.0 1.0 1.0 1.0 1.0 1.0	DAY	OCT	Nov	DEC	JAN				MAY	JUN	JUL	AUG	SEP
2 6.3 31 10 0 e6.0 e14 4.4 4.3 148 31 4.0 e28 e75.6 3 5.7 17 20 e15 e15 e15 5.0 4.5 20 12 3.9 e17 e75.6 5.7 17 20 e15 e15 e15 5.0 4.5 20 12 3.9 e17 e75.6 5.7 4.5 11 11 6.5 11.9 e17 e75.6 6.9 e161 6.7 6.8 6.8 e10 2.2 e17	1	11	9.7	6.9	10	8.8	4.7	4.2	139	41	4.2	e22	e11
\$ 5.9 12 14 12 67.6 5.7 4.7 13 6.5 6.9 161 7.6 \$ 6 4.4 7.7 6.3 163 6.8 6.8 5.2 3.0 63 10 6.1 627 44 7 4.1 25 4.7 16 6.7 5.6 7.2 4.7 4.9 13 6.5 6.9 9130 4.6 621 9.1 8 12 47 6.7 5.6 7.2 4.7 4.9 18 8.8 6.0 13 6.7 5.4 10 3.7 10 3.7 10 3.7 10 4.7 73 5.9 5.0 12 8.8 6.0 13 6.7 5.4 11 3.6 5.7 4.9 13 6.1 5.6 5.8 6.8 6.0 12 2.0 6.1 6.7 12 3.4 6.7 1.7 1.8 6.7 1.8 6.7 1.8 6.7 1.8 6.8 6.8 6.0 12 0.0 12 6.1 6.1 6.7 12 3.4 6.7 1.7 1.8 6.7 1.8 6.7 1.8 6.8 6.8 6.8 6.0 12 0.0 12 6.1 6.1 6.7 12 3.4 6.1 7.1 5.0 7.0 7.0 5.9 1.2 2.8 6.0 2.0 13 6.5 5.6 5.8 6.0 1.0 1.0 6.1 6.1 6.1 6.7 1.1 6.5 6.1 6.8 6.8 6.1 6.1 6.1 6.1 6.1 6.1 6.1 6.1 6.1 6.1													e7.6
5 8.6 6.4 12 245 e7:2 4.4 3.1 11 6.5 6.9 e161 7.6 6 4.4 7.7 6.2 1615 6.9 6.9 5.2 1.0 63 10 64.6 e27 4.1 7 4.1 25 4.7 15 6.7 1.0 4.6 7.9 e100 4.6 e27 4.1 8 12 47 6.7 5.6 7.2 4.7 4.9 5.8 e80 13 27 4.7 9 4.7 15 5.9 19 5.5 5.0 19 15 e25 26 e277 4.7 10 3.7 10 4.7 73 5.9 5.5 5.0 19 15 e25 26 e277 4.7 11 3.6 5.7 4.9 11 8.7 6.4 4.4 4.9 5.8 e80 13 e15 9.1 11 3.1 6.7 7.7 10 8.7 6.1 5.6 5.8 6.8 e10 22 e31 5.4 11 3.1 6.7 7.7 10 8.7 6.1 5.4 6.1 5.6 5.8 6.8 e10 22 e31 5.4 11 3.1 6.7 7.7 5.9 13 5.4 6.7 7.2 1.2 8.3 6.8 e10 22 e31 5.4 11 3.1 6.7 7.7 5.9 13 5.4 6.7 7.2 1.2 8.3 1.2 e10 28 e35 6.5 11 5 4.5 7.7 1.4 1.5 1.4 6.7 6.8 6.8 6.8 e10 22 e31 5.4 11 5 4.5 7.7 6.9 1.1 8.7 6.4 6.8 1.5 1.6 2.4 9.2 13 6.0 e35 6.5 11 6 3.2 12 6.0 6.7 e25 6.7 5.4 6.8 1.5 2.4 9.2 13 6.0 11 15 4.5 7.7 6.7 1.1 1.2 6.7 e25 6.7 5.4 6.8 1.5 1.6 2.4 9.2 13 6.0 11 16 3.2 12 12 6.7 e25 6.7 5.6 6.5 4.6 6.8 1.6 6.8 1.0 9.2 13 6.0 11 16 3.2 12 12 6.7 e25 6.7 5.9 6.5 4.9 26 5.2 5.3 e4.1 18.4 17 3.1 e3.0 6.7 e25 6.5 5.9 6.5 4.6 6.8 4.6 6.8 4.5 5.7 e4.1 18.4 18 76 e6.0 9.1 14 7.4 5.5 9.6 6.5 4.6 6.8 4.5 5.7 e4.1 18.4 19 16 e5.0 7.8 6.5 9.6 6.5 4.9 26 5.2 5.3 e4.1 18.4 20 6.4 4.0 22 7.4 7.0 5.9 7.8 6.5 4.5 2.0 9.8 6.5 1.5 2.4 21 5.9 71 11 22 6.5 8.0 12 3.4 2.5 5.1 7.6 e12 e40 7.4 22 7.6 5.8 15 6.9 12 3.4 2.5 5.1 7.6 e12 e40 7.4 22 7.6 5.8 15 6.9 12 3.4 2.5 5.1 7.6 e12 e40 7.4 22 7.6 5.8 15 6.9 12 3.4 2.5 5.1 7.6 e12 e40 7.4 22 7.6 5.8 15 6.9 12 3.4 2.5 5.1 7.6 e12 e40 7.4 23 5.7 9 71 12 6.5 8.0 9.1 12 8.2 6.5 4.0 116 6.4 e.9 9.2 e30 7.4 24 5.5 9 30 13 4.8 5.9 12 5.6 6.5 4.5 6.5 1.0 7.2 12 e18 e621 12 24 7.6 5.8 15 6.9 12 3.4 2.5 5.1 7.6 e12 e40 7.4 25 5.9 30 13 4.8 5.9 12 5.7 7.8 3.4 5.4 140 5.7 e11 11 24 6.4 6.4 1.0 22 7.4 5.7 7.8 5.2 6.5 1.0 7.2 12 e18 e621 12 25 7.6 5.8 15 6.9 12 3.4 6.7 7.8 5.2 6.5 4.5 12 1.0 7.4 12 1.0 11 25 8.4 1.1 1.1 1.6 1.5 12.4 1.2 1.2 1.2 1.2 1.2 1.2 1.2 1.2 1.2 1.2				20	e4.5	e11	5.0				3.9		
6 4.4 7.7 6.3 163 6.8 5.2 3.0 63 10 6.1 27 44.1 7.1 7.2 6.3 163 6.8 5.2 3.0 63 10 6.1 227 44.1 7.1 8.1 1.1 1.1 1.1 1.1 1.1 1.1 1.1 1.1 1													
7 4.1 25 4.7 16 6.7 4.0 4.6 7.9 e130 4.6 e21 9.1 8 12 47 6.7 5.6 7.2 4.7 4.9 5.8 e80 13 e27.3 5.4 9 4.7 15 5.3 19 5.5 5.3 3.9 4.9 15 e25 26 e277 4.7 10 3.7 10 4.7 73 5.9 5.0 12 8.3 e15 5.6 26 e277 4.7 11 3.6 5.7 4.9 13 6.1 5.6 5.8 6.8 e10 22 e21 5.4 11 3.6 5.7 4.9 13 6.1 5.6 5.8 6.8 e10 22 e21 5.4 11 3.1 e7.7 5.9 13 5.4 4.4 4.4 4.4 3.9 e2.0 9.0 e16 5.4 11 3.1 e7.7 5.9 13 5.4 5.7 2.0 3.2 e10 22 e21 5.4 11 3.1 e2.7 5.9 13 5.4 6.8 4.4 4.4 3.9 e2.0 9.0 e16 5.4 11 3.1 e2.7 5.9 13 5.4 6.8 4.5 1.6 2.2 3.2 e10 22 e21 5.4 11 5.4 64.1 7.2 6.7 6.8 6.8 6.8 e10 22 e21 5.4 11 5.4 64.1 7.2 6.8 6.8 6.8 e10 22 e21 5.4 11 5.4 64.1 7.2 6.8 6.8 6.8 6.8 e10 22 e21 5.4 11 5.4 64.1 7.2 6.8 6.8 6.8 6.8 e10 22 e21 5.4 11 5.4 64.1 7.8 6.8 6.8 6.8 6.8 e10 22 e21 5.4 11 5.4 64.1 7.2 6.8 6.8 6.8 6.8 e10 22 e21 5.4 11 5.4 64.1 7.2 6.8 6.8 6.8 6.8 e10 22 e21 5.4 11 5.4 64.1 7.2 6.8 6.8 6.8 6.8 6.8 e10 22 e21 5.4 11 5.4 64.1 7.2 6.8 6.8 6.8 6.8 6.8 e10 22 e21 5.4 11 5.4 64.1 7.2 6.8 6.8 6.8 6.8 6.8 e10 22 e21 5.4 11 5.4 64.1 7.2 6.8 6.8 6.8 6.8 6.8 e10 22 e21 5.4 12 6.8 6.8 6.8 6.8 6.8 e10 22 e21 5.4 12 6.8 6.8 6.8 6.8 e10 22 e21 5.4 12 6.8 6.8 6.8 6.8 e10 22 e21 5.4 13 6.8 6.8 6.8 e10 22 e21 5.4 14 6.8 6.8 6.8 e10 22 e21 5.4 15 6.8 6.8 e10 22 e21 5.4 15 6.8 6.8 e10 22 e21 5.4 16 6.8 6.8 6.8 e10 22 e21 5.4 17 7.2 6.8 6.8 6.8 6.8 6.8 e10 22 e21 5.4 18 6.8 6.8 e10 22 e21 5.4 19 6.8 6.8 6.8 e10 22 e21 5.4 19 6.8 6.8 e10 22 e21 5.4 19 6.8 6.8 6.8 e10 22 e21 5.4 19 6.8 6.8 e10 22 e21 5.	>	8.6	6.4	12	245	e7.2	4.4	3.1	11	6.5	6.9	e 161	7.6
8 12 47 6.7 5.6 7.2 6.7 5.6 7.2 4.7 4.9 5.8 680 13 67.3 5.4 6.9 10 3.7 10 4.7 73 5.9 5.9 5.0 12 8.3 e15 26 e277 4.7 10 3.7 110 4.7 73 5.9 5.9 5.0 12 8.3 e15 26 e277 4.7 10 3.7 110 4.7 73 5.9 5.9 5.0 12 8.3 e15 2.6 e277 4.7 10 3.7 110 4.7 73 5.9 5.9 5.0 12 8.3 e15 2.6 e277 4.7 10 3.7 110 4.7 73 5.9 5.9 5.0 12 8.3 e15 2.6 e277 4.7 111 3.6 5.9 11 8.7 6.4 4.4 4.4 3.9 ee.0 2.0 2.0 e16 5.4 112 3.1 e2.7 5.9 13 5.4 5.7 2.0 3.2 e10 2.8 e25 5.5 114 3.4 6.4 1.7 1.5 5.0 7.0 5.9 3.2 2.0 3.2 e10 2.8 e25 5.5 5.1 1.5 4.5 7.9 4.1 5.4 6.8 4.5 1.6 2.4 9.2 10 14 e289 7.4 115 1.5 4.5 7.9 4.1 5.4 6.8 4.5 1.6 2.4 9.2 10 14 e289 7.4 115 1.5 4.5 7.9 1.1 5.4 6.8 4.5 1.6 2.4 9.2 10 14 e289 7.4 115 1.5 4.5 7.9 1.1 5.4 6.8 4.5 1.6 2.4 9.2 10 14 e289 7.4 115 1.5 4.5 7.9 1.1 5.4 6.8 4.5 1.6 2.4 9.2 10 14 e289 7.4 115 1.5 4.5 7.9 1.1 5.4 6.8 4.5 1.6 2.4 9.2 10 14 e289 7.4 115 1.5 4.5 7.9 1.1 5.4 6.8 4.5 1.6 2.4 9.2 10 14 e289 7.4 115 1.5 4.5 7.9 1.1 5.4 6.8 4.5 1.6 2.4 9.2 10 14 e289 7.4 115 1.5 4.5 1.6 2.4 9.2 10 1.1 1.5 1.5 1.5 1.5 1.5 1.5 1.6 2.4 9.2 10 1.1 1.5 1.5 1.5 1.5 1.5 1.6 2.4 9.2 10 1.1 1.5 1.5 1.5 1.5 1.5 1.6 2.4 9.2 10 1.1 1.5 1.5 1.5 1.5 1.5 1.6 2.4 9.2 10 1.1 1.5 1.5 1.5 1.5 1.5 1.6 2.4 9.2 1.5 1.5 1.5 1.5 1.5 1.5 1.5 1.5 1.5 1.5			7.7	6.3	163	6.8	5.2	3.0		10	6.1	e27	
9 4.7 15 5.9 19 5.5 3.9 19 5.5 3.9 4.9 15 625 26 6277 4.7 10 3.7 10 4.7 73 5.9 5.0 12 8.3 e15 26 6277 4.7 11 3.6 5.7 4.9 13 6.1 5.6 5.6 5.8 6.8 e10 22 e11 5.7 11 3.6 5.7 4.9 13 6.4 6.4 4.4 4.4 3.9 e8.0 2.0 9.0 e16 5.4 13 3.1 e7.7 5.9 13 5.4 5.7 2.0 3.2 e10 28 e25 6.5 13 3.1 e7.7 5.9 13 5.4 5.7 2.0 3.2 e10 28 e25 6.5 14 3.4 e4.1 7.1 5.0 7.0 5.9 3.2 2.2 8 10 14 e289 7.4 15 4.5 7.9 4.1 5.4 6.8 4.5 1.6 2.4 9.2 13 e20 11 e28 27 1.4 15 4.5 7.9 4.1 5.4 6.8 6.8 4.5 1.6 2.4 9.2 13 e20 11 e28 27 1.4 15 4.5 7.9 4.1 5.4 6.8 6.8 4.5 1.6 2.4 9.2 13 e20 11 e28 27 1.4 15 4.5 7.9 4.1 5.4 6.8 6.8 4.5 1.6 2.4 9.2 13 e20 11 e28 27 1.4 15 4.5 7.9 4.1 5.4 6.8 6.8 4.5 1.6 2.4 9.2 13 e20 11 e28 27 1.4 15 4.5 7.9 4.1 5.4 6.8 6.8 6.0 4.1 11 4.8 6.9 e4.7 10 1.8 16 3.2 12 6.7 e25 6.7 8.6 6.7 5.6 8.0 4.1 11 4.8 6.9 e4.7 10 1.8 18 76 e6.0 9.1 14 7.4 5.6 4.6 68 4.4 5.7 e4.4 7.4 13 16 e.3 6.5 7.8 6.5 9.6 6.5 49 26 5.5 45 1.6 5.7 e4.0 7.8 12 0.6 4 4.0 22 7.4 7.0 5.9 7.8 13 4.9 47 e5.4 7.2 12 1.5 9 71 12 6.5 8.0 5.8 3.0 7.8 13 4.9 47 e5.4 7.2 12 1.5 9 71 12 6.5 8.0 5.8 3.0 7.8 13 4.9 47 e5.4 7.2 12 2 2 5 5 38 12 4.7 8.9 5.4 5.4 5.4 116 6.8 4.4 9.2 6.2 4.7 12 2 5 4.5 38 15 15 6.9 12 3.4 4.9 1.0 1.0 1.0 1.0 1.0 1.0 1.0 1.0 1.0 1.0													
10 3.7 10 4.7 73 5.9 5.0 12 8.3 e15 9.4 e281 4.7 11 3.6 5.7 4.9 13 6.1 5.6 5.8 6.8 e10 22 e31 5.4 13 3.4 67.7 11 9.7 15.9 6.4 4.4 4.6 3.2 e80 0.9 2.0 e35 5.4 14 3.4 e7.7 11 9.7 15.0 7.0 5.9 3.2 2.8 10 14 e289 7.4 15 4.5 7.9 4.1 5.0 7.0 5.9 3.2 2.8 10 14 e289 7.4 16 3.2 12 6.7 e25 6.7 5.6 2.0 98 6.1 6.6 e11 8.4 17 3.1 e8.0 6.7 e16 7.8 8.0 4.1 18 76 e6.0 9.1 e14 7.4 5.6 4.6 68 4.4 5.7 e4.4 20 6.4 4.0 22 7.4 7.0 5.9 7.8 13 21 5.9 7.8 13 e8.0 6.7 e4.4 7.4 20 6.4 4.0 22 7.4 7.0 5.9 7.8 13 21 5.9 7.8 15 6.9 12 1.4 7.8 15 6.9 12 1.4 2.5 5.1 7.6 e12 e40 7.7 21 5.9 71 11 5.0 6.5 8.0 5.8 3.0 7.8 13 4.9 47 e5.4 5.2 22 7.6 58 15 6.9 12 3.4 2.5 5.1 7.6 e12 e40 7.7 22 7.6 58 15 6.9 12 3.4 2.5 5.1 7.6 e12 e40 7.7 23 5.9 30 13 4.8 5.8 5.2 4.0 116 6.4 e0.3 e1.7 e1.1 11 26 6.4 11 6.2 11 7.4 5.2 6.5 8.0 5.8 3.0 7.2 12 e18 e621 12 27 4.5 5.9 6.6 9.1 6.7 7.8 1.4 5.4 6.8 4.5 5.1 7.6 e12 e40 7.7 28 5.9 30 13 4.8 5.8 5.2 5.6 6.8 4.0 5.7 e116 e12 12 21 5.5 9.7 8 12 6.7 7.8 1.4 5.4 5.5 4.0 116 6.4 e0.9 3 e1.7 e11 11 26 6.4 11 6.2 11 7.4 5.2 6.5 2.1 5.1 7.6 e12 e40 7.7 27 4.5 5.5 6.6 9.1 6.6 9.1 6.6 6.7 7.8 1.4 5.4 140 5.7 e116 e12 28 3.7 8.6 3.7 9.7 6.6 88 3.0 5.8 3.0 7.8 13 e1.7 e1.7 e1.7 e1.7 e1.7 e1.7 e1.7 e1.7													
111 3.6 5.7 4.9 13 6.1 5.6 5.8 6.8 e10 22 e31 5.4 112 3.4 e5.9 11 8.7 6.4 4.4 4.4 3.9 e8.0 9.0 e16 5.4 113 3.4 e5.9 11 8.7 6.4 5.4 4.4 4.4 3.9 e8.0 9.0 e16 5.4 114 3.1 e7.7 5.9 15 5.0 7.0 4.5 7.2 0.0 3.2 e10 28 e32 6.5 115 4.5 7.9 4.1 5.0 7.0 6.8 4.5 1.6 2.4 9.2 13 e30 11.4 116 3.2 12 6.7 e25 6.7 5.6 2.0 98 6.1 6.6 e11 8.4 117 118 7.1 e8.0 6.7 e16 7.7 e25 6.7 5.6 2.0 98 6.1 6.6 e11 8.4 119 710 6.7 e16 7.7 e25 6.7 5.6 2.0 98 6.1 6.6 e11 8.4 119 710 6.7 e17 e17 e17 e17 e17 e17 e17 e17 e17 e1													
12				•••	,,	2.9	3.0		0.5	413	,. .	0201	•••
13													
14													
15													
18 76 66.0 9.1 14 7.4 5.6 4.6 68 4.4 5.7 e4.7 10 18 76 66.0 9.1 14 7.4 5.6 4.6 68 4.4 5.7 e4.4 7.4 19 16 e5.0 7.8 6.5 9.6 6.5 49 26 5.2 5.3 e4.1 42 20 6.4 4.0 22 7.4 7.0 5.9 7.8 13 4.9 47 e5.4 5.2 21 5.9 71 12 6.5 9.6 6.5 49 26 5.2 5.3 e4.1 42 22 7.6 58 15 6.9 12 3.4 2.5 5.1 7.6 e12 e40 7.7 23 5.9 30 12 4.8 5.8 5.2 4.0 116 6.4 e9.3 e28 41 24 5.5 538 12 6.7 7.8 3.4 5.4 140 5.7 e116 6.2 212 25 4.2 11 5.9 12 8.2 5.0 6.8 45 5.9 e17 e11 11 26 6.4 11 6.2 11 7.4 5.2 6.5 211 5.9 e17 e11 11 27 4.5 5.8 5.2 4.0 116 6.4 e9.3 e28 41 28 3.7 8.6 5.7 9.7 6.6 88 3.8 62 4.7 e19 7.0 e11 11 29 3.4 8.8 5.2 8.3 6.6 5.7 9.7 6.6 88 3.8 62 4.7 e19 7.0 11 29 3.4 8.8 5.2 8.3 6.6 8.7 9.7 6.6 88 3.8 62 4.7 e19 7.0 11 29 3.4 8.8 5.2 8.3 6.6 8.9 10.8 71 4.8 e9.8 7.4 12 30 19 7.3 9.7 7.7 2.6 51 83 4.3 e7.6 e22 24 31 7.7 3.6 6.5 4.3 20 e117 e28 TOTAL 26.2 50.0 3 269.4 757.3 219.9 238.2 332.2 1462.4 493.6 641.7 2072.6 412.5 MIN 3.1 4.0 3.6 4.7 5.7 8.9 5.9 5.9 5.9 5.9 5.9 5.9 5.9 5.9 5.9 5													
18 76 66.0 9.1 14 7.4 5.6 4.6 68 4.4 5.7 e4.7 10 18 76 66.0 9.1 14 7.4 5.6 4.6 68 4.4 5.7 e4.4 7.4 19 16 e5.0 7.8 6.5 9.6 6.5 49 26 5.2 5.3 e4.1 42 20 6.4 4.0 22 7.4 7.0 5.9 7.8 13 4.9 47 e5.4 5.2 21 5.9 71 12 6.5 9.6 6.5 49 26 5.2 5.3 e4.1 42 22 7.6 58 15 6.9 12 3.4 2.5 5.1 7.6 e12 e40 7.7 23 5.9 30 12 4.8 5.8 5.2 4.0 116 6.4 e9.3 e28 41 24 5.5 538 12 6.7 7.8 3.4 5.4 140 5.7 e116 6.2 212 25 4.2 11 5.9 12 8.2 5.0 6.8 45 5.9 e17 e11 11 26 6.4 11 6.2 11 7.4 5.2 6.5 211 5.9 e17 e11 11 27 4.5 5.8 5.2 4.0 116 6.4 e9.3 e28 41 28 3.7 8.6 5.7 9.7 6.6 88 3.8 62 4.7 e19 7.0 e11 11 29 3.4 8.8 5.2 8.3 6.6 5.7 9.7 6.6 88 3.8 62 4.7 e19 7.0 11 29 3.4 8.8 5.2 8.3 6.6 8.7 9.7 6.6 88 3.8 62 4.7 e19 7.0 11 29 3.4 8.8 5.2 8.3 6.6 8.9 10.8 71 4.8 e9.8 7.4 12 30 19 7.3 9.7 7.7 2.6 51 83 4.3 e7.6 e22 24 31 7.7 3.6 6.5 4.3 20 e117 e28 TOTAL 26.2 50.0 3 269.4 757.3 219.9 238.2 332.2 1462.4 493.6 641.7 2072.6 412.5 MIN 3.1 4.0 3.6 4.7 5.7 8.9 5.9 5.9 5.9 5.9 5.9 5.9 5.9 5.9 5.9 5	16	2.0	40									-44	
18 76 e6.0 9.1 144 7.4 5.6 4.6 68 4.4 5.7 e4.4 7.4 19.1 16 e5.0 7.8 6.5 9.6 6.5 49 26 5.2 5.3 e4.1 4.2 20 6.4 4.0 22 7.4 7.0 5.9 7.8 13 4.9 26 5.2 5.3 e4.1 4.2 20 6.4 4.0 22 7.4 7.0 5.9 7.8 13 4.9 26 5.2 5.3 e4.1 4.2 20 6.4 4.0 22 7.4 7.0 5.9 7.8 13 4.9 47 e5.4 52 21 5.9 7.8 13 4.9 47 e5.4 52 21 5.9 30 12 6.5 8.0 5.9 12 6.5 8.0 5.9 1.5 5.1 7.6 6.4 19.3 e621 12 24 5.5 9 30 12 6.7 7.8 13.4 5.4 140 5.7 e116 e12 12 12 25 4.2 11 15.9 12 8.2 5.0 6.8 45 5.7 e116 e12 12 12 12 12 12 12 12 12 12 12 12 12 1													
19 16 e5.0 7.8 6.5 9.6 6.5 9.1 6.5 9.6 6.5 49 26 5.2 5.3 e4.1 42 20 6.4 4.0 22 7.4 7.0 5.9 7.8 13 4.9 47 e5.4 52 21 5.9 71 12 6.5 8.0 5.8 3.0 7.2 12 e18 e621 12 22 7.6 58 15 6.9 12 3.4 2.5 5.1 7.6 e12 e40 7.7 24 5.9 30 13 4.8 5.8 5.2 4.0 116 6.4 e5.3 e28 41 24 5.5 9.30 13 6.7 7.8 3.5 5.4 140 5.7 e116 e12 12 25 4.2 11 5.9 12 8.2 5.0 6.8 45 5.7 e17 e11 11 26 6.4 11 6.2 11 7.4 5.2 6.5 8.0 5.4 140 5.7 e116 e12 12 27 4.5 9.5 6.6 9.1 6.6 4.7 5.5 66 5.4 e61 e9.3 11 28 3.7 8.6 3.7 9.7 6.6 88 3.8 32 4.7 e19 7.0 11 29 3.4 8.8 5.2 8.3 6.6 5.9 100 71 4.8 e9.8 7.4 12 30 19 7.3 9.7 7.7 2.6 51 83 4.3 e9.8 7.0 11 31 7.7 3.6 6.5 4.3 20 e117 e28 TOTAL 262.9 500.3 269.4 757.3 219.9 288.2 333.2 146.4 493.6 641.7 2072.6 412.5 81 MEAN 8.48 16.7 8.69 24.4 5.8 7.68 10.8 47.2 16.5 20.7 66.9 13.7 MAX 76 71 22 244 7.58 7.68 10.8 47.2 16.5 20.0 7.7 66.7 13.7 MAX 76 71 22 244 7.58 7.68 10.8 47.2 16.5 20.0 7.7 66.7 13.7 MAX 76 71 22 244 7.58 7.68 10.8 47.2 16.5 20.0 7.7 66.7 13.7 MAX 76 71 22 244 7.58 7.68 10.8 47.2 16.5 20.0 7.7 66.7 13.7 MAX 76 71 22 244 7.58 7.68 10.8 47.2 16.5 20.0 7.6 6.9 13.7 MAX 76 71 22 244 7.58 7.68 10.8 47.2 16.5 20.7 66.9 13.7 MAX 76 71 3.1 4.0 3.6 4.5 5.4 2.6 1.6 2.4 4.9 3.6 641.7 2072.6 412.5 MIN 3.1 4.0 3.6 4.5 5.4 2.6 1.6 2.4 4.9 3.3 9 4.1 3.8 CFEM 1.13 2.23 1.16 3.26 1.01 1.03 1.14 6.3 2.20 2.20 2.7 66.9 59.5 MIN 3.1 4.0 3.6 4.5 5.4 2.6 1.6 2.4 4.9 3.6 641.7 2072.6 412.5 MIN 3.1 4.0 3.6 4.5 5.4 2.6 1.6 2.4 4.9 3.9 4.9 4.9 4.9 4.9 4.9 4.9 4.9 4.9 4.9 4													
20 6.4 4.0 22 7.4 7.0 5.9 7.8 13 4.9 47 e5.4 52 21 5.9 71 12 6.5 8.0 5.8 3.0 7.2 12 e18 e621 12 22 7.6 5.8 15 6.9 12 3.4 2.5 5.1 7.6 e12 e40 7.7 23 5.9 30 13 4.8 5.8 5.2 4.0 116 6.4 e9.3 e28 41 25 5.5 e38 12 6.7 7.8 3.4 5.4 140 5.7 e115 e12 12 25 4.2 11 5.9 9.1 2 8.2 5.0 6.8 45 5.9 e17 e11 11 26 6.4 11 6.2 11 7.4 5.2 6.5 211 5.2 e8.4 e13 12 27 4.5 9.5 6.6 9.1 6.6 4.7 5.5 66 5.4 e61 e9.3 11 28 3.7 8.6 3.7 9.7 6.6 88 3.8 32 4.7 e19 7.0 11 29 3.4 8.8 5.2 8.3 6.6 5.9 100 71 4.8 e9.8 7.4 12 30 19 7.3 9.7 7.7 2.6 51 83 1.3 4.3 e7.6 22 24 31 7.7 3.6 6.5 5.5 4.3 20 e117 e28 2 TOTAL 262.9 500.3 269.4 757.3 219.9 238.2 323.2 1462.4 493.6 641.7 2072.6 412.5 MEAN 8.88 16.7 8.69 24.4 7.58 7.68 10.8 47.2 10.5 11.5 20 2.7 66.9 13.7 MAX 76 71 22 245 14 88 10.8 47.2 10.5 11.5 20.7 66.9 13.7 MAX 76 71 22 245 14 88 10.8 47.2 10.5 11.5 20.7 66.9 13.7 MAX 76 71 22 245 14 88 10.8 47.2 10.5 20.7 66.9 13.7 MAX 76 71 22 245 14 88 10.8 47.2 10.5 20.7 66.9 13.7 MAX 76 71 22 245 14 88 10.8 47.2 10.5 20.7 66.9 13.7 MAX 76 71 22 245 14 88 10.8 47.2 40.4 31.5 20.7 66.9 13.7 MAX 76 71 22 245 14 88 10.8 47.2 40.4 31.5 20.7 66.9 13.7 MAX 76 71 22 245 14 88 10.8 47.2 40.4 31.5 20.7 66.9 13.7 MAX 76 71 22 245 14 88 10.8 47.2 40.4 31.5 20.7 66.9 13.7 MAX 76 71 22 245 14 88 10.8 47.2 40.4 31.5 20.7 66.9 13.7 MAX 76 71 22 245 14 88 10.8 47.2 40.4 31.5 20.7 66.9 13.7 MAX 76 71 22 245 14 88 10.8 47.2 40.4 31.5 20.7 66.9 13.7 MAX 76 71 22 31.16 33.2 11.6 33.2 11.0 11.0 11.7 621 52 WHEAN 31.1 16.5 12.4 16.3 15.1 12.4 13.8 20.8 14.1 16.0 29.3 27.6 41.5 31.0 41.0 11.0 11.0 11.0 11.0 11.0 11.0 1													
22 7.6 58 15 6.9 12 3.4 2.5 5.1 7.6 e12 e40 7.7 23 5.9 30 12 4.8 5.8 5.2 4.0 116 6.4 e9.3 e28 41 24 5.5 e38 12 6.7 7.8 3.4 5.4 140 5.7 e116 e12 12 25 4.2 11 5.9 12 8.2 5.0 6.8 45 5.9 e17 e11 11 26 6.4 11 6.2 11 7.4 5.2 6.5 211 5.2 e8.4 e13 12 27 4.5 9.5 6.6 9.1 6.6 4.7 5.5 66 5.4 e61 e9.3 11 28 3.7 8.6 3.7 9.7 6.6 88 3.8 32 4.7 e19 7.0 11 29 3.4 8.8 5.2 8.3 6.6 5.9 100 71 4.8 e9.8 7.4 12 31 17.7 3.6 6.5 5.1 100 71 4.8 e9.8 7.4 12 31 7.7 3.6 6.5 5.1 100 71 4.8 e9.8 7.4 12 31 7.7 3.6 6.5 5.1 100 71 4.8 e9.8 7.4 12 31 7.7 3.6 6.5 5.1 100 71 4.8 e9.8 7.4 12 31 7.7 3.6 6.5 5.1 100 71 4.8 e9.8 7.4 12 31 7.7 3.6 6.5 5.1 100 71 4.8 e9.8 7.4 12 31 7.7 3.6 6.5 5.1 100 71 4.8 e9.8 7.4 12 31 7.7 3.6 6.5 5.1 100 71 4.8 e9.8 7.4 12 31 7.7 3.6 6.5 5.1 100 71 4.8 e9.8 7.4 12 31 7.7 3.6 6.5 5.1 100 71 4.8 e9.8 7.4 12 31 7.7 3.6 6.5 5.1 100 71 4.8 e9.8 7.4 12 31 7.7 3.6 6.5 5.1 100 71 4.8 e9.8 7.4 12 31 7.7 3.6 6.5 5.1 100 71 4.8 e9.8 7.4 12 31 7.7 3.6 6.5 5.1 100 71 4.8 e9.8 7.4 12 31 7.7 3.6 6.5 5.1 100 71 4.8 e9.8 7.4 12 31 7.7 3.6 6.5 5.1 100 71 4.8 e9.8 7.4 12 31 7.7 3.6 6.5 5.1 100 71 4.8 e9.8 7.4 12 31 7.7 3.6 6.5 5.1 100 71 4.8 e9.8 7.4 12 31 7.7 3.6 6.5 5.1 100 71 4.8 e9.8 7.4 12 31 7.7 3.6 6.5 5.4 2.6 1.6 2.4 4.3 3.9 4.1 3.8 4.3 100 21 31 7.7 8.69 24.4 7.58 7.68 10.8 47.2 16.5 20.7 66.9 13.7 8.2 10.1 10.0 11.0 11.0 11.	20	6.4							13	4.9	47	e5.4	
22 7.6 58 15 6.9 12 3.4 2.5 5.1 7.6 e12 e40 7.7 23 5.9 30 12 4.8 5.8 5.2 4.0 116 6.4 e9.3 e28 41 24 5.5 e38 12 6.7 7.8 3.4 5.4 140 5.7 e116 e12 12 25 4.2 11 5.9 12 8.2 5.0 6.8 45 5.9 e17 e11 11 26 6.4 11 6.2 11 7.4 5.2 6.5 211 5.2 e8.4 e13 12 27 4.5 9.5 6.6 9.1 6.6 4.7 5.5 66 5.4 e61 e9.3 11 28 3.7 8.6 3.7 9.7 6.6 88 3.8 32 4.7 e19 7.0 11 29 3.4 8.8 5.2 8.3 6.6 5.9 100 71 4.8 e9.8 7.4 12 31 17.7 3.6 6.5 5.1 100 71 4.8 e9.8 7.4 12 31 7.7 3.6 6.5 5.1 100 71 4.8 e9.8 7.4 12 31 7.7 3.6 6.5 5.1 100 71 4.8 e9.8 7.4 12 31 7.7 3.6 6.5 5.1 100 71 4.8 e9.8 7.4 12 31 7.7 3.6 6.5 5.1 100 71 4.8 e9.8 7.4 12 31 7.7 3.6 6.5 5.1 100 71 4.8 e9.8 7.4 12 31 7.7 3.6 6.5 5.1 100 71 4.8 e9.8 7.4 12 31 7.7 3.6 6.5 5.1 100 71 4.8 e9.8 7.4 12 31 7.7 3.6 6.5 5.1 100 71 4.8 e9.8 7.4 12 31 7.7 3.6 6.5 5.1 100 71 4.8 e9.8 7.4 12 31 7.7 3.6 6.5 5.1 100 71 4.8 e9.8 7.4 12 31 7.7 3.6 6.5 5.1 100 71 4.8 e9.8 7.4 12 31 7.7 3.6 6.5 5.1 100 71 4.8 e9.8 7.4 12 31 7.7 3.6 6.5 5.1 100 71 4.8 e9.8 7.4 12 31 7.7 3.6 6.5 5.1 100 71 4.8 e9.8 7.4 12 31 7.7 3.6 6.5 5.1 100 71 4.8 e9.8 7.4 12 31 7.7 3.6 6.5 5.1 100 71 4.8 e9.8 7.4 12 31 7.7 3.6 6.5 5.1 100 71 4.8 e9.8 7.4 12 31 7.7 3.6 6.5 5.1 100 71 4.8 e9.8 7.4 12 31 7.7 3.6 6.5 5.4 2.6 1.6 2.4 4.3 3.9 4.1 3.8 4.3 100 21 31 7.7 8.69 24.4 7.58 7.68 10.8 47.2 16.5 20.7 66.9 13.7 8.2 10.1 10.0 11.0 11.0 11.	21	5.9	71	12	6 5	e n	E 0	3 0	7 2	12	-18	e621	12
23 5.9 30 13 4.8 5.8 5.2 4.0 116 6.4 e9.3 e28 41 24 5.5 e38 12 6.7 7.8 3.4 5.4 140 5.7 e116 e12 12 25 4.2 11 5.9 12 8.2 5.0 6.8 45 5.9 e17 e116 e12 12 12 6.7 7.8 3.4 5.4 140 5.7 e116 e12 12 12 6.6 6.4 11 5.9 12 8.2 5.0 6.8 45 5.9 e17 e11 11 11 12 12 12 12 12 12 12 12 12 12 1													
26 6.4 11 6.2 11 7.4 5.9 12 8.2 5.0 6.8 45 5.9 e17 e11 11 26 6.4 11 6.2 11 7.4 5.2 6.5 211 5.2 e8.4 e13 12 27 4.5 9.5 6.6 9.1 6.6 4.7 5.5 66 5.4 e61 e9.3 11 28 3.7 8.6 3.7 9.7 6.6 88 3.8 32 4.7 e19 7.0 11 29 3.4 8.8 5.2 8.3 6.6 5.9 100 71 4.8 e9.8 7.4 12 30 19 7.3 9.7 7.7 2.6 51 83 4.3 e7.6 22 24 31 7.7 3.6 6.5 4.3 20 e117 e28 TOTAL 262.9 500.3 269.4 757.3 219.9 238.2 323.2 1462.4 493.6 641.7 2072.6 412.5 MEAN 8.48 16.7 8.69 24.4 7.58 7.68 10.8 47.2 16.5 20.7 66.9 13.7 MAX 76 71 22 245 14 88 100 211 130 117 621 52 MIN 3.1 4.0 3.6 4.5 5.4 2.6 1.6 2.4 4.3 3.9 4.1 3.8 CFSH 1.13 2.23 1.16 3.26 1.01 1.03 1.44 6.30 2.20 2.76 8.93 1.84 IN. 1.31 2.48 1.34 3.76 1.09 1.08 1.61 7.26 2.85 3.19 10.29 2.05 E Batimated STATISTICS OF MONTHLY MEAN DATA FOR WATER YEARS 1988 - 1992, BY WATER YEAR (WY) MEAN 3.1.1 16.5 12.4 16.3 15.1 12.4 13.8 20.8 14.1 16.0 29.3 27.4 MAX 75.7 3 1.9 1991 1999 1991 1992 1991 1990 1988 1992 1989 1990 1990 1990 1990 1991 SUMMARY STATISTICS FOR 1991 CALENDAR YEAR FOR 1992 WATER YEAR (WY) SUMMARY STATISTICS FOR 1991 CALENDAR YEAR FOR 1992 WATER YEAR WATER YEAR 1988 - 1992 ANNUAL TOTAL ANNUAL MEAN 13.0 12.7 Aug 8 10.4 Aug 21 10.0 13.0 Aug 21 10.0 13.0 Aug 21 10.0 Aug 21 10.													
26 6.4 11 6.2 11 7.4 5.2 6.5 211 5.2 e8.4 e13 12 27 4.5 9.5 6.6 9.1 6.6 4.7 5.5 66 5.4 e61 e9.3 11 28 3.7 8.6 3.7 9.7 6.6 88 3.8 3.2 4.7 e19 7.0 11 29 3.4 8.8 5.2 8.3 6.6 5.9 100 71 4.8 e9.8 7.4 12 30 19 7.3 9.7 7.7 2.6 51 83 4.3 e9.8 7.4 12 31 7.7 3.6 6.5 4.3 20 e117 e28 TOTAL 262.9 500.3 269.4 757.3 219.9 238.2 323.2 1462.4 493.6 641.7 2072.6 412.5 MAX 76 71 22 245 14 88 10.8 47.2 16.5 20.7 66.9 13.7 MAX 76 71 22 245 14 88 10.0 211 130 117 621 52 MIN 3.1 4.0 3.6 4.5 5.4 2.6 1.6 2.4 4.3 3.9 4.1 3.8 AC-FT 521 992 534 1500 436 472 641 2900 979 1270 4110 818 CFSM 1.13 2.23 1.16 3.26 1.01 1.03 1.44 6.30 2.20 2.76 8.93 1.84 IN. 1.31 2.48 1.34 3.76 1.09 1.18 1.61 7.26 2.45 3.19 10.29 2.05 E Estimated STATISTICS OF MONTHLY MEAN DATA FOR WATER YEARS 1988 - 1992, BY WATER YEAR (WY) MEAN 31.1 16.5 12.4 16.3 15.1 12.4 13.8 20.8 14.1 16.0 29.3 27.4 MAX 57.3 24.2 16.8 24.4 23.6 19.5 23.2 47.2 24.8 26.6 66.9 59.5 (WY) 1991 1989 1991 1992 1991 1990 1988 1992 1989 1989 1992 1993 SUMMARY STATISTICS POR 1991 CALENDAR YEAR FOR 1992 WATER YEAR (WY) SUMMARY STATISTICS POR 1991 CALENDAR YEAR FOR 1992 WATER YEAR WATER YEAR 1988 - 1992 ANNUAL MEAN 13.0 1455.1 Aug 21 621 Aug 21 621 Aug 21 629.9 1991 SUMMARY STATISTICS POR 1991 CALENDAR YEAR FOR 1992 WATER YEAR WATER YEAR 1988 - 1992 ANNUAL MEAN 13.0 2.5 Aug 11 1.6 Apr 15 1.6 Apr 15 1992 ANNUAL MEAN 13.0 2.5 Aug 11 1.6 Apr 15 1.6 Apr 15 1992 ANNUAL MEAN 13.0 2.5 Aug 11 1.6 Apr 15 1.6 Apr 15 1.6 Apr 15 1992 ANNUAL MEAN 13.0 2.5 Aug 11 1.6 Apr 15 1.6 Apr 15 1992 ANNUAL MEAN 13.0 1455.1 Aug 21 621 Aug 21 621 Aug 21 1992 ANNUAL WATER YEAR 1988 - 1992 ANNUAL MEAN 1.4 Apr 12 2.7 Aug 8 3.1 Apr 12 2.7 Aug 8 1991 INSTANTANTANCOUS PERK FLOW 1.74 Aug 21 1992 ANNUAL RONOFF (CFSH) 1.74 Aug 21 16.0 Aug 21 16.0 Aug 21 1992 ANNUAL RONOFF (CFSH) 1.74 Aug 21 16.0 Aug 21 1992 ANNUAL RONOFF (CFSH) 1.74 Aug 21 16.0 Aug 21 1998 INSTANTANTEOUS PERK FLOW 1.74 Aug 21 16.0 Aug 21 1998 INSTANTANTANCOUS PERK FLOW 1.74 Aug 21 16.0 Aug 21 1998 INSTANTANTANCOUS PERK FLOW													
27 4.5 9.5 6.6 9.1 1 6.6 4.7 5.5 66 5.4 e61 e9.3 11 28 3.7 8.6 3.7 9.7 6.6 88 3.8 3.2 4.7 e19 7.0 11 29 3.4 8.8 5.2 8.3 6.6 5.9 100 71 4.8 e9.8 7.4 12 30 19 7.3 9.7 7.7 2.6 51 83 4.3 e7.6 22 24 31 7.7 3.6 6.5 4.3 20 e117 e28 TOTAL 262.9 500.3 269.4 757.3 219.9 238.2 232.2 1462.4 493.6 641.7 2072.6 412.5 MEAN 8.48 16.7 8.69 24.4 7.58 7.68 10.8 47.2 16.5 20.7 66.9 13.7 MAX 76 71 22 245 14 98 100 211 130 117 621 52 MIN 3.1 4.0 3.6 4.5 5.4 28 100 21 130 117 621 52 MIN 3.1 4.0 3.6 4.5 5.4 28 100 21 130 117 621 52 MIN 3.1 3.1 2.23 1.16 3.26 1.01 1.03 1.44 6.30 2.20 2.76 8.93 1.84 CFSM 1.13 2.23 1.16 3.26 1.01 1.03 1.44 6.30 2.20 2.76 8.93 1.84 IN. 1.31 2.48 1.34 3.76 1.09 1.08 1.61 7.26 2.45 3.19 10.29 2.05 E Batimated STATISTICS OF MONTHLY MEAN DATA FOR WATER YEARS 1988 - 1992, BY WATER YEAR (WY) MEAN 31.1 16.5 12.4 16.3 15.1 12.4 13.8 20.8 14.1 16.0 29.3 27.4 MAX 57.3 24.2 16.8 24.4 23.6 19.5 23.2 47.2 24.8 26.6 66.9 59.5 (WY) 1991 1989 1991 1992 1991 1990 1988 1992 1989 1999 1992 1999 MIN 8.48 7.51 8.69 12.1 7.58 7.68 10.4 9.9 8.74 7.43 6.60 6.90 (WY) 1992 1991 1990 1988 1992 1999 1990 1990 1990 1990 1990 1990	25	4.2	11	5.9	12	8.2	5.0	6.8	45	5.9	e1 7	e11	11
27 4.5 9.5 6.6 9.1 6.6 4.7 5.5 66 5.4 e61 e9.3 11 28 3.7 8.6 3.7 9.7 6.6 88 3.8 3.2 4.7 e19 7.0 11 29 3.4 8.8 5.2 8.3 6.6 5.9 100 71 4.8 e9.8 7.4 12 30 19 7.3 9.7 7.7 2.6 51 83 4.3 e7.6 22 24 31 7.7 3.6 6.5 5.9 100 71 4.8 e9.8 7.4 12 30 19 7.3 9.7 7.7 2.6 51 83 4.3 e7.6 22 24 31 7.7 3.6 6.5 5.9 10.0 71 4.8 e9.8 7.4 12 30 19 7.3 9.7 7.7 2.6 51 83 4.3 e7.6 22 24 31 7.7 3.6 6.5 5.9 10.0 71 4.8 e9.8 7.4 12 30 19 9.7 3.6 6.5 5.9 10.0 71 4.8 e9.8 7.4 12 30 19 9.7 3.6 6.5 5.9 10.0 71 4.8 e9.8 7.4 12 31 7.7 3.6 6.5 24.4 7.5 21 31 7.7 3.6 6.5 24.4 7.5 21 31 7.7 3.6 6.5 24.4 7.5 21 31 7.7 20	26	6.4	11	6.2	11	7.4	5.2	6.5	211	5.2	e8.4	e13	12
29 3.4 8.8 5.2 8.3 6.6 5.9 100 71 4.8 e9.8 7.4 12 30 19 7.3 9.7 7.7 2.6 51 83 4.3 e7.6 22 24 31 7.7 3.6 6.5 4.3 2 20 2 e117 e28 2 TOTAL 262.9 500.3 269.4 757.3 219.9 238.2 323.2 1462.4 493.6 641.7 2072.6 412.5 TREAN 8.48 16.7 8.69 24.4 7.58 7.68 10.8 47.2 16.5 20.7 66.9 13.7 MAX 76 71 22 245 14 88 100 211 130 117 621 52 MIN 3.1 4.0 3.6 4.5 5.4 2.6 1.6 2.4 4.3 3.9 4.1 3.8 AC-PT 521 992 534 1500 436 472 641 2900 979 1270 4110 818 CCSM 1.13 2.23 1.16 3.26 1.01 1.03 1.44 6.30 2.20 2.76 8.93 1.84 IN. 1.31 2.48 1.34 3.76 1.09 1.18 1.61 7.26 2.45 3.19 10.29 2.05 • Estimated STATISTICS OF MONTHLY MEAN DATA FOR WATER YEARS 1988 - 1992, BY WATER YEAR (WY) MEAN 31.1 16.5 12.4 16.3 15.1 12.4 13.8 20.8 14.1 16.0 29.3 27.4 MAX 57.3 24.2 16.8 24.4 23.6 15.5 23.2 47.2 24.8 26.6 66.9 55.5 (WY) 1991 1999 1999 1992 1999 1991 1990 1998 1992 1989 MIN 8.48 7.51 8.69 12.1 7.58 7.68 10.4 9.09 8.74 7.43 6.60 6.99 MIN 9.48 7.51 8.69 12.1 7.58 7.68 10.4 9.09 8.74 7.43 6.60 6.99 MIN 8.48 7.51 8.69 12.1 7.58 7.68 10.4 9.09 8.74 7.43 6.60 6.99 MIN 8.48 7.51 8.69 12.1 7.58 7.68 10.4 9.09 8.74 7.43 6.60 6.99 MIN 8.48 7.51 8.69 12.1 7.58 7.68 10.4 9.09 8.74 7.43 6.60 6.99 MIN 991 1992 1991 1992 1999 1992 1992 1991 1990 1996 SUMMARY STATISTICS FOR 1991 CALENDAR YEAR FOR 1992 WATER YEAR YEAR WATER YEARS 1988 - 1992 ANNUAL MEAN 13.0 2.7 Aug 8 3.1 Apr 12 2.7 Aug 8 1992 ANNUAL MEAN 14.6 Apr 15 1992 ANNUAL MEAN 14.6 Apr 15 1.6 Apr 15 1.6 Apr 15 1.6 Apr 15 1992 ANNUAL WEAN 14.2 Aug 21 46.0 Aug 21 1992 ANNUAL SEVEN-DAY MINIMUM 2.7 Aug 8 3.1 Apr 12 2.7 Aug 8 1992 INSTANTANEOUS PEAR FLOW INSTANTANEOUS PEAR FLOW INSTANTANEOUS PEAR FLOW INSTANTANTANEOUS PEAR STAGE ANNUAL RUNOFF (CFSM) 1.74 22 2.7 Aug 8 1910 ANNUAL RUNOFF (CFSM) 1.74 22 2.69 ANNUAL RUNOFF (CFSM) 1.74 22 2.69 ANNUAL RUNOFF (CFSM) 1.74 22 2.69 ANNUAL RUNOFF (CFSM) 1.74 2.79 ANNUAL RUNOFF (CFSM)			9.5	6.6	9.1	6.6	4.7	5.5	66				
30 19 7.3 9.7 7.7 7.7 2.6 51 83 4.3 e7.6 22 24 31 7.7 3.6 6.5 4.3 20 e117 e28 TOTAL 262.9 500.3 269.4 757.3 219.9 238.2 323.2 1462.4 493.6 641.7 2072.6 412.5 MEAN 8.48 16.7 8.69 24.4 7.58 7.68 10.8 47.2 16.5 20.7 66.9 13.7 MAX 76 71 22 245 14 88 100 211 130 117 621 52 MIN 3.1 4.0 3.6 4.5 5.4 2.6 1.6 2.4 4.3 3.9 4.1 3.8 AC-FT 521 992 534 1500 436 472 641 2900 979 1270 4110 818 CFSH 1.13 2.23 1.16 3.26 1.01 1.03 1.44 6.30 2.20 2.76 8.93 1.84 IN. 1.31 2.48 1.34 3.76 1.09 1.18 1.61 7.26 2.45 3.19 10.29 2.05 • Estimated STATISTICS OF MONTHLY MEAN DATA FOR WATER YEARS 1988 - 1992, BY WATER YEAR (WY) MEAN 31.1 16.5 12.4 16.3 15.1 12.4 13.8 20.8 14.1 16.0 29.3 27.4 MAX 57.3 24.2 16.8 24.4 23.6 19.5 23.2 47.2 24.8 26.6 66.9 59.5 (WY) 1991 1989 1991 1992 1991 1990 1988 1992 1989 1989 1992 1989 MIN 8.48 7.51 8.69 12.1 7.58 7.68 10.4 9.09 8.74 7.43 6.60 6.90 (WY) 1992 1991 1992 1989 1992 1992 1991 1989 1990 1990 1990 1990 SUMMARY STATISTICS FOR 1991 CALENDAR YEAR FOR 1992 WATER YEAR WATER YEAR 18.6 HIGHEST ANNUAL MEAN 13.0 2.5 Aug 11 1.6 Apr 15 1.6 Apr 15 1.6 Apr 15 1992 ANNUAL SEVEN-DAY MINIMUM 2.7 Aug 8 3.1 Apr 12 2.7 Aug 8 19.1 MINSTANTANEOUS PEAK FLOW 155 Aug 21 16.0 Aug 21 16.0 8 Aug 24 1988 INSTANTANEOUS PEAK STAGE 1.74 1.74 2.79 2.79 2.49 ANNUAL ROWOFF (CFSM) 1.74 22.6 3.60 1.33.81 10 PERCENT EXCREDS 25 43 40 10 7.5 8.4													
31 7.7 3.6 6.5 4.3 20 e117 e28 TOTAL 262.9 500.3 269.4 757.3 219.9 238.2 333.2 1462.4 493.6 641.7 2072.6 412.5 MEAN 8.48 16.7 8.69 24.4 7.58 7.68 10.8 47.2 16.5 20.7 66.9 13.7 MX 76 71 22 245 14 88 100 211 130 117 621 52 MIN 3.1 4.0 3.6 4.5 5.4 2.6 1.6 2.4 4.3 3.9 4.1 3.8 AC-FT 521 992 534 1500 436 472 641 2900 979 1270 4110 818 CFSM 1.13 2.23 1.16 3.26 1.01 1.03 1.44 6.30 2.20 2.76 8.93 1.84 IN. 1.31 2.48 1.34 3.76 1.09 1.18 1.61 7.26 2.45 3.19 10.29 2.05 E Batimated STATISTICS OF MONTHLY MEAN DATA FOR WATER YEARS 1988 - 1992, BY WATER YEAR (WY) MEAN 31.1 16.5 12.4 16.3 15.1 12.4 13.8 20.8 14.1 16.0 29.3 27.4 MAX 57.3 24.2 16.8 24.4 23.6 19.5 23.2 47.2 24.8 26.6 66.9 59.5 (WY) 1991 1989 1991 1992 1991 1990 1988 1992 1989 1989 1992 1988 MIN 8.48 7.51 8.69 12.1 7.58 7.68 10.4 9.09 8.74 7.43 6.60 6.90 (WY) 1992 1991 1992 1989 1992 1993 1989 1990 1990 1990 1991 SUMMARY STATISTICS FOR 1991 CALENDAR YEAR FOR 1992 WATER YEAR WATER YEAR WATER YEARS 1988 - 1992 ANNUAL TOTAL 4755.1 7654.0 ANNUAL MEAN 13.0 20.9 18.6 611 Aug 21 621 Aug 21 90.9 1991 LOWEST ANNUAL MEAN 13.0 20.9 18.6 611 Aug 21 621 Aug 21 90.9 1991 LOWEST ANNUAL MEAN 13.0 20.9 18.6 611 Aug 21 621 Aug 21 90.9 1991 LOWEST ANNUAL MEAN 13.0 20.9 18.6 621 Aug 21 4680 Aug 24 1888 INSTANTANEOUS PEAR FLOW 4250 Aug 21 4680 Aug 24 1888 INSTANTANEOUS PEAR STAGE 14.74 12.74 Aug 21 16.08 Aug 24 1988 INSTANTANEOUS PEAR STAGE 11.74 22.76 Aug 8 1911 ANNUAL SEVEN-DAY MININUM 2.7 Aug 8 3.1 Apr 12 2.7 Aug 8 1991 ANNUAL SEVEN-DAY MININUM 2.7 Aug 8 3.1 Apr 12 2.7 Aug 8 1991 ANNUAL SEVEN-DAY MININUM 2.7 Aug 8 3.1 Apr 12 2.7 Aug 8 1991 ANNUAL SEVEN-DAY MININUM 1.74 2.79 2.49 ANNUAL SEVEN-DAY MININUM 1.74 2.79 2.49 ANNUAL SEVEN EXCERDS 25 443 40 40 50 PERCENT EXCERDS 26 43 40 50 PERCENT EXCERDS 27 6.8 8.4													
TOTAL 262.9 500.3 269.4 757.3 219.9 238.2 323.2 1462.4 493.6 641.7 2072.6 412.5 MEAN 8.48 16.7 8.69 24.4 7.58 7.68 10.8 47.2 16.5 20.7 66.9 13.7 MAX 76 71 22 245 14 88 10.8 47.2 16.5 20.7 66.9 13.7 MAX 3.6 71 22 245 14 88 10.8 2.4 4.3 3.9 4.1 3.8 AC-FT 521 992 534 1500 436 4.5 5.4 2.6 1.6 2.4 4.3 3.9 4.1 3.8 AC-FT 521 992 534 1500 436 472 641 2900 979 1270 4110 818 CFSM 1.13 2.23 1.16 3.26 1.01 1.03 1.44 6.30 2.20 2.76 8.33 1.84 IN. 1.31 2.48 1.34 3.76 1.09 1.18 1.61 7.26 2.45 3.19 10.29 2.05 • Estimated STATISTICS OF MONTHLY MEAN DATA FOR WATER YEARS 1988 - 1992, BY WATER YEAR (WY) MEAN 31.1 16.5 12.4 16.3 15.1 12.4 13.8 20.8 14.1 16.0 29.3 27.4 MAX 57.3 24.2 16.8 24.4 23.6 19.5 23.2 47.2 24.8 26.6 66.9 59.5 (WY) 1991 1989 1991 1992 1991 1990 1988 1992 1989 1989 1992 1989 MIN 8.48 7.51 8.69 12.1 7.58 7.68 10.4 9.09 8.74 7.43 6.60 6.90 (WY) 1992 1991 1992 1989 1992 1992 1991 1990 1990 1990 1990 199													
MEAN 8.48 16.7 8.69 24.4 7.58 7.68 10.8 47.2 16.5 20.7 66.9 13.7 MAX 76 71 22 245 14 88 100 211 130 117 621 52 MIN 3.1 4.0 3.6 4.5 5.4 2.6 1.6 2.4 4.3 3.9 4.1 3.8 AC-FT 521 992 534 1500 436 472 641 2900 979 1270 4110 818 CFSM 1.13 2.23 1.16 3.26 1.01 1.03 1.44 6.30 2.20 2.76 8.93 1.84 IN. 1.31 2.48 1.34 3.76 1.09 1.18 1.61 7.26 2.45 3.19 10.29 2.05 Estimated STATISTICS OF MONTHLY MEAN DATA FOR WATER YEARS 1988 - 1992, BY WATER YEAR (WY) MEAN 31.1 16.5 12.4 16.3 15.1 12.4 13.8 20.8 14.1 16.0 29.3 27.4 MAX 57.3 24.2 16.8 24.4 23.6 19.5 23.2 47.2 24.8 26.6 66.9 55.5 (WY) 1991 1989 1991 1992 1999 1991 1992 1999 1999													
MAX 76 71 22 245 14 88 100 211 130 117 621 52 MIN 3.1 4.0 3.6 4.5 5.4 2.6 1.6 2.4 4.3 3.9 4.1 3.8 AC-FT 521 992 534 1500 436 472 641 2900 979 1270 4110 818 CFSM 1.13 2.23 1.16 3.26 1.01 1.03 1.44 6.30 2.20 2.76 8.93 1.84 IN. 1.31 2.48 1.34 3.76 1.09 1.18 1.61 7.26 2.45 3.19 10.29 2.05 • Estimated STATISTICS OF MONTHLY MEAN DATA FOR WATER YEARS 1988 - 1992, BY WATER YEAR (WY) MEAN 31.1 16.5 12.4 16.3 15.1 12.4 13.8 20.8 14.1 16.0 29.3 27.4 MAX 57.3 24.2 16.8 24.4 23.6 19.5 23.2 47.2 24.8 26.6 66.9 59.5 (WY) 1991 1999 1991 1992 1999 MIN 8.48 7.51 8.69 12.1 7.58 7.68 10.4 9.09 8.74 7.43 6.60 6.90 (WY) 1992 1991 1992 1999 1992 1992 1991 SUMMARY STATISTICS FOR 1991 CALENDAR YEAR FOR 1992 WATER YEAR WATER YEAR 1988 - 1992 ANNUAL TOTAL 4755.1 7654.0 13.0 20.9 1990 1990 1990 1990 1990 1990 1990 1													
MIN 3.1 4.0 3.6 4.5 5.4 2.6 1.6 2.4 4.3 3.9 4.1 3.8 AC-PT 521 992 534 1500 436 472 641 2900 979 1270 4110 818 CPSM 1.13 2.23 1.16 3.26 1.01 1.03 1.44 6.30 2.20 2.76 8.93 1.84 IN. 1.31 2.48 1.34 3.76 1.09 1.18 1.61 7.26 2.45 3.19 10.29 2.05 Estimated STATISTICS OF MONTHLY MEAN DATA FOR WATER YEARS 1988 - 1992, BY WATER YEAR (WY) MEAN 31.1 16.5 12.4 16.3 15.1 12.4 13.8 20.8 14.1 16.0 29.3 27.4 MAX 57.3 24.2 16.8 24.4 23.6 19.5 23.2 47.2 24.8 26.6 66.9 59.5 (WY) 1991 1989 1991 1992 1991 1992 1991 1990 1990 199													
AC-FT 521 992 534 1500 436 472 641 2900 979 1270 4110 818 CFSM 1.13 2.23 1.16 3.26 1.01 1.03 1.44 6.30 2.20 2.76 8.93 1.84 IN. 1.31 2.48 1.34 3.76 1.09 1.18 1.61 7.26 2.45 3.19 10.29 2.05 E Ratimated STATISTICS OF MONTHLY MEAN DATA FOR WATER YEARS 1988 - 1992, BY WATER YEAR (WY) MEAN 31.1 16.5 12.4 16.3 15.1 12.4 13.8 20.8 14.1 16.0 29.3 27.4 MAX 57.3 24.2 16.8 24.4 23.6 19.5 23.2 47.2 24.8 26.6 66.9 55.5 (WY) 1991 1989 1991 1992 1991 1990 1988 1992 1989 1989 1992 1989 MIN 8.48 7.51 8.69 12.1 7.58 7.68 10.4 9.09 8.74 7.43 6.60 6.90 (WY) 1992 1991 1992 1989 1992 1991 1989 1991 1992 1991 1989 1991 1992 1991 1989 1991 1992 1991 1989 1990 1990 1990 1990 1991 SUMMARY STATISTICS FOR 1991 CALENDAR YEAR FOR 1992 WATER YEAR WATER YEARS 1988 - 1992 ANNUAL TOTAL ANNUAL MEAN 13.0 20.9 18.6 15.7 1990 HIGHEST ANNUAL MEAN 20.9 13.0 20.9 18.6 HIGHEST ANNUAL MEAN 145 Aug 21 621 Aug 21 621 Aug 21 621 Aug 21 1992 LOWEST DAILY MEAN 2.5 Aug 11 1.6 Apr 15 1992 LOWEST DAILY MEAN 2.5 Aug 11 1.6 Apr 15 1992 LOWEST DAILY MEAN 2.5 Aug 11 1.6 Apr 15 1992 LOWEST DAILY MEAN 2.7 Aug 8 3.1 Apr 12 2.7 Aug 8 1991 INSTANTANEOUS PEAK FLOW 1NSTANTANEOUS PEAK FLOW 1NSTANTANEOUS PEAK FLOW 1NSTANTANEOUS PEAK FLOW 1NSTANTANEOUS PEAK STAGE ANNUAL RUNOFF (CFSM) 1.74 2.79 2.49 ANNUAL RUNOFF (CFSM) 1.74 2.79 2.49 ANNUAL RUNOFF (CFSM) 1.74 2.79 2.49 ANNUAL RUNOFF (INCHES) 23.62 38.01 33.81 10 PERCENT EXCERDS 25 43 40 40 50 PERCENT EXCERDS 7.0 7.5 8.4													
CFSM 1.13 2.23 1.16 3.26 1.01 1.03 1.44 6.30 2.20 2.76 8.93 1.84 IN. 1.31 2.48 1.34 3.76 1.09 1.18 1.61 7.26 2.45 3.19 10.29 2.05 • Estimated STATISTICS OF MONTHLY MEAN DATA FOR WATER YEARS 1988 - 1992, BY WATER YEAR (WY) MEAN 31.1 16.5 12.4 16.3 15.1 12.4 13.8 20.8 14.1 16.0 29.3 27.4 MAX 57.3 24.2 16.8 24.4 23.6 19.5 23.2 47.2 24.8 26.6 66.9 59.5 (WY) 1991 1989 1991 1992 1991 1990 1988 1992 1989 1992 1989 MIN 8.48 7.51 8.69 12.1 7.58 7.68 10.4 9.09 8.74 7.43 6.60 6.90 (WY) 1992 1991 1992 1989 1992 1992 1991 1989 1990 1990 1990 1990 1991 SUMMARY STATISTICS FOR 1991 CALENDAR YEAR FOR 1992 WATER YEAR WATER YEARS 1988 - 1992 ANNUAL TOTAL 4755.1 7654.0 13.0 20.9 18.6 15.7 1990 HIGHEST ANNUAL MEAN 13.0 20.9 189.6 15.7 1990 HIGHEST DAILY MEAN 2.5 Aug 11 1.6 Apr 15 1.6 A													
E Batimated STATISTICS OF MONTHLY MEAN DATA FOR WATER YEARS 1988 - 1992, BY WATER YEAR (WY) MEAN 31.1 16.5 12.4 16.3 15.1 12.4 13.8 20.8 14.1 16.0 29.3 27.4 MAX 57.3 24.2 16.8 24.4 23.6 19.5 23.2 47.2 24.8 26.6 66.9 59.5 (WY) 1991 1989 1991 1992 1991 1990 1988 1992 1989 1992 1989 MIN 8.48 7.51 8.69 12.1 7.58 7.68 10.4 9.09 8.74 7.43 6.60 6.90 (WY) 1992 1991 1992 1989 1992 1999 1999 1990 1990 1990 1990 199													
MEAN 31.1 16.5 12.4 16.3 15.1 12.4 13.8 20.8 14.1 16.0 29.3 27.4 MAX 57.3 24.2 16.8 24.4 23.6 19.5 23.2 47.2 24.8 26.6 66.9 59.5 (WY) 1991 1989 1991 1992 1991 1990 1988 1992 1989 1999 1992 1989 MIN 8.48 7.51 8.69 12.1 7.58 7.68 10.4 9.09 8.74 7.43 6.60 6.90 (WY) 1992 1991 1992 1989 1992 1991 1992 1991 1992 1991 1992 1991 1998 1990 1990 1990 1990 1990 1991 1992 1992 1991 1992 1992 1991 1992 1992 1991 1992 1992 1991 1992 1992 1991 1992 1992 1992 1991 1992 1992 1991 1992 1992 1991 1992 1992 1991 1992 1992 1991 1992 1992 1991 1992 1992 1991 1992 1992 1992 1992 1992 1992 1992 1992 1992 1992 1992 1992 1991 1992 199	IN.	1.31	2.48	1.34	3.76	1.09	1.18	1.61	7.26	2.45	3.19	10.29	2.05
MEAN 31.1 16.5 12.4 16.3 15.1 12.4 13.8 20.8 14.1 16.0 29.3 27.4 MAX 57.3 24.2 16.8 24.4 23.6 19.5 23.2 47.2 24.8 26.6 66.9 59.5 (WY) 1991 1989 1991 1992 1991 1990 1988 1992 1989 1989 1992 1989 MIN 8.48 7.51 8.69 12.1 7.58 7.68 10.4 9.09 8.74 7.43 6.60 6.90 (WY) 1992 1991 1992 1989 1992 1991 1989 1990 1990 1990 1990 1991 SUMMARY STATISTICS FOR 1991 CALENDAR YEAR FOR 1992 WATER YEAR WATER YEARS 1988 - 1992 ANNUAL TOTAL 4755.1 3.0 20.9 18.6 HIGHEST ANNUAL MEAN 13.0 20.9 18.6 HIGHEST ANNUAL MEAN 15.7 1990 LOWEST ANNUAL MEAN 15.7 1990 LOWEST DAILLY MEAN 145 Aug 21 621 Aug 21 621 Aug 21 1992 LOWEST DAILLY MEAN 2.5 Aug 11 1.6 Apr 15 1992 ANNUAL SEVEN-DAY MINIMUM 2.7 Aug 8 3.1 Apr 12 2.7 Aug 8 1991 INSTANTANBOUS PEAR FLOW 1NSTANTANBOUS PEAR STAGE 14.27 Aug 21 16.08 Aug 24 1988 INSTANTANBOUS PEAR STAGE 14.27 Aug 21 16.08 Aug 24 1988 ANNUAL RUNOFF (CFSM) 1.74 2.79 2.49 ANNUAL RUNOFF (CFSM) 1.75 8.4	e Bs	timated											
MAX 57.3 24.2 16.8 24.4 23.6 19.5 23.2 47.2 24.8 26.6 66.9 59.5 (WY) 1991 1989 1991 1992 1991 1990 1988 1992 1989 1989 1989 1992 1989 MIN 8.48 7.51 8.69 12.1 7.58 7.68 10.4 9.09 8.74 7.43 6.60 6.90 (WY) 1992 1991 1992 1989 1992 1992 1991 1989 1990 1990 1990 1990 1991 1992 SUMMARY STATISTICS FOR 1991 CALENDAR YEAR FOR 1992 WATER YEAR WATER YEARS 1988 - 1992 ANNUAL MEAN 13.0 20.9 18.6 HIGHEST ANNUAL MEAN 20.9 1992 1991 1990 15.7 1990 HIGHEST ANNUAL MEAN 13.0 20.9 15.7 1990 HIGHEST DAILY MEAN 145 Aug 21 621 Aug 21 621 Aug 21 1992 LOWEST DAILY MEAN 2.5 Aug 11 1.6 Apr 15 1992 LOWEST DAILY MEAN 2.7 Aug 8 3.1 Apr 12 2.7 Aug 8 1991 INSTANTANEOUS PEAK FLOW 4250 Aug 21 4680 Aug 24 1988 INSTANTANEOUS PEAK STAGE 11.74 2.79 2.49 ANNUAL RUNOFF (AC-FT) 9430 15180 13500 2.49 ANNUAL RUNOFF (INCHES) 23.62 38.01 33.81 10 PERCENT EXCREDS 7.0 7.5 8.4	STATIST	CICS OF M	KONTHLY ME	AN DATA F	OR WATER Y	EARS 1988	- 1992	, BY WATER	YBAR (WY)			
MAX 57.3 24.2 16.8 24.4 23.6 19.5 23.2 47.2 24.8 26.6 66.9 59.5 (WY) 1991 1989 1991 1992 1991 1990 1988 1992 1989 1989 1989 1992 1989 MIN 8.48 7.51 8.69 12.1 7.58 7.68 10.4 9.09 8.74 7.43 6.60 6.90 (WY) 1992 1991 1992 1989 1992 1992 1991 1989 1990 1990 1990 1990 1991 1992 1991 1992 1991 1992 1991 1989 1990 1990 1990 1990 1991 1991	MEAN	31.1	16.5	12.4	16.3	15.1	12.4	13.8	20.8	14.1	16.0	29.3	27.4
MY	MAX											66.9	59.5
SUMMARY STATISTICS	(WY)				1992	1991	1990	1988					
SUMMARY STATISTICS FOR 1991 CALENDAR YEAR FOR 1992 WATER YEAR WATER YEARS 1988 - 1992 ANNUAL TOTAL 4755.1 7654.0 ANNUAL MEAN 13.0 20.9 18.6 HIGHEST ANNUAL MEAN 20.9 1992 LOWEST ANNUAL MEAN 15.7 1990 HIGHEST DAILY MEAN 145 Aug 21 621 Aug 21 621 Aug 21 1992 LOWEST DAILY MEAN 2.5 Aug 11 1.6 Apr 15 1.6 Apr 15 1992 ANNUAL SEVEN-DAY MINIMUM 2.7 Aug 8 3.1 Apr 12 2.7 Aug 8 1991 INSTANTANEOUS PEAK FLOW 4250 Aug 21 4680 Aug 24 1988 INSTANTANEOUS PEAK STAGE 14.27 Aug 21 16.08 Aug 24 1988 INSTANTANEOUS PEAK STAGE 15180 13500 ANNUAL RUNOFF (AC-FT) 9430 15180 13500 ANNUAL RUNOFF (CFSM) 1.74 2.79 2.49 ANNUAL RUNOFF (INCHES) 23.62 38.01 33.81 10 PERCENT EXCERDS 25 43 40 FOR 1992 WATER YEAR WATER YEAR WATER YEAR WATER YEAR 1992 18.6 18.6 20.9 1992 18.6 Aug 21 Aug 21 621 Aug 21 2.7 Aug 8 1991 1.6 Apr 15 1992 1.7 Aug 8 1991 1.7 Aug 8 3.1 Apr 12 2.7 Aug 8 1991 1.7 Aug 8 3.1 Apr 12 2.7 Aug 8 1991 1.7 Aug 8 3.1 Apr 12 2.7 Aug 8 1991 1.7 Aug 8 1991 1.7 Aug 8 3.1 Apr 12 2.7 Aug 8 3.1 Apr 12 2.7 Aug 8 1991 1.7 Aug 8 3.1 Apr 12 2.7 Aug 8 3.1 Apr 12 2.7 Aug 8 1991 1.7 Aug 8 3.1 Apr 12 2.7 Aug 8 3.1 Apr 12 2.7 Aug 8 1991 1.7 Aug 8 3.1 Apr 12 2.7 Aug 8 3.1 Apr 12 2.7 Aug 8 1991 1.7 Aug 8 3.1 Apr 12 2.7 Aug 8 3.1 Apr 12 2.7 Aug 8 1991 1.7 Aug 8 3.1 Apr 12 2.7 Aug 8 3.1 Apr 12 2.7 Aug 8 1991 1.7 Aug 8 3.1 Apr 12 2.7 Aug													
ANNUAL TOTAL ANNUAL MEAN 13.0 20.9 18.6 HIGHEST ANNUAL MEAN 15.7 1990 HIGHEST DAILY MEAN 145 Aug 21 1621 Aug 21 16	(WY)	1992	1991	1992	1989	1992	1992	1991	1989	1990	1990	1990	1991
ANNUAL MEAN 13.0 20.9 18.6 HIGHEST ANNUAL MEAN 20.9 1992 LOWEST ANNUAL MEAN 145 Aug 21 621 Aug 21 621 Aug 21 1992 LOWEST DAILY MEAN 2.5 Aug 11 1.6 Apr 15 1.6 Apr 15 1992 LOWEST DAILY MEAN 2.7 Aug 8 3.1 Apr 12 2.7 Aug 8 1991 INSTANTANEOUS PEAK FLOW 4250 Aug 21 4680 Aug 24 1988 INSTANTANEOUS PEAK STAGE 14.27 Aug 21 16.08 Aug 24 1988 INSTANTANEOUS PEAK STAGE 15180 13500 ANNUAL RUNOFF (AC-FT) 9430 15180 13500 ANNUAL RUNOFF (INCHES) 23.62 38.01 33.81 10 PERCENT EXCEEDS 7.0 7.5 8.4	SUMMARY	STATIST	'ICS	FOR	1991 CALEN	DAR YEAR	1	FOR 1992 WA	TER YEAR		WATER	YEARS 1988	- 1992
HIGHEST ANNUAL MEAN 145 Aug 21 621 Aug 21 621 Aug 21 1992 1993 1994 199												_	
LOWEST ANNUAL MEAN					13.0			20.9					****
HIGHEST DAILY MEAN 145 Aug 21 621 Aug 21 621 Aug 21 1992 LOWEST DAILY MEAN 2.5 Aug 11 1.6 Apr 15 1992 ANNOLL SEVEN-DAY MINIMUM 2.7 Aug 8 3.1 Apr 12 2.7 Aug 8 1991 INSTANTANEOUS PEAK FLOW 4250 Aug 21 4680 Aug 24 1988 INSTANTANEOUS PEAK STAGE 14.27 Aug 21 16.08 Aug 24 1988 INSTANTANEOUS PEAK STAGE 15180 13500 ANNOLL RUNOFF (AC-FT) 9430 15180 13500 ANNOLL RUNOFF (CFSM) 1.74 2.79 2.49 ANNOLL RUNOFF (INCHES) 23.62 38.01 33.81 10 PERCENT EXCEEDS 7.0 7.5 8.4													
LOWEST DAILY MEAN 2.5 Aug 11 1.6 Apr 15 1.6 Apr 15 1992 ANNUAL SEVEN-DAY MINIMUM 2.7 Aug 8 3.1 Apr 12 2.7 Aug 8 1991 INSTANTANEOUS PEAK FLOW 4250 Aug 21 4680 Aug 24 1988 INSTANTANEOUS PEAK STAGE 11.27 Aug 21 16.08 Aug 24 1988 ANNUAL RUNOFF (AC-FT) 9430 15180 13500 ANNUAL RUNOFF (CFSM) 1.74 2.79 2.49 ANNUAL RUNOFF (INCHES) 23.62 38.01 33.81 10 PERCENT EXCERDS 25 43 40 50 PERCENT EXCERDS 7.0 7.5 8.4					145	λ uσ 21		621	Aug 21				
ANNUAL SEVEN-DAY MINIMUM 2.7 Aug 8 3.1 Apr 12 2.7 Aug 8 1991 INSTANTANEOUS PEAK FLOW 4250 Aug 21 4680 Aug 24 1988 INSTANTANEOUS PEAK STAGE 14.27 Aug 21 16.08 Aug 24 1988 ANNUAL RUNOFF (AC-FT) 9430 15180 13500 ANNUAL RUNOFF (CFSM) 1.74 2.79 2.49 ANNUAL RUNOFF (INCHES) 23.62 38.01 33.81 10 PERCENT EXCERDS 25 43 40 50 PERCENT EXCERDS 7.0 7.5 8.4												6 Apr	15 1992
INSTANTANEOUS PEAK STAGE ANNUAL RUNOFF (AC-FT) 9430 ANNUAL RUNOFF (CFSM) 1.74 2.79 2.49 ANNUAL RUNOFF (INCHES) 23.62 38.01 33.81 10 PERCENT EXCERDS 7.0 7.5 8.4								3.1	Apr 12				
ANNUAL RUNOFF (AC-FT) 9430 15180 13500 ANNUAL RUNOFF (CFSM) 1.74 2.79 2.49 ANNUAL RUNOFF (INCHES) 23.62 38.01 33.81 10 PERCENT EXCERDS 25 43 40 50 PERCENT EXCERDS 7.0 7.5 8.4													
ANNUAL RUNOFF (CFSM) 1.74 2.79 2.49 ANNUAL RUNOFF (INCHES) 23.62 38.01 33.81 10 PERCENT EXCERDS 25 43 40 50 PERCENT EXCERDS 7.0 7.5 8.4				i .	0422				Aug 21				24 1988
ANNUAL RUNOFF (INCHES) 23.62 38.01 33.81 10 PERCENT EXCEEDS 25 43 40 50 PERCENT EXCEEDS 7.0 7.5 8.4													
10 PERCENT EXCERDS 25 43 40 50 PERCENT EXCERDS 7.0 7.5 8.4													
	10 PBRC	ENT BXCE	RDS		25								
90 PERCENT EXCERDS 3.5 4.1 4.7													
	90 PBRC	ENT BXCE	RDS		3.5			4.1			4.	7	

50048770 RIO PIEDRAS AT EL SENORIAL, PR--Continued

WATER-QUALITY RECORDS

PERIOD OF RECORDS. -- Water years 1988 to current year.

INSTRUMENTATION. -- USD-77 and automatic sediment sampler.

PERIOD OF DAILY RECORD .--

SUSPENDED-SEDIMENT DISCHARGE: April 1988 to September 1992.

EXTREMES FOR PERIOD OF DAILY RECORD .--

SEDIMENT CONCENTRATION: Maximum daily mean, 24,600 mg/L Sep. 18, 1989; Minimum daily mean, 2 mg/L November 18, 1988.

SEDIMENT LOADS: Maximum daily mean, e114,000tons (e103,000tonnes) Sep. 18, 1989; Minimum daily mean, 0.04 ton (0.03 tonne) May 6, 1990.

EXTREMES FOR WATER YEAR 1992.--SEDIMENT CONCENTRATION: Maximum daily mean, 10,700 mg/L Jan. 05, 1992; Minimum daily mean, 10 mg/l several days.

SEDIMENT LOADS: Maximum daily mean, e114,000 tons (e103,000 tonnes) Jan. 05, 1992; Minimum daily mean, 0.05 ton (0.04 tonne) Apr. 15.

	MRAN			MRAN		MRAN			
	MRAN	CONCEN-	SEDIMENT	Mean	CONCEN-	Sediment	MRAN	CONCEN-	SRDIMENT
	DISCHARGE	TRATION	DISCHARGE	DISCHARGE	TRATION	DISCHARGE	DISCHARGE	TRATION	DISCHARGE
DAY	(CFS)	(MG/L)	(TONS/DAY)	(CFS)	(MG/L)	(TONS/DAY)	(CFS)	(MG/L)	(TONS/DAY)
		OCTOBER		1	NOVEMBER		1	DECEMBER	
1	11	126	8.0	9.7	102	4.3	6.9	64	1.3
2	6.3	71	1.4	31	456	87	10	98	3.2
3	5.7	49	.79	17	220	29	20	255	25
ă	5.9	61	1.1	12		5.7	14	152	6.1
5	8.6	83	3.0	6.4	123	1.3	12	165	7.2
3	0.0	83	3.0	0.4	60	1.3	14	165	/··
6 7	4.4	33	. 37	7.7	77	2.2	6.3	58	1.1
7	4.1	29	.31	25	659	99	4.7	40	.54
8	12	158	34	47	700	158	6.7	35	. 63
9	4.7	37	.50	15	188	9.4	5.9	33	. 55
10	3.7	29	.29	10	110	4.1	4.7	25	.29
11	3.6	25	.22	5.7	48	.80	4.9	39	. 55
12	3.4	24	.21	e5.9	54	e.84	11	151	22
13	3.1	22	.18	e7.7	76	e2.0	5.9	63	1.8
14	3.4	25	. 26	e4.1	39	e.45	7.1	95	3.4
15	4.5	39	.68	7.9	71	2.4	4.1	32	.38
16	3.2	24	.21	12	126	10	6.7	87	2.4
17	3.1	24	.21	e8.0	39	e.84	6.7	61	1.2
18	76	1670	2990	e6.0	50	e.82	9.1	52	1.5
19	16	148	7.3	e5.0	40	e.54	7.8	99	3.7
20	6.4	53	. 89	4.0	38	.67	22	299	51
21	5.9	51	. 84	71	1400	1660	12	180	7.1
22	7.6	61	1.5	58		289	15	220	13
23	5.9	53	1.1	30	812 441	157	13	190	10
24	5.5						12	125	6.9
25		31	.44	e38	459	e83			1.1
45	4.2	36	. 39	11	94	2.8	5.9	56	1.1
26	6.4	71	2.8	11	106	3.6	6.2	44	.95
27	4.5	38	.49	9.5	79	2.3	6.6	67	2.5
28	3.7	22	. 23	8.6	67	1.5	3.7	30	.31
29	3.4	37	.47	8.8	96	2.7	5.2	42	.78
30	19	242	45	7.3	89	1.7	9.7	99	15
31	7.7	77	2.7				3.6	22	. 23
TOTAL	262.9		3105.88	500.3		2622.96	269.4		191.71

e Estimated

187

SEDIMENT DISCHARGE, SUSPENDED (TONS/DAY), WATER YEAR OCTOBER 1991 TO SEPTEMBER 1992

DAY	MRAN DISCHARGE (CFS)	MRAN CONCEN- TRATION (MG/L)	SEDIMENT DISCHARGE (TONS/DAY)	MRAN DISCHARGE (CFS)	MRAN CONCEN- TRATION (MG/L)	SEDIMENT DISCHARGE (TONS/DAY)	MRAN DISCHARGE (CFS)	MRAN CONCEN- TRATION (MG/L)	SEDIMENT DISCHARGE (TONS/DAY)
		JANUARY		1	PBBRUARY			MARCH	
1	10	127	14	8.8	38	.86	4.7	30	.37
2	e6.0	67	e1.1	e14	174	e20	4.4	16	. 19
3	e4.5	42	e.51	e11	131	e4.5	5.0	15	.20
4	12	126	5.9	e7.6	53	e1.1	5.7	30	.46
5	245	5850	11100	e7.2	40	e.74	4.4	40	. 48
6	163	3180	3010	6.8	42	.76	5.2	41	.57
7	16	175	9.8	6.7	48	.92	4.0	36	. 39
8	5.6	53	.88	7.2	46	.96	4.7	34	. 42
9	19	245	62	5.5	41	.63	3.9	33	. 34
10	73	1230	428	5.9	35	.59	5.0	35	. 47
11	13	136	5.5	6.1	30	.47	5.6	43	. 65
12	8.7	68	1.4	6.4	30	.50	4.4	40	. 47
13	13	165	11	5.4	30	.45	5.7	41	. 62
14	5.0	22	.30	7.0	65	1.7	5.9	61	. 97
15	5.4	24	.34	6.8	68	1.7	4.5	82	. 99
16	e25	21	1.4	6.7	58	1.2	5.6	103	1.6
17	e16	126	6.5	7.8	71	1.8	8.0	119	2.6
18	14	138	6.1	7.4	79	1.9	5.6	84	1.3
19	6.5	55	1.0	9.6	91	2.7	6.5	55	1.2
20	7.4	50	1.1	7.0	64	1.3	5.9	59	1.1
21	6.5	50	. 83	8.0	70	1.5	5.8	51	1.1
22	6.9	64	1.6	12	138	16	3.4	24	.21
23	4.8	31	. 37	5.8	44	. 69	5.2	47	.78
24	6.7	40	.74	7.8	58	1.2	3.4	23	. 20
25	12	129	5.5	8.2	70	1.5	5.0	56	. 90
26	11	110	5.1	7.4	68	1.4	5.2	41	.78
27	9.1	83	2.4	6.6	60	1.1	4.7	39	.72
28	9.7	90	2.7	6.6	56	1.0	88	1900	4820
29	8.3	53	1.2	6.6	56	1.0	5.9	98	1.6
30	7.7	34	.76				2.6	73	.51
31	6.5	17	.33				4.3	70	. 82
TOTAL	757.3		14688.36	219.9		70.17	238.2		4843.01

e Estimated

50048770 RIO PIRDRAS AT EL SENORIAL, PR--Continued

DAY	MEAN DISCHARGE (CFS)	MRAN CONCEN- TRATION (MG/L)	SEDIMENT DISCHARGE (TONS/DAY)	MEAN DISCHARGE (CFS)	MEAN CONCEN- TRATION (MG/L)	SEDIMENT DISCHARGE (TONS/DAY)	MEAN DISCHARGE (CFS)	MEAN CONCEN- TRATION (MG/L)	SEDIMENT DISCHARGE (TONS/DAY)
		APRIL			MAY			JUNE	
1	4.2	60	. 68	139	2160	3400	41	699	385
2 3	4.3	47	. 54	148	2460	2030	31	366	38
3	4.5	35	. 42	20	186	11	12	86	2.8
4	4.7	37	.46	13	135	6.4	8.5	82	2.2
5	3.1	22	. 18	11	115	4.6	6.5	60	1.2
6	3.0	22	.18	63	1090	969	10	96	7.7
7	4.6	35	. 44	7.9	69	1.8	e130	2070	e727
8	4.9	61	. 81	5.8	64	1.2	e80	1600	e346
9 10	4.9	49	. 87	15	202	39	e25	711	e48
10	12	137	16	8.3	77	2.3	e15	216	e8.7
11	5.8	45	.73	6.8	57	3.2	e10	120	e3.2
12	4.4	22	.28	3.9	44	.50	e8.0	80	e1.7
13	2.0	18	.09	3.2	32	.32	e10	80	e2.2
14	3.2	13	. 12	2.8	30	.27	10	125	5.3
15	1.6	10	. 05	2.4	12	.08	9.2	97	6.1
16	2.0	10	.06	98	2090	2280	6.1	61	1.3
17	4.1	50	. 87	11	117	5.6	4.8	32	. 42
18	4.6	44	.77	68	1410	1530	4.4	26	.28
19	49	2110	1970	26	312	34	5.2	49	.78
20	7.8	97	2.1	13	145	14	4.9	34	.46
21	3.0	45	. 37	7.2	51	.93	12	131	7.3
22	2.5	19	. 12	5.1	42	. 63	7.6	69	1.7
23	4.0	35	.60	116	2480	2080	6.4	63	1.6
24	5.4	64	1.1	140	2100	1460	5.7	29	.48
25	6.8	80	2.2	45	564	92	5.9	23	.38
26	6.5	7 7	2.1	211	4330	7860	5.2	21	. 33
27	5.5	80	1.6	66	979	245	5.4	18	. 28
28	3.8	49	.70	32	417	90	4.7	16	. 22
29	100	3220	3710	71	1350	1280	4.8	16	. 22
30	51	803	372	83	1420	623	4.3	12	. 15
31				20	262	16			
TOTAL	323.2		6086.44	1462.4		24080.83	493.6		1601.00

e Rstimated

50048770 RIO PIEDRAS AT EL SENORIAL, PR--Continued SEDIMENT DISCHARGE, SUSPENDED (TONS/DAY), WATER YEAR OCTOBER 1991 TO SEPTEMBER 1992

MBAN MRAN MRAN MEAN CONCRN-SEDIMENT MRAN CONCEN-SEDIMENT MEAN CONCEN-SEDIMENT DISCHARGE TRATION DISCHARGE DISCHARGE TRATION DISCHARGE (MG/L) (TONS/DAY) DISCHARGE TRATION DISCHARGE (MG/L) (TONS/DAY) DAY (CFS) (MG/L) (TONS/DAY) (CFS) (CFS) JULY AUGUST SEPTEMBER 4.2 .18 .21 .22 1 2 e22 465 e3.4 e28 e11 114 20 20 117 e203 e15 e7.3 411 336 e7.6 e28 84 60 e5.4 3.8 7.6 3 3.9 e17 e. 87 **4** 5 225 40 .41 6.9 53 1.1 e161 3000 e5200 47 27 25 e27 e98 6 7 6.1 .43 .34 5.5 e27 9.1 5.4 375 764 763 4.6 e21 2.1 311 86 13 e7.3 . 91 8 121 76 e1.5 63 26 9.4 368 55 2.6 5190 e23100 41 . 51 86 10 e281 5240 e24700 4.7 37 .46 22 11 289 34 e31 437 e37 5.4 41 . 59 1.3 171 15 9.0 50 440 12 e16 e25 264 330 e11 e69 5.4 6.5 44 50 . 64 . 87 28 13 14 15 14 13 320 201 e289 5740 e25700 12 11 **e**30 360 e41 45 1.3 16 6.6 81 1.7 e11 167 e5.0 8.4 22 . 48 2.4 .93 .87 114 94 60 17 18 6.9 5.7 75 52 e4.7 e1.5 10 7.4 54 77 1.5 e4.4 e1.1 1.5 5.3 50 e.66 42 720 733 20 519 47 805 e5.4 42 884 12 7.7 21 **e**18 174 e8.5 e621 10700 e114000 143 6.1 22 23 24 e4.5 e2.6 82 792 e12 140 2.0 e40 767 e83 e9.3 102 e28 e12 466 e113 41 814 5.0 2270 e2800 e3.7 12 132 25 e17 229 e3.2 3.6 110 26 125 e8.4 e2.8 e13 114 e4.0 12 91 102 2.8 e777 27 e61 e19 1020 e9.3 105 e2.6 11 1.8 28 208 104 77 7.0 75 108 e9.8 e7.6 e2.8 29 84 306 1.9 12 97 3.4 e1.6 22 296 24 31 e117 2290 e3160 e28 420 e60 TOTAL 641.7 7629.58 2072.6 --- 193610.87 412.5 3052.70 YEAR 7654.0 261583.51

e Estimated

50048770 RIO PIEDRAS AT EL SENORIAL, PR--Continued

WATER QUALITY DATA, WATER YEAR OCTOBER 1991 TO SEPTEMBER 1992

PARTICLE-SIZE DISTRIBUTION OF SUSPENDED SEDIMENT

DATE	TIME	DIS- CHARGE, INST. CUBIC FEBT PER SBCOND	SEDI - MENT, SUS- PENDED (MG/L)	SUS- PENDED	SED. SUSP. FALL DIAM. PERCENT FINER THAN .002 MM	SED. SUSP. FALL DIAM. PERCENT FINER THAN .004 MM	FINER THAN
MAR 1992							
28	1625	e88	43300	e10300	24	34	48
APR						37	51
29 May	2255	390	28700	30200	27	37	51
16	1200	798	45700	98500	22	33	44
23	1753	172	8200	3810	26	34	41
AUG							
05	0330	1390	38100	143000	25	35	43
DATE	SED. SUSP. FALL DIAM. PERCENT FINER THAN	FINER THAN	FINER THAN	FINER THAN	SED. SUSP. SIEVE DIAM. PERCENT FINER THAN .250 MM	SED. SUSP. SIEVE DIAM. PERCENT FINER THAN .500 MM	FINER THAN
MAR 1992							
28	61	76	89	96	98	99.7	100
APR							
29 May	64	75	90	97	99	99.8	100
16	62	68	83	92	98	99.7	100
23 AUG	51	56	75	85	95	99.5	100
05	56	67	83	92	98	99.8	100

50048770 RIO PIEDRAS AT EL SENORIAL, PR--Continued WATER QUALITY DATA, WATER YEAR OCTOBER 1991 TO SEPTEMBER 1992 81

SILT AN	D CLAY	PERCENT	OF	SUSPENDED	SEDIMENL

DATE	TIKE	STREAM- FLOW, INSTAN- TANEOUS (CFS)	SEDI - MENT, SUS- PENDED (MG/L)	SEDI- MENT, DIS- CHARGE, SUS- PENDED (T/DAY)	SED. SUSP. SIEVE DIAM. PERCENT FINER THAN .062 MM
NOV 1991					
20 MAR 1992	1458	5	444	6	98
29	1830	479	4180	5410	82
30	1124	16	247	11	94
MAY					
01	1850	209	6310	3560	85
16	1200	798	1870	4020	77
23	1908	381	6730	6920	54

50048800 RIO PIRDRAS NEAR RIO PIEDRAS, PR

WATER-QUALITY RECORDS

LOCATION.--Lat 18°22'.15", long 66°03'40", at bridge on Winston Churchill Avenue in the El Señorial Housing area, 0.5 mi (0.8 km) west of Highway 176, and 2.5 mi (4.0 km) southwest of Río Piedras plaza.

DRAINAGE AREA. -- 8.17 m1 2 (20.9 km2).

PERIOD OF RECORD .-- Water years 1972 to current year.

WATER QUALITY DATA, WATER YEAR OCTOBER 1991 TO SEPTEMBER 1992

		MATO	C GOVERNIE DA	IIN, MAIDI	N IBAN C	nado i o	1991 10	SPE I BELLIAN	1 <i>)</i>		
DATE	TIME	DIS- CHARGE, INST. CUBIC FEET PER SECOND	CIFIC V CON- E DUCT- (S ANCE	ARD I	EMPER- ATURE WATER DEG C)	TUR- BID- ITY (NTU)	OXYGEN DIS- SOLVE (MG/L	CENT D SATUR-	ICAL (HIGH	COLI- FORM, FECAL, 0.45 UM-MF (COLS./ 100 ML)	STREP- TOCOCCI FECAL, (COLS. PER 100 ML)
OCT 1991											
07 DBC	1200	4.1	442	8.1	28.5	8.5	7.	6 97	13	56000	22000
11 FRB 1992	1050	5.6	433	7.4	23.5	2.4	7.	0 93	15	K12000	6300
10	1045	5.7	380	7.5	25.0	3.7	3.	6 60	16	K83000	K40000
04 JUN	0830	7.0	430	7.3	24.0	14	7.	7 90	22	39000	23000
08	1115	28	415	7.2	27.0	7.0	8.	2 79	32	7000	21000
20	1200	9.3	437	7.9	29.4	5.0	7.	9 72	11	3000	3500
	NI To	OTAL DI	MAGNE CIUM SIUM S- DIS- LVRD SOLVE	4, SODIU	M, J	ND-	POTAS- L SIUM, W DIS- T		LFIDE D	LFATE RI IS- Di	HLO- IDE, IS- DLVRD

							YTKY-			
	HARD-		Magne -		SODIUM	POTAS-	LINITY			CHLO-
	ness	CALCIUM	SIUM,	SODIUM,	AD-	SIUM,	WAT WH		SULFATE	RIDE,
	TOTAL	DIS-	DIS-	DIS-	SORP-	DIS-	TOT FET	SULFIDE	DIS-	DIS-
	(MG/L	SOLVED	SOLVED	SOLVED	TION	SOLVED	FIELD	TOTAL	SOLVED	SOLVED
DATE	AS	(MG/L	(MG/L	(MG/L	RATIO	(MG/L	MG/L AS	(MG/L	(MG/L	(NG/L
	CACO3)	AS CA)	AS MG)	AS NA)		AS K)	CACO3	AS S)	AS SO4)	AS CL)
OCT 1991										
07	160	43	13	29	1	2.9	160	<0.5	19	33
DEC										
11							170			
FBB 1992										
10							130			
MAY										
04	140	38	12	28	1	3.4	130	<0.5	33	40
JUN										
08							82			
AUG										
20	150	43	13	27	0.9	3.2	160		27	35
			SOLIDS,		RESIDUE					
	FLUO-	SILICA,	SUM OF	SOLIDS,	TOTAL	NITRO-	NITRO-	NITRO-	NITRO-	NITRO-
	RIDE,	DIS-	CONSTI-	DIS-	AT 105	GEN,	GEN,	GEN,	GEN,	GEN,
	RIDE, DIS-	DIS- SOLVED	CONSTI- TURNTS,	SOLVED	AT 105 DEG. C,	GEN, NITRATE	GEN, NITRITE	GEN, NO2+NO3	GEN, AMMONIA	GEN, ORGANIC
DATE	DIS-	SOLVED	TURNTS,	SOLVED	DEG. C,	NITRATE	NITRITE	NO2+NO3	AMMONIA	ORGANIC
DATE	DIS- SOLVED	SOLVED (MG/L	TURNTS, DIS-	SOLVED (TONS	DEG. C, SUS-	NITRATE TOTAL	NITRITE TOTAL	NO2+NO3 TOTAL	AMMONIA TOTAL	ORGANIC TOTAL
DATE	DIS- SOLVED (MG/L	SOLVED (MG/L AS	Turnts, Dis- Solved	SOLVED (TONS PER	DEG. C, SUS- PENDED	NITRATE TOTAL (MG/L	NITRITE TOTAL (MG/L	NO2+NO3 TOTAL (MG/L	AMMONIA TOTAL (MG/L	ORGANIC TOTAL (MG/L
OCT 1991	DIS- SOLVED (MG/L AS F)	SOLVED (MG/L AS SIO2)	Tuents, DIS- SOLVED (MG/L)	SOLVED (TONS PER DAY)	DEG. C, SUS- PENDED (MG/L)	NITRATE TOTAL (MG/L AS N)	NITRITE TOTAL (MG/L AS N)	NO2+NO3 TOTAL (MG/L AS N)	AMMONIA TOTAL (MG/L AS N)	ORGANIC TOTAL (MG/L AS N)
OCT 1991 07	DIS- SOLVED (MG/L	SOLVED (MG/L AS	Turnts, Dis- Solved	SOLVED (TONS PER	DEG. C, SUS- PENDED	NITRATE TOTAL (MG/L	NITRITE TOTAL (MG/L	NO2+NO3 TOTAL (MG/L	AMMONIA TOTAL (MG/L	ORGANIC TOTAL (MG/L
OCT 1991	DIS- SOLVED (MG/L AS F)	SOLVED (MG/L AS SIO2)	Tuents, DIS- SOLVED (MG/L)	SOLVED (TONS PER DAY)	DEG. C, SUS- PENDED (MG/L)	NITRATE TOTAL (MG/L AS N)	NITRITE TOTAL (MG/L AS N)	NO2+NO3 TOTAL (MG/L AS N)	AMMONIA TOTAL (MG/L AS N)	ORGANIC TOTAL (MG/L AS N)
OCT 1991 07 DEC 11	DIS- SOLVED (MG/L AS F)	SOLVED (MG/L AS SIO2)	Tuents, DIS- SOLVED (MG/L)	SOLVED (TONS PER DAY)	DEG. C, SUS- PENDED (MG/L)	NITRATE TOTAL (MG/L AS N)	NITRITE TOTAL (MG/L AS N)	NO2+NO3 TOTAL (MG/L AS N)	AMMONIA TOTAL (MG/L AS N)	ORGANIC TOTAL (MG/L AS N)
OCT 1991 07 DEC 11 FEB 1992	DIS- SOLVED (MG/L AS F)	SOLVED (MG/L AS SIO2)	TUENTS, DIS- SOLVED (MG/L)	SOLVED (TONS PER DAY)	DEG. C, SUS- PENDED (MG/L)	NITRATE TOTAL (MG/L AS N) 0.640 0.790	NITRITE TOTAL (MG/L AS N) 0.150 0.180	NO2+NO3 TOTAL (MG/L AS N) 0.790	AMMONIA TOTAL (MG/L AS N) 0.930	ORGANIC TOTAL (MG/L AS N) 0.37
OCT 1991 07 DEC 11 FEB 1992 10	DIS- SOLVED (MG/L AS F)	SOLVED (MG/L AS SIO2)	TUENTS, DIS- SOLVED (MG/L)	SOLVED (TONS PER DAY)	DEG. C, SUS- PENDED (MG/L)	NITRATE TOTAL (MG/L AS N)	NITRITE TOTAL (MG/L AS N)	NO2+NO3 TOTAL (MG/L AS N)	AMMONIA TOTAL (MG/L AS N)	ORGANIC TOTAL (MG/L AS N)
OCT 1991 07 DEC 11 FEB 1992 10	DIS- SOLVED (MG/L AS F)	SOLVED (MG/L AS SIO2)	TUENTS, DIS- SOLVED (MG/L) 269	SOLVED (TONS PER DAY)	DEG. C, SUS- PENDED (MG/L) 22 1	NITRATE TOTAL (MG/L AS N) 0.640 0.790 0.630	NITRITE TOTAL (MG/L AS N) 0.150 0.180	NO2+NO3 TOTAL (MG/L AS N) 0.790 0.970 0.670	AMMONIA TOTAL (MG/L AS N) 0.930 0.740 0.310	ORGANIC TOTAL (MG/L AS N) 0.37 0.56
OCT 1991 07 DRC 11 FEB 1992 10 MAY 04	DIS- SOLVED (MG/L AS F)	SOLVED (MG/L AS SIO2)	TUENTS, DIS- SOLVED (MG/L)	SOLVED (TONS PER DAY)	DEG. C, SUS- PENDED (MG/L)	NITRATE TOTAL (MG/L AS N) 0.640 0.790	NITRITE TOTAL (MG/L AS N) 0.150 0.180	NO2+NO3 TOTAL (MG/L AS N) 0.790	AMMONIA TOTAL (MG/L AS N) 0.930 0.740	ORGANIC TOTAL (MG/L AS N) 0.37
OCT 1991 07 DEC 11 FEB 1992 10 MAY 04 JUN	DIS- SOLVED (MG/L AS F)	SOLVED (MG/L AS SIO2)	TUENTS, DIS- SOLVED (MG/L) 269	SOLVED (TONS PER DAY)	DEG. C, SUS- PENDED (MG/L) 22 1 1	NITRATE TOTAL (MG/L AS N) 0.640 0.790 0.630 0.570	NITRITE TOTAL (MG/L AS N) 0.150 0.180 0.040	NO2+NO3 TOTAL (MG/L AS N) 0.790 0.970 0.670 0.600	AMMONIA TOTAL (MG/L AS N) 0.930 0.740 0.310	ORGANIC TOTAL (MG/L AS N) 0.37 0.56 0.39
OCT 1991 07 DEC 11 FEB 1992 10 MAY 04 JUN 08	DIS- SOLVED (MG/L AS F)	SOLVED (MG/L AS SIO2)	TUENTS, DIS- SOLVED (MG/L) 269	SOLVED (TONS PER DAY)	DEG. C, SUS- PENDED (MG/L) 22 1	NITRATE TOTAL (MG/L AS N) 0.640 0.790 0.630	NITRITE TOTAL (MG/L AS N) 0.150 0.180	NO2+NO3 TOTAL (MG/L AS N) 0.790 0.970 0.670	AMMONIA TOTAL (MG/L AS N) 0.930 0.740 0.310	ORGANIC TOTAL (MG/L AS N) 0.37 0.56
OCT 1991 07 DEC 11 FEB 1992 10 MAY 04 JUN 08	DIS- SOLVED (MG/L AS F) 0.10	SOLVED (MG/L AS SIO2) 33 25	TURNTS, DIS- SOLVED (MG/L) 269 258	SOLVED (TONS PER DAY) 2.95 4.87	DEG. C, SUS- PRNDED (MG/L) 22 1 1 20	NITRATE TOTAL (MG/L AS N) 0.640 0.790 0.630 0.570 0.600	NITRITE TOTAL (MG/L AS N) 0.150 0.180 0.040 0.030	NO2+NO3 TOTAL (MG/L AS N) 0.790 0.970 0.670 0.600	AMMONIA TOTAL (MG/L AS N) 0.930 0.740 0.310 0.350	ORGANIC TOTAL (MG/L AS N) 0.37 0.56 0.39 0.25
OCT 1991 07 DEC 11 FEB 1992 10 MAY 04 JUN 08	DIS- SOLVED (MG/L AS F) 0.10	SOLVED (MG/L AS SIO2) 33 25	TUENTS, DIS- SOLVED (MG/L) 269 258	SOLVED (TONS PER DAY) 2.95 4.87	DEG. C, SUS- PENDED (MG/L) 22 1 1	NITRATE TOTAL (MG/L AS N) 0.640 0.790 0.630 0.570	NITRITE TOTAL (MG/L AS N) 0.150 0.180 0.040	NO2+NO3 TOTAL (MG/L AS N) 0.790 0.970 0.670 0.600	AMMONIA TOTAL (MG/L AS N) 0.930 0.740 0.310	ORGANIC TOTAL (MG/L AS N) 0.37 0.56 0.39

K = non-ideal count

50048800 RIO PIEDRAS NEAR RIO PIEDRAS, PR--Continued WATER QUALITY DATA, WATER YEAR OCTOBER 1991 TO SEPTEMBER 1992

DATE	NITRO- GEN, AM- MONIA + ORGANIC TOTAL (MG/L AS N)	NITRO- GEN, TOTAL (MG/L AS N)	NITRO- GEN, TOTAL (MG/L AS NO3)	PHOS- PHORUS TOTAL (MG/L AS P)	ARSENIC TOTAL (UG/L AS AS)	BARIUM, TOTAL RECOV- ERABLE (UG/L AS BA)	BORON, TOTAL RECOV- ERABLE (UG/L AS B)	CADMIUM TOTAL RECOV- ERABLE (UG/L AS CD)	CHRO- MIUM, TOTAL RECOV- ERABLE (UG/L AS CR)	COPPER, TOTAL RECOV- ERABLE (UG/L AS CU)
OCT 1991 07	1.3	2.1	9.3	0.310	2	100	<10	<1	2	<10
DBC										
11 FEB 1992	1.3	2.3	10	0.330						
10 May	0.70	1.4	6.1	0.220						
04 JUN	0.60	1.2	5.3	0.160	2	200	40	<1	<1	<10
08 AUG	2.3	3.0	13	0.500						
20	0.40	1.1	4.9	0.180						
DATE	IRON, TOTAL RECOV- ERABLE (UG/L AS FE)	LEAD, TOTAL RECOV- ERABLE (UG/L AS PB)	MANGA - NESE, TOTAL RECOV- ERABLE (UG/L AS MN)	MERCURY TOTAL RECOV- ERABLE (UG/L AS HG)	SELE- NIUM, TOTAL (UG/L AS SE)	SILVER, TOTAL RECOV- ERABLE (UG/L AS AG)	ZINC, TOTAL RECOV- ERABLE (UG/L AS ZN)	CYANIDE TOTAL (MG/L AS CN)	PHENOLS TOTAL (UG/L)	MRTHY- LENE BLUE ACTIVE SUB- STANCE (MG/L)
OCT 1991			244							
07	680	2	210	<0.10	<1	<1	<10	<0.010	2	0.06
11 FEB 1992										
10 May										
04 JUN	610	<1	120	<0.10	<1	<1	<10	<0.010	2	0. 0 5
08										
20										
			P	ESTICIDE .	analyses					
DATE	TIME	PCB, TOTAL (UG/L)	ALDRIN, TOTAL (UG/L)	CHLOR- DANE, TOTAL (UG/L)	DDD, TOTAL (UG/L)	DDE, TOTAL (UG/L)	DDT, TOTAL (UG/L)	DI- AZINON, TOTAL (UG/L)	DI- ELDRIN TOTAL (UG/L)	ENDO- SULFAN, TOTAL (UG/L)
JUN 1992										
08	1115	<0.1	<0.010	<0.1	<0.010	<0.010	<0.010	0.06	<0.010	<0.010
DA [,] JUN 19	(UG/	er TRD ethi C tot		OR, EPOX AL TOT	OR IDE LIND AL TOT		ON, CHL AL TOT	Y- PAR OR, THI 'AL TOT	ON, MIR	EX, TAL /L)
08		NA P		010 <0.	010 <0.	010 0	.05 <0	.01 <0	.01 <0	.01
D ā ʻ	PAR THI TE TOT	ON, CHL AL TOT	ES, Y- PE OR. THA AL TOT	NE APHE AL TOT	NB, TR AL THI	I- 2,4	AL TOT		AL TOT	
JUN 19 08		.01 <0	.10 <	0.1 <	1 <0	.01 0	. 04 <0	.01 <0	.01 <0	.01

50049000 RIO PIEDRAS AT RIO PIEDRAS, PR

LOCATION.--Lat 18°23'48", long 66°03'24", Hydrologic Unit 21010005, on left bank, at bridge on Highway 1, 0.3 mi (0.5 km) southwest of the plaza in Río Piedras, and 0.4 mi (0.6 km) downstream from diversion for water supply.

DRAINAGE AREA. -- 12.5 mi 2 (32.4 km2).

WATER-DISCHARGE RECORDS

PERIOD OF RECORD. --October 1958 (maximum discharge measurement only), 1959-64 (annual low-flow measurements only), July 1971 to September 1982, October 1987 to current year.

GAGE. -- Water-stage recorder and crest-stage gage. Elevation of gage is 50 ft (15 m), from topographic map.

REMARKS.--Records fair. Low flow affected by diversions for water supply. Gage-height and precipitation satellite telemetry at station.

telem	etry at a	station.										
		DISCHAR	GR, CUBIC	FRET PER		MATER Y	YBAR OCTOBER VALUES	1991 TO	September	1992		
DAY	OCT	NOV	DEC	JAN	FRB	MAR	APR	MAY	JUN	JUL	AUG	SEP
1	20	17	12	9.7	8.8	5.8	9.5	202	95	7.7	33	9.6
2	12	69	13	7.7	13	6.6	8.9	149	23	7.6	40	6.6
3	9.9	18	37	7.5	12	6.2	9.2	11	15	8.3	18	6.3
4	9.7			6.3	9.2		10	6.9	14	14	20	6.3
		14	14			11	9.6	5.7	13	9.0	155	8.2
5	12	9.0	14	455	8.6	7.3	3.6					
6 7	7.0 6.5	9.3 30	12 8.9	168 14	8.1 8.6	7.4	10 12	76 12	23 189	8.9 8.1	16 20	59 7.8
É	8.8	41	15	9.6	8.9	7.4	19	8.8	114	41	8.3	5.7
ğ	5.9	11	14	26	8.6	6.8	15	14	30	56	222	5.5
10	5.4	9.6	8.8	119	8.6	7.9	21	17	19	13	154	5.4
11	5.4	7.4	9.1	13	8.7	8.5	13	14	12	28	20	8.1
12	5.5	7.2	16	13	8.8	7.6		8.6	15	12	15	5.6
			8.9	17	8.9	9.0		7.9	11	33	20	6.5
13	5.7	9.5					6.9	7.8	18	43	274	6.2
14	4.8	6.9	14	11	8.9	12				29	34	6.3
15	7.3	7.8	7.6	10	8.8	8.3	6.0	8.3	12			
16	5.8	17	20	45 13	7.8 8.7	8.7 15	6.7 7.2	122 19	9.2 7.8	17 51	19 12	5.8 17
17	4.9	9.5	7.3				13	87	6.9	13	9.7	6.6
18	66	9.1	7.8	11	7.5	11			7.6	11	8.5	18
19	13	8.1	7.1	8.4	9.2	10	73	59				62
20	7.9	8.3	29	9.9	6.5	9.1	13	24	8.1	96	10	
21	6.9	201	13	8.3	6.3	9.8		46	14	21	324	16
22	6.5	76	13	7.8	20	7.2	5.7	15	9.9	18	30	6.7
23	8.7	32	13	7.6	7.3	10	6.6	167	9.7	11	38	99
24	6.9	43	9.1	8.2	7.5	7.8		127	8.8	76	10	8.7
25	6.2	9.9	8.6	13	7.2	7.9	8.4	31	8.2	18	8.5	6.3
26	9.4	12	9.6	10	7.4	8.5	8.7	354	7.9	13	8.3	5.8
27	6.5	15	13	9.2	7.8	8.2		54	7.8	123	7.1	5.0
28	6.2	8.7	9.6	12	7.0	132	9.7	31	7.2	25	6.3	4.8
29	6.2	8.9	9.7	8.8	7.0	13	561	58	6.9	12	6.5	5.4
30	26	9.9	23	8.6		8.0		74	7.3	9.3	20	85
31	12		11	8.7		9.1		29		124	28	
TOTAL	325.0	735.1	408.1	1076.3	255.7	395.0	1027.6	1846.0	730.3	956.9	1595.2	505.2
			13.2					59.5	24.3	30.9	51.5	16.8
MRAN	10.5	24.5		34.7	8.82	12.7		354	189	124	324	99
MAX	.66	201	37	455	20	132			6.9	7.6	6.3	4.8
MIN	4.8	6.9	7.1	6.3	6.3	5.8		5.7			3160	1000
AC-FT	645	1460	809	2130	507	783		3660	1450	1900		
CFSM	. 84	1.96	1.05	2.78	.71	1.02		4.76	1.95	2.47	4.12	1.35
IN.	.97	2.19	1.21	3.20	.76	1.18	3.06	5.49	2.17	2.85	4.75	1.50
STATIST	rics of M	ONTHLY MEA	N DATA P	OR WATER Y	EARS 1971	- 199	2, BY WATER	YEAR (WY)			
MBAN	50.0	35.5	35.1	17.4	20.2	16.1	23.8	32.6	18.9	20.6	38.2	38.0
MAX	122	133	133	34.7	98.9	42.5		121	59.7	55.6	120	112
(WY)	1977	1978	1976	1992	1979	1972		1979	1989	1989	1979	1989
MIN	10.5	8.16	9.88	4.03	4.40	2.67		3.46	3.25	3.35	4.30	10.1
(WY)	1992	1974	1977	1973	1977	1976		1975	1974	1976	1976	1973
(#1)	1334	4374	1311	1973	1311	1976	13/4	13/3	1374	13.0	20.0	20.0
SUMMARY	Y STATIST	IC S	FOR	1991 CALEN	DAR YEAR		FOR 1992 WA	ATER YEAR		WATER 1	TRARS 1971	- 1992
ANNUAL	TOTAL			7849.3			9856.4					
ANNUAL	MRAN			21.5			26.9			29.3		
HIGHEST	L ANNUAL	MRAN								54.2	2	1979
LOWEST	ANNUAL M	BAN								11.9	•	1974
	DAILY M			403	Feb 18		561	Apr 29		2030		15 1979
LOWEST	DAILY MR	AN		4.8	Oct 14		4.8	Oct 14		.:	6 May	19 1977
		MINIMUM Y			Oct 11			Oct 11		.:	33 Aug	14 1976
		BAK FLOW						Apr 29		10000	Dec	11 1975
		BAK STAGE						Apr 29		21.0		11 1975
	RUNOFF (15570			19550			21110		
	RUNOFF (1.72	,		2.15			2.		
	RUNOFF (23.36			29.33			31.0		
	BOXE THES			33	•		29.33 59	•		52	•	
	CENT BACE			11			9.7			12		
				6.9			6.5			3.3	2	
JU PER	CENT EXCE	200		6.9			0.3			٥.,	•	

50049000 RIO PIEDRAS AT RIO PIEDRAS, PR--Continued

WATER-QUALITY RECORDS

PERIOD OF RECORDS. -- Water years 1988 to current year.

INSTRUMENTATION. -- USD-77 and automatic sediment sampler.

PERIOD OF DAILY RECORD . --

SUSPENDED-SEDIMENT DISCHARGE: October 1988 to September 1992.

EXTREMES FOR PERIOD OF DAILY RECORD.--SEDIMENT CONCENTRATION: Maximum daily mean, 13,000 mg/L Sep. 18, 1989; Minimum daily mean, 4 mg/L June 4, 1990.

SEDIMENT LOADS: Maximum daily mean, 165,000 tons (150,200 tonnes) Sep. 18, 1989; Minimum daily mean, 0.09 ton (0.08 tonne) Sep. 24, 1991.

EXTREMES FOR WATER YEARS 1992.--SEDIMENT CONCENTRATION: Maximum daily mean, 2,080 mg/L Jan. 05, 1992; Minimum daily mean, 10 mg/L several days.

SEDIMENT LOADS: Maximum daily mean, 8,860 tons (8,040 tonnes) Aug. 21, 1992; Minimum daily mean, 0.13 tons (0.12 tonnes) Sep. 28, 1992.

	MEAN			MRAN			MBAN			
DAY	MEAN DISCHARGE (CFS)	CONCEN- TRATION (MG/L)	SEDIMENT DISCHARGE (TONS/DAY)	MEAN DISCHARGE (CFS)	CONCEN- TRATION (MG/L)	SEDIMENT DISCHARGE (TONS/DAY)	MEAN DISCHARGE (CFS)	CONCEN- TRATION (MG/L)	SEDIMENT DISCHARGE (TONS/DAY)	
		OCTOBER			NOVEMBER			DECEMBER		
1	20	87	13	17	53	2.4	12	35	1.6	
2	12	39	1.6	69	438	306	13	24	.90	
3	9.9	38	1.1	18	64	6.1	37	187	43	
4	9.7	22	. 64	14	53	2.7	14	33	1.5	
5	12	39	2.1	9.0	25	.66	14	22	.73	
6 7 8 9	7.0	14	. 25	9.3	19	.49	12	23	.75	
7	6.5	14	.25	30	166	66	8.9	22	. 52	
8	8.8	22	. 98	41	205	48	15	42	2.2	
	5.9	14	. 22	11	23	.71	14	38	1.9	
10	5. 4	13	.21	9.6	15	.38	8.8	24	. 64	
11	5.4	11	. 16	7.4	14	.29	9.1	19	.43	
12	5.5	12	. 17	7.2	15	.28	16	59	7.4	
13	5.7	10	. 15	9.5	25	.72	8.9	24	.73	
14	4.8	11	. 14	6.9	17	.31	14	46	3.1	
15	7.3	24	1.0	7.8	16	.32	7.6	17	. 34	
16	5.8	11	. 16	17	58	6.0	20	93	28	
17	4.9	10	. 13	9.5	17	.47	7.3	17	. 35	
18	66	459	784	9.1	16	.40	7.8	15	.29	
19	13	48	3.5	8.1	17	.35	7.1	15	.26	
20	7.9	18	.37	8.3	19	.42	29	143	32	
21	6.9	15	.28	201	821	2280	13	47	2.0	
22	6.5	16	. 33	76	535	425	13	51	2.3	
23	8.7	19	.43	32	147	38	13	39	1.7	
24	6.9	14	.28	43	232	78	9.1	16	.41	
25	6.2	12	. 19	9.9	26	.75	8.6	16	.40	
26	9.4	28	1.6	12	34	1.9	9.6	17	.46	
27	6.5	13	.20	15	58	6.0	13	40	2.4	
28	6.2	13	.20	8.7	21	.50	9.6	21	.51	
29	6.2	13	.20	8.9	20	.44	9.7	22	. 58	
30	26	127	30	9.9	20	.50	23	95	21	
31	12	44	1.4				11	34	1.9	
TOTAL	325.0		845.24	735.1		3274.09	408.1		160.30	

50049000 RIO PIEDRAS AT RIO PIEDRAS, PR--Continued

	MRAN				MRAN		MRAN		
DAY	MEAN DISCHARGE (CFS)	CONCEN- TRATION (MG/L)	SEDIMENT DISCHARGE (TONS/DAY)	MEAN DISCHARGE (CFS)	CONCEN- TRATION (MG/L)	SEDIMENT DISCHARGE (TONS/DAY)	MEAN DISCHARGE (CFS)	CONCEN- TRATION (MG/L)	SEDIMENT DISCHARGE (TONS/DAY)
		JANUA RY		1	FEBRUARY			MARCH	
1	9.7	81	3.5	8.8	16	.42	5.8	35	. 54
2	7.7	18	.38	13	35	4.2	6.6	40	.66
3	7.5	27	.58	12	38	2.7	6.2	33	.55
4	6.3	11	.20	9.2	17	.47	11	38	3.0
5	455	2080	7290	8.6	16	.40	7.3	14	. 27
6	168	1260	1460	8.1	16	.34	7.4	11	.25
7	14	41	1.6	8.6	16	.38	7.9	13	.29
8	9.6	25	. 65	8.9	16	.40	7.4	13	. 25
9	26	138	37	8.6	16	.37	6.8	13	.22
10	119	862	679	8.6	16	.34	7.9	13	.28
11	13	41	1.6	8.7	16	.37	8.5	14	.33
12	13	43	2.0	8.8	16	.38	7.6	14	.26
13	17	64	4.7	8.9	16	.37	9.0	15	.37
14	11	24	. 63	8.9	16	.37	12	21	. 69
15	10	23	. 56	8.8	15	.39	8.3	27	. 63
16	45	241	178	7.8	15	.33	8.7	36	. 89
17	13	53	2.2	8.7	13	.32	15	37	1.6
18	11	44	1.3	7.5	13	.28	11	26	.78
19	8.4	41	. 90	9.2	16	. 39	10	20	.46
20	9.9	40	. 97	6.5	15	.28	9.1	16	.40
21	8.3	40	. 83	6.3	13	.20	9.8	17	. 44
22	7.8	38	.73	20	88	14	7.2	17	.33
23	7.6	29	. 55	7.3	13	.27	10	29	.96
24	8.2	21	. 42	7.5	13	.27	7.8	14	.28
25	13	35	1.4	7.2	13	.27	7.9	15	.34
26	10	19	.51	7.4	13	.28	8.5	15	.36
27	9.2	19	.46	7.8	13	.28	8.2	15	.36
28	12	19	. 65	7.0	15	.28	132	982	2540
29	8.8	17	.36	7.0	23	. 4 4	13	47	2.2
30	8.6	16	.38				8.0	34	. 75
31	8.7	16	.40				9.1	27	.75
TOTAL	1076.3		9672.46	255.7		29.79	395.0		2559.49

50049000 RIO PIEDRAS AT RIO PIEDRAS, PR--Continued

DAY	MRAN DISCHARGE (CFS)	MBAN CONCEN- TRATION (MG/L)	SEDIMENT DISCHARGE (TONS/DAY)	MEAN DISCHARGE (CFS)	MEAN CONCEN- TRATION (MG/L)	SEDIMENT DISCHARGE (TONS/DAY)	MRAN DISCHARGE (CFS)	MEAN CONCEN- TRATION (MG/L)	SEDIMENT DISCHARGE (TONS/DAY)
		APRIL			MAY			JUNE	
1	9.5	20	.53	202	1030	2500	95	591	1140
2	8.9	20	.48	149	1000	1370	23	92	7.6
3	9.2	20	. 53	11	33	1.2	15	34	1.2
4	10	20	. 55	6.9	11	.21	14	32	1.2
5	9.6	18	.45	5.7	10	.15	13	31	. 95
6	10	17	.41	76	604	1020	23	97	18
7	12	19	. 63	12	35	1.2	189	1200	2680
8	19	67	9.0	8.8	23	.59	114	815	652
9	15	51	4.1	14	49	8.4	30	120	12
10	21	86	11	17	57	4.7	19	69	5.1
11	13	41	2.0	14	38	1.8	12	31	. 97
12	11	35	1.5	8.6	19	.43	15	46	2.9
13	6.8	14	. 24	7.9	16	.32	11	28	.81
14	6.9	11	.21	7.8	15	.30	18	72	11
15	6.0	11	. 16	8.3	15	.34	12	40	1.9
16	6.7	12	.22	122	789	1570	9.2	20	.45
17	7.2	13	. 27	19	64	3.7	7.8	15	.27
18	13	47	4.5	87	553	850	6.9	13	.22
19	73	512	721	59	373	223	7.6	16	.32
20	13	45	3.7	24	86	7.9	8.1	19	. 42
21	9.4	29	1.7	46	314	267	14	39	1.9
22	5.7	10	.14	15	48	2.1	9.9	19	.49
23	6.6	10	.18	167	1290	1800	9.7	19	.48
24	7.5	10	.21	127	922	980	8.8	17	.40
25	8.4	10	.23	31	148	18	8.2	14	.31
26	8.7	10	.24	354	2050	6250	7.9	13	.29
27	8.8	10	.26	54	287	62	7.8	16	. 32
28	9.7	13	. 34	31	141	18	7.2	19	.37
29	561	2210	15100	58	365	254	6.9	19	. 34
30	121	854	1190	74	457	170	7.3	19	.38
31				29	127	17			
TOTAL	1027.6		17054.78	1846.0		17402.34	730.3		4542.59

RIO PUERTO NUEVO BASIN

50049000 RIO PIEDRAS AT RIO PIEDRAS, PR--Continued

SEDIMENT DISCHARGE, SUSPENDED (TONS/DAY), WATER YEAR OCTOBER 1991 TO SEPTEMBER 1992

	MRAN				MRAN		MBAN		
	MEAN	CONCEN-	SEDIMENT	MBAN	CONCEN-	SEDIMENT	mran	CONCEN-	SEDIMENT
	DISCHARGE	TRATION	DISCHARGE	DISCHARGE	TRATION	DISCHARGE	DISCHARGE	TRATION	DISCHARGE
DAY	(CFS)	(MG/L)	(TONS/DAY)	(CFS)	(MG/L)	(TONS/DAY)	(CFS)	(MG/L)	(TONS/DAY)
		JULY			AUGUST		Si	PTEMBER	
1	7.7	19	.38	33	137	26	9.6	65	2.7
2	7.6	19	.37	40	223	86	6.6	28	.48
3	8.3	14	.31	18	60	3.6	6.3	17	.28
4	14	49	6.4	20	78	8.2	6.3	13	.21
5	9.0	18	.45	155	1260	2910	8.2	18	.50
6	8.9	16	.39	16	127	6.4	59	399	584
7	8.1	16	.32	20	119	19	7.8	19	.43
8	41	207	45	8.3	21	.54	5.7	12	. 17
9	56	324	119	222	1460	4610	5. 5	11	.16
10	13	37	1.2	154	937	2090	5.4	12	. 17
11	28	111	13	20	85	5.8	8.1	26	. 82
12	12	33	1.1	15	46	2.4	5.6	11	.17
13	33	248	78	20	104	7.7	6.5	11	.20
14	43	389	137	274	1050	3790	6.2	11	.17
15	29	137	31	34	153	20	6.3	11	. 16
16	17	61	5.0	19	64	4.9	5.8	10	. 16
17	51	265	62	12	31	.99	17	64	6.6
18	13	35	1.2	9.7	26	.70	6.6	18	.38
19	11	26	.72	8.5	21	.48	18	104	54
20	105	581	690	10	16	.40	62	957	1410
21	21	71	4.4	324	1580	8860	16	65	10
22	18	66	4.3	30	120	13	6.7	15	.48
23	11	30	.99	38	219	80	99	393	918
24	76	528	310	10	30	.94	8.7	21	. 52
25	18	63	4.3	8.5	19	.41	6.3	11	. 17
26	13	57	3.1	8.3	17	.35	5.8	10	. 15
27	123	614	1240	7.1	23	.42	5.0	10	. 15
28	25	135	13	6.3	20	.30	4.8	10	. 13
29	12	28	1.0	6.5	11	.19	5.4	10	. 14
30	9.3	21	.51	20	102	47	85	244	379
31	124	810	1520	28	127	24			
TOTAL	965.9		4294.44	1595.2		22619.72	505.2		3370.50
YBAR	9865.4		85825.74						

50049000 RIO PIEDRAS AT RIO PIEDRAS, PR--Continued

WATER QUALITY DATA, WATER YEAR OCTOBER 1991 TO SEPTEMBER 1992

PARTICLE-SIZE DISTRIBUTION OF SUSPENDED SEDIMENT

TIME	DIS- CHARGE, INST. CUBIC FRET PER SECOND	SEDI - MENT , SUS- PRNDED (MG/L)	SEDI- MENT, DIS- CHARGE, SUS- PENDED (T/DAY)	SED. SUSP. FALL DIAM. PERCENT FINER THAN .002 MM	SED. SUSP. FALL DIAM. PERCENT FINER THAN .004 MM	SED. SUSP. FALL DIAM. PERCENT FINER THAN .008 MM
0552	548	3800	554	38	47	53
1637	2560	10500	72500	48	50	56
1752	818	15800	34900	34	40	47
2037	17600	8410	17600	45	52	60
1705	1290	8430	29400	40	47	54
0330	1390	17600	66000	27	45	52
	0552 1637	CHARGE, INST. CUBIC FRET TIME PER SECOND 0552 548 1637 2560 1752 818 2037 17600 1705 1290	CHARGE, INST. SEDI- CUBIC MENT, FRET SUS- FRET PENDED SECOND (MG/L) 0552 548 3800 1637 2560 10500 1752 818 15800 2037 17600 8410 1705 1290 8430	CHARGE, INST. SEDI- CUBIC MENT, FRET SUS- SECOND (MG/L) (T/DAY) 10552 S48 3800 554 1637 2560 10500 72500 1752 818 15800 34900 2037 17600 8410 17600 1705 1290 8430 29400	CHARGE, INST. SEDI- DIS- DIAM. CUBIC MENT, CHARGE, SUS- SUS- SUS- PENDED THAN SECOND (MG/L) (T/DAY) .002 MM 152 S48 3800 554 38 1637 2560 10500 72500 48 1752 818 15800 34900 34 2037 17600 8410 17600 45 1705 1290 8430 29400 40	DIS- CHARGE, INST. SEDI- CUBIC MENT, CUBIC MENT, FALL DIAM. CUBIC MENT, FRET SUS- SUS- FINER FINER FINER FINER SECOND (MG/L) (T/DAY) .002 MM .004 MM 0552 548 3800 554 38 47 1637 2560 10500 72500 48 50 1752 818 15800 34900 34 40 2037 17600 8410 17600 45 52 1705 1290 8430 29400 40 47

DATE	SED. SUSP. FALL DIAM. PERCENT FINER THAN .016 MM	SED. SUSP. FALL DIAM. PERCENT FINER THAN .031 MM	SED. SUSP. SIEVE DIAM. PERCENT FINER THAN .062 MM	SED. SUSP. SIEVE DIAM. PERCENT FINER THAN .125 MM	SED. SUSP. SIEVE DIAM. PERCENT FINER THAN .250 MM	SED. SUSP. SIEVE DIAM. PERCENT FINER THAN .500 MM	SED. SUSP. SIEVE DIAM. PERCENT FINER THAN 1.00 MM
NOV 1991							
02	61	73	89	96	99	99.7	100
JAN 1992							
05	64	76	94	98	99	99.7	100
MAR							
28	64	75	95	99	99.6	99.8	100
MAY							
01	69	78	95	99	99.7	100	100
JUL							
27	62	71	90	96	98	99	99.8
AUG							
05	60	73	92	98	99	99.8	100

50049000 RIO PIEDRAS AT RIO PIEDRAS, PR--Continued WATER QUALITY DATA, WATER YEAR OCTOBER 1991 TO SEPTEMBER 1992

SILT AND CLAY PERCENT OF SUSPENDED SEDIMENT

DATE	TIME	STREAM- FLOW, INSTAN- TANEOUS (CFS)	SEDI- MENT, SUS- PENDED (MG/L)	SEDI- MENT, DIS- CHARGE, SUS- PENDED (T/DAY)	SED. SUSP. SIEVE DIAM. PERCENT FINER THAN .062 MM
OCT 1991					
15	1544	32	338	29	99
NOV					
02	0522	336	3500	3170	94
21	1900	344	3020	2810	95
21	2030	409	1520	1680	97
JAN 1992	4547	456	0.00	2452	
05	1517	476	2470	3170	89 89
05 16	1907 1905	1170 366	4040 2670	12800 2640	78
MAR	1905	366	26/0	2640	/ 6
28	1642	1690	5530	25200	70
MAY	1042	1090	3330	25200	, 0
01	2207	1240	6880	23000	92
06	0844	1110	5700	17100	83
JUL			2.22	2.200	-
20	1610	438	10200	12100	67
27	1635	1010	6390	17400	79
AUG					
05	0300	1790	10100	48700	87
09	1650	1890	11000	56100	74
14	1445	2760	9380	70000	89
SEP					
20	0055	581	14800	23200	96
30	1410	956	1720	4440	59

•

LOCATION.--Lat 18°24'34", long 66°04'10", Hydrologic Unit 21010005, at bridge on Avenida Piñeiro at Expreso Las Américas, and 0.8 mi (1.3 km) southwest of Hato Rey.

50049100 RIO PIEDRAS AT HATO RRY, PR

DRAINAGE AREA. -- 15.4 mi 2 (39.9 km2).

WATER-DISCHARGE RECORDS

PERIOD OF RECORD. -- June 1970 to December 1987 (discharge measurements only), 1972 to December 1982 (maximum discharge only), January 1988 to current year.

GAGE. -- Water-stage recorder and crest-stage gage. Elevation of gage is 16 ft (5 m), from topographic map.

REMARKS.--Records fair. Mean daily discharge affected by sewage discharges (approximately 2.0 ft 3 /s (0.06 m 3 /s)), 20 ft (6 m) upstream from gaging station.

20 ft	: (6 ma) u	pstream f	rom gaging	station.								
		DISCHA	RGE, CUBIC	FERT PRE		WATER Y	BAR OCTOBER ALUES	1991 TO	SEPTEMBE	RR 1992		
DAY	ост	NOV	DEC	JAN	FEB	MAR	APR	MAY	JUN	JUL	AUG	SEP
1	35	23	16	13	11	6.9	18	307	146	9.8	53	27
2	19	135	16	11	14	8.4	21	218	45	9.8	62	18
3	15	43	76	13	19	8.1	15	27	25	10	23	17
4	16	34	17	11	12	86	14	19	46	17	27	18
5	21	22	17	637	10	20	12	16	50	10	247	22
6	13	25	14	320	9.6	17	11	126	54	9.9	38	112
7	11	62	9.8	43	9.4	21	13	23	304	8.6	47	35
8	19	104	32	26	8.8	10	26	16	209	102	17	31
9 10	12 10	22 16	29 13	63 315	8.2 8.7	9.6 9.9	37 26	21 39	58 44	115 13	241 195	27 26
11	10	15	12	30	9.2	10	24	22	20	47	36	39
12	10	13	20	40	9.9	8.8	16	14	23	9.9	23	22
13	12	16	13	39	10	9.5	10	13	15	45	26	24
14	12	10	19	19	11	15	11	12	29	89	368	25
15	17	8.6	9.0	17	11	11	9.5	13	19	45	45	28
16	13	19	31	72	9.9	9.8	10	167	15	20	32	30
17	12	9.9	9.1	25	11	22	12	27	13	120	17	88
18	85	12	9.4	19	8.3	14	32	111	13	12	15	25
19	20	13	9.0	16	9.8	13	93	105	13	11	15	51
20	11	17	40	16	7.4	12	16	34	13	172	17	125
21	9.9	317	18	16	8.3	13	15	143	25	33	336	42
22	9.5	221	18	14	42	9.8	8.2	20	14	30	70	20
23	12	104	20	14	7.6	16	9.4	278	12	14	92	164
24	12	122	12	13	8.1	13	10	200	12	121	28	28
25	12	17	10	25	8.5	10	11	56	12	22	23	20
26	13	22	11	19	8.1	10	9.9	616	11	15	25	17
27	9.0	26	18	14	8.0	11	10	72	11	246	25	15
28	8.7	11	14	17	7.7	205	9.5	38	11	75	23	15
29	8.7	10	14	12	7.7	42	838	74	12	28	20	16
30 31	34 14	10	23 15	11 11		17 18	224	122 73	9.9	17 177	42 91	178
TOTAL	515.8	1479.5	584.3	1911	314.2	686.8	1571.5	3022	1283.9	1654.0	2319	1305
MEAN	16.6	49.3	18.8	61.6	10.8	22.2	52.4	97.5	42.8	53.4	74.8	43.5
MAX	85	317	76	637	42	205	838	616	304	246	368	178
MIN AC-FT	8.7 1020	8.6	9.0	11 3790	7.4	6.9	8.2	12 5990	9.9 2550	8.6 3280	15 4600	15 2590
CFSM	1.09	2930 3.24	1160 1.24	4.06	623 .71	1360 1.46	3120 3.45	6.41	2.82	3.51	4.92	2.86
IN.	1.26	3.62	1.43	4.68	.77	1.68	3.85	7.40	3.14	4.05	5.68	3.19
STATIST	TCS OF I	MONTHILY MR	AN DATA FO	D WATER V	TADE 1988	- 1992	, BY WATER Y	/RAD (WV	,			
MEAN	68.9	44.2	34.3	40.0	40.6	33.5	49.7	51.5	40.7	41.1	61.5	74.2
MAX	134	58.1	55.6	61.6	80.2	53.8	87.9	97.5	78.1	55.0	84.2	150
(WY)	1991	1990	1991	1992	1991	1990	1988	1992	1989	1989	1988	1989
MIN (WY)	16.6 1992	23.9 1991	18.8 1992	29.9 1989	10.8 1992	22.2 1992	31.6 1991	30.8 1989	23.0 1991	24.8 1990	22.6 1990	32.6 1991
(#1)	1994	1991	1992	1707	1994	1994	1991	1909	1331	1330	1330	1771
SUMMARY	Y STATIS	rics	FOR 1	991 CALEN	DAR YEAR		FOR 1992 WAT	er year		WATER YE	ARS 1988	- 1992
	MRAN L'ANNUAL			13078.3 35.8			16647.0 45.5			46.8 53.4		1989
	ANNUAL I									41.4		1990
	r DAILY I			679	Feb 18		838	Apr 29		1830		8 1989
	DAILY M			8.6	Nov 15		6.9			6.9		1 1992
		MUMINIM YA		9.4	May 29		7.8			7.8		6 1992
		PEAK FLOW					5840	Apr 29		8640		7 1970
		PBAK STAGE		25042				Apr 29		20.77 33880	Jun 1	7 1970
	RUNOFF RUNOFF			25940 2.36			33020 2.99			3.08	2	
	RUNOFF			32.01			40.74			41.81		
	CENT EXC			69	•		113			104	-	
	CENT EXC			17			17			21		
	CENT BXC			ií			9.7			12		

50049100 RIO PIEDRAS AT HATO REY, PR--Continued

WATER-QUALITY RECORDS

PERIOD OF RECORD. -- Water years 1971 to current year.

WATER-QUALITY DATA, WATER YEAR OCTOBER 1991 TO SEPTEMBER 1992

DATE	TIME	DIS CHARC INS CUB: PE: PE: SECC	GR, SPE T. CIE IC CON RT DUC R ANC	PIC WHO I- PIE TT- (ST) EB AF	TER OLE SILD TEN AND- AT	IPER- TURE ITER IG C)	TUR BID ITY (NTU	- DI SOL	SOI EN, (PI S- CI VED SAT	S- DI LVBD G R- SNT TOR- L	KYGEN EMAND, CHEM- ICAL (HIGH EVEL) MG/L)	COLI FORM PECA 0.45 UM-N (COLS	i, STR L, TOCO FEO IF (COI	CAL, LS. KR
OCT 1991 07	1505	11		457	8.0	31.0	1.		6.4	84	20	490	100 5	200
DEC														
11 FEB 1992	1250	12	_	372	7.2	26.5	4.		5.3	86	<10	K120		3600
10 May	1245		.1	436	7.1	26.5	15		6.3	83	22	360		1400
04 Jun	1235	21		500	7.5	29.5	13		6.0	87	24	K880	000 K11	1000
22 AUG	1500	4	. 3	396	7.6	30.0	2.	0	6.4	89	18	K1100	000 K18	3000
12	1205	22		450	7.7	29.0	10		5.7	85	<10	2900	000 35	000
DATE	N T (ARD- ESS OTAL MG/L AS ACO3)	CALCIUM DIS- SOLVED (MG/L AS CA)	MAGNE- SIUM, DIS- SOLVED (MG/L AS MG)	SODIUM, DIS- SOLVED (MG/L AS NA)	SOI T	DIUM AD- RP- ION TIO	POTAS- SIUM, DIS- SOLVED (MG/L AS K)	ALKA- LINITY WAT WH TOT FET FIELD MG/L AS CACO3	SULFII TOTAI (MG/I AS S	DE DI L SC L (1	LFATE (S-)LVED (G/L SO4)	CHLO- RIDB, DIS- SOLVED (MG/L AS CL)	
OCT 1991 07		170	49	12	31		1	3.5	160	<0	. 5 2	12	35	
DEC 11									100					
FEB 1992 10									160					
MAY 04		160	46	12	30		1	4.1	160	<0	. 5 2	19	42	
JUN 22									150					
AUG 12		160	44	12	26		0.9	3.7	140		2	16	32	
****		100			20		0.3	3.,	140		•	. •	32	
DATE	R S ()	LUO- IDE, DIS- OLVED MG/L S P)	SILICA, DIS- SOLVED (MG/L AS SIO2)	SOLIDS, SUM OF CONSTI- TUENTS, DIS- SOLVED (MG/L)	SOLIDS, DIS- SOLVEI (TONS PER DAY)	TOT: AT DEG SU: PEN	105 . C, : s-	NITRO- GEN, NITRATE TOTAL (MG/L AS N)	NITRO- GEN, NITRITE TOTAL (MG/L AS N)	NITRO GEN NO2+NO TOTAL (MG/) AS N	, G D3 AM 0 L TC L ()	TRO- EN, SONIA STAL SG/L SN)	NITRO- GEN, ORGANIC TOTAL (MG/L AS N)	
OCT_1991														
07 Dec		0.10	33	282	8.21	L	6	0.730	0.120	0.8		1.460	0.44	
11 FEB 1992							1	0.600	0.090	0.69	90 0	.300	0.50	
10 May							1	0.790	0.060	0.8	50 0	.180	0.42	
04 JUN		0.20	25	284	15.9		24	0.680	0.070	0.79	50 0	.590	0.41	
22 AUG							10	0.570	0.070	0.6	10 0	.290	0.51	
12		0.20	25	259	15.4		25	0.760	0.070	0.8	30 1	.20	0.80	

K = non-ideal count

*2*03

50049100 RIO PIEDRAS AT HATO REY, PR--Continued

WATER-QUALITY DATA, WATER YEAR OCTOBER 1991 TO SEPTEMBER 1992

DATE	NITRO- GEN, AM- MONIA + ORGANIC TOTAL (MG/L AS N)	NITRO- GEN, TOTAL (MG/L AS N)	NITRO- GEN, TOTAL (MG/L AS NO3)	PHOS- PHORUS TOTAL (MG/L AS P)	ARSENIC TOTAL (UG/L AS AS)	BARIUM, TOTAL RECOV- ERABLE (UG/L AS BA)	BORON, TOTAL RECOV- ERABLE (UG/L AS B)	CADMIUM TOTAL RECOV- ERABLE (UG/L AS CD)	CHRO- MIUM, TOTAL RECOV- ERABLE (UG/L AS CR)	COPPER, TOTAL RECOV- ERABLE (UG/L AS CU)
OCT 1991										
07 DBC	0.90	1.7	7.7	0.350	2	200	<10	<1	<1	10
11	0.80	1.5	6.6	0.290						
FRB 1992 10	0.60	1.5	6.4	0.320						
MAY	1.0	1.7			_	2.22		_		4.0
04 JUN	_	1.7	7.7	0.280	2	200	50	<1	<1	<10
22 AUG	0.80	1.4	6.4	0.260						
12	2.0	2.8	13	0.410						
			manga-							MRTHY~
DATE	IRON, TOTAL RECOV- ERABLE (UG/L AS FE)	LEAD, TOTAL RECOV- ERABLE (UG/L AS PB)	NESE, TOTAL RECOV- ERABLE (UG/L AS MN)	MERCURY TOTAL RECOV- ERABLE (UG/L AS HG)	SELE- NIUM, TOTAL (UG/L AS SE)	SILVER, TOTAL RECOV- ERABLE (UG/L AS AG)	ZINC, TOTAL RECOV- ERABLE (UG/L AS ZN)	CYANIDE TOTAL (MG/L AS CN)	PHENOLS TOTAL (UG/L)	LENE BLUE ACTIVE SUB- STANCE (MG/L)
OCT 1991	TOTAL RECOV- ERABLE (UG/L AS FE)	TOTAL RECOV- ERABLE (UG/L AS PB)	NESE, TOTAL RECOV- ERABLE (UG/L AS MN)	TOTAL RECOV- ERABLE (UG/L AS HG)	NIUM, TOTAL (UG/L AS SE)	TOTAL RECOV- ERABLE (UG/L AS AG)	TOTAL RECOV- ERABLE (UG/L AS ZN)	TOTAL (MG/L AS CN)	TOTAL (UG/L)	LENE BLUE ACTIVE SUB- STANCE (MG/L)
OCT 1991 07 DEC	TOTAL RECOV- ERABLE (UG/L	TOTAL RECOV- ERABLE (UG/L	NESE, TOTAL RECOV- ERABLE (UG/L	TOTAL RECOV- ERABLE (UG/L	NIUM, TOTAL (UG/L	TOTAL RECOV- ERABLE (UG/L	TOTAL RECOV- ERABLE (UG/L	TOTAL (MG/L	TOTAL	LENE BLUE ACTIVE SUB- STANCE
OCT 1991 07 DEC 11	TOTAL RECOV- ERABLE (UG/L AS FE)	TOTAL RECOV- ERABLE (UG/L AS PB)	NESE, TOTAL RECOV- ERABLE (UG/L AS MN)	TOTAL RECOV- ERABLE (UG/L AS HG)	NIUM, TOTAL (UG/L AS SE)	TOTAL RECOV- ERABLE (UG/L AS AG)	TOTAL RECOV- ERABLE (UG/L AS ZN)	TOTAL (MG/L AS CN)	TOTAL (UG/L)	LENE BLUE ACTIVE SUB- STANCE (MG/L)
OCT 1991 07 DEC 11 FEB 1992 10	TOTAL RECOV- ERABLE (UG/L AS FE)	TOTAL RECOV- ERABLE (UG/L AS PB)	NESE, TOTAL RECOV- ERABLE (UG/L AS MN)	TOTAL RECOV- BRABLE (UG/L AS HG)	NIUM, TOTAL (UG/L AS SE)	TOTAL RECOV- ERABLE (UG/L AS AG)	TOTAL RECOV- ERABLE (UG/L AS ZN)	TOTAL (MG/L AS CN)	TOTAL (UG/L)	LENE BLUE ACTIVE SUB- STANCE (MG/L)
OCT 1991 07 DEC 11 FEB 1992	TOTAL RECOV- ERABLE (UG/L AS FE)	TOTAL RECOV- ERABLE (UG/L AS PB)	NESE, TOTAL RECOV- ERABLE (UG/L AS MN)	TOTAL RECOV- ERABLE (UG/L AS HG) <0.10	NIUM, TOTAL (UG/L AS SE)	TOTAL RECOV- ERABLE (UG/L AS AG)	TOTAL RECOV- ERABLE (UG/L AS ZN) <10	TOTAL (MG/L AS CN) 0.060	TOTAL (UG/L)	LENE BLUE ACTIVE SUB- STANCE (MG/L)
OCT 1991 07 DEC 11 FBB 1992 10 MAY 04 JUN	TOTAL RECOV- ERABLE (UG/L AS FE) 440	TOTAL RECOV- ERABLE (UG/L AS PB)	NESE, TOTAL RECOV- ERABLE (UG/L AS MN)	TOTAL RECOV- BRABLR (UG/L AS HG) <0.10 <0.10	NIUM, TOTAL (UG/L AS SE)	TOTAL RECOV- ERABLE (UG/L AS AG)	TOTAL RECOV- ERABLE (UG/L AS ZN)	TOTAL (MG/L AS CN) 0.060	TOTAL (UG/L) 1	LENE BLUE ACTIVE SUB- STANCE (MG/L) 0.09 0.13
OCT 1991 07 DBC 11 FBB 1992 10 MAY	TOTAL RECOV- ERABLE (UG/L AS FE) 440	TOTAL RECOV- ERABLE (UG/L AS PB)	NESE, TOTAL RECOV- ERABLE (UG/L AS MN)	TOTAL RECOV- BRABLE (UG/L AS HG)	NIUM, TOTAL (UG/L AS SE)	TOTAL RECOV- ERABLE (UG/L AS AG)	TOTAL RECOV- ERABLE (UG/L AS ZN)	TOTAL (MG/L AS CN) 0.060	TOTAL (UG/L) 1	LENE BLUE ACTIVE SUB- STANCE (MG/L) 0.09

50049820 LAGUNA SAN JOSE NO. 2 AT SAN JUAN, PR

WATER-QUALITY RECORDS

LOCATION.--Lat 18°25'46", long 66°02'10", 0.2 mi (0.3 km) east of Caño de Martín Peña, and 650 ft (200 m) south of Isla Guachinango.

DRAINAGE AREA. -- Indeterminate.

PERIOD OF RECORD. -- Water years 1974 to current year.

WATER-QUALITY DATA, WATER YEAR OCTOBER 1991 TO SEPTEMBER 1992

DATE	TIME	SPB- CIFIC CON- DUCT- ANCE (US/CM)	PH WATER WHOLE FIELD (STAND- ARD UNITS)	TEMPER- ATURE WATER (DEG C)	TRANS- PAR- ENCY (SECCHI DISK) (IN)	OXYGEN, DIS- SOLVED (MG/L)	OXYGEN, DIS- SOLVED (PER- CENT SATUR- ATION)	COLI- FORM, FECAL, 0.45 UM-MF (COLS:/ 100 ML)	STREP- TOCOCCI FECAL, (COLS. PER 100 ML)
NOV 1991									
01	1005	32000	7.5	28.5	19.9	3.7	48	32000	7100
JAN 1992									
02	0910	23000	7.1	25.0	13.8	0.4	16	48000	8300
MAR 03	0825	26700	7.1	25.5	37.2	1.8	21	31000	17000
MAY	0025	20,00	7.1	-3.3	3,	1.0		31000	1,000
21	1230	22700	7.2	31.0	24.0	11.0	144	310	K10
20T	07.55	24.000						22000	
10 SEP	0755	21000	8.6	28.5	19.0	6.0	69	33000	
03	1215	24000	8.0	20.0	23.0	1.2	20	K22000	90
DATE	ALKA- LINITY WAT WH TOT FET FIELD MG/L AS CACO3	RESIDUE TOTAL AT 105 DEG. C, SUS- PENDED (MG/L)	NITRO- GEN, NITRITE TOTAL (MG/L AS N)	NITRO- GEN, NO2+NO3 TOTAL (MG/L AS N)	NITRO- GEN, AMMONIA TOTAL (MG/L AS N)	NITRO- GEN, ORGANIC TOTAL (MG/L AS N)	NITRO- GEN, AM- MONIA + ORGANIC TOTAL (MG/L AS N)	PHOS- PHORUS TOTAL (MG/L AS P)	CARBON, ORGANIC TOTAL (MG/L AS C)
	LINITY WAT WH TOT FET FIELD MG/L AS	TOTAL AT 105 DEG. C, SUS- PENDED	GEN, NITRITE TOTAL (MG/L	GEN, NO2+NO3 TOTAL (MG/L	GEN, AMMONIA TOTAL (MG/L	GEN, ORGANIC TOTAL (MG/L	GEN, AM- MONIA + ORGANIC TOTAL (MG/L	PHORUS TOTAL (MG/L	ORGANIC TOTAL (MG/L
DATE NOV 1991 01	LINITY WAT WH TOT FET FIELD MG/L AS	TOTAL AT 105 DEG. C, SUS- PENDED	GEN, NITRITE TOTAL (MG/L	GEN, NO2+NO3 TOTAL (MG/L	GEN, AMMONIA TOTAL (MG/L	GEN, ORGANIC TOTAL (MG/L	GEN, AM- MONIA + ORGANIC TOTAL (MG/L	PHORUS TOTAL (MG/L	ORGANIC TOTAL (MG/L
NOV 1991 01 JAN 1992	LINITY WAT WH TOT FET FIELD MG/L AS CACO3	TOTAL AT 105 DEG. C, SUS- PENDED (MG/L)	GEN, NITRITE TOTAL (MG/L AS N)	GEN, NO2+NO3 TOTAL (MG/L AS N)	GEN, AMMONIA TOTAL (MG/L AS N)	GEN, ORGANIC TOTAL (MG/L AS N)	GEN, AM- MONIA + ORGANIC TOTAL (MG/L AS N)	PHORUS TOTAL (MG/L AS P)	ORGANIC TOTAL (MG/L AS C)
NOV 1991 01 JAN 1992 02	LINITY WAT WH TOT PET FIELD MG/L AS CACO3	TOTAL AT 105 DEG. C, SUS- PENDED (MG/L)	GEN, NITRITE TOTAL (MG/L AS N)	GEN, NO2+NO3 TOTAL (MG/L AS N)	GEN, AMMONIA TOTAL (MG/L AS N)	GEN, ORGANIC TOTAL (MG/L AS N)	GEN, AM- MONIA + ORGANIC TOTAL (MG/L AS N)	PHORUS TOTAL (MG/L AS P)	ORGANIC TOTAL (MG/L AS C)
NOV 1991 01 JAN 1992 02 MAR	LINITY WAT WH TOT FET FIELD MG/L AS CACO3	TOTAL AT 105 DEG. C, SUS- PENDED (MG/L)	GEN, NITRITE TOTAL (MG/L AS N) 0.020	GEN, NO2+NO3 TOTAL (MG/L AS N) <0.050	GEN, AMMONIA TOTAL (MG/L AS N) 0.710	GEN, ORGANIC TOTAL (MG/L AS N) 0.59	GEN, AM- MONIA + ORGANIC TOTAL (MG/L AS N)	PHORUS TOTAL (MG/L AS P) 0.460 0.300	ORGANIC TOTAL (MG/L AS C) 7.8
NOV 1991 01 JAN 1992 02	LINITY WAT WH TOT FET FIELD MG/L AS CACO3	TOTAL AT 105 DEG. C, SUS- PENDED (MG/L)	GEN, NITRITE TOTAL (MG/L AS N)	GEN, NO2+NO3 TOTAL (MG/L AS N)	GEN, AMMONIA TOTAL (MG/L AS N)	GEN, ORGANIC TOTAL (MG/L AS N)	GEN, AM- MONIA + ORGANIC TOTAL (MG/L AS N)	PHORUS TOTAL (MG/L AS P)	ORGANIC TOTAL (MG/L AS C)
NOV 1991 01 JAN 1992 02 MAR 03 MAY 21	LINITY WAT WH TOT FET FIELD MG/L AS CACO3	TOTAL AT 105 DEG. C, SUS- PENDED (MG/L)	GEN, NITRITE TOTAL (MG/L AS N) 0.020	GEN, NO2+NO3 TOTAL (MG/L AS N) <0.050	GEN, AMMONIA TOTAL (MG/L AS N) 0.710	GEN, ORGANIC TOTAL (MG/L AS N) 0.59	GEN, AM- MONIA + ORGANIC TOTAL (MG/L AS N)	PHORUS TOTAL (MG/L AS P) 0.460 0.300	ORGANIC TOTAL (MG/L AS C) 7.8
NOV 1991 01 JAN 1992 02 MAR 03 MAY 21	LINITY WAT WH TOT FET FIELD MG/L AS CACO3 180 110 130 64	TOTAL AT 105 DEG. C, SUS- PENDED (MG/L) 10 14	GEN, NITRITE TOTAL (MG/L AS N) 0.020 0.010 <0.010	GEN, NO2+NO3 TOTAL (MG/L AS N) <0.050 <0.050 <0.050	GEN, AMMONIA TOTAL (MG/L AS N) 0.710 1.70 2.90 0.030	GEN, ORGANIC TOTAL (MG/L AS N) 0.59 0.0	GEN, AM- MONIA + ORGANIC TOTAL (MG/L AS N) 1.3 1.1 3.7 <0.20	PHORUS TOTAL (MG/L AS P) 0.460 0.300 0.790 0.050	ORGANIC TOTAL (MG/L AS C) 7.8 8.1 6.8
NOV 1991 01 JAN 1992 02 MAR 03 MAY 21	LINITY WAT WH TOT FET FIELD MG/L AS CACO3 180 110 130	TOTAL AT 105 DEG. C, SUS- PENDED (MG/L)	GEN, NITRITE TOTAL (MG/L AS N) 0.020 0.010 <0.010	GEN, NO2+NO3 TOTAL (MG/L AS N) <0.050 <0.050	GEN, AMMONIA TOTAL (MG/L AS N) 0.710 1.70 2.90	GEN, ORGANIC TOTAL (MG/L AS N) 0.59 0.0	GEN, AM- MONIA + ORGANIC TOTAL (MG/L AS N) 1.3 1.1	PHORUS TOTAL (MG/L AS P) 0.460 0.300	ORGANIC TOTAL (MG/L AS C) 7.8 8.1 6.8

K = non-ideal count

50049920 BAHIA DR SAN JUAN NO. 5 AT SAN JUAN, PR

WATER-QUALITY RECORDS

LOCATION--Lat 18°26'37", long 66°05'11", 0.4 mi (0.6 km) west of Puente de la Constituci[n, and 0.5 mi (0.8 km) south from U.S. Naval Reservation.

DRAINAGE--Indeterminate.

PERIOD OF RECORD--Water years 1974 to present.

WATER-OUTLITY DATA, WATER YEAR OCTORER 1991 TO SEPTEMBER 1992

		MY	TBR-QUA	LITY	DATA,	WATE	R YE	AR OCTO	BBR 1	991 T	O SE	PTEMB	R 19	92			
DATE	TIME	SPB- CIFIC CON- DUCT- ANCB (US/CM	FII (St) Ai	TER OLE SLD AND-	TEMPE ATUR WATE (DEG	R- B (TRANS PAR ENC! SECCI	- f OXY ii d so	GEN, IS- LVED G/L)	OXYG DI SOL (PE CE SAT ATI	S- VED R- NT UR-	FORI FECI 0.4! UM-1 (COL:	1, 1, 1, 1, 1, 1, 1, 1, 1, 1, 1, 1, 1, 1	STREP TOCOCC FECAL (COLS. PER 100 ML	I WAT , TOT FIE MG/I	TY WH FET LD AS	RESIDUE TOTAL AT 105 DEG. C, SUS- PENDED (MG/L)
NOV 1991 04	1145	3600	^	7.4	28		29.		2.7		42	37		520	^	120	25
JAN 1992	1145	3600	U	7.4	20	. 5	23.	,	2.,		42	37	,,,,	320	v	120	• •
02 MAR	1010	4800	0	8.0	26	. 5	23.	1	2.2		39	24	00	₹ 730	0	120	29
02 MAY	1130	5000	0	7.9	26	. 5	20.	3	3.7		52	58	00	490	0	130	26
22 JUL	1000	3300	0	7.5	29	. 0	17.0)	4.4		57	₹ 600	00	2000	0	130	63
10 SEP	0850	4500	0	7.1	28	. 0	28.	•	1.0		25		•	K12000	0	190	30
03	1345	5000	0	8.3	29	. 0	41.	5	6.0		59	:	30	1	0	120	35
DAT	NI' To B (1	GEN, TRATE N OTAL MG/L	NITRO- GEN, ITRITE TOTAL (MG/L AS N)		AL S/L	NITR GEN AMMON TOTA (MG/	i, IA (L L	NITRO- GEN, ORGANIC TOTAL (MG/L AS N)	GEN MON ORG TO (M	TRO- , AM- IA + ANIC TAL G/L N)	TO (M	FRO- EN, FAL G/L N)	NIT GE TOT (MG AS N	N, P AL /L	PHOS- HORUS TOTAL (MG/L AS P)	CARI ORGA TOT (MC	NIC FAL E/L
NOV 199 04 JAN 199	2	0.100	0.030		130	0.6		0.17		0.80		0.93		.1	0.190		5.7
02 Mar	1	0.070	0.030	0.	100	0.2	60	0.04		0.30		0.40	1	. 8	0.060		3.0
02 MAY			0.020	<0.	050	0.6	80	0.32		1.0			-	-	0.210	(5.2
22 JUL	(0.150	0.040	0.	190	0.4	70	0.43		0.90	:	1.1	4	. 8	0.200	(5.2
10 SEP	(0.090	0.030	ο.	120	1.2	0	0.0		1.2	;	1.3	5	. 8	0.260	•	7.9
03			<0.010	<0.	050	0.0	30		<	0.20			-	-	0.100	:	2.5

K = non-ideal count

THIS PAGE WAS LEFT BLANK INTENTIONALLY




Figure 20:-Río Grande de Loíza basin.

50050300 QUEBRADA BLASINA NEAR CAROLINA, PR

WATER-QUALITY RECORDS

LOCATION.--Lat 18°23'27", long 65°58'28", at bridge on Highway 3, 1.4 mi (2.3 km) south of Valle Arriba Heights housing area, and 1.2 mi (1.9 km) west-southwest of Carolina plaza.

PH WATER

WHOLE

DRAINAGE AREA . -- 2.96 mi 2 (7.67 km2).

PERIOD OF RECORD. -- Water years 1973 to current year.

DIS-CHARGE,

INST.

SPE-

CIFIC

WATER-QUALITY DATA, WATER YEAR OCTOBER 1991 TO SEPTEMBER 1992

OXYGEN, OXYGEN DIS- DEMAND,

CHEM-

SOLVED

COLI-

FECAL,

STREP-

DATE	TIME	PE	BIC COL BET DUC BR AN	n- fi CT- (ST. CB A	AND- A	MPER- TURE NATER DEG C)	TUR BIC ITY (NTU	o- DI	SEN, (P. S- C. VED SA	ER- I ENT () TUR- LE		O.45 UM-MF (COLS./	FECAL, (COLS. PER
OCT 1991					2.1	100							
16	0955	6	.4	430	7.8	26.0	27		2.0	25	31	K68000	20000
26 FBB 1992	1135	4	.1	443	7.5	23.5	25		5.3	37	23	43000	62000
12 MAY	1050	4	. 8	460	7.2	24.0	190		6.1	42	60	K71000	4400
11 JUN	0900	7	.2	470	6.9	26.0	2.	5	4.5	55	25	230000	K8500
22 AUG	1045	8	1.3	395	7.0	29.0	19		7.3	48	25	25000	3900
17	1300	6	. 6	385	7.4	28.5	22		6.2	36	20	59000	5600
DATE	TO ()	ARD- SSS OTAL 4G/L AS ACO3)	CALCIUM DIS- SOLVED (MG/L AS CA)	MAGNE- SIUM, DIS- SOLVED (MG/L AS MG)	SODIUM DIS- SOLVED (MG/I AS NA	SOI TI	DIUM AD- RP- ION TIO	POTAS- SIUM, DIS- SOLVED (MG/L AS K)	ALKA- LINITY WAT WH TOT FET FIELD MG/L AS CACO3	SULFID TOTAL (MG/L AS S)	SOL	ATE R - D VED S /L (CHLO- XIDE, DIS- SOLVED (MG/L AS CL)
OCT 1991													
DEC		160	52	8.4	29		1	3.8	140	<0.	5 30		35
26 FEB 1992				175					150		-		
MAY									180		-		
JUN		150	46	9.5	32		1	3.6	140	<0.			45
22 AUG									140		-		
17		140	44	6.9	21		0.8	2.8	160		3:	2	29
DATE	RI I SC ()	LUO- IDE, DIS- DLVED 4G/L 3 F)	SILICA, DIS- SOLVED (MG/L AS SIO2)	SOLIDS, SUM OF CONSTI- TUENTS, DIS- SOLVED (MG/L)	SOLIDS DIS- SOLVE (TONS PER DAY)	TOTAL AT 1 DEG. SUS	105 . C, 8-	NITRO- GEN, NITRATE TOTAL (MG/L AS N)	NITRO- GEN, NITRITE TOTAL (MG/L AS N)	NITRO GEN, NO2+NO TOTAL (MG/L AS N)	GEI 3 AMMOI TOT	N, NIA OR AL T /L (NITRO- GEN, RGANIC FOTAL MG/L AS N)
OCT 1991													
DEC		0.10	23	265	4.5	6	49	0.750	0.080	0.83	0 0.:	280	1.1
26 FEB 1992				17			24	1.03	0.170	1.20	0.	580	0.82
12 MAY				1.55	7-		390	1.14	0.160	1.30	0.:	390	1.9
11 JUN		0.20	26	268	5.2	2	<1	0.720	0.210	0.93	0 0.	740	0.86
22							37	0.930	0.070	1.00	0.	150	0.45
17		0.40	16	224	3.5	5	98	0.750	0.060	0.81	0 0.	160	0.64

0.750

98

0.060

0.810

0.160

0.64

K = non-ideal count

0.40

224

3.55

17...

50050300 QUEBRADA BLASINA NEAR CAROLINA, PR--Continued WATER-QUALITY DATA, WATER YEAR OCTOBER 1991 TO SEPTEMBER 1992

DATE	NITRO- GEN, AM- MONIA + ORGANIC TOTAL (MG/L AS N)	NITRO- GEN, TOTAL (MG/L AS N)	NITRO- GEN, TOTAL (MG/L AS NO3)	PHOS- PHORUS TOTAL (MG/L AS P)	ARSENIC TOTAL (UG/L AS AS)	BARIUM, TOTAL RECOV- ERABLE (UG/L AS BA)	BORON, TOTAL RECOV- ERABLE (UG/L AS B)	CADMIUM TOTAL RECOV- ERABLE (UG/L AS CD)	CHRO- MIUM, TOTAL RECOV- ERABLE (UG/L AS CR)	COPPER, TOTAL RECOV- ERABLE (UG/L AS CU)
OCT 1991										
16	1.4	2.2	9.9	0.700	<1	<100	30	<1	4	20
DEC 26	1.4	2.6	12	0.450						
FEB 1992										
12 May	2.3	3.6	16	0.720						
11	1.6	2.5	11	0.390	2	<100	60	<1	<1	<10
JUN					_			-		
22 AUG	0.60	1.6	7.1	0.160						
17	0.80	1.6	7.1	0.290						
DATE	IRON, TOTAL RECOV- ERABLE (UG/L AS FE)	LEAD, TOTAL RECOV- ERABLE (UG/L AS PB)	MANGA- NESE, TOTAL RECOV- BRABLE (UG/L AS MN)	MERCURY TOTAL RECOV- ERABLE (UG/L AS HG)	SELE- NIUM, TOTAL (UG/L AS SE)	SILVER, TOTAL RECOV- ERABLE (UG/L AS AG)	ZINC, TOTAL RECOV- ERABLE (UG/L AS ZN)	CYANIDE TOTAL (MG/L AS CN)	PHENOLS TOTAL (UG/L)	METHY- LENE BLUE ACTIVE SUB- STANCE (MG/L)
OCT 1991	TOTAL RECOV- ERABLE (UG/L AS FE)	TOTAL RECOV- ERABLE (UG/L AS PB)	NESE, TOTAL RECOV- BRABLE (UG/L AS MN)	TOTAL RECOV- ERABLE (UG/L AS HG)	NIUM, TOTAL (UG/L AS SE)	TOTAL RECOV- ERABLE (UG/L AS AG)	TOTAL RECOV- BRABLE (UG/L AS ZN)	TOTAL (MG/L AS CN)	TOTAL (UG/L)	LENE BLUE ACTIVE SUB- STANCE (MG/L)
OCT 1991 16	TOTAL RECOV- BRABLE (UG/L	TOTAL RECOV- ERABLE (UG/L	NESE, TOTAL RECOV- ERABLE (UG/L	TOTAL RECOV- ERABLE (UG/L	NIUM, TOTAL (UG/L	TOTAL RECOV- BRABLE (UG/L	TOTAL RECOV- BRABLE (UG/L	TOTAL (MG/L	TOTAL	LENE BLUE ACTIVE SUB- STANCE
OCT 1991	TOTAL RECOV- ERABLE (UG/L AS FE)	TOTAL RECOV- ERABLE (UG/L AS PB)	NESE, TOTAL RECOV- BRABLE (UG/L AS MN)	TOTAL RECOV- ERABLE (UG/L AS HG)	NIUM, TOTAL (UG/L AS SE)	TOTAL RECOV- ERABLE (UG/L AS AG)	TOTAL RECOV- BRABLE (UG/L AS ZN)	TOTAL (MG/L AS CN)	TOTAL (UG/L)	LENE BLUE ACTIVE SUB- STANCE (MG/L)
OCT 1991 16 DEC 26 FRB 1992	TOTAL RECOV- ERABLE (UG/L AS FE)	TOTAL RECOV- ERABLE (UG/L AS PB)	NESE, TOTAL RECOV- BRABLE (UG/L AS MN)	TOTAL RECOV- ERABLE (UG/L AS HG) 0.10	NIUM, TOTAL (UG/L AS SE)	TOTAL RECOV- ERABLE (UG/L AS AG) <1	TOTAL RECOV- BRABLE (UG/L AS ZN) 10	TOTAL (MG/L AS CN) <0.010	TOTAL (UG/L)	LENE BLUE ACTIVE SUB- STANCE (MG/L)
OCT 1991 16 DEC 26 FEB 1992 12	TOTAL RECOV- ERABLE (UG/L AS FE)	TOTAL RECOV- ERABLE (UG/L AS PB)	NESE, TOTAL RECOV- BRABLE (UG/L AS MN)	TOTAL RECOV- ERABLE (UG/L AS HG)	NIUM, TOTAL (UG/L AS SE)	TOTAL RECOV- ERABLE (UG/L AS AG)	TOTAL RECOV- BRABLE (UG/L AS ZN)	TOTAL (MG/L AS CN)	TOTAL (UG/L)	LENE BLUE ACTIVE SUB- STANCE (MG/L)
OCT 1991 16 DRC 26 FRB 1992 12 MAY	TOTAL RECOV- ERABLE (UG/L AS FE)	TOTAL RECOV- ERABLE (UG/L AS PB)	NESE, TOTAL RECOV- BRABLE (UG/L AS MN)	TOTAL RECOV- ERABLE (UG/L AS HG) 0.10	NIUM, TOTAL (UG/L AS SE)	TOTAL RECOV- ERABLE (UG/L AS AG) <1	TOTAL RECOV- BRABLE (UG/L AS ZN) 10	TOTAL (MG/L AS CN) <0.010	TOTAL (UG/L)	LENE BLUE ACTIVE SUB- STANCE (MG/L)
OCT 1991 16 DEC 26 FBB 1992 12	TOTAL RECOV- ERABLE (UG/L AS FE) 890	TOTAL RECOV- ERABLE (UG/L AS PB)	NESE, TOTAL RECOV- BRABLE (UG/L AS MN) 460	TOTAL RECOV- BRABLE (UG/L AS HG) 0.10	NIUM, TOTAL (UG/L AS SE) <1	TOTAL RECOV- BRABLB (UG/L AS AG) <1	TOTAL RECOV- BRABLE (UG/L AS ZN)	TOTAL (MG/L AS CN) <0.010	TOTAL (UG/L) 2	LENE BLUE ACTIVE SUB- STANCE (MG/L)

50050900 RIO GRANDE DE LOIZA AT QUEBRADA ARENAS, PR

LOCATION.--Lat 18°07'10", long 65°59'22", Hydrologic Unit 21010005, at intersection of Highways 181 and 9990, 0.2 mi (0.3 km) upstream from confluence with Río Emajagua and about 7.1 mi (11.4 km) southwest of San Lorenzo.

DRAINAGE AREA. -- 6.00 mi 2 (15.54 km2).

WATER-DISCHARGE RECORDS

PERIOD OF RECORD. -- October 1977 to current year.

GAGE.--Water-stage recorder. Elevation of gage is 640 ft (195 m), from topographic map.

REMARKS.--Records fair except those for estimated daily discharges, which are poor. Gage-height and precipitation satellite telemetry at station.

					OND, WATER DAILY MEAN		TOBER 199	1 TO SEPTE	MBER 199	2		
DAY	OCT	NOA	DEC	JAN	PRB	MAR	APR	MAY	JUN	JUL	λŪĠ	SEP
1	24	8.9	e18	e10	11	8.5	e 8.0	e6.0	e 80	15	12	21
2	75	9.2	e17	e 9.0	10	9.5	e8.2	e15	e70	14	13	18
3	24	8.8	e18	e8.4	10	9.1	e6.0	e13	e27	13	12	27
4	18	16	e25	e8.0	11	9.1	e5.8	e7.0	e140	13	13	17
5	18	11	e18	e1000	11	8.8	e5.6	e6.4	e4 0	18	e150	15
6	15	11	e15	e200	24	8.8	e5.4	e20	e30	13	e50	18
7	13	237	e14	e 60	14	22	e 5.6	e13	e27	12	e20	16
8 9	12 18	e840 e150	e13 e14	43 32	13	e 20	e6.4	e10	e29 e31	18 15	e17 e30	26 56
10	13	78	e12	33	12 13	e12 e8.0	e6.2 e6.0	e8.0 e6.6	e60	13	e20	26
11	14	34	e11	28	12	6.6	e10	e6.0	e62	33	e18	17
12	33	30	e11	24	12	6.2	e15	e7.0	e150	15	e15	15
13	15	23	e12	21	11	6.3	e11	e8.0	e100	13	14	15
14	12	19	10	19	14	6.4	e13	e9.0	e 80	15	44	13
15	12	17	9.7	22	15	7.3	e10	e8.0	e4 5	14	20	12
16	13	15	13	18	13	5.9	e9.0	e30	e37	12	19	19
17 18	15 11	14 13	10 9.4	17 16	11	e8.0	e7.0	e13	e60 e35	31 15	17 15	50 4 9
19	11	12	9.1	15	12 11	e9.0 6.2	e6.6 e8.0	e12 e12	e25	18	15	75
20	10	12	16	15	11	6.2	e20	11	e22	19	16	24
21	9.4	e55	12	14	10	5.7	e13	11	e150	20	14	e19
22	9.5	e70	9.0	13	11	6.1	e8.0	11	e35	101	13	e17
23	11	e20	9.1	14	11	5.9	e7.4	e150	30	18	15	e 15
24	10	e 80	8.6	14	12	5.8	e6.4	e 300	26	15	16	e14
25	9.4	e35	8.6	14	11	5.7	e6.0	e50	23	48	14	e13
26	9.7	e20	e8.4	14	15	6.0	e5.4	e350	21	16	16	e12
27	9.7	e45	e8.3	13	14	5.4	e5.2	e 60	20	13	15	e11
28	9.7	e35	e8.4	13	12	5.2	e5.0	e30	18	11	18	e11
29	9.3	e30	e9.0	11	9.4	5.2	e5.0	e22	17	10	16	e11
30 31	9.0 8.8	e20 	e11 e12	11 11		5.3 e6.5	e5.4	e35 e22	16	10 9.8	16 22	e12
TOTAL	481.5	1968.9	379.6	1740.4	356.4			1262.0	1506	600.8	705	664
MEAN	15.5	65.6	12.2	56.1	12.3	246.7 7.96	239.6 7.99	40.7	50.2	19.4	22.7	22.1
MAX	75	840	25	1000	24	22	20	350	150	101	150	75
MIN	8.8	8.8	8.3	8.0	9.4	5.2	5.0	6.0	16	9.8	12	11
AC-FT	955	3910	753	3450	707	489	475	2500	2990	1190	1400	1320
CFSM	2.59	10.9	2.04	9.36	2.05	1.33	1.33	6.78	8.37	3.23	3.79	3.69
IN.	2.99	12.21	2.35	10.79	2.21	1.53	1.49	7.82	9.34	3.72	4.37	4.12
e Ba	stimated											
STATIS?	rics of 1	MONTHLY M	RAN DATA	FOR WATER	YEARS 1978	- 1992.	BY WATER	YEAR (WY)				
MRAN	43.6	48.4	24.7							34.6	29.8	35.6
MAX	123	122	55.2	18.3 56.1	16.8 38.0	12.7 33.1	13.1 27.1	34.2 77.5	37.9 122	82.2	90.0	94.3
(WY)	1986	1988	1988	1992	1982	1989	1985	1985	1979	1979	1979	1979
MIN	13.1	8.34	6.65	8.16	6.36	5.07	4.64	9.56	11.3	12.5	9.30	11.8
(WY)	1990	1990	1990	1990	1979	1979	1979	1988	1985	1986	1991	1981
SUMMAR	Y STATIS	rics	FOR	1991 CALE	NDAR YEAR	P	OR 1992 W	NATER YEAR		WATER Y	EARS 1978	- 1992
ANNUAL				7245.2			10150.9					
	MEAN [ANNUAL ANNUAL]			19.8			27.7	•		29.2 49.6 14.5		1979 1990
	r daily i			840			1000	Jan 5		1250	Oct	6 1985
	DAILY M			4.5			5.0	Apr 28		3.1		7 1979
		AY MINIMU		4.7	Apr 27		5.4			3.6		1 1979
		PRAK FLOW					4810			11700		5 1983
		PRAK STAG	R				10.7	6 Nov 8		14.7		5 1983
		LOW FLOW		14370			2012-			2.8	May	5 1979
	RUNOFF RUNOFF			14370	1		20130			21150 4.8	7	
	RUNOFF			44.9			4.6 62.9			66.1		
	ENT EXC			26	_		44	·=		49	_	
	CENT EXC			10			13			15		
90 PERC	CENT BXC	REDS		6.1			6.6	5		6.9		

50050900 RIO GRANDE DE LOIZA AT QUEBRADA ARENAS, PR--Continued

WATER QUALITY RECORDS

PERIOD OF RECORD .-- WATER YEARS AUGUST 1981 TO CURRENT YEAR

DATE	TIME	STREAMFLOW, INSTANTANEOUS (CFS)	SPECIFIC CON- DUCTANCE (UMHOS)	TEMPERA- TURE (DEG C)	DATE		TIME	STREAMFLOW, INSTANTANEOUS (CFS)	SPECIFIC CON- DUCTANCE (UMHOS)	TEMPERA- TURE (DEG C)
JAN. 28	1438	13.9	150	27.0	JUN.	22	1152	39.2	110	25.5
FRB. 18	1452	11.6	160	26.5	JUL.	8 0	1132	16.4	130	27.0
MAR. 26	1247	6.88	150	27.0	AUG.	12	1305	13.6	120	27.0
MAY. 20	1348	11.1	110	27.5						

212

RIO GRANDE DE LOIZA BASIN

50051150 QUEBRADA BLANCA AT EL JAGUAL, PR

LOCATION.--Lat 18°09'40", long 65°58'58", Hydrologic Unit 21010005, 0.1 mi (0.2 km) upstream from bridge on Highway 181, and 2.8 mi (4.5 km) southwest of San Lorenzo.

DRAINAGE AREA. -- 3.25 mi² (8.42 km²).

WATER-DISCHARGE RECORDS

PERIOD OF RECORD. -- October 1984 to current year.

GAGE.--Water-stage recorder and crest-stage gage. Blevation of gage is 459 ft (140 m), from topographic map.

REMARKS.--Records fair. Gage-height and precipitation satellite telemetry at station.

	DISCHARGE, CUBIC FEET PER SECOND, WATER YEAR OCTOBER 1991 TO SEPTEMBER 1992 DAILY MEAN VALUES											
DAY	OCT	NOV	DEC	JAN	FEB	MAR	λPR	MAY	JUN	JUL	AUG	SEP
1	11	1.5	13	1.4	2.1	2.3	1.3	2.7	12	2.2	2.5	2.0
2	31	1.5	9.9	. 95	2.1	2.5	1.1	5.3	8.5	2.0	3.2	1.6
3	11	1.6	14	. 81	2.3	2.6	1.1	2.1	5.2	2.1	3.3	4.0
4	5.6	3.4	12	.72	3.9	2.4	1.1	1.8	31	7.0	4.1	2.5
5	4.2	2.7	7.9	194	3.3	2.4	1.1	1.5	8.1	10	51	1.6
6	3.1	7.8	6.3	55	7.3	2.7	1.2	2.3	4.5	2.7	14	1.9
7	2.5	41	5.4	7.5	8.8	2.5	1.5	2.8	4.8	2.3	7.2	1.8
8 9	2.1 1.9	114 60	4.8	5.9 4.1	5.3 5.5	2.3	1.3	2.0 1.7	6.1 4.5	5.7 4.0	4.3 3.8	1.6 3.9
10	1.6	39	3.9 3.2	3.6	7.7	2.1 2.0	1.1	1.6	12	2.4	7.2	1.8
11	1.9	24	3.0	2.6	5.7	1.8	1.5	1.8	7.0	4.9	4.4	1.6
12	1.4	16	3.3	2.1	4.8	1.8	1.9	2.0	32	3.4	8.7	1.6
13	1.6	11	2.5	1.8	4.3	1.7	1.4	1.6	13	2.2	5.1	1.6
14	2.0	7.5	3.2	1.7	3.8	1.7	1.4	1.6	14	1.9	4.6	1.7
15	2.0	5.8	2.1	1.5	4.1	1.7	1.4	2.0	11	2.1	4.3	1.7
16	2.6	27	2.7	1.6	4.0	1.6	1.3	20	10	3.9	3.5	11
17	3.1	16	2.1	2.2	3.6	2.0	1.2	8.0	10	20	3.1	13
18	3.0	7.7	1.7	1.5	3.4	1.9	1.2	6.2	6.6	3.1	2.5	7.7
19	2.1	5.6	1.5	1.3	3.4	1.7	1.3	6.9	4.2	2.5	2.2	28
20	1.6	4.5	5.8	1.2	3.4	1.5	1.5	19	5.6	4.0	2.0	57
21	1.4	16	3.7	1.2	3.2	1.5	1.4	14	30	4.3	1.9	26
22	1.5	33	1.8	1.1	3.1	1.4	1.6	12	12	18	1.8	11
23	1.7	15	1.5	1.1	3.1	1.4	1.5	60	7.2	3.6	1.7	8.5
24	1.5	53	1.3	1.3	4.1	1.2	1.4	42	5.1	4.5	2.2	4.8
25	1.4	30	1.2	1.4	3.6	1.2	1.4	16	3.9	12	2.1	3.1
26	1.4	15	1.1	1.5	3.1	1.2	1.5	34	3.6	5.4	2.0	2.3
27	1.4	31	1.0	1.5	2.9	1.1	1.6	13	3.4	4.7	2.2	1.9
28	1.4	41	.92	1.9	2.6	1.1	1.5	7.4	2.9	3.9	1.9	1.6
29	1.6	28	.93	1.9	2.4	1.1	1.5	6.6	2.4	3.2	1.7	1.4
30	1.6	18	.96	1.8		1.1	1.7	6.2	2.3	2.7	1.6	1.3
31	1.5		1.8	2.0		1.2		4.0		2.5	3.7	
TOTAL	111.7	677.6	124.51	308.18	116.9	54.7	41.0	308.1	282.9	153.2	163.8	209.5
MRAN	3.60	22.6	4.02	9.94	4.03	1.76	1.37	9.94	9.43	4.94	5.28	6.98
MAX	31	114	14	194	8.8	2.7	1.9	60	32	20	51	57
MIN	1.4	1.5	. 92	.72	2.1	1.1	1.0	1.5	2.3	1.9	1.6	1.3
AC-FT	222	1340	247	611	232	108	81	611	561	304	325	416
CFSM	1.11	6.95	1.24	3.06	1.24	. 54	.42	3.06	2.90	1.52	1.63	2.15
IN.	1.28	7.76	1.43	3.53	1.34	. 63	.47	3.53	3.24	1.75	1.87	2.40
Statist	rics of m	ONTHLY M	BAN DATA	FOR WATER	YBARS 1984	- 1992,	BY WATER	YEAR (WY)			
MRAN	13.0	19.7	7.90	4.82	4.04	4.65	2.53	9.41	6.20	5.03	6.44	7.68
MAX	47.8	36.9	30.1	9.94	8.21	20.7	4.88	31.5	21.3	13.0	20.2	14.3
(WY)	1986	1985	1988	1992	1989	1989	1989	1985	1987	1988	1988	1985
MIN	3.20	2.49	1.49	1.79	1.32	1.76	.90	1.51	2.40	2.02	2.21	1.36
(WY)	1987	1990	1990	1990	1985	1992	1991	1990	1991	1986	1985	1990
SUMMARY	STATIST	'IC S	FOR	1991 CALE	NDAR YEAR	P	OR 1992 WA	TER YEAR		WATER Y	BARS 1984	- 1992
ANNUAL	TOTAT.			1958.4			2552.09	,				
ANNUAL				5.3			6.97			7.6	3	
	ANNUAL	MRAN		5.0	•		0.5.			12.3		1988
	ANNUAL M									2.5		1990
	DAILY M			114	Nov 8		194	Jan 5		457		7 1987
LOWEST	DAILY ME	'AN		.3	8 Aug 10		.72	Jan 4		.3		10 1991
	SEVEN-DA				2 Aug 7		1.1			.4:	2 Aug	7 1991
	LYNEORS b						7180			7400		17 1985
	ANBOUS P		B					Jan 5		14.5	8 May	17 1985
	TANBOUS L			2000				Jan 5		EE 22		
	RUNOFF (3880 1.6			5060			5530 2.3	2	
	RUNOFF (22.4			2.15 29.21			31.8	_	
	RUNUFF (22.4 14			14			13		
	CENT BACE			1.8			2.5			2.5		
	CENT BACE			.6			1.3			1.1		
				.0	-		2.3					

50051150 QUEBRADA BLANCA AT EL JAGUAL, PR--Continued

WATER-QUALITY RECORDS

PERIOD OF RECORDS. -- Water years 1985 to 1986 and water year 1989 to current year.

PERIOD OF DAILY RECORD . --

SUSPENDED-SEDIMENT DISCHARGE: October 1984 to September 1986 and from October 1989 to September 1992.

EXTREMES FOR PERIOD OF DAILY RECORD. -SEDIMENT CONCENTRATION: Maximum daily mean, 7,300 mg/L Oct. 06, 1985; Minimum daily mean, 1 mg/L several days.

SEDIMENT LOADS: Maximum daily mean, 4,940 tons (23,400 tonnes) May 17, 1985; Minimum daily mean, 0.0 ton (0.0 tonne) several days.

EXTREMES FOR WATER YEARS 1992. --

SEDIMENT CONCENTRATION: Maximum daily mean, 1,150 mg/L Nov. 08, 1991; Minimum daily mean, 1 mg/L several days.

SEDIMENT LOADS: Maximum daily mean, 2,440 tons (2,210tonnes) Jan. 05, 1992; Minimum daily mean, 0 ton several days.

	MEAN				MRAN			MBAN	
	MRAN	CONCEN-	SEDIMENT	MRAN	CONCEN-	SEDIMENT	MRAN	CONCEN-	SEDIMENT
	DISCHARGE	TRATION	DISCHARGE	DISCHARGE	TRATION	DISCHARGE	DISCHARGE	TRATION	DISCHARGE
DAY	(CFS)	(MG/L)	(TONS/DAY)	(CFS)	(MG/L)	(TONS/DAY)	(CFS)	(MG/L)	(TONS/DAY)
	(/	(,,	(====,==,	(,	(1111)	,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,	,		, , ,
		OCTOBER		1	NOVEMBER		1	DECEMBER	
1	11	33	1.3	1.5	2	.00	13	12	.41
2	31	193	27	1.5	2	.00	9.9	7	.20
3	11	25	. 86	1.6	2	.01	14	7	.30
4	5.6	16	. 25	3.4	6	.08	12	11	.34
5	4.2	14	. 16	2.7	4	.04	7.9	10	.20
_								_	10
6	3.1	13	. 10	7.8	22	.88	6.3	7	. 12
7	2.5	11	. 07	41	292	52	5.4	5	.08
8	2.1	8	. 05	114	1150	634	4.8	4	. 05
9	1.9	8	.04	60	350	66	3.9	3	. 03
10	1.6	7	. 04	39	36	4.1	3.2	4	. 03
11	1.9	7	.03	24	22	1.5	3.0	5	.04
12	1.4	6	. 02	16	14	.61	3.3	6	.06
13	1.6	6	. 03	11	9	.27	2.5	6	.04
14	2.0	6	. 04	7.5	5	.10	3.2	6	.06
15	2.0	6	. 04	5.8	2	.04	2.1	6	.04
		_			_				
16	2.6	6	.04	27	125	26	2.7	9	. 07
17	3,1	6	. 05	16	42	2.5	2.1	10	. 05
18	3.0	6	.04	7.7	9	.19	1.7	9	. 04
19	2.1	5	.03	5.6	9	. 14	1.5	7	. 03
20	1.6	4	.02	4.5	9	.11	5.8	4	. 05
21	1.4	3	. 02	16	63	12	3.7	5	.06
22	1.5	3	. 02	33	184	20	1.8	5	. 02
23	1.7	3	.01	15	38	1.6	1.5	6	. 02
24	1.5	3	.02	53	357	70	1.3	ž	.02
25	1.4	3	.02	30	114	10	1.2	10	.02
23	1.4	,	. 02	30	114	10			
26	1.4	2	.01	15	18	.77	1.1	11	. 03
27	1.4	2	.00	31	145	16	1.0	7	.02
28	1.4	2	.00	41	240	45	.92	3	.00
29	1.6	2	.00	28	62	5.2	.93	3	.01
30	1.6	2	.00	18	15	.71	.96	6	. 02
31	1.5	2	.00				1.8	11	.06
TOTAL	111.7		30.31	677.6		969.85	124.51		2.52

50051150 QUEBRADA BLANCA AT BL JAGUAL, PR--Continued

DAY	MRAN DISCHARGE (CFS)	MEAN CONCEN- TRATION (MG/L)	SEDIMENT DISCHARGE (TONS/DAY)	MEAN DISCHARGE (CFS)	MEAN CONCEN- TRATION (MG/L)	SEDIMENT DISCHARGE (TONS/DAY)	MRAN Discharge (CFS)	MEAN CONCEN- TRATION (MG/L)	SEDIMENT DISCHARGE (TONS/DAY)
		JANUARY		1	BBRUARY			MARCH	
1 2 3	1.4 .95 .81	16 20 19	.06 .04 .04	2.1 2.1 2.3	4 4 3	.02 .02 .02	2.3 2.5 2.6	2 1 1	.02 .01 .01
4 5	.72 194	17 1020	.04 2440	3.9 3.3	3 1	.03 .01	2.4 2.4	2 3	.02 .02
6 7 8 9	55 7.5 5.9 4.1 3.6	649 13 7 6 6	154 .28 .11 .08 .06	7.3 8.8 5.3 5.5 7.7	2 3 3 3 3	.04 .07 .05 .04 .06	2.7 2.5 2.3 2.1 2.0	3 4 3 2 2	.02 .02 .02 .02 .02
11 12 13 14	2.6 2.1 1.8 1.7 1.5	5 4 3 2 3	.04 .03 .01 .01	5.7 4.8 4.3 3.8 4.1	3 3 3 2 1	.05 .04 .04 .03	1.8 1.8 1.7 1.7	2 2 2 3 4	.01 .00 .01 .02
16 17 18 19	1.6 2.2 1.5 1.3	3 4 3 3 2	.02 .03 .02 .02	4.0 3.6 3.4 3.4 3.4	1 1 1 1	.01 .00 .00 .00	1.6 2.0 1.9 1.7	5 6 7 8 7	.02 .03 .04 .04
21 22 23 24 25	1.2 1.1 1.1 1.3	2 2 2 2 2 17	.00 .00 .00 .00	3.2 3.1 3.1 4.1 3.6	1 1 2 2 3	.00 .01 .02 .02 .03	1.5 1.4 1.4 1.2	6 5 3 3 5	.02 .02 .01 .01
26 27 28 29 30 31	1.5 1.5 1.9 1.9 1.8 2.0	4 5 6 4 2 3	.02 .02 .03 .02 .02	3.1 2.9 2.6 2.4	2 2 2 2	.02 .02 .02 .02	1.2 1.1 1.1 1.1 1.1	5 3 2 3 4 5	.02 .01 .00 .01 .02
TOTAL	308.18		2595.11	116.9		0.71	54.7		0.56

50051150 QUEBRADA BLANCA AT EL JAGUAL, PR--Continued

		MRAN			MBAN		Mea		
DAY	MRAN DISCHARGE (CFS)	CONCEN- TRATION (MG/L)	SEDIMENT DISCHARGE (TONS/DAY)	MEAN DISCHARGE (CFS)	CONCEN- TRATION	SEDIMENT DISCHARGE (TONS/DAY)	MEAN DISCHARGE (CFS)	CONCEN- TRATION (MG/L)	SEDIMENT DISCHARGE (TONS/DAY)
DAI	(CFS)	(MG/L)	(TONS/DAI)	(CFS)	(MG/L)	(TONS/DAI)	(CFS)	(MG/L)	(TONS/DAI)
		APRIL			MAY			JUNE	
1	1.3	4	. 02	2.7	7	.09	12	57	6.8
2	1.1	3	.01	5.3	13	.28	8.5	26	.78
3	1.1	2	.00	2.1	3	.03	5.2	12	. 17
4	1.1	3	.01	1.8	1	.00	31	318	117
5	1.1	6	.02	1.5	2	.01	8.1	34	.75
6	1.2	7	. 03	2.3	3	.02	4.5	31	.40
7	1.5	6	. 03	2.8	4	.03	4.8	24	. 32
8	1.3	5	. 02	2.0	4	.02	6.1	15	.26
9	1.1	4	.01	1.7	3	.02	4.5	9	.11
10	1.0	3	.00	1.6	2	.01	12	41	2.5
11	1.5	3	.01	1.8	1	.00	7.0	22	.55
12	1.9	2	.01	2.0	1	.00	32	217	31
13	1.4	2	.00	1.6	3	.01	13	27	. 95
14	1.4	2	.00	1.6	5	.02	14	34	1.5
15	1.4	1	.00	2.0	5	.02	11	14	.39
16	1.3	1	.00	20	554	81	10	29	1.2
17	1.2	1	.00	8.0	23	.55	10	12	.32
18	1.2	1	.00	6.2	10	.16	6.6	7	. 14
19	1.3	2	.01	6.9	6	.12	4.2	5	. 05
20	1.5	2	.01	19	159	19	5.6	9	.29
21	1.4	2	.00	14	31	1.4	30	169	25
22	1.6	2	.01	12	4	.14	12	9	.30
23	1.5	2	.00	60	462	258	7.2	6	. 12
24	1.4	2	.00	42	278	47	5.1	6	.08
25	1.4	2	.00	16	53	2.9	3.9	11	. 10
26	1.5	2	.01	34	310	50	3.6	15	. 16
27	1.6	3	.02	13	45	1.9	3.4	16	.15
28	1.5	3	.02	7.4	13	.26	2.9	16	.11
29	1.5	4	. 02	6.6	6	.11	2.4	14	. 08
30	1.7	5	.02	6.2	17	.42	2.3	8	. 05
31				4.0	7	.09			
TOTAL	41.0		0.29	308.1		463.61	282.9		191.63

50051150 QUEBRADA BLANCA AT EL JAGUAL, PR--Continued SEDIMENT DISCHARGE, SUSPENDED (TONS/DAY), WATER YEAR OCTOBER 1991 TO SEPTEMBER 1992

DAY	MEAN DISCHARGE (CFS)	MEAN CONCEN- TRATION (MG/L) JULY	SEDIMENT DISCHARGE (TONS/DAY)	MBAN Discharge (CFS)	MEAN CONCEN- TRATION (MG/L)	SEDIMENT DISCHARGE (TONS/DAY)	MRAN DISCHARGE (CFS)	MEAN CONCEN- TRATION (MG/L)	SEDIMENT DISCHARGE (TONS/DAY)
		OOLI			AUGUST		81	SPIEMDER	
1	2.2	4	.03	2.5	4	.02	2.0	2	.01
2	2.0	3	.01	3.2	4	.04	1.6	2	.00
3	2.1	3	.01	3.3	4	.05	4.0	1	.01
4	7.0	28	2.3	4.1	6	.10	2.5	1	.00
5	10	42	1.9	51	461	121	1.6	1	.00
6	2.7	7	. 05	14	83	3.9	1.9	1	.00
7	2.3	7	.04	7.2	27	. 53	1.8	1	.00
8	5.7	15	.41	4.3	16	.20	1.6	2	.00
9	4.0	4	.06	3.8	12	.13	3.9	2	. 03
10	2.4	3	.02	7.2	8	.15	1.8	2	.01
11	4.9	3	. 04	4.4	6	.10	1.6	1	.00
12	3.4	4	. 03	8.7	21	.73	1.6	3	.01
13	2.2	4	. 02	5.1	- 8	.11	1.6	5	,02
14	1.9	4	.03	4.6	5	.08	1.7	5	.02
15	2.1	5	. 03	4.3	3	.04	1.7	4	.02
16	3.9	5	. 05	3.5	2	.02	11	62	9.2
17	20	135	19	3.1	2	.02	13	45	3.0
18	3.1	10	.08	2.5	3	.03	7.7	19	.56
19	2.5	5	. 04	2.2	6	.04	28	243	32
20	4.0	5	. 05	2.0	5	.03	57	329	412
21	4.3	5	.06	1.9	3	.02	26	49	3.8
22	18	79	6.6	1.8	2	.01	11	7	. 19
23	3.6	15	.17	1.7	2	.00	8.5	3	.08
24	4.5	8	.09	2.2	1	.00	4.8	3	.04
25	12	30	1.7	2.1	2	.01	3.1	2	.02
26	5.4	5	.07	2.0	3	.01	2.3	2	.02
27	4.7	4	.06	2.2	4	.02	1.9	2	.01
28	3.9	ā	. 04	1.9	6	.03	1.6	ī	.00
29	3.2		. 04	1.7	6	.03	1.4	ī	.00
30	2.7	ā	. 03	1.6	Š	.02	1.3	ī	.00
31	2.5	i	.02	3.7	3	. 02			
TOTAL	153.2		33.08	163.8		127.49	209.5		461.05
YEAR	2552.09		4876.21						

50051150 QUEBRADA BLANCA AT BL JAGUAL, PR--Continued

WATER QUALITY DATA, WATER YEAR OCTOBER 1991 TO SEPTEMBER 1992

PARTICLE-SIZE DISTRIBUTION OF SUSPENDED SEDIMENT

DATE	TIME	DIS- CHARGE, INST. CUBIC FERT PER SECOND	SEDI - MENT, SUS- PENDED (MG/L)	SEDI- MENT, DIS- CHARGE, SUS- PENDED (T/DAY)	SED. SUSP. FALL DIAM. PERCENT FINER THAN .002 MM	SED. SUSP. FALL DIAM. PERCENT FINER THAN .004 MM	SED. SUSP. FALL DIAM. PERCENT FINER THAN .008 MM
NOV 1991							
08	1633	101	1230	335	58	60	70
16	1420	120	1130	366	47		63
28	1340	111	1190	401		52	58
JAN 1992	1340		1130	401		J.	50
05	1020	113	851	260	54	56	59
MAY			452				
16	1238	83	82500	18500	2	3	5
JUN							
04	0940	341	3150	2900	23	29	35
	SED.	SED.	SED.	SED.	SED.	SED.	SED.
	SUSP.	SUSP.	SUSP.	SUSP.	SUSP.	SUSP.	SUSP.
	FALL	FALL	SIEVE	SIEVE	SIEVE	SIEVE	SIEVE
	DIAM.	DIAM.	DIAM.	DIAM.	DIAM.	DIAM.	DIAM.
	PERCENT	PERCENT	PERCENT	PERCENT	PERCENT	PERCENT	PERCENT
	FINER	FINER	FINER	FINER	FINER	FINER	FINER
DATE	THAN	THAN	THAN	THAN	THAN	THAN	THAN
	.016 MM	.031 MM	.062 MM	.125 MM	.250 MM	.500 MM	1.00 MM
NOV 1991							
08 <i>.</i>	82	86	96	98	99	99.8	99.9
16	67	69	92	97	99	99.7	99.8
28	65	76	95	98	99	99.8	99.9
JAN 1992							
05		74	96	98	99	99.6	99.9
MAY							
16 JUN	9	17	35	64	86	97	99
04	43	52	69	82	93	98	99

50051150 QUEBRADA BLANCA AT EL JAGUAL--Continued

WATER QUALITY DATA, WATER YEAR OCTOBER 1991 TO SEPTEMBER 1992

SILT AND CLAY PERCENT OF SUSPENDED SEDIMENT

DATE	TIME	STREAM- FLOW, INSTAN- TANEOUS (CFS)	SEDI- MENT, SUS- PENDED (MG/L)	SEDI - MENT, DIS - CHARGE, SUS - PENDED (T/DAY)	SED. SUSP. SIEVE DIAM. PERCENT FINER THAN .062 MM
NOV 1991					
16	1455	120	459	149	96
28	1410	122	897	296	97
JAN 1992					
05	0955	72	662	129	97
06	1343	37	143	14	95
MAY					
16	1258	118	3306	1050	91
JUN					
04	1035	69	1600	299	95
04	1125	70	5 6 4	106	96
AUG					
05	1015	40	52	5.6	96
05	1858	70	1970	372	95
SEP					
19	1635	97	1530	401	86

50051180 QUEBRADA SALVATIERRA NEAR SAN LORENZO, PR

LOCATION.--Lat 18°10'24", long 65°58'38", Hydrologic Unit 21010005, on left downstream side of bridge on Highway 181, 0.2 mi (0.3 km) upstream from Río Grande de Loíza, and 1.5 mi (2.4 km) southwest of San Lorenzo.

DRAINAGE AREA. -- 3.74 mi 2 (9.69 km2).

WATER-DISCHARGE RECORDS

PERIOD OF RECORD. -- January 1984 to current year.

GAGE.--Water-stage recorder and crest-stage gage. Elevation of gage is 330 ft (100 m), from topographic map.

REMARKS.--Records fair except those for estimated daily discharges, which are poor. Gage-height and precipitation satellite telemetry at station.

	DISCHARGE, CUBIC FERT PER SECOND, WATER YEAR OCTOBER 1991 TO SEPTEMBER 1992 DAILY MEAN VALUES											
DAY	OCT	NOA	DEC	JAN	FRB	MAR	APR	MAY	JUN	JUL	AUG	SEP
1	14	1.6	3.7	2.1	1.4	1.2	1.0	3.1	3.3	1.2	1.2	e1. 9
2	21	1.8	2.4	1.7	1.4	1.1	1.0	8.4	3.2	1.1	1.3	e 1.6
3	15	.95	7.2	1.4	1.4	1.1	.94	2.0	1.6	1.0	1.2	3.7
4 5	15 9.2	1.2 1.5	8.1 4.9	1.4 472	1.7 1.3	1.2 1.3	1.1 1.1	e1.1 e1.2	45 6.8	2.4 3.6	1.2 64	e2. 5 e1. 6
•	3.8	1.3	4.3	4/4	1.3	1.3	1.1	41.2	0.0	3.0	•	41.0
6	5.1	9.4	3.1	169	2.3	1.4	.99	e1.8	3.5	1.2	13	e3. 5
7	3.0	38	2.1	16	3.2	1.4	1.6	e2.2	3.0	1.0	7.5	e2.5
8 9	2.3 1.6	209 69	1.9 1.7	8.3 6.3	1.6 1.4	1.3 1.1	1.6 1.3	e1.6 e1.4	3.3 3.0	1.1 1.3	5.2 3.4	e1.8 e4.0
10	1.3	17	1.5	5.8	4.4	1.0	1.1	e1.3	4.9	1.0	9.0	2.2
11	3.7	10 6.7	1.3	3.9	2.1	1.0	1.5	e1.4	4.5 41	1.5	4.9 6.2	1.7 1.6
12 13	1.4 1.4	3.7	2.1 2.0	3.0 2.4	1.5 1.4	1.0 1.0	2.3 1.4	e1.5 e1.3	16	1.3 1.1	4.7	1.5
14	1.0	2.3	2.4	2.0	1.2	1.1	1.2	e1.2	11	.99	3.6	1.5
15	.90	1.8	1.8	2.0	1.4	1.5	1.4	e1.2	6.5	. 93	3.2	1.7
• •	.85					• •		••		2.0	2.5	2.8
16 17	1.2	4.1 3.1	2.2 2.2	2.0 4.2	1.3 1.2	1.2 1.3	1.4	12 2.7	6.4 4.7	2.0 6.9	2.1	6.3
18	.79	1.5	2.1	1.9	1.2	1.5	1.3	1.4	3.2	1.8	2.1	6.7
19	.73	1.1	2.2	1.8	1.2	1.2	1.7	1.2	2.3	1.7	1.8	54
20	.60	1.1	4.4	1.8	1.3	1.5	1.1	4.7	2.3	2.0	1.7	119
21	. 53	2.9	5.2	1.6	1.3	1.1	.84	2.3	10	1.8	1.6	56
22	.53	8.2	2.1	1.4	1.3	1.1	.90	1.3	3.5	6.7	1.5	20
23	2.4	2.6	1.8	1.4	1.4	1.1	1.0	57	2.3	2.4	1.4	13
24	.82	22	1.4	1.6	1.7	.91	.94	60	2.0	1.7	e2.5	10
25	. 65	9.1	1.4	1.7	1.6	1.0	1.0	12	1.8	1.7	e2.0	9.1
26	. 64	4.7	1.4	1.7	1.5	1.1	1.1	40	1.4	1.4	e2.2	8.9
27	.61	11	1.4	1.5	1.4	1.1	1.1	8.0	1.6	1.4	e2.0	8.6
28	.57	10	1.3	1.5	1.4	1.0	1.1	4.4	1.6	1.4	e1.9	7.9
29 30	2.8 7.7	8.9 5.8	1.3 1.3	1.6 1.5	1.3	1.0 .94	.90 1.4	2.5 2.2	1.3 1.2	1.3 1.2	e1.8 e1.7	7.2 7.0
31	1.9		2.9	1.5		. 97		1.6		1.2	e3.5	
TOTAL	119.22	470.05	80.8	726.0	46.8	35.72	36.41	244.0	202.2	57.32	161.9	369.8
MEAN MAX	3.85 21	15.7 209	2.61 8.1	23.4 472	1.61	1.15 1.5	1.21 2.3	7.87 60	6.74 45	1.85 6.9	5.22 64	12.3 119
MIN	.53	. 95	1.3	1.4	1.2	.91	.84	1.1	1.2	. 93	1.2	1.5
AC-PT	236	932	160	1440	93	71	72	484	401	114	321	733
CFSM	1.03	4.19	.70	6.26	.43	.31	.32	2.10	1.80	.49	1.40	3.30
IN.	1.19	4.68	.80	7.22	.47	.36	.36	2.43	2.01	. 57	1.61	3.68
e B	stimated											
STATIS	TICS OF	MONTHLY M	BAN DATA FO	R WATER	YEARS 1984	- 1992,	BY WATER	YEAR (WY)			
MRAN	11.1	15.1	5.94	5.37	3.57	3.74	2.80	8.58	6.56	4.30	5.46	10.7
MAX	36.2	33.4	22.8	23.4	10.3	17.4	6.60	35.8	15.0	12.1	14.4	29.0
(WY) MIN	1986 2.31	1988 2.72	1988 1.17	1992 1.16	1984 1.23	1989 1.15	1985 .8 8	19 8 5 1.53	1984 1.78	1988 1.58	19 88 1.95	1989 1.88
(WY)	1987	1990	1990	1990	1990	1992	1984	1990	1991	1986	1985	1990
SUMMAR	Y STATIS	TICS	FOR 1	991 CALE	NDAR YEAR	F	OR 1992 W	ATER YEAR		WATER Y	EARS 1984	- 1992
	TOTAL			1561.2	9		2550.2					
	MRAN			4.2	8		6.9	7		6.9		1000
	T ANNUAL									10.4 3.1		1988 1990
	T DAILY			209	Nov 8		472	Jan 5		472		27 1987
	DAILY M			.3	3 Jul 13		. 5	3 Oct 21				
		AY MINIMU		.4	9 Jun 14					.4	9 Sep 1 May	19 1990
		PRAK FLOW					5240	Jan 5		9320	May 0 May 6 May	17 1985
		PRAK STAG LOW FLOW					15.2	a uan b		1/.1	U MAY	30 1000 T\ TARD
		(AC-FT)		3100			5060	5 Oct 16 Jan 5 2 Jan 5 8 Oct 29		5010	- may	1330
ANNUAL	RUNOFF	(CFSM)		. 1.1	4		1.8	6		1.8	5	
ANNUAL	RUNOFF	(INCHES)		15.5	3		25.3			25.1		
	CENT EXC			8.0			9.1			10		
	CENT EXC			1.4			1.7 1.0			2.0		
FAR				. 0	-		1.0				-	

50051180 QUEBRADA SALVATIERRA NEAR SAN LORENZO, PR--Continued

WATER-QUALITY RECORDS

PERIOD OF RECORD. -- Water years 1984 to 1986 and water years 1989 to current year.

PERIOD OF DAILY RECORD . --

SUSPENDED-SEDIMENT DISCHARGE: October 1984 to September 1986 and from October 1989 to September 1992.

EXTREMES FOR PERIOD OF DAILY RECORD. --SEDIMENT CONCENTRATION: Maximum daily mean, 7,300 mg/L Oct. 06, 1985; Minimum daily mean, 1 mg/L several days.

SEDIMENT LOADS: Maximum daily mean, 11,100 tons (10,100 tonnes) Jan. 05, 1992; Minimum daily mean, 0.0 ton (0.0 tonne) several days.

EXTREMES FOR WATER YEARS 1992.--SEDIMENT CONCENTRATION: Maximum daily mean, 472 mg/L Jan. 05, 1992; Minimum daily mean, 0.53 mg/L several days.

SEDIMENT LOADS: Maximum daily mean, 11,100 tons (10,100 tonnes) Jan. 05 1992; Minimum daily mean, 0.0 ton (0.0 tonne) several days.

DISCHARGE, CUBIC FEET PER SECOND, WATER YEAR OCTOBER 1991 TO SEPTEMBER 1992

		MRAN			MRAN			MEAN	
DAY	MEAN DISCHARGE (CF8)	CONCEN- TRATION (MG/L)	LOAD (TONS/ DAY)	MBAN Discharge (CFS)	CONCEN- TRATION (MG/L)	LOAD (TONS/ DAY)	MEAN DISCHARGE (CFS)	CONCEN- TRATION (MG/L)	LOAD (TONS/ DAY)
		OCTOBER		1	NOVEMBER		1	DECEMBER	
1	14	14	2.3	1.6	1.6	.19	3.7	3.7	.08
2	21	21	6.3	1.8	1.8	.21	2.4	2.4	. 03
3	15	15	3.0	. 95	. 95	.09	7.2	7.2	1.1
Ä	15	15	3.9	1.2	1.2	.11	8.1	8.1	. 61
5	9.2	9.2	1.1	1.5	1.5	.15	4.9	4.9	.11
6	5.1	5.1	.30	9.4	9.4	2.8	3.1	3.1	. 05
7	3.0	3.0	.09	38	38	35	2.1	2.1	.03
8	2.3	2.3	. 06	209	209	1660	1.9	1.9	. 02
9	1.6	1.6	. 02	69	69	161	1.7	1.7	. 02
10	1.3	1.3	. 02	17	17	3.9	1.5	1.5	. 02
11	3.7	3.7	. 42	10	10	.30	1.3	1.3	.01
12	1.4	1.4	.01	6.7	6.7	. 12	2.1	2.1	. 02
13	1.4	1.4	.01	3.7	3.7	. 05	2.0	2.0	.02
14	1.0	1.0	.02	2.3	2.3	.03	2.4	2.4	.01
15	.90	. 90	.02	1.8	1.8	.02	1.8	1.8	. 02
16	.85	.85	.03	4.1	4.i	.40	2.2	2.2	.01
17	1.2	1.2	.02	3.1	3.1	.19	2.2	2.2	. 02
18	.79	.79	. 02	1.5	1.5	.02	2.1	2.1	. 02
19	.73	.73	. 02	1.1	1.1	.02	2.2	2.2	. 02
20	.60	.60	. 02	1.1	1.1	.02	4.4	4.4	.30
21	.53	.53	.02	2.9	2.9	.34	5.2	5.2	. 16
22	.53	.53	.02	8.2	8.2	1.0	2.1	2.1	. 02
23	2.4	2.4	. 27	2.6	2.6	.08	1.8	1.8	.01
24	. 82	.82	.00	22	22	24	1.4	1.4	.00
25	.65	. 65	.00	9.1	9.1	1.1	1.4	1.4	.00
26	. 64	. 64	.00	4.7	4.7	. 17	1.4	1.4	.00
27	.61	.61	.00	11	11	2.0	1.4	1.4	.00
28	.57	. 57	.00	10	10	1.7	1.3	1.3	.00
29	2.8	2.8	.50	8.9	8.9	.81	1.3	1.3	.00
30	7.7	7.7	3.2	5.8	5.8	.20	1.3	1.3	.01
31	1.9	1.9	21				2.9	2.9	. 13
TOTAL	119.22		42.69	470.05		1896.02	80.8		2.85

50051180 QUEBRADA SALVATIERRA NEAR SAN LORENZO, PR--Continued

DISCHARGE, CUBIC FEET PER SECOND, WATER YEAR OCTOBER 1991 TO SEPTEMBER 1992

DAY	MEAN DISCHARGE (CFS)	MEAN CONCEN- TRATION (MG/L)	LOAD (TONS/ DAY)	MEAN DISCHARGE (CFS)	MEAN CONCEN- TRATION (MG/L)	LOAD (TONS/ DAY)	MEAN DISCHARGE (CFS)	MEAN CONCEN- TRATION (MG/L)	LOAD (TONS/ DAY)
		JANUARY		1	PEBRUARY			MARCH	
1	2.1	2.1	.06	1.4	1.4	.01	1.2	1.2	.01
2	1.7	1.7	. 02	1.4	1.4	.00	1.1	1.1	. 02
3	1.4	1.4	. 02	1.4	1.4	.00	1.1	1.1	. 02
4	1.4	1.4	. 02	1.7	1.7	.01	1.2	1.2 1.3	.02 .01
5	472	472	11100	1.3	1.3	.00	1.3	1.3	.01
6	169	169	819	2.3	2.3	.00	1.4	1.4	.00
7	16	16	1.8	3.2	3.2	.00	1.4	1.4	. 00
8	8.3	8.3	. 18	1.6	1.6	.00	1.3	1.3	.00
9 10	6.3 5.8	6.3 5.8	. 08	1.4	1.4	.00 .26	1.1	1.1 1.0	.00
10	5.8	5.8	.08	4.4	4.4	.26	1.0	1.0	.00
11	3.9	3.9	. 05	2.1	2.1	.07	1.0	1.0	.00
12	3.0	3.0	. 02	1.5	1.5	.01	1.0	1.0	.00
13	2.4	2.4	.01	1.4	1.4	.00	1.0	1.0	.00
14	2.0	2.0	. 02	1.2	1.2	.00	1.1	1.1	.00
15	2.0	2.0	. 02	1.4	1.4	.00	1.5	1.5	.00
16	2.0	2.0	.03	1.3	1.3	.01	1.2	1.2	.00
17	4.2	4.2	.19	1.2	1.2	.02	1.3	1.3	.00
18	1.9	1.9	. 03	1.2	1.2	.01	1.5	1.5	.00
19	1.8	1.8	. 02	1.2	1.2	.00	1.2	1.2	.00
20	1.8	1.8	. 02	1.3	1.3	.01	1.5	1.5	.04
21	1.6	1.6	.01	1.3	1.3	.01	1.1	1.1	. 02
22	1.4	1.4	.00	1.3	1.3	.02	1.1	1.1	.01
23	1.4	1.4	.00	1.4	1.4	.01	1.1	1.1	.00
24	1.6	1.6	.00	1.7	1.7	.02	.91	.91	.00
25	1.7	1.7	.00	1.6	1.6	.02	1.0	1.0	.00
26	1.7	1.7	.00	1.5	1.5	.02	1.1	1.1	.00
27	1.5	1.5	.00	1.4	1.4	.01	1.1	1.1	.00
28	1.5	1.5	.01	1.4	1.4	.00	1.0	1.0	.00
29	1.6	1.6	. 02	1.3	1.3	.00	1.0	1.0	.01
30	1.5	1.5	. 02				.94	.94	. 00
31	1.5	1.5	. 02				. 97	. 97	. 01
TOTAL	726.0		11921.75	46.8		0.52	35.72		0.17

RIO GRANDE DE LOIZA BASIN 50051180 QUEBRADA SALVATIERRA NEAR SAN LORENZO, PR--Continued DISCHARGE, CUBIC FEET PER SECOND, WATER YEAR OCTOBER 1991 TO SEPTEMBER 1992

DAY	MRAN DISCHARGE (CFS)	MEAN CONCEN- TRATION (MG/L)	LOAD (TONS/ DAY)	MEAN DISCHARGE (CFS)	MRAN CONCEN- TRATION (MG/L)	LOAD (TONS/ DAY)	MEAN DISCHARGE (CFS)	MEAN CONCEN- TRATION (MG/L)	LOAD (TONS/ DAY)
		APRIL			MAY			JUNE	
1	1.0	1.0	.00	3.1	3.1	. 39	3.3	3.3	.25
2	1.0	1.0	.00	8.4	8.4	1.6	3.2	3.2	. 35
3	. 94	.94	.00	2.0	2.0	.04	1.6	1.6	. 06
4	1.1	1.1	.00	e1.1	1.1	e.02	45	45	250
5	1.1	1.1	.00	e1.2	1.2	e.02	6.8	6.8	.41
6	.99	.99	.00	e1.8	1.8	e.02	3.5	3.5	. 14
7	1.6	1.6	.00	e2.2	2.2	e.02	3.0	3.0	. 10
8	1.6	1.6	.00	e1.6	1.6	e.01	3.3	3.3	.07
9	1.3	1.3	.00	e1.4	1.4	e.02	3.0	3.0	. 05
10	1.1	1.1	.01	e1.3	1.3	e.02	4.9	4.9	. 32
11	1.5	1.5	.00	e1.4	1.4	e.02	4.5	4.5	. 15
12	2.3	2.3	.02	e1.5	1.5	e.02	41	41	130
13	1.4	1.4	.02	e1.3	1.3	e.02	16	16	3.6
14	1.2	1.2	.01	e1.2	1.2	e.02	11	11 '	1.4
15	1.4	1.4	.03	e1.2	1.2	e.02	6.5	6.5	. 19
16	1.4	1.4	.03	12	12	17	6.4	6.4	.41
17	1.1	1.1	.02	2.7	2.7	.11	4.7	4.7	. 14
18	1.3	1.3	.03	1.4	1.4	.00	3.2	3.2	.06
19	1.7	1.7	. 04	1.2	1.2	.01	2.3	2.3	.03
20	1.1	1.1	. 02	4.7	4.7	.60	2.3	2.3	.05
21	.84	.84	.01	2.3	2.3	.06	10	10	1.9
22	.90	.90	.01	1.3	1.3	.02	3.5	3.5	. 16
23	1.0	1.0	.01	57	57	540	2.3	2.3	.10
24	. 94	.94	.01	60	60	73	2.0	2.0	.08
25	1.0	1.0	. 01	12	12	3.0	1.8	1.8	. 05
26	1.1	1.1	.01	40	40	190	1.4	1.4	. 04
27	1.1	1.1	.00	8.0	8.0	.22	1.6	1.6	. 03
28	1.1	1.1	.00	4.4	4.4	.08	1.6	1.6	. 02
29	.90	.90	.00	2.5	2.5	.04	1.3	1.3	. 02
30	1.4	1.4	.00	2.2	2.2	.04	1.2	1.2	. 02
31				1.6	1.6	.03			
TOTAL	36.41		0.29	244.0		826.47	202.2		390.20

e Estimated

50051180 QUEBRADA SALVATIERRA NEAR SAN LORENZO, PR--Continued

DISCHARGE, CUBIC FEET PER SECOND, WATER YEAR OCTOBER 1991 TO SEPTEMBER 1992

DAY	MEAN DISCHARGE (CFS)	MEAN CONCEN- TRATION (MG/L)	LOAD (TONS/ DAY)	MEAN DISCHARGE (CFS)	MRAN CONCEN- TRATION (MG/L)	LOAD (TONS/ DAY)	MRAN DISCHARGE (CFS)	MEAN CONCEN- TRATION (MG/L)	LOAD (TONS/ DAY)
		JULY			AUGUST		S	RPTEMBER	
1	1.2	1.2	.02	1.2	1.2	.02	e1. 9	1.9	e.04
2	1.1	1.1	.01	1.3	1.3	.02	e1.6	1.6	e.04
3	1.0	1.0	. 02	1.2	1.2	.02	3.7	3.7	. 09
4	2.4	2.4	.18	1.2	1.2	.02	e 2.5	2.5	e.06
5	3.6	3.6	.33	64	64	269	e 1.6	1.6	e. 04
6	1.2	1.2	. 07	13	13	26	e3.5	3.5	e.06
7	1.0	1.0	.03	7.5	7.5	1.6	e2.5	2.5	e. 04
8	1.1	1.1	.02	5.2	5.2	. 65	e1.8	1.8	e. 09
9	1.3	1.3	.02	3.4	3.4	.19	e4 .0	4.0	e.22
10	1.0	1.0	.02	9.0	9.0	.69	2.2	2.2	. 04
11	1.5	1.5	.01	4.9	4.9	.27	1.7	1.7	. 02
12	1.3	1.3	.02	6.2	6.2	.21	1.6	1.6	.01
13	1.1	1.1	.02	4.7	4.7	.09	1.5	1.5	. 02
14	.99	.99	.02	3.6	3.6	.04	1.5	1.5	. 02
15	.93	.93	. 02	3.2	3.2	.04	1.7	1.7	.00
16	2.0	2.0	. 02	2.5	2.5	.04	2.8	2.8	.19
17	6.9	6.9	2.1	2.1	2.1	.03	6.3	6.3	. 45
18	1.8	1.8	. 36	2.1	2.1	.04	6.7	6.7	.61
19	1.7	1.7	.28	1.8	1.8	.02	54	54	226
20	2.0	2.0	. 29	1.7	1.7	.02	119	119	980
21	1.8	1.8	. 25	1.6	1.6	.02	56	56	52
22	6.7	6.7	1.9	1.5	1.5	.03	20	20	1.9
23	2.4	2.4	.23	1.4	1.4	.05	13	13	. 65
24	1.7	1.7	. 05	e2.5	2.5	e.11	10	10	. 19
25	1.7	1.7	. 04	e2.0	2.0	e.06	9.1	9.1	.09
26	1.4	1.4	. 04	e2.2	2.2	e.03	8.9	8.9	.11
27	1.4	1.4	.03	e2.0	2.0	e.02	8.6	8.6	. 12
28	1.4	1.4	. 02	e1.9	1.9	e.02	7.9	7.9	. 07
29	1.3	1.3	. 02	e1.8	1.8	e.02	7.2	7.2	. 06
30	1.2	1.2	. 02	e1.7	1.7	e.03	7.0	7.0	. 05
31	1.2	1.2	. 02	e3.5	3.5	€.07			
TOTAL	57.32		6.48	161.9		299.47	369.8		1263.28
YBAR	2550.22		16650.19						

e Estimated

50051180 QUEBRADA SALVATIERRA NEAR SAN LORENZO, PR--Continued WATER QUALITY DATA, WATER YEAR OCTOBER 1991 TO SEPTEMBER 1992

PARTICLE-SIZE DISTRIBUTION OF SUSPENDED SEDIMENT

DATE	TIME	DIS- CHARGE, INST. CUBIC FEBT PER SECOND	SEDI - MENT, SUS- PENDED (MG/L)	SEDI- MENT, DIS- CHARGE, SUS- PENDED (T/DAY)	SED. SUSP. FALL DIAM. PERCENT FINER THAN .002 MM	SED. SUSP. FALL DIAM. PERCENT FINSR THAN .004 MM	SED. SUSP. FALL DIAM. PERCENT FINER THAN .008 MM
NOV 1991							
08	1615	248	2120	1420	41	49	55
MAY 1992							
23	2027	375	30400	30800	24	30	34
JUN							
04	0941 0426	417 115	5500	6190	27	34 37	41
12	0426	115	4040	1250	32	3 /	42
DATE	SED. SUSP. FALL DIAM. PERCENT FINER THAN .016 MM	SED. SUSP. FALL DIAM. PERCENT FINER THAN .031 MM	SED. SUSP. SIEVE DIAM. PERCENT FINER THAN .062 MM	SED. SUSP. SIEVE DIAM. PERCENT FINER THAN	SED. SUSP. SIEVE DIAM. PERCENT FINER THAN .250 MM	SED. SUSP. SIEVE SIEVE PERCENT FINER THAN .500 MM	SED. SUSP. SIEVE DIAM. PERCENT FINER THAN 1.00 MM
NOV 1991							
08	72	80	98	99	99.7	99.8	100
MAY 1992 23	48	60	82	94	99	99.7	100
JUN	• 0	60	04	34	79	39.7	100
04	52	62	78	82	87	91	96
12	52	63	88	97	99	99.8	100

50051180 QUEBRADA SALVATIERRA NEAR SAN LORENZO--COntinued WATER QUALITY DATA, WATER YEAR OCTOBER 1991 TO SEPTEMBER 1992 SILT AND CLAY PERCENT OF SUSPENDED SEDIMENT

DATE	TIME	STREAM- FLOW, INSTAN- TANEOUS (CFS)	SEDI- MENT, SUS- PENDED (MG/L)	SEDI- MENT, DIS- CHARGE, SUS- PENDED (T/DAY)	SED. SUSP. SIEVE DIAM. PERCENT FINER THAN .062 MM
NOV 1991					
06	1011	0.83	38	0.1	83
JAN 1992					
06	1325	86	134	31	97
MAY					
23	2012	261	2290	1610	91
24	0047	255	1130	781	65
JUN					
04	0921	117	3840	1210	55
04	1055	210	1780	1010	96
04	1221	95	459	117	98
12	0421	108	11000	3200	90
SEP					
18	1025	11	603	18	97

50051310 RIO CAYAGUAS AT CERRO GORDO, PR

LOCATION.--Lat 18°09'13", long 65°57'20", Hydrologic Unit 21010005, at downstream side of bridge on Highway 912, at Barrio Cerro Gordo, 2.8 mi (4.5 km) south of San Lorenso.

DRAINAGE AREA. -- 10.2 ml2 (26.4 km2).

WATER-DISCHARGE RECORDS

PERIOD OF RECORD. -- October 1977 to current year.

GAGE.--Water-stage recorder and crest-stage gage. Elevation of gage is 490 ft (150 m), from topographic map. Prior to Oct. 1, 1983, at site 2,000 ft (610 m) downstream at different datum.

REMARKS.--Records poor. Sand removal at a commercial level is practiced at times during the year. This takes place about one hundred feet downstream from the low water control. Gage-height and precipitation satellite telemetry at station.

	DIS	CHARGE,	CUBIC FEET		OND, WATER DAILY MEAN		TOBER 199	1 TO SEPTE	MBER 199	2		
DAY	OCT	NOV	DEC	JAN	FEB	MAR	APR	MAY	JUN	JUL	D U Q	SEP
1	21	11	15	11	9.9	11	11	14	109	25	40	43
2	35	12	16	10	10	11	12	30	73	25	38	40
3	19	12	16	9.5	10	11	10	13	41	25	39	52
4	16	14	17	9.3	11	12	9.6	11	195	32	42	35
5	17	16	15	777	10	11	9.2	10	112	46	284	31
6	16	13	14	264	14	12	9.0	30	89	31	98	45
7 8	14	60	13	26	12	16	9.4 9.0	22	80 81	32 46	39 37	43 38
9	14 15	970 120	13 13	14 11	10 11	16 11	8.7	13 11	79	47	54	159
10	14	43	13	ii	12	10	8.5	10	105	43	108	37
11	13	21	12	10	11	10	9.4	10	83	83	52	26
12	15	19	13	9.8	10	10	15	10	e177	51	60	25
13	15	17	12	9.8	10	10	13	9.5	118	42	40	26
14 15	14 14	16 15	12 12	9.3 9.7	11 12	11 11	11 12	9.9 12	110 79	41 53	56 53	26 28
16	13	15	14	10	11	10	11	170	82	42	41	56
17	16	14	12	9.4	10	14	11	30	110	96	42	39
18	14	14	12	9.5	10	14	11	21	94	72	32	42
19	13	13	12	9.4	11	11	22	18	78	84	28	131
20	12	13	13	9.5	11	11	33	20	85	99	30	694
21	12	15	13	9.3	11	12	15	17	184	68	25	240
22	12	38	11	9.5	11	11	13	16	41	186	25	44
23	12	18	11	9.6	11	11	11	330	38	54	27 35	32 25
24 25	12 11	49 22	11 10	9.8 9.8	12 11	11 11	11 11	165 72	27 27	44 88	28	20
26	11	16	10	9.9	12	11	10	831	26	52	32	16
27	11	23	10	9.5	12	11	10	54	29	46	39	15
28	11	20	10	9.9	12	10	10	33	27	40	40	15
29	11	19	10	10	11	10	10	28	26	38	44	16
30	11	16	11	9.8		9.9	11	27	26	36	39	17
31	11		12	9.9		9.9		25		36	51	
TOTAL	445	1664	388	1346.2	319.9	350.8	356.8	2072.4	2431	1703	1598	2056
MEAN	14.4	55.5	12.5	43.4	11.0	11.3	11.9	66.9	81.0	54.9	51.5	68.5
MAX	35	970	17	777	14	16	33	831	195 26	186	284 25	694 15
min ac-ft	11 883	11 330 0	10 770	9.3 2670	9.9 635	9.9 696	8.5 708	9.5 4110	4820	25 3380	3170	4080
CFSM	1.41	5.44	1.23	4.26	1.08	1.11	1.17	6.55	7.94	5.39	5.05	6.72
IN.	1.62	6.07	1.42	4.91	1.17	1.28	1.30	7.56	8.87	6.21	5.83	7.50
e Ra	timated											
STATIST	ICS OF MO	NTHLY M	RAN DATA FO	R WATER	YBARS 1977	- 1992,	BY WATER	YEAR (WY)				
									48 -		45	
MBAN	66.0	75.2	46.9	28.7	26.7	21.9	20.9 46.0	50.3 155	47.9 140	42.2 118	47.6 202	55.4 216
MAX (WY)	176 1986	196 1988	163 1988	46.4 1988	67.5 198 4	45.4 1989	1985	1985	1979	1979	1979	1979
MIN	14.4	19.2	12.5	14.6	11.0	11.3	10.7	9.68	14.4	16.0	14.5	16.9
(WY)	1992	1982	1992	1990	1992	1992	1980	1990	1991	1990	1991	1980
SUMMARY	STATISTI	cs	FOR 1	.991 CALE	NDAR YEAR	F	'OR 1992 W	ATER YEAR		WATER YE	ARS 1977	- 1992
ANNUAL	TOTAL			7044.7			14731.1					
ANNUAL				19.3			40.2	:		44.2		
	ANNUAL M									89.7		1979
	ANNUAL ME			070	N 2		07.0	No C		18.6	3 3	1990
	DAILY MEA			970 9.0			970 8.5			290 0 7.1		1 1979 4 1981
	SEVEN-DAY		M	9.4			9.0			8.6		7 1983
	ANBOUS PE						7300			13200	Aug 3	1 1979
	ANEOUS PE		E				19.1	.2 May 26		9.44		1 1979
	ANBOUS LC									7.1	Feb	4 1981
	RUNOFF (A			13970 1.8	a		29220 3.9	·E		32030 4.33		
	RUNOFF (C			25.6			3.9 53.7			58.90		
	ENT BXCEE			22	-		80	-		67		
50 PERC	ENT EXCEE	RDS		14			15			24		
90 PERC	ENT EXCEE	BDS		10			10			12		

LOCATION.--Lat 18°11'09", long 65°57'42", Hydrologic Unit 21010005, at upstream side of bridge on Highway 183 by-pass, 0.4 mi (0.6 km) south from Plaza de San Lorenzo, 1.4 mi (2.2 km), southwest from Escuela Rafael Colón Garcia and 2.0 mi (3.2 km) northwest from Escuela Segunda Unidad de Carlos Zayas.

50051800 RIO GRANDE DE LOIZA AT HWY 183 NEAR SAN LORENZO, PR

DRAINAGE AREA. -- 25.0 mi 1 (64.8 km2).

WATER-DISCHARGE RECORDS

PERIOD OF RECORD. -- February 1990 to current year.

GAGE. -- Water-stage recorder. Elevation of gage is 262 ft (80 m), from topographic map.

REMARKS.--Records poor. Water purification plant located about 0.2 mi (0.3 km) upstream from gage. Gage-height and precipitation satellite telemetry at station.

	DI	SCHARGE,	CUBIC FRE		OND, WATER DAILY MEAN		TOBER 19	91 TO SEPTI	MBER 199	2		
DAY	OCT	NOA	DEC	Jan	FEB	MAR	APR	MAY	JUN	JUL	AUG	SEP
1	159	e 66	124	71	24	12	e19	9.1	e 300	92	100	75
2 3	221 162	e46	127	55	22	11	e 16	50	e 270	80 78	100	64
4	121	e54 e49	127 151	51 48	22 26	e13 e20	e14 13	12 7.8	e100 e540	99	109 104	103 71
Š	118	e43	114	3380	22	e 30	11	6.9	e150	127	592	61
6	102	e 66	102	1080	41	e 20	10	43	e140	81	273	76
7	79	e76	e94	168	38	e22	14	36	e250	76	192	73
8	73	e2600	e88	117	26	e18	12	16	e490	92	157	59
9 10	76 72	402 248	e 90 e84	83 85	23 33	e17 e15	10 10	12 11	⊕52 0 ⊕4 70	95 83	160 241	177 72
11 12	68 99	173	e76	66	25	e14	13	12	e660	134	161	60
13	78	150 127	≘ 80 ≘ 76	57 53	20	e14 e15	47 35	12 8.4	e500	98 80	168 130	54 49
14	66	115	e70	47	18 21	e20	30	8.7	e460 e400	79	157	47
15	68	103	e72	48	25	e14	26	28	e360	90	142	48
16	63	116	e 76	46	21	e 23	14	e 600	377	86	116	e 75
17	79	103	e74	48	17	e21	12	e120	385	179	103	e420
18	63	88	e62	40	16	e28	11	e 60	289	111	92	e110
19	54	82	e 60	38	16	e18	22	e45	179	132	85	e800
20	43	79	e74	37	14	e 20	65	●80	173	159	85	e2 500
21	43	94	e130	35	14	e21	23	e56	466	123	79	e1400
22	40	240	e68	34	16	e17	14	e38	210	270	76	e230
23	e 66	142	e 67	31	16	e 16	11	●800	179	134	74	180
24	e50	299	61	33	17	e14	9.2	e1200	150	116	85	153
25	-44	196	59	32	16	e18	8.3	e180	133	192	73	137
26	e40	135	54	34	16	e17	7.9	e1600	124	127	70	126
27	e35	228	55	29	16	e 16	7.1	e2 70	122	116	79	117
28	e34	220	54	30	15	-14	6.8	e120	115	105	70	106
29 30	e33	192	55	28	14	e13	6.3	e85	102	98	78	103
31	e120 e150	143	58 79	26 25		e13 e14	6.5	e140 e84	97 	96 96	65 84	100
TOTAL	2519	6675	2561	5955	610	538	504.1	5750.9	8711	3524	4100	7646
MEAN	81.3	222	82.6	192	21.0	17.4	16.8	186	290	114	132	255
MAX	221	2600	151	3380	41	30	65	1600	660	270	592	2500
MIN	33	43	54	25	14	11	6.3	6.9	97	76	65	47
AC-FT	5000	13240	5080	11810	1210	1070	1000	11410	17280	6990	8130	15170
CFSM	3.25	8.90	3.30	7.68	. 84	. 69	. 67	7.42	11.6	4.55	5.29	10.2
IN.	3.75	9.93	3.81	8.86	.91	.80	.75	8.56	12.96	5.24	6.10	11.38
e Ra	timated											
STATIST	ICS OF M	ONTHLY M	BAN DATA F	OR WATER	YEARS 1990	- 1992.	BY WATE	R YBAR (WY)			
						·		-		06.5	06.0	
MBAN MBAN	174 266	168 222	84.7 86.7	127	46.6	34.7	25.5	85.9	140	86.8	96.0	135 255
(WY)	1991	1992	1991	192 1992	71.1 1991	48.7 1991	31.8 1991	186 1992	290 1992	114 1992	132 1992	1992
MIN	81.3	113	82.6	62.9	21.0	17.4	16.8	35.1	47.8	66.0	48.6	59.7
(WY)	1992	1991	1992	1991	1992	1992	1992	1991	1991	1990	1991	1990
SUMMARY	STATIST	ICS	FOR :	1991 CALE	NDAR YEAR	1	OR 1992	WATER YEAR		WATER Y	EARS 1990	- 1992
ANNUAL	TOTAL.			27414			49094.	0				
ANNUAL				75.1			134	-		108		
Highest	ANNUAL	MBAN								134		1992
	ANNUAL M							_		82.2		1991
	DAILY M			2600	Nov 8		3380			3380		5 1992
	DAILY ME		vr	17 21	Jun 26 Jun 22		6. 7.	3 Apr 29 4 Apr 25		6.3 7.4		29 1992 25 1992
	ANBOUS P			41	Uun 22		28200			28200	.Tan	5 1992
	ANBOUS P							36 Jan 5		27.3		5 1992
ANNUAL	RUNOFF (AC-FT)		54380			97380			78390		_
	RUNOFF (3.0			_5.			4.3		
	RUNOFF (40.7	9		73.	05		58.8	ı	
	ENT EXCE			130 4 9			233 72			164 50		
	ENT EXCE			25			14			19		

50051800 RIO GRANDE DE LOIZA AT HWY 183 NEAR SAN LORENZO, PR--Continued

WATER-QUALITY RECORDS

PERIOD OF RECORDS .-- Water years 1990 to current year.

INSTRUMENTATION .-- DH-48 and automatic sediment sampler.

PERIOD OF DAILY RECORD.--SUSPENDED-SEDIMENT DISCHARGE: February 1990 to September 1992

EXTREMES FOR PERIOD OF DAILY RECORD. --SEDIMENT CONCENTRATION: Maximum daily mean, 1,570 mg/L Jun. 11, 1992; Minimum daily mean, 5 mg/L Several days.

SEDIMENT LOADS: Maximum daily mean, 46,800 tons (42,400 tonnes) Jan. 05, 1992; Minimum daily mean, 0.20 ton (0.18 tonne) May 05, 1992.

EXTREMES FOR WATER YEARS 1990-92.--

Water Year	Suspended-sediment maximum	concentration (mg/L) minimum	Suspended-sediment maximum	discharge (tons per day) minimum
1990	569 (Jun. 15)	41 (Apr. 30)	1,950 (Aug. 28)	2 (May, 21)
1991	950 (Oct. 21)	5 (Jun. 04-05)	5,740 (Oct. 21)	.33 (Jun. 04)
1992	1,570 (Jun. 11)	5 (Several days)	46,800 (Jan. 05)	.20 (May, 05)

DAY	MEAN DISCHARGE (CFS)	MEAN CONCEN- TRATION (MG/L)	SEDIMENT DISCHARGE (TONS/DAY)	MEAN DISCHARGE (CFS)	MEAN CONCEN- TRATION (MG/L)	SEDIMENT DISCHARGE (TONS/DAY)	MEAN DISCHARGE (CFS)	MEAN CONCEN- TRATION (MG/L)	SEDIMENT DISCHARGE (TONS/DAY)
		JANUARY		1	PEBRUARY			MARCH	
1				e4 6			40	87	9.8
2				e38			37	81	8.2
3				e 35			33	80	7.1
4				e 30			32	79	7.1
5				e29			30	73	5.8
6				e40			28	69	5.2
7				e 50			27	64	4.8
8				e65			26	64	4.5
9				e 50	97	e13	29	64	5.0
10				46	93	12	35	72	6.9
11				36	79	7.8	34	83	7.9
12				32	73	6.5	46	93	11
13				33	87	7.3	50	102	14
14				41	94	10	130	206	82
15				37	93	9.6	64	138	25
16				32	75	6.8	56	120	18
17				35	74	6.7	56	121	19
18				41	83	8.8	40	91	10
19				35	81	7.7	34	77	7.2
20				39	96	11	33	80	7.2
21				60	118	21	30	75	6.3
22				64	125	24	27	66	4.7
23				57	124	18	31	74	5.9
24				204	267	188	29	75	5.8
25				60	121	20	28	64	4.8
26				48	96	12	26	61	4.4
27				41	90	10	27	64	4.9
28				36	85	8.5	29	71	5.4
29							32	72	6.3
30							30	70	5.4
31							29	67	5.3
TOTAL				1360			1178		324.9

e Estimated

SEDIMENT DISCHARGE, SUSPENDED (TONS/DAY), WATER YEAR OCTOBER 1989 TO SEPTEMBER 1990

	mean				MRAN			MBAN		
DAY	MEAN DISCHARGE (CFS)	CONCEN- TRATION (MG/L)	SEDIMENT DISCHARGE (TONS/DAY)	MEAN Discharge (CFS)	CONCEN- TRATION (MG/L)	SEDIMENT DISCHARGE (TONS/DAY)	MRAN Discharge (CFS)	CONCEN- TRATION (MG/L)	SEDIMENT DISCHARGE (TONS/DAY)	
		APRIL			MAY			JUNE		
1	27	63	4.7	19	49	2.6	18	47	2.2	
2	26	61	4.4	20	50	2.7	19	48	2.4	
3	27	62	4.5	19	79	3.8	18	47	2.3	
4	26	65	4.5	19	89	4.8	19	63	3.3	
5	27	62	4.5	19	89	4.7	41	160	18	
6	25	59	4.1	18	87	4.3	53	121	19	
7	23	57	3.4	18	83	3.7	39	67	7.0	
8	22	57	3.3	22	64	3.9	24	60	4.0	
9	22	57	3.2	154	141	412	38	80	9.8	
10	21	50	2.8	247	303	301	26	67	4.7	
11	20	52	2.6	118	184	66	21	72	3.8	
12	21	55	3.2	44	93	12	19	50	2.5	
13	42	84	10	34	78	7.2	19	53	2.5	
14	37	80	8.6	36	60	5.6	515	375	1620	
15	24	58	3.9	30	75	6.2	399	569	754	
16	23	85	5.2	27	66	4.7	136	209	83	
17	24	60	3.7	25	65	4.3	77	125	28	
18	23	60	3.6	24	61	3.9	54	49	7.1	
19	26	162	11	21	54	3.2	46	46	5.8	
20	26	192	14	20	49	2.6	78	128	29	
21	21	174	10	17	41	2.0	50	69	9.4	
22	19	152	7.5	19	55	2.9	41	61	6.9	
23	19	121	5.8	19	62	3.4	38	57	5.9	
24	19	61	3.1	18	55	2.7	52	54	7.6	
25	53	97	22	15	56	2.4	263	321	275	
26	76	183	40	30	69	5.9	123	151	50	
27	49	84	11	25	65	4.7	72	52	11	
28	27	66	5.0	20	53	2.8	52	85	12	
29	22	54	3.3	19	55	2.8	44	61	7.1	
30	19	41	2.1	15	46	2.0	40	86	9.4	
31				17	43	2.0				
TOTAL	836		215.0	1148		892.8	2434		3002.7	

TOTAL

975.4

RIO GRANDE DE LOIZA BASIN

50051800 RIO GRANDE DE LOIZA AT HWY 183 NEAR SAN LORENZO, PR--Continued

SEDIMENT DISCHARGE, SUSPENDED (TONS/DAY), WATER YEAR OCTOBER 1989 TO SEPTEMBER 1990

MEAN MEAN MEAN CONCEN- SEDIMENT TRATION DISCHARGE CONCEN-SEDIMENT CONCEN- SEDIMENT TRATION DISCHARGE MRAN MRAN MRAN DISCHARGE DISCHARGE DISCHARGE TRATION DISCHARGE DAY (MG/L) (TONS/DAY) (MG/L) (TONS/DAY) (CFS) (MG/L) (TONS/DAY) JULY SEPTEMBER AUGUST 8.6 5.5 7.8 9.1 2 3 4 5 6.9 7.6 39 85 8.7 9.1 38 55 40 64 9.5 6.0 22 197 7 8 8.0 58 42 41 113 210 285 33 83 7.2 7.3 43 2570 72 619 6.4 12 13 14 4.8 4.3 6.4 17 5.1 37 52 55 53 105 64 36 102 147 5.7 82 151 84 43 17 62 15 51 8.9 6.3 4.7 3.0 47 150 78 45 62 108 46 25 22 23 36 31 78 51 9.4 7.5 2.8 9.0 99 80 2.9 9.6 8.0 49 25 224 47 44 94 12 3.4 27 28 8 9 5 5 108 16 320 2.6 143 197 186 86 82 70 137 9.5

5343.5

853.3

RIO GRANDE DE LOIZA BASIN
50051800 RIO GRANDE DE LOIZA AT HWY 183 NEAR SAN LORENZO, PR--Continued

	MBAN			MEAN		MBAN			
DAY	MRAN DISCHARGE (CFS)	CONCEN- TRATION (MG/L)	SEDIMENT DISCHARGE (TONS/DAY)	MEAN DISCHARGE (CFS)	CONCEN- TRATION (MG/L)	SEDIMENT DISCHARGE (TONS/DAY)	MEAN DISCHARGE (CFS)	CONCEN- TRATION (MG/L)	SEDIMENT DISCHARGE (TONS/DAY)
	(-12)	OCTOBER	(10115, 5111,		NOVEMBER	(1010, 0111,	•	DECEMBER	(1000, 2000,
1	65	120	23	163	236	100	102	199	59
2	51	92	13	152	225	89	84	154	37
3	57	77	11	138	177	66	122	225	82
4	50	62	8.8	359	373	571	95	179	50
5	46	65	8.0	320	309	340	70	131	24
6	41	70	8.1	199	27 7	157	61	118	19
7	37	77	7.9	152	182	78	56	111	17
8	45	94	13	130	103	39	54	106	15
9	135	189	146	113	73	22	53	104	15
10	133	204	75	105	58	16	51	54	7.5
11	88	159	40	96	45	11	55	49	7.5
12	60	125	21	89	30	7.0	49	51	7.0
13	142	223	91	84	15	3.2	42	65	7.5
14	117	187	75	79	9	1.9	229	295	214
15	97	223	59	76	9	1.8	120	180	61
16	353	382	734	76	9	1.8	86	154	36
17	144	144	66	74	10	1.9	70	132	25
18	301	243	451	71	10	1.9	61	117	19
19	724	351	877	70	10	1.8	56	109	16
20	410	391	1820	69	10	1.8	56	109	16
21	1390	950	5740	66	11	1.9	52	106	15
22	243	123	104	70	14	2.5	53	98	13
23	170	195	90	64	17	2.9	51	85	11
24	484	421	1530	60	20	3.1	52	68	9.2
25	810	638	1960	60	20	3.2	48	45	5.8
26	800	663	1650	74	75	20	45	15	1.8
27	398	430	506	90	151	35	47	9	1.2
28	269	340	267	83	151	35	54	11	1.7
29	213	285	162	64	145	26	70	63	15
30	192	285	152	159	235	115	78	158	34
31	188	271	140				566	508	1120
TOTAL	8253		16848.8	3405		1756.7	2688		1962.2

RIO GRANDE DE LOIZA BASIN
50051800 RIO GRANDE DE LOIZA AT HWY 183 NEAR SAN LORENZO, PR--Continued

DAY	MRAN DISCHARGE (CFS)	MEAN CONCEN- TRATION (MG/L)	SEDIMENT DISCHARGE (TONS/DAY)	MEAN Discharge (CFS)	MEAN CONCEN- TRATION (MG/L)	SEDIMENT DISCHARGE (TONS/DAY)	MEAN DISCHARGE (CFS)	MEAN CONCEN- TRATION (MG/L)	SEDIMENT DISCHARGE (TONS/DAY)
		JANUARY		1	PEBRUARY			MARCH	
1	124	117	42	54	106	16	58	340	54
2	77	29	6.8	46	92	11	50	306	41
3	65	21	3.6	56	103	15	53	274	38
4	59	21	3.3	50	102	14	67	240	43
5	82	79	29	121	164	115	63	235	41
6	80	154	38	129	196	79	106	235	65
7	86	136	32	81	134	31	89	235	55
8	90	161	42	45	94	12	93	230	57
9	89	175	44	40	84	9.1	67	228	42
10	79	134	27	42	89	11	54	228	33
11	69	126	23	111	180	65	49	227	30
12	70	131	25	133	189	118	50	227	30
13	66	131	25	155	252	122	45	226	28
14	67	56	9.6	68	197	38	47	225	29
15	80	48	10	60	204	33	45	229	29
16	65	48	8.6	51	201	29	40	241	27
17	55	4.8	7.4	46	198	24	37	250	25
18	50	46	6.4	45	193	24	38	260	26
19	49	45	5.8	80	159	35	47	268	32
20	47	43	5.3	74	158	37	36	303	29
21	46	42	5.1	94	145	38	34	333	31
22	44	42	5.1	69	118	23	46	345	44
23	46	42	5.3	58	109	17	46	363	45
24	44	42	5.2	59	110	17	35	375	36
25	48	42	5.2	59	117	19	32	390	35
26	46	48	6.1	58	111	18	31	408	33
27	46	57	7.1	49	98	13	31	432	35
28	46	67	8.1	59	216	38	30	433	35
29	45	92	11				e34	425	e37
30	43	88	10				e29	418	e36
31	47	104	13				e29	415	e33
TOTAL	1950		475.0	1992		1021.1	1511		1154

e Estimated

50051800 RIO GRANDE DE LOIZA AT HWY 183 NEAR SAN LORENZO, PR--Continued

	mean				MRAN			mean			
	MRAN	CONCEN-	SEDIMENT	MEAN	CONCEN-	SEDIMENT	MRAN	CONCEN-	SEDIMENT		
	DISCHARGE	TRATION	DISCHARGE	DISCHARGE	TRATION	DISCHARGE	DISCHARGE	TRATION	DISCHARGE		
DAY	(CFS)	(MG/L)	(TONS/DAY)	(CFS)	(MG/L)	(TONS/DAY)	(CFS)	(MG/L)	(TONS/DAY)		
		APRIL			MAY			JUNE			
1	e29	400	e31	e22	358	e21	25	6	.41		
2	e3 0	375	e30	e21	358	e20	30	6	.48		
3	e30	378	e31	e22	358	e21	22	6	. 35		
4	e28	378	e29	e30	358	e29	23	5	.33		
5	e28	378	e29	e26	358	e2 5	28	5	. 37		
6	e28	378	e 29	e 25	58	e 3.9	52	96	14		
7	e27	378	e 28	e27	61	e4.4	42	82	9.5		
8	e35	378	e 36	e25	58	e3.9	33	322	26		
9	e 39	378	e4 0	e24	56	e 3.6	29	64	4.9		
10	e 57	378	e58	e22	52	•3.1	26	68	4.8		
11	e38	378	e58	e23	54	e3.4	32	93	8.0		
12	e44	378	e45	e55	107	e16	82	135	37		
13	e34	378	e 35	e28	63	64.8	38	93	9.9		
14	e2 9	378	e 30	e23	54	e3.4	27	68	5.0		
15	e55	378	e56	e24	56	•3.6	31	67	5.9		
16	e4 6	390	e4 8	e26	690	e4 8	23	55	3.5		
17	e34	400	e 37	e23	760	e47	20	50	2.8		
18	e37	400	e4 0	e39	830	e 87	20	49	2.7		
19	e32	410	e 35	e2 9	920	e72	19	50	2.5		
20	e 26	415	e29	e30	67	e5.4	19	50	2.5		
21	e2 6	415	e 29	e54	105	e15	26	61	4.6		
22	e28	425	e32	57	99	15	25	66	4.7		
23	e2 6	416	e29	31	83	7.0	21	57	3.4		
24	e24	400	e 26	23	68	4.5	22	42	2.5		
25	e 27	400	e 29	197	244	233	21	59	3.4		
26	e 26	380	e 27	62	128	25	17	51	2.4		
27	e25	375	e25	32	72	6.5	19	52	2.7		
28	e 23	370	e23	26	61	4.4	24	57	3.8		
29	e22	358	e21	22	58	3.4	30	68	6.7		
30	e21	358	e20	21	24	1.4	609	383	1540		
31				20	7	.37					
TOTAL	954		1015	1089		741.07	1435		1715.14		

e Estimated

RIO GRANDE DE LOIZA BASIN

50051800 RIO GRANDE DE LOIZA AT HWY 183 NEAR SAN LORENZO, PR--Continued

DAY	MRAN DISCHARGE (CFS)	MBAN CONCEN- TRATION (MG/L)	SEDIMENT DISCHARGE (TONS/DAY)	MEAN DISCHARGE (CFS)	MRAN CONCEN- TRATION (MG/L)	SEDIMENT DISCHARGE (TONS/DAY)	MEAN DISCHARGE (CFS)	MBAN CONCEN- TRATION (MG/L)	SEDIMENT DISCHARGE (TONS/DAY)
		JULY			AUGUST		Si	B PTRM BER	
1	597	552	1410	38	85	8.7	43	100	12
2	143	230	95	36	77	7.4	60	98	16
3	83	161	36	33	73	6.6	35	78	7.6
4	71	131	24	29	67	5.5	31	71	5.8
5	53	106	16	28	65	5.1	29	70	5.5
6	47	91	11	30	69	5.8	33	78	7.0
7	40	82	8.6	29	56	4.3	28	85	6.7
8	34	76	7.2	25	61	3.9	31	78	6.7
9	33	72	6.4	24	61	3.8	67	119	28
10	33	79	7.1	22	57	3.3	55	109	18
11	27	75	5.8	23	55	3.5	49	90	12
12	25	60	4.1	20	54	2.9	37	81	7.9
13	25	59	4.1	22	58	3.4	34	77	7.0
14	24	57	3.8	26	71	5.3	34	76	6.8
15	75	115	57	32	69	6.1	33	73	6.5
16	371	362	442	26	59	4.2	31	74	6.0
17	117	181	62	49	89	12	330	414	758
18	69	136	26	62	101	17	132	46	19
19	56	139	22	40	82	8.8	80	28	5.9
20	65	126	23	29	74	5.8	61	23	3.9
21	50	97	13	61	84	14	79	94	25
22	42	89	10	145	208	112	187	265	157
23	44	96	11	95	173	54	217	277	159
24	56	113	18	49	96	13	130	206	77
25	48	104	14	38	80	8.1	85	153	34
26	38	85	8.8	35	74	6.8	69	136	26
27	42	85	9.4	118	171	97	88	157	41
28	40	85	9.4	170	267	138	165	249	123
29	39	89	9.0	71	136	28	268	361	277
30	64	143	26	56	104	15	198	271	147
31	51	115	16	46	91	11			
TOTAL	2502		2415.7	1507		620.3	2719		2012.3
YEAR	30005		31737.31						

	MBAN				MEAN		MRAN		
DAY	MEAN DISCHARGE (CFS)	CONCEN- TRATION (MG/L)	SEDIMENT DISCHARGE (TONS/DAY)	MBAN Discharge (CFS)	CONCEN- TRATION (MG/L)	SEDIMENT DISCHARGE (TONS/DAY)	MEAN DISCHARGE (CFS)	CONCEN- TRATION (MG/L)	SEDIMENT DISCHARGE (TONS/DAY)
		OCTOBER		1	NOVEMBER		1	DECEMBER	
1	159	230	102	e66	81	e14	124	100	33
2	221	367	245	e46	55	e6.8	127	69	22
3	162	229	103	e54	65	e9.5	127	57	20
4	121	156	49	e49	59	e7.8	151	48	19
5	118	176	63	e43	52	e6.0	114	38	12
6	102	142	42	e 66	81	e14	102	41	11
7	79	101	22	e 76	94	e 19	e94	48	e12
8	73	89	17	e2600	1000	e18200	e88	48	e11
9	76	97	20	402	851	1260	e90	43	e10
10	72	95	20	248	410	284	e84	39	e8. 9
11	68	85	16	173	265	131	e76	38	e7.8
12	99	162	54	150	166	68	e80	38	e8.2
13	78	95	20	127	95	35	e 76	38	e7.8
14	66	88	17	115	75	23	e70	38	e 7.2
15	68	88	16	103	70	19	e72	25	e4.9
16	63	88	15	116	130	51	e76	15	e3.1
17	79	89	19	103	145	44	e74	9	e1.8
18	63	95	16	88	111	26	e62	6	e1.1
19	54	108	16	82	103	23	e60	5	e.82
20	43	119	14	79	99	21	e74	5	e1.0
21	43	121	14	94	127	46	e130	7	e2.6
22	40	110	12	240	385	286	e68	10	e1.8
23	e66	81	e14	142	87	35	e67	10	e1.8
24	e50	60	e8.1	299	553	567	61	10	1.7
25	e44	53	e6.3	196	220	128	59	7	1.2
26	e40	48	. e5.2	135	60	23	54	5	.77
27	e35	42	e4.0	228	369	250	55	7	1.1
28	e34	41	e3.8	220	363	230	54	10	1.5
29	e33	40	e3.6	192	314	179	55	8	1.2
30	e120	163	e53	143	173	69	58	7	1.1
31	e150	213	e86				79	14	3.0
TOTAL	2519		1096.0	6675		22075.1	2561		220.39

e Estimated

RIO GRANDE DE LOIZA BASIN

50051800 RIO GRANDE DE LOIZA AT HWY 183 NEAR SAN LORENZO, PR--Continued SEDIMENT DISCHARGE, SUSPENDED (TONS/DAY), WATER YEAR OCTOBER 1991 TO SEPTEMBER 1992

DAY	MRAN DISCHARGE (CFS)	MEAN CONCEN- TRATION (MG/L)	SEDIMENT DISCHARGE (TONS/DAY)	MEAN DISCHARGE (CFS)	MEAN CONCEN- TRATION (MG/L)	SEDIMENT DI SCHARGE (TONS/DAY)	MEAN DISCHARGE (CFS)	MBAN CONCEN- TRATION (MG/L)	SEDIMENT DISCHARGE (TONS/DAY)
		JANUARY		1	BRUARY			MARCH	
1	71	15	3.2	24	45	2.8	12	18	. 57
2 3	55	15	2.3	22	55	3.3	11	18	. 55
	51	18	2.4	22	61	3.6	e 13	20	e.66
4	48	20	2.6	26	61	3.9	e 20	20	e1.1
5	3380	1380	46800	22	59	3.7	e 30	20	e 1.6
6	1080	507	1950	41	58	6.2	e20	20	e1.1
7	168	190	92	38	59	6.2	e22	20	e1.2
8	117	63	21	26	81	5.3	e1 8	21	e1. 0
9	83	56	13	23	94	5.9	e17	21	e.94
10	85	68	14	33	113	10	e15	20	e.82
11	66	65	12	25	74	5.3	e14	20	e.76
12	57	55	8.7	20	48	2.7	e14	20	e.76
13	53	45	6.4	18	27	1.3	e15	20	e.82
14	47	34	4.3	21	19	1.1	e 20	20	e1.1
15	48	31	4.1	25	20	1.3	e14	20	e.76
16	46	46	5.6	21	19	1.1	e23	20	e1.2
17	48	59	7.6	17	17	.75	e21	20	e1.1
18	40	53	5.6	16	14	.60	e28	20	e1.5
19	38	38	3.8	16	14	.61	e18	20	e.98
20	37	28	2.7	14	19	.77	e20	19	e1 .0
21	35	28	2.6	14	22	.84	e21	17	e.96
22	34	30	2.6	16	21	.84	e1 7	16	e.74
23	31	29	2.5	16	20	.91	e 16	16	e.70
24	33	25	2.2	17	19	.92	e14	16	e.60
25	32	21	1.9	16	18	. 82	e18	18	e.88
26	34	20	1.7	16	16	.66	e1 7	22	e.99
27	29	20	1.6	16	15	.63	e16	27	e1.2
28	30	20	1.6	15	16	.60	e14	34	e1. 3
29	28	21	1.7	14	17	.60	e13	41	e1.4
30	26	26	1.8				e 13	46	e 1.6
31	25	35	2.3				e14	251	e9. 5

TOTAL 5955 --- 48983.8 610 --- 73.25 538 --- 39.39

e Estimated

50051800 RIO GRANDE DE LOIZA AT HWY 183 NEAR SAN LORENZO, PR--Continued

237

DAY	MRAN DISCHARGE (CFS)	MEAN CONCEN- TRATION (MG/L)	SEDIMENT DISCHARGE (TONS/DAY)	MEAN DISCHARGE (CFS)	MEAN CONCEN- TRATION (MG/L)	SEDIMENT DISCHARGE (TONS/DAY)	MEAN DISCHARGE (CFS)	MEAN CONCEN- TRATION (MG/L)	SEDIMENT DISCHARGE (TONS/DAY)
		APRIL			MAY			JUNE	
1	e19	41	e2.1	9.1	16	.52	e300	533	e432
2	e16	32	e1.4	50	65	12	e270	459	e335
3	e14	25	e.93	. 12	15	.58	e100	131	e35
4	13	22	.78	7.8	10	.22	e540	1200	e1750
5	11	24	.70	6.9	10	.20	e150	212	e 86
6	10	24	.70	43	54	15	e140	196	e74
7	14	20	.70	36	50	6.1	e250	412	e278
8	12	18	. 63	16	18	.78	e490	1050	e1390
9	10	19	. 53	12	16	.52	e520	1140	e1600
10	10	22	.57	11	13	.36	e470	995	e1260
11	13	21	. 69	12	12	.36	e 660	1570	e2800
12	47	55	10	12	14	.49	e500	1080	e1460
13	35	47	5.8	8.4	11	.25	e460	165	e2 05
14	30	38	4.3	8.7	11	.31	e400	155	e167
15	26	32	2.7	28	35	3.4	e 360	145	e141
16	14	19	.76	e 600	3290	e 9390	377	138	129
17	12	13	. 41	e120	163	e53	385	660	811
18	11	10	.30	e60	73	e12	289	371	316
19	22	28	2.4	e45	46	e5.5	179	95	47
20	65	80	21	e 80	17	e3.6	173	76	35
21	23	23	1.6	e 56	15	e2.3	466	1370	3230
22	14	20	.76	e38	83	e8. 5	210	200	123
23	11	18	. 59	e8 00	1900	e41 00	179	53	27
24	9.2	17	. 47	e1200	2660	e8620	150	16	6.3
25	8.3	18	. 39	e 180	264	e128	133	11	3.9
26	7.9	21	.46	e1600	3350	e14500	124	11	3.6
27	7.1	25	.49	e270	459	e335	122	11	3.4
28	6.8	31	.57	e120	163	e53	115	10	3.1
29	6.3	29	.49	e85	108	e25	102	10	2.8
30	6.5	20	. 36	e140	196	e74	97	10	2.6
31				e84	106	e24			
TOTAL	504.1		63.58	5750.9		37374.99	8711		16756.7

e Estimated

50051800 RIO GRANDE DE LOIZA AT HWY 183 NEAR SAN LORENZO, PR--Continued SEDIMENT DISCHARGE, SUSPENDED (TONS/DAY), WATER YEAR OCTOBER 1991 TO SEPTEMBER 1992

DAY	MEAN DISCHARGE (CFS)	MEAN CONCEN- TRATION (MG/L)	SEDIMENT DISCHARGE (TONS/DAY)	MEAN DISCHARGE (CFS)	MRAN CONCEN- TRATION (MG/L)	SEDIMENT DISCHARGE (TONS/DAY)	MEAN DI SCHARGE (CFS)	MEAN CONCEN- TRATION (MG/L)	SEDIMENT DISCHARGE (TONS/DAY)
		JOLY			AUGUST		SI	RPTEMBER	
1	92	10	2.5	100	39	10	75	73	14
2	80	10	2.2	100	41	12	64	106	19
3	78	10	2.1	109	89	26	103	129	42
4	99	73	38	104	138	40	71	35	7.6
5	127	154	63	592	2490	5600	61	28	4.7
6	81	55	13	273	811	653	76	27	5.0
7	76	23	4.5	192	484	235	73	23	4.5
8	92	93	27	157	238	106	59	20	3.5
9	95	59	17	160	246	122	177	252	159
10	83	17	3.8	241	324	221	72	73	16
11	134	167	79	161	196	83	60	44	7.2
12	98	71	22	168	174	76	54	32	4.7
13	80	23	4.9	130	160	54	49	22	2.9
14	79	17	3.7	157	216	94	47	22	2.7
15	90	18	4.1	142	291	119	48	37	4.7
16	86	19	4.3	116	143	45	e 75	74	e15
17	179	287	191	103	436	125	e420	245	e278
18	111	108	32	92	23	5.8	e110	209	e62
19	132	147	61	85	25	5.8	e800	453	e977
20	159	253	107	85	28	6.3	e2 500	418	e2820
21	123	164	53	79	30	6.6	e14 00	350	e1320
22	270	776	767	76	41	8.5	e230	196	e123
23	134	130	49	74	64	13	180	41	20
24	116	63	21	85	73	16	153	18	7.4
25	192	217	148	73	52	10	137	20	7.1
26	127	138	50	70	28	5.5	126	31	10
27	116	99	30	79	29	6.3	117	44	14
28	105	88	25	70	34	6.5	106	49	14
29	98	79	21	78	37	8.3	103	40	11
30	96	55	14	65	36	6.5	100	26	7.1
31	96	39	10	84	40	9.1			
TOTAL	3524		1870.1	4100		7735.2	7646		5983.1
YRAR	49094.0		142271.60						

e Estimated

50051800 RIO GRANDE DE LOIZA AT HWY 183 NEAR SAN LORENZO, PR--Continued

WATER QUALITY DATA, WATER YEAR OCTOBER 1991 TO SEPTEMBER 1992

PARTICLE-SIZE DISTRIBUTION OF SUSPENDED SEDIMENT

DATE	TIMR	DIS- CHARGE, INST. CUBIC FEST PER SECOND	SEDI - MENT, SUS- PENDED (MG/L)	SEDI- MENT, DIS- CHARGE, SUS- PENDED (T/DAY)	SED. SUSP. FALL DIAM. PERCENT FINER THAN .002 MM	SED. SUSP. FAIL DIAM. PERCENT FINER THAN .004 MM	SED. SUSP. FALL DIAM. PERCENT FINER THAN .008 MM
NOV 1991 08 JAN 1992	2056	1190	4460	14300	21	29	35
05	1936	27800	17300	1300000	19	24	29
MAY 16 JUN	1616	e600	11700	e18900	22	27	31
21 SEP	0535	2110	7360	41900	18	26	30
05	1905	2500	6300	42500	19	23	27
DATE	SED. SUSP. FALL DIAM. PERCENT FINER THAN .016 MM	SED. SUSP. FALL DIAM. PERCENT FINER THAN .031 MM	Piner Than	SUSP. SIEVE DIAM. PERCENT FINER THAN	Finer Than	SUSP. SIEVR DIAM.	SED. SUSP. SIEVE DIAM. PERCENT FINER THAN 1.00 MM
NOV 1991 08	45	55	75	90	97	99	100
JAN 1992 05	36	44	55	77	92	98	99
MAY 16	40	50	67	86	97	99	100
JUN 21	41	52	70	87	96	99	100
SEP 05	37	44	58	77	90	98	99

50051800 RIO GRANDE DE LOIZA AT HWY 183 NEAR SAN LORENZO, PR--Continued WATER QUALITY DATA, WATER YEAR OCTOBER 1991 TO SEPTEMBER 1992

SILT AND CLAY PERCENT OF SUSPENDED SEDIMENT

Date	TIME	STREAM- FLOW, INSTAN- TANEOUS (CFS)	SEDI- MENT, SUS- PENDED (MG/L)	SEDI- MENT, DIS- CHARGE, SUS- PENDED (T/DAY)	SED. SUSP. SIEVE DIAM. PERCENT FINER THAN .062 MM
NOV 1991					
08	1641	2080	5420	30400	66
08	2141	8130	3810	83670	81
24	1040	308	999	831	87
JAN 1992					
05	1806	3900	7410	78100	65
05	2236	8080	1160	25400	99
06	1220	634	540	925	82
FRB					
25	0945	14	172	6.5	94
JUN					
21	0505	2550	6280	43300	56
21	0720	854	3000	6890	86
JUL					
17	0927	295	942	750	72
22	1030	476	2560	3290	86
AUG					
05	0925	461	3010	3750	83
05	0940	407	4390	4820	74
05	1155	3 2 3	2790	2430	89
05	2020	2040	5490	30270	57
05	2205	1080	2210	6450	100

....

50053025 RIO TURABO ABOVE BORINQUEN, PR

LOCATION.--Lat 18°09'35", long 66°02'26", Hydrologic Unit 21010005, on left bank at Highway 765, 1.2 mi (1.9 km) south of Villa Borinquen, 8.1 mi (13.0 km) upstream from Río Grande de Loíza.

DRAINAGE AREA. -- 7.14 mi 2 (18.49 km2).

WATER-DISCHARGE RECORDS

PERIOD OF RECORD. -- January 1990 to current year.

GAGE.--Water-stage recorder and crest-stage gage. Elevation of gage is 492 ft (150 m), from topographic map.

REMARKS.--Records fair except those for estimated daily discharges, which are poor. Gage-height and precipitation satellite telemetry at station.

94141	TILE CEL	temetry at	. Station.									
	DISCHARGE, CUBIC FEET PER SECOND, WATER YEAR OCTOBER 1991 TO SEPTEMBER 1992 DAILY MEAN VALUES											
DAY	OCT	NOV	DEC	JAN	FEB	MAR	APR	MAY	JUN	ஶ	λŪG	SEP
1	16	8.2	18	13	14	10	7.3	15	65	14	11	9.9
2	37	8.1	17	12	14	11	6.3	37	29	14	13	10
3	17	8.4	21	12	14	10	5.9	8.3	24	14	14	17
4 5	15 13	8.4 8.6	23 18	12 605	15 13	10 10	5.7 5.5	6.2 5.9	68 26	13 15	14 183	11 9.3
•		5.0	10	003			3.3	3.3			100	
6	11	8.2	16	328	29	11	5.8	11	22	12	62	11
7 8	11 10	133 227	15	31 13	23	10	9.8	10 7.2	29 40	11 16	28 22	11 11
ŝ	13	111	15 14	8.8	18 16	10 9.0	8.0 6.9	6.2	27	14	18	43
10	11	52	14	11	21	9.0	6.7	6.2	114	12	22	12
		0.5	4.0		4.5				- 405	20	20	
11 12	9.7 14	25 e21	13 14	8.6 9.7	17 15	8.6 8.4	8.2 34	7.0 7.7	e125 149	20 13	20 21	9.6 8.7
13	9.7	18	13	12	13	8.6	13	7.9	e101	11	17	8.2
14	9.4	16	13	14	14	9.3	15	6.3	e69	11	24	7.9
15	8.8	14	e13	18	15	9.9	10	9.0	44	11	19	7.5
16	8.9	21	15	43	12	8.6	7.5	88	36	12	16	34
17	9.5	17	13	47	12	19	6.8	16	82	34	15	27
18	9.2	15	13	27	11	11	6.9	10	37	12	12	17
19 20	8.5 8.0	14 13	13 24	24 22	12 11	9.0 8.6	24 18	8.3 24	26 24	17 19	12 12	87 205
40	0.0	13	4*	44	11	0.0	10	••	••	13		203
21	8.1	20	18	21	11	8.6	7.7	11	137	13	11	147
22	8.4	37	14	19	12	8.5	7.0	8.6	37	34	10	33
23 24	8.3 7.9	20 127	13 13	19 19	12 12	7.5 7.5	6.3 5.9	150 151	28 23	16 12	10 11	21 17
25	8.0	32	13	20	12	7.3	5.7	49	20	39	10	14
26	7.9	22	12	19	16	6.8	5.4	134	19	16	16	13
27 28	7.3 7.3	47 38	12 12	17 20	12 11	6.8 6.6	5.4 5.4	40 19	18 16	13 12	13 11	11 10
29	7.3	27	12	17	11	6.2	5.1	14	15	11	11	9.5
30	7.3	21	13	16		6.2	5.6	40	16	12	9.8	9.4
31	7.3		14	15		7.0		15		11	12	
TOTAL	334.8	1137.9	461	1473.1	418	280.0	270.8	928.8	1466	484	679.8	842.0
MBAN	10.8	37.9	14.9	47.5	14.4	9.03	9.03	30.0	48.9	15.6	21.9	28.1
MAX	37	227	24	605	29	19	_34	151	149	39	183	205
MIN AC-FT	7.3 664	8.1 2260	12 914	8.6 2920	11 829	6.2 555	5.1 537	5.9 18 4 0	15 2910	11 960	9.8 1350	7.5 1670
CFSM	1.51	5.31	2.08	6.66	2.02	1.27	1.26	4.20	6.84	2.19	3.07	3.93
IN.	1.74	5.93	2.40	7.67	2.18	1.46	1.41	4.84	7.64	2.52	3.54	4.39
e Bi	stimated											
QT ATT Q	TTC9 OF 1	MONTHLY M	BAN DATA F	^D W1#9D 1	/DIDE 1000	1992	av wardd	VPAD /WV				
oral io	IICB OF I	MONTHIA MA	SAM DAIR P	OR WAISK	BARB 1330	- 1334,	DI WATER	I I I I I I I I I I I I I I I I I I I	,			
WBYN	29.5	28.3	19.0	23.6	13.8	10.7	7.37	16.6	26.2	18.5	18.2	21.4
MAX	48.2	37.9	23.1	47.5	18.1	11.6	9.03	30.0	48.9	21.2	21.9	28.1
(WY) MIN	1991 10.8	1992 18.7	1991 14.9	1992 7.85	1991 8.93	1991 9.03	1992 6.18	1992 8.99	1992 9.59	1991 15.6	1992 10.8	1992 14.1
(WY)	1992	1991	1992	1990	1990	1992	1990	1990	1991	1992	1991	1990
SUMMARY	Y STATIS	Tic s	FOR	1991 CALE	NDAR YEAR	1	FOR 1992 W	ATER YEAR		WATER Y	RARS 1990	- 1992
ANNUAL				5768.1			8776.2					
ANNUAL		M		15.8			24.0			21.0		1002
	T ANNUAL ANNUAL I									24.0 18.1		1992 1991
	T DAILY			277	Jul 16		605	Jan 5			_	5 1992
LOWEST	DAILY M	Ban		4.4	Aug 8 Aug 8		5.1	Jan 5 Apr 29 Apr 24 Jan 5 Jan 5 Apr 29		4.1	May	22 1000
		AY MINIMU		4.4	Aug 8		5.5	Apr 24		35.00	Aug Jan	8 1991
		PBAK FLOW PBAK STAGI					3590 14.3	Jan 5		3590 14.7	Jan 17 Jan	5 1992
		LOW FLOW					5.1	Apr 29		3.9	May	22 1990
ANNUAL	RUNOFF	(AC-FT)		11440			17410			15240	_	
	RUNOFF			2.23 30.09	1		3.3			2.9 40.0		
	KUNOFF CENT EXC	(INCHES) Reds		30.09 21	•		45.7 37	4		31	•	
	CENT BXC			9.1			13			10		
90 PER	CENT BXC	rrds		5.7			7.3			5.7	'	

50053025 RIO TURABO ABOVE BORINQUEN, PR--Continued

WATER-QUALITY RECORDS

PERIOD OF RECORDS .-- Water years 1990 to current year.

INSTRUMENTATION. -- DH-48 and automatic sediment sampler.

PERIOD OF DAILY RECORD. --

SUSPENDED-SEDIMENT DISCHARGE: January 1990 to September 1992

EXTREMES FOR PERIOD OF DAILY RECORD. --

SEDIMENT CONCENTRATION: Maximum daily mean, 955 mg/L Jan. 05, 1992; Minimum daily mean, 1 mg/L Several days.

SEDIMENT LOADS: Maximum daily mean, 4,920 tons (4,460 tonnes) Jan. 05, 1992; Minimum daily mean, 0.01 ton (0.01 tonne) Several days.

EXTREMES FOR WATER YEARS 1990-92.--

Water Year	Suspended-sediment maximum	concentration (mg/L) minimum	Suspended-sediment discharge maximum	e (tons per day) minimum
1990	469 (May, 10)	3 (Several days)	220 (Jun. 14)	.04 (Several days)
1991	294 (Oct. 21)	1 (Several days)	598 (Sep. 17)	.01 (Several days)
1992	955 (Jan. 05)	1 (Several days)	4,920 (Jan. 05)	.02 (Several days)

DAY	MRAN DISCHARGE (CFS)	MEAN CONCEN- TRATION (MG/L)	SEDIMENT DISCHARGE (TONS/DAY)	MEAN DISCHARGE (CFS)	MEAN CONCEN- TRATION (MG/L)	SEDIMENT DISCHARGE (TONS/DAY)	MEAN DISCHARGE (CFS)	MEAN CONCEN- TRATION (MG/L)	SEDIMENT DISCHARGE (TONS/DAY)
	,,	,	(,			,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,	,,		
		JANUARY		,	PBBRUARY			MARCH	
1	e7.6			6.9	6	.12	8.2	7	.16
2	e7.4			7.7	6	.12	7.6	6	. 14
3	e6.4			6.8	6	.10	6.8	6	.11
4	e6.0			6.3	5	.09	6.7	6	.10
5	e 6.2			6.2	5	.09	6.5	6	.10
6	e6.4			6.1	5	.09	6.3	6	.10
7	e 6.6			6.3	6	.11	6.2	6	.10
8	e 6.2			8.3	7	.16	6.2	6	.10
9	e 6.4			9.4	9	.22	8.4	7	. 15
10	e7.4			8.3	7	.18	8.3	8	. 19
11	e6.8			6.8	6	.11	10	10	.32
12	e6.2			6.4	6	.10	22	21	1.5
13	e6.0			6.0	6	.10	34	30	3.6
14	e5.8			11	7	.21	80	77	3 2
15	e5.6			7.7	7	.16	15	13	. 55
16	e5.6			6.9	6	.12	16	15	. 80
17	e5.4			6.7	6	.10	12	11	. 37
18	e6.0			7.6	6	. 12	8.8	7	. 17
19	6.8	6	. 10	6.7	6	.10	7.4	6	.13
20	14	13	.79	7.9	7	.16	6.9	6	. 12
21	7.4	7	. 15	12	12	.42	6.7	6	.11
22	6.1	5	.09	11	10	.31	6.3	6	.10
23	5.9	5	.09	12	11	.51	6.3	5	.08
24	6.6	6	. 10	35	32	5.2	6.2	5	.08
25	7.5	7	. 15	10	9	.26	6.1	5	. 08
26	26	25	2.5	8.5	7	.18	6.1	5	.08
27	12	14	. 47	7.7	7	.15	6.0	5	.08
28	13	11	.36	7.8	7	.15	6.2	5	.08
29	9.0	8	.23				6.0	5	.08
30	7.8	6	. 14				6.5	5	.08
31	7.4	6	.12				6.1	5	.08
TOTAL	243.5			250.0		9.74	351.8		41.74

e Estimated

50053025 RIO TURABO ABOVE BORINQUEN, PR--Continued

	Mean				MBAN		KEAN		
DAY	MEAN DISCHARGE (CFS)	CONCEN- TRATION (MG/L)	SEDIMENT DISCHARGE (TONS/DAY)	MRAN Discharge (CFS)	CONCEN- TRATION (MG/L)	SEDIMENT DISCHARGE (TONS/DAY)	MEAN DISCHARGE (CFS)	CONCEN- TRATION (MG/L)	SEDIMENT DISCHARGE (TONS/DAY)
		APRIL			MAY			JUNE	
1	5.6	5	.08	5.4	5	.06	4.9	5	.06
2	5.4	5	.08	5.3	5	.06	5.4	5	.08
3	5.3	5	. 07	5.2	4	.06	4.9	5	.06
4	5.2	5	.06	5.4	4	.06	5.8	6	.10
5	5.1	5	.06	5. 5	4	.06	6.2	10	.16
6	5.1	5	.06	5.3	5	.06	6.3	13	.21
7	4.9	5	.06	5.2	5	.07	8.0	13	. 27
8	5.0	5	.06	5.3	6	.08	6.0	11	.18
9	4.9	5	.06	81	84	126	11	8	.25
10	5.1	5	.06	39	469	35	6.9	7	.14
11	4.9	4	.06	13	25	.96	6.6	7	. 12
12	5.1	3	. 05	7.3	17	.34	6.6	7	. 12
13	8.9	3	.09	5.9	13	.20	6.3	7	. 12
14	6.4	4	. 07	8.9	7	.18	162	161	220
15	5.5	4	.06	6.2	4	.08	92	91	41
16	5.2	4	.06	5.4	4	.06	17	16	.81
17	5.1	4	.06	5.2	4	.06	11	11	. 31
18	5.1	4	. 06	5.0	4	.06	8.3	10	. 22
19	7.0	4	.08	4.9	4	.05	7.8	8	.18
20	6.6	4	. 07	4.8	4	.04	10	8	.21
21	5.3	4	.06	4.7	4	.04	7.9	7	.15
22	5.2	4	. 06	4.4	4	.04	6.8	7	.1?
23	5.3	4	. 05	4.1	4	.04	7.1	7	. 13
24	4.9	4	. 05	4.1	4	.04	10	7	. 18
25	11	11	. 65	4.1	4	.04	99	100	56
26	16	16	1.0	4.9	4	.06	37	33	4.3
27	8.9	10	.28	4.9	4	.06	14	13	.50
28	6.3	6	.11	4.6	4	.04	10	10	.28
29	5.6	6	.08	4.6	4	.04	8.3	7	. 17
30	5.4	5	. 07	4.4	4	.04	8.1	7	. 15
31				4.6	4	.04			
TOTAL	185.3		3.72	278.6		164.02	601.2		326.59

50053025 RIO TURABO ABOVE BORINQUEN, PR--Continued

	Mean				MEAN		MEAN		
	MEAN	CONCEN-	SEDIMENT	mban	CONCEN-	SEDIMENT	MRAN	CONCEN-	SEDIMENT
	DISCHARGE	TRATION	DISCHARGE	DISCHARGE	TRATION	DISCHARGE	DISCHARGE	TRATION	DISCHARGE
DAY	(CFS)	(MG/L)	(TONS/DAY)	(CFS)	(MG/L)	(TONS/DAY)	(CFS)	(MG/L)	(TONS/DAY)
		JULY			AUGUST		SI	EPTEMBER	
	15	15	.79				14	12	.72
1 2				6.9	•	.08			
	9.8 8.7	9 7	. 25	8.2	4	.09	11	11 8	. 35
3			. 18	7.5	3	.08	9.8		.21
5	14 9.1	13 8	.70 .20	8.7	3	.08	13 9.0	12 8	.53 .20
3	3.1	•	.20	11	3	.09	9.0	•	. 20
6	15	15	.79	7.7	3	.07	8.4	7	. 18
7	12	11	.36	- 11	9	.42	11	9	.27
8	9.9	9	.25	30	28	3.2	9.8	10	.27
9	8.6	8	.20	1.3	11	.39	8.8	10	.23
10	8.9	7	. 18	178	176	184	8.2	8	.18
11	7.9	7	. 15	30	27	2.8	7.9	8	. 17
12	8.1	7	. 14	15	10	.40	8.4	8	.19
13	8.3	. 8	.17	13	7	.26	9.0	ž	. 19
14	9.2	8	.21	11	7	.21	9.8	8	.22
15	20	19	2.1	9.7	7	.19	9.2	13	.32
					•	*			
16	12	27	. 89	8.7	8	.20	13	14	.50
17	20	31	1.9	8.1	10	.21	11	10	.28
18	24	23	4.3	8.2	10	.22	23	24	2.8
19	50	46	11	9.0	10	. 23	12	6	. 25
20	15	10	.41	8.1	10	.22	9.1	6	. 15
21	11	4	. 13	14	16	1.2	8.9	6	. 13
22	11	4	. 11	18	18	1.5	8.7	6	. 13
23	12	4	. 13	12	11	.41	10	6	. 17
24	13	6	.22	11	9	.28	9.8	7	. 19
25	101	115	76	9.2	12	.31	26	23	5.4
26	92	91	79	8.4	8	.19	14	14	.79
27	19	14	. 83	7.4	6	.12	9.7	12	.34
28	12	6	.21	96	96	107	9.1	12	.31
29	9.4	5	. 13	67	73	37	8.4	12	. 28
30	8.1	5	.11	19	18	1.1	104	107	142
31	7.2	5	. 09	12	11	.33			
TOTAL	581.2		182.13	676.8		342.88	424.0		157.95

50053025 RIO TURABO ABOVE BORINQUEN, PR--Continued

SEDIMENT DISCHARGE, SUSPENDED (TONS/DAY), WATER YEAR OCTOBER 1990 TO SEPTEMBER 1991

245

	MRAN				MEAN		Mean		
DAY	MEAN DISCHARGE (CFS)	CONCEN- TRATION (MG/L)	SEDIMENT DISCHARGE (TONS/DAY)	MEAN Discharge (CPS)	CONCEN- TRATION (MG/L)	SEDIMENT DISCHARGE (TONS/DAY)	MEAN DISCHARGE (CFS)	CONCEN- TRATION (MG/L)	SEDIMENT DISCHARGE (TONS/DAY)
		OCTOBER		1	NOVEMBER		1	December	
1	13	21	.74	18	8	.41	17	10	.51
2	8.0	13	.28	17	وَ	.42	16	10	. 42
3	8.4	14	.32	16	10	.44	36	31	5.6
4	7.7	13	. 27	63	58	43	22	11	. 63
5	6.5	11	.20	55	54	27	16	7	. 32
6	6.1	10	. 16	26	22	1.7	15	5	. 23
7	6.4	10	. 18	21	12	.66	14	5	. 19
8	7.4	10	.20	19	11	.54	13	5	. 18
9	6.4	25	. 43	17	9	.41	13	5	. 18
10	8.3	30	. 68	16	7	.29	13	5	. 18
11	7.4	30	. 60	15	6	.24	13	3	. 10
12	6.3	30	. 52	15	6	.24	13	3	. 12
13	22	30	1.8	15	5	.20	12	4	. 15
14	30	29	2.3	14	5	.18	87	85	34
15	25	23	1.6	14	5	.18	35	33	7.3
16	148	138	55	14	5	.18	18	16	. 85
17	e45	40	e4.9	14	5	.18	15	10	.39
18	e60	53	e8.6	13	5	.20	14	10	. 37
19	e70	62	e12	13	6	.24	13	10	.36
20	e 50	44	5.9	13	7	.25	12	9	.31
21	e300	294	e238	14	8	.34	12	7	. 23
22	42	36	3.9	16	10	.42	12	5	. 17
23	33	31	2.8	13	8	.31	11	5	. 14
24	64	64	34	12	6	.19	11	7	.22
25	126	125	88	12	5	.17	11	12	.36
26	204	206	192	14	5	.18	11	15	.41
27	80	50	19	19	13	. 93	10	14	.38
28	37	12	1.2	15	12	.46	10	11	.29
29	26	12	. 86	15	12	.50	12	. 8	.26
30	22	12	.71	22	11	.62	15	11	.58
31	19	7	. 37				195	195	187
TOTAL	1494.9		677.52	560		81.08	717		242.43

e Estimated

50053025 RIO TURABO ABOVE BORINQUEN, PR--Continued

DAY	MEAN DISCHARGE (CFS)	MEAN CONCEN- TRATION (MG/L)	SEDIMENT DISCHARGE (TONS/DAY)	MEAN DISCHARGE (CFS)	MEAN CONCEN- TRATION (MG/L)	SEDIMENT DISCHARGE (TONS/DAY)	MRAN DISCHARGE (CFS)	MEAN CONCEN- TRATION (MG/L)	SEDIMENT DISCHARGE (TONS/DAY)
		JANUARY		1	BBRUARY			MARCH	
1	29	23	2.1	11	5	.16	12	8	.29
2	19	5	. 26	9.8	5	.13	11	9	.28
3	16	5	.20	10	5	. 13	11	9	.28
4	13	5	.18	10	5	.13	16	9	.38
5	45	42	25	19	17	1.9	13	10	.36
6	21	19	1.2	14	16	.62	18	10	.45
7	19	17	.77	12	13	.42	20	11	. 57
8	21	24	1.5	11	11	.31	15	12	.45
9	21	35	1.9	9.8	10	.26	12	13	.44
10	21	40	2.2	12	11	.34	11	13	.40
11	18	35	1.8	32	31	4.1	11	12	. 34
12	17	24	1.0	97	96	85	10	8	.24
13	15	12	.50	41	33	6.1	9.7	6	.16
14	15	7	.28	19	12	.59	10	4	. 12
15	17	7	.30	15	12	.47	9.1	3	. 09
16	15	7	. 27	13	12	.42	8.5	3	. 07
17	13	7	.23	12	12	.39	8.0	3	.06
18	12	7	.22	13	11	.38	9.1	3	.07
19	11	8	. 26	17	10	.43	10	3	.09
20	11	11	.30	18	7	.34	8.5	4	. 10
21	11	23	. 67	19	6	.30	7.6	5	. 12
22	11	25	.74	15	5	.23	12	7	.21
23	11	21	.61	14	5	.18	9.5	8	.21
24	9.9	16	.42	14	5	.18	7.4	8	. 17
25	9.1	11	. 26	13	5	.18	7.3	6	.11
26	9.0	6	. 15	12	5	.17	43	4	.46
27	8.9	5	.13	12	6	.18	9.7	7	. 17
28	9.6	4	.11	12	7	.24	8.1	14	.30
29	9.3	4	.10				7.6	15	.29
30	9.2	4	.11				7.4	13	. 25
31	12	5	. 15				6.9	12	. 22
TOTAL	479.0		43.92	506.6		104.28	359.4		7.75

50053025 RIO TURABO ABOVE BORINQUEN, PR--Continued

DAY	MEAN DISCHARGE (CFS)	MEAN CONCEN- TRATION (MG/L)	SEDIMENT DISCHARGE (TONS/DAY)	MEAN DISCHARGE (CFS)	MEAN CONCEN- TRATION (MG/L)	SEDIMENT DISCHARGE (TONS/DAY)	MEAN DISCHARGE (CFS)	MEAN CONCEN- TRATION (MG/L)	SEDIMENT DISCHARGE (TONS/DAY)
		APRIL			MAY			JUNE	
1	6.9	10	. 18	5.7	10	.15	6.2	1	.01
2	6.7	8	. 15	5.7	12	.18	6.5	1	. 02
3	6.6	8	. 14	5.7	12	.18	6.2	1	. 02
4	6.6	8	. 14	7.1	11	.20	6.0	1	. 02
5	6.6	8	. 14	6.3	7	.12	6.4	1	. 02
6	6.6	8	.14	6.1	3	.06	7.7	1	.01
7	6.5	10	. 17	5.7	1	.03	7.6	1	.01
8	10	11	.30	5.7	1	.02	6.9	1	. 02
9 10	7.5 10	9 7	. 18	6.3	1	.02	6.7	1	. 02
10	10	7	. 18	6.1	1	.01	6.3	1	. 02
11	7.6	7	. 15	21	18	5.6	8.3	2	. 05
12	7.9	7	. 16	11	5	.17	19	13	1.1
13	7.2	9	. 17	6.1	1	.03	8.3	4	.09
14	6.9	10	. 18	5.8	1	.02	7.3	4	.10
15	e8.4	12	e.28	6.0	1	.02	6.7	5	.10
16	8.2	18	.39	5.8	1	.02	6.1	4	.08
17	6.9	17	.33	5.5	1	.02	6.2	3	. 05
18	7.1	13	.23	6.9	1	.01	6.0	1	.03
19	6.4	8	. 15	6.3	1	.01	5.8	1	. 02
20	6.3	8	. 14	6.0	1	.02	5.7	1	.02
21	6.3	8	. 14	6.5	1	.01	6.1	1	.02
22	6.3	8	. 14	6.8	1	.02	6.1	1	. 02
23	6.2	8	. 13	5.9	1	.02	5.8	1	.02
24	6.1		. 14	5.4	1	.02	5.9	1	. 02
25	5.9	10	. 17	130	136	137	5.7	1	. 02
26	6.3	10	. 18	11	11	.36	5.7	1	. 02
27	6.2	7	. 12	7.8	9	.19	5.8	1	. 03
28	5.7	6	.10	7.0	10	.18	5.5	2	. 03
29	5.7	6	. 10	6.6	8	.14	8.3	7	.20
30 31	5.7	6	. 10	6.6	4	.07	87	82	92
31				6.4	1	.02			
TOTAL	207.3		5.22	340.8		144.92	287.8		94.19

e Estimated

50053025 RIO TURABO ABOVE BORINQUEN, PR--Continued

DAY	MEAN DISCHARGE (CFS)	MEAN CONCEN- TRATION (MG/L)	SEDIMENT DISCHARGE (TONS/DAY)	MEAN DISCHARGE (CFS)	MEAN CONCEN- TRATION (MG/L)	SEDIMENT DI SCHARGE (TONS/DAY)	MEAN Discharge (CFS)	MRAN CONCEN- TRATION (MG/L)	SEDIMENT DISCHARGE (TONS/DAY)
		JULY			augus t		Si	ep tember	
1	102	153	77	5.1	2	.03	6.2	12	.20
2	14	66	2.8	5.1	1	.02	7.4	12	.26
3	9.4	19	.51	5.1	ĩ	.02	5.7	12	. 18
4	8.5	14	.33	4.8	1	.02	5.4	13	. 18
5	7.6	8	. 16	4.9	ī	.02	5.4	13	. 18
6	7.4	5	.10	4.9	1	.02	5.7	14	.20
7	6.8	3	. 07	4.8	2	.02	5.6	14	.21
8	6.3	2	. 05	4.4	2	.03	5.3	15	.21
9	6.4	1	.03	4.4	2	.03	11	15	. 45
10	6.3	1	.02	4.4	2	.03	7.3	17	.34
11	6.2	1	.02	4.4	1	.02	7.5	17	.35
12	5.7	ī	.02	4.4	ī	.02	6.3	15	.28
13	5.6	ī	.02	4.4	î	.02	6.0	13	.22
14	5.1	ī	.02	4.4	i	.02	6.0	8	. 13
15	68	66	71	4.7	2	.03	5.7	7	.10
16	277	228	374	4.7	4	.05	5.7	7	.10
17	19	5	. 32	7.1	5	.10	240	250	598
18	10	2	.06	7.6	7	.13	20	20	1.3
19	8.6	2	.04	5.7	10	.13	18	17	1.0
20	7.7	2	. 04	4.4	13	. 15	12	12	.43
21	6.3	1	. 03	5.3	14	.20	11	9	.27
22	6.2	1	.01	62	63	39	52	50	19
23	6.0	1	.01	13	12	. 57	37	28	2.9
24	8.0	1	.03	7.3	6	.13	17	15	.79
25	6.1	1	. 02	6.1	5	.09	12	8	.26
26	5.7	1	.02	5.5	5	.07	10	8	.22
27	5.7	1	.02	91	87	70	9.2	8	. 22
28	5.4	1	.02	21	21	1.6	32	29	5.1
29	5.1	1	.02	9.2	10	.25	69	67	23
30	8.0	1	.02	7.4	11	.21	22	21	1.3
31	6.0	3	.06	6.5	11	.21			
TOTAL	656.1		526.87	334.0		113.24	663.4		657.38
YBAR	6606.3		2698.80						

50053025 RIO TURABO ABOVE BORINQUEN, PR--Continued

DAY	MEAN DISCHARGE (CFS)	MEAN CONCEN- TRATION (MG/L)	SEDIMENT DISCHARGE (TONS/DAY)	MRAN DISCHARGE (CFS)	MEAN CONCEN- TRATION (MG/L)	SEDIMENT DISCHARGE (TONS/DAY)	MEAN DISCHARGE (CFS)	MEAN CONCEN- TRATION (MG/L)	SEDIMENT DISCHARGE (TONS/DAY)
		OCTOBER		1	NOVEMBER		1	DECEMBER	
1	16	15	. 65	8.2	12	.28	18	15	.77
2	37	112	16	8.1	12	.27	17	11	. 47
3	17	15	. 68	8.4	10	.22	21	10	.55
4	15	9	.38	8.4	9	.21	23	9	.60
5	13	4	.12	8.6	10	.23	18	8	.38
6	11	12	. 36	8.2	10	.24	16	7	.31
7	11	24	. 67	133	206	160	15	9	.36
8	10	30	.80	227	334	416	15	9	.35
9	13	21	.74	111	143	65	14	6	.23
10	11	11	.31	52	25	5.8	14	4	. 17
11	9.7	10	. 25	25	5	.39	13	5	.20
12	14	20	1.1	e21	5	e.26	14	7	.28
13	9.7	6	. 17	18	5	.23	13	8	.30
14	9.4	3	. 07	16	5	.22	13	10	.35
15	8.8	2	. 04	14	5	.20	e13	10	e.38
16	8.9	2	. 05	21	47	5.2	15	10	.43
17	9.5	2	.04	17	16	.74	13	10	. 37
18	9.2	1	.03	15	12	.45	13	10	.34
19	8.5	1	. 02	14	7	.28	13	10	.34
20	8.0	1	. 02	13	5	.18	24	24	3.0
21	8.1	2	.04	20	14	2.1	18	15	.88
22	8.4	3	.06	37	36	5.5	14	5	.20
23	8.3	4	.08	20	10	.54	13	2	.06
24	7.9	7	.16	127	174	134	13	3	. 12
25	8.0	11	. 23	32	40	3.6	13	4	. 15
26	7.9	12	. 24	22	24	1.5	12	3	.10
27	7.3	12	.23	47	63	8.4	12	5	. 17
28	7.3	11	. 22	38	46	4.8	12	10	.30
29	7.3	10	. 19	27	35	2.5	12	11	.34
30	7.3	10	. 19	21	25	1.5	13	12	.39
31	7.3	11	.21				14	12	. 47
TOTAL	334.8		24.35	1137.9		820.84	461		13.36

e Estimated

50053025 RIO TURABO ABOVE BORINQUEN, PR--Continued

DAY	MRAN DISCHARGE (CFS)	MEAN CONCEN- TRATION (MG/L)	SEDIMENT DISCHARGE (TONS/DAY)	MEAN DISCHARGE (CFS)	MEAN CONCEN- TRATION (MG/L)	SEDIMENT DISCHARGE (TONS/DAY)	MEAN DISCHARGE (CFS)	MEAN CONCEN- TRATION (MG/L)	SEDIMENT DISCHARGE (TONS/DAY)
		JANUARY		1	BRUARY			MARCH	
1	13	13	.47	14	7	.30	10	4	. 12
2 3	12	13	.43	14	10	.40	11	4	.11
	12	12	.40	14	11	.41	10	2	.08
4	12	13	.39	15	11	.42	10	3	.11
5	605	955	4920	13	10	.38	10	5	. 15
6	328	854	1010	29	30	3.4	11	7	.20
7	31	34	4.0	23	21	1.5	10	7	.21
8	13	14	.50	18	11	.52	10	5	. 16
9	8.8	13	. 33	16	10	.43	9.0	4	.11
10	11	16	.49	21	5	.31	9.0	7	. 17
11	8.6	18	.43	17	4	.19	8.6	12	.26
12	9.7	20	. 53	15	4	.17	8.4	16	. 37
13	12	21	.72	13	4	.15	8.6	20	. 45
14	14	23	. 84	14	3	.13	9.3	21	. 55
15	18	21	.99	15	5	.21	9.9	24	. 60
16	43	56	20	12	6	.23	8.6	23	. 52
17	47	38	10	12	7	.24	19	28	1.8
18	27	10	.71	11	8	.25	11	26	.79
19	24	16	1.0	12	7	.22	9.0	21	. 51
20	22	20	1.2	11	5	.16	8.6	20	.46
21	21	18	.99	11	5	.14	8.6	15	. 34
22	19	14	.71	12	5	.17	8.5	7	. 17
23	19	6	.34	12	5	.18	7.5	6	. 13
24	19	5	.26	12	6	.22	7.5	9	. 18
25	20	5	. 24	12	7	.23	7.3	11	. 20
26	19	4	.20	16	8	.39	6.8	13	. 24
27	17	4	. 18	12	8	.28	6.8	16	.28
28	20	17	1.1	11	7	.22	6.6	15	.26
29	17	7	.33	11	6	.17	6.2	14	. 23
30	16	3	. 12				6.2	12	.19
31	15	4	.16				7.0	10	.18
TOTAL	1473.1		5978.06	418		12.02	280.0		10.13

50053025 RIO TURABO ABOVE BORINQUEN, PR--Continued

DAY	MRAN DISCHARGE (CFS)	MEAN CONCEN- TRATION (MG/L)	SEDIMENT DISCHARGE (TONS/DAY)	MEAN DISCHARGE (CFS)	MRAN CONCEN- TRATION (MG/L)	SEDIMENT DISCHARGE (TONS/DAY)	MEAN DISCHARGE (CFS)	MEAN CONCEN- TRATION (MG/L)	SEDIMENT DISCHARGE (TONS/DAY)
		APRIL			MAY			JUNE	
1	7.3	10	.22	15	31	5.4	65	93	70
2	6.3	10	.16	37	93	16	29	124	9.8
3	5.9	10	. 15	8.3	11	.27	24	26	2.2
4	5.7	9	. 14	6.2	6	.11	68	95	46
5	5.5	10	.14	5.9	6	.09	26	24	1.8
6	5.8	10	. 15	11	9	.28	22	17	1.1
7	9.8	11	.27	10	13	.35	29	33	5.1
8	8.0	11	.26	7.2	18	.35	40	47	6.8
9	6.9	13	.24	6.2	26	.43	27	27	2.1
10	6.7	13	.23	6.2	30	.49	114	166	74
11	8.2	15	.36	7.0	27	.51	e125	197	e99
12	34	38	4.6	7.7	21	.45	149	294	136
13	13	26	. 97	7.9	18	.40	e101	144	e 61
14	15	22	.86	6.3	17	.27	e69	89	e19
15	10	13	.39	9.0	12	.29	44	50	6.3
16	7.5	8	.17	88	166	177	36	36	3.7
17	6.8	10	. 17	16	36	1.7	82	109	66
18	6.9	16	.29	10	39	. 98	37	31	3.2
19	24	43	11	8.3	40	.89	26	24	1.6
20	18	24	1.8	24	53	7.6	24	22	1.4
21	7.7	13	. 26	11	32	1.1	137	245	346
22	7.0	8	. 15	_8.6	22	.50	37	23	2.7
23	6.3	5	. 09	150	247	417	28	10	.74
24	5.9	4	. 07	151	211	144	23	8	.50
25	5.7	4	.06	49	5 5	8.8	20	7	.41
26	5.4	4	.07	134	202	173	19	7	.37
27	5.4	7	.11	40	130	15	18	7	.34
28	5.4	10	. 14	19	23	1.4	16	7	.31
29	5.1	13	. 17	14	10	.36	15	7	.28
30	5.6	18	.26	40	49	18	16	7	. 29
31				15	14	.61			
TOTAL	270.8		23.95	928.8		993.63	1466		968.04

e Estimated

50053025 RIO TURABO ABOVE BORINQUEN, PR--Continued

DAY	MRAN DISCHARGE (CFS)	MBAN CONCEN- TRATION (MG/L)	SEDIMENT DISCHARGE (TONS/DAY)	MEAN DISCHARGE (CFS)	MRAN CONCEN- TRATION (MG/L)	SEDIMENT DISCHARGE (TONS/DAY)	MEAN DISCHARGE (CFS)	MEAN CONCEN- TRATION (MG/L)	SEDIMENT DISCHARGE (TONS/DAY)
		JULY			AUGUST		S	ep tember	
1	14	6	.23	11	10	.30	9.9	8	.22
2	14	5	.20	13	9	.33	10	9	. 25
3	14	5	. 18	14	18	.73	17	11	. 52
4	13	5	. 17	14	14	.56	11	13	.38
5	15	6	.24	183	317	613	9.3	15	.39
6	12	12	.37	62	80	22	11	16	.48
7	11	17	.51	28	16	1.2	11	13	. 42
8	16	21	. 95	22	11	.66	11	12	.98
9	14	19	.71	18	10	.49	43	51	13
10	12	18	.56	22	8	.44	12	11	.34
11	20	40	2.8	20	7	.43	9.6	9	.23
12	13	43	1.6	21	9	.52	8.7	7	.18
13	11	35	1.1	17	8	.39	8.2	8	. 18
14	11	28	. 85	24	22	2.1	7.9	10	.20
15	11	21	. 65	19	25	1.3	7.5	11	.21
16	12	13	.43	16	24	1.0	34	43	15
17	34	43	12	15	19	.80	27	31	3.4
18	12	10	. 35	12	13	.40	17	15	. 67
19	17	22	1.2	12	8	.25	87	391	164
20	19	45	2.3	12	5	.17	205	326	815
21	13	35	1.2	11	4	.12	147	191	221
22	34	47	11	10	3	.09	3 3	6	. 60
23	16	12	.48	10	3	.08	21	5	.28
24	12	10	.33	11	3	.09	17	3	.16
25	39	47	11	10	3	.08	14	4	. 15
26	16	10	.40	16	12	.94	13	5	. 18
27	13	10	. 35	13	10	.35	11	8	. 27
28	12	10	. 29	11	7	.20	10	10	.27
29	11	10	.31	11	6	.18	9.5	10	.25
30	12	12	. 37	9.8	8	.20	9.4	10	.26
31	11	12	.36	12	9	.29			
IATOT	484		53.49	679.8		649.69	842.0		1239.47
YEAR	8776.2		10787.03						

50053025 RIO TURABO ABOVE BORINQUEN, PR--Continued

WATER QUALITY DATA, WATER YEARS DECEMBER 1990 TO SEPTEMBER 1992

PARTICLE-SIZE DISTRIBUTION OF SUSPENDED SEDIMENT

DATE	TIME	DIS- CHARGE, INST. CUBIC FEET PER SECOND	SEDI- MENT, SUS- PENDED (MG/L)	SEDI- MENT, DIS- CHARGE, SUS- PENDED (T/DAY)	SED. SUSP. FALL DIAM. PERCENT FINER THAN .002 MM	SED. SUSP. FALL DIAM. PERCENT FINER THAN .004 MM	SED. SUSP. FALL DIAM. PERCENT FINER THAN .008 MM
DEC 1990							
14 Jan 1992	1330	95	1930	495	55	65	69
05	1656	1350	13600	49600	29	44	57
DATE	SED. SUSP. FALL DIAM. PERCENT FINER THAN .016 MM	SED. SUSP. FAIL DIAM. PERCENT FINER THAN	SED. SUSP. SIEVE DIAM. PERCENT FINER THAN .062 MM	SED. SUSP. SIEVE DIAM. PERCENT FINER THAN .125 MM	SED. SUSP. SIEVE DIAM. PERCENT FINER THAN .250 MM	SED. SUSP. SIEVE DIAM. PERCENT FINER THAN .500 MM	SED. SUSP. SIEVE DIAM. PERCENT FINER THAN 1.00 MM
DEC 1990							
14 JAN 1992	78	84	98	99	99.4	99.8	100
05	75	78	83	90	94	97	99

50053025 RIO TURABO ABOVE BORINQUEN, PR--Continued

WATER QUALITY DATA, WATER YEAR OCTOBER 1991 TO SEPTEMBER 1992

SILT AND CLAY PERCENT OF SUSPENDED SEDIMENT

DATE	Time	STREAM- FLOW, INSTAN- TANEOUS (CFS)	SEDI- MENT, SUS- PENDED (MG/L)	SEDI- MENT, DIS- CHARGE, SUS- PENDED (T/DAY)	SED. SUSP. SIEVE DIAM. PERCENT FINER THAN .062 MM
OCT 1991					
02	1015	49	193	25	98
JAN 1992					
05	1711	2340	4830	30600	82
16	1648	29	168	13	98
MAY					
14	1520	14	540	20	96
JUN					
03	1445	49	395	52	99
AUG					
04	1200	12	4080	132	100
SEP					
19	2056	96	1540	399	98

rio grande de loiza basin 255

50055000 RIO GRANDE DE LOIZA AT CAGUAS, PR

LOCATION.--Lat 18°14'33", long 66°00'34", Hydrologic Unit 21010005, on right bank 250 ft (76 m) upstream from bridge on Highway 189, 1.2 mi (1.9 km) downstream from Río Turabo, and 1.8 mi (2.9 km) east of Plaza de Caguas.

DRAINAGE AREA. -- 89.8 mi* (232.6 km²).

WATER-DISCHARGE RECORDS

PERIOD OF RECORD.--1959 (low-flow measurement only), February to November 1959 (monthly measurements only), December 1959 to current year.

GAGE.--Water-stage recorder. Datum of gage is 143.28 ft (43.672 m) above mean sea level.

REMARKS. -- Records good. Gage-height and precipitation satellite telemetry at station.

	DI	SCHARGE,	CUBIC FRET		OND, WATER DAILY MEAN		TOBER 19	91 TO SEPTE	MBER 199	2		
DAY	OCT	NOV	DEC	Jan	FRB	MAR	APR	MAY	JUN	JUL	AUG	SEP
1	304	68	157	106	91	56	52	42	521	89	66	87
2	466	80	152	78	87	53	53	174	479	81	66	72
3	301	72	154	72	89	57	38	60	17 7	78	76	104
4	195	63	216	68	96	55	36	41	922	77	63	93
5	174	101	151	7930	92	60	36	35	265	146	1610	80
6	166	118	126	4920	108	62	33	64	196	84	644	89
7	113	1130	115	609	143	58	42	117	184	74	233	89
8	99	4110	109	311	100	109	45	62	207	84	159	73
9	98	1640	113	246	86	59	39	47	221	98	123	280
10	102	696	105	282	121	51	37	41	436	77	243	103
11	88	292	96	198	97	48	39	40	442	141	150	78
12	126	219	9 9	171	82	45	72	64	1070	108	171	70
13	107	194	95	164	76	47	108	49	689	76	122	63
14	86	160	94	144	76	47	60	39	522	69	130	61
15	87	136	83	135	90	65	81	71	264	76	161	60
16	83	145	94	149	84	48	49	1090	263	82	111	99
17	100	159	93	219	71	50	42	214	400	222	104	284
18	82	119	78	132	68	82	41	106	259	100	99	165
19	79	105	75	119	66	56	59	74	169	93	91	746
20	66	98	90	115	65	60	145	146	147	146	91	2870
21	63	112	174	110	62	55	75	101	1020	106	88	1660
22	102	454	83	110	60	54	48	63	234	364	80	335
23	77	186	77	106	68	48	47	1400	179	118	81	207
24	65	641	73	110	69	44	38	2020	144	89	113	161
25	58	329	71	109	68	41	35	333	127	171	85	135
26	52	187	69	113	64	41	35	2740	116	105	73	121
27	51	423	68	101	70	40	32	399	113	82	89	113
28	49	313	68	100	64	39	30	202	110	75	77	103
29	181	272	74	103	58	49	31	144	97	66	85	102
30	241	191	68	93		40	35	249	93	62	73	102
31	104		96	91		38		146		66	95	
TOTAL	3965	12813	3216	17314	2371	1657	1513	10373	10066	3305	5452	8605
MBAN	128	427	104	559	81.8	53.5	50.4	335	336	107	176	287
MAX	466	4110	216	7930	143	109	145	2740	1070	364	1610	2870
MIN	49	63	68	68	58	38	30	35	93	62	63	60
AC-FT	7860	25410	6380	34340	4700	3290	3000	20570	19970	6560	10810	17070
CFSM	1.42	4.76	1.16	6.22	.91	. 60	.56	3.73	3.74	1.19	1.96	3.19
IN.	1.64	5.31	1.33	7.17	. 98	. 69	.63	4.30	4.17	1.37	2.26	3.56
STATIST	CICS OF M	ONTHLY M	EAN DATA FO	OR WATER	YEARS 1960	- 1992,	BY WATE	R YEAR (WY)				
MEAN	388	316	233	148	111	91.2	84.7	254	260	223	259	259
MAX	1910	1131	714	559	291	306	226	863	1283	660	949	764
(WY)	1971	1988	1988	1992	1984	1989	1985	1985	1979	1961	1979	1979
MIN	44.2	64.9	33.6	45.3	35.6	23.2	38.0	33.7	34.1	21.8	53.6	37.4
(WY)	1968	1968	1968	1968	1968	1968	1968	1974	1975	1974	1967	1967
						_						4000
SUMMARY	STATIST	TCB	FOR :	ISSI CYM	ENDAR YEAR	F	OR 1992	WATER YEAR		WATER YE	AKS 1960	- 1992
ANNUAL				48124			80650					
annual				132			220			220		
	'ANNUAL ANNUAL M									526 82.3		1979 1967
	DAILY M			4110	Nov B		7970	Jan 5		17900	Oct	9 1970
	DAILY ME			20			30			11		8 1968
	SEVEN-DA		DMI	22			34			11		B 1968
	ANEOUS P						43300			71500		6 1960
	ANEOUS P							32 Jan 5		31.17		6 1960
INSTANT	I SUOSNAT	OW FLOW					28	Apr 27			_	
ANNUAL	RUNOFF (AC-FT)		95450			160000	-		159100		
	RUNOFF (1.4			2.			2.45		
	RUNOFF (19.	94		33.	41		33.22		
	BNT BXCE			218			312			365		
	ENT EXCE			72			95			106		
90 PERC	ENT BXCE	RDS		29			48			40		

50055000 RIO GRANDE DE LOIZA AT CAGUAS, PR--Continued

WATER-QUALITY RECORDS

PERIOD OF RECORD. -- Water years 1959 to current year.

PERIOD OF DAILY RECORD . --

SUSPENDED-SEDIMENT DISCHARGE: October 1983 to September 1989.

INSTRUMENTATION .-- USD-49 and automatic sediment sampler.

EXTREMES FOR PERIOD OF DAILY RECORD.-SEDIMENT CONCENTRATION: Maximum daily mean, 14,500 mg/L Nov 27, 1987; Minimum daily mean, 8 mg/L

January 23, 1992.

SEDIMENT LOADS: Maximum daily mean, 227,000 tons (205,890 tonnes) Nov 27, 1987; Minimum daily mean, 1.3 tons (1.2) July 14, 1985.

EXTREMES FOR CURRENT YEAR.-SEDIMENT CONCENTRATION: Maximum daily mean, 2,790 mg/L January 05, 1992 ; minimum daily mean,

8 mg/L January 23, 1992.

SEDIMENT LOADS: Maximum daily mean, 199,000 tons (180,000 tonnes) January 05, 1992; minimum daily 1.9 ton (1.7 tonnes) several days.

MV.LRM-	CONTILI	DATA,	MATER	IKAK	OCTOBER	1331	10	SELICHORK	1774

DATE	TIME	DIS- CHARGE, INST. CUBIC FERT PER SECOND	SPE- CIFIC CON- DUCT- ANCE (US/CM)	PH WATER WHOLE FIELD (STAND- ARD UNITS)	TEMPER- ATURE WATER (DEG C)	TUR- BID- ITY (NTU)	OXYGEN, DIS- SOLVED (MG/L)	OXYGEN, DIS- SOLVED (PBR- CENT SATUR- ATION)	OXYGEN DEMAND, CHEM- ICAL (HIGH LEVEL) (MG/L)	COLI- FORM, FECAL, 0.45 UM-MF (COLS./ 100 ML)	STREP- TOCOCCI FECAL, (COLS. PER 100 ML)
OCT 1991											
18	1215	80	242	7.8	28.5	28	7.6	96	16	20000	440
DBC	_	_		_							
05	1445	145	219	7.6	24.0	170	7.8	97	19	20000	630
FEB_1992											
27	1240	71	262	7.3	26.5	45	7.7	93	14	5400	380
MAY											
18	1155	102	200	7.4	27.5	31	7.1	89	25	25000	3000
JUN											
11	0815	702	144	7.1	25.5	170	8.0	99	23	K4800	23000
AUG											
19	1125	84	228	7.4	29.5	7.8	7.3	90	<10	K1700	400

DATE	HARD- NESS TOTAL (MG/L AS CACO3)	CALCIUM DIS- SOLVED (MG/L AS CA)	MAGNE- SIUM, DIS- SOLVED (MG/L AS MG)	SODIUM, DIS- SOLVED (MG/L AS NA)	SODIUM AD- SORP- TION RATIO	POTAS- SIUM, DIS- SOLVED (MG/L AS K)	ALKA- LINITY WAT WH TOT FRT FIELD MG/L AS CACO3	SULFIDE TOTAL (MG/L AS 8)	SULFATE DIS- SOLVED (MG/L AS SO4)	CHLO- RIDR, DIS- SÖLVED (MG/L AS CL)
OCT 1991										
18	71	18	6.4	23	1	2.0	75	<0.5	9.6	19
DEC 05							66			
FBB 1992							66			
27							84			
МАҮ 18	56	15	4.5	15	0.9	2.5	90	<0.5	14	18
JUN	30	15	4.5	15	0.9	2.5	30	۷۰.5	14	10
11							40			
AUG 19	66	17	5.7	19	1	1.9	74		10	17
22111			2.,		•	2.3				
DATE	FLUO- RIDE, DIS- SOLVED (MG/L AS F)	SILICA, DIS- SOLVED (MG/L AS SIO2)	SOLIDS, SUM OF CONSTI- TUENTS, DIS- SOLVED (MG/L)	SOLIDS, DIS- SOLVED (TONS PER DAY)	RESIDUE TOTAL AT 105 DEG. C, SUS- PENDED (MG/L)	NITRO- GEN, NITRATE TOTAL (MG/L AS N)	NITRO- GEN, NITRITE TOTAL (MG/L AS N)	NITRO- GEN, NO2+NO3 TOTAL (MG/L AS N)	NITRO- GEN, AMMONIA TOTAL (MG/L ÀS N)	NITRO- GEN, ORGANIC TOTAL (MG/L AS N)
OCT 1991										
18	0.10	35	158	34.1	18	0.370	0.050	0.420	0.090	0.51
DEC 05					495	0.480	0.070	0.550	0.070	0.23
FRB 1992					475	0.460	0.070	0.550	0.070	0.23
27					51	0.350	0.050	0.400	0.110	0.19
MAY 18	0.10	22	122	33.5	12	0.550	0.030	0.580	0.140	0.46
JUN	0.10	44	144	33.3	12	v.550	V. V. V	0.500	0.140	V. 10
11					219	0.350	0.070	0.420	0.050	0.35
AUG 19	. <0.10	29	144	32.7	11	0.250	0.020	0.270	0.060	0.14

K = non-ideal count

50055000 RIO GRANDE DE LOIZA AT CAGUAS, PR--Continued WATER-QUALITY DATA, WATER YEAR OCTOBER 1991 TO SEPTEMBER 1992

DATE	NITRO- GEN, AM- MONIA + ORGANIC TOTAL (MG/L AS N)	NITRO- GEN, TOTAL (MG/L AS N)	NITRO- GEN, TOTAL (MG/L AS NO3)	PHOS- PHORUS TOTAL (MG/L AS P)	ARSENIC TOTAL (UG/L AS AS)	BARIUM, TOTAL RECOV- ERABLE (UG/L AS BA)	BORON, TOTAL RECOV- BRABLE (UG/L AS B)	CADMIUM TOTAL RECOV- ERABLE (UG/L AS CD)	CHRO- MIUM, TOTAL RECOV- ERABLE (UG/L AS CR)	COPPER, TOTAL RECOV- ERABLE (UG/L AS CU)
OCT 1991										
18 DEC	0.60	1.0	4.5	0.300	<1	<100	10	<1	<1	<10
05 FBB 1992	0.30	0.85	3.8	0.290						
27	0.30	0.70	3.1	0.210						
18	0.60	1.2	5.2	0.160	<1	<100	20	<1	<1	20
11	0.40	0.82	3.6	0.100						
19	0.20	0.47	2.1	0.150						
D ATE	IRON, TOTAL RECOV- ERABLE (UG/L AS FE)	LEAD, TOTAL RECOV- ERABLE (UG/L AS PB)	MANGA- NESE, TOTAL RECOV- ERABLE (UG/L AS MN)	MERCURY TOTAL RECOV- ERABLE (UG/L AS HG)	SELE- NIUM, TOTAL (UG/L AS SE)	SILVER, TOTAL RECOV- ERABLE (UG/L AS AG)	ZINC, TOTAL RECOV- BRABLE (UG/L AS ZN)	CYANIDE TOTAL (MG/L AS CN)	PHENOLS TOTAL (UG/L)	METHY- LENE BLUE ACTIVE SUB- STANCE (MG/L)
DATE	TOTAL RECOV- ERABLE (UG/L	TOTAL RECOV- BRABLE (UG/L	NESE, TOTAL RECOV- ERABLE (UG/L	TOTAL RECOV- ERABLE (UG/L	NIUM, TOTAL (UG/L	TOTAL RECOV- ERABLE (UG/L	TOTAL RECOV- BRABLE (UG/L	TOTAL (MG/L	TOTAL	Lene Blue Active Sub- Stance
OCT 1991 18	TOTAL RECOV- ERABLE (UG/L	TOTAL RECOV- BRABLE (UG/L	NESE, TOTAL RECOV- ERABLE (UG/L	TOTAL RECOV- ERABLE (UG/L	NIUM, TOTAL (UG/L	TOTAL RECOV- ERABLE (UG/L	TOTAL RECOV- BRABLE (UG/L	TOTAL (MG/L	TOTAL	Lene Blue Active Sub- Stance
OCT 1991 18 DEC	TOTAL RECOV- ERABLE (UG/L AS FE)	TOTAL RECOV- ERABLE (UG/L AS PB)	NESE, TOTAL RECOV- ERABLE (UG/L AS MN)	TOTAL RECOV- ERABLE (UG/L AS HG)	NIUM, TOTAL (UG/L AS SE)	TOTAL RECOV- ERABLE (UG/L AS AG)	TOTAL RECOV- BRABLE (UG/L AS ZN)	TOTAL (MG/L AS CN)	TOTAL (UG/L)	LENE BLUE ACTIVE SUB- STANCE (MG/L)
OCT 1991 18 DRC 05 FRB 1992	TOTAL RECOV- RRABLE (UG/L AS FE)	TOTAL RECOV- ERABLE (UG/L AS PB)	NESE, TOTAL RECOV- BRABLE (UG/L AS MN)	TOTAL RECOV- ERABLE (UG/L AS HG) 0.10	NIUM, TOTAL (UG/L AS SE)	TOTAL RECOV- ERABLE (UG/L AS AG)	TOTAL RECOV- BRABLE (UG/L AS ZN)	TOTAL (MG/L AS CN)	TOTAL (UG/L)	LENE BLUE ACTIVE SUB- STANCE (MG/L)
OCT 1991 18 DEC 05 FEB 1992 27	TOTAL RECOV- ERABLE (UG/L AS FE)	TOTAL RECOV- ERABLE (UG/L AS PB)	NESE, TOTAL RECOV- ERABLE (UG/L AS MN)	TOTAL RECOV- ERABLE (UG/L AS HG)	NIUM, TOTAL (UG/L AS SE)	TOTAL RECOV- ERABLE (UG/L AS AG)	TOTAL RECOV- BRABLE (UG/L AS ZN)	TOTAL (MG/L AS CN)	TOTAL (UG/L)	LENE BLUE ACTIVE SUB- STANCE (MG/L)
OCT 1991 18 DRC 05 FEB 1992 27 MAY 18	TOTAL RECOV- RRABLE (UG/L AS FE)	TOTAL RECOV- ERABLE (UG/L AS PB)	NESE, TOTAL RECOV- BRABLE (UG/L AS MN)	TOTAL RECOV- ERABLE (UG/L AS HG) 0.10	NIUM, TOTAL (UG/L AS SE)	TOTAL RECOV- ERABLE (UG/L AS AG)	TOTAL RECOV- BRABLE (UG/L AS ZN)	TOTAL (MG/L AS CN)	TOTAL (UG/L)	LENE BLUE ACTIVE SUB- STANCE (MG/L)
OCT 1991 18 DRC 05 FEB 1992 27	TOTAL RECOV- BRABLE (UG/L AS FE)	TOTAL RECOV- BRABLE (UG/L AS PB)	NESE, TOTAL RECOV- BRABLE (UG/L AS MN)	TOTAL RECOV- ERABLE (UG/L AS HG)	NIUM, TOTAL (UG/L AS SE) <1	TOTAL RECOV- BRABLE (UG/L AS AG)	TOTAL RECOV- BRABLE (UG/L AS ZN)	TOTAL (MG/L AS CN)	TOTAL (UG/L)	LENE BLUE ACTIVE SUB- STANCE (MG/L) 0.01

50055000 RIO GRANDE DE LOIZA AT CAGUAS, PR--Continued

DAY	MEAN DISCHARGE (CFS)	MEAN CONCEN- TRATION (MG/L)	SEDIMENT DISCHARGE (TONS/DAY)	MRAN DISCHARGE (CPS)	MEAN CONCEN- TRATION (MG/L)	SEDIMENT DISCHARGE (TONS/DAY)	MEAN DISCHARGE (CFS)	MEAN CONCEN- TRATION (MG/L)	SEDIMENT DISCHARGE (TONS/DAY)
		OCTOBER		1	NOVEMBER		1	December	
1	304	255	236	68	122	23	157	56	24
2	466	390	596	80	82	19	152	25	10
3	301	123	111	72	62	14	154	50	25
4	195	35	19	63	55	9.8	216	208	122
5	174	71	36	101	97	29	151	244	100
6	166	133	62	118	99	45	126	179	63
7	113	94	29	1130	1390	6250	115	104	33
8	99	82	22	4110	2080	40000	109	64	19
9	98	76	20	1640	1250	9130	113	45	14
10	102	70	19	696	591	1510	105	40	11
11	88	64	16	292	222	179	96	40	10
12	126	99	40	219	131	79	99	60	16
13	107	84	25	194	84	45	95	68	18
14	86	49	12	160	46	21	94	48	11
15	87	51	12	136	28	10	83	36	8.3
16	83	75	17	145	45	22	94	29	7.1
17	100	84	23	159	107	50	93	23	5.8
18	82	64	14	119	38	12	78	21	4.5
19	79	69	15	105	23	6.6	75	20	4.1
20	66	77	13	98	21	5.4	90	60	17
21	63	75	13	112	67	25	174	145	80
22	102	101	44	454	385	577	83	44	10
23	77	183	38	186	159	82	77	19	4.0
24	65	171	29	641	573	1490	73	17	3.3
25	58	150	23	329	211	219	71	14	2.6
26	52	130	18	187	135	70	69	11	2.1
27	51	103	14	423	336	469	68	10	1.9
28	49	83	11	313	176	163	68	10	1.9
29	181	198	207	272	214	164	74	10	2.0
30	241	204	249	191	122	65	68	11	2.1
31	104	156	48				96	60	16
TOTAL	3965		2031	12813		60783.8	3216		648.7

50055000 RIO GRANDE DE LOIZA AT CAGUAS, PR--Continued

DAY	MEAN DI SCHARGE (CFS)	MEAN CONCEN- TRATION (MG/L)	SEDIMENT DISCHARGE (TONS/DAY)	MEAN DISCHARGE (CFS)	MRAN CONCEN- TRATION (MG/L)	SEDIMENT DISCHARGE (TONS/DAY)	MEAN DISCHARGE (CFS)	MBAN CONCEN- TRATION (MG/L)	SEDIMENT DISCHARGE (TONS/DAY)
		JANUARY		1	PEBRUARY			MARCH	
1	106	62	20	91	16	3.8	56	60	9.0
2	78	28	5.9	87	17	4.0	53	58	8.2
3	72	25	4.7	89	28	6.6	57	5,6	8.5
4	68	22	3.9	96	35	9.2	55	55	8.4
5	7930	2790	199000	92	31	7.6	60	55	9.1
6	4920	2620	44000	108	88	30	62	55	9.5 8.2
7	609	242	522	143	114	46	58	52	
8	311	57	48	100	79	21	109	120	39
9	246	76	53	86	76	18	59	92	15
10	282	147	110	121	104	35	51	75	10
11	198	109	60	97	53	14	48	57	7.2
12	171	65	30	82	45	10	45	40	4.9
13	164	22	9.4	76	41	8.4	47	37	4.5
14	144	17	6.4	76	40	8.5	47	40	5.1
15	135	18	6.8	90	63	15	65	47	7.8
16	149	18	11	84	105	23	48	53	6.6
17	219	17	9.7	71	138	27	50	60	8.3
18	132	15	5.4	68	153	28	82	68	15
19	119	15	4.9	66	158	28	56	59	8.9
20	115	14	4.2	65	160	28	60	50	8.0
21	110	11	3.3	62	158	26	55	47	7.0
22	110	9	2.7	60	153	25	54	45	6.4
23	106	8	2.3	68	146	26	48	42	5.5
24	110	9	2.7	69	137	26	44	39	4.5
25	109	10	3.0	68	127	23	41	41	4.5
26	113	12	3.4	64	117	21	41	41	4.5
27	101	12	3.3	70	105	19	40	39	4.2
28	100	12	3.4	64	86	15	39	33	3.5
29	103	14	3.9	58	69	11	49	27	3.6
30	93	15	3.8				40	26	2.8
31	91	15	3.7				38	26	2.6
TOTAL	17314		243950.8	2371		563.1	1657		250.3

50055000 RIO GRANDE DE LOIZA AT CAGUAS, PR--Continued

DAY	MRAN DISCHARGE (CFS)	MRAN CONCEN- TRATION (MG/L)	SEDIMENT DISCHARGE (TONS/DAY)	MEAN DISCHARGE (CFS)	MEAN CONCEN- TRATION (MG/L)	SEDIMENT DISCHARGE (TONS/DAY)	MEAN DISCHARGE (CFS)	MEAN CONCEN- TRATION (MG/L)	SEDIMENT DISCHARGE (TONS/DAY)
		APRIL			MAY			JUNE	
1	52	54	8.0	42	69	8.3	521	349	1790
2	53	91	13	174	160	88	479	788	1430
3	38	104	11	60	94	16	177	122	63
4	36	101	9.8	41	79	9.0	922	665	3830
5	36	99	9.3	35	71	6.7	265	40	29
6	33	95	8.4	64	86	22	196	40	21
7	42	78	8.4	117	137	47	184	82	45
8	45	59	7.2	62	110	18	207	131	83
9	39	46	4.8	47	91	12	221	169	104
10	37	39	3.9	41	72	8.2	436	361	566
11	39	39	4.2	40	61	6.8	442	348	465
12	72	78	17	64	69	12	1070	961	4290
13	108	100	30	49	79	11	689	570	1220
14	60	74	12	39	74	7.6	522	421	644
15	81	88	19	71	65	13	264	114	87
16	49	93	12	1090	2190	15200	263	183	141
17	42	99	12	214	998	761	400	406	608
18	41	101	11	106	82	25	259	348	243
19	59	105	17	74	70	14	169	170	81
20	145	201	87	146	170	148	147	117	47
21	75	151	33	101	298	88	1020	1470	6150
22	48	113	15	63	240	41	234	108	75
23	47	109	14	1400	834	8620	179	58	27
24	38	105	10	2020	695	7420	144	50	19
25	35	101	9.3	333	101	112	127	52	17
26	35	99	9.4	2740	1420	21400	116	69	21
27	32	96	8.1	399	246	293	113	80	24
28	30	92	7.1	202	80	49	110	111	33
29 30	31	85	7.2	144	40	16	97	136	36
31	35	75 	6.8	249	168	235	93	168	41
31				146	93	41			+
TOTAL	1513		424.9	10373		54748.6	10066		22230

50055000 RIO GRANDE DE LOIZA AT CAGUAS, PR--Continued

	MBAN				MRAN		Mran		
DAY	MRAN Discharge (CFS)	CONCEN- TRATION (MG/L)	SEDIMENT DISCHARGE (TONS/DAY)	MBAN Discharge (CFS)	CONCEN- TRATION (MG/L)	SEDIMENT DISCHARGE (TONS/DAY)	MRAN DISCHARGE (CPS)	CONCEN- TRATION (MG/L)	SEDIMENT DISCHARGE (TONS/DAY)
		JULY			AUGUST		Si	ep tem ber	
1	89	203	47	66	23	4.0	87	40	10
2	81	190	41	66	21	3.8	72	46	9.0
3	78	137	28	76	19	4.0	104	84	25
4	77	87	18	63	19	3.3	93	80	21
5	146	118	51	1610	1520	11800	80	67	15
6	84	61	15	644	917	2280	89	74	19
7	74	39	7.8	233	213	148	89	72	17
8	84	48	13	159	130	58	73	64	13
9	98	46	13	123	100	., 34	280	274	267
10	77	24	4.9	243	317	235	103	65	20
11	141	108	58	15Ò	130	54	78	50	10
12	108	95	31	171	183	92	70	58	11
13	76	55	12	122	56	19	63	54	9.4
14	69	56	10	130	100	14	61	51	8.3
15	76	89	19	161	140	67	60	53	8.6
16	82	170	38	111	76	23	99	117	36
17	222	231	179	104	43	12	284	247	262
18	100	92	25	9 9	19	5.2	165	131	60
19	93	87	22	91	15	3.7	746	661	2490
20	146	112	45	91	17	4.1	2870	1450	28400
21	106	93	27	88	19	4.5	1660	1310	9040
22	364	386	598	80	20	į. i.	335	338	304
23	118	266	89	81	20	4.4	207	286	167
24	89	145	36	113	84	28	161	166	76
25	171	143	86	85	66	15	135	83	30
26	105	75	24	73	62	iā	121	33	11
27	82	3 3	7.3	89	66	16 11 16	113	13	3.9
28	75	23	4.6	77	53	11	103	18	4.9
29	66	21	3.7	85	68	16	102	24	6.7
30	62	25	4.1	73	61	12 21	102	33	8.8
31	66	27	4.6	95	77	21			
TOTAL	3305		1562.0	5452		15039.4	8605		41363.6
YEAR	80650		443596.2						

50055000 RIO GRANDE DE LOIZA AT CAGUAS, PR--Continued

WATER QUALITY DATA, WATER YEAR OCTOBER 1991 TO SEPTEMBER 1992

PARTICLE-SIZE DISTRIBUTION OF SUSPENDED SEDIMENT

D AT R	TIME	DIS- CHARGE, INST. CUBIC FEST PER SECOND	SEDI- MENT, SUS- PENDED (MG/L)	SEDI- MENT, DIS- CHARGE, SUS- PENDED (T/DAY)	SED. SUSP. FALL DIAM. PERCENT FINER THAN .002 MM	SED. SUSP. FALL DIAM. PERCENT FINER THAN .004 MM	SED. SUSP. FALL DIAM. PERCENT FINER THAN .008 MM
NOV 1991							
07	0923	3460	3010	28100	29	38	50
08	1000	3210	4310	37300	16	25	36
24	1358	1260	18500	62800	4	15	23
JAN 1992							
05	2039	40600	9250	1010000	21	30	39
MAY							
16	1355	1580	17500	74800	5	9	14
23 26	2313 0337	9720 14400	3150 4800	82700 186000	33 27	41 33	47 43
	SED.	SED.	SED.	SED.	SED.	SED.	SED.
	SUSP.	SUSP.	SUSP.	SUSP.	SUSP.	SUSP.	SUSP.
	PALL	FALL	SIEVE	SIEVE	SIEVE	SIRVE	SIEVE
	DIAM.	DIAM.	DIAM.	DIAM.	DIAM.	DIAM.	DIAM.
	PERCENT	PERCENT	PERCENT	PERCENT	PERCENT	PERCENT	PERCENT
DATE	PINER THAN	PINER THAN	PINER THAN	Finer Than	PINER THAN	FINER THAN	finer Than
DATE	.016 MM	.031 MM	.062 MM	.125 MM	.250 MM	.500 MM	1.00 MM
NOV 1991							
07	70	77	98	99.2	99.6	99.	99.9
08	50	64	88	95	99.4	99.	
24	35	51	71	90	97	98	99
JAN 1992							
05	55	70	80	88	93	98	99
MAY							
16	21	34	42	65	83	96	99
23		60	93	98.6	99.5	99.	
26	54	63	91	97	99	99.7	7 99.8

50055000 RIO GRANDE DE LOIZA AT CAGUAS--Continued

WATER QUALITY DATA, WATER YEAR OCTOBER 1991 TO SEPTEMBER 1992

SILT AND CLAY PERCENT OF SUSPENDED SEDIMENT

DATE	TIME	STREAM- FLOW, INSTAN- TANEOUS (CFS)	SEDI- MENT, SUS- PENDED (MG/L)	SEDI - MENT, DIS- CHARGE, SUS- PENDED (T/DAY)	SED. SUSP. SIEVE DIAM. PERCENT FINER THAN .062 MM
NOV 1991					
07	0733	1320	6340	22600	94
07	1323	1620	1220	5360	98
08	0620	2000	1360	7330	95
08	0855	3670	3260	32300	93
08	1140	2370	4560	29200	87
08	1255	1870	507	2560	96
24	1553	1250	593	2010	97
JAN 1992					
05	1654	2520	7500	51100	99
05	1924	34100	5230	482000	94
MAR					
03	1108	50	54	7.3	94
APR					
21	0900	162	162	71	98
MAY					
16	1445	6720	9240	168000	96
16	1805	1800	4600	22300	97
21 23	0904	99 1642	307	82	96 85
23	2023 2243		3840 3020	17000 102300	
26	1242	12600 1050	491	1390	96 98
JUN	1444	1050	431	1330	30
01	2052	1380	2080	7770	73
02	0012	1530	1900	7850	95
21	0607	1480	1630	6500	73
21	0812	3450	3060	28600	96
21	1037	1540	3850	16100	92
JUL					
20	0610	138	231	86	99
23	0813	120	287	93	99
AUG					
05	0935	1520	2060	8470	95
10	0800	317	633	542	99
SEP					
19	1100	191	288	148	98
19	1841	2527	1000	6860	93
19	2134	1433	1693	6550	97

50055100 RIO CAGUITAS NEAR AGUAS BUENAS, PR

LOCATION.--Lat 18°14'48", long 66°05'37", Hydrologic Unit 21010005, on right bank 450 ft (137 m) upstream from bridge on Highway 777, 1.0 mi (1.6 km) southeast from Aguas Buenas, 3.9 mi (6.3 km) northwest from Caguas, and 2.1 mi (3.4 km) southwest from Las Carolinas.

DRAINAGE AREA. -- 5.30 mi2 (13.72 km2).

WATER-DISCHARGE RECORDS

PERIOD OF RECORD .-- February 1990 to current year.

GAGE. --Water-stage recorder and crest-stage gage. Rlevation of gage is 394 ft (120 m), from topographic map.

REMARKS.--Records fair except those for estimated daily discharges, which are poor. Gage-height and precipitation satellite telemetry at station.

DESCRIPTION OF STATEMENT AT STATEMENT												
	DI	SCHARGE,	CUBIC FEET	PER SEC	OND, WATER	YEAR OC	rober 1991	TO SEPTE	MBER 199	2		
				1	DAILY MEAN	VALUES						
DAY	OCT	VOV	DRC	JAN	FRB	MAR	APR	MAY	JUN	JUL	AUG	SEP
1	6.7	5.2	5.1	4.9	4.1	3.8	2.9	3.0	4.1	3.4	3.2	3.3
2 3	11 6.6	5.3 4.4	5.0 7.4	4.8	4.1 4.3	3.8 3.8	3.0 3.0	3.6 2.8	4.1	3.3 3.4	3.4 3.8	3.2 e3.9
Ä	5.2	4.4	9.4	4.9	4.3	3.7	2.9	2.6	4.3	3.4	6.1	e3.5
5	5.6	5.2	6.2	235	4.3	3.6	2.9	2.6	3.9	3.9	77	e6.3
6	5.0	5.6	5.6	116	4.3	3.6	3.0	2.9	3.7	3.4	13	64.4
7	5.5	16	5.3	14	4.2	3.6	3.4	2.9	4.7	3.4	5.7	e3.9
8 9	5.3 4.8	42 15	5.1 5.0	7.8 7.1	4.2 4.3	3.5	3.1	2.6 2.5	4.4 3.9	4.0 s3.6	4.5 4.0	e3.9 e7.6
10	4.8	7.3	5.0	9.2	5.4	3.4 3.5	2.9 2.8	2.4	4.3	3.4	3.6	s 3.5
11	4.7	6.0	4.9	6.0	4.5	3.5	2.9	2.5	4.4	4.2	3.7	3.4
12	4.6	5.5	5.1	5.4	4.3	3.3	3.1	3.5	6.2	3.3	3.8	3.2
13	4.5	5.3	5.4	5.4	4.3	3.3	2.8	3.1	5.6	e3.1	3.5	3.1
14	4.5	5.1	6.5	5.0	4.3	3.4	2.7	2.7	4.4	e3.1	3.6	4.0
15	4.7	4.9	5.0	4.8	4.2	3.6	2.7	2.7	4.0	e3.5	3.4	3.6
16	4.4	4.9	5.0	11	4.4	3.3	2.7	3.6	4.4	e5.0	3.2	6.1
17	4.4	4.9	5.0	8.7	4.3	4.3	2.9	5.1	4.0	e7.0	3.1	4.1
18 19	4.2 4.3	4.7	4.9 4.8	5.3 4.8	4.3 4.3	3.7 3.5	2.9 11	3.7 4.6	3.8 3.7	e4.5 e3.8	3.0 2.9	4.6 41
20	4.2	4.8	8.7	4.7	4.1	3.4	5.1	5.1	3.6	e3.6	2.9	31
21	4.1	9.7	7.7	4.6	4.0	3.2	3.1	7.4	5.0	e5.0	2.9	14
22	9.9	10	5.6	4.6	4.1	3.3	3.0	5.0	3.7	e7.0	2.9	19
23	5.0	5.6	5.3	4.5	4.1	3.1	2.8	36	3.5	e4.3	3.0	e11
24 25	4.4	6.4	5.2	4.5	4.2	2.9	2.7	34	3.4	e5.0	3.1	e6.4
45	4.1	5.3	5.1	4.6	4.2	2.9	2.6	18	3.4	e6.2	3.0	5.3
26	4.1	5.0	5.0	4.6	4.1	2.9	2.6	9.6	3.3	e4 · 8	3.0	4.9
27 28	4.1	5.3 5.0	5.0 5.0	4.4	4.0	2.9 9.1	2.6 2.6	6.5 5.2	3.4 3.6	e4.8 e3.4	3.5 3.2	4.7 4.6
29	4.1	4.9	5.0	4.4	3.8	3.7	2.5	4.7	3.6	3.0	3.4	4.5
30	10	5.4	5.0	4.4		3.1	2.6	4.5	3.3	3.1	3.9	4.8
31	5.3		5.0	4.1		2.9		4.3		3.1	4.3	
TOTAL	164.2	223.8	173.3	518.8	123.0	111.6	95.8	199.7	121.7	126.0	193.6	226.8
MEAN	5.30	7.46	5.59	16.7	4.24	3.60	3.19	6.44	4.06	4.06	6.25	7.56
MAX MIN	11 4.1	4.4	9.4 4.8	235 4.1	5.4 3.8	9.1	11	36 2.4	6.2	7.0 3.0	77 2.9	41 3.1
AC-FT	326	144	344	1030	244	2.9 221	2.5 190	396	3.3 241	250	384	450
CFSM	1.00	1.41	1.05	3.16	.80	. 68	.60	1.22	.77	.77	1.18	1.43
IN.	1.15	1.57	1.22	3.64	.86	.78	. 67	1.40	.85	.88	1.36	1.59
e Ra	stimated											
STATIST	TICS OF M	ONTHLY M	EAN DATA FO	R WATER	YRARS 1990	- 1992.	BY WATER	YBAR (WY)				
										5 5 6	F (A	
MRAN MAX	13.1 20.9	6.61 7.46	7.44 9.28	12.0 16.7	5.24 8.00	6.29 8.87	4.17 5.64	4.56 6.41	3.79 4.06	5.21 7.29	5.68 6.28	6.01 7.95
(WY)	1991	1992	1991	1992	1991	1990	1991	1992	1992	1991	1992	1992
MIN	5.30	5.76	5.59	7.19	3.51	3.60	3.19	2.48	3.40	3.74	5.14	5.01
(WY)	1992	1991	1992	1991	1990	1992	1992	1990	1991	1990	1991	1991
SUMMARY	STATIST	ICS	FOR 1	991 CALE	NDAR YEAR	F	OR 1992 WA	TER YEAR		WATER Y	EARS 1990	- 1992
ANNUAL				2161.0			2278.3					
ANNUAL	MEAN LANNUAL:	MBAN		5.9	2		6.22			6.8 7.4		1991
	ANNUAL M									6.3		1991
	DAILY M			82	Jul 16		235	Jan 5		235	Jan	5 1992
Lowest	DAILY ME	AN		2.8	Jun 18 Jun 16		2.4	May 10		1.8	May	7 1990
	SEVEN-DA			2.8	Jun 16			Apr 24		1.9 1460	Mav	22 1990
	TANEOUS P						1850	Aug 5 Aug 5		1460 15.2		15 1990 15 1990
	ANBOUS L		-				2.4			1.8		3 1990
ANNUAL	RUNOFF (AC-FT)		4290			4520			4970	_	
	RUNOFF (1.1			1.17			1.2		
	RUNOFF (ENT EXCE			15.1° 7.4	′		15.99 7.0			17.5 7.8		
	ENT EXCE			5.2			4.3			4.4		

MPAN

RIO GRANDE DE LOIZA BASIN

50055100 RIO CAGUITAS NEAR AGUAS BUENAS, PR--Continued

WATER-QUALITY RECORDS

PERIOD OF RECORDS. -- Water years 1990 to current year.

INSTRUMENTATION. -- DH-48 and automatic sediment sampler.

PERIOD OF DAILY RECORD. --

SUSPENDED-SEDIMENT DISCHARGE: February 1990 to September 1992

EXTREMES FOR PERIOD OF DAILY RECORD. -SEDIMENT CONCENTRATION: Maximum daily mean, 1,370 mg/L Jan. 05, 1992; Minimum daily mean,
2 mg/L Several days.

SEDIMENT LOADS: Maximum daily mean, 3,730 tons (3,360 tonnes) Jan. 05, 1992; Minimum daily mean, 0.02 ton (0.03 tonne) Several days.

EXTREMES FOR WATER YEARS 1990-92.--

MEAN

Water	Suspended-sediment concentration (mg/L maximum minimum	Suspended-sediment discharg	ge (tons per day)
Year		maximum	minimum
1990	326 (Sep. 03) 4 (May, 18)	297 (Jul. 13)	.02 (May, 18)
1991	782 (Jul. 16) 2 (Nov. 4-5)	1.020 (Oct. 15)	.04 (Nov. 4-5)
1992	1,370 (Jan. 05) 2 (Several days)	3,730 (Jan. 05)	.02 (Several days)

MEAN

		MEAN			MRAN			MRAN	
	MRAN	CONCEN-	SEDIMENT	MEAN	CONCEN-	SEDIMENT	MRAN	CONCEN-	SEDIMENT
	DISCHARGE	TRATION	DISCHARGE	DISCHARGE	TRATION	DISCHARGE	DISCHARGE	TRATION	DISCHARGE
DAY		(MG/L)			(MG/L)		(CFS)	(MG/L)	(TONS/DAY)
DAI	(CFS)	(EG/L)	(TONS/DAY)	(CFS)	(MG/L)	(TONS/DAY)	(CES)	(#G/D)	(TONS/DAI)
		JANUARY		i	FEBRUARY			MARCH	
1				e3.6			3.7	13	. 13
2				e4.2			3.3	12	.10
3				e4.0			3.0	11	.08
4							3.0	11	.08
				e3.4					
5				e3.0			2.9	11	.08
6				e2.7			2.9	11	.08
7				e2.6			2.9	11	. 08
8				e3.0			2.8	10	.08
9				e3.5	13	e5.0	13	62	4.3
10				e5.0	19	e.26	6.3	27	. 52
10				65.0	17	0.20	0.0		
11				e4.0	16	e.18	5.3	22	.36
12				e3.6	12	e.12	19	88	5.5
13				2.9	11	.08	39	201	24
14				4.8	19	.29	50	258	54
15				3.2	13	.11	13	55	2.1
13				3.2	13	• • • • • • • • • • • • • • • • • • • •	13		•••
16				3.0	11	.08	16	76	5.1
17				3.4	13	.12	12	55	2.0
18				3.7	15	.16	8.0	34	. 75
19				3.4	12	.12	6.5	26	. 45
20				3.1	12	.10	5.9	23	.34
20				3.1	14	.10	5.9	23	.34
21				3.7	14	.14	5.3	20	.28
22				4.3	16	.18	5.1	19	.26
23				3.7	16	.17	5.2	19	.26
24				3.7	14	.14	4.8	18	.24
25				3.4	12	.12	4.6	17	.22
26				3.4	13	.12	4.5	17	.22
27				3.0	12	.10	4.4	17	.23
							4.4	19	.22
28				3.0	11	.08		19	.24
29							4.7		
30							4.9	19	.26
31							4.5	18	.23
TOTAL				98.3			270.9		102.79

e Estimated

50055100 RIO CAGUITAS NEAR AGUAS BUENAS, PR--Continued

		MEAN			mran			MEAN	
DAY	MEAN DISCHARGE (CFS)	CONCEN- TRATION (MG/L)	SEDIMENT DISCHARGE (TONS/DAY)	MEAN DISCHARGE (CFS)	CONCEN- TRATION (MG/L)	SEDIMENT DISCHARGE (TONS/DAY)	MEAN DISCHARGE (CFS)	CONCEN- TRATION (MG/L)	SEDIMENT DISCHARGE (TONS/DAY)
		APRIL			MAY			JUNE	
1	4.2	17	. 19	2.1	7	.04	2.7	9	. 06
2	3.9	16	. 17	2.1	7	.04	2.9	9	. 08
3	3.9	15	. 15	2.0	7	.04	2.8	9	. 06
4	3.7	14	. 14	2.0	7	.04	2.8	10	. 07
5	3.7	14	. 14	2.0	7	.04	3.1	11	. 09
6	3.6	14	-14	1.9	7	.04	2.9	10	. 07
7	3.6	14	. 14	1.8	7	.04	4.1	16	.26
8	3.5	14	.13	1.8	7	.04	3.4	11	.11
9	3.8	14	. 15	6.6	30	1.3	2.8	8	. 07
10	3.9	15	. 17	4.9	17	.21	2.3	7	.04
11	3.4	13	.12	4.0	11	.12	2.3	7	.04
12	3.2	13	.11	2.7	10	.08	2.3	7	. 04
13	5.5	22	. 45	2.8	11	.09	2.3	7	. 04
14	4.2	16	. 19	3.0	11	.09	4.2	39	. 43
15	3.6	12	.11	2.7	10	.08	12	52	1.8
16	3.4	11	. 10	2.5	8	.06	6.0	23	.37
17	3.2	11	. 10	2.1	7	.04	4.8	17	.21
18	3.0	11	. 09	2.1	4	.02	4.4	15	. 17
19	4.6	17	. 24	2.1	7	.04	4.3	14	. 16
20	3.8	13	. 14	2.0	7	.04	4.1	13	. 14
21	3.0	11	.09	1.9	7	.04	4.1	13	.14
22	2.5	10	. 07	1.8	7	.04	4.1	13	. 14
23	2.3	8	. 05	1.8	7	.04	9.0	38	1.6
24	2.1	7	. 04	1.9	7	.04	6.2	23	.37
25	9.7	44	4.4	2.0	7	.04	7.1	19	.36
26	5.4	22	.42	2.0	7	.04	5.5	18	.26
27	2.8	10	. 07	2.0	7	.04	4.7	15	. 19
28	2.4	8	. 05	2.1	7	.04	4.5	14	. 17
29	2.1	7	. 04	2.1	7	.04	4.4	13	.16
30	2.1	7	.04	2.2	7	.04	4.1	13	.14
31				2.9	8	.07			
TOTAL	110.1		8.44	75.9		2.96	130.2		7.84

DAY	MEAN DISCHARGE (CFS)	MEAN CONCEN- TRATION (MG/L)	SEDIMENT DISCHARGE (TONS/DAY)	MEAN DISCHARGE (CFS)	MEAN CONCEN- TRATION (MG/L)	SEDIMENT DISCHARGE (TONS/DAY)	MEAN DISCHARGE (CFS)	MBAN CONCEN- TRATION (MG/L)	SEDIMENT DISCHARGE (TONS/DAY)	
	JULY				AUGUST			SEPTEMBER		
1	4.1	14	. 15	3.1	20	.17	2.7	6	. 05	
2	4.0	7	.08	18	85	9.0	4.7	17	.34	
3	3.9	11	.12	7.1	27	.57	37	326	98	
4	3.9	11	. 12	4.4	15	.18	10	238	9.2	
5	3.2	11	.10	5.4	34	.68	4.7	40	. 51	
6	6.1	23	.45	4.1	41	.44	4.6	40	.50	
7	4.0	15	. 16	4.4	40	.46	4.2	38	. 46	
8	3.7	12	.11	4.6	37	.46	3.9	37	.38	
9	3.4	11	.10	3.6	34	.33	3.6	24	.23	
10	3.2	11	. 10	4.3	31	.36	e3.5	15	e. 14	
11	3.2	11	.10	3.8	28	.28	e3.1	11	e.09	
12	3.2	11	.10	3.6	23	.21	3.0	11	.08	
13	3.7	14	. 14	44	270	297	3.0	12	.09	
14	3.7	14	. 14	10	55	1.8	3.3	11	.10	
15	11	50	5.0	4.6	40	.50	3.4	11	.10	
16	4.0	17	. 19	3.9	38	.39	4.4	14	.19	
17	6.9	29	.88	3.7	33	.35	3.7	18	. 17	
18	5.3	21	.36	3.9	30	.32	3.6	17	. 15	
19	3.6	13	. 12	3.2	34	.29	3.5	14	. 13	
20	3.1	11	.09	2.9	39	.31	3.4	11	. 10	
21	2.6	10	. 07	2.9	40	.32	3.2	10	.08	
22	2.5	8	. 05	3.1	35	.30	6.0	24	.78	
23	2.3	7	.04	3.3	25	.22	4.6	19	.24	
24	4.1	28	. 83	3.0	15	.12	3.8	17	.18	
25	3.9	82	1.0	3.4	10	.10	3.5	14	. 12	
26	2.8	45	.34	3.4	10	.09	3.5	12	.10	
27	2.5	39	. 25	2.9	10	.08	3.8	11	. 12	
28	2.2	36	.21	2.9	10	.08	3.4	11	. 09	
29	2.3	33	.20	2.9	10	.08	3.2	10	.08	
30	2.5	28	. 18	2.8	10	.08	4.5	18	.37	
31	2.6	23	.16	2.7	7	.06				
TOTAL	117.5		11.94	175.9		315.63	152.8		113.17	

e Estimated

RIO GRANDE DE LOIZA BASIN 50055100 RIO CAGUITAS NEAR AGUAS BUENAS, PR--Continued

DAY	MEAN DISCHARGE (CFS)	MEAN CONCEN- TRATION (MG/L)	SEDIMENT DISCHARGE (TONS/DAY)	MEAN DISCHARGE (CFS)	MEAN CONCEN- TRATION (MG/L)	SEDIMENT DISCHARGE (TONS/DAY)	MEAN DISCHARGE (CFS)	MBAN CONCEN- TRATION (MG/L)	SEDIMENT DISCHARGE (TONS/DAY)
		OCTOBER		1	NOVEMBER		1	DECEMBER	
1	3.8	12	. 15	7.3	16	.32	9.5	38	1.3
2	3.3	12	. 11	7.0	8	. 17	7.4	32	. 83
3	3.8	13	. 15	6.7	3	.07	29	152	19
4	4.1	15	. 16	6.5	2	.04	9.7	42	1.3
5	3.6	14	. 13	6.1	2	.04	6.2	24	.40
6	3.6	14	. 13	6.0	4	.06	5.4	20	.29
7	11	74	8.9	5.9	5 5	.08	5.1	20	.26
8	4.2	83	. 99	5.8	5	.08	4.9	19	.24
9	3.5	80	. 82	5.5	4	.07	4.9	25	.32
10	11	103	4.7	5.4	5	.07	4.7	26	.34
11	5.8	110	1.8	5.2	6	.08	4.6	16	.20
12	4.2	110	1.3	5.2	6	.08	4.4	10	. 12
13	5.5	94	1.5	5.1	7	.10	4.5	10	. 12
14	6.6	78	1.3	5.0	9	.12	5.0	20	.26
15	100	590	1020	5.1	8	.12	6.2	27	.46
16	30	200	24	6.8	23	.51	5.2	23	.34
17	13	59	2.4	5.4	12	.17	4.7	20	. 25
18	77	424	212	5.3	8	.12	4.6	25	.30
19	32	151	21	5.2	8	.11	4.5	37	.44
20	36	225	76	6.2	17	.42	4.4	47	.56
21	109	597	278	5.4	16	.24	4.4	48	. 57
22	19	88	5.0	5.6	13	.19	4.5	43	. 52
23	11	51	1.7	5.3	9	. 14	4.6	38	. 47
24	17	77	8.0	5.0	6	.09	4.6	30	. 37
25	25	118	11	4.9	5	.06	4.4	19	. 22
26	47	240	45	7.1	17	.35	4.4	9	.11
27	20	79	5.2	6.4	29	.61	6.1	18	.43
28	12	35	1.1	5.4	22	.32	5.4	22	.35
29	9.5	30	.76	5.0	20	.28	9.5	42	1.9
30	8.5	28	. 63	6.1	29	.59	12	55	2.4
31	7.6	23	. 48				93	499	186
TOTAL	647.6		1734.41	172.9		5.70	287.8		220.67

50055100 RIO CAGUITAS NEAR AGUAS BUENAS, PR--Continued

DAY	MEAN DISCHARGE (CFS)	MEAN CONCEN- TRATION (MG/L)	SEDIMENT DISCHARGE (TONS/DAY)	MBAN DISCHARGE (CFS)	MRAN CONCEN- TRATION (MG/L)	SEDIMENT DISCHARGE (TONS/DAY)	MEAN DISCHARGE (CFS)	MEAN CONCEN- TRATION (MG/L)	SEDIMENT DISCHARGE (TONS/DAY)
		JANUARY		1	FEBRUARY			MARCH	
1	32	148	18	5.7	30	.48	5.6	18	.27
2	10	22	. 63	5.6	29	.43	5.5	29	.43
3	7.8	18	.38	5.6	24	.35	5.5	37	.55
4	6.8	18	.33	5.3	16	.22	5.8	43	. 67
5	7.4	28	. 67	41	209	117	6.0	39	. 62
6	10	48	2.0	14	67	3.4	6.1	29	.46
7	7.2	29	.58	7.7	59	1.2	5.8	21	.32
8	6.8	25	.44	6.0	40	.66	6.0	13	.20
9	7.3	25	.50	5.\$	25	.37	5.8	10	. 15
10	8.6	25	. 65	5.3	20	.28	5.4	8	.12
11	7.4	28	. 54	5.8	20	.29	5.5	8	.12
12	6.7	32	. 56	15	74	8.6	5.5	10	. 14
13	6.3	27	. 45	9.8	59	1.8	5.\$	12	. 17
14	5.9	16	. 25	6.6	33	.61	5.5	14	.20
15	5.9	11	. 17	6.1	24	.39	5.5	14	.21
16	5.8	11	. 17	5.8	21	.32	5.7	14	.22
17	5.7	12	. 17	5.7	20	.30	5.7	14	.22
18	5.7	11	.16	6.3	23	.42	6.2	17	.28
19	5.7	9	. 14	8.2	56	1.3	6.3	40	.71
20	5.6	8	. 12	6.4	52	.92	5.9	30	.49
21	5.5	7	.10	6.1	48	.85	5.8	18	.27
22	5.5	6	.08	6.0	43	.69	23	213	23
23	5.3	5	.08	5.9	36	.57	8.2	46	1.3
24	5.3	4	. 07	5.9	29	.45	6.7	20	.36
25	5.2	6	. 09	5.8	20	.31	6.1	18	.30
26	5.2	8	. 12	5.7	12	.18	5.8	13	.20
27	5.2	8	. 12	5.6	7	. 12	5.7	10	. 15
28	5.2	9	. 13	5.7	8	.13	5.6	14	.21
29	5.2	15	.21				5.5	17	.26
30	5.2	25	.35				5.5	17	.26
31	5.5	30	. 47				5.4	16	.23
TOTAL	222.9		28.73	224.1		142.64	198.1		33.09

50055100 RIO CAGUITAS NEAR AGUAS BUENAS, PR--Continued

DAY	MEAN DISCHARGE (CFS)	MEAN CONCEN- TRATION (MG/L)	SEDIMENT DISCHARGE (TONS/DAY)	MEAN DISCHARGE (CFS)	MEAN CONCEN- TRATION (MG/L)	SEDIMENT DISCHARGE (TONS/DAY)	MRAN DISCHARGE (CFS)	MEAN CONCEN- TRATION (MG/L)	SEDIMENT DISCHARGE (TONS/DAY)
		APRIL			MAY			JUNE	
1	5.4	12	.17	7.7	24	.50	3.3	15	. 14
2	5.5	9	. 13	7.5	30	.60	3.2	15	. 13
3	5.5	8	. 12	6.2	24	.40	3.2	15	. 12
4	5.5	7	. 10	5.8	23	.35	3.2	14	.11
5	5.2	6	.08	5.7	21	.32	3.2	12	.10
6	5.2	6	.08	5.7	21	.32	3.6	11	.11
7	5.2	7	.10	7.3	27	.57	3.3	11	.10
8	6.6	9	.16	7.0	31	. 67	3.2	10	.08
9	5.8	7	.11	4.1	17	.21	3.1	8	.06
10	5.6	6	.09	4.4	86	1.1	3.0	9	. 07
11	5.8	8	. 13	4.3	106	1.3	3.0	10	.08
12	6.3	10	.18	4.4	85	.95	3.1	10	.08
13	7.2	10	.20	3.6	61	.60	3.1	7	.06
14	5.9	10	.16	3.5	38	.35	3.0	6	. 05
15	5.8	10	.16	3.4	32	.29	2.9	9	. 07
16	5.9	10	. 16	3.4	28	.26	2.9	8	. 07
17	5.6	10	. 15	3.4	23	.22	2.9	7	. 06
18	5.5	10	. 14	3.9	18	.21	2.8	10	. 07
19	5.5	8	. 13	6.5	28	.84	2.8	11	.08
20	5.5	6	. 10	4.1	17	.20	2.8	11	.08
21	5.5	5	.08	3.7	16	.18	2.8	8	.06
22	5.4	5	.08	3.6	24	.23	2.8	6	.04
23	5.3	6	.08	3.4	21	.19	4.0	16	.21
24	5.3	8	.11	3.3	20	.18	3.5	19	.18
25	5.3	10	. 14	11	52	3.1	3.3	16	. 14
26	5.7	10	. 15	4.1	24	.29	3.2	13	.11
27	5.3	10	. 14	3.7	22	.23	3.3	11	.10
28	5.3	12	. 17	3.5	22	.21	3.2	11	. 10
29	5.5	14	.21	3.3	20	.18	3.3	11	.10
30	6.1	17	.27	3.3	13	.12	11	47	5.7
31				3.3	14	. 13			
TOTAL	169.2		4.08	148.1		15.30	102.0		8.46

50055100 RIO CAGUITAS NEAR AGUAS BUENAS, PR--Continued

DAY	MRAN DISCHARGE (CFS)	MEAN CONCEN- TRATION (MG/L)	SEDIMENT DISCHARGE (TONS/DAY)	MEAN DISCHARGR (CFS)	MEAN CONCEN- TRATION (MG/L)	SEDIMENT DISCHARGE (TONS/DAY)	MEAN DISCHARGE (CFS)	MEAN CONCEN- TRATION (MG/L)	SEDIMENT DISCHARGE (TONS/DAY)
		JULY			August		SI	SPTEMBER	
1	13	64	6.0	4.2	6	.06	4.1	12	.13
2	4.2	26	.30	4.0	7	.07	4.2	11	. 12
3	3.4	21	.20	4.0	8	.08	4.1	10	. 12
4	3.5	21	. 19	4.1	8	.09	4.1	9	.10
5	3.3	20	. 18	4.1	9	.10	4.0	9	. 09
6	3.3	20	. 18	4.3	9	.10	3.8	10	.10
7	3.8	34	. 47	4.3	8	.10	3.9	10	. 11
8	5.2	25	.58	4.3	7	.08	4.1	10	. 10
9	4.1	20	. 22	4.2	6	.07	4.3	8	. 09
10	3.3	20	. 18	4.4	8	.10	4.3	8	.08
11	3.3	19	. 17	4.3	11	.13	4.2	8	.08
12	3.4	16	. 14	4.4	14	.16	4.1	8	.08
13	3.3	14	.12	4.3	15	.18	4.1	8	.08
14	3.4	13	.12	4.4	15	.18	4.1	Ř	.08
15	9.7	45	4.2	4.4	15	.18	3.9	8	.08
16	82	782	477	4.7	15	.19	3.9	8	.08
17	8.1	183	4.5	4.9	16	.23	17	73	9.2
18	6.2	43	.74	5.0	16	.23	5.4	22	.35
19	5.7	26	.42	4.8	14	.18	5.5	60	.88
20	5.3	20	.30	4.8	11	. 15	4.5	18	.22
21	4.9	15	.19	5.2	10	.14	4.3	16	. 19
22	4.7	10	. 13	8.3	36	1.4	5.2	16	. 24
23	4.6	10	. 12	5.5	44	. 65	6.7	38	.75
24	4.8	11	. 13	4.7	32	.40	4.7	28	.38
25	4.5	12	. 14	4.4	29	.34	4.2	17	.20
26	4.1	12	. 14	4.2	23	.25	4.1	13	.14
27	4.1	12	. 13	18	82	12	5.1	18	.33
28	4.2	11	. 12	7.2	26	. 62	4.9	22	.29
29	4.2	11	. 12	5.0	13	.17	7.1	22	. 44
30	4.2	9	. 11	4.5	13	.16	6.3	26	. 49
31	4.1	7	.08	4.3	13	.15			
TOTAL	225.9		497.62	159.2		18.94	150.2		15.62
YEAR	2708.0		2725.26						

50055100 RIO CAGUITAS NEAR AGUAS BUENAS, PR--Continued
SEDIMENT DISCHARGE, SUSPENDED (TONS/DAY), WATER YEAR OCTOBER 1991 TO SEPTEMBER 1992

	MBAN				MRAN		mean		
	MRAN	CONCEN-	SEDIMENT	MEAN	CONCEN-	SEDIMENT	MRAN	CONCEN-	SEDIMENT
	DI SCHARGE	TRATION	DISCHARGE	DISCHARGE	TRATION	DISCHARGE	DI SCHARGE	TRATION	DISCHARGE
DAY	(CFS)	(MG/L)	(TONS/DAY)	(CFS)	(MG/L)	(TONS/DAY)	(CFS)	(MG/L)	(TONS/DAY)
		OCTOBER		1	NOVEMBER		1	DECEMBER	
								425	1.9
1	6.7	38	. 75	5.2	18	.25	5.1	135	1.7
2	11	106	5.5	5.3	18	.26	5.0	127	2.5
3 4	6.6	33	. 58	4.4	17	.21	7.4	126	3.0
	5.2	22	. 31	4.4	16	.19	9.4	113	
5	5.6	15	.20	5.2	16	.22	6.2	48	. 86
6	5.0	12	. 16	5.6	26	.39	5.6	16	.24
7	5.5	21	.47	16	559	34	5.3	11	. 15
8	5.3	42	. 62	42	724	111	5.1	8	.11
9	4.8	36	.48	15	142	8.3	5.0	8	. 10
10	4.8	30	.40	7.3	46	.98	5.0	8	.10
11	4.7	24	.31	6.0	33	.53	4.9	8	. 10
12	4.6	20	.24	5.5	27	.40	5.1	8	.10
13	4.5	19	.22	5.3	22	.31	5.4	12	.21
14	4.5	15	. 19	5.1	20	.27	6.5	27	.58
15	4.7	12	.15	4.9	19	.25	5.0	- é	.11
	•••	**	. 13	4.,	1.9		3.0	•	• • • • • • • • • • • • • • • • • • • •
16	4.4	12	. 14	4.9	15	.20	5.0	8	.10
17	4.4	12	. 14	4.9	12	.16	5.0	8	,10
18	4.2	12	. 14	4.7	12	.16	4.9	8	. 10
19	4.3	12	. 14	4.7	12	.15	4.8	8	. 10
20	4.2	12	. 14	4.8	11	. 14	8.7	60	2.8
21	4.1	12	. 14	9.7	95	9.0	7.7	44	1.1
22	9.9	98	15	10	70	2.3	5.6	12	. 18
23	5.0	13	. 19	5.6	35	.53	5.3	10	.13
24	4.4	11	. 13	6.4	34	.72	5.2	16	.22
25	4.1	10	. 12	5.3	19	.27	5.1	29	. 39
26	4.1	10	. 12	5.0	22	.29	5.0	34	.45
27	4.1	10	. 12	5.0 5.3	58	. 17	5.0	24	.32
28	4.1	10	.11	5.0	100	1.3	5.0	13	.17
29	4.1	9	. 10	4.9	119	1.6	5.0	8	.11
30	10	94	8.2	5.4	129	1.8	5.0	8	.10
31	5.3	21	.32	J.4	143		5.0	8	.10
31	3.3	• •	, 3.				3.0	J	.10
TOTAL	164.2		35.83	223.8		176.95	173.3		18.23

50055100 RIO CAGUITAS NEAR AGUAS BURNAS, PR--continued

DAY	MEAN DISCHARGE (CFS)	MEAN CONCEN- TRATION (MG/L)	SEDIMENT DISCHARGE (TONS/DAY)	MEAN Discharge (CFS)	MEAN CONCEN- TRATION (MG/L)	SEDIMENT DISCHARGE (TONS/DAY)	MRAN DISCHARGE (CFS)	MEAN CONCEN- TRATION (MG/L)	SEDIMENT DISCHARGE (TONS/DAY)
		JANUARY		1	PEBRUARY			MARCH	
1	4.9	8	.10	4.1	5	.06	3.8	6	. 05
2	4.8	8	.10	4.1	6	.08	3.8	5	.04
3	4.9	8	.10	4.3	8	.10	3.8	4	. 03
4	4.9	8	.10	4.3	10	.11	3.7	3	. 02
5	235	1370	3730	4.3	9	.10	3.6	3	.02
6	116	1340	566	4.3	7	.07	3.6	4	.04
7	14	104	4.9	4.2	5	.06	3.6	6	.06
8	7.8	26	.57	4.2	7	.08	3.5	7	. 07
9	7.1	22	.48	4.3	10	.11	3.4	8	.08
10	9.2	62	2.1	5.4	10	.13	3.5	8	.08
11	6.0	11	.17	4.5	10	.11	3.5	7	. 07
12	5.4	11	. 15	4.3	9	.10	3.3	6	. 06
13	5.4	11	. 15	4.3	8	.09	3.3	6	.06
14	5.0	11	. 14	4.3	6	.07	3.4	5	. 05
15	4.8	11	.14	4.2	6	.07	3.6	4	.04
16	11	123	17	4.4	8	.08	3.3	4	- 04
17	8.7	60	2.6	4.3	9	.11	4.3	5	. 05
18	5.3	82	1.2	4.3	13	.15	3.7	5	. 05
19	4.8	12	. 15	4.3	18	.21	3.5	5	.04
20	4.7	12	. 14	4.1	20	.22	3.4	6	. 05
21	4.6	10	. 12	4.0	19	.21	3.2	7	.06
22	4.6	6	. 08	4.1	15	.16	3.3	6	. 05
23	4.5	5	.06	4.1	10	.10	3.1	4	. 03
24	4.5	5	.06	4.2	8	.08	2.9	3	. 02
25	4.6	5	.06	4.2	8	.09	2.9	6	.04
26	4.6	5	.06	4.1	8	.09	2.9	9	.06
27	4.4	5	.06	4.0	8	.08	2.9	10	.08
28	4.4	5	.06	4.0	8	.08	9.1	91	11
29	4.4	5	. 06	3.8	7	.07	3.7	20	. 22
30	4.4	5	.06				3.1	16	. 12
31	4.1	5	.06				2.9	12	. 09
TOTAL	518.8		4327.03	123.0		3.07	111.6		12.77

50055100 RIO CAGUITAS NEAR AGUAS BUENAS, PR--Continued

	MEAN				MRAN		MRAN		
	MRAN	CONCEN-	SEDIMENT	MEAN	CONCEN-	sediment	MRAN	CONCEN-	SEDIMENT
	DISCHARGE	TRATION	DISCHARGE	DISCHARGE	TRATION	DISCHARGE	DISCHARGE	TRATION	DISCHARGE
DAY	(CFS)	(MG/L)	(TONS/DAY)	(CFS)	(MG/L)	(TONS/DAY)	(CFS)	(MG/L)	(TONS/DAY)
	(CID)	(20, 2)	(IOND, DAI)	(CFD)	(224, 11)	(IOND) Dail)	(015)	(110, 2,	(10115, 5011,
		APRIL			MAY			JUNE	
1	2.9	10	.07	3.0	10	.08	4.1	12	. 14
2	3.0	8	.06	3.6	7	.08	4.1	12	.13
3	3.0	ĕ	.05	2.8	5	.03	4.0	12	.12
ă	2.9	ĭ	.04	2.6	3	.02	4.3	11	. 14
5	2.9	7	.04	2.6	3	.02	3.9	11	.11
,	4.3	•		2.0	3		3.,		• • • •
6	3.0	7	.07	2.9	2	.02	3.7	9	.09
7	3.4	12	.11	2.9	2	.02	4.7	18	. 35
8	3.1	13	. 11	2.6	2	.02	4.4	37	. 46
9	2.9	11	.09	2.5	2	.02	3.9	29	. 32
10	2.8	9	.07	2.4	2	.02	4.3	25	.30
11	2.9	6	.05	2.5	2	.02	4.4	21	.26
12	3.1	5	.04	3.5	13	.34	6.2	128	2.5
13	2.8					.34	5.6	31	.53
		4	. 03	3.1	37		4.4	18	. 22
14	2.7	2	. 02	2.7	33	.25		16	
15	2.7	2	. 02	2.7	25	.20	4.0	10	.18
16	2.7	2	.02	3.6	21	.22	4.4	15	. 17
17	2.9	3	.03	5.1	36	1.7	4.0	13	. 14
18	2.9	5	. 04	3.7	15	.17	3.8	12	. 12
19	11	117	19	4.6	25	.46	3.7	12	. 12
20	5.1	40	.80	5.1	32	.83	3.6	12	.12
21	3.1	23	. 19	7.4	63	3.7	5.0	27	.46
22	3.0	21	. 17	5.0	26	.40	3.7	24	.24
23	2.8	20	.15	36	420	167	3.5	20	. 18
24	2.7	16	.11	34	468	97	3.4	15	.13
25	2.6	12	.08	18	227	31	3.4	10	. 09
						_			
26	2.6	13	.09	9.6	75	2.3	3.3	11	.09
27	2.6	13	.10	6.5	31	.56	3.4	16	.15
28	2.6	12	.08	5.2	19	.26	3.6	19	. 18
29	2.5	10	. 06	4.7	16	.20	3.6	17	.16
30	2.6	10	. 07	4.5	14	.16	3.3	13	. 11
31				4.3	12	.14			
TOTAL	95.8		21.86	199.7		307.58	121.7		8.31

RIO GRANDE DE LOIZA BASIN
50055100 RIO CAGUITAS NEAR AGUAS BUENAS, PR--Continued

	MBAN				MBAN		mban		
DAY	MEAN DISCHARGE (CFS)	CONCEN- TRATION (MG/L)	SEDIMENT DISCHARGE (TONS/DAY)	MEAN DISCHARGE (CFS)	CONCEN- TRATION (MG/L)	SEDIMENT DISCHARGE (TONS/DAY)	MRAN Discharge (CPS)	CONCEN- TRATION (MG/L)	SEDIMENT DISCHARGE (TONS/DAY)
		JULY		august			SEPTEMBER		
1	3.4	8	.08	3.2	8	.07	3.3	11	. 11
2	3.3	8	.07	3.4	9	.08	3.2	12	.10
3	3.4	10	.07	3.4	10	.10	e3.2	12	e. 11
4	3.4	10	.10	6.1	36	1.2	e3.5	11	e. 11
5	3.9	10	.10	77	712	621	e6.3	72	e2.2
•	3.9	10	. 10	,,	/12	621	e 0.3	12	42.2
6	3.4	10	.10	13	186	11	-4.4	131	e1.7
7	3.4	10	.10	5.7	68	1.1	e3.9	109	e1.1
8	4.0	10	.10	4.5	36	.44	e 3.9	96	e.98
9	s 3.6	8	.09	4.0	36	.37	e7.6	114	e4.1
10	3.4	9	. 09	3.6	33	.32	£3.5	56	. 57
11	4.2	19	.22	3.7	25	.25	3.4	33	.29
12	3.3	35	.31	3.8	15	.15	3.2	25	.22
13	e3.1	45	e.38	3.5	7	.07	3.1	19	. 16
14	e3.1	41	e.34	3.6	À	.04	4.0	20	.28
15	e3.5	27	e.25	3.4	5	.04	3.6	22	.23
16	e 5.0	20	e.26	3.2	5	.04	6.1	38	1.0
17	e7.0	19	e.36	3.1	5	.04	4.1	19	.21
18	e4.5	17	e.20	3.0	5	.04	4.6	24	. 41
19	e3.8	15	e.16	2.9	6	.04	41	483	230
20	e 3.6	13	e. 12	2.9	6	.04	31	601	103
21	e 5.0	11	e. 14	2.9	4	.03	14	896	37
22	e 7.0	15	e.28	2.9	4	.03	19	635	45
23	e4.3	19	e.21	3.0	7	.06	e11	196	e7.4
24	e5.0	17	e.22	3.1	10	.08	e6.4	90	e1 .6
25	e 6.2	13	e.22	3.0	11	.08	5.3	55	. 82
26	e4 .8	10	e.13	3.0	10	.08	4.9	35	.48
27	e4.8	7	e.09	3.5	12	.11	4.7	30	.39
28	e3.4	5	e.04	3.2	12	.10	4.6	27	.33
29	3.0	5	. 04	3.4	11	.09	4.5	20	.24
30	3.1	5	. 04	3.9	11	.12	4.8	13	. 17
31	3.1	6	. 06	4.3	11	. 13			
TOTAL	126.0		4.99	193.6		637.34	226.8		440.31
YEAR	2278.3		5994.27						

e Estimated

50055100 RIO CAGUITAS NEAR AGUAS BUENAS, PR--Continued

WATER QUALITY DATA, WATER YEAR OCTOBER 1991 TO SEPTEMBER 1992

PARTICLE-SIZE DISTRIBUTION OF SUSPENDED SEDIMENT

DATE	TIME	DIS- CHARGE, INST. CUBIC FRET PER SECOND	SEDI - MENT, SUS- PENDED (MG/L)	SEDI- MENT, DIS- CHARGE, SUS- PENDED (T/DAY)	SED. SUSP. FALL DIAM. PERCENT FINER THAN .002 MM	SED. SUSP. FAIL DIAM. PERCENT FINER THAN .004 MM	SED. SUSP. FALL DIAM. PERCENT FINER THAN .008 MM
OCT 1991							
02	0915	13	2070	72	64	73	74
JAN 1992							
05	1752	1550	7960	33300	31	37	44
DATE	SED. SUSP. FALL DIAM. PERCENT FINER THAN	SED. SUSP. FAIL DIAM. PERCENT FINER THAN	SED. SUSP. SIEVE DIAM. PERCENT FINER THAN	SED. SUSP. SIEVE DIAM. PERCENT FINER THAN	SED. SUSP. SIEVE DIAM. PERCENT FINER THAN	SED. SUSP. SIEVE DIAM. PERCENT FINER THAN	SED. SUSP. SIEVE DIAM. PERCENT FINER THAN
	.016 MM	.031 MM	.062 MM	.125 MM	.250 MM	.500 MM	1.00 MM
OCT 1991							
02	76	80	99	99.4	99.8	100	100
JAN 1992							
05	51	60	76	85	94	98	99

50055100 RIO CAGUITAS NRAR AGUAS BUENAS, PR--Continued WATER QUALITY DATA, WATER YEAR OCTOBER 1991 TO SEPTEMBER 1992 SILT AND CLAY PERCENT OF SUSPENDED SEDIMENT

DATE	TIME	STREAM- FLOW, INSTAN- TANEOUS (CFS)	SEDI- MENT, SUS- PENDED (MG/L)	SEDI- MENT, DIS- CHARGE, SUS- PENDED (T/DAY)	SED. SUSP. SIEVE DIAM. PERCENT FINER THAN .062 MM
NOV 1991					
07	1521	5.9	813	13	100
JAN 1992					
05	1657	706	7700	14600	87
05	1927	943	3840	9760	87
05	2052	602	2860	4650	84
07	1450	11	50	1.5	99
MAY					
16	1845	2.8	1700	13	99
SEP					
18	1622	5.3	343	5	98
22	1725	46	1340	166	98
22	1931	41	1540	170	99

50055225 RIO CAGUITAS AT VILLA BLANCA AT CAGUAS, PR

LOCATION.--Lat 18°14'55", long 66°01'40", Hydrologic Unit 21010005, on left bank, at C. 4 street Villa Blanca housing area at Caguas, 1.8 mi (2.9 km) upstream from Río Grande de Loíxa, and 0.95 mi (1.53 km) northeast from Caguas Plaza.

DRAINAGE AREA. -- 11.71 mi2 (30.33 km2).

90 PERCENT EXCEEDS

WATER-DISCHARGE RECORDS

PERIOD OF RECORD, -- December 1990 to current year.

GAGE.--Water-stage recorder. Elevation of gage is 164 ft (50 m), from topographic map.

REMARKS.--Records fair. Gage-height and precipitation satellite telemetry at station.

DISCHARGE, CUBIC FERT PER SECOND, WATER YEAR OCTOBER 1991 TO SEPTEMBER 1992 DAILY MEAN VALUES DAY OCT NOV DEC JAN FEB APR MAY JUN JUL AUG SEP 35 15 6.7 7.6 6.7 8.7 7.7 13 8.8 8.7 31 11 11 26 23 8.7 42 12 11 25 12 11 8.0 7.8 29 17 25 12 12 9.8 12 8.5 14 16 70 15 4 5 23 14 28 12 12 8.4 8.1 9.7 31 7.6 13 570 21 1930 9.3 54 19 12 16 19 30 17 15 28 7 19 1160 12 7.8 6.7 17 9.4 81 15 105 17 12 9.2 24 13 10 23 40 60 6.9 206 18 36 11 7.2 8.7 8.2 18 21 13 75 16 36 7.2 8.2 7.9 10 18 45 10 13 33 14 36 27 6.7 8.1 7.2 26 9.4 18 18 11 13 26 24 6.7 8.9 7.9 28 24 15 21 12 13 11 9.8 22 38 18 11 6.9 7.0 9.9 8.2 22 27 10 18 15 15 16 11 26 22 16 11 11 25 7.0 8.8 8.5 15 10 21 17 18 11 10 9.1 9.3 12 8.2 16 17 23 50 29 23 12 15 6.9 27 17 9.5 20 14 43 9.8 12 11 150 13 19 16 8.0 24 17 9.7 12 12 10 18 19 14 21 11 13 13 20 7.5 18 17 23 12 20 7.2 19 28 8.1 15 28 23 12 9.4 11 172 16 21 7.0 32 32 16 8.1 11 11 19 20 13 11 103 22 92 44 9.3 10 18 8.5 13 143 23 8.1 7.5 9.7 8.1 23 23 18 15 8.8 159 14 11 12 48 24 12 14 22 28 26 14 10 124 12 11 22 43 9.6 13 16 8.8 6.8 8.1 11 16 9.8 18 26 19 34 17 7.5 15 9.2 9.7 7.2 10 11 14 39 9.8 27 8.8 14 14 8.1 7.2 7.2 32 9.2 11 9.8 14 7.3 18 17 9.2 28 8.6 13 7.2 22 8.9 16 56 54 8.2 9.9 29 12 13 16 18 8.1 16 15 30 16 8.3 9.0 8.2 18 15 14 18 11 25 13 8.9 1035 1327 TOTAL 621.1 532 3716 313.8 271.5 294.4 939.4 506.6 364.0 1119.1 MEAN 20.0 34.5 120 10.8 8.76 9.81 30.3 16.9 11.7 44.2 17.2 36.1 MAX 92 206 32 1930 27 16 28 159 70 28 570 327 7.0 MIN 7.0 13 23 12 11 6.7 6.7 8.2 7.2 9.0 8.1 8.7 11 18 13 MED 16 17 11 18 16 AC-PT 1230 2050 1060 7370 622 539 1860 1000 722 2220 2630 . 92 CFSM 1.71 2.95 1.47 10.2 . 75 .84 2.59 1.44 1.00 3.08 3.78 1.97 IN. 3.29 1.00 1.61 3.56 4.22 1.69 11.80 . 86 . 94 2.98 1.16 STATISTICS OF MONTHLY MEAN DATA FOR WATER YEARS 1991 - 1992, BY WATER YEAR (WY) MEAN 20.0 34.5 17.2 70.1 17.2 12.1 23.8 13.7 18.7 25.0 30.3 11.1 MAX 20.0 34.5 17.2 120 23.8 15.3 12.4 30.3 16.9 25.6 36.1 44.2 (WY) 1992 1992 1992 1992 1991 1991 1991 1992 1992 1991 1992 1992 MIN 20.0 34.5 17.2 20.3 10.8 8.76 9.81 17.2 10.5 11.7 13.8 16.4 1992 1991 1992 1992 1991 (WY) 1991 1992 1992 1992 1991 1992 1991 SUMMARY STATISTICS FOR 1991 CALENDAR YEAR FOR 1992 WATER YEAR WATER YEARS 1991 - 1992 ANNUAL TOTAL 6891.1 11039.9 18.9 30.2 30.2 HIGHEST ANNUAL MEAN 1992 30.2 LOWEST ANNUAL MEAN HIGHEST DAILY MEAN 30.2 1992 Jan 5 1992 Jun 29 1991 360 Jul 16 1930 Jan 1930 LOWEST DAILY MEAN 6.7 5.6 Mar 5.6 Jun 29 ANNUAL SEVEN-DAY MINIMUM Mar Aug 3 1991 Aug INSTANTANEOUS PEAK FLOW INSTANTANEOUS PEAK STAGE 13400 Jan 5 13400 Jan 5 1992 5 1992 19.91 19.91 Jan Jan ANNUAL RUNOFF (AC-FT) ANNUAL RUNOFF (CFSM) 13670 21900 1.61 2.58 2.58 ANNUAL RUNOFF (INCHES) 21.89 35.07 35.00 10 PERCENT EXCEEDS 32 33 32 50 PERCENT EXCEEDS 13 13 7.2

8.1

6.8

50055225 RIO CAGUITAS AT VILLA BLANCA AT CAGUAS, PR--Continued

WATER QUALITY RECORDS

PERIOD OF RECORD .-- OCTOBER 1990 TO CURRENT YEAR

DATE	TIME	STREAMFLOW, INSTANTANEOUS (CFS)	SPECIFIC CON- DUCTANCE (UMHOS)	TEMPERA- TURE (DEG C)	DATE	TIME	STREAMFLOW, INSTANTANEOUS (CFS)	SPECIFIC CON- DUCTANCE (UMHOS)	TEMPERA- Ture (Deg C)
MAR. 03 JUN. 02		7.10 12.5	420 410	28.0 32.0	AUG. 28	1120	10	420	30.0

50055225 RIO CAGUITAS AT VILLA BLANCA AT CAGUAS, PR--Continued

WATER-QUALITY RECORDS

PERIOD OF RECORDS. -- Water years 1991 to current year.

INSTRUMENTATION .-- DH-48 and automatic sediment sampler.

PERIOD OF DAILY RECORD.--SUSPENDED-SEDIMENT DISCHARGE: December 1990 to September 1992

EXTREMES FOR PERIOD OF DAILY RECORD. --SEDIMENT CONCENTRATION: Maximum daily mean, 1,430 mg/L Jan. 05, 1992; Minimum daily mean, 5 mg/L Several days.

SEDIMENT LOADS: Maximum daily mean, 8,820 tons (8,000 tonnes) Jan. 05, 1992; Minimum daily mean, 0.16 ton (0.14 tonne) Oct. 28, 1991.

EXTREMES FOR WATER YEARS 1991-92. --

Water Year	Suspended-sediment maximum	concentration (mg/L) minimum	Suspended-sediment discharge (tons per day) maximum minimum			
1991	770 (Jul. 16)	20 (Several days)	902 (Jul. 16)	.35 (Several days)		
1992	1,430 (Jan. 06)	5 (Several days)	8,820 (Jan. 06)	.16 (Oct. 28)		

MEAN DISCHARCE CONCENS SEDIMENT MEAN DISCHARCE CONCENS SEDIMENT CONCENS CONCENS SEDIMENT CONCENS CONCENS			MRAN MRAN			Mean				
DISCHARGE Corporation Co		MRAN		SEDIMENT	MBAN		SEDIMENT	MRAN	CONCEN-	SEDIMENT
DAY CFS (MG/L) (TONS/DAY) CFS (MG/L) (TONS/DAY) CFS (MG/L) (TONS/DAY)		DISCHARGE	TRATION	DISCHARGE	DISCHARGE		DISCHARGE	DISCHARGE	TRATION	DISCHARGE
OCTOBER NOVEMBER DECEMBER 1	DAY	(CFS)						(CFS)	(MG/L)	(TONS/DAY)
1		,,	(, -,	(5 500-) 5111)	(,	(110, 2,	(10110, 5111,	,,	(, -,	(
2			OCTOBER		I	NOVEMBER		1	DECEMBER	
2										
\$										
4										
6										
6										
7	5									
7										
8										
10										
111										
11										
12	10									
12										
13										
14										
15										
16										
17	15									
17										
18										
19										
21										
21										
22	20									
22										
23										
24										
26										
26										
27 16 87 3.8 29 39 152 28 30 46 200 27 31 357 546 628	25									
27 16 87 3.8 29 39 152 28 30 46 200 27 31 357 546 628	2.0									
28 16 87 3.8 29 39 152 28 30 46 200 27 31 357 546 628						_		_		
29 39 152 28 30 46 200 27 31 357 546 628										
30 46 200 27 31 357 546 628					_					
31 357 546 628										
TOTAL	31							357	546	628
TOTAL	moma -									
	TOTAL									

50055225 RIO CAGUITAS AT VILLA BLANCA AT CAGUAS, PR--Continued

	MBAN				MBAN		mban		
	mran	CONCEN-	SEDIMENT	mran	CONCEN-	SEDIMENT	mban	CONCEN-	SEDIMENT
	DISCHARGE	TRATION	DISCHARGE	DISCHARGE	TRATION	DISCHARGE	DISCHARGE	TRATION	DISCHARGE
DAY	(CFS)	(MG/L)	(TONS/DAY)	(CFS)	(MG/L)	(TONS/DAY)	(CFS)	(MG/L)	(TONS/DAY)
	()	(,	(,,			••	, , ,	
		JANUARY		1	FEBRUARY			MARCH	
1	97	266	85	14	97	3.5	12	63	1.9
2	37	151	15	13	110	3.9	10	39	1.1
3	26	125	9.2	14	121	4.4	13	49	1.8
4	22	112	7.0	14	117	4.4	16	66	2.7
5	23	110	6.7	119	257	181	19	114	6.6
6	29	114	8.5	45	170	25	25	130	11
7	23	118	7.6	30	146	12	14	83	3.1
8	23	116	8.5	18	103	5.3	15	88	3.8
9	20	100	5.3	15	85	3.5	13	80	2.9
10	25	110	7.1	14	79	3.2	10	75	2.1
11	22	114	7.0	28	125	12	11	76	2.2
12	19	102	5.5	50	161	45	11	109	3.2
13	16	92	4.1	39	328	36	11	150	4.4
14	15	87	3.6	24	245	15	13	154	5.2
15	16	85	3.6	21	145	8.2	12	136	4.5
16	16	87		16	66		9.8	117	3.3
			3.8			3.2			
17	15	88	3.6	14	81	3.1	8.9	99	2.4
18	14	83	3.2	22	110	7.8	14	82	3.0
19	15	84	3.4	35	172	17	11	92	2.8
20	14	81	3.1	20	142	7.9	11	72	2.1
21	16	78	3.2	17	90	4.2	11	72	2.1
22	12	72	2.6	13	85	3.1	73	308	76
23	13	74	2.5	13	114	4.0	32	306	26
24	13	75	2.6	12	180	5.9	16	236	10
25	13	75	2.6	13	235	8.0	14	170	6.6
26	13	75	2.6	10	281	7.9	17	124	6.3
27	13	75	2.6	9.8	232	6.2	12	68	2.3
28	12	70	2.3	13	118	4.3	11	67	2.0
29	12	69	2.2				10	120	3.3
30	12	76	2.5				10	202	5.4
31	13	86	2.9				10	252	6.8
TOTAL	629		229.4	665.8		445.0	475.7		216.9

282

RIO GRANDE DE LOIZA BASIN

50055225 RIO CAGUITAS AT VILLA BLANCA AT CAGUAS, PR--Continued

SEDIMENT DISCHARGE, SUSPENDED (TONS/DAY), WATER YEAR OCTOBER 1990 TO SEPTEMBER 1991

	MBAN				MRAN		MBAN		
DAY	MRAN Discharge (CFS)	CONCEN- TRATION (MG/L)	SEDIMENT DISCHARGE (TONS/DAY)	MEAN Discharge (CFS)	CONCEN- TRATION (MG/L)	SEDIMENT DISCHARGE (TONS/DAY)	MRAN DISCHARGE (CFS)	CONCEN- TRATION (MG/L)	SEDIMENT DISCHARGE (TONS/DAY)
		APRIL			MAY			JUNE	
1	10	218	5.9	10	44	1.2	11	25	.77
2	10	145	3.9	9.6	47	1.2	10	25	.70
3	īĭ	92	2.6	13	51	1.8	9.5	26	. 67
4	12	71	2.2	9.2	57	1.4	10	27	.72
5	13	74	2.5	8.7	60	1.4	15	69	3.9
6	13	75	2.6	10	68	2.1	15	59	3.7
7	13	75	2.6	16	84	4.1	11	29	. 86
8	38	128	19	26	115	12	10	79	2.0
9	16	80	3.4	19	101	5.4	8.5	103	2.3
10	11	65	1.9	15	74	3.3	7.4	89	1.7
11	13	79	3.3	34	142	18	9.5	63	2.2
12	23	109	9.9	36	142	19	14	65	3.3
13	21	106	7.0	14	63	2.5	7.9	21	.43
14	12	77	2.6	13	80	2.7	7.2	21	.40
15	14	86	3.5	13	132	4.6	7.7	21	. 43
16	12	95	3.2	13	168	5.7	7.8	21	.43
17	9.8	95	2.6	12	125	4.1	6.7	21	.38
18	9.5	88	2.2	23	111	7.7	6.5	21	. 37
19	9.5	68	1.7	43	149	26	6.7	22	.39
20	9.8	43	1.1	26	110	9.4	6.3	22	.35
21	11	33	. 96	17	93	4.7	6.5	22	.41
22	10	30	. 84	16	51	2.4	6.5	22	.39
23	9.0	36	. 84	13	23	.77	13	64	3.7
24	8.9	44	1.0	12	34	1.1	7.8	39	.88
25	9.3	42	1.0	37	120	17	6.3	25	.43
26	8.9	40	. 94	17	44	2.0	7.6	29	. 57
27	8.6	40	.94	13	33	1.2	5.8	30	.49
28	8.1	40	.88	12	28	.91	6.7	47	1.0
29	7.9	41	.84	12	25	.78	5.6	49	.76
30	8.5	48	1.2	11	25	.74	61	190	108
31				10	25	.68			
TOTAL	370.8		93.14	533.5		165.88	314.5		142.63

/

50055225 RIO CAGUITAS AT VILLA BLANCA AT CAGUAS, PR--Continued

		MEAN			MRAN			MEAN	
DAY	MRAN DISCHARGE (CFS)	CONCEN- TRATION (MG/L)	SEDIMENT DISCHARGE (TONS/DAY)	MBAN Discharge (CFS)	CONCEN- TRATION (MG/L)	SEDIMENT DISCHARGE (TONS/DAY)	MRAN DISCHARGE (CFS)	CONCEN- TRATION (MG/L)	SEDIMENT DISCHARGE (TONS/DAY)
		JULY			AUGUST		gi	eptember	
1	93	232	100	e7.0	39	e.62	e7.8	50	e1.2
2	16	128	6.1	e6.4	43	6.74	e8.0	44	e. 95
3	9.0	65	1.6	e6.0	47	e.75	e7.8	49	e.98
4	8.1	42	.91	e5.8	45	e.71	e7.8	70	e1.4
5	8.1	51	1.1	e5.8	41	e.64	e7.4	88	e1.8
6	7.6	80	1.7	e 6.0	40	e.64	e7.1	97	e1.9
7	10	99	2.8	e6.0	40	e.64	e7.4	99	e1.9
8	12	71	2.5	e6.0	40	e.64	e7.7	101	e2.1
9	11	70	2.0	e5.8	103	e1.7	e8.0	100	e2. 6
10	7.3	42	. 87	e 6.0	89	e1.5	e8.1	48	e1.0
11	6.8	25	.46	e5.8	63	e.98	e7. 9	32	e. 69
12	6.7	24	.44	e 6.0	45	e.73	e7.7	27	e.57
13	6.4	29	. 51	e5.8	40	e.62	e7.7	44	e.90
14	6.3	32	. 54	e6.0	60	e.97	e7.8	71	e1.5
15	55	142	64	e6.1	83	e1.3	e7. 3	75	e1.5
16	360	770	902	e6.6	55	e.93	e7.4	70	e1.4
17	30	163	14	e6.8	40	e.90	e120	352	e166
18	18	132	6.6	e6.2	36	e.59	e15	149	e6.7
19	19	134	8.1	e 6.0	32	e.51	e2 0	152	e21
20	14	91	3.5	e 6.0	31	e.50	e13	116	e5.3
21	10	72	2.0	e7.0	45	e.86	e15	139	e8.0
22	9.3	50	1.3	e65	205	e140	e25	152	e13
23	9.1	38	.88	e20	105	e7.1	e27	178	e22
24	12	69	2.7	e 9.0	49	e1.2	e18	68	e2.8
25	8.7	36	. 85	e8.3	40	e.89	e13	41	e1.7
26	6.9	21	.39	e8.0	39	e.86	e11	34	e1.1
27	6.7	20	. 35	e126	353	e223	e12	32	e.96
28	6.4	20	.36	e37	308	e39	e21	86	e5.9
29	e6.4	22	0.41	e9.2	108	e2.7	e 35	195	e25
30	e6.4	29	e.55	e8.4	69	e1.6	e25	127	e6.8
31	e 6.6	38	e.65	e 8.0	52	e 1.1			
TOTAL	792.8		1130.17	428.0		434.92	492.9		308.65

e Estimated

50055225 RIO CAGUITAS AT VILLA BLANCA AT CAGUAS, PR--Continued

		MBAN			MRAN			MBAN	
DAY	MEAN DISCHARGE (CFS)	CONCEN- TRATION (MG/L)	SEDIMENT DISCHARGE (TONS/DAY)	MRAN Discharge (CFS)	CONCEN- TRATION (MG/L)	SEDIMENT DISCHARGE (TONS/DAY)	MEAN DISCHARGE (CFS)	CONCEN- TRATION (MG/L)	SEDIMENT DISCHARGE (TONS/DAY)
		OCTOBER		Ī	NOVEMBER		1	DECRMBER	
1	31	74	6.4	35	116	24	15	22	. 90
2	42	93	11	23	56	3.6	16	13	.57
3	29	44	3.7	17	49	2.5	25	47	4.6
4	23	17	1.1	14	17	. 65	28	30	2.4
5	21	11	. 63	13	10	.36	19	13	. 67
6	19	12	. 61	30	54	7.9	17	12	. 56
7	15	8	.34	105	224	121	17	10	. 44
8	15	7	.31	206	328	278	18	8	.41
9	13	8	.29	75	286	86	16	7	.30
10	13	10	. 34	33	70	6.4	14	5	.20
11	13	12	.40	26	30	2.1	14	5	.19
12	11	12	. 35	22	16	.99	18	5	.23
13	9.8	11	. 27	38	59	14	16	5	. 23
14	9.4	10	. 25	25	55	3.8	22	5	. 27
15	10	10	. 27	21	39	2.2	17	5	.22
16	9.5	10	.28	23	27	1.7	14	5	. 19
17	9.5	10	. 25	20	19	1.0	14	5	.20
18	8.0	10	. 22	19	13	. 68	14	5	.20
19	7.5	10	. 20	18	10	.49	14	5	.20
20	7.2	10	.20	19	10	.52	28	40	5.1
21	7.0	10	. 19	32	48	10	32	72	6.7
22	92	165	213	44	46	6.9	18	28	1.4
23	23	59	4.5	23	9	.58	18	10	.48
24	12	28	. 97	26	24	2.2	14	14	. 54
25	9.6	14	. 37	22	6	.34	13	28	1.0
26	9.2	8	.21	19	5	.26	14	41	1.5
27	8.8	7	. 17	34	72	9.3	14	26	. 99
28	8.6	7	. 16	18	24	1.2	13	14	. 47
29	56	103	121	17	10	.45	12	7	. 23
30	54	112	58	18	31	1.7	15	26	1.5
31	25	61	4.6				13	35	1.2
TOTAL	621.1		430.58	1035		590.82	532		34.09

50055225 RIO CAGUITAS AT VILLA BLANCA AT CAGUAS, PR--Continued

DAY	MRAN DISCHARGE (CFS)	MEAN CONCEN- TRATION (MG/L)	SEDIMENT DISCHARGE (TONS/DAY)	MEAN DISCHARGE (CFS)	MEAN CONCEN- TRATION (MG/L)	SRDIMENT DISCHARGE (TONS/DAY)	MRAN DISCHARGE (CFS)	MEAN CONCEN- TRATION (MG/L)	SEDIMENT DISCHARGE (TONS/DAY)
		JANUARY		1	FEBRUARY			MARCH	
1	11	33	1.0	11	15	.46	6.7	63	1.1
2	12	30	. 95	11	16	.49	7.6	66	1.3
3	12	27	. 85	12	17	.56	6.7	67	1.2
4	12	23	. 73	12	18	.58	8.4	64	1.5
5	1930	621	8220	12	18	.56	9.3	59	1.5
6	1160	1430	6730	12	17	.53	7.8	50	1.1
7	60	93	17	13	15	.52	6.9	43	.80
8	36	21	2.0	11	14	.43	7.2	39	.76
9	36	34	5.1	11	12	.37	7.2	37	.73
10	36	83	8.0	27	55	5.2	6.7	38	.68
11	24	48	3.2	12	17	.57	6.7	39	.70
12	21	30	1.7	11	15	.45	6.9	40	.75
13	22	20	1.2	11	13	.39	7.0	40	.74
14	19	14	.73	13	27	1.1	7.0	38	.73
15	18	11	. 52	11	29	.87	10	36	1.0
16	50	225	155	9.9	25	.66	6.9	34	. 62
17	43	240	53	9.8	25	.65	12	32	1.1
18	21	21	1.2	9.7	29	.77	12	30	. 99
19	17	20	. 93	9.2	39	. 98	12	28	. 85
20	16	18	.80	8.1	50	1.1	15	26	1.1
21	16	13	. 55	8.1	55	1.2	11	25	.78
22	16	9	.38	9.3	55	1.4	8.5	25	.56
23	15	8	. 32	8.8	54	1.3	8.1	26	.56
24	14	6	. 25	10	51	1.4	7.5	26	. 53
25	16	5	.22	8.8	47	1.1	6.8	25	.47
26	17	5	.20	9.7	45	1.2	7.2	23	.44
27	14	5	.18	8.1	46	1.0	7.2	21	.40
28	13	6	.22	7.3	52	1.0	12	30	1.5
29	13	8	.31	7.0	58	1.1	16	54	2.6
30	14	11	.40				8.3	36	. 82
31	12	14	. 45				8.9	35	. 84
TOTAL	3716		15207.39	313.8		27.94	271.5		28.75

50055225 RIO CAGUITAS AT VILLA BLANCA AT CAGUAS, PR--Continued

		MBAN			MRAN			MEAN	
DAY	MEAN DI SCHARGE (CFS)	CONCEN- TRATION (MG/L)	SEDIMENT DISCHARGE (TONS/DAY)	MEAN Discharge (CFS)	CONCEN- TRATION (MG/L)	Sediment Discharge (Tons/Day)	MRAN DISCHARGE (CFS)	CONCEN- TRATION (MG/L)	SEDIMENT DISCHARGE (TONS/DAY)
		APRIL			MAY			JUNE	
1	8.7	37	. 85	26	84	13	13	61	2.1
2	7.7	36	.75	25	63	5.6	12	59	2.0
3	8.0	29	,62	9.8	40	1.1	12	57	1.9
4	7.8	22	.47	8.1	33	.72	70	157	81
5	7.6	19	. 38	7.2	29	.56	19	50	2.7
6	6.7	16	.29	17	80	4.0	15	37	1.7
7	12	36	1.3	10	95	2.6	23	58	5.4
8	8.7	29	. 66	8.2	92	2.0	18	49	2.5
9	8.2	26	. 57	7.9	90	2.0	14	44	1.7
10	8.1	25	. 54	7.2	87	1.7	26	59	5.5
11	8.9	24	.59	7.9	83	1.8	18	42	2.1
12	9.9	25	. 67	22	99	11	27	77	7.2
13	8.2	25	. 56	11	70	2.2	26	54	4.0
14	7.8	25	. 52	8.8	56	1.3	14	35	1.3
15	9.1	22	. 55	9.3	45	1.1	12	30	. 94
16	8.1	19	.42	29	70	10	23	35	3.0
17	11	27	. 97	150	240	391	13	10	. 37
18	10	26	.74	24	108	8.5	11	10	.30
19	23	53	8.6	17	57	2.8	12	10	.32
20	28	65	6.3	23	69	5.3	12	9	.28
21	11	29	. 86	19	94	4.8	20	57	3.5
22	10	27	.71	22	77	4.9	13	24	. 87
23	9.7	29	. 76	159	313	403	14	18	. 68
24	8.1	30	. 67	124	251	190	12	14	.47
25	8.1	29	. 64	43	92	12	11	11	. 32
26	7.5	27	. 56	39	90	10	10	24	. 68
27	7.2	25	. 50	32	76	7.2	9.2	21	.52
28	7.2	24	.45	22	49	2.9	9.2	18	.44
29	8.2	23	. 61	18	52	2.5	9.2	18	. 45
30 31	9.9	61	1.6	18	56	2.8	9.0	19	.47
31				15	60	2.5			
TOTAL	294.4		33.71	939.4		1110.88	506.6		134.71

50055225 RIO CAGUITAS AT VILLA BLANCA AT CAGUAS, PR--Continued

		MEAN			MBAN			MBAN	
	MEAN DISCHARGE	CONCEN- TRATION	SEDIMENT DISCHARGE	MEAN DISCHARGE	CONCEN- TRATION	SEDIMENT DISCHARGE	Mran Discharge	CONCEN- TRATION	Sediment Discharge
DAY	(CFS)	(MG/L)	(TONS/DAY)	(CFS)	(MG/L)	(TONS/DAY)	(CFS)	(MG/L)	(TONS/DAY)
		JULY			AUGUST		SI	EPTEMBER	
1	8.8	22	. 52	8.7	21	.49	14	29	1.1
2	8.7	27	. 62	11	17	.51	11	20	. 59
3	8.5	31	.71	14	32	2.3	16	14	.58
4	9.7	36	.95	31	145	24	15	10	.41
5	16	84	3.7	570	526	2080	54	127	42
6	9.4	87	2.3	81	321	127	28	71	5.4
7	9.2	75	1.9	40	76	11	24	54	3.4
8	16	48	2.2	24	56	3.9	21	56	5.0
9	10	18	.50	18	39	1.9	45	100	18
10	9,4	10	.25	18	33	1.6	18	25	1.2
11	28	54	13	24	97	8.3	15	26	1.1
12	10	27	.76	18	62	3.1	15	28	1.1
13	11	47	1.6	16	48	2.0	15	29	1.1
14	8.5	59	1.4	18	36	1.7	15	30	1.3
15	8.2	43	. 93	16	28	1.2	17	31	1.4
16	12	36	1.3	15	24	.94	42	104	14
17	19	39	2.5	16	22	. 97	27	61	4.7
18	13	7	.24	13	20	. 69	20	34	1.8
19	11	18	. 57	12	19	.61	327	724	1780
20	9.4	33	. 83	11	25	.71	172	1090	5 79
21	13	38	1.7	11	33	1.0	103	443	139
22	19	52	3.4	12	38	1.2	143	367	177
23	11	32	. 90	12	39	1.2	48	150	22
24	11	30	.91	22	62	4.6	28	253	18
25	16	37	1.8	9.8	32	.83	18	295	14
26	11	25	.78	9.8	26	. 69	15	120	5.0
27	11	21	.59	9.8	24	.63	14	27	1.0
28	8.9	16	.38	11	20	. 58	16	19	.80
29	8.1	15	.31	16	45	2.5	15	19	.77
30	8.2	13	.29	11	53	1.6	16	21	.90`
31	11	29	1.0	20	38	2.0			
TOTAL	364.0		48.84	1119.1		2289.75	1327		2841.65
YRAR	11039.9		22779.11						

50055225 RIO CAGUITAS AT VILLA BLANCA AT CAGUAS, PR--Continued WATER QUALITY DATA, WATER YEARS JULY 1991 TO SEPTEMBER 1992

PARTICLE-SIZE DISTRIBUTION OF SUSPENDED SEDIMENT

		DIS- CHARGE, INST. CUBIC FRET	SEDI - MENT, SUS-	SEDI- MENT, DIS- CHARGE, SUS-	SED. SUSP. FALL DIAM. PERCENT FINER	SED. SUSP. FALL DIAM. PERCENT FINER	SED. SUSP. FALL DIAM. PERCENT FINER
DATE	TIME	PER	PENDED	PENDED	THAN	THAN	THAN
		SECOND	(MG/L)	(T/DAY)	.002 MM	.004 MM	.008 MM
JUL 1991							
16	1348	427	2010	2320	55	66	72
AUG	1.10	/		-5-0		•	′-
22	1102	393	2330	2470	35	42	48
27	1610	774	1260	2630	43		49
OCT							
22	1622	869	1800	4200	37	46	53
NOV 08	2322	202	1170	000	60	67	
JAN 1992	4344	292	1170	922	60	0/	
05	1702	2882	4450	34600	39	50	68
05	1952	8476	2540	58100	43	52	62
MAY							
17	1855	1190	3350	10700	35	41	48
DATE	SED. SUSP. FALL DIAM. PERCENT THAN THAN	SED. SUSP. FALL DIAM. PERCENT FINER THAN .031 MM	SED. SUSP. SIEVE DIAM. PERCENT FINER THAN .062 MM	SED. SUSP. SIEVE DIAM. PERCENT FINER THAN .125 MM	SED. SUSP. SIEVE DIAM. PERCENT FINER THAN .250 MM	SED. SUSP. SIEVE DIAM. PERCENT FINER THAN .500 MM	SED. SUSP. SIEVE DIAM. PERCENT FINER THAN 1.00 MM
JUL 1991							
16	78	82	97	98	99	99.8	100
AUG							
22 27	60	69 69	86	93	97	98	99
OCT		69	94	98	99	100	100
22	64	71	90	95	98	99	100
NOV		• -					
08	70	74	98	99	99.6	100	100
JAN 1992							
05	75	81	98	99.3	99.8	100	100
05	75	81	98	99	99.8	100	100
МАҮ 17	60	70	0.4	07			100
1/	60	72	94	97	99	99.7	100

50055225 RIO CAGUITAS AT VILLA BLANCA AT CAGUAS, PR--Continued
WATER QUALITY DATA, WATER YEAR OCTOBER 1991 TO SEPTEMBER 1992
SILT AND CLAY PERCENT OF SUSPENDED SEDIMENT

D ATE	TIME	STREAM- FLOW, INSTAN- TANEOUS (CFS)	SEDI- MENT, SUS- PENDED (MG/L)	SRDI- MENT, DIS- CHARGE, SUS- PENDED (T/DAY)	SED. SUSP. SIEVE DIAM. PERCENT FINER THAN .062 MM
OCT 1991					
22	1642	1310	1360	4820	97
22	1740	264	615	439	94
NOV					
07	1243	106	266	76	99
08	1902	537	1020	1470	91
08	2027	484	440	575	90
08	2212	455	904	1110	98
DBC					
26	1253	13	47	2	96
JAN 1992					
05	1622	1050	1130	3210	98
05	2007	8450	771	17600	99
05	2202	2490	1750	1170	99
16	2052	488	2170	2860	77
16	2242	135	1270	464	77
17	0027	122	1135	374	77
MAY					
17	1655	604	1470	2400	84
24	1255	57	175	27	98
JUN					
03	1524	12	336	11	98
AUG					
05	0357	298	723	582	90
SEP	1700	1204	2000	7010	
19	1722	1394	2080	. 7810	84
19	2120	1080	2120	6200	88
22	1357	267	1680	1210	79

50055250 RIO CAGUITAS AT HIGHWAY 30 AT CAGUAS, PR

WATER-QUALITY RECORDS

LOCATION.--Lat 18°15'11", long 66°01'26", at Highway 30 bridge, and 0.8 mi (1.3 km) east of Caguas plaxa. DRAINAGE AREA.--14.1 mi $^{\circ}$ (36.5 km $^{\circ}$).

PERIOD OF RECORD. -- Water years 1972 to current year.

WATER-QUALITY DATA, WATER YEAR OCTOBER 1991 TO SEPTEMBER 1992

DATE	TIME	CHARCE INST	GE, SPI C. CII IC CON ET DUC R ANG	PIC WHO V- PIE CT- (STA CB AF	'ER OLE ELD TEM IND- AT ID WA	PBR- URB TBR G C)	TUR BID ITY (NTU	- DI SOL	SEN, (I S- (I VED SA	GEN, DIS- DLVED PER- CENT ATUR- TION)	OXYGEN DEMANI CHEM- ICAL (HIGH LEVEL) (MG/L)	PORM PECA 0.45 UM-M (COLS	, STREP- L, TOCOCCI FECAL, F (COLS. ./ PER
OCT 1991													7106000
08 Dec	1050	38		564	7.3	28.0	15		1.5	39	25	350000	K106000
06	0945	41		594	7.3	25.5	3.	4	0.9	21	59	350000	33000
PEB 1992 13	0910	33		644	7.1	25.5	1.:	1	2.0	64	84	6600	3600
MYA	1110	•	•					•			05	20000	71100
05 Jun	1110	9	. 1	651	6.7	28.5	3.	y	2.3	48	85	20000	K1100
10 Aug	1000	31		517	6.6	28.0	14		2.6	53	62	K100000	59000
20	1040	28		630	7.0	30.0	3.	0	1.6	41	67	2900	2400
DATE OCT 1991	NE TO (1	ARD- SSS YTAL IG/L AS ACO3)	CALCIUM DIS- SOLVED (MG/L AS CA)	MAGNE- SIUM, DIS- SOLVED (MG/L AS MG)	SODIUM, DIS- SOLVED (MG/L AS NA)	SOF	ON	POTAS- SIUM, DIS- SOLVED (MG/L AS K)	ALKA- LINITY WAT WH TOT FET FIBLD MG/L AS CACO3	TO:	FIDE FAL 3/L	GULFATE DIS- SOLVED (MG/L AS SO4)	CHLO- RIDE, DIS- SOLVED (MG/L AS CL)
08		110	25	11	26		1	5.2	170	•	<0.5	14	29
06 FRB 1992						-			160	•			
13						-			180	•			
MAY 05 JUN		140	38	12	48		2	7.6	170		<0.5	52	61
10						-			90				
AUG		140	38	••	40							5 4	59
20		140	36	12	49		2	7.0	110		- -	51	39
DATE	R] I S(()	LUO- IDE, DIS- DLVED 4G/L E P)	SILICA, DIS- SOLVED (MG/L AS SIO2)	SOLIDS, SUM OF CONSTI- TUENTS, DIS- SOLVED (MG/L)	SOLIDS, DIS- SOLVED (TONS PER DAY)	TOTA AT 1 DEG. SUS PENI	L05 . C, 1 3-	NITRO- GEN, NITRATE TOTAL (MG/L AS N)	NITRO- GEN, NITRITE TOTAL (MG/L AS N)	GI NO2- TO (M	TRO- EN, +NO3 A TAL G/L N)	NITRO- GEN, MMONIA TOTAL (MG/L AS N)	NITRO- GEN, ORGANIC TOTAL (MG/L AS N)
OCT 1991													
08		0.10	29	241	24.5		30	1.58	0.220) 1	.80	9.00	4.0
06 FRB 1992							16	0.230	0.130	0	.360	8.70	2.3
13							25	0.120	0.060	0	.180	11.0	5.0
MAY 05 JUN		0.20	29	350	9.16		10	0.100	0.080	0	.180	13.0	5.0
10							23	0.510	0.100	0	.610	6.80	2.5
AUG 20		0.20	28	344	26		6	0.130	0.080	0	.210	0.610	13

K = non-ideal count

RIO GRANDE DE LOIZA BASIN

50055250 RIO CAGUITAS AT HIGHWAY 30 AT CAGUAS, PR--Continued WATER-QUALITY DATA, WATER YEAR OCTOBER 1991 TO SEPTEMBER 1992

DATE	NITRO- GEN, AM- MONIA + ORGANIC TOTAL (MG/L AS N)	NITRO- GEN, TOTAL (MG/L AS N)	NITRO- GEN, TOTAL (MG/L AS NO3)	PHOS- PHORUS TOTAL (MG/L AS P)	ARSENIC TOTAL (UG/L AS AS)	BARIUM, TOTAL RECOV- ERABLE (UG/L AS BA)	BORON, TOTAL RECOV- ERABLE (UG/L AS B)	CADMIUM TOTAL RECOV- RRABLE (UG/L AS CD)	CHRO- MIUM, TOTAL RECOV- ERABLE (UG/L AS CR)	COPPER, TOTAL RECOV- ERABLE (UG/L AS CU)
OCT 1991										
08 Dec	13	15	66	3.00	<1	<100	<10	<1	<1	<10
06 FEB 1992	11	11	50	3.10						
13	16	16	72	3.30						
05	18	18	80	3.60	<1	<100	120	<1	5	20
10	9.3	9.9	44	2.90						
20	14	14	63	2.70						
DATE	IRON, TOTAL RECOV- ERABLE (UG/L AS FE)	LEAD, TOTAL RECOV- ERABLE (UG/L AS PB)	MANGA- NESE, TOTAL RECOV- BRABLE (UG/L AS MN)	MERCURY TOTAL RECOV- ERABLE (UG/L AS HG)	SELE- NIUM, TOTAL (UG/L AS SE)	SILVER, TOTAL RECOV- ERABLE (UG/L AS AG)	ZINC, TOTAL RECOV- BRABLE (UG/L AS ZN)	CYANIDE TOTAL (MG/L AS CN)	PHENOLS TOTAL (UG/L)	METHY- LENE BLUE ACTIVE SUB- STANCE (MG/L)
OCT 1991	TOTAL RECOV- ERABLE (UG/L AS FE)	TOTAL RECOV- ERABLE (UG/L AS PB)	NESE, TOTAL RECOV- ERABLE (UG/L AS MN)	TOTAL RECOV- ERABLE (UG/L AS HG)	NIUM, TOTAL (UG/L AS SE)	TOTAL RECOV- ERABLE (UG/L AS AG)	TOTAL RECOV- ERABLE (UG/L AS ZN)	TOTAL (MG/L AS CN)	TOTAL (UG/L)	LENE BLUE ACTIVE SUB- STANCE (MG/L)
OCT 1991 08 DBC	TOTAL RECOV- ERABLE (UG/L AS FE)	TOTAL RECOV- ERABLE (UG/L	NESE, TOTAL RECOV- BRABLE (UG/L	TOTAL RECOV- ERABLE (UG/L AS HG)	NIUM, TOTAL (UG/L AS SE)	TOTAL RECOV- ERABLE (UG/L	TOTAL RECOV- ERABLE (UG/L AS ZN)	TOTAL (MG/L	TOTAL (UG/L)	LENE BLUE ACTIVE SUB- STANCE (MG/L)
OCT 1991 08	TOTAL RECOV- ERABLE (UG/L AS FE)	TOTAL RECOV- ERABLE (UG/L AS PB)	NESE, TOTAL RECOV- ERABLE (UG/L AS MN)	TOTAL RECOV- ERABLE (UG/L AS HG)	NIUM, TOTAL (UG/L AS SE)	TOTAL RECOV- ERABLE (UG/L AS AG)	TOTAL RECOV- ERABLE (UG/L AS ZN)	TOTAL (MG/L AS CN)	TOTAL (UG/L)	LENE BLUE ACTIVE SUB- STANCE (MG/L)
OCT 1991 08 DEC 06	TOTAL RECOV- ERABLE (UG/L AS FE)	TOTAL RECOV- ERABLE (UG/L AS PB)	NESE, TOTAL RECOV- ERABLE (UG/L AS MN)	TOTAL RECOV- ERABLE (UG/L AS HG)	NIUM, TOTAL (UG/L AS SE)	TOTAL RECOV- ERABLE (UG/L AS AG)	TOTAL RECOV- ERABLE (UG/L AS ZN)	TOTAL (MG/L AS CN)	TOTAL (UG/L)	LENE BLUE ACTIVE SUB- STANCE (MG/L)
OCT 1991 08 DEC 06 FEB 1992 13 MAY 05	TOTAL RECOV- ERABLE (UG/L AS FE)	TOTAL RECOV- ERABLE (UG/L AS PB)	NESE, TOTAL RECOV- BRABLE (UG/L AS MN)	TOTAL RECOV- ERABLE (UG/L AS HG) <0.10	NIUM, TOTAL (UG/L AS SE)	TOTAL RECOV- ERABLE (UG/L AS AG) <1	TOTAL RECOV- ERABLE (UG/L AS ZN) <10	TOTAL (MG/L AS CN) <0.010	TOTAL (UG/L) 1	LENE BLUE ACTIVE SUB- STANCE (MG/L)
OCT 1991 08 DEC 06 FEB 1992 13	TOTAL RECOV- BRABLE (UG/L AS FE) 1300	TOTAL RECOV- ERABLE (UG/L AS PB)	NESE, TOTAL RECOV- BRABLE (UG/L AS MN)	TOTAL RECOV- ERABLE (UG/L AS HG) <0.10	NIUM, TOTAL (UG/L AS SE) <1	TOTAL RECOV- ERABLE (UG/L AS AG) <1	TOTAL RECOV- ERABLE (UG/L AS ZN)	TOTAL (MG/L AS CN) <0.010	TOTAL (UG/L) 1	LENE BLUE ACTIVE SUB- STANCE (MG/L) 0.06

292

RIO GRANDE DE LOIZA BASIN

50055390 RIO BAIROA AT BAIROA, PR

LOCATION.--Lat 10°15'32", long 66°02'24", Hydrologic Unit 21010005, on left bank, in the Bairoa Housing Area, 1.6 mi (2.6 km) northwest of Plaza de Caguas, 4.1 mi (6.6 km) east of Plaza de Aguas Buenas, and 0.9 mi (1.4 km) northwest of Escuela Pepita Garriga.

DRAINAGE AREA. -- 5.08 mi 3 (13.15 km²).

WATER-DISCHARGE RECORDS

PERIOD OF RECORD. -- November 1990 to current year.

GAGE.--Water-stage recorder and crest-stage gage. Elevation of gage is 131 ft (40 m), from topographic map.

REMARKS.--Records poor. Gage-height and precipitation satellite telemetry at station. Mean daily discharge affected by domestic discharge from nearby station.

AIIec	ted by d	omest1C	discharge	IFOR REAL	y station	•						
	DI	SCHARGE,	CUBIC FRE	T PER SECO	ND, WATER		TOBER 199	1 TO SEPTI	EMBER 199	2		
DAY	OCT	NOV	DRC	JAN	FRB	MAR	APR	MAY	JUN	JUL	AUG	SEP
1	e4. 0	17	3.9	e3.8	e3.3	3.0	e2. 3	e2.5	5.1	e2.8	3.6	5.4
2	e7.0	11	3.9	e3.6	e3.4	2.8	e2.4	e3.2	5.0	e2.8	3.8	3.4
3	3.9	4.7	e5.6	e3.6	e3.5	2.8	e2.4	e2. 7	4.0	e2.7	4.9	3.2
4	3.2	4.8	e6.4	e3.6	e3.5	2.8	e2.4	e2. 3	9.4	e3.1	15	8.3
5	4.0	8.9	4.6	e180	e3.5	2.8	e2.3	e2.2	3.8	e5.2	82	4.4
6	3.2	5.8	4.3	e100	e3.5	2.8	e2.4	e2.6	4.8	e3.0	18	11
7	3.2	18	3.9	e10	e3.4	2.8	e2.7	e2. 5	5.1	e2.8	9.5	49
8	3.2	57	3.8	e6.0	e3.5	e2.6	e2.6	e2. 3	5.6	e5.2	5.8	4.0
9 10	3.3 3.2	21 6.7	3.9 3.9	e5.4 5.8	e3.6 e4.3	e2.6 e2.7	e2.4 e2.3	e2.2 e2.1	5.9 5.5	e3.2 e3.0	4.7 4.5	7.5 3.6
	J	• • • •	3.3	3.0	34.5	02. ,	02.5	52. 1	3.3	03.0	•••	3.5
11	3.1	e5.3	3.9	4.1	e3.6	e2.6	e2.4	e2.2	e4.5	e12	5.7	4.4
12	3.1	e4.8	3.9	3.8	e3.4	e2.5	e2.6	e 3.0	e8.6	e7.6	5.1	3.1
13 14	3.0 3.3	e4.6 e4.4	e4.9 e5.2	4.1 3.5	e3.4 e3.4	e2.5 e2.4	e2.4 e2.2	e2.7 e2.4	e8.2 e4.5	5.7 6.1	4.4	3.9 2.8
15	3.8	e4.2	4.0	3.2	e3.4	e2.7	e2.2	62.5	e3.8	6.7	4.4	2.9
			• • •						••••			
16	3.4	e4 .0	3.8	22	e3.5	e2.6	e2.2	e3.5	e7.4	6.1	4.2	3.1
17	3.3	3.8	3.7	8.2	e3.4	e5.2	e2.4	64.7	e4.1	5.6	4.3	3.4
18 19	3.0 3.0	3.8 3.8	3.6 3.6	e4.4 e3.9	e3.4 e3.4	e2.8 e2.7	e3.7 e7.4	e3.4 e4.3	e3.5 e3.8	4.2 3.7	4.3	3.3 e88
20	2.9	3.9	e15	e3.8	e3.2	e2.6	e3.5	e4.7	e3.8	3.5	3.8	e35
21	3.7	9.2	e9.2	e3.8	e3.3	e2 · 5	e2.9	e6.4	e6.4	3.9	3.6	e10
22 23	5.0	16 12	4.1	e3.7 e3.7	e3.2	e2.5 e2.4	e2.5 e2.4	e4.6 e32	e4.2 e4.5	3.8 5.0	3.7 3.4	3.9 3.5
24	4.6 3.3	8.8	4.0 3.8	e3.7	3.7 4.0	e2.3	e2.4	e30	e3.8	4.1	3.8	3.5
25	3.0	6.3	3.8	e3.8	3.3	e2.3	e2.2	e14	e3.5	4.1	3.2	3.6
26	3.0	6.1	3.7	e3.7	3.2	e2.3	e2.2	e12	e3.2	3.7	3.4	3.7
27	2.9	10	3.8	e3.6	3.6	e2.3	e2.2	e10	e3.0	3.7	e2.9 e3.5	3.8 4.0
28 29	2.7 5.1	4.3	3.8 3.8	e3.6 e3.6	3.5 3.4	e33 e4.0	e2.2 e2.1	7.9 6.7	e3.0 e3.0	3.6 3.2	e5.2	4.2
30	24	4.0	3.8	e3.6		e2.7	e2.2	5.9	e2.9	3.2	e3.5	4.2
31	5.9		3.8	e3.4		e2.4		5.3		3.1	3.8	
mom t											026.0	204.4
TOTAL MEAN	133.3 4.30	278.3 9.28	143.4 4.63	423.0 13.6	100.7 3.47	115.0 3.71	78.4 2.61	192.8 6.22	143.9 4.80	136.4 4.40	236.9 7.64	294.1 9.80
MAX	24	57	15	180	4.3	3.71	7.4	32	9.4	12	82	88
MIN	2.7	3.8	3.6	3.2	3.2	2.3	2.1	2.1	2.9	2.7	2.9	2.8
MBD	3.3	5.6	3.9	3.8	3.4	2.6	2.4	3.4	4.3	3.7	4.3	3.9
AC-FT	264	552	284	839	200	228	156	382	285	271	470	583
CFSM IN.	.85 .98	1.83	.91 1.05	2.69 3.10	.68 .74	.73 .84	.51 .57	1.22 1.41	.94 1.05	.87 1.00	1.50 1.73	1.93 2.15
144.	. , 0	2.04	1.03	3.10	.,•	.04		1.41	1.03	1.00	1.75	2.13
e Ba	timated											
STATIST	CICS OF M	ONTHLY M	IBAN DATA I	OR WATER Y	TEARS 1991	- 1992,	BY WATER	YEAR (WY))			
										46 -		
MBAN MAX	14.8 25.3	8.38 9.28	7.46 10.3	10.8 13.6	5.99 8.60	4.44 5.18	3.18 3.76	6.09 6.22	4.58	10.5 16.5	5.87 7.64	7.15 9.80
(WY)	1991	1992	1991	1992	1991	1991	1991	1992	1992	1991	1992	1992
MIN	4.30	7.48	4.63	7.91	3.47	3.71	2.61	5.96	4.37	4.40	4.09	4.50
(WY)	1992	1991	1992	1991	1992	1992	1992	1991	1991	1992	1991	1991
SUMMARY	STATIST	ICS	FOR	1991 CALEN	DAR YEAR	P	OR 1992 W	ATER YEAR		WATER Y	BARS 1991	- 1992
ANNUAL	TOTAL			2405.1 6.59			2276.2				_	
WINDWT	MBAN 'ANNUAL :			6.59	•		6.2	2		7. 4 8.7	6 1	1991
	ANNUAL M									6.2	2	
HIGHEST	DAILY M	BAN		191	Jul 16		180	Jan 5		191	_ Jul	16 1991
Lowest	DAILY ME	AN		2.6	Jun 16		2.1	Apr 29		2.1	Apr	29 1992
ANNUAL	SEVEN-DA	Y MINIMU	M.	2.8	Jul 16 Jun 16 Jun 13		2.2	Apr 24		2.2	λpr	24 1992
THOUANN	ANDOUS P	DVV LTVA	1				1580	Jan 5		1580	Jan	5 1992
TUSLVAI	RUNOFF (MAN STAG AC-FT)	••	4770			4510	Jan 5 Apr 29 Apr 24 Jan 5 2 Jan 5		5410	- Jan	3 1334
ANNUAL	RUNOFF (CFSM)	.5	1.30			1.2	2		1.4	7	
ANNUAL	RUNOFF (INCHES)		17.61			16.6			19.9		
10 PERC	RML BYCR	BDS		8.4			8.4			10		
	ENT EXCE			4.0			3.7			4.0		
JU PERC	ENT EXCE	מעם		3.1			2.5			2.8		

293

RIO GRANDE DE LOIZA BASIN

50055390 RIO BAIROA AT BAIROA, PR--Continued

WATER QUALITY RECORDS

PERIOD OF RECORD .-- OCTOBER 1990 TO CURRENT YEAR

DATE TIME	STREAMFLOW, INSTANTANEOUS (CFS)	SPECIFIC CON- DUCTANCE (UMHOS)	TEMPERA- TURE (DEG C)	DATE TIM	STREAMFLOW, E INSTANTANEOUS (CFS)	SPECIFIC CON- DUCTANCE (UMHOS)	TEMPERA- Ture (DEG C)
MAY 15 1440	2.48	460	27.5	JUL. 08 145		380	27.5
JUN. 11 0932	4.0	320	25.5	AUG. 27 125		410	30.0

50055390 RIO BAIROA AT BAIROA, PR--Continued

WATER QUALITY DATA, WATER YEARS JULY 1991 TO SEPTEMBER 1992

PARTICLE-SIZE DISTRIBUTION OF SUSPENDED SEDIMENT

	r na	ATCHE DI	m D101011	2011011 01		, ordinal.	•
DATE	TIME	DIS- CHARGE, INST. CUBIC FRET PER SECOND	SEDI - MENT, SUS- PENDED (MG/L)	SEDI- MENT, DIS- CHARGE, SUS- PENDED (T/DAY)	SED. SUSP. FALL DIAM. PERCENT FINER THAN .002 MM	SED. SUSP. FALL DIAM. PERCENT FINER THAN .004 MM	SED. SUSP. FALL DIAM. PERCENT FINER THAN .008 MM
JUL 1991							
01	1255	154	1540	640	64	69	73
16	1030	586	4040	6390	42	53	63
16	1120	700	3910	7390	45	54	66
18	1552	357	4000	3850	56	66	79
DATE	SED. SUSP. FALL DIAM. PERCENT FINER THAN	SED. SUSP. FAIL DIAM. PERCENT FINER THAN	SED. SUSP. SIEVE DIAM. PERCENT FINER THAN	SED. SUSP. SIEVE DIAM. PERCENT FINER THAN	SED. SUSP. SIEVE DIAM. PERCENT FINER THAN	SED. SUSP. SIEVE DIAM. PERCENT FINER THAN	SED. SUSP. SIEVE DIAM. PERCENT FINER THAN
JUL 1991	.016 MM	.031 MM	.062 MM	.125 MM	.250 MM	.500 MM	1.00 MM
01	75	79	98	99	99.3	99.6	99.8
16	วรั	84	98	99	99.6	99.8	100
16	79	83	96	98	99	99.3	99.8
18	85	87	99	99.4	99.7	99.8	100

295

RIO GRANDE DE LOIZA BASIN

50055390 RIO BAIROA AT BAIROA, PR--Continued

WATER QUALITY DATA, WATER YEAR OCTOBER 1991 TO SEPTEMBER 1992

SILT AND CLAY PERCENT OF SUSPENDED SEDIMENT

DATE	TIME	STREAM- PLOW, INSTAN- TANEOUS (CFS)	SEDI- MENT, SUS- PENDED (MG/L)	SEDI- MENT, DIS- CHARGE, SUS- PÉNDED (T/DAY)	SED. SUSP. SIEVE DIAM. PERCENT FINER THAM .062 MM
NOV 1991					
08	1557	29	422	33	100
22	1250	10	186	5	99
JAN 1992					
07	1241	10	115	3	97
SRP					
07	1404	218	720	423	97

50055400 RIO BAIROA NEAR CAGUAS, PR

WATER-QUALITY RECORDS

LOCATION.--Lat 18°15'28", long 66°02'13", at bridge on Highway 1, about 2.5 mi (4.0 km) upstream from Río Grande de Loíza, and 1.4 mi (2.3 km) north of Caguas plaza.

DRAINAGE ARRA. -- 5.4 mi2 (14.0 km2).

PERIOD OF RECORD.--Water years 1958, 1962-66, 1973-74, 1979 to current year.

WATER-QUALITY DATA, WATER YEAR OCTOBER 1991 TO SEPTEMBER 1992

DATE	TIME	PR	GE, SPI T. CII IC COI ET DUC	Fic Who N- Fii CT- (ST/ CB Ai	TER DLE SLD TEM AND- AT RD WA'	URE I	FUR- (31D- (TY F TU)	DXYGEN, DIS- SOLVED (MG/L)	OXYGEN, DIS- SOLVEI (PER- CENT SATUR- ATION)	DEMA ICA (H)	AND, FORM PROPERTY OF THE PROP	OLI- ORM, BCAL, .45 M-MF OLS./ O ML)	STREP- TOCOCCI FECAL, (COLS. PER 100 ML)
OCT 1991 16	1230	3	.9	440	7.6	26.5	3.8	1.9	2:	3	20	59000	30000
DEC 06	1140	0	.51	470	7.2	24.5	16	1.4	19	,	82 K	63000	K80000
FRB 1992 13	1000	5	.1	416	7.3	23.0	0.30	7.5	102	2	<10	K7700	2700
MAY 14	0920	1	8	485	6.9	25.5	0.60	5.5	6:	3	11 4	50000	330000
JUN 19	1235		. 0	360		28.0	2.2	7.5	104		21	2000	2100
AUG 26	1515		5	430		28.5	1.2	5.4	59			41000	k1700
		_						3.1			120		
DATE	N T	ARD- ESS OTAL MG/L AS ACO3)	CALCIUM DIS- SOLVED (MG/L AS CA)	MAGNE- SIUM, DIS- SOLVED (MG/L AS MG)	SODIUM, DIS- SOLVED (MG/L AS NA)	SODIUM AD- SORP- TION RATIO	POTA SIU DIS SOLV (MG/ AS I	AS- LIN JM, WAT S- TOT /ED FI /L MG/	RLD '	ULFIDE POTAL (MG/L AS S)	SULFAT DIS- SOLVE (MG/L AS SO4	R RI DI D SO (M	ILO- DE, S- LVED G/L CL)
ОСТ 1991 16		170	40	16	30	1	4.		150	<0.5	20	2	5
DRC 06									150			•	
FEB 1992 13								_	140				
MAY 14		170	40	16	30	1	4.		150	<0.5	35		5
JUN 19							•		150			•	
AUG 26		150	37	15	26	0.9			160		21	2	9
20		130	3,	13	20	v. :	•		100		•1	,	,
DATE	R S	LUO- IDE, DIS- OLVED MG/L S F)	SILICA, DIS- SOLVED (MG/L AS SIO2)	SOLIDS, SUM OF CONSTI- TUENTS, DIS- SOLVED (MG/L)	SOLIDS, DIS- SOLVED (TONS PER DAY)	RESIDUI TOTAL AT 105 DEG. C. SUS- PENDED (MG/L)	NITE GEN NITE TOTA (MG/	N, G ATR NIT AL TO 'L (M	EN, TRITE NO TAL 1 G/L	NITRO- GEN, D2+NO3 FOTAL (MG/L AS N)	NITRO GEN, AMMONI TOTAL (MG/L AS N)	G A ORG TO (M	TRO- EN, ANIC TAL G/L
OCT 1991													
DEC		0.20	30	266	2.83	< :			.070	1.40	1.10		0.90
06 FRB 1992						3 (1.5	50 0	.100	1.60	4.10		2.4
13 May						•	1.3	36 0	.040	1.40	0.09	0	0.21
14 Jun		0.10	31	291	1.40	3	1.9	57 0	.030	1.60	0.13	0	0.07
19 AUG						4	1.5	57 0	.030	1.60	0.11	0	0.19
26		0.20	28	259	1.05	:	1.3	35 0	.050	1.40	0.18	0	0.42

K = non-ideal count

297

50055400 RIO BAIROA NEAR CAGUAS, PR--Continued WATER-QUALITY DATA, WATER YEAR OCTOBER 1991 TO SEPTEMBER 1992

DATE	NITRO- GEN, AM- MONIA + ORGANIC TOTAL (MG/L AS N)	NITRO- GEN, TOTAL (MG/L AS N)	NITRO- GBN, TOTAL (MG/L AS NO3)	PHOS- PHORUS TOTAL (MG/L AS P)	ARSENIC TOTAL (UG/L AS AS)	BARIUM, TOTAL RECOV- ERABLE (UG/L AS BA)	BORON, TOTAL RECOV- ERABLE (UG/L AS B)	CADMIUM TOTAL RECOV- ERABLE (UG/L AS CD)	CHRO- MIUM, TOTAL RECOV- ERABLE (UG/L AS CR)	COPPER, TOTAL RECOV- ERABLE (UG/L AS CU)
OCT 1991										
16	2.0	3.4	15	0.690	2	<100	40	<1	1	20
DBC 06	6.5	8.1	36	2.10						
FRB 1992 13	0.30	1.7	7.5	0.500						
MAY						400	50			.40
14 Jun	0.20	1.8	8.0	0.660	3	<100	50	<1	<1	<10
19 AUG	0.30	1.9	8.4	0.640						
26	0.60	2.0	8.9	0.890						
DATE	IRON, TOTAL RECOV- ERABLE (UG/L AS FR)	LEAD, TOTAL RECOV- ERABLE (UG/L AS PB)	MANGA- NESE, TOTAL RECOV- ERABLR (UG/L AS MN)	MERCURY TOTAL RECOV- ERABLE (UG/L AS HG)	SELE- NIUM, TOTAL (UG/L AS SR)	SILVER, TOTAL RECOV- ERABLE (UG/L AS AG)	ZINC, TOTAL RECOV- ERABLE (UG/L AS ZN)	CYANIDE TOTAL (MG/L AS CN)	PHENOLS TOTAL (UG/L)	METHY- LENE BLUE ACTIVE SUB- STANCE (MG/L)
OCT 1991 16	TOTAL RECOV- ERABLE (UG/L	TOTAL RECOV- BRABLE (UG/L	NESE, TOTAL RECOV- BRABLE (UG/L	TOTAL RECOV- ERABLE (UG/L	NIUM, TOTAL (UG/L	TOTAL RECOV- BRABLE (UG/L	TOTAL RECOV- ERABLE (UG/L	TOTAL (MG/L	TOTAL	LENR BLUE ACTIVE SUB- STANCE
OCT 1991 16 DEC 06	TOTAL RECOV- ERABLE (UG/L AS FR)	TOTAL RECOV- ERABLE (UG/L AS PB)	NESE, TOTAL RECOV- ERABLE (UG/L AS MN)	TOTAL RECOV- ERABLE (UG/L AS HG)	NIUM, TOTAL (UG/L AS SR)	TOTAL RECOV- ERABLE (UG/L AS AG)	TOTAL RECOV- ERABLE (UG/L AS ZN)	TOTAL (MG/L AS CN)	TOTAL (UG/L)	LENR BLUE ACTIVE SUB- STANCE (MG/L)
OCT 1991 16 DEC 06 FEB 1992	TOTAL RECOV- ERABLE (UG/L AS FR)	TOTAL RECOV- ERABLE (UG/L AS PB)	NESE, TOTAL RECOV- ERABLE (UG/L AS MN)	TOTAL RECOV- ERABLE (UG/L AS HG)	NIUM, TOTAL (UG/L AS SR)	TOTAL RECOV- ERABLE (UG/L AS AG)	TOTAL RECOV- ERABLE (UG/L AS ZN)	TOTAL (MG/L AS CN)	TOTAL (UG/L)	LENR BLUE ACTIVE SUB- STANCE (MG/L)
OCT 1991 16 DEC 06 FEB 1992 13	TOTAL RECOV- ERABLE (UG/L AS FR)	TOTAL RECOV- BRABLE (UG/L AS PB)	NESE, TOTAL RECOV- BRABLE (UG/L AS MN)	TOTAL RECOV- ERABLE (UG/L AS HG) <0.10	NIUM, TOTAL (UG/L AS SE) <1	TOTAL RECOV- BRABLE (UG/L AS AG)	TOTAL RECOV- ERABLE (UG/L AS ZN) <10	TOTAL (MG/L AS CN) <0.010	TOTAL (UG/L)	LENE BLUE ACTIVE SUB- STANCE (MG/L)
OCT 1991 16 DBC 06 FBB 1992 13	TOTAL RECOV- ERABLE (UG/L AS FR)	TOTAL RECOV- BRABLE (UG/L AS PB)	NESE, TOTAL RECOV- BRABLE (UG/L AS MN)	TOTAL RECOV- ERABLE (UG/L AS HG) <0.10	NIUM, TOTAL (UG/L AS SR) <1	TOTAL RECOV- BRABLE (UG/L AS AG) <1	TOTAL RECOV- ERABLE (UG/L AS ZN) <10	TOTAL (MG/L AS CN) <0.010	TOTAL (UG/L)	LENE BLUE ACTIVE SUB- STANCE (MG/L)
OCT 1991 16 DEC 06 FEB 1992 13 MAY	TOTAL RECOV- ERABLE (UG/L AS FR)	TOTAL RECOV- BRABLE (UG/L AS PB)	NESE, TOTAL RECOV- BRABLE (UG/L AS MN)	TOTAL RECOV- ERABLE (UG/L AS HG) <0.10	NIUM, TOTAL (UG/L AS SE) <1	TOTAL RECOV- BRABLE (UG/L AS AG)	TOTAL RECOV- ERABLE (UG/L AS ZN) <10	TOTAL (MG/L AS CN) <0.010	TOTAL (UG/L)	LENE BLUE ACTIVE SUB- STANCE (MG/L)

50055750 RIO GURABO BELOW EL MANGO, PR

LOCATION.--Lat 18°14'02", long 65°53'07", Hydrologic Unit 21010005, on left bank, 2.43 mi (3.91 km) northeast of Plaza de Juncos, 1.3 mi (2.1 km) southeast of Escuela La Placita and 0.35 mi (0.56 km) southwest of El Mango.

DRAINAGE ARRA. -- 22.3 mi 2 (57.8 km2).

WATER-DISCHARGE RECORDS

PERIOD OF RECORD. -- March 1990 to current year.

GAGE. -- Water-stage recorder. Elevation of gage is 230 ft (70 m), from topographic map.

REMARKS.--Records fair. Gage-height and precipitation satellite telemetry at station. Low-flow is affected by sewage discharges from a water treatment plant, 0.60 mi (0.96 km) upstream from gaging station since 1990.

	D	escharge,	CUBIC FEET		OND, WATER DAILY MEAN		TOBER 1991	TO SEPI	EMBER 1992			
DAY	OCT	NOV	DEC	JAN	FEB	MAR	APR	MAY	JUN	JUL	AUG	SEP
1	158	6.0	28	13	14	6.9	4.7	16	448	3.0	3.4	14
2	244	39	34	12	14	7.2	5.2	168	224	2.6	4.1	8.8
3	144	12	64	11	14	7.7	4.7	11	31	2:4	5.0	9.4
4	46	10	140	10	18	8.4	4.4	6.5	190	2.3	4.3	8.2
5	39	23	29	550	17	16	4.3	5.3	103	2.2	405	7.4
6 7	26	52 456	20 16	699	46	8.4	4.3 5.0	482 102	101 258	1.9 1.7	36 29	21 13
8	16 12	1420	15	140 52	34 17	49 37	5.5	15	109	2.1	31	9.4
9	14	260	16	35	14	10	13	8.1	46	3.2	13	16
10	14	215	16	111	14	7.3	22	6.7	399	2.4	11	12
11	14	76	16	37	15	6.1	7.6	13	141	2.1	24	8.7
12	10	43	15	27	12	5.7	6.4	10	537	2.3	31	8.7
13	11	35	16	31	11	5.7	9.1	5.6	180	1.5	36	7.1
14	10	28	19	27	11	5.7	7.2	4.8	167	1.4	154	6.5
15	11	24	15	20	11	15	7.9	4.7	₫ 0	1.6	50	6.2
16	26	23	14	19	11	7.7	6.6	6.8	160	2.5	22	23
17	12	22	18	17	8.9	6.4	5.7	8.8	111	12	30	122
18	9.9	19	13	16	8.3	8.9	5.6	5.4	25	5.0	14	28
19 20	9.0	18	13	16	8.3	8.9	7 8	4.7	16	2.8	11	255 945
20	7.2	16	32	16	7.9	6.8	26	9.6	14	2.7	11	
21	6.5	25	74	15	8.0	6.1	11	8.6	68	5.6	9.7	815
22	6.3	142	17	15	7.5	7.5	7.4	5.1	35	82	8.7	35
23	6.2	28	15	15	7.8	8.8	6.3	765	76	7.6	8.2	14
24	6.0	95	13	16	7.8	6.4	5.8	657	14	135	11	16
25	6.1	31	12	18	8.0	5.8	5.3	256	8.0	38	8.9	8.0
26	5.2	19	11	20	8.3	5.4	5.0	880	5.9	9.0	8.0	6.5
27	5.0	41	11	19	9.7	5.1	4.9	122	5.2	25	7.9	6.1
28	4.7	29	11	16	8.8	5.0	4.7	41	4.6	24	7.4	7.5
29	4.9	21	11	18	8.4	4.8	4.6	25	3.8	6.2	7.3	3.6
30	5.8	35	11	16		4.7	4.7	20	3.3	4.1	7.1	16
31	5.4		11	14		4.6		153		3.4	18	455
TOTAL	895.2	3263.0	746	2041	380.7	299.0	292.9	3826.7	3523.8	397.6	1027.0	2457.1
MEAN	28.9	109	24.1	65.8	13.1	9.65	9.76	123	117	12.8	33.1	81.9
MAX	244	1420	140	699	46	49	78	880	537	135	405	945
MIN	4.7	6.0	11	10	7.5	4.6	4.3	4.7	3. 3	1.4	3.4	3.6
ac-ft	1780	6470	1480	4050	755	593	581	7590	6990	789	2040	4870
CFSM	1.29	4.88	1.08	2.95	.59	.43	.44	5.54	5.27	. 58	1.49	3.67
IN.	1.49	5.44	1.24	3.40	. 64	. 50	.49	6.38	5.88	. 66	1.71	4.10
STATIS	TICS OF	MONTHLY M	BAN DATA FO	R WATER	YBARS 1990	- 1992,	BY WATER	YBĀR (W)	r)			
MBAN	94.9	72.1	41.5	51.0	28.3	13.9	8.73	48.0	52.3	23.9	34.1	53.8
MAX	161	109	59.0	65.8	44.0	18.1	9.76	123	117	33.1	35.2	81.9
(WY)	1991	1992	1991	1992	1991	1991	1992	1992	1992	1990	1990	1992
MIN	28.9	35.5	24.1	36.2	13.1	9.65	7.52	4.83	14.7	12.8	33.1	34.9
(WY)	1992	1991	1992	1991	1992	1992	1990	1990	1991	1992	1992	1990
SUMMARY	Y STATIS	TICS	FOR 1	991 CALE	NDAR YRAR	P	OR 1992 WA	TBR YEAI	ì	WATER 1	TEARS 1990	- 1992
ANNUAL						-						
YNNOYT				12213.2 33.5			19150.0 52.3			47.0	1	
	T ANNUAL	MBIN		33.3			34.3			52.3		1992
	ANNUAL									41.0		1991
	T DAILY			1420	Nov 8		1420	Nov 8	3	1420		8 1991
	DAILY M				Aug 12		1.4			1.6		14 1992
ANNUAL	SEVEN-D	NINIM YA		1.7	Aug 8		2.0			1.7		8 1991
		PEAK FLOW			-		5870	Nov 8	3	5870		8 1991
		PEAK STAG	R					Nov 8	3	17.3	Nov	8 1991
		LOW FLOW					1.4	Jul 13	3	1.4	Jul	13 1992
	RUNOFF			24220			37980			34040		
	RUNOFF			1.5			2.35			2.1		
		(INCHES)		20.3	7		31.95	5		28.6	3	
	CENT EXC			71			122			94		
	CENT BXC			12			12			12		
SO PER	CENT EXC	PRDS		3.9			4.7			3.9	,	

50055750 RIO GURABO BELOW EL MANGO, PR--Continued

WATER QUALITY RECORDS

PERIOD OF RECORD .-- OCTOBER 1990 TO CURRENT YEAR

DATE TIME	STREAMFLOW, INSTANTANEOUS (CFS)	SPECIFIC CON- DUCTANCE (UMHOS)	TEMPERA- TURE (DEG C)	DATE	Time	STREAMFLOW, INSTANTANEOUS (CFS)	SPECIFIC CON- DUCTANCE (UMHOS)	TEMPERA- Ture (Deg C)
MAR. 16 0855 JUN. 03 1037 JUN. 23 0921	7.58 31.3 87.7	300 240 220	24.5 26.0 26.5	JUL. 1. AUG. 2		1.37 9.73	420 350	28.0 31.0

50055750 RIO GURABO BELOW EL MANGO, PR--Continued

WATER-QUALITY RECORDS

MRAN

PERIOD OF RECORDS. -- Water years 1985 to 1986 and water year 1989 to current year.

PERIOD OF DAILY RECORD . --

SUSPENDED-SEDIMENT DISCHARGE: March 1990 to September 1992.

INSTRUMENTATION. -- DH-48 and automatic sediment sampler.

EXTREMES FOR PERIOD OF DAILY RECORD. --SEDIMENT CONCENTRATION: Maximum daily mean, 1,000 mg/L Oct. 21, 1990; Minimum daily mean, 4 mg/L April 7,1991.

SEDIMENT LOADS: Maximum daily mean, 7,110 tons (6,450 tonnes) Nov. 08, 1991; Minimum daily mean, 0.05 ton (0.3 tonne) several days.

EXTREMES FOR CURRENT YEAR. -

SEDIMENT CONCENTRATION: Maximum daily mean, 978 mg/L NOV. 08, 1991; Minimum daily mean, 5 mg/L Several days.

SEDIMENT LOADS: Maximum daily mean, 7,110 tons (6,450tonnes) Nov. 08, 1991; Minimum daily mean, 0.05 ton (0.04 tonne) several days.

		MRYN			MRAN			MEAN	
DAY	MEAN DI SCHARGE (CFS)	CONCEN- TRATION (MG/L)	SEDIMENT DISCHARGE (TONS/DAY)	MEAN Discharge (CFS)	CONCEN- TRATION (MG/L)	SEDIMENT DISCHARGE (TONS/DAY)	MEAN DI SCHARGE (CFS)	CONCEN- TRATION (MG/L)	SEDIMENT DISCHARGE (TONS/DAY)
		OCTOBER		1	NOVEMBER		1	DECEMBER	
1	158	167	76	6.0	18	.44	28	42	3.2
2	244	240	180	39	59	9.9	34	50	4.7
3	144	172	75	12	26	. 84	64	76	27
4	46	65	8.5	10	21	.58	140	105	61
5	39	55	6.4	23	34	2.6	29	36	2.9
6	26	51	3.7	52	62	20	20	24	1.3
7	16	45	2.0	456	443	1050	16	21	. 93
8 9	12	35	1.2	1420	978	7110	15	18	.74
9	14	29	1.1	260	192	149	16	14	.59
10	14	23	. 88	215	224	157	16	12	. 52
11	14	30	1.2	76	88	19	16	12	.51
12	10	25	.70	43	48	5.7	15	12	.51
13	11	25	. 72	35	35	3.5	16	16	. 65
14	10	24	. 64	28	24	1.8	19	21	1.1
15	11	24	.71	24	15	1.0	15	18	.75
16	26	46	3.8	23	16	1.0	14	18	. 69
17	12	21	.71	22	21	1.2	18	14	. 67
18	9.9	25	. 65	19	23	1.2	13	12	. 44
19	9.0	28	.70	18	27	1.3	13	11	.37
20	7.2	30	. 59	16	29	1.3	32	31	12
21	6.5	31	. 54	25	36	4.4	74	52	16
22	6.3	32	. 53	142	107	61	17	24	1.2
23	6.2	32	. 54	28	22	1.8	15	20	.77
24	6.0	30	. 48	95	113	36	13	15	.51
25	6.1	25	.41	31	31	3.1	12	13	. 42
26	5.2	21	.30	19	19	1.0	11	12	.36
27	5.0	19	. 26	41	53	6.6	11	11	, 32
28	4.7	17	. 22	29	33	2.7	11	10	.28
29	4.9	16	.21	21	29	1.7	11	9	.27
30	5.8	16	.25	35	50	5.3	11	8	.26
31	5.4	16	. 22				11	8	.24
TOTAL	895.2		369.16	3263.0		8660.96	746		141.20

50055750 RIO GURABO BELOW EL MANGO, PR--Continued

		MEAN			MRAN			MEAN	
	MRAN DISCHARGE	CONCEN- TRATION	SEDIMENT DISCHARGE	Mran Dischargr	Concen- Tration	Sediment Discharge	MRAN DI SCHARGE	CONCEN- TRATION	SEDIMENT DISCHARGE
DAY	(CFS)	(MG/L)	(TONS/DAY)	(CFS)	(MG/L)	(TONS/DAY)	(CFS)	(MG/L)	(TONS/DAY)
		JANUARY		1	FEBRUARY			MARCH	
1	13	9	. 32	14	41	1.5	6.9	15	.28
2	12	10	.31	14	35	1.3	7.2	19	.36
3 4	11	10	.29	14	29	1.2	7.7	14	.29
4	10	10	.28	18	23	1.1	8.4	10	.25
5	550	431	2650	17	15	.71	16	36	1.7
6 7	699	325	858	46	46	12	8.4	29	. 67
7	140	113	45	34	56	5.7	49	50	21
8	52	71	11	17	17	.82	37	33	4.1
9	35	43	4.3	14	12	.45	10	27	.76
10	111	61	26	14	13	.50	7.3	22	.45
11	37	20	2.0	15	13	.51	6.1	20	.34
12	27	16	1.2	12	13	.43	5.7	20	.31
13	31	12	. 96	11	13	.37	5.7	17	.27
14	27	11	. 82	11	13	.37	5.7	12	. 19
15	20	12	. 66	11	12	.36	15	22	1.1
16	19	12	. 64	11	13	.37	7.7	17	.37
17	17	14	. 65	8.9	15	.35	6.4	12	.20
18	16	14	.63	8.3	16	.35	8.9	8	.18
19	16	14	. 59	8.3	17	.39	8.9	10	.23
20	16	14	. 59	7.9	13	.28	6.8	10	. 19
21	15	14	. 57	8.0	10	.20	6.1	10	. 17
22	15	14	. 56	7.5	6	.12	7.5	10	.20
23	15	15	. 60	7.8	5	.10	8.8	11	.24
24	16	20	. 88	7.8	5	.11	6.4	12	.20
25	18	26	1.3	8.0	6	.13	5.8	13	.20
26	20	33	1.8	8.3	6	.15	5.4	13	.19
27	19	41	2.0	9.7	. 8	.21	5.1	13	. 18
28	16	49	2.2	8.8	10	.24	5.0	13	. 18
29	18	54	2.6	8.4	12	.27	4.8	13	. 17
30	16	52	2.2				4.7	13	. 16
31	14	46	1.7				4.6	14	. 16
TOTAL	2041		3620.65	380.7		30.59	299.0		35.29

50055750 RIO GURABO BELOW EL MANGO, PR--Continued

DAY	MRAN DISCHARGE (CFS)	MEAN CONCEN- TRATION (MG/L)	SEDIMENT DISCHARGE (TONS/DAY)	MEAN DISCHARGE (CFS)	MRAN CONCEN- TRATION (MG/L)	SEDIMENT DISCHARGE (TONS/DAY)	MRAN DISCHARGE (CFS)	MEAN CONCEN- TRATION (MG/L)	SEDIMENT DISCHARGE (TONS/DAY)
		APRIL			MAY			JUNE	
1	4.7	15	.19	16	822	30	448	410	1570
2	5.2	15	.21	168	130	136	224	335	273
3	4.7	12	. 15	11	23	.68	31	77	7.4
4	4.4	8	. 09	6.5	19	.34	190	190	169
5	4.3	8	.10	5.3	16	.22	103	118	44
6	4.3	10	. 12	482	323	858	101	119	35
7	5.0	10	. 14	102	120	52	258	253	389
8	5.5	11	.16	15	47	1.9	109	126	43
9	13	23	2.2	8.1	33	.74	46	65	8.9
10	22	38	3.3	6.7	21	.38	399	398	770
11	7.6	9	. 19	13	21	.92	141	154	75
12	6.4	8	. 15	10	12	.36	537	456	1210
13	9.1	9	. 22	5.6	13	.19	180	185	101
14	7.2	10	. 19	4.8	15	.19	167	172	92
15	7.9	11	. 24	4.7	17	.22	40	59	7.2
16	6.6	14	. 24	6.8	18	.30	160	83	98
17	5.7	24	.36	8.8	18	.44	111	71	26
18	5.6	30	.45	5.4	17	.24	25	34	2.6
19	78	111	43	4.7	17	.22	16	25	1.2
20	26	80	5.8	9.6	15	.38	14	24	. 95
21	11	72	2.2	8.6	12	.30	68	81	31
22	7.4	70	1.4	5.1	12	.17	35	50	7.7
23	6.3	65	1.1	765	555	3190	76	99	29
24	5.8	57	. 90	657	628	1850	14	54	2.3 .85
25	5.3	49	.72	256	23 3	405	8.0	38	. 85
26	5.0	42	.57	880	624	2930	5.9	29	. 47
27	4.9	35	. 46	122	84	30	5.2	28	. 39
28	4.7	26	.34	41	55	6.3	4.6	24	.29
29	4.6	22	.28	25	28	2.0	3.8	19	.19
30	4.7	22	.27	20	11	.63	3.3	17	. 14
31				153	152	261			
TOTAL	292.9		65.74	3826.7		9759.12	3523.8		4995.58

50055750 RIO GURABO BELOW EL MANGO, PR--Continued

DAY	MEAN DISCHARGE (CFS)	MRAN CONCEN- TRATION (NG/L)	SEDIMENT DISCHARGE (TONS/DAY)	MEAN DISCHARGE (CFS)	MEAN CONCEN- TRATION (MG/L)	SEDIMENT DISCHARGE (TONS/DAY)	MRAN DISCHARGE (CFS)	MEAN CONCEN- TRATION (MG/L)	SEDIMENT DISCHARGE (TONS/DAY)
		JULY			AUGUST		SI	ep temb er	
1	3.0	15	. 12	3.4	18	.16	14	20	.79
2	2.6	16	. 11	4.1	13	.15	8.8	11	.25
3	2.4	17	.10	5.0	29	.38	9.4	11	.29
4	2.3	17	.10	4.3	43	.49	8.2	12	.27
5	2.2	17	.10	4 0 5	430	1070	7.4	12	. 23
6	1.9	17	. 09	36	52	6.5	21	31	2.7
7	1.7	17	.08	29	43	3.4	13	24	. 92
8	2.1	18	.10	31	48	4.3	9.4	19	.48
9	3.2	22	.20	13	29	1.1	16	28	1.3
10	2.4	14	. 09	11	20	.60	12	30	. 97
11	2.1	11	. 07	24	37	3.8	8.7	24	.57
12	2.3	12	. 07	31	45	4.9	8.7	23	.54
13	1.5	12	. 05	36	52	7.0	7.1	23	.44
14	1.4	14	. 05	154	154	131	6.5	23	.42
15	1.6	17	. 07	50	98	19	6.2	23	.38
16	2.5	19	. 13	22	38	3.0	23	25	1.7
17	12	28	. 93	30	45	4.4	122	219	105
18	5.0	12	. 17	14	28	1.1	28	62	5.0
19	2.8	7	. 05	11	25	.74	255	253	818
20	2.7	8	.07	11	21	.57	945	686	3980
21	5.6	13	. 22	9.7	19	.52	819	578	2760
22	82	90	41	8.7	20	.45	47	65	9.3
23	7.6	17	. 39	8.2	20	.46	21	35	2.1
24	135	142	187	11	20	.59	23	40	2.7
25	38	53	9.0	8.9	22	.53	12	26	. 84
26	9.0	18	.48	8.0	22	.46	9.9	21	. 58
27	25	35	7.9	7.9	20	.43	9.1	19	. 54
28	24	85	7.3	7.4	18	.36	11	21	. 84
29	6.2	36	.61	7.3	16	.32	5.5	13	. 19
30	4.1	29	.33	7.1	11	.21	20	35	3 .9
31	3.4	24	.23	18	29	1.6			
TOTAL	397.6		257.21	1027.0		1268.52	2506.9		7701.24
YEAR	19199.8		36905.26						

50055750 RIO GURABO BELOW RL MANGO, PR--Continued

WATER QUALITY DATA, WATER YEAR OCTOBER 1991 TO SEPTEMBER 1992

PARTICLE-SIZE DISTRIBUTION OF SUSPENDED SEDIMENT

D ATE	TIME	DIS- CHARGE, INST. CUBIC FEST PER SECOND	SEDI- MENT, SUS- PENDED (MG/L)	SEDI- MENT, DIS- CHARGE, SUS- PENDED (T/DAY)	SED. SUSP. FALL DIAM. PERCENT FINER THAN .002 MM	SED. SUSP. PALL DIAM. PERCENT FINER THAN .004 MM	SED. SUSP. PALL DIAM. PERCENT FINER THAN .008 MM
MAY 1992							
06	1155	1950	1780	9370	54	57	67
DATE	SED. SUSP. FALL DIAM. PERCENT FINER THAN .016 MM	SED. SUSP. FALL DIAM. PERCENT FINER THAN .031 MM	SED. SUSP. SIEVE DIAM. PERCENT FINER THAN .062 MM	SED. SUSP. SIEVE DIAM. PERCENT FINER THAN .125 MM	SED. SUSP. SIEVE DIAM. PERCENT FINER THAN .250 MM	SED. SUSP. SIEVE DIAM. PERCENT FINER THAN .500 MM	SED. SUSP. SIEVE DIAM. PERCENT FINER THAN 1.00 MM
	·						
MAY 1992							
06	82	87	96	9 9	99.5	99.7	99.8

50055750 RIO GURABO BELOW EL MANGO--Continued

WATER QUALITY DATA, WATER YEAR OCTOBER 1991 TO SEPTEMBER 1992

SILT AND CLAY PERCENT OF SUSPENDED SEDIMENT

DATE	TIME	STREAM- FLOW, INSTAN- TANEOUS (CFS)	SEDI- MENT, SUS- PENDED (MG/L)	SEDI- MENT, DIS- CHARGE, SUS- PENDED (T/DAY)	SED. SUSP. SIEVE DIAM. PERCENT FINER THAN .062 MM
OCT 1991					
03	1406	129	170	59	97
JAN 1992					
06	1015	724	166	324	95
MAR					
07	1952	239	786	507	68
07	2057	304	199	163	95
MAY					
01	2343	412	799	888	94
06	1130	843	1610	3670	94
06	170 0	1390	861	3230	97
JUN					
12	0916	635	265	454	99
16	0112	411	109	120	93
16	1847	428	940	1080	87
λŪG					
14	1602	3 25	475	417	92
SRP					
17	0406	350	417	395	88
21	1030	156	156	66	92

50056400 RIO VALENCIANO NEAR JUNCOS, PR

LOCATION.--Lat 18°12'58", long 65°55'34", Hydrologic Unit 21010005, on left bank at Highway 919, 0.5 mi (0.8 km) upstream from Quebrada Don Victor, 1.7 mi (2.7 km) upstream from Rio Gurabo and 1.0 mi (1.6 km) south of Juncos.

DRAINAGE AREA. -- 16.4 mi 2 (42.5 km2).

WATER-DISCHARGE RECORDS

PERIOD OF RECORD. -- January 1971 to current year.

GAGE .- Water-stage recorder. Rlevation of gage is 320 ft (98 m), from topographic map.

REMARKS.--Records fair except those for estimated daily discharges, which are poor. Minor diversion from public water supply tank, 0.5 ml upstream, during low flow. Gage-height and precipitation satellite telemetry at station.

EXTREMES OUTSIDE PERIOD OF RECORD.--Approximate discharges (no stages were recorded) of major floods are as follows: Sept. 6, 1960, 37,100 ft 3 /s (1,050 m 3 /s), Oct. 9, 1970, 18,200 ft 3 /s (515 m 3 /s).

Sept.	6, 1960	, 37,100 1	[t³/s (1,	050 m³/s),	Oct. 9, 1	970, 18,	200 ft'/s	(515 m²/s)	•			
	DISCHARGE, CUBIC FEET PER SECOND, WATER YEAR OCTOBER 1991 TO SEPTEMBER 1992 Daily mean values											
DAY	OCT	NOV	DEC	JAN	PEB	MAR	APR	MAY	JUN	JUL	AUG	SRP
1	124	8.1	17	13	10	6.9	5.6	6.2	115	14	13	21
2	190	9.2	17	11	9.4	7.8	6.6	42	87	13	25	16
3	104	8.4	22	9.7	9.5	7.9	4.7	7.2	34	13	21	19
4	29	8.7	36	9.4	12	9.2	4.6	5.2	27	12	17	15
5	29	13	19	1150	10	12	4.4	4.5	30	28	236	14
6 7	22 14	22 205	16 15	779 60	29 17	16 9.1	4.2 10	8.9 8.4	28 42	13 11	50 84	47 27
8	13	1340	15	29	ii	9.6	5.0	6.0	83	11	46	18
9	14	206	14	23	10	7.5	5.0	4.7	84	13	26	48
10	16	133	14	25	16	7.1	5.7	4.6	80	10	31	17
11	38	44	13	18	12	6.4	8.1	6.4	109	16	24	15
12	16	31	14	16	10	6.4	8.8	7.7	157	13	29	13
13	15	26	13	16	9.4	6.5	5.8	4.4	138	9.2	23	13
14	13	20	13	15	10	6.8	6.4	4.3	95	9.1	29	12
15	18	17	12	14	12	9.3	9.8	6.8	64	8.9	25	12
16 17	17 23	17	14	14	11 9.2	6.5	5.3	34	43 40	10 41	20 21	47 125
18	16	16 15	13 11	14 14	9.1	10 10	5.6 13	11 6.7	29	15	17	33
19	17	15	11	12	9.0	7.0	26	5.7	25	22	15	201
20	12	15	13	12	8.2	11	7.8	14	34	22	20	970
21	e12	20	16	12	8.0	7.9	11	11	204	23	39	509
22	e15	52	11	11	8.1	8.2	5.9	5.5	50	89	16	56
23	011	21	11	11	8.6	6.9	4.8	678	47	19	20	54
24	011	113	11	12	9.4	6.5	4.3	458	27	16	80	36
25	10	29	10	13	8.5	5.7	4.0	103	22	23	20	30
26	9.1	20	11	16	8.3	6.7	3.8	801	20	18	18	25
27	7.4	72	11	12	8.1	6.3	3.4	56	19	16	18	26
28	6.9	26	10	12	7.7	5.9	3.5	33	17	16	16	27
29	9.5	24	10	12	7.4	5.0	3.5	25	15	14	18	22
30 31	16 8.0	20	10 14	11 10		4.9	4.1	23 20	15	13 13	15 33	22
						5.0						
TOTAL	855.9	2566.4	437	2386.1	307.9	242.0	200.7	2412.2	1780	564.2	1065	2490
MBAN	27.6	85.5	14.1	77.0	10.6	7.81	6.69	77.8	59.3	18.2	34.4	83.0
MAX MIN	190	1340	36 10	1150 9.4	29 7.4	16 4.9	26 3.4	801 4.3	204 15	89 8.9	236 13	970 12
AC-FT	6.9 1700	8.1 5090	867	4730	611	480	398	4780	3530	1120	2110	4940
CFSM	1.68	5.22	.86	4.69	.65	.48	.41	4.74	3.62	1.11	2.09	5.06
IN.	1.94	5.82	. 9 9	5.41	.70	. 55	.46	5.47	4.04	1.28	2.42	5.65
e Rs	timated											
STATIST	TCS OF B	MONTHLY MR.	AN DATA I	OR WATER	YRARS 1971	- 1992.	. BY WATER	YEAR (WY)				
												70 -
MEAN	81.9	94.3	59.1	23.1	17.7	19.6	15.3	54.9	50.3	46.1	64.4 231	79.5 255
MAX	293	461 1988	550	77.0	47.9	39.7	4 1.7 1985	268 1985	188 1979	163 1981	1979	1979
(WY) MIN	1986 21.8	19.5	1988 11.0	1992 11.4	1984 7.21	1973 7.01	5.82	5.02	6.21	5.36	15.5	10.8
(WY)	1984	1990	1990	1976	1974	1977	1991	1990	1977	1974	1980	1987
()			2224	22.0		23						
SUMMARY	STATIST	rics	FOR	1991 CALE	NDAR YEAR	E	OR 1992 W	ATER YEAR		WATER YE	ARS 1971	- 1992
ANNUAL				9203.8			15307.4					
ANNUAL				25.2			41.8	1		50.8		
	NNUAL									121		1988
	ANNUAL 1			40.0						17.1	D	1990
	DAILY			1340			1340			9100 1.8		8 1987 12 1990
	DAILY ME	ean Ay minimum			May 2 Apr 29		3.4	Apr 27		2.6		19 1990
		PEXK FLOW		3.8	nyi 49		9940			40000		8 1987
		PBAK STAGB						9 Jan 5		25.63		8 1987
		LOW FLOW					25.0			1.4		21 1988
	RUNOFF			18260			30360			36790	-	
ANNUAL	RUNOFF	(CFSM)		1.5			2.5			3.10		
	RUNOPP			20.8	8		34.7	2		42.07	r	
	ENT EXC			35			56			73		
	ENT BXC			11			14			19		
90 PERC	CENT EXC	erds		5.5			6.4	1		7.1		

307

RIO GRANDE DE LOIZA BASIN

50056400 RIO VALENCIANO NEAR JUNCOS, PR--Continued

WATER QUALITY RECORDS

PERIOD OF RECORD. -- WATER YEARS AUGUST 1981 TO CURRENT YEAR

DATE	TIME	STREAMFLOW, INSTANTANEOUS (CFS)	SPECIFIC CON- DUCTANCE (UMHOS)	TEMPERA- TURE (DEG C)	DATE	TIME	STREAMFLOW, INSTANTANEOUS (CFS)	SPECIFIC CON- DUCTANCE (UMHOS)	TEMPERA- TURE (DEG C)
MAR. 16	1033	6.23	280	25.0	JUN. 03	1316	30.9	210	27.0

50056400 RIO VALENCIANO NEAR JUNCOS, PR--Continued

WATER-QUALITY RECORDS

PERIOD OF RECORDS .-- Water years 1983 to 1986 and water year 1989 to current year.

PERIOD OF DAILY RECORD. --SUSPENDED-SEDIMENT DISCHARGE: October 1989 to September 1992.

INSTRUMANTATION. -- Automatic sediment sampler.

EXTREMES FOR PERIOD OF DAILY RECORD. -SEDIMENT CONCENTRATION: Maximum daily mean, 1,600 mg/L Oct. 06, 1985; Minimum daily mean, 1 mg/L several days.

SEDIMENT LOADS: Maximum daily mean, 46,300 tons (42,000 tonnes) May 18, 1985; Minimum daily mean, 0.01 ton (0.01 tonne) several days.

EXTREMES FOR WATER YEAR 1992.-

SEDIMENT CONCENTRATION: Maximum daily mean, 945 mg/L Nov. 08, 1991; Minimum daily mean, 4 mg/L several days.

SEDIMENT LOADS: Maximum daily mean, 10,500 tons (9,500 tonnes) Jan. 05, 1992; Minimum daily mean, 0.10 ton (0.09 tonne) several days.

SEDIMENT DISCHARGE, SUSPENDED (TONS/DAY), WATER YEAR OCTOBER 1991 TO SEPTEMBER 1992

	MEAN				MEAN		MEAN			
DAY	MRAN Discharge (CFS)	CONCEN- TRATION (MG/L)	SEDIMENT DISCHARGE (TONS/DAY)	MEAN DISCHARGE (CFS)	CONCEN- TRATION (MG/L)	SEDIMENT DISCHARGE (TONS/DAY)	MEAN DISCHARGE (CFS)	CONCEN- TRATION (MG/L)	SEDIMENT DISCHARGE (TONS/DAY)	
		OCTOBER		1	NOVEMBER		1	DECEMBER		
1	124	163	76	8.1	30	. 67	17	35	1.6	
2	190	240	138	9.2	30	.73	17	24	1.0	
3	104	143	50	8.4	30	.70	22	29	2.3	
4	29	53	4.3	8.7	30	.75	36	76	8.1	
5	29	56	5.5	13	29	1.2	19	50	2.5	
6	22	46	3.0	22	40	3.4	16	45	1.9	
7	14	31	1.2	205	260	275	15	42	1.7	
8	13	23	.77	1340	945	7590	15	42	1.7	
9	14	18	. 69	206	221	168	14	41	1.6	
10	16	36	1.7	133	181	83	14	35	1.3	
11	38	74	11	44	51	6.6	13	28	. 97	
12	16	47	2.1	31	19	1.6	14	22	.76	
13	15	35	1.3	26	13	.95	13	14	.48	
14	13	24	.88	20	10	.56	13	8	.29	
15	18	20	1.0	17	10	.45	12	9	. 29	
16	17	36	1.8	17	10	.42	14	11	.39	
17	23	48	3.5	16	8	.33	13	14	.45	
18	16	41	1.8	15	6	.24	11	17	. 49	
19	17	35	1.7	15	5	.19	11	18	. 54	
20	12	28	. 91	15	5	.20	13	18	. 64	
21	e12	18	e.53	20	28	2.5	16	15	. 67	
22	e15	10	e.40	52	120	20	11	13	. 37	
23	e11	10	e.30	21	71	4.1	11	11	.31	
24	e11	14	e.43	113	187	88	11	8	.24	
25	10	25	. 68	29	78	7.2	10	8	.22	
26	9.1	34	. 81	20	14	.75	11	7	.22	
27 28	7.4	40	. 85	72	184	83	11	7	.20	
28 29	6.9 9.5	41	.78	26	59	4.4	10 10	10 21	.25 .55	
		40	1.1	24	55	3.8				
30 31	16 8.0	41	2.0	20	45	2.4	10 14	31 31	.87 1.2	
		30	.70					31		
TOTAL	855.9		315.73	2566.4		8351.14	437		34.10	

e Estimated

50056400 RIO VALENCIANO NEAR JUNCOS, PR--Continued

	MEAN				MRAN		MEAN			
DAY	MEAN DISCHARGE (CFS)	CONCEN- TRATION (MG/L)	SEDIMENT DISCHARGE (TONS/DAY)	MEAN DISCHARGE (CFS)	CONCEN- TRATION (MG/L)	SEDIMENT DISCHARGE (TONS/DAY)	MRAN DISCHARGE (CFS)	CONCEN- TRATION (MG/L)	SEDIMENT DISCHARGE (TONS/DAY)	
		JANUARY		;	FEBRUARY			MARCH		
1	13	30	1.1	10	20	.52	6.9	52	. 98	
2	11	27	.75	9.4	20	.52	7.8	52	1.1	
3	9.7	22	.58	9.5	20	.52	7.9	55	1.3	
4	9.4	18	.45	12	23	.74	9.2	58	1.6	
5	1150	762	10500	10	35	.95	12	64	2.1	
6	779	510	1520	29	61	6.0	16	70	3.2	
7	60	92	17	17	58	3.0	9.1	71	1.8	
8	29	50	4.1	11	47	1.4	9.6	74	1.9	
9	23	38	2.5	10	48	1.3	7.5	75	1.6	
10	25	29	1.9	16	50	2.2	7.1	73	1.4	
11	18	27	1.3	12	48	1.6	6.4	69	1.2	
12	16	17	.76	10	42	1.1	6.4	55	. 95	
13	16	10	.42	9.4	34	. 85	6.5	36	. 63	
14	15	10	. 37	10	25	.64	6.8	28	, 55	
15	14	14	.51	12	20	.63	9.3	22	. 56	
16	14	18	. 65	11	28	.81	6.5	20	. 36	
17	14	21	. 80	9.2	41	.99	10	25	. 84	
18	14	21	.77	9.1	51	1.2	10	22	, 67	
19	12	19	. 59	9.0	56	1.3	7.0	15	.28	
20	12	17	.51	8.2	48	1.0	11	35	1.4	
21	12	17	.51	8.0	33	.68	7.9	59	1.3	
22	11	19	. 57	8.1	25	.53	8.2	60	1.3	
23	11	21	. 60	8.6	34	.77	6.9	6 6	1.3	
24	12	25	.75	9.4	51	1.3	6.5	73	1.3	
25	13	28	. 94	8.5	68	1.6	5.7	73	1.1	
26	16	28	1.2	8.3	77	1.6	6.7	62	1.2	
27	12	27	. 88	8.1	67	1.4	6.3	34	. 57	
28	12	26	. 88	7.7	54	1.1	5.9	30	. 49	
29	12	24	. 85	7.4	52	1.0	5.0	30	.40	
30	11	22	. 66				4.9	30	.40	
31	10	22	.58				5.0	30	.43	
TOTAL	2386.1		12063.48	307.9		37.25	242.0		34.21	

50056400 RIO VALENCIANO NEAR JUNCOS, PR--Continued

	MEAN				MEAN		mban		
DAY	MEAN DISCHARGE (CFS)	CONCEN- TRATION (MG/L)	SEDIMENT DISCHARGE (TONS/DAY)	MEAN Discharge (CFS)	CONCEN- TRATION (MG/L)	SEDIMENT DISCHARGE (TONS/DAY)	MEAN DISCHARGE (CFS)	CONCEN- TRATION (MG/L)	SEDIMENT DISCHARGE (TONS/DAY)
		APRIL			MAY			JUNE	
1	5.6	30	.48	6.2	13	.28	115	124	155
2	6.6	33	.54	42	112	17	87	133	45
3	4.7	35	.48	7.2	26	.61	34	55	5.8
4	4.6	37	.45	5.2	12	.16	27	30	2.3
5	4.4	42	. 47	4.5	11	.13	30	50	4.7
6	4.2	47	. 57	8.9	18	.51	28	37	2.6
7	10	50	1.4	8.4	17	.42	42	68	9.4
8	5.0	35	.50	6.0	9	. 14	83	137	49
9	5.0	32	.48	4.7	11	.14	84	125	36
10	5.7	39	.58	4.6	26	.32	80	109	33
11	8.1	44	. 99	6.4	38	.66	109	153	56
12	8.8	33	.76	7.7	51	1.0	157	200	136
13	5.8	23	.40	4.4	54	. 63	138	179	101
14	6.4	11	.20	4.3	51	.62	95	136	39
15	9.8	20	. 61	6.8	50	. 89	64	94	17
16	5.3	12	. 17	34	92	15	43	38	4.3
17	5.6	12	. 19	11	96	3.5	40	47	5.9
18	13	21	3.2	6.7	62	1.1	29	46	3.6
19	26	46	6.0	5.7	47	.70	25	30	1.9
20	7.8	17	. 35	14	43	2.0	34	101	9.1
21	11	42	1.2	11	38	1.3	204	586	533
22	5.9	43	. 65	5.5	50	.73	50	78	12
23	4.8	33	. 45	678	513	4190	47	68	11
24	4.3	23	.26	458	382	887	27	27	2.0
25	4.0	15	. 15	103	131	142	22	21	1.2
26	3.8	11	.11	801	630	4750	20	13	. 67
27	3.4	10	.10	56	89	14	19	8	.40
28	3.5	10	.10	33	66	6.1	17	10	.43
29	3.5	10	. 10	25	58	4.0	15	14	.58
30 31	4.1	10	.11	23	50	3.1	15	19	.72
31				20	39	2.1			
TOTAL	200.7		22.05	2412.2		10046.14	1780		1278.60

50056400 RIO VALENCIANO NEAR JUNCOS, PR--Continued

SEDIMENT DISCHARGE, SUSPENDED (TONS/DAY), WATER YEAR OCTOBER 1991 TO SEPTEMBER 1992

311

DAY	MEAN DISCHARGE (CFS)	MBAN CONCEN- TRATION (MG/L)	SEDIMENT DISCHARGE (TONS/DAY)	MEAN DISCHARGE (CFS)	MRAN CONCEN- TRATION (MG/L)	SEDIMENT DISCHARGE (TONS/DAY)	MEAN DISCHARGE (CFS)	MBAN CONCEN- TRATION (MG/L)	SEDIMENT DISCHARGE (TONS/DAY)
		JULY			AUGUST		SI	ep tem ber	
1	14	20	.71	13	4	.15	21	33	2.2
2	13	19	. 62	25	39	3.9	16	13	.55
3	13	18	. 58	21	37	2.5	19	10	.50
4	12	17	.51	17	15	1.0	15	8	.34
5	28	55	4.7	236	514	419	14	8	.32
6	13	37	1.3	50	77	13	47	64	15
7	11	25	.72	84	116	43	27	40	3.8
8	11	16	.46	46	60	8.4	18	12	. 59
9	13	7	.25	26	40	2.8	48	76	14
10	10	4	.12	31	55	5.4	17	17	. 77
11	16	24	1.4	24	40	2.4	15	7	.27
12	13	24	. 86	29	39	3.3	13	5	.20
13	9.2	13	.33	23	15	.84	13	5	. 17
14	9.1	5	. 12	29	39	4.1	12	5	.16
15	8.9	7	. 18	25	32	2.4	12	5	.16
16	10	14	. 35	20	26	1.3	47	61	27
17	41	65	13	21	41	2.4	125	165	101
18	15	30	1:3	17	39	1.8	33	43	4.0
19	22	38	2.6	15	35	1.5	201	231	250
20	22	40	2.8	20	34	3.1	970	697	7690
21	23	41	2.5	39	134	19	509	482	1430
22	89	119	52	16	64	2.9	56	90	16
23	19	27	1.6	20	36	2.1	54	84	16
24	16	19	.90	80	109	41	36	48	4.9
25	23	42	2.7	20	25	1.5	30	30	2.4
26	18	21	1.0	18	14	.68	25	30	2.0
27	16	9	.35	18	9	.44	26	35	2.4
28	16	6	.28	16	8	.36	27	34	2.8
29	14	5	. 18	18	8	.35	22	10	. 60
30	13	5	. 18	15	8	.33	22	8	.48
31	13	4	. 16	33	54	6.1			
TOTAL	564.2		94.76	1065		597.05	2490		9588.61
YEAR	15307.4		42463.12						

50056400 RIO VALENCIANO NEAR JUNCOS, PR--Continued

WATER QUALITY DATA, WATER YEAR OCTOBER 1991 TO SEPTEMBER 1992

PARTICLE-SIZE DISTRIBUTION OF SUSPENDED SEDIMENT

DATE	TIME	DIS- CHARGE, INST. CUBIC FEST PER SECOND	SEDI- MENT, SUS- PENDED (MG/L)	SEDI- MENT, DIS- CHARGE, SUS- PENDED (T/DAY)	SED. SUSP. FALL DIAM. PERCENT FINER THAN .002 MM	SED. SUSP. FALL DIAM. PERCENT FINER THAN .004 MM	SED. SUSP. FALL DIAM. PERCENT FINER THAN .008 MM
JAN 1992							
05	1937	8500	5640	129000	31	41	46
05	2132	3800	7610	78100	23	28	33
DATE	SED. SUSP. FALL DIAM. PERCENT FINER THAN .016 MM	SED. SUSP. FALL DIAM. PERCENT FINER THAN .031 MM	SED. SUSP. SIEVE DIAM. PERCENT FINER THAN .062 MM	SED. SUSP. SIEVE DIAM. PERCENT FINER THAN .125 MM	SED. SUSP. SIEVE DIAM. PERCENT FINER THAN .250 MM	SED. SUSP. SIEVE DIAM. PERCENT FINER THAN .500 MM	SED. SUSP. SIEVE DIAM. PERCENT FINER THAN 1.00 MM
JAN 1992							
05	57	65	90	97	99	99.8	99.9
05	42	51	63	71	76	85	96

50056400 RIO VALENCIANO NEAR JUNCOS, PR--Continued

WATER QUALITY DATA, WATER YEAR OCTOBER 1991 TO SEPTEMBER 1992

SILT AND CLAY PERCENT OF SUSPENDED SEDIMENT

DATE	TIME	STREAM- FLOW, INSTAM- TANEOUS (CFS)	SEDI- MENT, SUS- PENDED (MG/L)	SEDI- MENT, DIS- CHARGE, SUS- PENDED (T/DAY)	SED. SUSP. SIEVE DIAM. PERCENT FINER THAN .062 MM
NOV 1991					
22	1140	33	134	12	96
24	1331	408	329	362	99
24	1622	205	440	243	100
27	0924	263	517	367	98
27	0954	235	1190	755	99
JAN 1992					
05	2252	2890	2230	17400	91
06	1050	782	325	688	96
JUN					
01	0015	623	4120	6940	65
02	0055	179	391	189	95
08	1300	205	122	68	92
12	0948	230	833	517	99
21	0320	712	1410	2700	99
21	0455	466	2310	2910	99
SRP					
21	1100	333	31	28	96

50056900 QUEBRADA MAMEY NEAR GURABO, PR

LOCATION.--Lat 18°14'57", long 65°56'44", Hydrologic Unit 21010005, at left downstream side of bridge on Highway 189, 1.9 mi (3.0 km) southeast of Gurabo plaza, and 2.1 mi (3.4 km) northwest of Juncos plaza.

DRAINAGE AREA. -- 2.30 mi 3 (5.96 km 2).

WATER-DISCHARGE RECORDS

PERIOD OF RECORD .-- December 1983 to current year.

GAGE.--Water-stage recorder and crest-stage gage. Elevation of gage is 180 ft (55 m), from topographic map.

REMARKS. -- Records fair except those for estimated daily discharges, which are poor.

DISCHARGE, CUBIC FRET PER SECOND, WATER YEAR OCTOBER 1991 TO SEPTEMBER 1992 DAILY MRAN VALUES												
DAY	OCT	NOV	DRC	JAN	FBB	MAR	APR	МУ	JUN	JUL	λŪĞ	SEP
1	.52	4.0	.67	. 53	.17	. 14	.14	9.0	1.6	. 29	e.23	e.37
2	3.7	5.0	.66	.51	.19	. 14	.16	11	.79	.34	e.45	e.30
3	1.1	. 94	.81	.49	.26	. 17	.16	1.9	.59	.47	e.38	e.25
4	.47	. 68	1.4	. 53	.45	.22	.15	.94	.47	. 53	e.31	e.28
5	.49	. 64	.97	99	.21	. 55	.15	.73	.45	.71	e4.0	e.26
6 7	.39 .31	1.6 24	.80 .84	78 3.7	.32 .29	.27 .25	.16 .22	3.9 2.5	.74 1.2	.66 .65	e.92 e1.5	e.84 e.45
8	.28	36	.65	.91	.20	.26	.29	1.2	1.3	.71	e.80	e. 33
9	.29	5.4	.70	.72	.21	. 24	.32	. 97	.89	. 49	e.48	e. 86
10	.31	2.2	.66	1.8	.45	.21	.52	. 89	1.2	.40	e.54	e. 31
11 12	.29	1.4	.73	. 45 . 29	.30	.21	.39	1.0	1.1 4.0	.50 .81	e.44 e.52	e.28 e.24
13	.32	1.1	.91		.19	.20	.34	1.1			e.42	e.24
14	.30 .25	1.1 .98	1.0 .75	. 25	.17	. 19	.31	1.2	.89	.61 e.51	e.52	e. 22
				.21	.27	.26	.27	1.1	.52			
15	.24	. 94	. 62	. 19	.21	. 47	.29	1.0	.32	e.43	e.45	e.22
16	.29	.90	. 64	.20	.19	.35	.27	1.7	.25	e.38	e.37	e1.0
17	.45	1.6	.63	. 17	.17	.36	.61	1.8	.23	e.74	e.38	e2.2
18	.53	.84	.56	. 15	.17	. 44	.46	15	.22	e.28	e.32	e.62
19	. 65	.72	. 63	. 16	.18	.40	.43	7.9	.21	e.39	e.28	e3.0
20	.72	. 69	.87	. 16	.17	. 34	.48	5.8	.23	e.41	e.40	e10
21	. 67	1.1	.68	. 16	.16	. 35	.41	5.9	10	e.60	e.70	e8. 0
22	.67	7.2	.49	.17	.17	. 67	.31	2.8	1.1	e1.6	e.30	e4.0
23	.67	1.7	.47	. 16	.20	.34	.32	52	.56	e.35	e.35	e1.0
24	.46	1.1	.48	. 15	.27	. 24	.23	48	.28	e.29	e1.5	e. 90
25	.40	.91	.50	. 17	.29	.21	.19	16	.22	e. 41	e.36	e. 64
26	.44	.88	.50	.24	.22	.20	.21	93	.21	e.33	e.33	e.54 e.46
27 28	.47	6.0	.52	. 19	.20	. 19	.25	21	.24	e.29	e.32	
29	.49 2.5	3.2 .87	.51	. 16	.16	. 18	.21	8.7 4.3	.23	e.29 e.29	e.30 e.33	e.48 e.47
30	12	.72	.53	. 15	.15	. 18	.20		.25	e.25	e.28	e.40
31	3.0		.52 .52	. 14 . 15		. 15 . 13	.49	2.6 1.7	.25	e. 24	e.60	
				•								
TOTAL	33.67	114.41	21.22	190.26	6.59	8.51	8.94	326.63	30.54	15.26	19.08	39.16
mban	1.09	3.81	. 68	6.14	.23	. 27	.30	10.5	1.02	.49	.62	1.31
MAX	12	36	1.4	99	.45	. 67	.61	93	10	1.6	4.0	10
MIN	.24	. 64	.47	.14	.15	. 13	.14	.73	.21	. 24	.23	. 22
AC-FT	67	227	42	377	13	17	18	648	61	30	38	78
CFSM	.47	1.66	.30	2.67	.10	. 12	.13	4.58	.44	.21	.27	. 57
IN.	.54	1.85	.34	3.08	.11	. 14	.14	5.28	.49	. 25	.31	. 63
e Es	stimated											
STATIS1	rics of 1	ONTHLY ME	AN DATA I	FOR WATER Y	EARS 1984	- 1992	2, BY WATER	YEAR (WY	·)			
MBAN	7.24	7.81	3.35	1.77	1.58	1.25	1.18	5.52	2.36	1.50	2.82	4.18
MAX	24.4	21.6	13.1	6.14	3.89	3.57	3.55	19.7	11.3	4.31	11.0	14.2
(WY)	1986	1988	1988	1992	1984	1985	1986	1985	1987	1988	1988	1989
MIN	1.09	1.13	.68	. 57	.23	. 27	.30	. 34	.68	.49	.62	. 63
(WY)	1992	1990	1992	1984	1992	1992	1992	1990	1985	1992	1992	1986
SUMMARY	Y STATIST	rics	FOR	1991 CALEN	DAR YEAR		FOR 1992 W	ATER YEAR		WATER Y	'EARS 198	- 1992
ANNUAL				504.15			814.2					
YNNAY				1.38	1		2.2	2		3.4		
	r annual									5.3		1988
	ANNUAL 1									1.2		1990
	L DYILA I			38	May 11		99	Jan 5		343		27 1987
	DAILY M		•		Sep 26			3 Mar 31		.1		31 1992
		AY MINIMUM		.27	Sep 3			5 Mar 30		.1		30 1992
		PEAK FLOW					3380			3380		26 1992
		PBAK STAGE	:					8 May 26		11.7	8 May	26 1992
	TANEOUS I			4655				0 Mar 31	-	.1	.0 Mar	31 1992
	Runoff Runoff			1000 .60	,		1620 .9	7		2470 1.4		
	RUNOFF			8.15			13.1			20.1		
	CENT BXC			1.6	•		2.7			3.2		
	CENT EXC			.65	:		.4			.8		
	CENT BXC			.30			.1			.3		
>- E BAC	BACI				•		.1	-		• • •	-	

50056900 QUEBRADA MAMEY NEAR GURABO, PR--Continued

WATER QUALITY RECORDS

PERIOD OF RECORD. -- WATER YEARS MARCH 1984 TO CURRENT YEAR

DATE T	LIMB	STREAMFLOW, INSTANTANEOUS (CFS)	SPRCIFIC CON- DUCTANCE (UMHOS)	TEMPERA- TURE (DEG C)	DATE	TIME	STREAMFLOW, INSTANTANEOUS (CFS)	SPRCIFIC CON- DUCTANCE (UMHOS)	TEMPERA- Ture (Deg C)
JAN. 13 1		0.26	420	26.0	JUN. 04		0.60	490	26.5
MAR. 24 1	1033	0.28	490	26.5	JUN. 23	1236	0.78	400	28.0

50057000 RIO GURABO AT GURABO, PR

LOCATION.--Lat 18°15'30", long 65°58'05", Hydrologic Unit 21010005, on left bank, at bridge on Highway 181, 0.3 mi (0.5 km) east of Gurabo, and 4.5 mi (7.6 km) upstream from Río Grande de Loíza.

DRAINAGE ARRA. -- 60.2 mi2 (155.9 km2).

WATER-DISCHARGE RECORDS

PERIOD OF RECORD. -- 1958 (occasional low-flow measurements only), January to September 1959 (monthly measurements only), October 1959 to current year.

GAGR.--Water-stage recorder and crest-stage gage. Datum of gage is 131.58 ft (40.106 m) above mean sea level. Prior to Oct. 1, 1989 datum 5.0 ft (1.5 m) higher.

REMARKS.--Records fair. Gage-height and precipitation satellite telemetry at station.

EXTREMES OUTSIDE PERIOD OF RECORD.--Approximate elevation to gage datum of the Aug. 4, 1945 flood, as pointed out by local residents, 26.6 ft (8.1 m), datum then is use.

Out D	DISCHARGE, CUBIC FEET PER SECOND, WATER YEAR OCTOBER 1991 TO SEPTEMBER 1992											
		DISCHAR	GR, CUBI	C FRET PER			YEAR OCTOBER VALUES	R 1991 TO	SEPTEMBE	R 1992		
DAY	OCT	NOA	DEC	JAN	FEB	MAR	APR	MAY	JUN	JUL	AUG	SEP
1	256	29	39	23	32	23	19	29	418	39	21	57
2	602	57	41	20	31	22		286	440	32	21	40
3	370	33	40	18	32	26		56	112	29	43	42
4	147	29	151	16	38	21		26	125	29	27	37
5	105	34	51	1940	42	46	20	19	151	42	569	32
6	110	41	37	2470	53	35		442	149	31	177	46
7	75	564	31	339	97	29		235	228	26	142	107
8 9	62 58	2740 501	29	162	47	70		65	263 255	29 32	146 84	47 96
10	63	336	28 27	121 151	37 42	34 23		40 25	405	28	74	63
11	60	114	27	105	44	19	25	30	316	28	64	47
12	40	73	27	80	33	17		50	627	38	109	43
13	34	61	27	73	29	16		26	332	28	86	37
14	34	49	26	73	29	16		21	242	23	182	33
15	33	41	27	62	31	27	24	23	158	23	167	32
16	37	39	24	56	33	26		35	130	25	72	69
17	40	38	27	52	28	19		59	216	83	81	312
18 19	28 30	33 29	24 22	50	25	31		52 68	96 64	60 35	52 42	135 330
20	23	27	25	43 41	25 25	26 21		39	60	44	40	1520
21	21	30	66	40	23	27	42	51	281	50	69	1440
22	26	174	30	37	24	24		26	168	177	37	205
23	20	54	24	37	24	24		1010	148	71	40	129
24	18	140	22	37	27	20		1950	88	82	97	111
25	19	76	19	41	29	17	14	350	62	142	53	80
26	16	41	18	49	25	16		1810	55	59	39	66
27 28	15 14	98 62	19	43	26	16		318	51	38 87	40	60 63
29	36	47	18 18	38 38	26 25	18		157 101	49 52	34	33 35	75
30	53	43	17	3 6 37	45 	17 17		79	49	25	31	67
31	39		19	33		17		93		24	64	
TOTAL	2484	5633	1000	6325	982	760	735.0	7571	5790	1493	2737	5421
MEYN	80.1	188	32.3	204	33.9	24.5	24.5	244	193	48.2	88.3	181
MAX	602	2740	151	2470	97	70		1950	627	177	569	1520
MIN	14	27	17	16	23	16		19	49	23	21	32
AC-FT CFSM	4930 1.33	11170 3.12	1980	12550	1950	1510		15020	11480	2960	5430	10750 3.00
IN.	1.53	3.12	.54 .62	3.39 3.91	.56 .61	.41		4.06 4.68	3.21 3.58	.80 .92	1.47	3.35
											2.03	3.33
STATIST	ICS OF M	ONTHLY MEA	N DATA F	OR WATER Y	RARS 1960	- 199	2, BY WATER	YEAR (WY)			
MEAN	210	208	164	62.7	46.4	40.1		155	136	117	177	228
MAX	1414	1045	863	204	131	97.5		746	468	371	610	1225
(WY)	1971	1988	1988	1992	1989	1985		1985	1970	1979	1979	1960
MIN (WY)	16.0 1968	37.3 1974	10.7 1968	16.4	12.6	11.2		12.7 1990	16.8	20.9 1967	24.8 1967	8.76 1967
(#1)	1300	13/4	1300	1968	1968	1965	1967	1990	1972	1907	1367	1307
SUMMARY	STATIST:	IC S	FOR	1991 CALEN	DAR YEAR		FOR 1992 W	ATER YEAR		WATER YE	NRS 1960	- 1992
ANNUAL	TOTAL.			22858.1			40931.0					
ANNUAL				62.6			112			134		
	ANNUAL I	MEAN								286		1979
	ANNUAL M									42.2		1967
	DAILY M			2740				Nov 8		21100		6 1960
	DAILY ME	AN Y MINIMUM		7.5				Apr 29		4.8 5.5		26 1967
		BAK FLOW		9.0	Aug 7		12 10100	Apr 24 Jan 5		74600		21 1967 6 1960
		BAK STAGE						7 Jan 5		27.70		6 1960
	ANBOUS LA									4.5		21 1968
	RUNOFF (45340			81190			97140		
	RUNOFF (1.04			1.80			2.23		
	RUNOFF (14.12			25.29	9		30.26		
	ENT EXCE			109			189			215 50		
	ENT BACE			30 13			39 19			50 19		
20 . DING				13			13					

50057000 RIO GURABO AT GURAGO, PR--Continued

WATER QUALITY RECORDS

PERIOD OF RECORD. -- WATER YEARS AUGUST 1981 TO CURRENT YEAR

DATE	TIME	STREAMFLOW, INSTANTANEOUS (CFS)	SPECIFIC CON- DUCTANCE (UMHOS)	TEMPERA- TURE (DEG C)	DATE	TIME	STREAMFLOW, INSTANTANEOUS (CFS)	SPECIFIC CON- DUCTANCE (UMHOS)	TEMPERA- TURE (DEG C)
MAR. 24 JUN. 04		19.6 74.1	320 280	27.0 28.0		4 1017 5 1148	85 22.1	230 330	28.5 30.0

50057000 RIO GURABO AT GURABO--Continued

WATER-QUALITY RECORDS

PERIOD OF DAILY RECORD. --

SUSPENDED-SEDIMENT DISCHARGE: October 1983 to September 1992.

INSTRUMENTATION. -- USD-49 and automatic sediment sampler.

EXTREMES FOR PERIOD OF DAILY RECORD. -SEDIMENT CONCENTRATION: Maximum daily mean, 9,220 mg/L Nov 27, 1987; Minimum daily mean, 4 mg/L
January 19,20,21, 1992.
SEDIMENT LOADS: Maximum daily mean, 686,000 tons (622,340 tonnes) Nov 27, 1987; Minimum daily mean,
0.14 ton (0.13 tonne) April 24, 1990.

EXTREMES FOR CURRENT YEAR.-SEDIMENT CONCENTRATION: Maximum daily mean, 726 mg/L September 16, 1992; minimum daily mean,
4 mg/L January 19,20,21, 1992.
SEDIMENT LOADS: Maximum daily mean, 6,560 tons (5,950 tonnes) January 05, 1992; minimum daily
0.31 ton (0.28 tonne) January 04, 1992.

		MRAN			MEAN			MEAN	
	MRAN	CONCEN-	SEDIMENT	mean	CONCEN-	SEDIMENT	MEAN	CONCEN-	Sediment
	DI SCHARGE	TRATION	DISCHARGE	DISCHARGE	TRATION	DISCHARGE	DISCHARGE	TRATION	DISCHARGE
DAY	(CFS)	(MG/L)	(TONS/DAY)	(CFS)	(MG/L)	(TONS/DAY)	(CFS)	(MG/L)	(TONS/DAY)
	•	OCTOBER	•		NOVEMBER	•	,	DECEMBER	
		Addorso		•	Nadmavon		•	DECEMBER	
1	256	178	139	29	30	2.5	39	25	2.6
2	602	415	767	57	48	8.0	41	14	1.5
3	370	232	272	33	31	2.7	40	11	1.2
2 3 4	147	97	40	29	25	2.0	151	108	58
5	105	79	23	34	19	1.7	51	23	3.5
6	110	82	25	41	24	3.3	37	14	1.5
7	75	59	12	564	358	847	31	14	1.2
8	62	48	8.0	2740	551	5670	29	13	.99
9	58	49	7.7	501	369	603	28	12	. 86
10	63	56	9.6	336	240	252	27	11	.76
11	60	42	6.8	114	82	28	27	11	.74
12	40	32	3.5	73	40	8.0	27	13	.96
13	34	28	2.7	61	25	4.0	27	15	1.1
14	34	24	2.2	49	18	2.3	26	13	.94
15	33	18	1.5	41	14	1.6	27	11	.77
16	37	16	1.5	39	14	1.5	24	10	. 65
17	40	16	1.7	38	13	1.3	27	8	.60
18	28	18	1.3	33	11	1.0	24	وَ	.58
19	30	18	1.3	29	10	.79	22	11	. 66
20	23	18	1.2	27	10	.73	25	17	1.3
21	21	16	.88	30	16	1.6	66	51	9.7
22	26	25	2.3	174	93	61	30	28	2.4
23	20	17	.88	54	28	4.2	24	15	1.0
24	18		. 62	140	241	128	22	10	.59
		13					19	10	.53
25	19	13	. 64	76	152	34	19	10	.53
26	16	13	. 57	41	77	9.0	18	10	.49
27	15	13	. 53	98	79	29	19	10	.51
28	14	13	.49	62	94	16	18	10	.50
29	36	29	5.9	47	65	8.2	18	10	.47
30	53	44	7.4	43	45	5.2	17	10	.46
31	39	34	4.4				19	9	.46
TOTAL	2484		1351.61	5633		7737.62	1000		97.52

50057000 RIO GURABO AT GURABO--Continued

DAY	MRAN DISCHARGE (CFS)	MBAN CONCEN- TRATION (MG/L)	SEDIMENT DISCHARGE (TONS/DAY)	MRAN DISCHARGE (CFS)	MEAN CONCEN- TRATION (MG/L)	SEDIMENT DISCHARGE (TONS/DAY)	MEAN DISCHARGE (CFS)	MRAN CONCEN- TRATION (MG/L)	SEDIMENT DISCHARGE (TONS/DAY)
		JANUARY		I	BBRUARY			MARCH	
1	23	8	. 52	32	11	.95	23	18	1.1
2	20	8	.44	31	15	1.3	22	18	1.0
3	18	7	. 37	32	19	1.6	26	18	1.2
4	16	7	.31	38	20	2.1	21	18	1.1
5	1940	303	6560	42	20	2.2	46	22	2.6
6	2470	461	4420	53	38	7.5	35	25	2.4
7	339	94	97	97	74	21	29	24	1.9
8	162	49	23	47	38	5.0	70	54	11
9	121	29	9.6	37	31	3.1	34	29	2.9
10	151	41	19	42	24	2.7	23	21	1.3
11	105	20	5.8	44	20	2.3	19	20	1.0
12	80	15	3.3	33	19	1.7	17	20	. 94
13	73	10	2.0	29	19	1.5	16	20	. 85
14	73	9	1.7	29	19	1.5	16	19	. 83
15	62	8	1.4	31	20	1.6	27	25	1.9
16	56	7	1.1	33	21	1.9	26	23	1.6
17	52	5	.77	28	22	1.6	19	20	1.0
18	50	5	. 67	25	18	1.2	31	19	1.5
19	43	4	. 55	25	15	.96	26	19	1.3
20	41	4	.44	25	16	1.0	21	20	1.2
21	40	4	.48	23	19	1.2	27	20	1.5
22	37	8	.78	24	25	1.6	24	20	1.2
23	37	14	1.3	24	30	1.9	24	19	1.1
24	37	16	1.6	27	31	2.2	20	18	. 95
25	41	14	1.5	29	27	2.0	17	15	. 69
26	49	11	1.5	25	21	1.5	16	12	.53
27	43	10	1.2	26	17	1.1	16	13	.59
28	38	9	. 92	26	17	1.1	18	16	.79
29	38 37	10	. 95 . 97	25	18	1.2	17 17	18 18	.83 .81
30 31	37	10					17	18 18	
31	33	10	.90				17	18	. 84
TOTAL	6325		11160.07	982		76.51	760		48.45

50057000 RIO GURABO AT GURABO--Continued

DAY	MRAN DISCHARGE (CFS)	MBAN CONCEN- TRATION (MG/L)	SEDIMENT DISCHARGE (TONS/DAY)	MEAN DISCHARGE (CFS)	MEAN CONCEN- TRATION (MG/L)	SEDIMENT DISCHARGE (TONS/DAY)	MEAN DISCHARGE (CFS)	MEAN CONCEN- TRATION (MG/L)	SEDIMENT DISCHARGE (TONS/DAY)
		APRIL			MAY			JUNE	
1	19	16	. 83	29	68	7.2	418	300	684
2	23	15	. 94	286	203	204	440	294	525
3	21	17	. 99	56	64	10	112	84	27
4	20	19	1.0	26	47	3.3	125	93	39
5	20	20	1.1	19	30	1.5	151	123	62
6	20	21	1.1	442	281	792	149	107	44
7	33	28	2.6	235	170	169	228	177	191
8	27	25	1.9	65	33	6.3	263	196	163
9	23	21	1.3	40	19	2.0	255	187	142
10	39	692	100	25	17	1.2	405	344	461
11	25	28	1.9	30	18	1.5	316	245	224
12	23	28	1.8	50	41	6.0	627	389	984
13	22	28	1.7	26	27	2.0	332	236	246
14	22	29	1.7	21	21	1.2	242	175	119
15	24	30	2.0	23	21	1.2	158	109	49
16	23	31	2.0	35	29	3.6	130	97	44
17	19	31	1.5	59	46	8.3	216	159	111
18	19	28	1.4	52	76	12	96	73	20
19	65	54	12	68	66	21	64	52	9.3
20	77	73	17	39	36	4.2	60	49	8.3
21	42	55	6.4	51	41	6.1	281	200	196
22	25	51	3.6	26	23	1.7	168	120	65
23	19	47	2.4	1010	377	2200	148	122	57
24	16	40	1.7	1950	657	4620	88	71	18
25	14	35	1.3	350	261	303	62	47	7.9
26	9.7	36	. 99	1810	634	3230	55	41	6.0
27	11	36	1.0	318	230	216	51	36	5.0
28	11	38	1.1	157	59	28	49	31	4.2
29	7.3	40	. 82	101	32	8.5	52	27	3.8
30	16	48	2.0,	79	38	8.0	49	25	3.3
31				93	54	23			
TOTAL	735.0		176.07	7571		11901.8	5790		4518.8

50057000 RIO GURABO AT GURABO--Continued

JUI	Y 25 2.7 26 2.3	24	AUGUST				
301					gl	3P TEMBER	
1 39	26 22	21	21	1.3	57	45	7.2
2 32	2 0 2 .3	21	22	1.3	40	34	3.8
3 29	29 2.3	43	37	5.2	42	35	3.8
4 29	31 2.4	27	31	2.6	37	39	4.0
5 42	37 4.3	569	474	1470	32	37	3.1
6 31	37 3.1	177	126	68	46	44	7.2
7 26	40 2.9	142	99	50	107	73	27
8 29	40 3.0	146	108	46	47	30	3.8
9 32	38 3.2	84	57	14	96	71	20
10 28	36 2.8	74	49	11	63	57	9.8
11 28	35 2.7	64	54	9.7	47	44	5.5
12 38	38 3.6	109	81	25	43	35	4.0
13 28	39 3.0	86	64	16	37	29	2.9
14 23	38 2.4	182	133	113	33	24	2.1
15 23	40 2.5	167	126	74	32	25	2.0
	42 2.7	72	57	11	69	726	69
17 83	69 20	81	64	15	312	223	233
18 60	48 8.8	52	45	6.7	135	103	40
19 35	30 2.9	42	36	4.3	330	273	609
20 44	36 4.5	40	34	3.8	1520	499	3300
	40 5.6	69	34	8.2	1440	619	303 0
	31 98	37	25	2.5	205	149	91
	89 19	40	34	3.8	129	83	30
24 82	66 37	97	90	32	111	86	27
25 142 1	09 55	53	110	17	80	64	14
	57 9.1	39	62	6.5	66	52	9.2
27 38	55 5.9	40	45	5.0	60	46	7.4
28 87	72 19	33	33	3.0	63	49	8.6
29 34	53 5.0	35	31	3.0	75	59	16
	46 3.2	31	29	2.4	67	54	11
31 24	31 2.1	64	51	10			
TOTAL 1493 -	341.0	2737		2041.3	5421		7601.4
YEAR 40931.0	47052.15						

50057000 RIO GURABO AT GURABO, PR--Continued

WATER QUALITY DATA, WATER YEAR OCTOBER 1991 TO SEPTEMBER 1992

PARTICLE-SIZE DISTRIBUTION OF SUSPENDED SEDIMENT

DATE	TIMB	DIS- CHARGE, INST. CUBIC FEET PER SECOND	SEDI- MENT, SUS- PENDED (MG/L)	SEDI- MENT, DIS- CHARGE, SUS- PENDED (T/DAY)	SED. SUSP. FALL DIAM. PERCENT FINER THAN .002 MM	SED. SUSP. FALL DIAM. PERCENT FINER THAN .004 MM	SED. SUSP. FALL DIAM. PERCENT FINER THAN .008 MM
NOV 1991							
08	1210	3900	1210	12700	49		53
JAN 1992 05	2057	8360	1180	26600	63	69	78
DATE	SED. SUSP. FALL DIAM. PERCENT FINER THAN	SED. SUSP. FALL DIAM. PERCENT FINER THAN	SED. SUSP. SIEVE DIAM. PERCENT FINER FIAN .062 MM	SED. SUSP. SIEVE DIAM. PERCENT FINER THAN	SED. SUSP. SIEVE DIAM. PERCENT FINER THAN	SED. SUSP. SIEVE DIAM. PERCENT FINER THAN	SED. SUSP. SIEVE DIAM. PERCENT FINER THAN 1.00 MM
	. UIU MM	. UJI MM	.002 AM	.123 FM	. 250 MM	. SVU MM	1.00 AM
NOV 1991 08 JAN 1992	59	76	93	95	97	99	100
05	83	83	99.7	99.8	99.9	99.9	100

50057000 RIO GURABO AT GURABO, PR--Continued

WATER QUALITY DATA, WATER YEAR OCTOBER 1991 TO SEPTEMBER 1992 SILT AND CLAY PERCENT OF SUSPENDED SEDIMENT

DATE	TIME	STREAM- PLOW, INSTAN- TANEOUS (CFS)	SEDI- MENT, SUS- PENDED (MG/L)	SEDI- MENT, DIS- CHARGE, SUS- PENDED (T/DAY)	SED. SUSP. SIEVE DIAM. PERCENT FINER THAN .062 MM
NOV 1991					
08	1040	650 0	795	14000	90
08	1140	4740	659	8440	91
08	1626	1170	520	1640	87
JAN 1992					
05	1757	2150	300	1740	99
05	2257	9540	1050	27000	99
MAR					
12	0905	17	41	2	99
MAY					
21	0918	59	114	18	99
24	1523	764	202	416	92
JUN					
01	2126	643	422	732	97
02	0041	1430	447	1720	97
11	0828	260	275	193	92
AUG					
05	0821	1990	2280	12300	84
05	1036	1390	1100	4120	96
05	1306	752	560	1140	95
25	0711	55	143	21	96
SEP					
01	0806	44	1290	153	98
19	2106	1346	1570	5700	86
19	2236	1045	860	2420	95

50057025 RIO GURABO NEAR GURABO, PR

WATER-QUALITY RECORDS

LOCATION.--Lat 18°15'56", long 65°59'04", at bridge on Highway 941, 1.2 mi (1.9 km) west-northwest from gaging station 50057000, and 1.0 mi (1.6 km) northwest of Gurabo plaza.

DRAINAGE AREA. -- 62.8 mi 2 (162.7 km2).

PERIOD OF RECORD. -- Water years 1979 to current year.

WATER-QUALITY DATA, WATER YEAR OCTOBER 1991 TO SEPTEMBER 1992

		WATER-QUA	TITY DATA	, WATER Y	BAR OCTOB	BR 1991 1	O SEPTEME	BR 1992		
DATE	TIME	SPR- CIFIC CON- DUCT- ANCE (US/CM)	PH WATER WHOLE FIELD (STAND- ARD UNITS)	TEMPER- ATURE WATER (DEG C)	TUR- BID- ITY (NTU)	OXYGEN, DIS- SOLVED (MG/L)	OXYGEN, DIS- SOLVED (PER- CENT SATUR- ATION)	OXYGEN DEMAND, CHEM- ICAL (HIGH LEVEL) (MG/L)	COLI- FORM, FECAL, 0.45 UM-MF (COLS./ 100 ML)	STREP- TOCOCCI FECAL, (COLS. PER 100 ML)
OCT 1991										
08	0930	338	7.0	28.0	1.2	1.6	20	62	2900	1000
06 FBB 1992	0905	303	7.0	24.5	23	2.8	42	28	2000	K820
13 MAY	0830	382	6.6	25.5	0.60	2.1	26	15	K 660	260
05 JUN	0850	327	6.6	25.5	13	1.8	22	29	2100	650
10 AUG	0915	260	7.0	27.0	130	4.2	60	33	30000	21000
19	1245	334	7.1	31.2	9.3	2.5	32	21	5800	200
DATE	HARD- NESS TOTAL (MG/L AS CACO3)	CALCIUM DIS- SOLVED (MG/L AS CA)	MAGNE- SIUM, DIS- SOLVED (MG/L AS MG)	SODIUM, DIS- SOLVED (MG/L AS NA)	SODIUM AD- SORP- TION RATIO	POTAS- SIUM, DIS- SOLVED (MG/L AS K)	ALKA- LINITY WAT WH TOT FET FIELD MG/L AS CACO3	SULFIDR TOTAL (MG/L AS S)	SULFATE DIS- SOLVED (MG/L AS SO4)	CHLO- RIDE, DIS- SOLVED (MG/L AS CL)
OCT 1991 08	150	41	12	53	2	6.9	110	<0.5	57	63
DEC					_					•••
06 FRB 1992							100			
13 May							130			
05 JUN	130	39	8.5	14	0.5	4.4	93	<0.5	24	34
10							80			
AUG 19	110	24	11	25	1	4.6	80		18	29
DATE	FLUO- RIDE, DIS- SOLVED (MG/L AS F)	SILICA, DIS- SOLVED (MG/L AS SIO2)	SOLIDS, SUM OF CONSTI- TURNTS, DIS- SOLVED (MG/L)	RESIDUE TOTAL AT 105 DEG. C, SUS- PENDED (MG/L)	NITRO- GEN, NITRATE TOTAL (MG/L AS N)	NITRO- GEN, NITRITE TOTAL (MG/L AS N)	NITRO- GEN, NO2+NO3 TOTAL (MG/L AS N)	NITRO- GEN, AMMONIA TOTAL (MG/L AS N)	NITRO- GEN, ORGANIC TOTAL (MG/L AS N)	NITRO- GEN, AM- MONIA + ORGANIC TOTAL (MG/L AS N)
OCT 1991	0.20	22	224	•		0.070	1 40	0 150	0.65	0.00
08	0.20	32	331	9	1.33	0.070	1.40	0.150	0.65	0.80
06 FRB 1992				36	0.880	0.120	1.00	0.370	0.73	1.1
13 MAY				10	0.810	0.100	0.910	0.710	0.59	1.3
05 JUN	0.80	24	204	30	0.860	0.140	1.00	0.480	0.52	1.0
10				145	0.750	0.050	0.800	0.610	0.69	1.3
AUG 19	0.20	27	203	17	1.13	0.070	1.20	0.270	0.53	0.80

K = non-ideal count

50057025 RIO GURABO NEAR GURABO, PR--Continued

WATER-QUALITY DATA, WATER YEAR OCTOBER 1991 TO SEPTEMBER 1992

DATE	NITRO- GEN, TOTAL (MG/L AS N)	NITRO- GEN, TOTAL (MG/L AS NO3)	PHOS- PHORUS TOTAL (MG/L AS P)	ARSENIC TOTAL (UG/L AS AS)	BARIUM, TOTAL RECOV- ERABLE (UG/L AS BA)	BORON, TOTAL RECOV- ERABLE (UG/L AS B)	CADMIUM TOTAL RECOV- BRABLE (UG/L AS CD)	CHRO- MIUM, TOTAL RECOV- ERABLE (UG/L AS CR)	COPPER, TOTAL RECOV- ERABLE (UG/L AS CU)	IRON, TOTAL RECOV- ERABLE (UG/L AS FE)
OCT 1991										
08	2.2	9.7	0.460	<1	<100	80	<1	7	30	500
DEC										
06	2.1	9.3	0.520							
FRB 1992										
13	2.2	9.8	0.550							
MAY										
05	2.0	8.9	0.480	2	<100	50	<1	2	10	660
JUN										
10	2.1	9.3	0.460							
AUG										
19	2.0	8.9	0.510							

DATE	LEAD, TOTAL RECOV- BRABLE (UG/L AS PB)	MANGA- NESE, TOTAL RECOV- ERABLE (UG/L AS MN)	MERCURY TOTAL RECOV- ERABLE (UG/L AS HG)	SELE- NIUM, TOTAL (UG/L AS SE)	SILVER, TOTAL RECOV- ERABLE (UG/L AS AG)	ZINC, TOTAL RECOV- ERABLE (UG/L AS ZN)	CYANIDE TOTAL (MG/L AS CN)	PHENOLS TOTAL (UG/L)	METHY- LENE BLUE ACTIVE SUB- STANCE (MG/L)
ост 1991									
08	3	210	0.10	<1	2	30	0.010	3	0.10
DEC									
06									
FEB 1992									
13 May									
05	3	460	<0.10			<10	<0.010	3	0.07
JUN	3	460	<0.10	<1	<1	<10	<0.010	3	0.07
10									
AUG									
19									
13				==					

50058350 RIO CAÑAS AT RIO CAÑAS, PR

LOCATION.--Lat 18°17'41", long 66°02'44", Hydrologic Unit 21010005, at right bank, off road 798, upstream side of bridge on Highway 52, .5 mi (.8 km) northeast from Escuela Segunda Unidad de Francisco Valdés, and .8 mi (1.3 km) north of La Barra.

DRAINAGE AREA. -- 7.53 mi 2 (19.50 km2).

WATER-DISCHARGE RECORDS

PERIOD OF RECORD .-- March 1990 to current year.

GAGE.--Water-stage recorder and crest-stage gage. Rlevation of gage is 164 ft (50 m), from topographic map.

REMARKS.--Records fair. Gage-height and precipitation satellite telemetry at station.

	DISCHARGE, CUBIC FEET PER SECOND, WATER YEAR OCTOBER 1991 TO SEPTEMBER 1992 DAILY MEAN VALUES											
DAY	ост	NOV	DEC	JAN	FEB	MAR	APR	MAY	JUN	JUL	AUG	SEP
1	5.5	11	5.9	5.0	8.4	6.7	4.5	58	10	3.8	3.8	5.7
2	4.9	7.5	5.9	5.0	8.4	6.7	4.5	55	7.0	5.3	2.9	5.1
3	4.5	5.4	11	4.7	8.4	6.6	4.5	12	5.9	4.9	3.5	5.1
4	4.6	4.8	7.9	4.7	8.4	6.2	4.4	7.7	17	4.9	11	9.4
5	4.8	4.6	6.4	241	7.8	6.2	3.6	6.2	6.2	3.5	68	12
6 7	4.4	4.4 9.5	6.0 5.6	145 32	7.8 7.8	6.1 5.7	3.1 6.6	11 6.4	5.6 27	3.5 3.2	15 4.6	61 65
8	4.1	16	5.5	20	7.8	5.7	4.6	4.5	22	4.5	3.5	19
9	4.1	8.4	5.7	15	7.8	5.7	4.1	5.2	86	5.3	266	12
10	4.1	5.2	5.5	29	8.9	5.7	4.1	4.3	18	4.9	33	9.7
11	4.0	4.5	5.3 5.3	16	7.7	5.7	4.1	3.5 3.0	8.9	5.7 4.5	17	9.1 9.4
12 13	3.8 3.8	4.4	5.1	13 16	6.7 6.7	5.7 5.7	3.6 3.6	2.7	10 6.3	4.9	8.8 6.3	24
14	3.8	4.3	5.6	11	8.5	5.6	3.7	2.7	5.4	5.3	15	7.3
15	3.9	4.3	5.5	12	9.0	5.8	3.5	2.5	4.9	5.3	6.8	4.4
16	4.0	4.7	5.0	31	7.8	5.3	3.8	49	4.9	4.5	4.5	5.9
17	3.8	4.3	5.0	25	7.2	8.2	4.2	6.5	4.9	4.1	4.0	18
18 19	4.9 3.9	4.2 3.9	5.0 5.0	13	7.2 7.2	7.1 5.8	4.0	6.7 4.5	5.2 5.0	4.1 3.5	3.5 3.5	5.1 20
20	3.7	3.9	12	11 11	7.2	5.3	4.7 5.7	4.5	4.8	3.2	3.5	22
21	3.7	16	6.1	9.8	7.4	5.4	3.5	3.8	21	3.2	11	25
22	6.2	17	5.0	9.7	7.6	5.5	3.5	3.2	5.7	3.2	4.6	5.4
23	4.2	32	4.8	9.1	7.8	4.8	3.5	50	4.9	3.2	3.4	3.6
24 25	3.7	15	4.7	9.9	7.8	4.5	3.5	52	4.9	4.5	3.2 3.0	3.1
	3.7	7.3	4.7	9.5	7.8	4.3	3.2	20	4.8	3.2		2.9
26	3.7	7.1	4.8	9.4	7.8	4.5	2.9	134	4.1	2.4	3.1	2.9
27 28	3.6 3.5	8.1 6.9	5.4 4.9	8.4	12 7.2	4.5	2.7 2.7	39 15	4.1	2.2 2.2	3.2 2.9	2.8 2.5
29	5.8	6.2	4.9	8.6 9.1	7.2	9.8 8.1	8.0	14	4.1 3.9	2.4	2.7	2.4
30	15	5.9	4.8	8.4	7.2	5.0	16	8.9	3.8	2.4	5.0	6.6
31	4.8		5.0	8.4		4.5		7.3		3.5	7.7	
TOTAL	142.6	241.6	179.3	760.7	229.3	182.4	134.4	603.1	326.3	121.3	534.0	386.4
MBAN	4.60	8.05	5.78	24.5	7.91	5.88	4.48	19.5	10.9	3.91	17.2	12.9
MAX	15	32	12	241	12	9.8	16	134	86	5.7	266	65
MIN	3.5	3.9	4.7	4.7	6.7	4.3	2.7	2.5	3.8	2.2	2.7	2.4
AC-FT CFSM	283	479	356	1510	455	362	267	1200	647	241	1060	766
IN.	.61 .70	1.07 1.19	.77 .89	3.26 3.76	1.05 1.13	.78 .90	.59 .66	2.58 2.98	1.44	.52 .60	2.29 2.64	1.71 1.91
											2.01	1.72
STATIS	rics of M	ONTHLY MI	SAN DATA E	OR WATER	YBARS 1990	- 1992,	HY WATER	YEAR (WY)			
MBAN	22.0	7.61	8.89	15.7	10.5	5.84	4.20	10.8	7.77	7.84	9.56	8.29
MAX	39.4	8.05	12.0	24.5	13.2	5.88	4.57	19.5	10.9	16.2	17.2	12.9 1992
(WY) MIN	1991 4.60	1992 7.18	1991 5.78	1992 6.76	1991 7.91	1992 5.80	1991 3.53	1992 3.32	1992 4.06	1991 3. 4 0	1992 4.36	5.62
(WY)	1992	1991	1992	1991	1992	1991	1990	1990	1990	1990	1990	1991
SUMMAR	Y STATIST	ICS	FOR	1991 CALE	NDAR YBAR	F	OR 1992 W	ATER YEAR		WATER Y	BARS 1990	- 1992
ANNUAL				2896.9			3841.4					
ANNUAL		MONN		7.9	4		10.5			10.9		1001
	T ANNUAL ANNUAL M									11.4 10.5		1991 1992
	T DAILY M			140	Feb 5		266	Aug 9		292		17 1990
	DAILY ME				May 4		2.2			2.2	Jul	27 1992
	ANNUAL SEVEN-DAY MINIMUM			3.3			2.6			2.6		25 1992
INSTANTANEOUS PEAK FLOW							1700			3830		17 1990
INSTANTANEOUS PEAK STAGE			K	E250			16.40 7620	6 Aug 9		20.55 Oct 17 1990 7910		
ANNUAL RUNOFF (AC-FT) 5750 ANNUAL RUNOFF (CFSM) 1.05				5		1.3	9		1.4			
ANNUAL RUNOFF (CFSM) 1.05 ANNUAL RUNOFF (INCHES) 14.31						18.9			19.7			
10 PER	CENT EXCE	EDS		11			16			14		
50 PERCENT EXCEEDS				5.2			5.4			5.0		
90 PER	90 PERCENT EXCEEDS			3.8			3.5		3.3			

50058350 RIO CAÑAS AT RIO CAÑAS, PR--Continued

WATER QUALITY RECORDS

PERIOD OF RECORD. -- OCTOBER 1990 TO CURRENT YEAR

DATE	TIME	STREAMFLOW, INSTANTANEOUS (CFS)	SPECIFIC CON- DUCTANCE (UMHOS)	TEMPERA- TURE (DEG C)	DATE	TIME	STREAMFLOW, INSTANTANEOUS (CFS)	SPECIFIC CON- DUCTANCE (UMHOS)	TEMPERA- Ture (Deg C)
MAR. 1	7 1321	10.3	340	24.0	JUN. 1	1 1153	7.60	310	27.0
MAY 25	2 1236	3.21	310	27 5					

50058350 RIO CAÑAS AT RIO CAÑAS, PR--Continued

WATER-QUALITY RECORDS

PERIOD OF RECORDS. -- Water years 1990 to current year.

PERIOD OF DAILY RECORD. --SUSPENDED-SEDIMENT DISCHARGE: March 1990 to September 1992.

INSTRUMENTATION. -- Automatic sediment sampler.

EXTREMES FOR PERIOD OF DAILY RECORD. --

SEDIMENT CONCENTRATION: Maximum daily mean, 1,770 mg/L Jan. 05, 1992; Minimum daily mean, 1 mg/L September 11,1991

SEDIMENT LOADS: Maximum daily mean, 4,920 tons (4,460 tonnes) October 17, 1990; Minimum daily mean, 0.02 ton (0.02 tonne) several days.

EXTREMES FOR CURRENT YEAR. -

SEDIMENT CONCENTRATION: Maximum daily mean, 1,770 mg/L JAN. 05, 1992; Minimum daily mean, 3 mg/L several days.

SEDIMENT LOADS: Maximum daily mean, 4,230 tons (3,840 tonnes) Jan. 05, 1992; Minimum daily mean, 0.02 ton (0.02 tonne) several days.

SEDIMENT DISCHARGE, SUSPENDED (TONS/DAY), WATER YEAR OCTOBER 1991 TO SEPTEMBER 1992

MEAN

MRAN

MBAN				mban			MBAN		
DAY	MEAN DISCHARGE (CFS)	CONCEN- TRATION (MG/L)	SEDIMENT DISCHARGE (TONS/DAY)	MBAN Discharge (CFS)	CONCEN- TRATION (MG/L)	SEDIMENT DISCHARGE (TONS/DAY)	MEAN DISCHARGE (CFS)	CONCEN- TRATION (MG/L)	SEDIMENT DISCHARGE (TONS/DAY)
		OCTOBER		1	NOVEMBER		1	DECEMBER	
1	5.5	31	.49	11	61	5.7	5.9	9	.15
2	4.9	24	.31	7.5	25	.57	5.9	8	.12
3	4.5	17	.21	5.4	17	.24	11	35	1.8
4	4.6	9	. 11	4.8	23	.29	7.9	32	. 69
5	4.8	7	.09	4.6	30	.38	6.4	26	. 45
6	4.4	7	.08	4.4	32	.39	6.0	25	.40
7	4.1	7	.08	9.5	36	1.3	5.6	25	. 38
8	4.1	7	. 07	16	60	3.8	5.5	25	. 38
9	4.1	5	.06	8.4	31	.85	5.7	50	.76
10	4.1	4	. 05	5.2	13	.18	5.5	13	.20
11	4.0	4	. 05	4.5	7	.09	5.3	10	.13
12	3.8	8	.09	4.4	4	.05	5.3	10	. 14
13	3.8	15	. 15	4.8	4	. 05	5.1	10	. 14
14	3.8	21	.21	4.3	3	.04	5.6	11	.16
15	3.9	18	.19	4.3	3	.04	5.5	13	. 17
16	4.0	14	.15	4.7	4	.06	5.0	13	.18
17	3.8	10	.11	4.3	7	.09	5.0	13	. 18
18	4.9	14	. 23	4.2	9	.10	5.0	16	.20
19	3.9	12	. 12	3.9	11	.12	5.0	19	. 24
20	3.7	17	.16	3.9	11	.11	12	50	3.6
21	3.7	22	.21	16	90	20	6.1	20	.36
22	6.2	29	. 80	17	254	29	5.0	11	. 14
23	4.2	15	. 17	32	169	127	4.8	9	.11
24	3.7	18	. 17	15	64	4.2	4.7	7	. 09
25	3.7	14	.13	7.3	15	.31	4.7	7	.08
26	3.7	12	.11	7.1	8	.16	4.8	7	.09
27	3.6	9	.09	8.1	14	.31	5.4	8	. 12
28	3.5	6	.06	6.9	11	.21	4.9	14	. 18
29	5.8	12	.31	6.2	11	.19	4.9	20	.26
30	15	81	19	5.9	10	.16	4.8	26	. 33
31	4.8	12	. 17				5.0	31	.41
TOTAL	142.6		24.23	241.6		195.99	179.3		12.64

SEDIMENT DISCHARGE, SUSPENDED (TONS/DAY), WATER YEAR OCTOBER 1991 TO SEPTEMBER 1992

DAY	MRAN DISCHARGE (CFS)	MEAN CONCEN- TRATION (MG/L)	SEDIMENT DISCHARGE (TONS/DAY)	MEAN DISCHARGE (CFS)	MRAN CONCEN- TRATION (MG/L)	SEDIMENT DISCHARGE (TONS/DAY)	MEAN Discharge (CFS)	MEAN CONCEN- TRATION (MG/L)	SEDIMENT DISCHARGE (TONS/DAY)
		JANUARY		1	BRUARY			MARCH	
1	5.0	24	.32	8.4	8	.19	6.7	7	. 13
2	5.0	15	. 19	8.4	10	.21	6.7	6	. 11
3	4.7	7	. 08	8.4	10	.23	6.6	5	. 10
4	4.7	5	.06	8.4	11	.25	6.2	7	. 12
5	241	1700	4230	7.8	13	.28	6.2	10	. 17
6	145	1170	797	7.8	13	.27	6.1	12	.20
7	32	99	9.8	7.8	13	.28	5.7	10	. 16
8	20	50	2.7	7.8	13	.28	5.7	8	. 13
9	15	44	1.8	7.8	13	.28	5.7	6	.09
10	29	37	2.8	8.9	13	.30	5.7	4	. 07
11	16	16	.70	7.7	14	.29	5.7	3	.05
12	13	9	.31	6.7	14	.26	5.7	3	.05
13	16	8	.38	6.7	15	.28	5.7	3	.04
14	11	7	.22	8.5	40	1.0	5.6	3	.04
15	12	5	. 15	9.0	8	.19	5.8	3	.04
16	31	602	192	7.8	8	.18	5.3	3	.04
17	25	413	35	7.2	9	.18	8.2	16	. 47
18	13	95	4.6	7.2	11	.22	7.1	10	. 19
19	11	37	1.1	7.2	11	.22	5.8	10	. 15
20	11	19	. 54	7.2	9	.18	5.3	8	. 13
21	9.8	10	.28	7.4	8	.16	5.4	7	.11
22	9.7	11	.28	7.6	8	.16	5.5	6	. 09
23	9.1	16	.40	7.8	7	. 15	4.8	5	. 07
24	9.9	17	.44	7.8	6	.13	4.5	9	. 10
25	9.5	16	.42	7.8	6	. 13	4.3	10	. 12
26	9.4	15	. 37	7.8	7	. 15	4.5	10	. 12
27	8.4	15	.35	12	28	1.7	4.5	10	.11
28	8.6	16	.39	7.2	7	.14	9.8	3	. 32
29	9.1	15	.35	7.2	7	.14	8.1	24	.61
30	8.4	12	. 27				5.0	5	. 07
31	8.4	8	.18				4.5	7	.08
TOTAL	760.7		5283.48	229.3		8.43	182.4		4.28

RIO GRANDE DE LOIZA BASIN 50058350 RIO CAÑAS AT RIO CAÑAS, PR--Continued

		MEAN			MBAN		Mean			
DAY	MEAN DISCHARGE (CFS)	CONCEN- TRATION (MG/L)	SEDIMENT DISCHARGE (TONS/DAY)	MEAN DISCHARGE (CFS)	CONCEN- TRATION (MG/L)	SEDIMENT DISCHARGE (TONS/DAY)	MEAN DISCHARGE (CFS)	CONCEN- TRATION (MG/L)	SEDIMENT DISCHARGE (TONS/DAY)	
		APRIL			MAY			June		
1	4.5	7	.08	58	459	321	10	27	1.3	
2	4.5	7	.08	55	358	123	7.0	18	.37	
3	4.5	ż	.08	12	41	1.5	5.9	14	. 22	
4	4.4	7	.08	7.7	20	.40	17	108	14	
5	3.6	7	.06	6.2	8	. 14	6.2	15	.26	
6	3.1	6	.04	11	33	1.3	5. 6	12	.18	
7	6.6	34	. 67	6.4	12	.22	27	161	43	
8	4.6	28	. 39	4.5	5	.06	22	105	17	
9	4.1	22	. 25	5.2	5	.08	86	708	487	
10	4.1	15	.16	4.3	6	.08	18	80	5.0	
11	4.1	15	. 16	3.5	7	.07	8.9	20	.53	
12	3.6	13	. 13	3.0	6	.05	10	34	1.9	
13	3.6	13	. 13	2.7	4	.03	6.3	14	. 24	
14	3.7	12	. 12	2.7	4	.03	5.4	8	. 13	
15	3.5	8	.08	2.5	5	.04	4.9	8	.09	
16	3.8	11	.11	49	367	277	4.9	13	. 17	
17	4.2	38	.42	6.5	21	.40	4.9	17	. 23	
18	4.0	18	. 19	6.7	10	.18	5.2	20	.28	
19	4.7	7	.08	4.5	7	.09	5.0	20	.26	
20	5.7	5	.08	4.5	6	.08	4.8	20	. 25	
21	3.5	4	.04	3.8	5	. 05	21	98	12	
22	3.5	6	. 05	3.2	5	.04	5.7	18	.29	
23	3.5	8	. 07	50	370	170	4.9	14	. 19	
24	3.5	11	.10	52	355	113	4.9	10	. 13	
25	3.2	17	. 14	20	78	8.1	4.8	8	.10	
26	2.9	23	. 18	134	1060	1490	4.1	7	.08	
27	2.7	29	.22	39	250	33	4.1	6	. 07	
28	2.7	34	. 24	15	32	1.6	4.1	5	.06	
29	8.0	56	3.6	14	45	3.4	3.9	4	. 05	
30	16	111	7.3	8.9	19	.50	3.8	4	.04	
31				7.3	10	.19				
TOTAL	134.4		15.33	603.1		2545.63	326.3		585.42	

50058350 RIO CAÑAS AT RIO CAÑAS, PR--Continued

	MEAN DISCHARGE	Mean Concen- Tration	Sediment Discharge	MEAN DISCHARGE	Mean Concen- Tration	Sediment Discharge	MRAN DISCHARGE	MEAN CONCEN- TRATION	Sediment Discharge
DAY	(CFS)	(MG/L)	(TONS/DAY)	(CFS)	(MG/L)	(TONS/DAY)	(CFS)	(MG/L)	(TONS/DAY)
		JULY			august		S	BP TRMBER	
1	3.8	4	.04	3.8	8	.08	5.7	16	.66
2	5.3	4	.06	2.9	7	.06	5.1	13	. 18
3	4:9	5	.08	3.5	5	.05	5.1	7	.11
4	4.9	6	.09	11	42	3.9	9.4	27	1.3
5	3:5	8	.08	68	4 67	153	12	41	2.2
6	3.5	8	.08	15	59	5.5	61	455	195
7	3.2	8	. 07	4.6	11	.15	65	500	190
8	4.5	8	.10	3.5		.08	19	77	5.6
9	5.3	6	.09	266	1550	3990	12	28	.94
10	4.9	4	.06	33	132	21	9.7	18	.48
11	5.7	5	.08	17	62	3.9	9.1	15	. 36
12	4.5	6	.08	8.8	19	.56	9.4	11	. 25
13	4.9	6	.08	6.3	_6	.10	24	136	26
14	5.3	7	.10	15	59	5.7	7.3	30	.90
15	5.3	7	.10	6.8	16	.35	4.4	10	. 14
16	4.5	7	.09	4.5	9	.10	5.9	9	. 14
17	4.1	7	.08	4.0	7	.08	18	76	8.3
18	4.1	8	.08	3.5	15	.14	5.1	20	.31
19	3.5	7	. 07	3.5	6	.05	20	106	14
20	3.2	6	.06	3.5	4	.04	22	109	15
21	3.2	6	.06	11	46	5.7	25	117	12
22	3.2	6	.06	4.6	11	.15	5.4	12	.18
23	3.2	6	. 05	3.4	6	.06	3.6	19	.18
24	4.5	8	.10	3.2	6	.06	3.1	22	. 18
25	3.2	11	.10	3.0	7	.06	2.9	19	. 15
26	2.4	12	.08	3.1	7	.07	2.9	15	.11
27	2.2	13	.08	3.2	8	. 07	2.8	9	.06
28	2.2	13	.08	2.9	9	.07	2.5	4	.02
29	2.4	12	.08	2.7	9	. 07	2.4	4	.02
30	2.4	10	. 07	5.0	16	.49	6.6	24	1.1
31	3.5	10	.09	7.7	20	.53			
TOTAL	121.3		2.42	534.0		4192.17	386.4		475.87
YEAR	3841.4		13345.89						

50058350 RIO CAÑAS AT CAÑAS, PR--Continued

WATER QUALITY DATA, WATER YEAR OCTOBER 1991 TO SEPTEMBER 1992

PARTICLE-SIZE DISTRIBUTION OF SUSPENDED SEDIMENT

DATE	TIME	DIS- CHARGE, INST. CUBIC FEET PER SECOND	SEDI- MENT, SUS- PENDED (MG/L)	SEDI- MENT, DIS- CHARGE, SUS- PENDED (T/DAY)	SED. SUSP. FALL DIAM. PERCENT FINER THAN .002 MM	SED. SUSP. FALL DIAM. PERCENT FINER THAN .004 MM	SED. SUSP. FALL DIAM. PERCENT FINER THAN .008 MM
JAN 1992							
16	2100	139	2550	957	31	41	46
DATE	SED. SUSP. FAIL DIAM. PERCENT FINER THAN .016 MM	SED. SUSP. FAIL DIAM. PERCENT FINER THAN .031 MM	SED. SUSP. SIEVE DIAM. PERCENT FINER THAN .062 MM	SED. SUSP. SIEVE DIAM. PERCENT FINER THAN .125 MM	SED. SUSP. SIEVE DIAM. PERCENT FINER THAN .250 MM	SED. SUSP. SIEVE DIAM. PERCENT FINER THAN .500 MM	SED. SUSP. SIEVE DIAM. PERCENT FINER THAN 1.00 MM
JAN 1992							
16	57	65	90	97	99	99.8	99.9

50058350 RIO CAÑAS AT CAÑAS, PR--Continued

WATER QUALITY DATA, WATER YEAR OCTOBER 1991 TO SEPTEMBER 1992 SILT AND CLAY PERCENT OF SUSPENDED SEDIMENT

DATE	TIME	STREAM - FLOW, INSTAN - TANEOUS (CFS)	SEDI- MENT, SUS- PENDED (MG/L)	SEDI- MENT, DIS- CHARGE, SUS- PENDED (T/DAY)	SED. SUSP. SIEVE DIAM. PERCENT FINER THAN .062 MM
NOV 1991					
08	1539	12	182	6	91
27	1250	9.6	224	6	99
DEC					
09	1207	5.5	95	1.4	94
JAN 1992					
07	1325	30	81	6.6	98
16	2200	174	1320	619	94
MAY					
18	0757	7.8	44	1	98
SEP					
06	1300	284	3010	2310	94
07	1345	152	874	358	89
30	1712	21	127	7	89

50059000 LAGO LOIZA AT DAMSITE, PR

LOCATION.--Lat 18°19'49", long 66°01'00", Hydrologic Unit 21010005, at pumpsite at damsite, and 1.9 mi (3.1 km) south of Trujillo Alto plaza.

DRANAIGE AREA. -- 208 mi* (539 km²).

ELEVATION RECORDS

PERIOD OF RECORD. -- December 1987 to current year.

GAGE .-- Water-stage recorder. Datum of gage is mean sea level.

REMARKS.--Lake is formed by Loiza Dam, a concrete structure completed in 1954. Useable capacity of impoundment is 30,000 acre-ft (37.0 hm²). Out flow from lake is controlled by five slide gates in powerplant and pump intake structure, four sluice gates, and concrete spillway with eight radial gates. Lake is used for municipal water supply and intermittent power generation. Gage-height satellite telemetry at station.

EXTREMES OBSERVED FOR PERIOD OF RECORD. -- Maximum elevation 147.42 ft (44.93 m), Sept. 18, 1989; minimum elevation, 125.86 ft (38.36 m), June 12, 1988.

EXTREMES OBSERVED FOR CURRENT YEAR.--Maximum elevation 135.30 ft (41.24 m), Sept. 20; minimum elevation, 127.15 ft (38.76 m), May 1.

Capacity Table (based on data from Puerto Rico Electric Power Authority)

Elevation, in feet	Contents in acre-feet	Elevation, in feet	Contents in acre-feet
98.4	5,000	128.6	18,000
111.5	8,900	137.8	26,000
120.4	13,000	147.6	35,000
BLEVAT	ION (FERT NGVD), WATER YEAR DAILY OBSERVATION A		1992

	DAILY OBSERVATION AT 20:00 VALUES												
DAY	OCT	Nov	DEC	JAN	FRB	MAR	APR	MAY	JUN	JUL	AUG	SRP	
1	134.36	133.86	134.70	134.22	134.74	133.59	130.48	127.70	135.01	134.74	133.62	134.21	
2	134.42	134.04	133.48	134.20	134.70	133.46	130.32	129.16	134.69	134.76	133.64	134.19	
3	133.36	134.06	133.84	134.16	134.70	133,36	130.14	129.22	133.54	134.76	133.76	134.25	
4	133.78	134.04	134.46	134.10	134.72	133.28	129.94	129.08	133.80	134.74	133.97	134.33	
5	134.08	134.10	134.72	133.24	134.74	133.24	129.78	128.90	134.68	134.48	133.23	134.51	
6	134.34	134.30	134.12	133.86	134.82	133.18	129.52	129.96	134.41	134.52	134.15	133.49	
7	134.44	134.16	134.24	134.50	134.52	133.10	129.44	130.62	133.87	134.50	133.80	134.73	
8	134.46	133.14	134.36	134.24	134.56	133.24	129.30	130.64	134.75	134.62	134.07	133.37	
9	134.48	134.34	134.46	134.18	134.56	133.16	129.10	130.58	133.78	134.12	134.05	134.05	
10	134.56	134.20	134.52	134.08	134.70	133.04	128.94	130.42	134.02	134.14	134.07	134.16	
11	134.60	134.46	134.56	134.04	134.74	132.90	128.80	130.28	134.22	134.40	133.40	134.18	
12	134.68	134.48	134.64	134.42	134.71	132.78	128.72	130.26	134.64	134.52	133.84	134.16	
13	133.82	134.56	134.72	134.80	134.66	132.58	128.86	130.19	133.94	134.54	134.05	134.14	
14	133.82	134.42	134.88	134.14	134.64	132.46	128.78	130.02	134.04	134.54	134.59	134.08	
15	133.84	134.54	134.37	134.38	134.64	132.38	128.78	129.98	133.32	134.56	133.40	134.02	
16	133.86	134.74	134.40	134.26	134.60	132.26	128.68	133.04	134.00	134.60	133.56	134.18	
17	133.92	134.10	134.44	134.80	134.54	132.22	128.52	134.04	133.48	134.32	133.72	133.34	
18	133.96	134.22	134.44	134.26	134.44	132.24	128.36	134.40	134.22	134.48	133.80	133.74	
19	133.96	134.28	134.42	134.40	134.38	132.18	128.54	134.00	134.60	134.58	133.82	133.18	
20	133.90	134.34	134.60	134.48	134.32	132.12	129.00	134.22	134.14	134.82	133.85	133.90	
21	133.84	133.22	134.38	134.58	134.24	132.04	129.08	134.36	133.52	134.28	133.92	133.17	
22	134.08	133.12	134.42	134.64	134.15	131.93	128.98	134.34	134.34	133.58	133.92	133.69	
23	134.12	133.74	134.44	134.70	134.09	131.82	128.84	131.91	134.84	133.83	133.90	133.33	
24	134.06	134.30	134.42	134.76	134.04	131.68	128.64	134.83	133.92	134.05	134.08	133.79	
25	134.00	134.33	134.38	134.50	133.98	131.50	128.41	133.13	134.14	134.55	134.10	133.37	
26	133.90	134.58	134.32	134.62	133.92	131.33	128.17	134.54	134.32	134.72	134.07	133.59	
27	133.80	134.60	134.30	134.66	133.88	131.16	127.94	134.41	134.46	134.82	134.08	133.77	
28	133.66	134.46	134.26	134.70	133.80	131.06	127.68	134.36	134.58	133.53	134.05	133.09	
29	134.20	134.22	134.22	134.74	133.70	130.96	127.48	134.73	134.66	133.55	134.05	133.27	
30	133.56	134.48	134.16	134.74		130.80	127.34	134.49	134.72	133.53	134.05	133.45	
31	133.66		134.18	134.74		130.60		134.10		133.66	134.15		
MEAN	134.05	134.18	134.38	134.39	134.42	132.31	128.89	132.00	134.22	134.35	133.90	133.82	
MAX	134.68	134.74	134.88	134.80	134.82	133.59	130.48	134.83	135.01	134.82	134.59	134.73	
MIN	133.36	133.12	133.48	133.24	133.70	130.60	127.34	127.70	133.32	133.53	133.23	133.09	

50059000 LAGO LOIZA AT DAMSITE, PR--Continued

WATER-QUALITY RECORDS

PERIOD OF RECORD .-- Water years 1974 to current year.

WATER-QUALITY DATA, WATER YEAR OCTOBER 1991 TO SEPTEMBER 1992

	ı	WATER-QUA	LITY DATA	, WATER	YEAR OCTO	BBR 1991 1	O SEPTEME	BR 1992		
DATE	TIME	SPE- CIFIC CON- DUCT- ANCE (US/CM)	PH WATER WHOLE FIELD (STAND- ARD UNITS)	TEMPER- ATURE WATER (DEG C)	OXYGEN, DIS- SOLVED (MG/L)	OXYGEN, DIS- SOLVED (PER- CENT SATUR- ATION)	OXYGEN DEMAND, CHEM- ICAL (HIGH LEVEL) (MG/L)	0.45 UM-MF (COLS./	STREP- TOCOCCI FBCAL, (COLS. PER 100 ML)	ALKA- LINITY WAT WH TOT PET FIELD MG/L AS CACO3
OCT 1991										
15	1115	350	7.2	26.0	2.8	34	20	56	46	77
DEC										
04 FEB 1992	1140	240	6.9	26.0	4.1	48	28	23	43	72
12	1140	294	6.8	27.5	2.3	30	13	10	10	97
MAY										
01	1320	368	7.0	29.0	4.4	56	24	60	21	100
JUN	0000			20.5			4.5			
12 AUG	0920	186	7.0	28.5	1.2	32	15	90	78	55
10	1345	298	7.4	28.5	1.8	39	27	K600	1100	60
			,				-,	Kooo		
	SULFIDE TOTAL	RESIDUE TOTAL AT 105 DEG. C, SUS-	NITRO- GEN, NITRATE TOTAL	NITRO- GEN, NITRITE TOTAL	NITRO- GEN, NO2+NO3 TOTAL	NITRO- GEN, AMMONIA TOTAL	NITRO- GEN, ORGANIC TOTAL	NITRO- GEN, AM- MONIA + ORGANIC TOTAL	NITRO- GEN, TOTAL	NITRO- GEN, TOTAL
DATE	(MG/L	PENDED	(MG/L	(MG/L	(MG/L	(MG/L	(MG/L	(MG/L	(MG/L	(MG/L
	AS S)	(MG/L)	AS N)	AS N)	AS N)	AS N)	AS N)	AS N)	AS N)	AS NO3)
OCT 1991										
15	<0.5	5	0.078	0.010	0.088	0.300	0.50	0.80	0.89	3.9
DRC										
04 FRB 1992		16	0.560	0.040	0.600	0.170	0.43	0.60	1.2	5.3
12		14		<0.010	<0.050	0.280	0.12	0.40		
MAY				10.020	(0.020	0.200	****			
01	<0.5	7	0.300	0.110	0.410	0.060	0.44	0.50	0.91	4.0
JUN										
12 AUG		43	0.460	0.060	0.520	0.400	0.40	0.80	1.3	5.8
10		54	0.530	0.080	0.610	0.190	0.51	0.70	1.3	5.8
							_			_
DATI	PHOR PHOR TOT. R (MG. AS:	US REC AL ERA /L (UG	AL TOI OV- REC BLB BRA /L (UC	CAL TO: COV- REG BLE ERI	ON, NE: TAL TO' COV- REG ABLE BRI G/L (U	COV- REG ABLE ERI G/L (UG	PAL COV- CYAN ABLE TOT S/L (MG	AL PHENO	BL ACT LS SU L STA	HY- NB IVB B- NCB /L)
OCT 199	1									
15		280	90	80 :	1200	260	100 <0.	010	2 0	.07
DEC								-	_ •	
04		200 -							-	-
FRB 1993	_	070 -								_
MAY	U.	070 -	- •		'		-		-	_
01	0.:	200	50	20	120	150	40 <0.	010	0.	09
JUN							1			
12 AUG	0.:	250 -				•-			-	-
10	0.:	250 -							_	_

K = non-ideal count

50059100 RIO GRANDE DE LOIZA BELOW TRUJILLO ALTO, PR

WATER-QUALITY RECORDS

LOCATION.--Lat 18°21'35", long 66°00'15", 100 ft (30 m) downstream of Highway 181 bridge, 0.4 mi (0.6 km) northwest of Trujillo Alto plaza, and 2.2 mi (3.5 km) northeast of Lago Loixa Reservoir.

TEMPER-

PH WATER

WHOLE

FIELD (STAND-

DRAINAGE AREA. -- 213 mi² (552 km²).

PERIOD OF RECORD. -- Water years 1981 to current year.

REMARKS: Flow controlled by Lago Loiza reservoir.

DIS-

SPE-

CIFIC

CON-DUCT-

CHARGE,

INST. CUBIC FERT

WATER-QUALITY DATA, WATER YEAR OCTOBER 1991 TO SEPTEMBER 1992

TUR-

OXYGEN,

COLI-

FORM,

FECAL, 0.45 UM-MF

STREP-

TOCOCCI FECAL,

OXYGEN

DEMAND,

CHEM-

ICAL (HIGH

OXYGEN,

DIS-

SOLVED

(PER-CENT

DATE	TIME	CUBIC FERT PER SECOND	CON- DUCT ANCE (US/C	r- (Sta B ar	IND- ID	EMPER- ATURE WATER DEG C)	TUF BII ITY (NTU)- DI 7 S OL	S- CI	SNT (H FUR- LEY	IGH UM BL) (CO	45 I-MP LS./ ML)	FECAL, (COLS. PER 100 ML)
OCT 1991													
15 DEC	1020	11	4	118	7.6	30.5	1.	. 0	4.0	53	18 K	9300	2000
04 FEB 1992	1050	10	3	166	7.1	25.5	8.	. 6	6.1	90	11	2900	690
21 MAY	1035	11	3	350	7.9	27.5	2.	.2 1	0.2	135	10	K740	K10
11 JUN	1100	3.0	4	118	7.3	31.0	8.	.3 1	1.5	151	20	500	K140
16	1300	10	4	125	7.0	32.5	6.	. 9	9.3	108	13	K90	K65
12	0740	14	3	10	7.5	27.5	3.	.7	5.3	74	<10	2900	200
DATE	NE TO (M A CA	TAL D G/L S S (LCIUM IS- OLVED MG/L S CA)	MAGNE- SIUM, DIS- SOLVED (MG/L AS MG)	SODIU DIS- SOLVE (MG/ AS N	M, SC D 1 L RA	DDIUM AD- DRP- TION ATIO	POTAS- SIUM, DIS- SOLVED (MG/L AS K)	ALKA- LINITY WAT WH TOT FET FIELD MG/L AS CACO3	SULFIDE TOTAL (MG/L AS S)	SULFATE DIS- SOLVED (MG/L AS SO4)	DIS SOI (MC	DR,
ОСТ 1991 15		100	26	9.7	23		1	4.3	110	<0.5	19	26	6
DEC 04									110			_	
FRB 1992 21									120				
MAY							_						_
11 JUN 16		140	33	13	31		1	2.8	140 60	<0.5	27	3 (•
AUG													
12		100	26	9.4	20		0.9	2.9	100		18	22	2
DATE	RII D So: (M	DE, D IS- S LVED (G/L	LICA, IS- OLVED MG/L AS IO2)	SOLIDS, SUM OF CONSTI- TUENTS, DIS- SOLVED (MG/L)	SOLID DIS SOLV (TON PER DAY	S, TOT S- AT PED DEC IS SU PEN	SIDUE TAL 105 S. C, US- IDED	NITRO- GEN, NITRATE TOTAL (MG/L AS N)	NITRO- GEN, NITRITE TOTAL (MG/L AS N)	NITRO- GEN, NO2+NO3 TOTAL (MG/L AS N)	GEN,	GI ORGI TOT	TRO- ZN, ANIC FAL 3/L N)
OCT 1991					_								
DEC			26	200		98	<1		<0.010	0.350			0.77
04 FRB 1992						•	22	0.890	0.020	0.910	0.030	• •	0.27
21 May							3	0.540	0.020	0.560			0.35
11 Jun	1	0.20	25	252	2.	01	<1	0.450	0.030	0.480	0.070	•	0.43
16 AUG							10	0.640	0.010	0.650	0.040	• •	0.16
12	1	0.20	23	182	6.	88	5	0.960	0.030	0.990	0.060	• •	0.24

K = non-ideal count

50059100 RIO GRANDE DE LOIZA BELOW TRUJILLO ALTO, PR--Continued WATER-QUALITY DATA, WATER YEAR OCTOBER 1991 TO SEPTEMBER 1992

DATE	NITRO- GEN, AM- MONIA + ORGANIC TOTAL (MG/L AS N)	NITRO- GEN, TOTAL (MG/L AS N)	NITRO- GEN, TOTAL (MG/L AS NO3)	PHOS- PHORUS TOTAL (MG/L AS P)	ARSENIC TOTAL (UG/L AS AS)	BARIUM, TOTAL RECOV- ERABLE (UG/L AS BA)	BORON, TOTAL RECOV- ERABLE (UG/L AS B)	CADMIUM TOTAL RECOV- ERABLE (UG/L AS CD)	CHRO- MIUM, TOTAL RECOV- ERABLE (UG/L AS CR)	COPPER, TOTAL RECOV- ERABLE (UG/L AS CU)
OCT 1991										
15 DBC	0.80	1.2	5.1	0.240	<1	<100	60	<1	1	<10
04 FRB 1992	0.30	1.2	5.4	0.210						
21 MAY	0.40	0.96	4.2	0.210						
11 JUN	0.50	0.98	4.3	0.200	1	100	50	<1	<1	10
16 AUG	0.20	0.85	3.8	0.120						
12	0.30	1.3	5.7	0.190						
DATE	IRON, TOTAL RECOV- ERABLE (UG/L AS FE)	LEAD, TOTAL RECOV- ERABLE (UG/L AS PB)	MANGA - NESE, TOTAL RECOV - ERABLE (UG/L AS MN)	MERCURY TOTAL RECOV- ERABLE (UG/L AS HG)	SELE- NIUM, TOTAL (UG/L AS SE)	SILVER, TOTAL RECOV- ERABLE (UG/L AS AG)	ZINC, TOTAL RECOV- ERABLE (UG/L AS ZN)	CYANIDE TOTAL (MG/L AS CN)	PHENOLS TOTAL (UG/L)	MRTHY- LENE BLUE ACTIVE SUB- STANCE (MG/L)
ОСТ 1991	TOTAL RECOV- ERABLE (UG/L AS FE)	TOTAL RECOV- ERABLE (UG/L AS PB)	NESE, TOTAL RECOV- ERABLE (UG/L AS MN)	TOTAL RECOV- ERABLE (UG/L AS HG)	NIUM, TOTAL (UG/L AS SE)	TOTAL RECOV- ERABLE (UG/L AS AG)	TOTAL RECOV- ERABLE (UG/L AS ZN)	TOTAL (MG/L AS CN)	TOTAL (UG/L)	LENE BLUE ACTIVE SUB- STANCE (MG/L)
OCT 1991 15	TOTAL RECOV- ERABLE (UG/L AS FE)	TOTAL RECOV- ERABLE (UG/L AS PB)	NESE, TOTAL RECOV- ERABLE (UG/L	TOTAL RECOV- ERABLE (UG/L AS HG)	NIUM, TOTAL (UG/L	TOTAL RECOV- ERABLE (UG/L AS AG)	TOTAL RECOV- ERABLE (UG/L	TOTAL (MG/L	TOTAL	LENE BLUE ACTIVE SUB- STANCE (MG/L)
OCT 1991 15 DEC 04 FRB 1992	TOTAL RECOV- ERABLE (UG/L AS FE)	TOTAL RECOV- ERABLE (UG/L AS PB)	NESE, TOTAL RECOV- ERABLE (UG/L AS MN)	TOTAL RECOV- ERABLE (UG/L AS HG)	NIUM, TOTAL (UG/L AS SE)	TOTAL RECOV- ERABLE (UG/L AS AG)	TOTAL RECOV- ERABLE (UG/L AS ZN)	TOTAL (MG/L AS CN)	TOTAL (UG/L)	LENE BLUE ACTIVE SUB- STANCE (MG/L)
OCT 1991 15 DEC 04	TOTAL RECOV- ERABLE (UG/L AS FE)	TOTAL RECOV- ERABLE (UG/L AS PB)	NESE, TOTAL RECOV- ERABLE (UG/L AS MN)	TOTAL RECOV- ERABLE (UG/L AS HG)	NIUM, TOTAL (UG/L AS SE)	TOTAL RECOV- ERABLE (UG/L AS AG)	TOTAL RECOV- ERABLE (UG/L AS ZN)	TOTAL (MG/L AS CN)	TOTAL (UG/L)	LENE BLUE ACTIVE SUB- STANCE (MG/L)
OCT 1991 15 DEC 04 FRB 1992 21	TOTAL RECOV- ERABLE (UG/L AS FE)	TOTAL RECOV- ERABLE (UG/L AS PB)	NESE, TOTAL RECOV- ERABLE (UG/L AS MN)	TOTAL RECOV- ERABLE (UG/L AS HG) <0.10	NIUM, TOTAL (UG/L AS SE) <1	TOTAL RECOV- ERABLE (UG/L AS AG) <1	TOTAL RECOV- ERABLE (UG/L AS ZN)	TOTAL (MG/L AS CN) <0.010	TOTAL (UG/L) 1	LENE BLUE ACTIVE SUB- STANCE (MG/L)
OCT 1991 15 DEC 04 FRB 1992 21 MAY 11	TOTAL RECOV- ERABLE (UG/L AS FE)	TOTAL RECOV- ERABLE (UG/L AS PB)	NESE, TOTAL RECOV- ERABLE (UG/L AS MN)	TOTAL RECOV- RRABLE (UG/L AS HG) <0.10	NIUM, TOTAL (UG/L AS SE) <1	TOTAL RECOV- BRABLE (UG/L AS AG)	TOTAL RECOV- ERABLE (UG/L AS ZN)	TOTAL (MG/L AS CN) <0.010	TOTAL (UG/L) 1	LENE BLUE ACTIVE SUB- STANCE (MG/L)

50061000 RIO GRANDE DE LOIZA AT CAROLINA, PR

LOCATION.--Lat 18°22'39", long 65°57'08", Hydrologic Unit 21010005, on upstream right bank of Highway 3 bridge, at Km 11.5, 0.5 mi (0.8 km) southeast of Carolina Plaza, 3.3 mi (5.3 km) west of Canóvanas Plaza and 2.5 mi (4.0 km) southwest of Cerro San José.

DRAINAGE AREA. -- 243 mi2 (629 km2).

WATER-STAGE RECORDS

PERIOD OF RECORD. -- January 1991 to current year (gage-height only).

GAGE. -- Water-stage recorder. Elevation of gage is 32.8 ft (10.0 m), from topographic map.

REMARKS. -- Flow regulated by Lago Loiza Dam. Gage-height and precipitation satellite telemetry at station.

EXTREMES FOR CURRENT PERIOD.--JANUARY TO SEPTEMBER 1991: Maximum gage-height, 12.76 ft (3.889 m), July 16; minimum, 4.01 ft (1.222 m), Aug. 6.

WATER YEAR 1992: Maximum gage-height, 33.18 ft (10.113 m), Jan. 6; minimum 3.91 ft (1.192 m), June 30.

GAGE HEIGHT, FEET, WATER YEAR OCTOBER 1990 TO SEPTEMBER 1991 DAILY MEAN VALUES

DAY	OCT	NOV	DEC	JAN	FBB	MAR	APR	MAY	JUN	JUL	AUG	SEP
1 2					5.13	5.04	5.81	5.73	5.14	6.58	4.90	5.09
2					5.00	4.79	6.02	5.87	5.19	6.13	4.83	5.13
3					5.25	4.86	6.24	6.06	5.28	5.84	4.81	5.06
4					5.40	4.96	6.49	6.29	5.28	5.10	4.87	5.09
5					6.70	5.02	6.63	6.52	5.27	5.08	4.86	5.28
6 7					7.33	5.82	6.21	6.01	5.33	5.04	4.78	5.3 5
7					6.88	5.95	5.30	5.43	5.38	4.96	4.83	5.83
8 9					4.84	4.88	5.37	5.54	5.34	5.44	4.93	5.69
9					4.83	4.87	5.23	5.89	5.29	5.09	4.98	5.34
10					4.85	4.92	5.06	6.09	5.24	4.92	5.01	5.28
11					5.76	5.10	5.12	6.15	5.18	4.97	5.04	5.23
12					5.41	6.02	5.27	6.35	5.14	5.02	5.03	5.32
13					6.14	5.72	5.54	6.67	5.18	5.02	4.92	5.30
14					5.95	5.89	5.66	6.54	5.24	5.10	4.95	5. 25
15					5.03	5.78	5.93	4.82	5.25	5.38	4.93	5.29
16					4.83	5.57	6.74	4.86	5.27	8.17	4.89	5.30
17					5.02	5.44	6.63	4.91	5.24	6.20	4.95	6.69
18					5.83	5.55	4.77	4.92	5.22	5.58	4.85	6.38
19					6.50	5.84	4.82	5.02	5.26	6.29	4.79	5.22
20					7.19	6.09	4.83	6.12	5.18	5.22	4.85	5.31
21					5.03	6.18	4.86	5.18	5.21	4.82	4.88	5.35
22				5.25	5.45	6.41	4.95	5.07	5.17	4.80	4.90	6.77
23				5.22	4.79	6.12	5.00	5.08	5.11	4.85	5.04	6.55
24				5.16	4.71	5.56	5.17	4.99	5.10	4.85	5.02	5.49
25				5.21	4.77	5.38	5.36	5.02	5.09	4.82	5.06	6.31
26				5.24	4.83	5.45	5.52	5.12	5.21	4.86	5.09	5.65
27				5.21	4.86	5.56	5.55	5.11	5.28	4.94	5.29	5.46
28				5.32	5.17	5.45	5.32	5.09	5.24	5.43	7.32	5.47
29				5.23		5.39	5.45	5.08	5.26	5.14	5.55	7.51
30				5.28		5.46	5.60	5.20	5.26	4.99	5.15	6.88
31				5.27		5.61		5.19		4.97	5.10	
MEAN					5.48	5.51	5.55	5.55	5.23	5.34	5.05	5.66
MAX					7.33	6.41	6.74	6.67	5.38	8.17	7.32	7.51
MIN					4.71	4.79	4.77	4.82	5.09	4.80	4.78	5.06

50061000 RIO GRANDE DE LOIZA AT CAROLINA, PR --Continued

GAGE HEIGHT, FEET, WATER YEAR OCTOBER 1991 TO SEPTEMBER 1992 DAILY MEAN VALUES

					DAIL	Y MKAN VA	LOES					
DAY	OCT	NOV	DEC	JAN	FRB	MAR	APR	MAY	JUN	JUL	AUG	SRP
1	5.46	6.58	5.34	5.03	4.84	4.76	5.41	5.59	5.80	4.73	5.03	5.66
2	6.59	6.22	6.45	5.08	4.91	4.82	5.50	6.27	6.97	4.84	4.97	5.47
3	6.71	5.93	5.44	5.13	5.06	4.87	5.56	4.97	5.95	4.89	4.99	5.28
4	5.46	5.76	5.26	5.21	5.32	4.83	5.61	4.81	6.22	4.90	5.06	5.19
5	5.42	5.66	5.23	9.89	5.18	4.84	5.65	4.82	5.00	5.47	7.98	5.42
6 7	5.36	5.68	5.89	18.54	4.90	4.87	5.72	5.04	5.85	4.85	7.15	6.36
7	5.30	7.80	5.17	7.02	5.54	4.84	5.78	4.94	6.46	4.76	5.98	6.16
8	5.33	11.26	5.04	6.17	4.89	4.82	5.90	4.88	5.27	4.76	4.91	6.87
9	5.12	10.23	5.04	6.14	4.86	4.94	6.01	4.91	7.05	5.53	5.60	6.12
10	5.08	6.79	5.04	6.75	4.79	4.93	6.15	4.98	6.00	4.82	5.37	5.63
11	5.14	5.39	5.05	5.08	4.74	4.82	6.26	4.99	6.19	4.81	6.26	6.26
12	5.15	6.27	5.05	5.51	4.83	4.78	6.35	4.98	6.67	4.79	4.92	5.92
13	6.12	5.40	5.16	5.12	4.87	4.79	6.39	5.01	7.10	4.81	4.94	6.20
14	5.18	6.18	5.20	5.96	4.85	4.82	6.40	4.96	6.17	4.82	5.18	6.15
15	5.22	5.37	5.85	4.96	4.89	4.84	6.40	4.89	4.99	4.83	6.29	5.81
16	5.23	5.38	5.10	5.30	4.92	4.93	6.12	4.85	6.08	4.85	4.99	5.56
17	5.19	6.19	5.07	5.26	4.86	4.95	5.13	4.89	5.18	5.35	4.90	6.65
18	5.23	5.49	5.07	5.83	4.90	5.10	5.03	6.25	5.48	5.18	4.97	5.23
19	5.37	5.44	5.06	4.98	4.88	4.89	5.00	6.53	4.77	4.85	5.13	6.12
20	5.47	5.61	5.27	4.86	4.79	4.81	4.94	5.65	5.10	4.84	4.98	9.50
21	5.61	6.03	6.35	4.84	4.78	4.79	4.93	4.94	7.64	5.59	5.00	10.19
22	5.57	6.99	5.74	4.82	4.75	4.98	4.93	4.88	4.83	5.89	5.02	7.12
23	5.51	6.54	5.29	4.81	4.71	5.23	4.82	6.70	4.74	5.28	5.03	6.47
24	5.41	6.05	5.20	4.72	4.68	4.94	4.78	11.29	5.84	4.93	4.99	5.67
25	5.41	6.61	5.24	5.31	4.72	4.81	4.95	6.52	4.83	4.82	5.15	6.28
26	5.41	5.42	5.12	4.87	4.65	4.82	5.01	12.94	4.77	4.86	5.17	5.71
27	5.43	6.06	5.14	4.92	4.68	4.93	4.86	7.33	4.68	4.88	5.17	5.95
28	5.56	5.95	5.05	4.88	4.72	4.89	4.85	6.08	4.69	6.15	5.55	6.48
29	5.71	5.95	5.13	4.82	4.74	5.00	5.07	5.56	4.71	4.95	5.56	6.04
30	6.26	5.55	5.09	4.86		5.19	5.65	6.11	4.74	4.91	5.61	6.27
31	7.20		5.06	4.84		5.30		5.80		5.02	5.60	
MBAN	5.56	6.33	5.30	5.86	4.87	4.91	5.51	5.88	5.66	5.03	5.40	6.26
MAX	7.20	11.26	6.45	18.54	5.54	5.30	6.40	12.94	7.64	6.15	7.98	10.19
MIN	5.08	5.37	5.04	4.72	4.65	4.76	4.78	4.81	4.68	4.73	4.90	5.19

WTR YR 1992 MEAN 5.55 MAX 18.54 MIN 4.65

50061800 RIO CANOVANAS NEAR CAMPO RICO, PR

LOCATION.--Lat 18°19'08", long 65°53'21", Hydrologic Unit 21010005, at center pier on downstream side of bridge, on paved secondary road, 0.4 mi (0.6 km) northeast of junction of Highways 185 and 186, 1.5 mi (2.4 km) south of Campo Rico, and 4.4 mi (7.1 km) south of Loiza.

DRAINAGE AREA. -- 9.84 mi 2 (25.48 km2).

WATER-DISCHARGE RECORDS

PERIOD OF RECORD. -- March 1967 to current year.

GAGE.--Water-stage recorder and crest-stage gage. Elevation of gage is 225 ft (68 m), from topographic map.

REMARKS. -- Records fair except those for estimated daily discharges, which are poor.

	DI	SCHARGE,	CUBIC FEE		ND, WATER AILY MEAN		TOBER 199	1 TO SEPTI	MBER 199	2		
DAY	ост	NOV	DRC	JAN	FEB	MAR	APR	MAY	JUN	JUL	AUG	SEP
1	e21	20	15	9.4	8.0	5.8	4.8	289	11	9.7	9.7	e10
2	e19	31	23	9.0	7.5	5.7	5.1	339	14	10	9.7	07.4
3	e10	14	23	8.7	7.8	5.6	4.9	41	9.2	10	9.9	e8.8
4	e11	12	40	8.6	8.5	5.5	4.8	16	23	10	11	e8.0
5	e16	12	18	376	8.4	6.0	4.6	10	16	11	127	e23
6	e10	33	14	218	12	5.9	4.6	169	17	11	59	e26
7 8	e6.0	109	12	37	15	6.1	6.8	44	57 24	11 23	18 17	e14 e7.6
	e5.4	377	12	21	9.5	10	6.9	16		18	12	e10
9	e5.8	68 79	12	19	8.1	6.9	6.4	13 12	14 20	14	12	e12
10	e5.4	/3	13	38	8.4	6.0	14	14	20	14	1.	612
11	5.0	21	12	20	8.0	5.6	6.8	11	19	15	20	e8. 0
12	5.3	16	13	15	7.4	5.6	5.5	11	147	13	22	e6.8
13	5.5	13	13	38	7.3	5.5	5.5	8.7	32	17	13	e6.2
14	5.0	11	15	21	7.2	5.6	5.9	7.9	34	19	18	e6.4
15	4.7	9.9	12	16	7.2	6.5	5.5	8.1	19	14	17	e15
16			- 0	4.4				14	72	16	13	e32
17	4.3	9.7 8.9	10	14	6.8 6.5	5.9	4.6 4.6	17	43	27	20	e29
			11	13		9.3				18	11	e28
18	4.1	8.2	9.8	12	6.3	11	4.6	11 19	19 13	13	9.5	e50
19 20	4.1	7.7 7.5	9.3 46	12 11	6.5 6.7	9.1 7.2	7.3 9.2	13	12	12	9.0	e58
20	4.1	,.,	40	**	0.7	,.2	3.2	13	+-		2.0	
21	3.9	22	44	11	6.2	6.4	5.8	10	22	11	8.6	e2 0
22	3.8	100	18	9.9	6.6	15	4.9	9.2	18	14	8.2	e17
23	4.1	29	14	10	6.8	12	4.6	339	12	13	7.8	13
24	3.7	53	12	9.6	21	7.1	4.4	201	10	15	e7.4	11
25	3.4	21	11	9.8	7.0	5.9	4.0	34	9.6	16	e7.2	9.5
26	3.4	15			6.7		4.5	128	9.2	12	e7.0	8.7
27	3.7	16	11 11	9.8 9.7	6.8	5.5 5.6	4.4	49	9.7	14	e7.0	7.9
28	4.7	17	10	9.0	6.8	5.4	5.5	25	9.5	13	e6.8	7.4
29	6.1	15	10	8.8	6.2	5.4	5.6	17	9.5	11	e7.0	8.5
30	9.3	16	9.6	8.4		5.1	14	14	9.7	10	e13	16
31	7.7		9.3	8.5		5.0		12		9.9	e22	
			2.0	•••								
TOTAL	209.7	1171.9	493.0	1021.2	237.2	213.2	180.1	1907.9	734.4	430.6	539.8	485.2
WEYN	6.76	39.1	15.9	32.9	8.18	6.88	6.00	61.5	24.5	13.9	17.4	16.2
MAX	21	377	46	376	21	15	14	339	147	27	127	58
MIN	3.4	7.5	9.3	8.4	6.2	5.0	4.0	7.9	9.2	9.7	6.8	6.2
AC-FT	416	2320	978	2030	470	423	357	3780	1460	854	1070	962
CFSM	.69	3.97	1.62	3.35	.83	.70	.61	6.25	2.49	1.41	1.77	1.64
IN.	.79	4.43	1.86	3.86	.90	. 81	.68	7.21	2.78	1.63	2.04	1.83
e B	stimated											
		MONTHUT V M	BAN DATA F	א משתגש מחי	Pape 1067	_ 1002	DV WAMPD	VDAD /WV	`			
DIATIS	TICS OF I	M Idhinos	DAN DATA F	OR MAIDE I	PW40 1101	- 1774,	DI MAISK	וא) אותנוג (או	,			
MBAN	45.5	46.5	34.4	24.2	19.6	14.7	16.3	30.6	19.2	18.0	26.7	33.0
MAX	273	125	116	62.4	48.4	36.2	53.2	93.2	63.7	63.7	137	103
(WY)	1971	1985	1971	1969	1988	1969	1971	1969	1970	1979	1979	1979
MIN	6.74	6.66	5.82	6.66	4.04	3.54	4.66	4.28	2.80	3.72	5.69	5.20
(WY)	1968	1981	1968	1977	1977	1977	1984	1974	1974	1974	1991	1967
SUMMAR	Y STATIST	rics	FOR	1991 CALEN	DAR YRAR	F	OR 1992 W	ATER YEAR		WATER Y	EARS 1967	- 1992
ANNUAL	TOTAL			5109.5			7624.2					
ANNUAL	MRAN			14.0			20.8	i		27.8		
	T ANNUAL									58.0		1971
	ANNUAL I									11.0		1977
	T DAILY			377	Nov 8			Nov 8		3160		9 1970
	DAILY M			2.7	Jul 21			Oct 25		. 8	o Jul	24 1977
		AY MINIMU		2.8	Jul 19		3.7			1.5	Jul	18 1977
		PEAK FLOW					5140			15000	Sep	13 1982
		PRAK STAG	B					8 Jan 5		1.5 15000 13.1	.0 Sep	13 1982
	TANBOUS I			40455			3.1					
	RUNOFF			10130	,		15120			20110 2.8	12	
	RUNOFF			1.42			2.1 28.8			38.3		
	RUNOFF			19.32 23	•		28.8 31	_		45	-	
	CENT EXC			23 9.0			10			13		
	CENT EXC			3.7			5.4			5.3	3	
JU FER	DAC			3.7			5.4			J.,	-	

50061800 RIO CANOVANAS NEAR CAMPO RICO, PR--Continued

WATER QUALITY RECORDS

PERIOD OF RECORD. -- WATER YEARS AUGUST 1981 TO CURRENT YEAR

DATE TIME	STREAMFLOW, INSTANTANEOUS (CFS)	SPECIFIC CON- DUCTANCE (UMHOS)	TEMPERA- TURE (DEG C)	DATE	TIME	STREAMFLOW, INSTANTANEOUS (CFS)	SPECIFIC CON- DUCTANCE (UMHOS)	TEMPERA- Ture (Deg C)
MAR. 11 1335 MAY 22 1150 APR. 09 1315	5.43 9.43 6.33	190 200 190	25.0 26.5 24.5	JUN. 20 JUL. 23		10.8 13.3	210 220	25.5 27.0

THIS PAGE WAS LEFT BLANK INTENTIONALLY




Figure 21:-Northeastern river basins the Río Herrera to Río Antón Ruíz basins.

50063440 QUEBRADA SONADORA NEAR EL VERDE, PR

LOCATION.--Lat 18°19'24", long 65°49'03", Hydrologic Unit 21010005, in Caribbean National Forest, at El Yunque, 0.6 mi (1.0 km) upstream from Río Espíritu Santo, 0.2 mi (0.3 km) upstream from Highway 186, and about 1.2 mi (1.9 km) south of El Verde.

DRAINAGE AREA. -- 1.01 mi 2 (2.62 km2).

WATER-DISCHARGE RECORDS

PERIOD OF RECORD. -- March 1983 to current year.

GAGE.--Water-stage recorder and crest-stage gage. Elevation of gage is 1,230 ft (375 m), from topographic map. REMARKS .-- Records poor.

		DISCH	ARGE, CUB	IC FEET PEF		WATER Y		BR 1991 T	O SEPTEMB	ER 1992		
DAY	OCT	NOV	DEC	JAN	FRB	MAR	APR	MAY	JUN	JUL	AUG	SEP
1	7.1	9.0	5.7	1.5	.54	e.21	.88	147	1.3	.18	.38	.38
2	5.1	4.2	17	. 90	.42	e.22	.73	76	3.6	. 15	.49	.79
3	2.5	5.7	38	. 67	.49	e.21	.44	5.5	.72	. 14	3.1	1.8
5	3.1 6.5	9.4	10 12	.56 51	1.1	e.18	.32	1.4	3.1 1.7	.12	2.5	12 . 89
6	2.5 1.5	17 46	6.2 3.5	6.2	4.1	29	1.2	63 8.9	8.4	.12	53 4.8	1.8
8	1.3	89	7.3	3.6	1.8	2.6	13	2.8	2.3	7.6	3.5	5.1
9	1.2	18	5.4	32	.83	.77	6.6	6.8	.96	8.9	1.6	12
10	2.4	12	3.9	39	6.6	.60	2.0	8.8	29	2.0	1.9	.77
11	1.6	3.0	2.2	6.0	1.2	.49	1.3	11	18	20	23	. 93
12	7.5	3.7	9.9	7.7	.66	8.8	12	1.9	14	1.2	11	.23
13	2.4	3.1	5.9	35	.49	1.8	5.3	1.3	4.5	3.9	4.3	.18
14 15	1.3	1.7	1.7	5.8 4.2	.39	1.7	3.0 1.9	1.1	3.7 1.8	14	19	.20 e3.0
16 17	.89	1.9	1.4	3.4	.26	. 69 16	.89	35 1.8	3.9	8.8	3.6	e4.0 26
18	.76	1.3	2.1	2.5	.19	27	28	1.1	1.5	9.5	2.0	6.8
19	.65	1.1	2.2	2.2	.21	7.6	4.8	1.1	1.9	1.8	.90	e1.0
20	.57	1.1	14	2.0	.44	2.6	1.7	1.5	.85	7.9	2.3	e10
21	.49	46	3.5	1.7	.20	1.3	1.0	.76	6.5	6.5	e1.5	e4.0
22	.42	39	1.8	1.6	2.4	5.6	.82	. 62	1.5	18	e.33	e.60
23	-40	30	1.6	1.4	. 68	7.7	.73	57	3.5	7.4	.36	e.50
24 25	.33 e.29	20 6.1	1.1	2.1	1.1	1.4	.63	18 5.6	.77	8.4	2.0 .25	e.45 e.30
26 27	e.27	9.7	1.2	1.4	2.0	.76	.48	14 11	1.4	1.7	.50	e.25 e.23
28	e.21	9.2	1.5	4.2	e.53	.67	.43	1.6	.45	6.3	.46	e.21
29	e.21	12	1.4	1.8	e.28	. 64	6.2	1.4	.30	8.1	1.2	e.20
30	e.23	7.8	1.6	.93		5.6	32	2.1	.23	1.2	.13	e.20
31	e.20		1.3	.70		1.9		1.2		. 55	9.3	
TOTAL	54.07	428.2	172.19	255.66	46.23	130.58	143.37	492.23	170.05	208.82	183.95	104.81
MRAN	1.74	14.3	5.55	8.25	1.59	4.21	4.78	15.9	5.67	6.74	5.93	3.49
MAX	7.5	89	38	51	17	29	32	147	42	24	53	26
AC-FT	.20 107	1.1 849	.92 342	. 56 507	.19 92	. 18 259	.32 284	976	.23 337	.09 414	.13 365	.18 208
CFSM	1.73	14.1	5.50	8.17	1.58	4.17	4.73	15.7	5.61	6.67	5.88	3.46
IN.	1.99	15.77	6.34	9.42	1.70	4.81	5.28	18.13	6.26	7.69	6.78	3.86
e B	stimated											
STATIS	TICS OF M	ONTHLY M	BAN DATA	FOR WATER Y	EARS 198	3 - 1992	, BY WATE	R YEAR (W	Y)			
MEAN	6.90	10.9	8.06	6.20			F 0F	0.60		6.66	7.79	6.43
MAX	17.1	20.1	21.6	10.8	12.0	6.08	5.25 9.99	8.60 15.9	6.01	12.8	14.5	15.6
(WY)	1986	1985	1988	1988	1988	1990	1987	1992	1987	1983	1988	1989
MIN	1.74	2.47	.95	3.41	1.59	2.32	1.09	4.02	.98	2.36	3.37	2.34
(WY)	1992	1991	1990	1985	1992	1984	1984	1991	1985	1991	1991	1986
SUMMAR	Y STATIST	rics	FOR	1991 CALEN	DAR YEAR	ı	FOR 1992	WATER YEA	R	WATER	YEARS 1983	- 1992
ANNUAL				1717.35			2390.				55.	
ANNUAL		MOLN		4.71			6.	53		7.		1988
	T ANNUAL M									9.4		1991
	T DAILY M			89	Nov 8		147	May	1	216		7 1987
	DAILY ME			0.27	Aug 8				7			7 1992
	SEVEN-DA		M		Aug 6			15 Jul			11 Aug	6 1991
	TANEOUS P						1180	May	1	2230		7 1987
	TANEOUS P		B	67.00				14 May	1	9.	42 Dec	7 1987
	RUNOFF (3410			4740	47		5110		
	RUNOFF (4.66			6.			6. 94.		
	RUNOFF (63.25 13	,		88. 17	03		17	74	
	CENT BACE			1.6			1.	В		3.	0	
	CENT EXCE			.27				30			69	

50063440 QUEBRADA SONADORA NEAR EL VERDE, PR--Continued

WATER QUALITY RECORDS

PERIOD OF RECORD. -- WATER YEARS APRIL 1983 TO CURRENT YEAR

DATE T	IMB	STREAMFLOW, INSTANTANEOUS (CFS)	SPECIFIC CON- DUCTANCE (UMHOS)	TEMPERA- TURE (DEG C)	DATE		TIME	STREAMFLOW, INSTANTANEOUS (CFS)	SPRCIFIC CON- DUCTANCE (UMHOS)	TEMPERA- TURE (DEG C)
FEB. 20 10	056	0.43	50	20.5	AUG.	25	1006	0.23	40	21.0
MAR. 12 13	325	0.45	50	21.5	SEP.	16	1022	5.89	50	23.5
JUN. 23 1	148	7.10	60	24.5						

50063500 QUEBRADA TORONJA AT EL VERDE, PR

LOCATION.--Lat 18°19'43", long 65°49'14", Hydrologic Unit 21010005, in Caribbean National Forest, at downstream side of culvert on Highway 186, 0.2 mi (0.3 km) upstream from Río Espíritu Santo, and about 0.9 mi (1.4 km) south of El Verde.

DRAINAGE AREA. -- 0.064 mi 2 (0.166 km2).

WATER-DISCHARGE RECORDS

PERIOD OF RECORD. -- April 1983 to current year.

GAGE.--Water-stage recorder and concrete broad-V-notch crested weir. Elevation of gage is 876 ft (267 m), from topographic map.

REMARKS. -- Records fair.

		DISCHAR	GR, CUBIC	FERT PER		WATER :	YBAR OCTOBER VALUES	1991 TO	September	1992		
DAY	OCT	NOV	DEC	JAN	FE B	MAR	APR	МАЧ	JUN	JUL	AUG	SEP
1	.21	. 11	.25	. 12	.11	. 04	.04	1.7	.27	. 10	.15	. 19
2	.15	. 11	.28	. 12	.10	. 04	.04	2.2	.25	. 10	.17	. 18
3	.08	. 07	.76	. 11	. 12	. 04	.04	.35	.22	. 09	.16	. 16
Ā	.10	. 16	.38	.10	.12	. 04	.04	. 22	.23	. 09	.26	. 14
5	.11	.39	.34	1.2	.08	. 04	. 04	. 18	.21	. 10	1.9	. 22
6	.08	. 60	.24	. 84	17	. 04	04	1.3	.34	. 08	. 95	. 27
7	.06	1.3	.18	.25	.17 .12	. 12	.04 .14	.47	.32	. 07	.33	.13
8	.05	3.3	.25	.20	.10	. 05	.13	. 26	.24	.16	.25	. 09
ğ	.05	. 59	.25	. 82	.10	. 04	.06	. 27	.20	.25	.23	. 84
10	.06	.36	.18	1.5	.17	. 04	.06	.44	.58	. 14	.23	.10
44	.05	10	4.5	25	4.0			20		20	0.0	
11 12	.05	. 19 . 18	.15 .24	.35 .32	.10	. 04	.06 .20	.28 .20	.40 .35	.30 .12	.86 .30	. 09 . 08
13	.06	.15	.15	1.2	.09 .09	. 05 . 04	.12	. 17	.28	. 14	.28	.07
14	.05	.12	.14	.34	.09	. 04	.06	. 16	.28	.47	1.5	.06
15	.05	. 12	.13	. 22	.08	. 03	.05	. 15	.20	.31	.55	.08
								•			***	
16	.04	. 14	.16	. 19	.10	. 03	.05	.75	1.5	.21	.54	. 18
17	.04	. 11	.13	. 17	.10	. 19	.05	.21	.47	. 53	.37	2.9
18	.04	.10	.18	. 15	.09	. 13	.21	. 16	.28	. 24	.34	. 35
19	.04	.09	.13	. 14	.10	.09	.11	. 15	.24	. 16	.31	. 16
20	. 04	. 09	.25	. 13	.09	. 06	.06	. 14	.20	.21	.32	.43
21	.04	1.7	.17	. 15	.11	. 04	.05	. 12	.22	. 16	.28	. 93
22	. 04	1.8	.13	. 14	.10	. 07	.04	. 12	. 19	. 52	.26	.33
23	.04	.78	.12	. 13	.08	.06	.04	1.4	.21	. 26	.34	. 59
24	.04	. 84	.11	. 13	.08	. 04	.04	. 89	.16	.33	.31	.31
25	.03	.33	.10	. 12	.07	. 04	.04	.29	.16	.41	.29	.20
26	.03	.34	.12	. 12	.08	. 04	. 04	. 53	.14	.21	.29	. 18
27	.03	.31	.15	.11	.05	. 04	.04	.48	.15	. 37	.27	. 19
28	.03	.27	. 14	. 13	.05	. 04	.03	. 35	.13	.26	.23	. 18
29	.03	.28	.13	. 12	.04	. 03	.26	.36	.12	.21	.21	. 18
30	.03	.31	.11	.12		. 03		. 42	.11	. 18	.21	.19
31	.03		.09	. 12		. 04		. 29		. 15	.27	
TOTAL	1.82	15.24	6.14	9.86	2.78	1.66	3.48	15.01	8.65	6.93	12.96	10.00
MEAN	. 059	.51	.20	. 32	.096	.054	.12	.48	.29	. 22	.42	.33
MAX	.21	3.3	.76	1.5	.17	. 19	1.3	2.2	1.5	. 53	1.9	2.9
MIN	.03	. 07	.09	.10	.04	. 03	.03	. 12	.11	. 07	. 15	. 06
AC-FT	3.6	30	12	20	5.5	3.3	6.9	30	17	14	26	20
CFSM	.98	8.47	3.30	5.30	1.60	. 89	1.93	8.07	4.81	3.73	6.97	5.56
IN.	1.13	9.45	3.81	6.11	1.72	1.03	2.16	9.31	5.36	4.30	8.04	6.20
STATIST	ICS OF M	ONTHLY MEA	N DATA FO	R WATER Y	EARS 1983	- 199	2, BY WATER Y	YEAR (WY)			
MEAN	.34	. 59	.41	20	2.4		2.0	. 33	.24	.23	.30	.29
MYX	1.35	1.34	1.34	.27 .58	.24 .44	. 23 . 63	.20 .61	. 64	.61	. 67	.54	. 61
(WY)	1986	1985	1988	1988	1988	1990	1987	1986	1987	1983	1988	1989
MIN	.059	.15	.091	.14	. 092	.054	.035	.11	.056	.046	.063	.060
(WY)	1992	1991	1990	1986	1987	1992	1984	1991	1991	1991	1991	1991
SUMMARY	STATIST	ICS	FOR 1	991 CALEN	DAR YEAR		FOR 1992 WAT	TER YEAR		WATER Y	YEARS 1983	- 1992
ANNUAL	TOTAL			55.48			94.53					
ANNUAL	mban			. 15			.26			. 3	30	
Highest	ANNUAL	MEAN								. 4	15	1988
	ANNUAL M											1984
	DYILA W				Nov 8		3.3			6.9		27 1987
	DAILY ME				Aug 5			Oct 25		. (1 Apr	10 1983
		MINIMUM Y		.01	Aug 5			Oct 25				5 1991
		BAK FLOW					19			101		13 1990
	ANEOUS P	BAK STAGE						Sep 17 Oct 24		2.6		13 1990 10 1983
	RUNOFF (110			188	UU 4		219		-4 1303
	RUNOFF (2.53			4.30			5.0		
	RUNOFF (34.40			58.61			68.		
	ENT EXCE			.33			.49					
	ENT EXCE			.08			. 15				15	
	ENT EXCE			.03			. 04				05	

347

RIO ESPIRITU SANTO BASIN

50063500 QUEBRADA TORONJA AT EL VERDE, PR--Continued

WATER QUALITY RECORDS

PERIOD OF RECORD. -- WATER YEARS APRIL 1983 TO CURRENT YEAR

DATE	TIME	STREAMFLOW, INSTANTANEOUS (CFS)	SPECIFIC CON- DUCTANCE (UMHOS)	TEMPERA- TURE (DEG C)	DATE T	IMB	STREAMFLOW, INSTANTANEOUS (CFS)	SPECIFIC CON- DUCTANCE (UMHOS)	TEMPERA- TURE (DEG C)
MAR. 12 MAY 27	1227 7 1457	0.03 1.35	90 80	22.0 24.0	JUN. 23 12	48	0.22	80	24.0

50063800 RIO ESPIRITU SANTO NEAR RIO GRANDE, PR

LOCATION.--Lat 18°21'37", long 65°48'49", Hydrologic Unit 21010005, at left abutment, on downstream side of bridge on Highway 966, 0.1 mi (0.2 km) upstream from Quebrada Jiménez, and 1.9 mi (3.1 km) southeast of Río Grande.

DRAINAGE AREA. -- 8.62 mi 2 (22.33 km2).

WATER-DISCHARGE RECORDS

PERIOD OF RECORD. -- February 1959 to April 1963 (annual low-flow and occasional measurements only), August 1966 to current year.

GAGE.--Water-stage recorder and crest-stage gage. Elevation of gage is 40 ft (12 m), from topographic map.

REMARKS.--Records fair except those for estimated daily discharges, which are poor.

		DI SCHAI	GE, CUBIC	FEST PER		WATER YE MEAN VA		R 1991 TO	SEPTEMBE	R 1992		
DAY	OCT	NOA	DEC	JAN	FEB	MAR	APR	МАЧ	JUN	JUL	AUG	SEP
1	57	e9.9	24	20	13	10	10	1010	13	6.7	23	23
2	40	e14	54	17	13	10	9.2	628	40	6.4	31	23
3	21	16	162	16	13	10	8.3	28	13	6.0	38	30
ă	21	14	64	14	19	9.7	8.1	12	21	6.2	52	26
5	38	e26	48	481	15	10	8.3	8.7	16	6.7	488	69
6	20	e56	34	212	81	11	7.5	428	68	5.5	318	90
7	13	•113	23	45	37	180	45	38	57	5.0	70	33
8	12	●700	40	24	22	31	46	14	26	31	52	22
9	11	101	36	147	15	11	36	15	13	22	43	94
10	14	88	33	356	38	9.3	19	37	104	11	35	22
11	14	15	22	43	18	8.6	12	22	41	52	225	24
12	37	15	50	37	14	21	32	10	90	8.9	54	20
13	21	15	41	189	13	20	42	7.5	27	10	53	17
14	12	10	40	40	12	9.8	17	6.6	21	57	162	16
15	11	9.3	23	27	12	18	18	6.3	15	34	56	23
					-							
16	10	17	28	24	12	9.3	9.0	204	295	27	30	66
17	9.6	11	23	22	11	49	8.2	13	37	136	34	291
18	9.2	8.7	26	20	11	83	132	9.0	17	34	24	107
19	9.3	8.0	24	18	11	47	50	7.8	15	13	21	57
20	9.6	8.5	89	18	13	21	17	9.4	11	24	29	e 200
										4.5		
21	8.6	●2 07	51	17	12	13	11	7.5	17	17	20	e140
22	8.5	e446	25	17	23	28	9.4	7.0	12	70	19	e50
23	8.5	119	23	16	15	30	8.8	412	16	29	19	e48
24	8.1	157	19	17	16	13	8.5	178	9.0	53	28 17	e40
25	7.7	27	17	19	15	10	8.2	27	8.3	63	17	e 25
26	7.8	38	17	21	22	9.9	8.4	113	7.3	20	16	e22
27	7.5	64	20	16	15	9.1	8.2	47	13	67	19	•19
28	7.4	46	20	23	15	8.8	8.3	17	8.1	41	16	●18
29	7.3	32	21	20	11	9.0	16	14	7.5	43	20	●17
30	7.3	40	20	14		18	250	20	7.2	24	17	e17
31	6.1		17	13		22		16		22	80	
mom> -	484 5				500				1015 4	054 4	2440	1640
TOTAL	474.5	2431.4	1134	1963	537	749.5	871.4	3372.8	1045.4	951.4	2109	1649
MEAN	15.3	81.0	36.6	63.3	18.5	24.2	29.0	109	34.8	30.7	68.0	55.0
MAX	57	700	162	481	81	180	250	1010	295	136	488	291
MIN	6.1	8.0	17	13	11	8.6	7.5	6.3	7.2	5.0	16	16 3270
AC-FT	941	4820	2250	3890	1070	1490	1730	6690	2070	1890	4180	
CFSM	1.78	9.40	4.24	7.35	2.15	2.80	3.37	12.6	4.04	3.56	7.89	6.38
IN.	2.05	10.49	4.89	8.47	2.32	3.23	3.76	14.56	4.51	4.11	9.10	7.12
• Rs	stimated											
STATIST	rics of i	MONTHLY ME	N DATA FO	R WATER Y	BARS 1966	- 19 9 2.	BY WATER	YBAR (W)	()			
MBAN	65.0	85.6	75.0	52.0	50.9	41.6	45.9	70.9	47.8	51.5	62.5	57.2
MAX	202	196	179	119	117	153	119	185	120	114	123	191
(WY)	1971	1985	1971	1969	1982	1990	1981	1979	1970	1983	1988	1989
MIN	12.3	29.1	18.1	18.5	10.8	13.0	6.27	14.9	10.0	11.1	22.3	17.7
(WY)	1969	1982	1990	1977	1983	1977	1984	1973	1975	1975	1974	1971
SUMMARY	Y STATIS	rics	FOR 1	991 CALEN	DAR YEAR	F	OR 1992 W	ATER YEAF	ર	WATER YE	ARS 1966	- 1992
ANNUAL	TOTAL.			13871.0			17288.4					
ANNUAL				38.0			47.2			59.3		
	LAUNUAL	MRAN					• • • • • • • • • • • • • • • • • • • •			98.6		1979
	ANNUAL I									37.3		1974
	DAILY I			700	Nov 8		1010	May 1	ı	2600	Dec	7 1987
	DAILY M			6.1			5.0			4.1		3 1975
ANNUAL	SEVEN-DA	AY MINIMUM		7.3			6.1		l	4.4	Jun :	30 1975
		PEAK FLOW					9520			19200		13 1990
		PEAK STAGE						9 May		15.74	Aug :	13 1990
		LOW FLOW					4.8			4.0		3 1975
	RUNOFF			27510			34290			42990		
	RUNOFF			4.41			5.4			6.88		
ANNUAL	RUNOFF	(INCHES)		59.86			74.6	1		93.53		
	CENT BXC			88			90			125		
	CENT EXC			20			20			26		
90 PERC	CENT EXC	REDS		8.6			8.5			11		

50063800 RIO ESPIRITU SANTO NEAR RIO GRANDE, PR--Continued

WATER-QUALITY RECORDS

PERIOD OF RECORD. -- Water years 1958, 1961-66, 1968 to current year.

WATER-QUALITY DATA, WATER YEAR OCTOBER 1991 TO SEPTEMBER 1992

DATE	TIME	DI: CHAR(INS' CUB: FE: PE: SEC(GE, SPE T. CIE IC CON RT DUC R ANC	PIC WHO I- FIE T- (STA ER AF	'ER OLE ILD TEM IND- AT ID WA	PBR- URB TER G C)	TUR- BID- ITY (NTU)	OXYG DI SOL (MG	I SC RN, (I S- C VED SA	GEN, DIS- DLVED PER- ENT TUR- TION)	OXYGEN DEMAND, CHEM- ICAL (HIGH LEVEL) (MG/L)	COLI FORM FECA 0.45 UM-M (COLS	i, S1 L, TOC FI IF (CC	PREP- COCCI SCAL, OLS. PER
OCT 1991 02	0900	49		92	7.5	24.0	25		7.0	82	19	K 65		4100
DEC														
16 FRB 1992	1120	25		105	7.2	22.5	2.5		8.7	118	<10	5	60	340
12 May	0920	13		106	6.7	22.0	1.6		8.1	106	<10	5	40	550
13	1045	7	. 8	90	6.3	25.0	1.7		7.8	94	<10	2	20	360
JUN 29	1245	7	. 6	120	6.9	29.0	1.5		6.1	81	<10	K9	00	K90
AUG 17	1120	33		92	7.0	26.5	2.5		7.8	97	<10	6	00	K160
DATE OCT 1993 02 DEC 16 FEB 1992 12 MAY 13 JUN 29 AUG 17	NI TC (1) C2 (0)	ARD- RSS OTAL MG/L AS ACO3) 0900) 27 26	CALCIUM DIS- SOLVED (MG/L AS CA) (00915) 5.9 5.7	MAGNR- SIUM, DIS- SOLVED (MG/L AS MG) (00925) 3.0 2.9	SODIUM, DIS- SOLVED (MG/L AS NA) (00930) 7.6 7.3	SOR TI: RAT: (009)	D- P- ON IO 31) (POTAS- SIUM, DIS- SOUG/L AS K) 00935) 0.60 0.50	ALKA- LINITY WAT WH TOT FET FIRLD MG/L AS CACO3 (00410)	TO! (MC AS (00))	Fide di Tal so 3/L (1 S) as	LFATE IS- OLVED MG/L SO4) 0945) 2.7 1.9 1.7	CHLO- RIDE, DIS- SOLVEI (MG/L AS CL) (00940) 11 10 9.1	
DATE	R: 1 S (1	LUO- IDE, DIS- OLVED MG/L S F)	SILICA, DIS- SOLVED (MG/L AS SIO2)	SOLIDS, SUM OF CONSTI- TUENTS, DIS- SOLVED (MG/L)	SOLIDS, DIS- SOLVED (TONS PER DAY)	RESI TOTA AT 1 DEG. SUS PENDO	L 05 C, N - Ed	NITRO- GEN, ITRATE TOTAL (MG/L AS N)	NITRO- GEN, NITRITE TOTAL (MG/L AS N)	GI NO2- TO (MC	EN, (HNO3 AM PAL TO 3/L (1	ITRO- GEN, MONIA OTAL MG/L S N)	NITRO- GEN, ORGANIO TOTAL (MG/L AS N)	
OCT 1991	-													
02 DBC	•	<0.10	15	61	8.20		10	0.090	0.020	0.	.110	0.030	0.27	'
16 FRB 1992	ì						1		<0.010	0.	.087 <	0.010		
12 MAY	•						8		<0.010	<0.	. 050	0.010		
13		<0.10	16	60	1.26		3		<0.010	<0.	.050	0.030		
JUN 29							<1		<0.010	<0.	. 050	0.030		
AUG 17		<0.10	14	60	5.35		3		<0.010	<0	. 050	0.020		

K = non-ideal count

RIO ESPIRITU SANTO BASIN 50063800 RIO ESPIRITU SANTO NEAR RIO GRANDE, PR--Continued WATER-QUALITY DATA, WATER YEAR OCTOBER 1991 TO SEPTEMBER 1992

DATE	NITRO- GEN,AM- MONIA + ORGANIC TOTAL (MG/L AS N)	NITRO- GEN, TOTAL (MG/L AS N)	NITRO- GEN, TOTAL (MG/L AS NO3)	PHOS- PHORUS TOTAL (MG/L AS P)	ARSENIC TOTAL (UG/L AS AS)	BARIUM, TOTAL RECOV- ERABLE (UG/L AS BA)	BORON, TOTAL RECOV- ERABLE (UG/L AS B)	CADMIUM TOTAL RECOV- ERABLE (UG/L AS CD)	CHRO- MIUM, TOTAL RECOV- ERABLE (UG/L AS CR)	COPPER, TOTAL RECOV- ERABLE (UG/L AS CU)
OCT 1991										
02	0.30	0.41	1.8	0.020	<1	<100		<1	1	<10
16 FBB 1992	<0.20			<0.010						
12 MAY	<0.20			<0.010						
13 JUN	<0.20			<0.010	<1	<100	20	<1	<1	<10
29 AUG	<0.20			<0.010						
17	<0.20			0.010						
DATE	IRON, TOTAL RECOV- ERABLE (UG/L AS FE)	LBAD, TOTAL RECOV- ERABLE (UG/L AS PB)	MANGA- NESE, TOTAL RECOV- ERABLE (UG/L AS MN)	MERCURY TOTAL RECOV- ERABLE (UG/L AS HG)	SELE- NIUM, TOTAL (UG/L AS SE)	SILVER, TOTAL RECOV- ERABLE (UG/L AS AG)	ZINC, TOTAL RECOV- ERABLE (UG/L AS ZN)	CYANIDE TOTAL (MG/L AS CN)	PHENOLS TOTAL (UG/L)	METHY- LENE BLUE ACTIVE SUB- STANCE (MG/L)
ост 1991	TOTAL RECOV- ERABLE (UG/L AS FE)	TOTAL RECOV- ERABLE (UG/L AS PB)	NESE, TOTAL RECOV- ERABLE (UG/L AS MN)	TOTAL RECOV- ERABLE (UG/L AS HG)	NIUM, TOTAL (UG/L AS SE)	TOTAL RECOV- ERABLE (UG/L AS AG)	TOTAL RECOV- ERABLE (UG/L AS ZN)	TOTAL (MG/L AS CN)	TOTAL (UG/L)	LENB BLUE ACTIVE SUB- STANCE (MG/L)
	TOTAL RECOV- ERABLE (UG/L	TOTAL RECOV- ERABLE (UG/L	NESE, TOTAL RECOV- ERABLE (UG/L	TOTAL RECOV- ERABLE (UG/L	NIUM, TOTAL (UG/L	TOTAL RECOV- ERABLE (UG/L	TOTAL RECOV- ERABLE (UG/L	TOTAL (MG/L	TOTAL	LENE BLUE ACTIVE SUB- STANCE
OCT 1991 02 DEC 16	TOTAL RECOV- ERABLE (UG/L AS FE)	TOTAL RECOV- ERABLE (UG/L AS PB)	NESE, TOTAL RECOV- ERABLE (UG/L AS MN)	TOTAL RECOV- ERABLE (UG/L AS HG)	NIUM, TOTAL (UG/L AS SE)	TOTAL RECOV- ERABLE (UG/L AS AG)	TOTAL RECOV- ERABLE (UG/L AS ZN)	TOTAL (MG/L AS CN)	TOTAL (UG/L)	LENB BLUE ACTIVE SUB- STANCE (MG/L)
OCT 1991 02 DEC 16 FEB 1992 12	TOTAL RECOV- ERABLE (UG/L AS FE)	TOTAL RECOV- ERABLE (UG/L AS PB)	NESE, TOTAL RECOV- ERABLE (UG/L AS MN)	TOTAL RECOV- ERABLE (UG/L AS HG)	NIUM, TOTAL (UG/L AS SE)	TOTAL RECOV- ERABLE (UG/L AS AG)	TOTAL RECOV- ERABLE (UG/L AS ZN)	TOTAL (MG/L AS CN)	TOTAL (UG/L)	LENE BLUE ACTIVE SUB- STANCE (MG/L)
OCT 1991 02 DEC 16 FEB 1992 12 MAY	TOTAL RECOV- ERABLE (UG/L AS FE)	TOTAL RECOV- ERABLE (UG/L AS PB)	NESE, TOTAL RECOV- ERABLE (UG/L AS MN)	TOTAL RECOV- ERABLE (UG/L AS HG) <0.10	NIUM, TOTAL (UG/L AS SE)	TOTAL RECOV- ERABLE (UG/L AS AG)	TOTAL RECOV- ERABLE (UG/L AS ZN)	TOTAL (MG/L AS CN) <0.010	TOTAL (UG/L) <1	LENE BLUE ACTIVE SUB- STANCE (MG/L)
OCT 1991 02 DEC 16 FEB 1992 12	TOTAL RECOV- ERABLE (UG/L AS FE) 1600	TOTAL RECOV- ERABLE (UG/L AS PB)	NESE, TOTAL RECOV- ERABLE (UG/L AS MN)	TOTAL RECOV- ERABLE (UG/L AS HG) <0.10	NIUM, TOTAL (UG/L AS SE) <1	TOTAL RECOV- ERABLE (UG/L AS AG) <1	TOTAL RECOV- ERABLE (UG/L AS ZN) <10	TOTAL (MG/L AS CN) <0.010	TOTAL (UG/L) <1 	LENE BLUE ACTIVE SUB- STANCE (MG/L)

50064200 RIO GRANDE NEAR EL VERDE, PR

LOCATION.--Lat 18°20'54", long 65°50'30", Hydrologic Unit 21010005, on left bank 250 ft (7.6 m) upstream side of bridge at Hwy 960, 0.05 mi (0.08 km) southwest of junction of Highways 956 and 960, 1.1 mi (1.8 km) west of El Verde, and 2.7 mi (4.3 km) south of Río Grande.

DRAINAGE AREA. -- 7.31 mi 2 (18.93 km2).

WATER-DISCHARGE RECORDS

PERIOD OF RECORD. -- May 1967 to December 1970, January 1972 to September 1982, August 1990 to current year.

GAGE.--Water-stage recorder. Elevation of gage is 131 ft (40 m), from topographic map.

REMARKS. -- Records fair. Gage-height and precipitation satellite telemetry at station.

		DISCHAR	GR, CUBIC	FEET PER		WATER YE MEAN VA	AR OCTOBER	1991 T O	SRP TEMBE R	1992		
DAY	OCT	NON	DEC	JAN	FEB	MAR	APR	MAY	JUN	ஶ	AUG	SEP
1	39	46	30	19	13	6.7	5.3	405	17	8.3	11	19
2	33	49	49	16	14	6.4	4.8	262	22	8.0	11	12
3	17	37	74	14	13	6.1	4.6	38	19	8.0	14	15
4	14	29	55	14	13	5.7	4.4	19	46	7.8	16	13
5	29	36	29	215	13	5.9	4.4	14	25	8.9	192	35
6	16	72	21	138	49	6.0	4.2	165	42	8.3	132	43
7	12	136	18	43	30	41	16	46	78	7.9	43	18
8	9.7	385	24	24	16	25	15	21	35	41	31	12
9	10	111	27	41	12	8.3	17	18	19	24	19	17
10	11	91	31	107	19	6.4	12	37	49	12	17	13
11	9.3	27	23	33	13	5.9	5.3	25	33	22	71	12
12	38	20	34	27	9.8	5.5	13	17	79	12	29	11
13	20	19	32	95	8.6	5.7	16	13	46	20	32	9.3
14	11	15	35	35	8.0	5.9	6.1	12	41	38	71	9.4
15	9.4	13	18	25	7.6	15	9.5	13	22	23	34	12
16	8.7	15	19	22	7.1	7.4	4.4	56	89	29	34	40
17	8.3	13	18	20	6.7	15	3.9	22	51	76	32	65
18	8.1	11	16	19	6.5	29	9.8	20	26	30	18	39
19	8.1	9.8	15	18	7.2	28	20	15	16	16	16	54
20	7.3	9.1	80	17	6.8	11	7.5	19	13	16	15	107
21	7.1	105	58	17	6.4	7.6	5.6	13	21	13	14	67
22	6.9	151	28	16	8.8	25	4.5	12	16	28	13	28
23	6.7	67	25	16	7.7	14	4.3	279	13	18	13	27
24	7.6	86	20	17	6.3	8.4	4.1	106	11	50	14	23
25	7.0	22	19	17	7.4	6.8	4.1	53	10	32	12	15
26	6.8	20	18	18	8.2	6.0	3.9	108	9.4	14	12	13
27	6.3	32	21	17	7.7	5.5	3.7	52	10	35	12	11
28	6.3	49	20	17	11	5.2	3.8	28	9.3	22	11	11
29	6.2	25	20	18	7.8	5.0	11	23	8.8	14	11	10
30	8.8	41	17	14		4.8	47	23	8.5	11	11	11
31	6.9		16	13		6.0		21		11	38	
TOTAL	395.5	1741.9	910	1122	344.6	340.2	275.2	1955	885.0	664.2	999	771.7
MBYN	12.8	58.1	29.4	36.2	11.9	11.0	9.17	63.1	29.5	21.4	32.2	25.7
MAX	39	385	80	215	49	41	47	405	89	76	192	107
MIN	6.2	9.1	15	13	6.3	4.8	3.7	12	8.5	7.8	11	9.3
AC-FT	784	3460	1800	2230	684	675	546	3880	1760	1320	1980	1530
CFSM	1.75	7.94	4.02	4.95	1.63	1.50	1.25	8.63	4.04	2.93	4.41	3.52
IN.	2.01	8.86	4.63	5.71	1.75	1.73	1.40	9.95	4.50	3.38	5.08	3.93
STATIST	TICS OF 1	MONTHLY ME	AN DATA FO	R WATER Y	BARS 1967	- 1992	, BY WATER	YBAR (WY)				
MBAN	67.4	74.2	51.6	43.5	32.0	23.3	31.4	60.1	34.2	38.0	46.5	50.9
MAX	392	172	140	151	76.4	54.4	119	203	86.5	109	90.0	153
(WY)	1971	1970	1971	1969	1969	1969	1978	1969	1968	1969	1968	1975
MIN	8.45	14.3	13.8	10.1	5.80	4.50	8.55	10.2	6.22	9.05	7.39	12.4
(WY)	1969	1981	1968	1977	1977	1977	1975	1974	1975	1991	1991	1967
OTTMAN DI	/ 0m>m=0	T.C.C.	POD 1	991 CALEN	Din Velo	•	POD 1002 WM	mon volo		WATER YEA	DO 1967	_ 1002
SUMMAR)	(STATIS	1100	FOR 1		PAR IBAK		FOR 1992 WA'	AAGI na.		unior im	LO 170/	4776
ANNUAL	TOTAL			7907.4			10404.3					
ANNUAL	MBAN			21.7			28.4			44.2		
	LYNNAT									87.1		1969
	ANNUAL I									25.8		1991
	DAILY			385	Nov 8		405	May 1		3470		1 1969 15 1991
	DAILY MI	YA MINIMOM RYN		2.2 2.5	Aug 15 Aug 10		3.7 4.1	Apr 27 Apr 22		2.2 -2.5		1991
				4.5	Mug 10		4450	Nov 8		17400		16 1975
		PEAK FLOW PEAK STAGE					12.88			15.50		16 1975
		LOW FLOW					3.6	Apr 26		1.6		13 1977
	RUNOFF			15680			20640			32020		
	RUNOFF			2.96			3.89			6.05		
	RUNOFF			40.24			52.95			82.14		
	CENT BXC			48			53			85		
50 PERC	CENT BXC	REDS		12			16			18		
90 PERC	CENT BXC	REDS		4.1			6.4			7.2		

50064200 RIO GRANDE NEAR BL VERDE, PR--Continued

WATER QUALITY RECORDS

PERIOD OF RECORD. -- OCTOBER 1990 TO CURRENT YEAR

DATE	TIME	STREAMFLOW, INSTANTANEOUS (CFS)	SPECIFIC CON- DUCTANCE (UMHOS)	TEMPERA- TURE (DEG C)	DATE	т	TIME	STREAMFLOW, INSTANTANEOUS (CFS)	SPECIFIC CON- DUCTANCE (UMHOS)	TEMPERA- TURE (DEG C)
MAR. 12	1453	5.37	140	26.5	MAY	22 0		11.8	120	25.0
APR. 10	1140	9.57	80	26.0	JUN.	23 1		13.4	110	25.0

RIO MAMBYES BASIN

50065500 RIO MAMEYES NEAR SABANA, PR

LOCATION.--Lat 18°19'46", long 65°45'04", Hydrologic Unit 21010005, on left bank, at bridge on Highway 988, 1.4 mi (2.3 km) west of Sabana, 2.0 mi (3.2 km) downstream from Río de la Mina, and 3.2 mi (5.1 km) southeast of Mameyes.

DRAINAGE AREA.--6.88 mi³ (17.82 km²).

WATER-DISCHARGE RECORDS

PERIOD OF RECORD. -- August 1967 to December 1973, June 1983 to current year.

GAGE.--Water-stage recorder and crest-stage gage. Elevation of gage is 275 ft (84 m), from topographic map.

REMARKS.--Records fair except those for estimated daily discharges, which are poor. Gage-height and precipitation satellite telemetry at station.

	1100 001	omeer, ac										
		DI SCHAR	GE, CUBI	C FEET PEI	R SECOND, N	WATER YE. MEAN VA		R 1991 TO	SEPTEMBE	R 1992		
DAY	OCT	Nov	DEC	JAN	FBB	MAR	APR	MAY	JUN	JUL	AUG	SEP
1	70	114	62	26	24	18	28	754	135	43	26	19
2	64	67	94	21	25	18	24	375	160	41	37	17
3	43	56	163	19	27	17	19	75	52	41	38	24
4 5	45 63	37 82	92 86	17 487	68 34	18 19	17 17	50 42	5 4 37	37 39	60 179	23 39
6	38	141	65	190	114	20	16	273	67	40	114	61
7 8	29 28	259 641	51 61	7 4 59	49 33	152 47	39 60	90 54	54 36	41 88	64 41	32 28
ğ	34	206	52	134	28	22	119	59	24	63	39	94
10	44	147	51	222	50	19	37	60	148	45	57	27
11	29	84	39	78	30	18	40	64	73	89	172	44
12	45	77	59	68	26	60	52	39	77	40	56	29
13	34	71	53	117	24	31	52	34	57	40	46	28
14	31	58	75	58	24	38	35	31	45	73	74	26
15	29	64	32	50	23	38	29	30	30	73	53	29
16	27	92	44	47	22	20	20	135	176	80	35	48
17	25	67 53	32	45	22	55	31	39	83	154	35	79
18 19	24 33	53 47	33 31	41 38	21 25	88 e30	132 73	33 30	56 54	61 4 0	26 22	64 51
20	24	44	60	35	25	e29	34	28	47	58	33	130
21	20	233	42	33	21	e22	24	26	88	43	23	123
22	20	228	31	31	40	e35	22	25	51	56	20	49
23	26	127	28	31	24	e 66	21	284	75	31	20	92
24	19	122	24	32	24	e35	20	104	48	53	32	76
25	18	72	23	38	23	e20	20	50	51	67	24	44
26	18	91	23	39	31	e23	19	122	45	61	21	34
27	19	94	23	30	34	e24	19	43	62	87	19	28
28 29	18 24	84 89	26 24	44 35	29 21	€70 €35	19 23	27 24	47 46	66 54	17 18	25 24
30	21	86	23	28		e110	92	46	45	32	21	30
31	18		31	26		e80		27		28	61	
TOTAL	980	3633	1533	2193	941	1277	1153	3073	2023	1764	1483	1417
MBAN	31.6	121	49.5	70.7	32.4	41.2	38.4	99.1	67.4	56.9	47.8	47.2
MAX	70	641	163	487	114	152	132	754	176	154	179	130
MIN	18	37	23	17	21	17	16	24	24	28	17	17
AC-FT	1940	7210	3040	4350	1870	2530	2290	6100	4010	3500	2940	2810
CFSM IN.	4.59 5.30	17.6 19.64	7.19 8.29	10.3 11.86	4.72 5.09	5.99 6.90	5.59 6.23	14.4 16.62	9.80 10.94	8.27 9.54	6.95 8.02	6.87 7.66

e Bs	timated											
STATIST	CICS OF M	ONTHLY MRA	N DATA F	OR WATER	YBARS 1967	- 1992,	BY WATER	YBAR (WY)			
MEAN	71.4	84.8	61.9	54.6	40.6	39.8	41.7	68.8	57.1	49.6	55.1	57.2
MAX	240	191	164	105	68.0	79.7	83.1	147	112	93.4	81.4	166
(WY)	1971	1985	1971	1969	1988	1990	1973	1970	1970	1969	1988	1989
MIN	20.3	36.3	16.6	25.0	21.7	18.1	14.5	18.7 1973	12.4 1985	20.5 1971	28.0 1985	26.6 1986
(WY)	1969	1974	1990	1985	1968	1968	1984	1973	1303	19/1	1303	1300
SUMMARY	STATIST	ICS	FOR	1991 CALE	NDAR YEAR	P	OR 1992 W	ATER YEAR		WATER Y	BARS 1967	- 1992
ANNUAL				16938.2			21470					
ANNUAL				46.4			58.7			57.8 78.0		1971
	'ANNUAL ANNUAL M									41.2		1972
	DAILY M			641	Nov 8		754	May 1		2780		18 1989
LOWEST	DAILY ME	AN		9.2	Apr 30		16	Apr 6		6.9	Apr	20 1970
		MUMINIM Y		14	Apr 27		19	Feb 29		9.4		12 1985
		BAK FLOW					10300			20500 13.1	Sep	18 1989
	'ANEOUS P 'ANEOUS L	EAK STAGE						0 May 1 Apr 7		13.1 5.1	y Sep	18 1989 8 1970
	RUNOFF (33600			12 42590	APE /		41850	WDL	3 13/4
	RUNOFF (6.7			8.5	3		8.4		
ANNUAL	RUNOFF (INCHES)		91.5			116.0			114.0	9	
	ENT EXCE			93			111			104		
	ENT EXCE			29 17			40 20			33 16		
JU PBKC	BAUB	SUA		1,			20			10		

RIO MAMEYES BASIN

50065500 RIO MAMEYES NEAR SABANA, PR--Continued

WATER QUALITY RECORDS

PERIOD OF RECORD. -- WATER YEARS JUNE 1983 TO CURRENT YEAR

DATE ?	TIMB	STREAMFLOW, INSTANTANEOUS (CFS)	SPECIFIC CON- DUCTANCE (UMHOS)	TEMPERA- TURE (DEG C)	DATE	TIME	STREAMFLOW, INSTANTANEOUS (CFS)	SPECIFIC CON- DUCTANCE (UMHOS)	TEMPERA- TURE (DEG C)
MAR. 10	1210	20.1	80	23.5	MAY 2	21 1230	25.9	100	25.5
APR. 09	1015	29.1	80	22.5	JUN. 1	11 1337	46.9	110	25.0

RIO SABANA BASIN

50067000 RIO SABANA AT SABANA, PR

LOCATION.--Lat 18°19'52", long 65°43'52", Hydrologic Unit 21010005, on right bank along Highway 988, 0.3 mi (0.5 km) north of junction of Highways 988 and 983 in Sabana, and 3.3 mi (5.3 km) south of Luquillo.

DRAINAGE AREA. -- 3.96 mi 2 (10.26 km2).

WATER-DISCHARGE RECORDS

PERIOD OF RECORD. -- October 1979 to current year.

GAGE.--Water-stage recorder and crest-stage gage. Elevation of gage is 260 ft (80 m), from topographic map.

REMARKS .-- Records fair except those for estimated daily discharges, which are poor.

	D	ISCHARGE,	CUBIC FEET	PER SE	COND, WATER DAILY MEAN		TOBER 1991	TO SEPTE	MBER 199	2		
DAY	ост	NOV	DEC	JAN	FEB	MAR	APR	MAY	JUN	JUL	AUG	SEP
1	16	e15	13	10	8.4	5.8	6.1	372	85	12	9.8	8.2
2	12	e8.7	16	9.5	8.3	5.4	5.5	199	195	11	10	9.2
3	9.0	7.3	65	9.5	8.7	5.3	4.2	20	42	11	9.9	8.3
4	8.4	6.1	25	9.3	32	5.7	4.0	14	20	11	13	7.4
5	12	e19	19	436	11	5.0	4.0	12	15	11	36	8.5
6 7	7.9 6.6	42 e144	15 13	95 24	35 14	5.1 25	3.9 5.3	50 16	14 15	10 10	28 20	11 8.3
8	6.5	e235	16	17	10	18	11	12	12	15	13	11
9	25	e151	14	35	9.2	6.3	42	11	11	13	12	40
10	12	52	14	89	11	5.4	11	11	74	11	21	9.3
11	8.3	19	12	24	8.6	4.8	6.6	10	18	19	66	12
12	24	e16	14	20	8.0	5.3	8.7	8.6	86	10	18	7.7
13	12	e16	14	27	7.4	6.3	10	8.1	25	9.4	13	6.8
14	7.7	e14	14	17	9.5	6.8	4.8	7.9	15 12	16	16	7.1 7.5
15	6.9	15	12	16	7.5	12	3.9	7.9		12	13	
16	6.2	19	19	15	7.2	5.3	2.7	15	66	9.8	12	12
17	5.9	15	12	15	7.3	13	9.4	8.5	19	29	11	29
18	6.1	12	12	13	7.2	9.4	49	7.5	16	11	9.9	18
19 20	14 7.9	e11 e11	12 36	13 12	7.3 7.8	6.0 6.0	16 7.9	7.1 6.9	15 18	10 21	9.6 11	10 37
21	6.3	e74	16	12	6.6	4.9	4.6	6.6	25	15	9.9	85
22	6.2	152	12	12	7.3	7.5	4.1	6.5	17	18	8.6	15
23	6.8	22	11	11	7.7	9.7	3.4	160	22	12	8.7	29
24	6.1	20	10	11	6.6	5.6	2.9	50	16	17	9.4	19
25	5.4	16	10	11	6.5	4.5	2.7	20	16	16	47	12
26	5.1	17	10	11	8.6	5.0	2.5	150	14	11	13	10
27	4.9	23	10	10	9.1	5.2	2.4	21	16	19	9.5	9.6
28	4.9	17	10	11	8.6	9.4	2.2	12	13	15	8.8	8.9
29	6.5	16	10	10	6.2	6.5	5.7	9.9	13	13	8.6	8.7
30	5.7	14	9.9	9.3		12	29	17	13	10	8.5	11
31	4.9		11	8.7		11		9.0		9.8	17	
TOTAL	277.2	1199.1	486.9	1023.3	292.6	243.2	275.5	1266.5	938	418.0	501.2	476.5
WRYN	8.94	40.0	15.7	33.0	10.1	7.85	9.18	40.9	31.3	13.5	16.2	15.9
MAX	25	235	65	436	35	25	49	372	195	29	66	85
MIN	4.9	6.1	9.9	8.7	6.2	4.5	2.2	6.5	11	9.4	8.5	6.8
AC-FT	550	2380	966	2030	580	482	546	2510	1860 7.90	829	994	945 4.01
CFSM IN.	2.26 2.60	10.1 11.26	3.97 4.57	8.34 9.61	2.55 2.75	1.98 2.28	2.32 2.59	10.3 11.90	8.81	3.41 3.93	4.08	4.48
. P.	stimated											
STATIST	rics of	MONTHLY M	BAN DATA FO	R WATER	R YEARS 1980	- 1992,	, BY WATER	YEAR (WY)				
MEYN	22.7	32.5	24.2	12.6	11.7	12.7	12.9	35.3	22.0	14.5	17.7	16.7
MAX	66.4	79.7	64.1	33.0	22.2	36.0	33.5	63.9	50.6	31.3	32.7	56.3
(WY)	1986	1988	1982	1992	1988	1987	1990	1982	1987	1989	1988	1989
MIN	6.48	8.15	3.92	6.12	2.94	3.78	2.20	14.8	4.70	5.84	6.39	7.23
(WY)	1983	1981	1990	1986	1983	1980	1984	1990	1985	1986	1985	1987
SUMMARY	Y STA TIS	TICS	FOR 1	.991 CAI	LENDAR YEAR	1	FOR 1992 WA	TER YEAR		WATER Y	EARS 1980	- 1992
ANNUAL				5412.			7398.0					
ANNUAL				14.	. 8		20.2			19.7		
	r annual									28.2		1988
	ANNUAL						,	7		11.9		1984
	DAILY			328			436	Jan 5 Apr 28		887		18 1989 10 1983
	DAILY M	KAN AY MINIMU	v	1. 2.			2.2 2.9			1.0		6 1983
		PEAK PLOW		۷.	.0 Apr 25		9600	Jan 5		9600		5 1992
		PEAK STAG					19.74			19.7		5 1992
		LOW FLOW	-				1.9			.80		17 1983
	RUNOFF			10740			14670			14250		
	RUNOFF				.74		5.10)		4.9	7	
		(INCHES)		50.			69.50)		67.49	9	
	CENT EXC			25			29			37		
	CENT EXC			6.			11			8.6		
90 PERC	CENT BXC	REDS		3 .	. 4		5.7			2.9		

RIO SABANA BASIN

50067000 RIO SABANA AT SABANA, PR--Continued

WATER QUALITY RECORDS

PERIOD OF RECORD. -- WATER YEARS AUGUST 1981 TO CURRENT YEAR

DATE	TIME	STREAMFLOW, INSTANTANEOUS (CFS)	SPECIFIC CON- DUCTANCE (UMHOS)	TEMPERA- TURE (DEG C)	DATE	т	TIME	STREAMFLOW, INSTANTANEOUS (CFS)	SPECIFIC CON- DUCTANCE (UMHOS)	TEMPERA- Ture (Deg C)
MAR. 10 APR. 09		5.89 6.60	110 110	24.0 23.5	MAY JUN.	21 0 11 1		7.23 16.3	10 0 9 0	25.0 25.0

50071000 RIO FAJARDO NEAR FAJARDO, PR

LOCATION.--Lat 18°17'56", long 65°41'42", Hydrologic Unit 21010005, on left bank off Highway 976, 0.1 mi (0.2 km) upstream from Highway 977 bridge, 0.3 mi (0.5 km) downstream from Quebrada Peñón, 1.1 mi (1.8 km) northeast of Colonia Paraíso, and 3.3 mi (5.3 km) southwest of Fajardo.

DRAINAGE AREA. -- 14.9 mi 2 (38.6 km2).

WATER-DISCHARGE RECORDS

PERIOD OF RECORD .-- 1960-61 (occasional low and peak-flow measurements only), March 1961 to current year.

GAGE.--Water-stage recorder and crest-stage gage. Datum of gage is 137.60 ft (41.940 m) above mean sea level.

Due to flood damage, gage datum has had changes as follows: Mar. 24, 1961 to May 5, 1969, 138.95 ft (42.352 m);

May 6, 1969 to Mar. 16, 1972, 135.05 ft (41.163 m); Mar. 17, 1972 to Mar 25, 1975, 138.60 ft (42.245 m).

REMARKS.--Records fair except those for estimated daily discharges, which are poor. Low flow affected by diversions for water supply about 400 m upstream from gaging station (estimated mean daily discharges is 9.0 ft³/s (0.255 m³/s). Gage-height and precipitation satellite telemetry at station.

- -		DISCHAR	GE, CUBI	C FEET PER		WATER YE		R 1991 TO	SRPTEMBE	R 1992		
DAY	ост	NOV	DBC	JAN	FEB	MAR	APR	MAY	JUN	JUL	AUG	SEP
1 2 3 4 5	41 37 25 22 38	55 32 26 15	49 62 145 90 56	16 13 11 10 e860	e14 e14 e15 e110 e21	5.7 5.8 5.7 6.4	21 12 6.3 4.8 4.0	e254 394 41 18 12	270 404 119 37 19	5.1 4.9 4.9 4.7 5.1	6.0 11 15 9.3 106	23 17 24 20 44
6 7 8 9 10	20 15 21 30 19	110 241 724 302 177	35 27 39 29 28	e150 e60 e35 e50 e250	e110 e35 e19 e17 e23	5.6 e40 77 22 16	4.9 17 13 297 63	237 56 19 e16 e15	41 36 e18 e10 213	4.4 4.2 8.9 8.0 4.8	117 30 37 16 19	46 22 20 85 26
11 12 13 14 15	17 52 27 16 14	77 59 54 47 43	23 41 26 35 20	e66 e54 e80 e38 e33	e15 e14 e8.8 8.0 8.3	14 e42 33 41 e56	47 17 21 14 12	e14 e13 e11 e10 e9.6	52 104 29 18 14	6.8 4.9 4.7 9.4 5.3	127 48 e20 e32 e29	63 22 15 12
16 17 18 19 20	12 11 20 40 19	57 41 33 30 30	42 22 23 19 75	e31 e31 e25 e25 e23	7.6 7.1 7.0 11 9.6	e24 e16 e40 e18 20	8.0 123 206 262 65	e24 e19 e17 e16 17	e60 18 10 8.2 7.9	7.4 73 18 14 26	25 25 20 15 28	63 61 79 58 230
21 22 23 24 25	13 13 67 17 13	129 225 63 71 43	43 17 14 13 13	e23 e24 e22 e23 e22	7.5 11 8.0 7.1 7.2	12 44 30 12 9.2	18 13 11 e9.8 e8.8	15 16 420 287 346	22 8.9 32 8.8 8.4	12 19 9.5 e22 e23	25 14 14 38 69	217 64 100 43 35
26 27 28 29 30 31	11 9.8 8.5 10 13 8.2	37 51 48 76 70	13 11 10 11 12 17	e23 e20 e23 e19 e17 e15	12 14 11 7.0	8.9 11 9.6 9.3 59	e8.0 e7.6 e6.8 e14 e50	478 83 40 28 51 37	7.4 9.7 7.4 6.3 5.7	e15 e25 e15 e9.2 7.3 6.2	27 19 14 18 48 77	33 28 23 19 79
TOTAL MEAN MAX MIN AC-FT CFSM IN.	679.5 21.9 67 8.2 1350 1.47	3010 100 724 15 5970 6.73 7.51	1060 34.2 145 10 2100 2.29 2.65	2092 67.5 860 10 4150 4.53 5.22	559.2 19.3 110 7.0 1110 1.29 1.40	743.9 24.0 77 5.6 1480 1.61 1.86	1365.0 45.5 297 4.0 2710 3.05 3.41	3013.6 97.2 478 9.6 5980 6.52 7.52	1604.7 53.5 404 5.7 3180 3.59 4.01	387.7 12.5 73 4.2 769 .84	1098.3 35.4 127 6.0 2180 2.38 2.74	1585 52.8 230 12 3140 3.55 3.96
	stimated	ONTHLY MEA	V D.M. D	OR MARRO S	mana 1061	1002	DV MAMO	VEND (M	•			
MEAN MAX (WY) MIN (WY)	99.4 260 1971 19.1 1969	106 295 1975 30.8 1981	79.6 237 1976 14.9 1990	45.0 101 1969 15.4 1977	37.7 80.4 1982 10.8 1983	36.2 109 1987 9.70 1977	46.2 129 1963 4.02 1984	97.1 399 1979 17.7 1973	61.9 166 1962 10.0 1985	50.5 132 1969 12.5 1992	58.9 159 1979 26.8 1985	87.4 421 1989 19.1 1991
SUMMAR	Y STATIST	ccs	FOR	1991 CALEN	DAR YEAR	1	FOR 1992 V	VATER YEAR	2	WATER Y	TRARS 1961	- 1992
LOWEST HIGHES' LOWEST ANNUAL INSTAM' ANNUAL ANNUAL ANNUAL 10 PER 50 PER		SAN BAN AN Y MINIMUM BAK FLOW BAK STAGE OW FLOW AC-FT) CFSM) INCHES) EDS EDS		13254.1 36.3 724 5.5 6.5 26290 2.44 33.09 66 19 9.1	Aug 9		860 47.6 860 4.6 23300 19.8 34110 3.1 42.2 86 20 7.9	Jan 5 3 Jul 5 3 Jul 5 38 Jan 5	5 1 5	67. 140 38.: 8800 1. 1.! 23500 20.: 49040 4.: 61. 129 34	Sep :	1979 1972 18 1989 6 1984 18 1984 18 1989 3 1984

RIO FAJARDO BASIN

50071000 RIO FAJARDO NEAR FAJARDO, PR--Continued

WATER-QUALITY RECORDS

PERIOD OF RECORD. -- Water years 1960 to current year.

WATER-QUALITY DATA, WATER YEAR OCTOBER 1991 TO SEPTEMBER 1992

DATE OCT 1991 01 DEC 10 FEB 1992 24	TIMB 0950 1145 1115	DIS- CHARGE, INST. CUBIC FEBT PER SECOND	SPE- CIFIC CON- DUCT- ANCE (US/CM) 98 118	PH WATER WHOLE FIBLD (STAND- ARD UNITS) 7.0 7.1	TEMPER- ATURE WATER (DEG C) 25.5 25.5	TUR-BID-ITY (NTU) 4.3 3.3	OXYGEN, DIS- SOLVED (MG/L) 7.8 6.2	OXYGEN, DIS- SOLVED (PER- CENT SATUR- ATION) 95	OXYGEN DEMAND, CHEM- ICAL (HIGH LEVEL) (MG/L) <10	COLI- FORM, FECAL, 0.45 UM-MF (COLS./ 100 ML) K110 210
APR 06	1340	4.0	138	6.3		0.80	8.6	106	<10	250
JUN				· -	27.5					
09	1030	10	125	7.1	25.5	1.7	8.6	109	<10	230
18	1000	19	108	7.1	30.0	24	7.6	90	<10	50
DATE	STREP- TOCOCCI FECAL, (COLS. PER 100 ML)	HARD- NESS TOTAL (MG/L AS CACO3)	CALCIUM DIS- SOLVED (MG/L AS CA)	MAGNE- SIUM, DIS- SOLVED (MG/L AS MG)	SODIUM, DIS- SOLVED (MG/L AS NA)	SODIUM AD- SORP- TION RATIO	POTAS- SIUM, DIS- SOLVED (MG/L AS K)	ALKA- LINITY WAT WH TOT FET FIELD MG/L AS CACO3	SULFIDE TOTAL (MG/L AS S)	SULFATE DIS- SOLVED (MG/L AS SO4)
OCT 1991	420	25					1.2	23	<0.5	4.1
DEC	420	45	5.5	2.7	9.2	0.8	1.2			4.1
10 FEB 1992	250							35		
24	80							30		
APR 06 JUN	310	39	8.2	4.5	12	0.8	1.3	30	<0.5	3.8
09 AUG	K50							30		
18	60	29	6.3	3.3	11	0.9	1.0	34		3.5
DATE	CHLO- RIDB, DIS- SOLVED (MG/L AS CL)	FLUO- RIDB, DIS- SOLVED (MG/L AS F)	SILICA, DIS- SOLVED (MG/L AS SIO2)	SOLIDS, SUM OF CONSTI- TUENTS, DIS- SOLVED (MG/L)	SOLIDS, DIS- SOLVED (TONS PER DAY)	RESIDUE TOTAL AT 105 DEG. C, SUS- PENDED (MG/L)	NITRO- GEN, NITRITE TOTAL (MG/L AS N)	NITRO- GEN, NO2+NO3 TOTAL (MG/L AS N)	NITRO- GEN, AMMONIA TOTAL (MG/L AS N)	NITRO- GEN, ORGANIC TOTAL (MG/L AS N)
OCT 1991										
01 DBC	12	0.20	19	68	5.99	4	<0.010	0.170	0.030	
10 FEB 1992						10	<0.010	0.210	<0.010	
24 APR						8	<0.010	0.160	0.020	
06 Jun	15	<0.10	24	87	0.94	3	<0.010	0.150	0.030	0.17
09						23	<0.010	0.130	0.010	
AUG 18	12	<0.10	20	77	3.95	4	<0.010	0.090	0.020	
K = non-id						_				

K = non-ideal count

RIO FAJARDO BASIN

50071000 RIO FAJARDO NEAR FAJARDO, PR--Continued
WATER-QUALITY DATA, WATER YEAR OCTOBER 1991 TO SEPTEMBER 1992

DATE	NITRO- GEN, AM- MONIA + ORGANIC TOTAL (MG/L AS N)	NITRO- GEN, TOTAL (MG/L AS N)	NITRO- GEN, TOTAL (MG/L AS NO3)	PHOS- PHORUS TOTAL (MG/L AS P)	ARSENIC TOTAL (UG/L AS AS)	BARIUM, TOTAL RECOV- ERABLE (UG/L AS BA)	BORON, TOTAL RECOV- BRABLE (UG/L AS B)	CADMIUM TOTAL RECOV- ERABLE (UG/L AS CD)	CHRO- MIUM, TOTAL RECOV- ERABLE (UG/L AS CR)	COPPER, TOTAL RECOV- ERABLE (UG/L AS CU)
OCT 1991										
01 DBC	<0.20			0.030	<1	<100	<10	<1	<1	<10
10 FBB 1992	<0.20			0.020						
24	<0.20			<0.010						
APR 06	0.20	0.35	1.5	<0.010	<1	<100	<10	<1	<1	<10
JUN 09	<0.20			<0.010						
AUG 18	<0.20			0.010						
DATE	IRON, TOTAL RECOV- BRABLE (UG/L AS FE)	LEAD, TOTAL RECOV- ERABLE (UG/L AS PB)	MANGA- NESE, TOTAL RECOV- ERABLE (UG/L AS MN)	MERCURY TOTAL RECOV- BRABLE (UG/L AS HG)	SELE- NIUM, TOTAL (UG/L AS SE)	SILVER, TOTAL RECOV- ERABLE (UG/L AS AG)	ZINC, TOTAL RECOV- ERABLE (UG/L AS ZN)	CYANIDE TOTAL (MG/L AS CN)	PHENOLS TOTAL (UG/L)	METHY- LENE BLUB ACTIVE SUB- STANCE (MG/L)
OCT 1991	120	3	50	.0.40			20	.0.040		0.00
DBC	420	3	50	<0.10	<1	<1	20	<0.010	<1	0.02
10 FBB 1992										
24 APR										
06 Jun	90	<1	10	<0.10	<1	<1	<10	<0.010	2	0.02
09										
18										
				PESTIC	IDE ANALY	SRS				
DATE	TIME	PCB, TOTAL (UG/L)	ALDRIN, TOTAL (UG/L)	CHLOR- DANE, TOTAL (UG/L)	DDD, TOTAL (UG/L)	DDR, TOTAL (UG/L)	DDT, TOTAL (UG/L)	DI- AZINON, TOTAL (UG/L)	DI- BLDRIN TOTAL (UG/L)	ENDO- SULFAN, TOTAL (UG/L)
JUN 1992 09	1030	<0.1	<0.010	<0.1	<0.010	<0.010	<0.010	<0.01	<0.010	<0.010
DAT JUN 199 09	(UG/ 2	BR TRD BTHI C TOT L) (UG	AL TOT (UG	OR, BPOX AL TOT /L) (UG	OR (IDB LINE (AL TOT (UG	AL TOT	ON, CHI FAL TOT F/L) (UC	(Y- PAR LOR, THI TAL TOT E/L) (UG	ON, MIR TAL TO I/L) (UG	EX, TAL (/L)
DAT JUN 199 09	(UG 2	LEN A- POI ON, CHI AL TOT /L) (UG/	IA- IES, IY- PE OR. THA I'AL TOT I'L) (UG	NE APHE AL TOT /L) (UG	AL THI	II- 2,4 ON TOI I/L) (UG	AL TO	3/L) (UG/	AL TOI L) (UG	

RIO FAJARDO BASIN

50072500 RIO FAJARDO BELOW FAJARDO, PR

WATER-QUALITY RECORDS

LOCATION.--Lat 18°19'35", long 65°38'47", 1.2 mi (1.9 km) southwest of Playa de Fajardo, and 0.5 mi (0.8 km) east of Fajardo plaza.

DRAINAGE ARRA. -- 23.4 mi 2 (60.6 km2).

K = non-ideal count

PERIOD OF RECORD. -- Water years 1974 to current year.

DIS-

SPE-

CIFIC CON-

DUCT-

CHARGE,

INST.

FRET

WATER-QUALITY DATA, WATER YEAR OCTOBER 1991 TO SEPTEMBER 1992

TUR-

BID-

TEMPER-

ATURE

PH

WATER

WHOLE

(STAND-

OXYGEN,

SOLVED (PER-

CENT

OXYGEN,

DIS-

OXYGEN

DEMAND,

CHEM-

(HIGH

ICAL

COLI-

FORM,

FECAL, 0.45

UM-MF

STREP-

TOCOCCI FECAL,

(COLS.

DATE	TIME	PE: SEC	R ANG	E AF	RD W	ATURE VATER DEG C)	BID ITY (NTU	r sol		UR- LEVI		S./ PER
OCT 1991 01 DEC	1235	25		135	6.8	27.0	34		7.0	83	16 K8	700 3100
10 FBB 1992	1330	24		147	7.0	26.0	4.	. 0	6.5	82	11	400 200
24 MAY	1235	18		196	7.0	26.0	2.	1	8.5	96	<10	720 800
13 JUN	0930	22		124	6.4	27.5	1.	. 0	6.4	80	12	360 510
09 AUG	1135	17		135	7.1	29.5	3.	.0	8.2	91	<10 2	800 260
18	1145	35		148	7.0	29.8	3.	.1	7.9	88	<10	490 20
DATE	i	HARD- NESS TOTAL (MG/L AS CACO3)	CALCIUM DIS- SOLVED (MG/L AS CA)	MAGNE- SIUM, DIS- SOLVED (MG/L AS MG)	SODIUM DIS- SOLVED (MG/L AS NA	1, SC) 1	DDIUM AD- DRP- TION ATIO	POTAS- SIUM, DIS- SOLVED (MG/L AS K)	ALKA- LINITY WAT WH TOT FET FIELD MG/L AS CACO3	SULFIDE TOTAL (MG/L AS S)	SULFATE DIS- SOLVED (MG/L AS SO4)	CHLO- RIDR, DIS- SOLVED (MG/L AS CL)
ОСТ 1991 01		35	8.4	3.3	13		1	1.9	35	<0.5	5.6	17
DEC 10									23			
FEB 1992 24									34			
MAY 13		31	6.8	3.3	11		0.9	1.2	23	<0.5	4.4	14
JUN 09									40			
AUG 18		37	8.5	3.8	13	•	0.9	1.1	18		4.3	20
DATE		FLUO- RIDE, DIS- SOLVED (MG/L AS F)	SILICA, DIS- SOLVED (MG/L AS SIO2)	SOLIDS, SUM OF CONSTI- TUENTS, DIS- SOLVED (MG/L)	SOLIDS DIS- SOLVE (TONS PER DAY)	S, TOI AT RD DEC S SU PEN	SIDUE TAL 105 S. C, JS- TDED	NITRO- GEN, NITRATE TOTAL (MG/L AS N)	NITRO- GEN, NITRITE TOTAL (MG/L AS N)	NITRO- GEN, NO2+NO3 TOTAL (MG/L AS N)	NITRO- GEN, AMMONIA TOTAL (MG/L AS N)	NITRO- GEN, ORGANIC TOTAL (MG/L AS N)
OCT 1991 01 DEC		0.20	19	89	6.1	13	18	0.220	0.030	0.250	0.130	0.37
10 FEB 1992							11		<0.010	0.100	0.020	
24 MAY							14		<0.010	0.110	0.030	
13		0.20	21	76	4.5	51	12		<0.010	<0.050	0.030	
JUN 09 AUG							<1		<0.010	0.120	0.040	
18		<0.10	20	93	8.7	79	<1		<0.010	0.056	0.040	

50072500 RIO FAJARDO BELOW FAJARDO, PR--Continued WATER-QUALITY DATA, WATER YEAR OCTOBER 1991 TO SEPTEMBER 1992

361

D ate	NITRO- GEN, AM- MONIA + ORGANIC TOTAL (MG/L AS N)	NITRO- GEN, TOTAL (MG/L AS N)	NITRO- GEN, TOTAL (MG/L AS NO3)	PHOS- PHORUS TOTAL (MG/L AS P)	ARSENIC TOTAL (UG/L AS AS)	BARIUM, TOTAL RECOV- ERABLE (UG/L AS BA)	BORON, TOTAL RECOV- ERABLE (UG/L AS B)	CADMIUM TOTAL RECOV- ERABLE (UG/L AS CD)	CHRO- MIUM, TOTAL RECOV- ERABLE (UG/L AS CR)	COPPER, TOTAL RECOV- ERABLE (UG/L AS CU)
ост 1991										
01 DRC	0.50	0.75	3.3	0.060	<1	<100		<1	2	<10
10	<0.20			0.020						
FEB 1992	<0.20			0.030						
MAY 13	<0.20			0.030	<1	<100	20	<1	<1	<10
JUN 09	<0.20			0.010						
AUG										
18	<0.20			0.060						
DATE	IRON, TOTAL RECOV- ERABLE (UG/L AS FE)	LEAD, TOTAL RECOV- ERABLE (UG/L AS PB)	MANGA- NESE, TOTAL RECOV- ERABLE (UG/L AS MN)	MERCURY TOTAL RECOV- ERABLE (UG/L AS HG)	SELR- NIUM, TOTAL (UG/L AS SE)	SILVER, TOTAL RECOV- ERABLE (UG/L AS AG)	ZINC, TOTAL RECOV- RRABLE (UG/L AS ZN)	CYANIDE TOTAL (MG/L AS CN)	PHENOLS TOTAL (UG/L)	MRTHY- LENR BLUE ACTIVE SUB- STANCE (MG/L)
OCT 1991	TOTAL RECOV- ERABLE (UG/L AS FE)	TOTAL RECOV- ERABLE (UG/L AS PB)	NESE, TOTAL RECOV- ERABLE (UG/L AS MN)	TOTAL RECOV- ERABLE (UG/L AS HG)	NIUM, TOTAL (UG/L AS SE)	TOTAL RECOV- ERABLE (UG/L AS AG)	TOTAL RECOV- ERABLE (UG/L AS ZN)	TOTAL (MG/L AS CN)	TOTAL (UG/L)	LENE BLUE ACTIVE SUB- STANCE (MG/L)
OCT 1991 01 DEC	TOTAL RECOV- ERABLE (UG/L	TOTAL RECOV- ERABLE (UG/L	NESE, TOTAL RECOV- ERABLE (UG/L	TOTAL RECOV- BRABLE (UG/L	NIUM, TOTAL (UG/L	TOTAL RECOV- BRABLE (UG/L	TOTAL RECOV- ERABLE (UG/L	TOTAL (MG/L	TOTAL	LENE BLUE ACTIVE SUB- STANCE
OCT 1991 01 DEC 10	TOTAL RECOV- ERABLE (UG/L AS FE)	TOTAL RECOV- ERABLE (UG/L AS PB)	NESE, TOTAL RECOV- ERABLE (UG/L AS MN)	TOTAL RECOV- ERABLE (UG/L AS HG)	NIUM, TOTAL (UG/L AS SE)	TOTAL RECOV- ERABLE (UG/L AS AG)	TOTAL RECOV- ERABLE (UG/L AS ZN)	TOTAL (MG/L AS CN)	TOTAL (UG/L)	LENE BLUE ACTIVE SUB- STANCE (MG/L)
OCT 1991 01 DEC 10 FEB 1992 24	TOTAL RECOV- ERABLE (UG/L AS FE)	TOTAL RECOV- ERABLE (UG/L AS PB)	NESE, TOTAL RECOV- ERABLE (UG/L AS MN)	TOTAL RECOV- BRABLE (UG/L AS HG)	NIUM, TOTAL (UG/L AS SE)	TOTAL RECOV- ERABLE (UG/L AS AG)	TOTAL RECOV- ERABLE (UG/L AS ZN)	TOTAL (MG/L AS CN)	TOTAL (UG/L)	LENE BLUE ACTIVE SUB- STANCE (MG/L)
OCT 1991 01 DEC 10 FEB 1992 24 MAY 13	TOTAL RECOV- ERABLE (UG/L AS FE)	TOTAL RECOV- ERABLE (UG/L AS PB)	NESE, TOTAL RECOV- ERABLE (UG/L AS MN)	TOTAL RECOV- BRABLE (UG/L AS HG) <0.10	NIUM, TOTAL (UG/L AS SE)	TOTAL RECOV- BRABLE (UG/L AS AG) <1	TOTAL RECOV- ERABLE (UG/L AS ZN)	TOTAL (MG/L AS CN)	TOTAL (UG/L)	LENE BLUE ACTIVE SUB- STANCE (MG/L)
OCT 1991 01 DEC 10 FEB 1992 24	TOTAL RECOV- ERABLE (UG/L AS FE) 1900	TOTAL RECOV- ERABLE (UG/L AS PB)	NESE, TOTAL RECOV- BRABLE (UG/L AS MN)	TOTAL RECOV- BRABLE (UG/L AS HG)	NIUM, TOTAL (UG/L AS SE)	TOTAL RECOV- BRABLE (UG/L AS AG) <1	TOTAL RECOV- ERABLE (UG/L AS ZN)	TOTAL (MG/L AS CN) <0.010	TOTAL (UG/L) <1	LENE BLUR ACTIVE S'JB- STANCE (MG/L) 0.03

RIO BLANCO BASIN

50075000 RIO ICACOS NEAR NAGUABO, PR

LOCATION.--Lat 18°16'38", long 65°47'09", Hydrologic Unit 21010005, in Caribbean National Forest, off Highway 191, at El Yunque, 1.6 mi (2.6 km) upstream from confluence with Río Cubuy, 2.8 mi (4.5 km) north of Florida, and 5.3 mi (8.5 km) northwest of Naguabo Plaza.

DRAINAGE AREA. -- 1.26 mi2 (3.26 km2).

WATER-DISCHARGE RECORDS

PERIOD OF RECORD.--July 1945 to March 1953 (operated by Puerto Rico Water Resources Authority), annual maximum, water years 1953-62, annual low-flow measurements 1962-66, October 1979 to current year.

GAGE.--Water-stage recorder, crest-stage gage and sharp-crested weir. Elevation of gage is 2,020 ft (616 m), from topographic map.

REMARKS.--Records fair except those for estimated daily discharges, which are poor.

DAY	OCT	NOV										
		MOV	DEC	JAN	FEB	MAR	APR	MAY	JUN	JUL	AUG	SRP
1	e36	49	e6.9	e5.8	4.8	4.2	5.8	102	40	7.3	6.8	6.2
2	e25	17	e13	e5.0	4.8	4.1	4.3	40	33	6.8	9.7	5.5
3	e1 3	9.6	e25	e4.6	4.8	3.9	3.9	9.8	12	6.4	7.8	7.8
4	e13	8.0	e45	e4.1	5.4	4.1	3.9	8.9	15	6.4	13	8.8
5	e23	14	e19	e 36	4.8	4.1	4.2	9.0	11	6.7	54	12
	e12	43	e13	e132	16	4.1	4.1	161	20	6.2	34	9.2
7	e8.0	53	e6.0	e26	7.3	75	17	17	24	6.0	13	7.8
8	e7.5	152	e11	e7.0	5.8	13	14	12	14	14	8.8	5.9
9 10	e7.0 e8.8	44 20	e10 e9.6	e13 e100	6.0 8.6	4.7	39 7.7	16 12	10 30	9.2 7.0	6.1 7.5	11 5.6
11 12	e8.8 e23	9.0 9.0	e6.4 e14	e12 e11	5.5 5.2	4.3 24	12 13	13 11	19 18	9.6 7.2	26 6.6	7.5 5.5
	e11	7.7	e12	e50	5.1	5.7	9.7	10	15	10	13	5.3
14	e7.4	7.0	e11	e12	4.9	8.0	8.4	و. وَ	15	9.8	20	5.6
15	e6.8	8.9	e7.0	e7.8	4.9	5.7	7.6	9.9	12	9.0	7.4	7.8
16	e6.2	10	e8.0	e7.0	4.8	4.0	6.1	44	30	10	8.3	15
17	e6.0	7.2	e6.8	e6.2	5.0	10	10	11	22	33	7.0	14
18	e5.8	6.3	e7.4	6.0	5.4	21	42	10	12	12	5.6	14
19	e5.9	6.0	e7.0	5.7	6.0	8.0	24	10	12	10	5.2	14
20	e6.0	5.9	e25	5.6	5.1	5.9	9.7	9.8	9.4	13	6.7	44
21	e5.4	45	e14	5.6	4.9	4.6	7.7	9.4	9.5	10	4.9	19
22	e5.4	34	e7.2	5.5	8.4	8.7	7.3	9.2	9.1	9.3	4.7	8.6
23	e5.4	23	e6.8	5.3	5.2	7.4	7.4	69	13	8.2	5.1	16
24	e5.1	14	e5.4	5.9	5.3	4.4	7.2	29	8.9	15	6.3	11
25	e4.8	e7.0	e4.8	7.7	5.2	4.2	6.9	25	8.4	10	4.8	7.1
26	e4.9	e12	e4.8	7.0	7.0	3.8	7.3	31	7.9	9.3	5.8	5.7
27	e4. 7	e18	e5.8	5.5	5.9	3.7	6.9	11	9.7	9.9	5.2	5.1
28	e4.5	e1 3	e5.8	8.2	4.8	3.6	6.9	11	7.9	8.3	4.4	4.8
29	7.5	e9.6	e6.0	5.9	4.5	3.4	7.6	10	7.6	8.2	4.1	4.9
30 31	4.7	e11	e5.8 e5.0	5.2 5.1		21 6.9	8.7	11 13	7.4	6.6 6.6	6.5 16	9.0
	297.1	673.2	334.5	523.7	171.4	289.8	320.3	754.9	462.8	301.0	334.3	303.7
MEAN	9.58	22.4	10.8	16.9	5.91	9.35	10.7	24.4	15.4	9.71	10.8	10.1
MAX MIN	36 4.5	152	45	132	16	75	42	161	40	33 6.0	54 4.1	44
AC-FT	589	5.9 1340	4.8 663	4.1 1040	4.5 340	3.4 575	3.9 635	8.9 1500	7.4 918	5.0 597	663	602
CFSM	7.61	17.8	8.56	13.4	4.69	7.42	8.47	19.3	12.2	7.71	8.56	8.03
IN.	8.77	19.88	9.88	15.46	5.06	8.56	9.46	22.29	13.66	8.89	9.87	8.97
e Ret	timated											
STATISTI	ICS OF M	ONTHLY ME	AN DATA F	OR WATER Y	BARS 1945	- 1992,	BY WATER	YEAR (WY))			
MEAN	16.3	18.6	15.4	12.6	13.5	10.8	13.0	17.6	12.5	14.0	14.8	17.1
MAX	32.1	46.8	31.3	26.9	44.0	26.1	34.4	26.3	20.5	38.8	24.5	37.6
(WY)	1986	1951	1988	1952	1950	1949	1950	1948	1987	1952	1945	1989
MIN	8.77	8.00	4.99	7.72	4.86	3.90	4.77	10.7	5.19	7.35	7.63	7.03
(WY)	1983	1948	1990	1987	1983	1951	1984	1951	1985	1991	1991	1986
SUMMARY	STATIST	ics	FOR	1991 CALEN	DAR YEAR	F	OR 1992 W	ATER YEAR		WATER Y	BARS 1945	- 1992
ANNUAL T				4123.8			4766.7					
ANNUAL M				11.3			13.0			14.7		
HIGHEST										21.0		1952
LOWEST A										11.2		1984
HIGHEST				152	Nov 8		161	May 6 Mar 29		470		18 1989
LOWEST D			•	3.6	Aug 7 Aug 4		3.4 4.1			1.5 2.0		22 1946 7 1946
		Y MINIMUM BAK FLOW		3.7	Aug 4		1260			2860		21 1983
		BAK STAGE					6.7	1 May 6		8.9		21 1983
Instanta	ANEOUS L	OW FLOW	-				2.9	Aug 29				
ANNUAL R				8180 8.97			9450 10.3			10630 11.6		
ANNUAL R				121.75			140.7			158.2		
10 PERCE				23			25	-		30		
50 PERCE				7.5			8.0			8.2		
90 PERCE				4.5			4.8			4.7		

RIO BLANCO BASIN

50075000 RIO ICACOS NEAR NAGUABO, PR--Continued

WATER QUALITY RECORDS

PERIOD OF RECORD. -- WATER YEARS AUGUST 1981 TO CURRENT YEAR

DATE	TIME	STREAMFLOW, INSTANTANEOUS (CFS)	SPECIFIC CON- DUCTANCE (UMHOS)	TEMPERA- TURE (DEG C)	DATE	TIME	STRRAMFLOW, INSTANTANEOUS (CFS)	SPECIFIC CON- DUCTANCE (UMHOS)	TEMPERA- Ture (DEG C)
MAR. 31		4.83	50	21.5	JUN. 12	1338	11.0	40	24.0
MAY. 20	1236	9.87	50	24.5					

THIS PAGE WAS LEFT BLANK INTENTIONALLY




Figure 22.--Southeastern river basins the Río Humacao to Río Seco basins.

RIO HUMACAO BASIN

50081000 RIO HUMACAO AT LAS PIEDRAS, PR

LOCATION.--Lat 18°10'27", long 65°52'11", Hydrologic unit 21010005, on left bank at downstream side of bridge on Highway 921, 0.6 mi (1.0 km) southeast of junction with Highway 30, 0.8 mi (1.3 km) downstream from Quebrada Blanca and 0.8 mi (1.3 km) south of Las Piedras.

DRAINAGE ARRA. -- 6.65 mi 2 (17.22 km2).

WATER-DISCHARGE RECORDS

PERIOD OF RECORD. -- September 1958 to December 1967 (monthly discharge measurements), July 1974 to September 1977, October 1987 to current year.

GAGE.--Water-stage recorder. Elevation of gage is 260 ft (79 m), from topographic map. Prior to July 1974, crest-stage gage at different datum. July 1974 to September 1977 at site 90 ft (27 m) upstream at present datum.

REMARKS.--Records fair except those above 1,000 ft³/s (28.3 m³/s) and estimated daily discharges, which are poor. Gage-height and precipitation satellite telemetry at station.

		DISCHAR	GE, CUB	IC FEET PER		WATER YE		1991 TO	SEPTEMBI	ER 1992		
DAY	OCT	NOV	DEC	JAN	FEB	MAR	APR	MAY	JUN	JUL	AUG	SEP
1	20	9.1	13	11	11	9.1	8.3	7.8	115	15	16	15
2	46	10	13	10	11	10	9.0	20	48	15	17	16
3	21	10	17	9.3	11	9.8	8.0	9.0	25	15	16	21
4	15	14	19	9.0	13	11	7.7	7.7	31	14	17	15
5	13	11	14	365	11	11	7.5	7.1	26	25	65	14
6	12	13	13	e290	22	12	9.1	13	21	16	22	21
7	12	96	12	e35	14	17	11	11	22	15	36	19
9	11 12	597 92	12 12	21 18	12	16	8.1	8.1	28 42	17 17	29 20	18 35
10	22	47	12	19	11	9.1	8.0 7.7	7.7	29	15	24	17
11	56	25	11	16	12	9.0	8.5	10	27	18	20	15
12	14	20	12	15	11	8.8	15	8.4	37	16	29	14
13	15	18	11	15	11	8.8	13	7.4	41	14	20	13
14	13	15	11	14	11	9.0	9.7	7.5	37	14	19	14
15	15	14	10	13	13	9.4	11	10	25	14	18	14
16	15	14	15	13	11	8.4	7.8	11	22	14	21	25
17	15	13	11	13	11	9.5	8.7	10	28	47	21	37
18	13	13	10	12	10	10	17	8.1	21	18	17	21
19 20	13 11	13 12	10 11	12 13	10 9.7	8.9	16 33	7.7	19 22	23 25	16 33	84 298
21	11 10	15 38	9.9	12 12	9.7 9.7	9.2 8.7	11 9.1	6.9	39 21	18 65	21 17	123 33
23	11	19	10	12	9.9	8.5	8.1	147	24	20	19	39
24	11	56	9.7	13	10	8.2	8.0	157	19	19	24	27
25	10	23	9.4	13	9.9	8.1	7.5	226	18	19	17	23
26	9.8	16	9.4	13	9.5	9.2	7.4	466	17	16	17	21
27	9.9	26	9.3	12	9.7	11	7.1	32	18	17	16	21
28	9.7	17	9.2	12	9.7	8.2	7.4	23	17	16	16	18
29	9.7	16	9.8	12	9.4	7.9	7.1	19	16	15	16	17
30	9.6	14	9.3	12		7.4	7.1	18	15	15	14	20
31	9.3		12	11		7.7		17		15	19	
TOTAL	475.0	1296.1	358.0	1057.3	327.2	303.9	303.9	1308.2	870	602	672	1068
MEAN	15.3	43.2	11.5	34.1	11.3	9.80	10.1	42.2	29.0	19.4	21.7	35.6
MAX	9.3	597	19	365	22	17	33	466	115	65	65	298
MIN AC-FT	942	9.1 2570	9.2 710	9.0 2100	9.4	7.4 603	7.1 603	6.9 2590	15 1730	14 1190	1330	13 2120
CFSM	2.30	6.50	1.74	5.13	1.70	1.47	1.52	6.35	4.36	2.92	3.26	5.35
IN.	2.66	7.25	2.00	5.91	1.83	1.70	1.70	7.32	4.87	3.37	3.76	5.97
e Ri	stimated											
						=						
STATIST	TICS OF I	MONTHLY MRA	IN DATA	FOR WATER Y	TRARS 1974	- 1992,	BY WATER	YEAR (WY)				
MEAN	35.3	44.6	36.3	19.9	15.0	11.7	9.27	15.3	15.3	17.6	19.8	31.4
MAX	74.9	126	112	34.1	20.5	16.4	13.1	42.2	29.0	33.2	32.7	54.1
(WY)	1975	1988	1988	1992	1988	1989	1976	1992	1992	1989	1977	1975
MIN	15.3	17.0	11.5	10.8	11.0	9.24	5.88	7.26	5.91	7.95	9.45	10.0
(WY)	1992	1990	1992	1990	1977	1977	1977	1990	1977	1990	1974	1990
SUMMARY	Y STATIS	rics	FOR	1991 CALE	DAR YEAR	F	OR 1992 WA	TER YEAR		WATER YE	ARS 1974	- 1992
ANNUAL	TOTAL			5784.7			8641.6					
ANNUAL	MEAN			15.8			23.6			22.8		
	T ANNUAL									37.6		1988
	ANNUAL I			40.50						12.1		1990
	T DAILY I			597			597	Nov 8		1670		27 1987
	DAILY M			4.9			6.9			2.2		15 1974
		MUMINIM YA		5.9	Apr 27		7.3			2.8		19 1974
		PEAK FLOW PEAK STAGE					3720	May 26		20800 34.40		6 1960 6 1960
	TANEOUS I						6.8	May 26 May 22		34.40	sep	0 1300
ANNUAL	RUNOFF	(AC-FT)		11470			17140	conf as		16530		
	RUNOFF			2.38			3.55			3.43		
	RUNOFF			32.3	5		48.34			46.61		
	CENT EXC			19			31			34		
	CENT EXC			9.8			14			14		
90 PER	CENT EXC	RRDS		6.6			8.5			6.7		

50082000 RIO HUMACAO AT HIGHWAY 3 AT HUMACAO, PR

WATER-QUALITY RECORDS

LOCATION.--Lat 18°08'49", long 65°49'37", at bridge on Highway 3, 300 ft (91 m) downstream from Quebrada Mariana, and 0.4 mi (0.6 km) south of Humacao.

TEMPER-

ATURE

PH WATER WHOLE

FIRLD

(STAND-

DRAINAGE AREA. -- 17.3 mi 2 (44.8 km2).

PERIOD OF RECORD. -- Water years 1958-66, 1969 to current year.

SPR-

CIFIC CON-

DUCT-

DIS-

CHARGE, INST. CUBIC

FERT

WATER-QUALITY DATA, WATER YEAR OCTOBER 1991 TO SEPTEMBER 1992

TUR-

BID-

OXYGEN,

DIS-

OXYGEN,

DIS-

SOLVED (PER-

CENT

OXYGEN

DEMAND,

CHEM-

ICAL

(HIGH

COLI-

FORM, FECAL, 0.45

UM-MP

STREP-TOCOCCI

(COLS.

FECAL,

DATB	TIME	PEI	R ANG	CR A	RD ITS)	WAT:	BR I	Y SO	LVED SAT	UR- LEVE	L) (COL	S./ PER
OCT 1991												
22 DEC	1210	3	. 4	400	7.0	2	8.5 13	1	2.4	31	61 K600	000 300000
12 FEB 1992	1215	13		346	6.9	2	5.5	3.0	4.3	47	31 58	000 42000
14 May	1250	21		315	7.5	2	6.0 20)	6.2	83	18 27	000 7400
08 Jun	1150	6	. 5	370	6.7	2	8.5 12	1	5.1	61	18 -	
18 AUG	1340			296	7.4		1.5 1		6.1	80		500 K1000
28	1430	8	. 6	306	7.4	3	0.0	5.9	5.2	64	64 290	000 6200
		HARD-		magne-			SODIUM	POTAS-	ALKA- LINITY			CHLO-
DATE	,	NESS TOTAL (MG/L AS CACO3)	CALCIUM DIS- SOLVED (MG/L AS CA)	SIUM, DIS- SOLVED (MG/L AS MG)	DI SOL (M	IUM, S- VED G/L NA)	AD- SORP- TION RATIO	SIUM, DIS- SOLVED (MG/L AS K)	WAT WH TOT FET FIELD MG/L AS CACO3	SULFIDE TOTAL (MG/L AS S)	SULFATE DIS- SOLVED (MG/L AS SO4)	RIDE, DIS- SOLVED (MG/L AS CL)
OCT 1991				,		,						,
22 DEC		95	26	7.2	3	4	2	3.4	130	<0.5	14	36
12 FRB 1992									90			
1 4 May									115			
MOL 08		89	26	5.9		7	1	2.2	100	<0.5	12	37
AUG									84			
28		83	23	6.1	2	4	1	2.8	100		13	31
		FLUO- RIDB,	SILICA, DIS-	SOLIDS, SUM OF CONSTI-		IDS,	RESIDUE TOTAL AT 105	ni tro- gen ,	NITRO- GEN,	NITRO- GEN,	NITRO- GEN,	NITRO- GEN,
		DIS-	SOLVED	TUENTS,		LVED	DEG. C,	NITRATE		NO3+NO3	AMMONIA	ORGANIC
DATE		SOLVED (MG/L	(MG/L AS	DIS- SOLVED		ONS ER	SUS- PENDED	TOTAL (MG/L	TOTAL (MG/L	TOTAL (MG/L	TOTAL (MG/L	TOTAL (MG/L
		AS F)	SIO2)	(MG/L)		AY)	(MG/L)	AS N)	AS N)	AS N)	AS N)	AS N)
OCT 1991												
22 Dec		0.10	37	236		2.18	<1	1.00	0.100	1.10	2.80	1.3
12 FEB 1992							5	0.910	0.090	1.00	1.40	0.90
14 May							36	1.09	0.110	1.20	0.190	0.51
80 NUC		0.20	33	203		3.59	4	0.650	0.050	0.700	0.060	
18 AUG							32	0.420	0.030	0.450	0.080	0.22
28		0.10	34	190		4.41	18	0.500	0.020	0.520	1.20	0.60

R = non-ideal count

RIO HUMACAO BASIN

50082000 RIO HUMACAO AT HIGHWAY 3 AT HUMACAO, PR--Continued

WATER-QUALITY DATA, WATER YEAR OCTOBER 1991 TO SEPTEMBER 1992

DATE	NITRO- GEN, AM- MONIA + ORGANIC TOTAL (MG/L AS N)	NITRO- GEN, TOTAL (MG/L AS N)	NITRO- GEN, TOTAL (MG/L AS NO3)	PHOS- PHORUS TOTAL (MG/L AS P)	ARSENIC TOTAL (UG/L AS AS)	BARIUM, TOTAL RECOV- ERABLE (UG/L AS BA)	BORON, TOTAL RECOV- ERABLE (UG/L AS B)	CADMIUM TOTAL RECOV- ERABLE (UG/L AS CD)	CHRO- MIUM, TOTAL RECOV- ERABLE (UG/L AS CR)	COPPER, TOTAL RECOV- ERABLE (UG/L AS CU)
OCT 1991										
22 Dec	4.1	5.2	23	0.880	<1	<100	30	<1	<1	10
12	2.3	3.3	15	0.570						
FBB 1992 14	0.70	1.9	8.4	0.440						
MAY					_			_		
08 Jun	<0.20			0.240	<1	<100	40	<1	<1	<10
18	0.30	0.75	3.3	0.130						
28	1.8	2.3	10	0.410						
DATE	IRON, TOTAL RECOV- ERABLE (UG/L AS FE)	LEAD, TOTAL RECOV- ERABLE (UG/L AS PB)	MANGA- NESE, TOTAL RECOV- ERABLE (UG/L AS MN)	MERCURY TOTAL RECOV- ERABLE (UG/L AS HG)	SELE- NIUM, TOTAL (UG/L AS SE)	SILVER, TOTAL RECOV- ERABLE (UG/L AS AG)	ZINC, TOTAL RECOV- ERABLE (UG/L AS ZN)	CYANIDE TOTAL (MG/L AS CN)	PHENOLS TOTAL (UG/L)	METHY- LENE BLUE ACTIVE SUB- STANCE (MG/L)
ост 1991	TOTAL RECOV- BRABLE (UG/L AS FE)	TOTAL RECOV- ERABLE (UG/L AS PB)	NESE, TOTAL RECOV- ERABLE (UG/L AS MN)	TOTAL RECOV- ERABLE (UG/L AS HG)	NIUM, TOTAL (UG/L AS SE)	TOTAL RECOV- ERABLE (UG/L AS AG)	TOTAL RECOV- ERABLE (UG/L AS ZN)	TOTAL (MG/L AS CN)	TOTAL (UG/L)	LENE BLUE ACTIVE SUB- STANCE (MG/L)
	TOTAL RECOV- BRABLE (UG/L	TOTAL RECOV- ERABLE (UG/L	NESE, TOTAL RECOV- ERABLE (UG/L	TOTAL RECOV- BRABLE (UG/L	NIUM, TOTAL (UG/L	TOTAL RECOV- ERABLE (UG/L	TOTAL RECOV- BRABLE (UG/L	TOTAL (MG/L	TOTAL	Lene Blur Active Sub- Stance
OCT 1991 22 DEC 12	TOTAL RECOV- BRABLE (UG/L AS FE)	TOTAL RECOV- ERABLE (UG/L AS PB)	NESE, TOTAL RECOV- ERABLE (UG/L AS MN)	TOTAL RECOV- ERABLE (UG/L AS HG)	NIUM, TOTAL (UG/L AS SE)	TOTAL RECOV- ERABLE (UG/L AS AG)	TOTAL RECOV- ERABLE (UG/L AS ZN)	TOTAL (MG/L AS CN)	TOTAL (UG/L)	LENE BLUE ACTIVE SUB- STANCE (MG/L)
OCT 1991 22 DEC 12 FEB 1992 14	TOTAL RECOV- ERABLE (UG/L AS FE)	TOTAL RECOV- ERABLE (UG/L AS PB)	NESE, TOTAL RECOV- ERABLE (UG/L AS MN)	TOTAL RECOV- ERABLE (UG/L AS HG)	NIUM, TOTAL (UG/L AS SE)	TOTAL RECOV- ERABLE (UG/L AS AG)	TOTAL RECOV- ERABLE (UG/L AS ZN)	TOTAL (MG/L AS CN)	TOTAL (UG/L)	LENE BLUE ACTIVE SUB- STANCE (MG/L)
OCT 1991 22 DEC 12 FEB 1992 14 MAY 08	TOTAL RECOV- ERABLE (UG/L AS FE)	TOTAL RECOV- ERABLE (UG/L AS PB)	NESE, TOTAL RECOV- ERABLE (UG/L AS MN)	TOTAL RECOV- ERABLE (UG/L AS HG) 0.20	NIUM, TOTAL (UG/L AS SE)	TOTAL RECOV- ERABLE (UG/L AS AG) 17	TOTAL RECOV- ERABLE (UG/L AS ZN) <10	TOTAL (MG/L AS CN) <0.010	TOTAL (UG/L) 10	LENE BLUE ACTIVE SUB- STANCE (MG/L)
OCT 1991 22 DEC 12 FEB 1992 14	TOTAL RECOV- RRABLE (UG/L AS FE)	TOTAL RECOV- ERABLE (UG/L AS PB)	NESE, TOTAL RECOV- ERABLE (UG/L AS MN) 250	TOTAL RECOV- ERABLE (UG/L AS HG)	NIUM, TOTAL (UG/L AS SE)	TOTAL RECOV- ERABLE (UG/L AS AG)	TOTAL RECOV- ERABLE (UG/L AS ZN)	TOTAL (MG/L AS CN) <0.010	TOTAL (UG/L) 10 	LENE BLUE ACTIVE SUB- STANCE (MG/L)

50083500 RIO GUAYANES AT YABUCOA, PR

WATER-QUALITY RECORDS

LOCATION.--Lat 18°03'33", long 65°54'03", at bridge on Highway 182, 1.4 mi (2.2 km) west-northwest of Yabucoa

DRAINAGE ARRA. -- 17.2 mi 2 (44.6 km2).

PERIOD OF RECORD. -- Water years 1958-62, 1968-70, 1980 to current year.

WATER-QUALITY DATA, WATER YEAR OCTOBER 1991 TO SEPTEMBER 1992

DATE	TIME	DIS CHARC INST CUBI FRI PRI SECC	GE, SPE F. CIF IC CON ST DUC R ANC	PIC WHO I- FIE T- (ST) ER AF	TER DLB SLD TEMI AND- ATU ND WAY	PER- JRE TER 3 C)	TUR- BID- ITY (NTU)	- DI SOL	D: SO: En, (P: S- C: VRD SA'	GEN, IS- LVED ER- ENT TUR- ION)	OXYGEN DEMAND CHEM- ICAL (HIGH LEVEL) (MG/L)	POR PRC 0.4 UM-1 (COL	M, STREP- AL, TOCOCCI 5 FECAL, MF (COLS. S./ PER	,
OCT 1991 22	1000	27		150	7.0	25.0	16		3.0	36	<1	10 42	000 210	^
DEC														
12 FEB 1992	1100	51		161	7.2	23.0	13		2.2	66	1	L3 K	220 K90	ס
19 May	0935	28		177	7.2	23.0	9.:	3	8.4	92	<1	LO K	990 K90	0
08	1000	33		160	6.3	25.0	33		6.9	90	1	16 2	100 3100	0
JUN 18	1135	88		127	6.9	26.0	53		6.4	74	1	14 4	100 3300	O
AUG 24	1250	28		150	7.0	28.0	8.	•	6.9	81	<1	LO K7	400 2600	0
DATE OCT 1991 22 DEC 12	NE T((1	ARD- RSS OTAL MG/L AS ACO3)	CALCIUM DIS- SOLVED (MG/L AS CA)	MAGNE- SIUM, DIS- SOLVED (MG/L AS MG)	SODIUM, DIS- SOLVED (MG/L AS NA)	SO T	DIUM AD- RP- ION TIO	POTAS- SIUM, DIS- SOLVED (MG/L AS K)	ALKA- LINITY WAT WH TOT FET FIELD MG/L AS CACO3	TO's	FIDE FAL 3/L	SULFATE DIS- SOLVED (MG/L AS SO4) 3.7	CHLO- RIDE, DIS- SOLVED (MG/L AS CL)	
FEB 1992 19									64					
MAY 08		43	11	3.8	14		0.9	1.9	25		c 0.5	5.6	15	
JUN 18									41		- -			
AUG														
24		47	12	4.2	14		0.9	1.4	40	•		3.6	14	
DATE	R: : S() ()	LUO- IDE, DIS- DLVED MG/L S F)	SILICA, DIS- SOLVED (MG/L AS SIO2)	SOLIDS, SUM OF CONSTI- TUENTS, DIS- SOLVED (MG/L)	SOLIDS, DIS- SOLVED (TONS PER DAY)	Tot At Deg Su Pen	105 . C, 1	NITRO- GEN, NITRATE TOTAL (MG/L AS N)	NITRO- GEN, NITRITE TOTAL (MG/L AS N)	G! NO2 - TO:	FAL 3/L	NITRO- GEN, AMMONIA TOTAL (MG/L AS N)	NITRO- GEN, ORGANIC TOTAL (MG/L AS N)	
ост 1991			2.5	4.5.5				0.00-	0.000	_	252			
22 DEC	•	<0.10	36	130	9.39		4	0.230	0.030	0	.260	0.090	0.11	
12 FRB 1992							8	1.19	0.010	1	.20	<0.010		
19							12		<0.010	0	.810	0.010		
MAY 08		0.20	32	98	8.72		26	0.320	0.030	0	.350	0.040	~-	
JUN 18							71	0.290	0.030	0	.320	0.060		
AUG 24		0.10	34	118	8.92		30	0.260	0.020	0	. 280	0.050		

K = non-ideal count

RIO GUAYANES BASIN

50083500 RIO GUAYANES AT YABUCOA, PR--Continued WATER-QUALITY DATA, WATER YEAR OCTOBER 1991 TO SEPTEMBER 1992

DATE	NITRO- GEN, AM- MONIA + ORGANIC TOTAL (MG/L AS N)	NITRO- GEN, TOTAL (MG/L AS N)	NITRO- GEN, TOTAL (MG/L AS NO3)	PHOS- PHORUS TOTAL (MG/L AS P)	ARSENIC TOTAL (UG/L AS AS)	BARIUM, TOTAL RECOV- ERABLE (UG/L AS BA)	TOTAL RECOV-	CADMIUM TOTAL RECOV- ERABLE (UG/L AS CD)	CHRO- MIUM, TOTAL RECOV- ERABLE (UG/L AS CR)	COPPER, TOTAL RECOV- ERABLE (UG/L AS CU)
OCT 1991										
22 DEC	0.20	0.46	2.0	0.060	<1	<100	<10	<1	1	<10
12 FEB 1992	<0.20			0.280						
19	<0.20			0.060						
MAY 08	<0.20			0.060	<1	<100	20	<1	<1	<10
JUN 18	<0.20			0.070						
AUG 24	<0.20			0.040						
DATE	IRON, TOTAL RECOV- ERABLE (UG/L AS FE)	LRAD, TOTAL RECOV- ERABLE (UG/L AS PB)	MANGA- NESE, TOTAL RECOV- ERABLE (UG/L AS MN)	MERCURY TOTAL RECOV- ERABLE (UG/L AS HG)	SELE- NIUM, TOTAL (UG/L AS SE)	SILVER, TOTAL RECOV- ERABLE (UG/L AS AG)	TOTAL RECOV- ERABLE (UG/L	CYANIDE TOTAL (MG/L AS CN)	PHENOLS TOTAL (UG/L)	METHY- LENB BLUB ACTIVE SUB- STANCE (MG/L)
OCT 1991										
22 DBC	1700	3	130	<0.10	<1	<1	<10	<0.010	2	0.02
12 FEB 1992										
19										
MAY 08	2000	1	100	<0.10	<1	<1	<10	<0.010	2	0.02
JUN 18										
AUG 24										
			9	ESTICIDE	ANAT.VSRS					
			_					DT	DT -	PATRO :
DATE	TIME	PCB, TOTAL (UG/L)	ALDRIN, TOTAL (UG/L)	CHLOR- DANE, TOTAL (UG/L)	DDD, TOTAL (UG/L)	DDB, TOTAL (UG/L)	DDT, TOTAL (UG/L)	DI- AZINON, TOTAL (UG/L)	DI- BLDRIN TOTAL (UG/L)	ENDO- SULFAN, TOTAL (UG/L)
JUN 1992 18	1135	<0.1	<0.010	<0.1	<0.010	<0.010	<0.010	<0.01	<0.010	<0.010
DA.	(UG/	BR TRD BTHI C TOT	ON, CHL	TA- CHI OR, BPOX 'AL TOT	IDR LINE	ANE TH	LA- O ION, CH TAL TO	XY- PAF LOR, THI TAL TOI	ION, MIR PAL TO	EX, TAL ;/L)
JUN 19 18		010 <0	.01 <0.	010 <0.	010 <0.	010 <	0.01 <	0.01 <0	0.01 <0	.01
DA	PAR THI TE TOT (UG	LEN A- POI ON, CHI AL TOT	IA- IES, .Y- PE .OR. THA 'AL TOT	NE APHE	'AL THI	II- 2, ON TO	TAL TO	,5-T 2, 4 TAL TOT G/L) (UG/	TOT	
JUN 19		01 -0	. 10	0 1		. 01	0.01 =	0 01 -1	۰ ۱ ۱	.01
18	. <0	.01 <0	.10 <	0.1	:1 <0	.01 <	0.01 <	0.01 <0).01 <0	.01

STREP-TOCOCCI

(COLS.

PER

PECAL,

RIO GUAYANES BASIN

50086500 RIO GUAYANES ABOVE MOUTH AT PLAYA DE GUAYANES, PR

WATER-QUALITY RECORDS

LOCATION.--Lat 18°03'45", long 65°49'42", at old railroad crossing, 0.2 mi (0.3 km) from mouth, 0.4 mi (0.6 km) west of Playa de Guayanés, and 3.5 mi (5.6 km) northeast of Yabucoa plaza.

TEMPER-

ATURE

WATER

PH

WATER

WHOLE

FIELD

(STAND-

ARD

DRAINAGE AREA. -- 34.0 mi 2 (88.1 km2).

TIME

DATE

PERIOD OF RECORD. -- Water years 1974 to current year.

DIS-

SPE-CIFIC

CON-

ANCE

DUCT-

CHARGE,

CUBIC

PBBT PBR

WATER-QUALITY DATA, WATER YEAR OCTOBER 1991 TO SEPTEMBER 1992

TUR-

BID-

ITY

OXYGEN,

DIS-

SOLVED

OXYGEN,

(PER-

CENT SATUR-

DIS-SOLVED OXYGEN

DEMAND, CHEM-

ICAL

TEART)

(HIGH

COLI-

FORM, FECAL,

0.45

UM-MF

(COLS./

DATE	TIME	Sec.		CB (CM) U	ARD NITS)	WAT (DEG		ITY UTM)			rur- Ion)	LEVEI			PER 0 ML)
OCT 1991															
28 DEC	1135	11		182	7.2	2	7.0	13		7.8	97		10 K	650	320
17 FRB 1992	1230	27		180	7.2	2	4.5	12		8.1	99		11	290	570
19 May	1140	35		185	7.6	2	5.0	9.	8	7.5	90		14	280	250
12 Jun	1145			184	6.5		9.0	11		5.4	72			370	290
19 AUG	1045			210	6.6		7.5	29	_	4.4	62			800	350
28	1250	39		255	7.3	2	9.5	7.	5	7.2	86	•	<10	480	330
		HARD-		MAGNE	! ~		SO	DIUM	POTAS-	ALKA- LINITY				CHLO-	
DATE		ness Total (MG/L AS	CALCIUM DIS- SOLVED (NG/L	DIS-	DI D SOI	IUM, S- VED IG/L	SOI	AD- RP- ION TIO	SIUM, DIS- SOLVED (MG/L	WAT WH TOT FET FIELD MG/L AS	SULE TOI (MG	FAL S/L	SULFATE DIS- SOLVED (MG/L	RIDE, DIS- SOLVE (MG/L	tD
		CACO3)	AS CA)	AS MO) AS	NA)			AS K)	CAC03	AS	S)	AS SO4)	AS CL	•)
OCT 1991 28 DEC		56	14	5.0	1	.8		1	2.0	54	•	0.5	5.4	17	
17 FRB 1992										46	-	-			
19 May										62	-				
12 JUN		48	12	4.3	1	.6		1	1.9	57		0.5	5.2	16	
19 AUG 28		62	16				•			. 66				•	
40		04	10	5.3		.8		1	1.6	40	-	_	5.5	16	
				SOLIDS				IDUR							
		FLUO- RIDE, DIS-	SILICA, DIS- SOLVED	CONST1	- I	IDS, IS- LVED		105 . C,	NITRO- GEN, NITRATE	NITRO- GEN, NITRITE	NO24		NITRO- GEN, AMMONIA	NITRO GEN, ORGANI	C
DATE		SOLVED (MG/L AS F)	(MG/L AS SIO2)	DIS- SOLVE (MG/I	D T	CONS PER DAY)	SU: PENI (M		TOTAL (MG/L AS N)	TOTAL (MG/L AS N)	TOT (MC AS	3/L	TOTAL (MG/L AS N)	TOTAL (MG/L AS N)	•
OCT 1991															
28		<0.10	39	13	3	3.84		29	0.210	0.010	0.	220	0.030		
17 FEB 1992								14	0.370	0.010	0.	380	<0.010		
19 May								22	~~	<0.010		370	0.010		
12 JUN		0.20	36	12	6 2	0.6		8		0.010		050	0.030		
19 AUG		0.10						48	0.260	0.040		300	0.170	0.5	3

K = non-ideal count

0.10

34

135

14.2

0.290

0.010

0.300

0.050

28...

RIO GUAYANES BASIN 50086500 RIO GUAYANES ABOVE MOUTH AT PLAYA DE GUAYANES, PR--Continued

WATER-QUALITY DATA, WATER YEAR OCTOBER 1991 TO SEPTEMBER 1992

DATE	NITRO- GEN, AM- MONIA + ORGANIC TOTAL (MG/L AS N)	NITRO- GEN, TOTAL (MG/L AS N)	NITRO- GEN, TOTAL (MG/L AS NO3)	PHOS- PHORUS TOTAL (MG/L AS P)	ARSENIC TOTAL (UG/L AS AS)	BARIUM, TOTAL RECOV- ERABLE (UG/L AS BA)	BORON, TOTAL RECOV- ERABLE (UG/L AS B)	CADMIUM TOTAL RECOV- ERABLE (UG/L AS CD)	CHRO- MIUM, TOTAL RECOV- BRABLE (UG/L AS CR)	COPPER, TOTAL RECOV- ERABLE (UG/L AS CU)
OCT 1991										
28 DBC	<0.20			0.080	∢1	<100	80	<1	1	20
17 FRB 1992	<0.20			0.040						
19 MAY	<0.20			0.040						
12 JUN	<0.20			0.020	<1	<100	20	<1	<1	<10
19 AUG	0.70	1.0	4.4	0.250						
28	<0.20			0.030						
	IRON, TOTAL RECOV-	LEAD, TOTAL	MANGA - NESE, TOTAL RECOV-	MERCURY TOTAL RECOV-	SRLE- NIUM,	SILVER,	ZINC, TOTAL RECOV-	CYANIDE		METHY- LENE BLUE ACTIVE
DATE	ERABLE (UG/L AS FE)	RECOV- ERABLE (UG/L AS PB)	ERABLE (UG/L AS MN)	ERABLE (UG/L AS HG)	TOTAL (UG/L AS SE)	RECOV- ERABLE (UG/L AS AG)	ERABLE (UG/L AS ZN)	TOTAL (MG/L AS CN)	PHENOLS TOTAL (UG/L)	SUB- STANCE (MG/L)
ОСТ 1991	ERABLE (UG/L AS FE)	ERABLE (UG/L	ERABLE (UG/L AS MN)	ERABLE (UG/L AS HG)	TOTAL (UG/L	ERABLE (UG/L AS AG)	ERABLE (UG/L AS ZN)	TOTAL (MG/L AS CN)	TOTAL	SUB- STANCE
	ERABLE (UG/L	ERABLE (UG/L	ERABLE (UG/L	ERABLE (UG/L	TOTAL (UG/L	ERABLE (UG/L	ERABLE (UG/L	TOTAL (MG/L	TOTAL	SUB- STANCE
OCT 1991 28	ERABLE (UG/L AS FE)	ERABLE (UG/L AS PB)	ERABLE (UG/L AS MN)	ERABLE (UG/L AS HG)	TOTAL (UG/L AS SE)	ERABLE (UG/L AS AG)	ERABLE (UG/L AS ZN)	TOTAL (MG/L AS CN)	TOTAL (UG/L)	SUB- STANCE (MG/L)
OCT 1991 28 DBC 17 FRB 1992 19	ERABLE (UG/L AS FE)	ERABLE (UG/L AS PB)	ERABLE (UG/L AS MN)	ERABLE (UG/L AS HG)	TOTAL (UG/L AS SE)	ERABLE (UG/L AS AG)	ERABLE (UG/L AS ZN)	TOTAL (MG/L AS CN)	TOTAL (UG/L)	SUB- STANCE (MG/L)
OCT 1991 28 DEC 17 FRB 1992 19 MAY	ERABLE (UG/L AS FE) 1800	ERABLE (UG/L AS PB)	ERABLE (UG/L AS MN)	ERABLE (UG/L AS HG)	TOTAL (UG/L AS SE)	ERABLE (UG/L AS AG)	ERABLE (UG/L AS ZN)	TOTAL (MG/L AS CN)	TOTAL (UG/L)	SUB- STANCE (MG/L) 0.02
OCT 1991 28 DEC 17 FEB 1992 19	ERABLE (UG/L AS FE) 1800	ERABLE (UG/L AS PB)	ERABLE (UG/L AS MN) 90	ERABLE (UG/L AS HG) <0.10	TOTAL (UG/L AS SE) <1	ERABLE (UG/L AS AG) <1	ERABLE (UG/L AS ZN) <10	TOTAL (MG/L AS CN) <0.010	TOTAL (UG/L)	SUB- STANCE (MG/L) 0.02

RIO MAUNABO BASIN

373 50090500 RIO MAUNABO AT LIZAS, PR

LOCATION.--Lat 18°01'38", long 65°56'24", Hydrologic Unit 21010005, on right bank, off Highway 759 at Lizas, about 1.0 mi (1.6 km) downstream from Quebrada Coroco, and about 3.0 mi (4.8 km) northwest of Maunabo.

DRAINAGE AREA. -- 5.38 mi 2 (13.93 km2).

WATER-DISCHARGE RECORDS

PERIOD OF RECORD. -- February 1971 to January 1985, February 1991 to current year.

GAGE. -- Water-stage recorder and crest-stage gage. Elevation of gage is 230 ft (70 m), from topographic map.

REMARKS.--Records fair except those for estimated daily discharges, which are poor. Gage-height and precipitation satellite telemetry at station.

		DI SCHA	RGE, CUB	IC FEET PE		WATER YE Y MEAN VA		R 1991 TO	SEPTEMBE	IR 1992		
DAY	ОСТ	NOV	DEC	JAN	FEB	MAR	APR	MAY	JUN	JUL	AUG	SEP
1	17	18	22	34	6.2	5.3	4.6	6.1	26	9.9	12	21
2	138	9.3	22	13	6.4	5.8	4.4	7.5	15	9.2	13	15
3	21	6.6	56	10	6.7	5.8	4.1	4.1	13	9.2	12	17
4	14	6.4	42	9.3	7.2	6.7	3.9	3.6	69	9.0	11	14
5	12	8,1	25	289	7.2	6.3	3.8	3.6	15	13	123	13
6	10	10	21	212	16	7.4	4.9	9.8	17	11	21	18
7	8.9	120	e19	32	8.8	28	4.7	6.4	13	11	33	15
8	8.8	506	e17	20	7.7	20	4.1	5.0	13	16	21	13
9 10	46 13	107 60	e16 15	18 21	7.1	7.3	4.0 3.9	4.1	16 36	15 13	18 20	30 24
		80	15	21	7.6	6.3	3.9	7.5	36	13	20	44
11	13	34	15	16	6.7	5.9	6.0	7.2	17	22	18	13
12	11	31	17	14	7.0	5.6	24	4.7	48	11	19	11
13	10	26	14	13	6.3	5.6	6.4	3.9	39	10	18	12
14	9.1	22	13	11	11	5.7	36	17	23	11	18	12
15	11	21	e 20	10	7.6	5.8	10	12	21	11	16	12
16	9.2	19	14	9.7	7.0	5.2	5.7	50	33	11	18	15
17	12	18	12	8.9	6.3	6.7	5.0	11	35	14	19	e28
18	13	16	11	8.2	6.6	6.1	9.0	6.1	20	14	17	e17
19 20	8.9 7.7	16 16	11 11	7.7 7.5	6.1 5.9	5.3 5.1	64 25	5.0 4.4	16 14	15 14	16 19	e60 e290
21	7.3	35	11	7.3	6.0	4.8	8.8	4.2	71	31	16	e170
22	6.8	24	10	6.8	7.9	4.6	6.4	4.0	17	26	15	e44
23	6.8	39	10	7.0	6.2	5.8	5.2	152	14	14	17	e22
24	6.6	115	9.6	9.1	7.5	4.8	4.8	76	14	14	24	e 16
25	6.5	28	9.3	7.8	6.5	4.4	4.5	24	12	15	12	e14
26	6.2	39	9.3	7.6	7.8	4.4	4.3	94	12	14	13	e12
27	6.0	56	9.5	6.5	6.6	4.3	4.3	6.9	12	12	13	e11
28	5.9	31	9.1	6.4	5.9	4.0	4.1	7.9	11	10	12	e1 0
29	6.0	32	8.8	6.0	5.6	4.0	5.2	15	11	9.8	12	e1 0
30	5.9	23	10	5.9		3.8	5.9	26	10	9.0	12	e9.8
31	5.4		32	6.0		5.3		18		9.6	19	
TOTAL	463.0	1492.4	521.6	840.7	211.4	206.1	287.0	607.0	683	413.7	627	968.8
MEAN	14.9	49.7	16.8	27.1	7.29	6.65	9.57	19.6	22.8	13.3	20.2	32.3
MAX	138	506	56	289	16	28	64	152	71	31	123	290
MIN	5.4	6.4	8.8	5.9	5.6	3.8	3.8	3.6	10	9.0	11	9.8
AC-FT	918	2960	1030	1670	419	409	569	1200	1350	821	1240	1920
CFSM	2.78	9.25	3.13	5.04	1.35	1.24	1.78	3.64	4.23	2.48	3.76	6.00
IN.	3.20	10.32	3.61	5.81	1.46	1.43	1.98	4.20	4.72	2.86	4.34	6.70
e Bi	stimated											
STATIST	rics of i	MONTHLY ME	AN DATA	FOR WATER	YEARS 197	1 - 1992,	BY WATER	YEAR (WY))			
MEAN	29.2	32.9	18.4	12.8	11.0	9.69	7.22	13.6	17.9	17.1	24.9	25.8
MAX	52.6	88.9	35.2	27.1	24.5	18.9	10.8	25.1	47.1	35.4	131	81.5
(WY)	1979	1978	1978	1992	1982	1976	1976	1979	1979	1979	1979	1979
MIN	12.7	7.46	8.87	7.79	6.10	4.32	3.92	5.13	4.40	3.70	6.18	7.99
(WY)	1982	1982	1981	1981	1979	1979	1979	1974	1974	1974	1974	1980
SUMMAR	Y STATIS	rics			FOR 1	992 WATER	R YEAR			WATER Y	BARS 197	1 - 1992
LOWEST	MBAN FANNUAL ANNUAL	MEAN				21.7 20.0				18.5 36.7 12.1		1979 1977
	T DAILY				5		lov 8			2480		31 1979
	DAILY M		_				lay 4			2.2		16 1974
		AY MINIMUM	1				Apr 4			2.8		11 1974
		PEAK PLOW			30		Jan 5			6780		25 1977
		PRAK STAGE	5				Jan 5			14.8	MOV	25 1977
	RUNOFF RUNOFF				149	3.72				13410 3.4		
	RUNOFF					50.63				46.7		
	CENT EXC					32				33	•	
	CENT BXC					11				11		
	CENT BXC					5.1				5.2		
										_		

RIO MAUNABO BASIN

50091000 RIO MAUNABO AT MAUNABO, PR

WATER-QUALITY RECORDS

LOCATION.--Lat 18°00'24", long 65°54'19", at bridge on Highway 3, 0.4 mi (0.6 km) southwest of Maunabo plaza, and 1.3 mi (2.1 km) upstream from mouth.

DRAINAGE AREA. -- 12.4 mi 2 (32.1 km2).

PERIOD OF RECORD. -- Water years 1958-66, 1975 to current year.

DIS-

CHARGE, INST. CUBIC

WATER-QUALITY DATA, WATER YEAR OCTOBER 1991 TO SEPTEMBER 1992

OXYGEN,

OXYGEN

COLI-

STREP-TOCOCCI

DATE	TIME	CHARC INS' CUB: FRI PEI SECC	r. CIE IC CON ET DUC R ANG	PIC WHO I- FIE TT- (STA ER AF	ole Eld Temi Ind- att Ed Wat	PER- JRE PER 3 C)	TUR- BID- ITY (NTU)	OXYG DI SOL (NG	SOI En, (Pi S- Ci VED SAI	LVED C 3R- I 3NT (TUR- LE	MAND, HEM- CAL HIGH VEL) G/L)	FORM, FECAL 0.45 UM-MF (COLS. 100 ML	FECAL, (COLS. / PER
OCT 1991 25	1140	2	.1	320	7.2	8.5	18		7.2	92	17	2300	D K63
DRC 17	1105	0	. 98	247	7.1	23.5	3.9		8.6	101	14	54	370
FEB 1992 18	1130	11		273	7.8	24.5	19		7.7	84	<10	220	620
MAY 12	0945	4	. 3	317	6.8	25.5	7.5		8.2	95	16	310	2000
JUN 17	1135	47		190	7.0	7.0	130		6.3	70	36	K7100	43000
AUG 26	1145	4	. 5	230	7.1	29.5	12		7.0	79	14	2900	520
DATE	NE TC ()	ARD- SSS YTAL MG/L AS ACO3)	CALCIUM DIS- SOLVED (MG/L AS CA)	MAGNE- SIUM, DIS- SOLVED (MG/L AS MG)	SODIUM, DIS- SOLVED (MG/L AS NA)	SODI AL SORE TIC RATI)- ?- ON [O	POTAS- SIUM, DIS- SOLVED (MG/L AS K)	ALKA- LINITY WAT WH TOT FET FIELD MG/L AS CACO3	SULFID TOTAL (MG/L AS S)	SOL	ATB I - I VED I	CHLO- RIDE, DIS- SOLVED (MG/L AS CL)
OCT 1991 25		97	23	9.5	27	1	L	2.2	110	<0.	5 15		29
DEC 17									90		_	_	
FEB 1992 18									120		_	_	
MAY 12		90	22	8.5	27	1	L	2.4	92	<0.	5 17		36
ງບ N 17							-		60		-	-	
AUG 26		69	17	6.5	19	1	L	1.4	70		8	.1	20
	RI	.UO- IDE, OIS-	SILICA, DIS- SOLVED	SOLIDS, SUM OF CONSTI- TUENTS,	SOLIDS, DIS- SOLVED	RESID TOTAL AT 10 DEG.	5	NITRO- GEN, ITRATE	NITRO- GBN, NITRITE	NITRO GEN, NO2+NO3	GE	N,	IITRO- GEN, RGANIC
DATE	SC (N	DLVED (G/L (F)	(MG/L AS SIO2)	DIS- SOLVED (MG/L)	(TONS PER DAY)	SUS- PENDE (MG/	RD	TOTAL (MG/L AS N)	TOTAL (MG/L AS N)	TOTAL (MG/L AS N)	TOT (MG AS	AL 1	OTAL (MG/L AS N)
OCT 1991													
DEC		0.20	39	211	1.22		18	0.230	0.050	0.28			0.30
17 FEB 1992							1		<0.010	0.37	_	010	
18 MAY							28	0.410	0.010	0.420		040	
12 Jun_		0.10	39	207	2.38		12	0.850	0.110	0.960		310	0.19
AUG							48	0.320	0.060	0.380		120	0.48
26		0.10	32	151	1.83		20	0.230	0.010	0.240	0.	050	0.15

K = non-ideal count

RIO MAUNABO BASIN

50091000 RIO MAUNABO AT MAUNABO, PR--Continued

WATER-QUALITY DATA, WATER YEAR OCTOBER 1991 TO SEPTEMBER 1992

DATE	NITRO- GRN, AM- MONIA + ORGANIC TOTAL (MG/L AS N)	NITRO- GEN, TOTAL (MG/L AS N)	NITRO- GEN, TOTAL (MG/L AS NO3)	PHOS- PHORUS TOTAL (MG/L AS P)	ARSENIC TOTAL (UG/L AS AS)	BARIUM, TOTAL RECOV- ERABLE (UG/L AS BA)	BORON, TOTAL RECOV- ERABLE (UG/L AS B)	CADMIUM TOTAL RECOV- ERABLE (UG/L AS CD)	CHRO- MIUM, TOTAL RECOV- ERABLE (UG/L AS CR)	COPPER, TOTAL RECOV- ERABLE (UG/L AS CU)
ОСТ 1991										
25 DRC	1.3	1.6	7.0	0.550	<1	<100	60	<1	1	20
17 FRB 1992	<0.20			0.030						
18 MAY	<0.20			0.090						
12 JUN	0.50	1.5	6.5	0.780	<1	<100	50	<1	<1	<10
17	0.60	0.98	4.3	0.140						
26	0.20	0.44	1.9	0.070						
DATE	IRON, TOTAL RECOV- ERABLE (UG/L AS FE)	LEAD, TOTAL RECOV- ERABLE (UG/L AS PB)	MANGA- NESE, TOTAL RECOV- ERABLE (UG/L AS MN)	MERCURY TOTAL RECOV- ERABLE (UG/L AS HG)	SELE- NIUM, TOTAL (UG/L AS SE)	SILVER, TOTAL RECOV- ERABLE (UG/L AS AG)	ZINC, TOTAL RECOV- ERABLE (UG/L AS ZN)	CYANIDE TOTAL (MG/L AS CN)	PHENOLS TOTAL (UG/L)	METHY- LENE BLUE ACTIVE SUB- STANCE (MG/L)
OCT 1991 25	TOTAL RECOV- ERABLE (UG/L	TOTAL RECOV- ERABLE (UG/L	NESE, TOTAL RECOV- ERABLE (UG/L	TOTAL RECOV- ERABLE (UG/L	NIUM, TOTAL (UG/L	TOTAL RECOV- ERABLE (UG/L	TOTAL RECOV- ERABLE (UG/L	TOTAL (MG/L	TOTAL	LENE BLUE ACTIVE SUB- STANCE
OCT 1991 25 DEC 17	TOTAL RECOV- ERABLE (UG/L AS FE)	TOTAL RECOV- ERABLE (UG/L AS PB)	NESE, TOTAL RECOV- ERABLE (UG/L AS MN)	TOTAL RECOV- ERABLE (UG/L AS HG)	NIUM, TOTAL (UG/L AS SE)	TOTAL RECOV- ERABLE (UG/L AS AG)	TOTAL RECOV- ERABLE (UG/L AS ZN)	TOTAL (MG/L AS CN)	TOTAL (UG/L)	LENE BLUE ACTIVE SUB- STANCE (MG/L)
OCT 1991 25 DEC 17 FEB 1992 18	TOTAL RECOV- ERABLE (UG/L AS FE)	TOTAL RECOV- ERABLE (UG/L AS PB)	NESE, TOTAL RECOV- ERABLE (UG/L AS MN)	TOTAL RECOV- BRABLE (UG/L AS HG)	NIUM, TOTAL (UG/L AS SE)	TOTAL RECOV- ERABLE (UG/L AS AG)	TOTAL RECOV- ERABLE (UG/L AS ZN)	TOTAL (MG/L AS CN)	TOTAL (UG/L)	LENE BLUE ACTIVE SUB- STANCE (MG/L)
OCT 1991 25 DRC 17 FRB 1992 18 MAY 12	TOTAL RECOV- ERABLE (UG/L AS FE)	TOTAL RECOV- ERABLE (UG/L AS PB) <1	NESE, TOTAL RECOV- ERABLE (UG/L AS MN)	TOTAL RECOV- BRABLE (UG/L AS HG) <0.10	NIUM, TOTAL (UG/L AS SE)	TOTAL RECOV- ERABLE (UG/L AS AG)	TOTAL RECOV- ERABLE (UG/L AS ZN)	TOTAL (MG/L AS CN) <0.010	TOTAL (UG/L)	LENE BLUR ACTIVE SUB- STANCE (MG/L)
OCT 1991 25 DEC 17 PEB 1992 18	TOTAL RECOV- BRABLE (UG/L AS PE) 2200	TOTAL RECOV- ERABLE (UG/L AS PB) <1	NESE, TOTAL RECOV- ERABLE (UG/L AS MN)	TOTAL RECOV- BRABLE (UG/L AS HG) <0.10	NIUM, TOTAL (UG/L AS SE) <1	TOTAL RECOV- RRABLE (UG/L AS AG) <1	TOTAL RECOV- ERABLE (UG/L AS ZN)	TOTAL (MG/L AS CN) <0.010	TOTAL (UG/L) <1 	LENE BLUR ACTIVE SUB- STANCE (MG/L) 0.03

RIO CHICO BASIN

50091800 RIO CHICO AT PROVIDENCIA, PR

WATER-QUALITY RECORDS

LOCATION.--Lat 17°59'16", long 66°00'18", at flat low bridge 200 ft (61 m) south of Highway 3, 0.5 mi (0.8 km) above mouth, and 1.5 mi (2.4 km) southeast of Patillas plaza.

TEMPER-

PH

WATER

MHOLE

FIRLD

DRAINAGE ARRA . - - 4 . 9 mi 2 (12 . 8 km2) .

PERIOD OF RECORD. -- Water years 1979 to current year.

DIS-

SPB-

CON-

CIFIC

CHARGE,

INST.

WATER-QUALITY DATA, WATER YEAR OCTOBER 1991 TO SEPTEMBER 1992

TUR-

OXYGEN,

OXYGEN.

DIS-

SOLVED

(PBR-

OXYGEN

DEMAND,

CHEM-

ICAL

COLI-

FORM,

FECAL,

0.45

STREP-

TOCOCCI FECAL,

SECOND (US/CM) UNITS) (DEG C) (NTU) (MG/L) ATION) (MG, OCT 1991	<10 21 19 2 28 31	.00 370 90 K 64 27 290
04 1035 3.4 327 7.4 29.0 3.0 4.3 55 DBC 09 1045 0.86 370 7.7 24.5 2.1 8.9 96 FEB 1992 18 1030 1.9 396 7.5 25.5 9.5 6.6 84 APR	19 2 28 31	90 R64 27 290
09 1045 0.86 370 7.7 24.5 2.1 8.9 96 FEB 1992 18 1030 1.9 396 7.5 25.5 9.5 6.6 84 APR	28 31	27 290
APR	31	_
06 1140 0.46 519 7.0 31.0 6.5 6.4 85 JUN		
17 1030 20 238 7.2 27.5 120 6.7 87 AUG	40 K1300	
25 1030 0.67 330 7.8 26.3 3.5 7.0 89	12 2	90 200
HARD- MAGNE- SODIUM POTAS- LINITY MESS CALCIUM SIUM, SODIUM, AD- SIUM, WAT WH TOTAL DIS- DIS- BORP- DIS- TOT PET SULFIDE (MG/L SOLVED SOLVED SOLVED TION SOLVED FIELD TOTAL DATE AS (MG/L (MG/L (MG/L RATIO (MG/L MG/L AS (MG/L CACO3) AS CA) AS MG) AS NA) AS K) CACO3 AS S)	SULFATE DIS- SOLVED (MG/L AS SO4)	CHLO- RIDE, DIS- SOLVED (MG/L AS CL)
OCT 1991 04 98 23 9.9 34 1 2.6 200 <0.5	19	32
DRC 09 125 FRB 1992		
18 88 APR		
06 87 23 7.1 61 3 11 64 <0.5	42	36
17 70 AUG		5
25 94 22 9.4 30 1 2.3 100	16	29
SOLIDS, RESIDUE FLUO- SILICA, SUM OF SOLIDS, TOTAL NITRO- NITRO- RIDE, DIS- CONSTI- DIS- AT 105 GEN, GEN, GEN, DIS- SOLVED TUENTS, SOLVED DEG. C, NITRATE NITRITE NO2+NO3 SOLVED (MG/L DIS- (TONS SUS- TOTAL TOTAL TOTAL DATE (MG/L AS SOLVED PER PENDED (MG/L (MG/L AS F) SIO2) (MG/L) DAY) (MG/L) AS N) AS N) AS N)	NITRO- GEN, AMMONIA TOTAL (MG/L AS N)	NITRO- GEN, ORGANIC TOTAL (MG/L AS N)
OCT 1991 04 0.10 32 273 2.47 5 <0.010 1.10 DBC	0.040	0.36
09 14 1.38 0.020 1.40 FEB 1992	0.030	0.27
18 16 3.86 0.040 3.90 APR	0.050	1.2
06 0.10 25 274 0.34 17 9.58 0.120 9.70 JUN	0.230	4.1

230

11

0.550

1.98

0.020

0.020

0.570

2.00

0.070

0.040

1.0

0.26

K = non-ideal count

0.20

31

206

0.37

AUG 25...

RIO CHICO BASIN

50091800 RIO CHICO AT PROVIDENCIA, PR--Continued WATER-QUALITY DATA, WATER YEAR OCTOBER 1991 TO SEPTEMBER 1992

DATE	NITRO- GEN, AM- MONIA + ORGANIC TOTAL (MG/L AS N)	NITRO- GEN, TOTAL (MG/L AS N)	NITRO- GEN, TOTAL (MG/L AS NO3)	PHOS- PHORUS TOTAL (MG/L AS P)	ARSENIC TOTAL (UG/L AS AS)	BARIUM, TOTAL RECOV- ERABLE (UG/L AS BA)	BORON, TOTAL RECOV- ERABLE (UG/L AS B)	CADMIUM TOTAL RECOV- ERABLE (UG/L AS CD)	CHRO- MIUM, TOTAL RECOV- ERABLE (UG/L AS CR)	COPPER, TOTAL RECOV- ERABLE (UG/L AS CU)
OCT 1991										
04	0.40	1.5	6.6	0.830	<1	<100		<1	<1	<10
DEC										
09 FRB 1992	0.30	1.7	7.5	1.20						
18	1.3	5.2	23	3.40						
APR 06	4.3	14	62	8.70	1	<100	150	<1	<1	10
JUN					_			-		
17 A UG	1.1	1.7	7.4	0.440						
25	0.30	2.3	10	0.810						
DATE	IRON, TOTAL RECOV- BRABLR (UG/L AS FE)	LEAD, TOTAL RECOV- ERABLE (UG/L AS PB)	MANGA- NESE, TOTAL RECOV- ERABLE (UG/L AS MN)	MERCURY TOTAL RECOV- ERABLE (UG/L AS HG)	SELE- NIUM, TOTAL (UG/L AS SE)	SILVER, TOTAL RECOV- ERABLE (UG/L AS AG)	ZINC, TOTAL RECOV- ERABLE (UG/L AS ZN)	CYANIDE TOTAL (MG/L AS CN)	PHENOLS TOTAL (UG/L)	MRTHY- LENE BLUE ACTIVE SUB- STANCE (MG/L)
DATE OCT 1991	TOTAL RECOV- BRABLE (UG/L AS FE)	TOTAL RECOV- BRABLE (UG/L	NESE, TOTAL RECOV- ERABLE (UG/L	TOTAL RECOV- ERABLE (UG/L AS HG)	NIUM, TOTAL (UG/L	TOTAL RECOV- RRABLE (UG/L	TOTAL RECOV- ERABLE (UG/L	TOTAL (MG/L AS CN)	TOTAL	LENE BLUE ACTIVE SUB- STANCE (MG/L)
OCT 1991 04	TOTAL RECOV- ERABLE (UG/L	TOTAL RECOV- BRABLE (UG/L	NESE, TOTAL RECOV- ERABLE (UG/L	TOTAL RECOV- RRABLE (UG/L	NIUM, TOTAL (UG/L	TOTAL RECOV- RRABLE (UG/L	TOTAL RECOV- ERABLE (UG/L	TOTAL (MG/L	TOTAL	LENE BLUE ACTIVE SUB- STANCE
OCT 1991 04	TOTAL RECOV- BRABLE (UG/L AS FE)	TOTAL RECOV- ERABLE (UG/L AS PB)	NESE, TOTAL RECOV- ERABLE (UG/L AS MN)	TOTAL RECOV- ERABLE (UG/L AS HG)	NIUM, TOTAL (UG/L AS SE)	TOTAL RECOV- ERABLE (UG/L AS AG)	TOTAL RECOV- ERABLE (UG/L AS ZN)	TOTAL (MG/L AS CN)	TOTAL (UG/L)	LENE BLUE ACTIVE SUB- STANCE (MG/L)
OCT 1991 04	TOTAL RECOV- BRABLE (UG/L AS FE)	TOTAL RECOV- ERABLE (UG/L AS PB)	NESE, TOTAL RECOV- ERABLE (UG/L AS MN)	TOTAL RECOV- ERABLE (UG/L AS HG)	NIUM, TOTAL (UG/L AS SE)	TOTAL RECOV- ERABLE (UG/L AS AG)	TOTAL RECOV- ERABLE (UG/L AS ZN)	TOTAL (MG/L AS CN)	TOTAL (UG/L)	LENE BLUE ACTIVE SUB- STANCE (MG/L)
OCT 1991 04 DEC 09 FEB 1992 18	TOTAL RECOV- BRABLE (UG/L AS FE)	TOTAL RECOV- ERABLE (UG/L AS PB)	NESE, TOTAL RECOV- ERABLE (UG/L AS MN)	TOTAL RECOV- ERABLE (UG/L AS HG)	NIUM, TOTAL (UG/L AS SE)	TOTAL RECOV- ERABLE (UG/L AS AG)	TOTAL RECOV- ERABLE (UG/L AS ZN)	TOTAL (MG/L AS CN)	TOTAL (UG/L)	LENE BLUE ACTIVE SUB- STANCE (MG/L)
OCT 1991 04 DEC 09 FEB 1992 18 APR 06	TOTAL RECOV- ERABLE (UG/L AS FR)	TOTAL RECOV- ERABLE (UG/L AS PB)	NESE, TOTAL RECOV- ERABLE (UG/L AS MN)	TOTAL RECOV- ERABLE (UG/L AS HG) <0.10	NIUM, TOTAL (UG/L AS SE)	TOTAL RECOV- RRABLE (UG/L AS AG) <1	TOTAL RECOV- ERABLE (UG/L AS ZN)	TOTAL (MG/L AS CN) <0.010	TOTAL (UG/L)	LENE BLUE ACTIVE SUB- STANCE (MG/L)
OCT 1991 04 DEC 09 FEB 1992 18	TOTAL RECOV- BRABLR (UG/L AS FR) 200	TOTAL RECOV- ERABLE (UG/L AS PB)	NESE, TOTAL RECOV- ERABLE (UG/L AS MN)	TOTAL RECOV- BRABLE (UG/L AS HG)	NIUM, TOTAL (UG/L AS SR)	TOTAL RECOV- RRABLE (UG/L AS AG)	TOTAL RECOV- ERABLE (UG/L AS ZN)	TOTAL (MG/L AS CN) <0.010	TOTAL (UG/L) <1 	LENE BLUE SUB- STANCE (MG/L)

RIO GRANDE DE PATILLAS BASIN

50092000 RIO GRANDE DE PATILLAS NEAR PATILLAS, PR--Continued (National stream-quality accounting network station)

LOCATION.--Lat 18°02'04", long 66°01'58", Hydrologic Unit 21010004, on left bank, at foot bridge, off Highway 184, 1.2 mi (1.9 km) upstream from Lago Patillas Dam and 2.2 mi (3.5 km) northwest of Patillas.

DRAINAGE ARRA. -- 18.3 mi 2 (47.4 km2).

WATER-QUALITY RECORDS

PERIOD OF RECORD. -- Water years 1960 to current year.

WATER-QUALITY DATA, WATER YEAR OCTOBER 1991 TO SEPTEMBER 1992

DATE	TIME	DIS- CHARGE, INST. CUBIC FEET PER SECOND	SPE- CIFIC CON- DUCT- ANCE (US/CM)	PH WATER WHOLE FIELD (STAND- ARD UNITS)	TEMPER- ATURE WATER (DEG C)	TUR- BID- ITY (NTU)	OXYGEN, DIS- SOLVED (MG/L)	OXYGEN, DIS- SOLVED (PER- CENT SATUR- ATION)	COLI- FORM, FECAL, 0.45 UM-MF (COLS./ 100 ML)	STREP- TOCOCCI FECAL, (COLS. PER 100 ML)	HARD- NESS TOTAL (MG/L AS CACO3)
OCT 1991											
03	1000	72	150	7.0	25.0	5.3	8.4	92	K1400	29000	42
JAN 1992											
28 APR	1050	33	185	7.5	27.0	1.4	8.9	101	490	K170	58
16	0950	9.7	165	7.1	23.5	1.5	8.5	99	K870	2200	53
JUL	4324		203		45.5	2.5	0.5				
13	1045	31	165	6.7	26.5	1.0	7.8	88	460	500	49
DATE	CALCIUM DIS- SOLVED (MG/L AS CA)	MAGNE- SIUM, DIS- SOLVED (MG/L AS MG)	SODIUM, DIS- SOLVED (MG/L AS NA)	SODIUM AD- SORP- TION RATIO	POTAS- SIUM, DIS- SOLVED (MG/L AS K)	ALKA- LINITY WAT WH TOT FET FIBLD MG/L AS CACO3	SULFATE DIS- SOLVED (MG/L AS SO4)	CHLO- RIDE, DIS- SOLVED (MG/L AS CL)	FLUO- RIDE, DIS- SOLVED (MG/L AS F)	SILICA, DIS- SOLVED (MG/L AS SIO2)	SOLIDS, RESIDUE AT 180 DEG. C DIS- SOLVED (MG/L)
03	10	4.1	13	0.9	1.0	40	9.1	12	0.10	22	110
JAN 1992	20	4.1	13	0.7	2.0	•	J. 1		0.10		110
28	14	5.5	15	0.9	0.80	54	10	13	0.20	21	100
APR	4.0						40	4-		4.0	0.0
16 JUL	13	5.0	14	0.8	0.80	50	12	15	0.20	19	97
13	12	4.7	13	0.8	0.60	64	11	13	<0.10	23	117
DATE	SOLIDS, SUM OF CONSTI- TUENTS, DIS- SOLVED (MG/L)	SOLIDS, DIS- SOLVED (TONS PER DAY)	NITRO- GEN, NO2+NO3 DIS- SOLVED (MG/L AS N)	NITRO- GEN, AMMONIA DIS- SOLVED (MG/L AS N)	NITRO- GEN, AMMONIA DIS- SOLVED (MG/L AS NH4)	NITRO- GEN, AM- MONIA + ORGANIC TOTAL (MG/L AS N)	PHOS- PHORUS TOTAL (MG/L AS P)	PHOS- PHORUS DIS- SOLVED (MG/L AS P)	PHOS- PHORUS ORTHO, DIS- SOLVED (MG/L AS P)	PHOS- PHATE, ORTHO, DIS- SOLVED (MG/L AS PO4)	ALUM- INUM, DIS- SOLVED (UG/L AS AL)
OCT 1991											
03 JAN 1992	97	21.3	0.360	0.120	0.15	0.90	0.020	0.030	0.030	0.09	80
28	112	8.94	<0.050	0.030	0.04	0.20	0.010	0.010	0.020	0.06	20
APR		2.54	10000	5.550	0.54					2.30	30
16	110	27.7	0.190	0.010	0.01	<0.20	<0.010	<0.010	0.020	0.06	20
JUL 13	117	9.63	0.190	0.030	0.04	40.20	<0.010	<0.010	0.020	0.06	<10
13	117	7.03	0.130	0.030	0.04	<0.20	<0.010	<0.010	0.020	0.06	<10

K = non-ideal count

RIO GRANDE DE PATILLAS BASIN

50092000 RIO GRANDE DE PATILLAS NEAR PATILLAS, PR--Continued (National stream-quality accounting network station)

WATER-QUALITY DATA, WATER YEAR OCTOBER 1991 TO SEPTEMBER 1992

DATE	BARIUM, DIS- SOLVED (UG/L AS BA)	COBALT, DIS- SOLVED (UG/L AS CO)	IRON, DIS- SOLVED (UG/L AS FE)	LITHIUM DIS- SOLVED (UG/L AS LI)	MANGA- NESE, DIS- SOLVED (UG/L AS MN)	MOLYB- DENUM, DIS- SOLVED (UG/L AS MO)	NICKEL, DIS- SOLVED (UG/L AS NI)	SELE- NIUM, DIS- SOLVED (UG/L AS SE)	SILVER, DIS- SOLVED (UG/L AS AG)	STRON- TIUM, DIS- SOLVED (UG/L AS SR)	VANA- DIUM, DIS- SOLVED (UG/L AS V)
OCT 1991											
03	11	<3	81	<4	11	<10	2	<1	<1.0	36	<6
JAN 1992 28	15	<3	28	<4	34	<10	2	<1	<1.0	51	<6
APR 16	13	<3	19	<4	13	<10	<1	<1	<1.0	45	<6
JUL 13	13	<3	14	<4	7	<10	<1	<1	<1.0	42	< 6

PARTICLE-SIZE DISTRIBUTION OF SUSPENDED SEDIMENT

DATE	TIMR	STREAM- FLOW, INSTAN- TANEOUS	SEDI- MENT, SUS- PENDED	SEDI- MENT, DIS- CHARGE, SUS- PENDED	SED. SUSP. SIEVE DIAM. PERCENT FINER THAN
		(CFS)	(MG/L)	(T/DAY)	.062 MM
OCT 1991					
03	1000	72	322	62	99
JAN 1992					
28	1050	33	34	3.02	88
APR					
16	0950	9.67	26	0.68	98
JOL					
13	1045	31	11.8	0.99	86

THIS PAGE WAS LEFT BLANK INTENTIONALLY




Figure 23:-South coast river basins the Río Salinas to Río Jacaguas basins.

50100200 RIO LAPA NEAR RABO DEL BUEY, PR

LOCATION.--Lat 18°03'36", long 66°14'28", Hydrologic Unit 21010004, on left bank, at bridge on Highway 1, Km 9.7, 1.5 mi (2.4 km) north of Rabo del Buey, and 4.4 mi (7.1 km) northeast of Salinas Plaza.

DRAINAGE AREA .-- 9.92 mi 2 (25.69 km2).

WATER-DISCHARGE RECORDS

PERIOD OF RECORD.--1953-63 (annual low-flow measurements only), September 1988 to current year.

GAGE.--Water-stage recorder and crest-stage gage. Elevation of gage is 394 ft (120 m), from topographic map.

REMARKS.--Records fair.

		DISCHA	RGE, CUB	IC FEET PER		WATER YE MEAN VA		R 1991 TO	SEPTEMBI	R 1992		
DAY	OCT	NOV	DEC	JAN	FEB	MAR	APR	MAY	JUN	JUL	AUG	SEP
1	. 87	1.2	1.0	1.4	2.5	2.5	1.7	2.5	11	3.9	1.3	1.5
2	.94	1.3	.98	1.4	3.1	2.5	2.5	2.1	10	3.8	1.4	1.4
3	.93	. 98	.96	1.4	2.7	2.8	2.0	1.8	9.0	3.6	1.4	1.3
4	.91	. 84	1.0	1.4	1.7	2.8	1.9	1.9	8.1	3.4	1.3	1.2
S	.81	. 83	.95	1080	1.9	2.8	1.8	1.8	7.5	3.2	50	1.3
6	.83	. 83	.94	517 171	3.1	2.6	1.8	2.9	7.1	3.1	7.0	1.2
8	1.4	11	.95	98	2.5	1.7	1.9	1.6	6.2	3.2	2.9	1.1
9	1.4	2.7	.90	56	2.5	1.6	2.0	1.4	5.8	3.0	2.6	1.1
10	1.1	1.3	.86	42	2.5	1.9	1.9	1.4	5.3	2.9	2.5	1.1
11	1.0	. 90	.78	26	2.6	2.2	1.7	1.2	7.4	3.0	2.5	.99
12 13	.93	.76	.77	13	2.5	2.1	2.1	1.2	6.8	3.0 2.9	2.5	.97
14	.88	.74	.76	9.3	2.4	2.1 1.9	1.9	9.6	6.7	2.9	2.1	.94
15	.84	. 65	.78	12	2.4	1.9	2.2	3.3	6.4	2.6	2.1	.90
16	.84	.61	.80	10	2.7	1.7	2.3	2.1	6.4	3.0	2.1	.85
17	.83	. 63	.80	8.6	2.4	1.7	1.6	1.9	5.9	2.7	2.0	.88
18	.84	. 69	.81	10	2.2	1.8	1.3	1.7	5.8	2.5	1.9	. 84
19	.86	. 64	.82	11	2.4	2.2	3.1	1.4	6.0	2.3	1.9	. 88
20	6.2	. 65	.88	9.2	2.2	2.1	26	1.3	5.7	1.9	1.9	4.1
21	1.6	.69	.97	7.7	2.5	2.6	5.8	1.4	6.0	2.0	1.7	3.5
22	9.4	.79	.95	7.1	2.5	2.4	3.3	1.3	5.4	2.1	1.7	2.3
23	1.1	.78	1.0	5.7	2.7	1.8	2.3	76	5.1	1.9	1.8	1.9
24 25	.82	. 97	1.0	3.9	2.2	1.7	2.2	113	4.8	2.0	1.7	1.7
	.82	1.0	1.0	2.8	2.2	1.8	2.4	60	4.7	1.8	1.6	1.6
26	.80	1.1	1.0	3.3	2.3	1.6	2.6	760	4.7	1.7	1.6	1.6
27 28	.75	1.3	1.1	3.2	2.5	1.6	2.5	26 15	4.5	1.6	1.5	1.5
29	1.3	1.2	1.3	3.3 2.9	2.5	1.5	2.6	13	4.2	1.6	1.5	1.4
30	2.2	1.1	1.3	2.2	2.5	1.6	2.6	12	4.0	1.5	1.5	1.5
31	1.3		1.4	1.9		3.2		12		1.4	1.5	
TOTAL	45.27	65.19	29.70	2133.7	73.4	64.5	92.2	1133.8	189.6	79.2	112.7	43.13
WEAN	1.46	2.17	.96	68.8	2.53	2.08	3.07	36.6	6.32	2.55	3.64	1.44
MAX	9.4	27	1.4	1080	3.6	3.2	26	760	11	3.9	50	4.1
MIN	.75	. 61	.76	1.4	1.7	1.5	1.3	1.0	4.0	1.4	1.3	. 84
AC-FT CFSM	90	129	59	4230	146	128	183	2250	376	157	224	86
IN.	.15	.22	.10	6.88 7.94	.25	.21	.31	4.22	.63	.26	.36	.14
												.10
STATIS	TICS OF E	MONTHLY ME	AN DATA	FOR WATER YI	BARS 1988	- 1992,	BY WATER	YEAR (WY)				
MEAN	23.3	9.32	2.50	18.6	4.24	1.25	1.16	9.64	2.05	.99	2.62	10.3
MAX	76.1	28.4	6.09	68.8	12.4	2.08	3.07	36.6	6.32	2.55	6.06	29.1
(WY)	1991	1991	1991	1992	1991	1992	1992	1992	1992	1992	1990	1989
MIN (WY)	1.46	2.17 1992	.96 1992	.56 1990	.49 1990	1990	.28 1990	.18 1990	.46 1989	. 14 1989	.18 1989	.82 1991
CTTMM A D	Y STATIST	RT CO	POP	1991 CALENI	DID VEID	P	OR 1992 W	AMPD VPAD		WATER YE	1DC 1000	_ 1002
			FOR		JAMES ALLER	F				WALLES IN	1,36	
ANNUAL				820.56 2.25			4062.3			7.20		
	T ANNUAL	MRAN		2.23			11.1			11.2		1991
	ANNUAL P									3.13		1990
	T DAILY N			74	Feb 12		1080	Jan 5		1000	Ton	5 1992
LOWEST	DAILY ME	RAN .		.16	Feb 12 Jul 23		. 6	Jan 5 1 Nov 16		.02	Aug	29 1989
		MUMINIM Y		.19	Jul 21		. 6	5 Nov 15		.07	Aug	24 1989
		PRAK FLOW					15700			15700		5 1992
	TANEOUS I	PEAK STAGE					17.8	2 Jan 5 8 Nov 20		17.82	Jan	5 1992
	RUNOFF			1630			8060	0 MOV 20		5210		
	RUNOFF			.22			1.1	1		.72		
	RUNOFF			3.05			15.1			9.78		
	CENT EXCE			3.4			7.8			11		
	CENT EXCE			1.0			1.9			1.3		
JU PER	CAMI BACE	SU S		.37			. 8	u		.21		

RIO SALINAS BASIN

383

50100450 RIO MAJADA AT LA PLENA, PR

LOCATION.--Lat 18°02'40", long 66°12'27", Hydrologic Unit 21010004, on right bank, upstream side of bridge on Hwy 712, about 0.3 mi (0.5 km) southwest of La Plena.

DRAINAGE AREA. -- 16.7 mi 2 (43.3 km2).

WATER-DISCHARGE RECORDS

PERIOD OF RECORD. -- September 1988 to current year.

GAGE.--Water-stage recorder. Elevation of gage is 410 ft (125 m), from topographic map.

REMARKS.-Records fair except those for estimated daily discharges, which are poor. Some regulation at low flow upstream from station by local residents for agricultural purposes.

11011	station	-		s for agric	_	_						
		DISCHA	RGB, CUB	IC FEET PE		WATER YE MEAN VA		R 1991 TO	SEPTEMBE	R 1992		
DAY	OCT	NOV	DEC	JAN	FRB	MAR	APR	MAY	JUN	JUL	AUG	SEP
1	2.6	1.6	2.3	2.1	3.3	2.4	4.8	2.5	17	5.6	3.4	4.1
2	2.6	1.1	2.7	2.4	3.2	2.3	7.0	2.8	16	5.5	3.5	3.9
3 4	2.8 2.0	. 97 . 85	2.8	2.2	3.3	2.3	3.9	2.3	16	5.3	4.5 3.5	5.1
5	1.6	. 91	5.4 4.6	1.9 e1520	3.4 3.2	2.2 2.3	2.5 2.1	1.9 1.6	15 14	5.0 5.8	77	3.4 3.1
6	1.4	. 90	3.3	e450	4.6	2.3	2.1	2.0	13	5.0	31	3.0
7	1.3	25	2.6	18	4.8	2.2	2.4	2.6	13	4.7	12	3.2
8	1.3	32	2.3	12	4.1	2.5	2.6	2.2	13	4.8	7.2	3.0
9 10	1.5 2.7	21 6.3	1.9 1.8	9.7 7.8	3.5 3.5	2.5 2.4	2.4 2.4	1.8 1.6	12 13	5.2 4.9	5.8 5.4	3.5 3.1
11 12	1.8 1.4	3.3 2.3	1.6 1.5	7.0 7.7	3.4 3.2	2.2 2.3	2.4 5.2	1.7 1.8	14 21	5.6 5.3	5.4 5.5	2.3 2.2
13	1.2	1.8	1.5	7.3	3.1	2.2	5.2	1.5	18	4.5	4.9	2.3
14	.97	1.4	1.3	5.7	3.0	2.1	4.0	6.8	16	4.1	4.8	2.1
15	.98	1.1	1.3	5.5	3.1	2.4	5.4	11	13	4.2	5.1	1.8
16	1.0	.90	1.4	5.4	3.0	2.3	3.3	3.3	11	8.1	4.5	2.0
17	.94	. 97	1.2	5.3	2.7	2.3	2.4	2.5	11	6.2	4.3	3.1
18 19	.94 .95	.88 .78	.88 .80	5.1 5.1	2.8 2.7	2.6 2.7	2.2 3.0	1.9 1.7	9.9 9.1	5.2 4.6	4.0 3.9	2.8 2.8
20	.97	.79	. 85	4.9	2.4	2.9	16	1.7	8.6	4.3	4.3	67
21	1.1	.70	1.8	4.8	2.4	2.8	8.3	1.7	17	4.2	3.7	48
22	.88	. 87	1.2	4.6	2.3	2.8	3.5	1.6	12	4.5	3.4	22
23 24	.77 .85	.98	.95 .95	4.6	2.4	2.7	2.6	32	9.7 8.7	4.5 4.2	3.2 3.2	14 10
25	.94	2.7 3.1	1.0	4.9 4.7	2.6 2.9	2.9 3.1	2.3 2.1	56 31	7.9	4.0	3.2	7.9
26	. 85	1.9	. 93	4.6	2.9	3.1	2.0	496	7.3	3.9	3.5	7.0
27	.84	3.2	.91	4.1	2.9	3.2	2.1	31	6.9	3.8	3.8	6.8
28	.75	4.5	.96	4.0	2.9	3.3	2.0	25	6.6	3.7	3.5	6.0
29 30	.69 1.9	4.1 3.3	1.0 .98	3.9 3.6	2.6	3.1 3.1	1.9 2.6	22 20	6.3 5.7	3.6 3.6	5.3 3.5	4.7 5.0
31	3.7		1.2	3.4		3.4		18		3.4	3.6	
TOTAL	44.22	130.20	53.91	2132.3	90.2	80.9	110.7	789.5	361.7	147.3	239.9	255.2
MBAN	1.43	4.34	1.74	68.8	3.11	2.61	3.69	25.5	12.1	4.75	7.74	8.51
MAX	3.7	32	5.4	1520	4.8	3.4	16	496	21	8.1	77	67
MIN AC-FT	. 69 88	.70 258	.80 107	1.9 4230	2.3 179	2.1 160	1.9 220	1.5 1570	5.7 717	3.4 292	3.2 476	1.8 506
CFSM	.09	.26	.10	4.12	.19	. 16	.22	1.53	.72	.28	.46	.51
IN.	.10	.29	.12	4.75	.20	. 18	.25	1.76	.81	. 33	.53	.57
e Ra	stimated											
STATIST	TICS OF	MONTHT.Y MR	AN DATA	FOR WATER	VRADG 1989	- 1992.	RY WATER	VRAR (WV	``			
						-	,	•	-			
MBAN MAX	22.3 76.4	10.4 25.2	4.17	19.5 68.8	4.83 12.1	2.36 3.92	1.97 3.69	7.33 25.5	3.79 12.1	2.12 4.75	2.96 7.74	11.6 30.1
(WY)	1991	1991	1991	1992	1991	1991	1992	1992	1992	1992	1992	1989
MIN	1.43	2.15	1.22	. 98	.63	. 59	.58	. 25	.53	. 62	.73	1.50
(WY)	1992	1990	1990	1990	1990	1990	1990	1990	1990	1989	1989	1991
SUMMARY	Y STATIS	TICS	FOR	1991 CALE	NDAR YEAR	F	OR 1992 W	ATER YEAR		WATER Y	EARS 1989	- 1992
ANNUAL				1186.8	-		4436.0					
ANNUAL	MKAN T ANNUA L	MPAN		3.2	5		12.1			7.8 12.1		1992
	ANNUAL									1.6		1990
HI GHRS'	T DAILY	MBYN		57	Feb 12		1520	Jan 5		1520	Jan	5 1992
	DAILY M		_		6 Aug 20			9 Oct 29		.0		4 1990
		AY MINIMUM PRAK FLOW		. 6	1 Sep 1		.8: 15200	1 Oct 23 Jan 5		.0 15200		4 1990 5 1992
		PBAK STAGE						9 Jan 5		17.1		5 1992
ANNUAL	runoff	(AC-FT)		2350			8800			5660		
	RUNOFF			.1			.7			.4		
	RUNOFF CENT EXC			2.6 5.5			9.8 13	•		6.3 11		
	CENT EXC			1.8			3.2			2.2		
	CENT EXC			.7			1.0			.4		

384 RIO COAMO BASIN

50106500 RIO COAMO NEAR COAMO, PR

WATER-QUALITY RECORDS

LOCATION.--Lat 18°03'52", long 66°22'10", Hydrologic Unit 21010004, on Highway 153 bridge, 0.4 mi (0.6 km) above Río de la Mina, and 1.8 mi (2.9 km) south of Coamo plaza.

DRAINAGE AREA. -- 46.0 mi2 (119.1 km2).

PERIOD OF RECORD. -- Water years 1978 to current year.

WATER-QUALITY RECORDS, WATER YEAR OCTOBER 1991 TO SEPTEMBER 1992

	WATER-	QUALITY R	LECORDS, W	ATER YEAR	OCTOBER	1991 TO	Sept em ber	1992		
DATE	TIME	DIS- CHARGE, INST. CUBIC FEET PER SECOND	SPE- CIFIC COM- DUCT- ANCE (US/CM)	PH WATER WHOLE FIELD (STAND- ARD UNITS)	TEMPER- ATURE WATER (DEG C)	TUR- BID- ITY (NTU)	(MG/L)	OXYGEN, DIS- SOLVED (PER- CENT SATUR- ATION)	OXYGEN DRMAND, CHEM- ICAL (HIGH LEVEL) (MG/L)	COLI- FORM, FECAL, 0.45 UM-MF (COLS./ 100 ML)
OCT 1991										
03 JAN 1992	1445	7.1	700	8.0	31.0	2.6	5.3	70	31	2100
02	1205	4.9	637	7.1	26.0	4.2	8.9	102	13	590
PEB 18	0820	12	680	7.3	25.0	1.3	4.9	68	10	270
MAY										
07 JUN	1300	10	652	7.0	31.5	1.3	6.1	80	25	30000
23	1330	9.3	630	7.0	32.5	1.5	10.7	116	20	2100
AUG 27	1200	8.7	688	7.7	32.0	1.0	8.4	96	<10	2600
DATE	STREP- TOCOCCI FECAL, (COLS. PER 100 ML)	HARD- NESS TOTAL (MG/L AS CACO3)	CALCIUM DIS- SOLVED (MG/L AS CA)	MAGNE- SIUM, DIS- SOLVED (MG/L AS MG)	SODIUM, DIS- SOLVED (MG/L AS NA)	SODIUM AD- SORP- TION RATIO	POTAS- SIUM, DIS- SOLVED (MG/L AS K)	ALKA- LINITY WAT WH TOT FET FIELD MG/L AS CACO3	SULFATE DIS- SOLVED (MG/L AS SO4)	CHLO- RIDE, DIS- SOLVED (MG/L AS CL)
OCT 1991 03	K160	260	69	21	46	1	5.6	270	37	56
JAN 1992	KIGO	200	63	21	40	-	3.0	2/0	3,	30
02 PEB	710							180		
18	290							260		
MAY 07	500	250	70	19	38	1	4.5	210	45	52
JUN										
23 AUG	20							240		
27	310	260	68	21	40	1	4.1	220	54	49
DATE	FLUO- RIDE, DIS- SOLVED (MG/L AS F)	SILICA, DIS- SOLVED (MG/L AS SIO2)	SOLIDS, SUM OF CONSTI- TUENTS, DIS- SOLVED (MG/L)	SOLIDS, DIS- SOLVED (TONS PER DAY)	RESIDUE TOTAL AT 105 DEG. C, SUS- PENDED (MG/L)	NITRO- GEN, NITRATE TOTAL (MG/L AS N)	NITRO- GEN, NITRITE TOTAL (MG/L AS N)	NITRO- GEN, NO2+NO3 TOTAL (MG/L AS N)	NITRO- GRN, AMMONIA TOTAL (MG/L AS N)	NITRO- GEN, ORGANIC TOTAL (MG/L AS N)
OCT 1991										
03 J an 1992	0.20	29	426	8.16	5	0.550	0.650	1.20	4.30	1.4
02					5	0.980	0.720	1.70	1.00	0.70
FRB 18					6	0.870	0.230	1.10	1.10	0.50
MAY 07	0.20	26	381	10.3	<1	0.820	0.680	1.50	1.20	0.60
JUN 23					10	2.01	0.190	2.20	0.800	0.90
AUG	,0 10	28	408	0.50	8	1.26	0.340	1.60	0.610	0.59
27	<0.10	28	408	9.58	8	1.46	U.34U	1.60	0.610	0.59
W - non-id	est count									

K = non-ideal count

50106500 RIO COAMO NEAR COAMO, PR--Continued

WATER-QUALITY RECORDS, WATER YEAR OCTOBER 1991 TO SEPTEMBER 1992

DATE	NITRO- GEN, AM- MONIA + ORGANIC TOTAL (MG/L AS N)	NITRO- GEN, TOTAL (MG/L AS N)	NITRO- GEN, TOTAL (MG/L AS NO3)	PHOS- PHORUS TOTAL (MG/L AS P)	ARSENIC TOTAL (UG/L AS AS)	BARIUM, TOTAL RECOV- ERABLE (UG/L AS BA)	BORON, TOTAL RECOV- ERABLE (UG/L AS B)	CADMIUM TOTAL RECOV- ERABLE (UG/L AS CD)	CHRO- MIUM, TOTAL RECOV- ERABLE (UG/L AS CR)	COPPER, TOTAL RECOV- ERABLE (UG/L AS CU)
OCT 1991										
03	5.7	6.9	31	1.20	1	<100		<1	<1	10
JAN 1992	1.7		15	0.500						
02 FBB	1.7	3.4	15	0.590						
18 MAY	1.6	2.7	12	0.440			, 			
07	1.8	3.3	15	0.550	1	100	100	<1	<1	<10
JUN 23	1.7	3.9	17	0.500						
AUG	1.7	3.9	17	0.500						
27	1.2	2.8	12	0.420						
DATE	IRON, TOTAL RECOV- ERABLE (UG/L AS FE)	LEAD, TOTAL RECOV- BRABLE (UG/L AS PB)	MANGA- NESE, TOTAL RECOV- ERABLE (UG/L AS MN)	MERCURY TOTAL RECOV- ERABLE (UG/L AS HG)	SELE- NIUM, TOTAL (UG/L AS SE)	SILVER, TOTAL RECOV- ERABLE (UG/L AS AG)	ZINC, TOTAL RECOV- BRABLE (UG/L AS ZN)	CYANIDE TOTAL (MG/L AS CN)	PHENOLS TOTAL (UG/L)	METHY- LENE BLUE ACTIVE SUB- STANCE (MG/L)
OCT 1991	TOTAL RECOV- ERABLE (UG/L AS FE)	TOTAL RECOV- ERABLE (UG/L AS PB)	NESE, TOTAL RECOV- BRABLE (UG/L AS MN)	TOTAL RECOV- ERABLE (UG/L AS HG)	NIUM, TOTAL (UG/L AS SE)	TOTAL RECOV- ERABLE (UG/L AS AG)	TOTAL RECOV- ERABLE (UG/L AS ZN)	TOTAL (MG/L AS CN)	TOTAL (UG/L)	LENE BLUE ACTIVE SUB- STANCE (MG/L)
ОСТ 1991 03	TOTAL RECOV- ERABLE (UG/L	TOTAL RECOV- BRABLE (UG/L	NESE, TOTAL RECOV- ERABLE (UG/L	TOTAL RECOV- BRABLE (UG/L	NIUM, TOTAL (UG/L	TOTAL RECOV- ERABLE (UG/L	TOTAL RECOV- BRABLE (UG/L	TOTAL (MG/L	TOTAL	LENE BLUE ACTIVE SUB- STANCE
OCT 1991	TOTAL RECOV- ERABLE (UG/L AS FE)	TOTAL RECOV- ERABLE (UG/L AS PB)	NESE, TOTAL RECOV- BRABLE (UG/L AS MN)	TOTAL RECOV- ERABLE (UG/L AS HG)	NIUM, TOTAL (UG/L AS SE)	TOTAL RECOV- ERABLE (UG/L AS AG)	TOTAL RECOV- ERABLE (UG/L AS ZN)	TOTAL (MG/L AS CN)	TOTAL (UG/L)	LENE BLUE ACTIVE SUB- STANCE (MG/L)
OCT 1991 03 JAN 1992 02 FEB	TOTAL RECOV- ERABLE (UG/L AS FE)	TOTAL RECOV- BRABLE (UG/L AS PB)	NESE, TOTAL RECOV- BRABLE (UG/L AS MN)	TOTAL RECOV- BRABLE (UG/L AS HG) <0.10	NIUM, TOTAL (UG/L AS SE)	TOTAL RECOV- ERABLE (UG/L AS AG)	TOTAL RECOV- ERABLE (UG/L AS ZN)	TOTAL (MG/L AS CN)	TOTAL (UG/L)	LENE BLUE ACTIVE SUB- STANCE (MG/L)
OCT 1991 03 JAN 1992 02 FEB 18	TOTAL RECOV- ERABLE (UG/L AS FE)	TOTAL RECOV- ERABLE (UG/L AS PB)	NESE, TOTAL RECOV- ERABLE (UG/L AS MN)	TOTAL RECOV- BRABLE (UG/L AS HG)	NIUM, TOTAL (UG/L AS SE)	TOTAL RECOV- ERABLE (UG/L AS AG)	TOTAL RECOV- ERABLE (UG/L AS ZN)	TOTAL (MG/L AS CN)	TOTAL (UG/L)	LENE BLUE ACTIVE SUB- STANCE (MG/L)
OCT 1991 03 JAN 1992 02 FEB 18 MAY 07	TOTAL RECOV- ERABLE (UG/L AS FE)	TOTAL RECOV- BRABLE (UG/L AS PB)	NESE, TOTAL RECOV- BRABLE (UG/L AS MN)	TOTAL RECOV- BRABLE (UG/L AS HG) <0.10	NIUM, TOTAL (UG/L AS SE)	TOTAL RECOV- ERABLE (UG/L AS AG) <1	TOTAL RECOV- ERABLE (UG/L AS ZN)	TOTAL (MG/L AS CN) <0.010	TOTAL (UG/L) <1	LENE BLUR ACTIVE SUB- STANCE (MG/L)
OCT 1991 03 JAN 1992 02 FEB 18	TOTAL RECOV- BRABLE (UG/L AS FE) 170	TOTAL RECOV- BRABLE (UG/L AS PB)	NESE, TOTAL RECOV- BRABLE (UG/L AS MN)	TOTAL RECOV- BRABLE (UG/L AS HG)	NIUM, TOTAL (UG/L AS SE)	TOTAL RECOV- BRABLE (UG/L AS AG) <1	TOTAL RECOV- BRABLE (UG/L AS ZN)	TOTAL (MG/L AS CN) <0.010	TOTAL (UG/L) <1 	LENE BLUB ACTIVE SUB- STANCE (MG/L)
OCT 1991 03 JAN 1992 02 FEB 18 MAY 07 JUN	TOTAL RECOV- BRABLE (UG/L AS FE) 170	TOTAL RECOV- BRABLE (UG/L AS PB)	NESE, TOTAL RECOV- BRABLE (UG/L AS MN)	TOTAL RECOV- BRABLE (UG/L AS HG)	NIUM, TOTAL (UG/L AS SE)	TOTAL RECOV- BRABLE (UG/L AS AG) <1	TOTAL RECOV- BRABLE (UG/L AS ZN)	TOTAL (MG/L AS CN) <0.010	TOTAL (UG/L) <1 	LENE BLUB ACTIVE SUB- STANCE (MG/L) 0.11

386

RIO DESCALABRADO BASIN

50108000 RIO DESCALABRADO NEAR LOS LLANOS, PR

LOCATION.--Lat 18°03'08", long 66°25'34", Hydrologic Unit 21010004, at bridge on Highway 14, 1.5 mi (2.4 km) west of Los Llanos, and 5.3 mi (8.5 km) east of Juana Díaz.

DRAINAGE AREA. -- 12.9 mi 2 (33.4 km2).

WATER-DISCHARGE RECORDS

PERIOD OF RECORD.--1959-65 (annual low-flow measurements only), 1965 (annual maximum discharge), January 1966 to June 1969, July to December 1969 (maximum discharge only), February 1984 to current year.

GAGE.--Water-stage recorder. Elevation of gage is 220 ft (67 m), from topographic map.

RRMARKS.--Records fair except those for estimated daily discharges, which are poor. Some regulation at low flow by local resident upstream from station.

local	local resident upstream from station.													
DAY	OCT	NOV	DEC	JAN	FRB	MAR	APR	MAY	JUN	JUL	AUG	SEP		
1	8.2	3.5	1.4	. 96	1.6	1.9	45	e5.8	74	4.0	6.1	e.72		
2	9.7	e10	1.3	. 87	2.1	2.3	17	e5.4	48	2.2	2.0	e.70		
3	5.8	e4.5	1.7	.79	1.9	2.2	7.9	e5.0	40	2.2	1.6	e.68		
4	4.7	e2.5	2.0	. 80	2.3	1.9	5.0	e4.7	34	2.0	1.6	e.68		
5	4.7	e1.5	1.6	457	2.8	1.8	4.0	e10	27	1.3	49	e. 66		
6	4.0	e1.1	1.4	543	7.2	2.1	5.5	e16	21	1.1	22	.77		
7	3.5	e1.3	1.3	e45	7.4	2.0	5.0	e10	17	1.3	10	7.3		
8	3.3	e1.1	.99	e18	5.4	1.5	3.0	e5.0	22	1.2	8.3	4.7		
9	4.7	e3.5	1.0	e12	2.5	1.3	2.6	e4.0	18	1.3	8.3	2.1		
10	6.0	e 3.0	1.0	e1 0	2.5	1.4	2.1	e3.8	13	1.7	7.8	1.6		
11	4.1	e2. 0	.97	e7.0	2.8	1.4	1.9	e1 0	9.9	1.8	6.0	1.6		
12	3.4	e1.5	.92	e5.6	4.2	1.3	3.9	e6.0	9.5	2.2	6.6	1.6		
13	2.6	e1.1	1.0	e4.0	2.5	1.3	2.9	e4.2	7.5	3.0	4.1	1.6		
14	2.3	e1.0	1.1	e3.2	2.4	1.6	3.9	e5.0	7.2	2.9	3.1	1.3		
15	1.9	e1.1	1.3	e2.6	2.2	1.5	7.7	e5.6	6.4	2.3	2.3	1.1		
16	1 0	-1 1	4 7	-2.2	2.0		4 1	e4.0	5.4	1.8	2.1	1.1		
17	1.8 2.3	e1.1 e1.1	1.7 2.0	e2.2 e1.8	2.0 1.9	1.4 1.9	4.1 7.0	e2.9	5.6	2.1	1.6	. 87		
18	1.4	e1.1	1.1	e1.5	2.0	1.7	4.8	2.2	5.7	3.9	1.8	.74		
19	1.6	e1.2	.85	1.1	1.9	1.3	8.3	1.1	5.4	5.4	2.1	3.1		
20	15	e1.1	.99	1.0	1.5	1.5	34	1.2	5.6	3.3	1.5	6.7		
21	7.5	1.1	.96	1.0	1.4	3.4	55	.79	8.1	3.9	1.4	8.2		
22	7.5	1.9	.98	. 72	1.2	3.9	13	1.1	6.0	4.3	1.6	5.5		
23	11	1.8	1.1	. 67	1.3	2.4	8.4	357	6.4	3.3	1.4	4.7		
24	3.2	2.2	1.3	.81	1.6	2.2	10	127	4.8	3.0	1.0	3.9		
25	2.3	2.0	1.2	.80	1.4	2.1	12	54	2.4	2.3	1.2	5.0		
26	1.7	1.8	1.2	. 63	1.6	1.9	8.4	789	1.7	2.3	1.1	7.4		
27	1.6	3.2	1.1	. 75	2.0	1.6	7.3	138	1.1	2.1	1.1	5.3		
28	1.3	3.2	1.1	. 84	2.3	1.7	6.6	84	1.3	1.6	1.1	3.2		
29	1.6	2.3	1.1	1.1	2.0	1.8	6.5	64	1.6	1.2	1.5	2.3		
30	1.5	1.4	.95	1.3		1.8	e6.0	52	2.1	1.1	1.6	e8.0		
31	7.6		1.0	1.5		1.8		44		4.2	1.4			
TOTAL	137.8	65.2	37.61	1128.54	73.9	57.9	308.8	1822.79	417.7	76.3	162.3	93.12		
MEAN	4.45	2.17	1.21	36.4	2.55	1.87	10.3	58.8	13.9	2.46	5.24	3.10		
MAX	15	10	2.0	543	7.4	3.9	55	789	74	5.4	49	8.2		
MIN	1.3	1.0	.85	. 63	1.2	1.3	1.9	.79	1.1	1.1	1.0	.66		
AC-FT	273	129	75	2240	147	115	613	3620	829	151	322	185		
CFSM	.34	.17	.09	2.82	.20	. 14	.80	4.56	1.08	. 19	.41	.24		
IN.	.40	.19	.11	3.25	.21	. 17	.89	5.26	1.20	. 22	.47	.27		
	•••		•	0.25		• • •	,	3.20			• • •			
e Ba	stimated													
STATIST	TICS OF M	ONTHLY M	RAN DATA	FOR WATER Y	TEARS 1966	- 1992,	BY WATE	R YEAR (WY)					
MEAN	29.2	17.2	5.58	5.73	2.04	1.13	3.92	15.9	5.20	2.39	3.51	13.4		
MAX	117	41.0	24.5	36.4	7.57	3.49	18.8	62.2	25.2	10.5	9.11	40.2		
(WY)	1986	1985	1988	1992	1986	1986	1985	1985	1987	1991	1988	1985		
MIN	2.02	2.17	.19	.057	.020	.012	.000	.032	.000	.000	.19	.063		
(WY)	1968	1992	1968	1968	1968	1968	1968	1968	1967	1967	1990	1967		
• - •														
SUMMARY	Y STATIST	ICS	FOR	1991 CALEN	DAR YEAR	F	OR 1992	WATER YEAR		WATER Y	EARS 1966	- 1992		
ANNUAL				1913.06	5		4381.	96						
ANNUAL	MRAN			5.24	l		12.	0		9.3	8			
HIGHEST	L ANNUAL	MRAN								18.4		1986		
LOWEST	ANNUAL M	Ban								1.8	9	1968		
	r DAILY M			138	Jul 16		789	May 26		2600		7 1985		
LOWEST	DAILY MR	AN		.23	Aug 10			63 Jan 26		.0	0 Jun	22 1966		
	SEVEN-DA			.28	Aug 7			63 Jan 26 75 Jan 22		.0	0 Jun	22 1966		
Instant	TANBOUS P	BAK FLOW	•		-		6020	May 26		30000	Oct	7 1985		
instant	PANBOUS P	BAK STAG	E				13.	46 May 26		24.3	7 Oct	7 1985		
	TANBOUS L							23 Jan 4						
	RUNOFF (3790			8690	0.2		6800 .7	2			
	RUNOFF (.41 5.52				93 64		9.8				
	CENT EXCE			9.5	•		10			13				
	CENT BACE			2.0			2.			1.3				
	CENT BACE			.47	,		1.			.0				
JU PARC		1200		.4			1.	-		. 0	•			

RIO JACAGUAS BASIN 387

50110900 RIO TOA VACA ABOVE LAGO TOA VACA, PR

LOCATION.--Lat 18°07'37", long 66°27'24", Hydrologic Unit 21010004, on right bank, off a dirt road about 0.3 mi (0.5 km) from road 553, 2.4 mi (3.9 km) southeast from Villalba plaza, and 0.2 mi (0.3 km) downstream from confluence with Quebrada Limón.

DRAINAGE AREA. -- 7.64 mi 2 (19.79 km2).

WATER-DISCHARGE RECORDS

PERIOD OF RECORD. -- April 1989 to current year.

REMARKS.--Records fair. Gage-height and precipitation satellite telemetry at station.

	DIS	SCHARGE,	CUBIC FRI		OND, WATER DAILY MEAN		TOBER 199	1 TO SEPTE	(BER 199	2		
DAY	OCT	NOV	DEC	JAN	FEB	MAR	APR	MAY	JUN	JUL	AUG	SEP
1	7.6	4.8	1.4	1.3	3.6	2.6	17	4.2	174	15	8.7	3.2
2	3.6	4.1	1.4	1.2	3.5	2.5	11	3.7	93	15	6.8	3.0
3	3.2	3.7	1.4	. 91	3.4	2.4	7.4	3.4	67	15	7.1	3.0
4	3.0	3.2	1.4	. 85	3.2	2.4	5.0	3.2	55	18	9.1	3.0
5	3.0	2.7	1.4	676	3.2	2.4	4.1	3.2	45	20	21	3.0
6	2.8	2.6	1.4	381	7.7	2.4	3.9	3.6	39	19	18	3.4
7	2.8	2.8	1.4	42	7.4	2.4	3.6	4.3	35	18	6.7	4.5
8	3.2	3.8	1.4	28	8.7	2.5	3.5	3.2	60	19	5.8	31
9	3.9	2.4	1.2	22	5.3	2.4	3.2	3.1	34	19	5.8	15
10	3.2	2.2	1.3	17	4.4	3.0	5.6	3.0	26	17	16	4.9
11	2.9	2.2	1.3	16	4.1	2.7	4.2	3.2	27	17	10	3.4
12	2.8	2.1	1.4	22	4.6	2.4	4.0	4.7	32	17	7.9	2.8
13	2.6	1.9	1.4	15	3.6	2.3	3.6	8.3	28	16	6.5	2.7
14	2.6	1.7	1.4	10	3.5	2.2	3.4	27	27	16	5.7	2.4
15	2.6	1.8	1.4	7.9	3.4	2.2	3.8	37	28	15	5.9	2.3
16	2.6	1.8	1.4	13	3.3	2.4	17	30	25	15	5.2	2.5
17	2.6	1.7	1.5	16	3.3	2.4	26	21	24	13	4.5	2.9
18	2.6	1.6	1.5	6.9	3.2	2.5	13	16	22	14	4.3	2.6
19	2.5	1.6	1.3	5.7	3.2	2.4	21	18	21	13	4.0	2.4
20	9.5	1.5	1.3	5.6	3.1	2.5	62	14	20	12	11	3.8
21	3.3	1.5	1.6	5.2	2.9	2.9	39	8.1	21	13	16	4.2
22	14	1.5	1.5	4.9	3.6	3.6	21	3.8	19	12	8.0	3.0
23	4.2	1.5	1.5	4.6	3.9	2.9	13	212	19	11	5.3	3.4
24	2.9	1.5	1.5	4.6	2.8	2.8	9.2	137	18	12	4.4	4.6
25	2.6	1.7	1.5	4.3	2.8	2.8	6.9	92	18	12	4.0	3.6
26	2.4	1.6	1.6	4.5	3.0	2.8	5.7	382	18	11	3.8	3.7
27	2.2	1.6	1.6	4.0	2.9	2.8	5.1	78	17	9.2	3.9	3.2
28	3.6	1.6	1.4	3.7	2.8	3.1	4.5	5 5	17	8.9	3.7	3.1
29	3.2	1.5	1.4	3.6	2.6	19	4.1	46	17	8.0	3.9	6.3
30 31	24 11	1.5	1.4	3.7 3.8		10 16	4.4	40 39	16 	7.8 17	3.5 3.3	62
		er =			445.0				1060			100 0
TOTAL	143.0	65.7	43.9	1335.26	113.0	117.7	335.2	1307.0	1062	444.9	229.8	198.9
MBAN MAX	4.61	2.19	1.42	43.1 676	3.90 8.7	3.80	11.2	42.2 382	35.4 174	14.4 20	7.41 21	6.63 62
MIN	2.2	4.8 1.5	1.6 1.2	.85	2.6	19	62 3.2	3.0	16	7.8	3.3	2.3
AC-FT	284	130	87	2650	224	2.2 233	665	2590	2110	882	456	395
CFSM	.60	. 29	.19	5.64	.51	.50	1.46	5.52	4.63	1.88	.97	. 87
IN.	.70	.32	.21	6.50	.55	. 57	1.63	6.36	5.17	2.17	1.12	. 97
6m > m 7 ds												
STATIST	LICS OF M	OMINTA WE	IAN DATA	FOR WATER	1 RAKS 1989	- 1992,	BI WATER	YEAR (WY)				
MBAN	54.3	18.2	5.93	17.2	3.68	3.39	5.17	14.7	10.8	7.39	6.96	25.6
MAX	109	40.1	11.2	43.1	4.75	4.71	11.2	42.2	35.4	14.4	11.9	46.2
(WY)	1991	1991	1991	1992	1991	1991	1992	1992	1992	1992	1989	1989
MIN	4.61	2.19	1.42	3.75	2.37	1.67	1.46	1.42	1.23	.71	2.74	6.63
(WY)	1992	1992	1992	1990	1990	1990	1990	1990	1990	1990	1990	1992
SUMMARY	Y STATIST	ıcs	FOR	1991 CALE	NDAR YEAR	I	OR 1992 W	NATER YEAR		WATER Y	BARS 1989	- 1992
ANNUAL	TOTAL			1952.7			5396.3	36				
ANNUAL				5.3			14.7	7		14.4		
HIGHES'	T ANNUAL I	MRAN								18.2		1991
	ANNUAL M									10.4		1990
	T DAILY M				May 20			Jan 5		676		5 1992
	DAILY MR		_	1.2				35 Jan 4		.4!		7 1990
	SEVEN-DA			1.3	Dec 5		1.2			.6		9 1990
	TANBOUS P						8700			8700		5 1992
	TANBOUS P		•				13.2	24 Jan 5		13.2		5 1992
	TANBOUS L			3870			10700	33 Jan 3		10460		7 1990
	RUNOFF (3870	· n		10700			1.8		
	RUNOFF (9.5			26.2			25.6		
	CENT EXCE			8.4			25			32	-	
	CENT EXCE			3.2			3.9	•		3.5		
	CENT EXCE			1.6			1.5			1.1		

RIO JACAGUAS BASIN 388

50110900 RIO TOA VACA ABOVE LAGO TOA VACA, PR--Continued

WATER-QUALITY RECORDS

PERIOD OF RECORDS. -- Water years 1988 to 1992.

PERIOD OF DAILY RECORD.--SUSPENDED-SEDIMENT DISCHARGE: April 1988 to September 1992.

INSTRUMENTATION. -- Automatic sediment sampler.

MRIN

EXTREMES FOR PERIOD OF DAILY RECORD.--SEDIMENT CONCENTRATION: Maximum daily mean, 3,170 mg/L January 05, 1992; Minimum daily mean, 1 mg/L several days.

SEDIMENT LOADS: Maximum daily mean, 18,300 tons (16,600 tonnes) January 05, 1992; Minimum daily mean, 0.0 ton (0.0 tonne) several days.

EXTREMES FOR CURRENT YEAR. -

SEDIMENT CONCENTRATION: Maximum daily mean, 3,170 mg/L January 05, 1992; Minimum daily mean, 1 mg/L several days.

SEDIMENT LOADS: Maximum daily mean, 18,300 tons (16,600 tonnes) January 05, 1992; Minimum daily mean, 0.0 ton (0.0 tonne) few days.

SEDIMENT DISCHARGE, SUSPENDED (TONS/DAY), WATER YEAR OCTOBER 1991 TO SEPTEMBER 1992

MELN

MPAN

		MBAN			MEAN			MKAN	
DAY	MEAN DISCHARGE (CFS)	CONCEN- TRATION (MG/L)	SEDIMENT DISCHARGE (TONS/DAY)	MEAN DISCHARGE (CFS)	CONCEN- TRATION (MG/L)	SEDIMENT DISCHARGE (TONS/DAY)	MEAN DISCHARGE (CFS)	CONCEN- TRATION (MG/L)	SEDIMENT DISCHARGE (TONS/DAY)
		OCTOBER		1	NOVEMBER		1	DECEMBER	
1	7.6	29	2.3	4.8	23	.33	1.4	5 5	. 02
2	3.6	8	.08	4.1	23	.28	1.4	5	. 02
3	3.2	7	.06	3.7	22	.27	1.4	6	.02
4	3.0	7	.06	3.2	21	.22	1.4	8	.03
5	3.0	7	.06	2.7	20	.18	1.4	10	.04
6	2.8	9	. 07	2.6	19	.16	1.4	11	.04
7	2.8	11	.08	2.8	16	. 12	1.4	13	. 05
8	3.2	11	. 09	3.8	15	.16	1.4	15	.06
9	3.9	9	.08	2.4	15	.10	1.2	16	. 05
10	3.2	11	. 09	2.2	15	.08	1.3	17	.06
11	2.9	17	. 13	2.2	15	.08	1.3	14	. 05
12	2.8	22	. 16	2.1	15	.08	1.4	11	. 04
13	2.6	22	. 16	1.9	13	.07	1.4	13	. 05
14	2.6	19	. 13	1.7	11	.06	1.4	16	. 05
15	2.6	16	.11	1.8	10	.05	1.4	15	. 05
16	2.6	15	.10	1.8	10	.05	1.4	15	.06
17	2.6	14	.10	1.7	10	.04	1.5	13	. 05
18	2.6	13	.10	1.6	10	.04	1.5	12	.04
19	2.5	15	.11	1.6	10	.04	1.3	11	.04
20	9.5	50	4.9	1.5	10	.04	1.3	11	.04
21	3.3	11	.11	1.5	10		1.6	14	.06
22	14	75	19	1.5	8	.04	1.5	18	.08
23	4.2	19	. 19	1.5	8	.04	1.5	21	.08
24	2.9	36	. 27	1.5	7	.03	1.5	21	.08
25	2.6	41	. 29	1.7	6	.02	1.5	20	.08
26	2.4	39	.26	1.6	6	.02	1.6	19	.08
27	2.2	35	.21	1.6	6	.02	1.6	17	. 07
28	3.6	48	. 54	1.6	5	.02	1.4	16	.06
29	3.2	20	.21	1.5	5	.02	1.4	15	.06
30	24	164	59	1.5	5	.02	1.4	14	. 05
31	11	62	2.8				1.3	17	.08
TOTAL	143.0		91.85	65.7		2.72	43.9		1.64

50110900 RIO TOA VACA ABOVE LAGO TOA VACA, PR--Continued

SEDIMENT DISCHARGE, SUSPENDED (TONS/DAY), WATER YEAR OCTOBER 1991 TO SEPTEMBER 1992

	MEAN			MRAN		MEAN			
DAY	MRAN DISCHARGE (CFS)	CONCEN- TRATION (MG/L)	SEDIMENT DISCHARGE (TONS/DAY)	MEAN DISCHARGE (CFS)	CONCEN- TRATION (MG/L)	Sediment Discharge (Tons/Day)	MEAN DISCHARGE (CFS)	CONCEN- TRATION (MG/L)	SEDIMENT DISCHARGE (TONS/DAY)
		JANUARY		1	PEBRUARY			MARCH	
1	1.3	15	. 05	3.6	24	.23	2.6	15	. 10
2	1.2	15	.05	3.5	28	.26	2.5	25	,17
3	.91	15	.04	3.4	33	.29	2.4	33	.21
4	.85	15	.04	3.2	35	.30	2.4	31	.20
5	671	3170	18300	3.2	28	.24	2.4	15	.10
6	381	2540	8100	7. 7	16	.34	2.4	11	. 07
7	42	279	38	7.4	14	.28	2.4	10	.06
8	28	85	6.9	8.7	14	.33	2.5	10	.06
9	22	25	1.6	5.3	16	.22	2.4	9	.06
10	17	9	.43	4.4	16	.19	3.0	8	. 07
11	16	9	.39	4.1	15	.18	2.7	7	. 05
12	22	13	.77	4.6	14	.17	2.4	7	.04
13	15	19	. 67	3.6	14	.13	2.3	6	. 03
14	10	24	. 63	3.5	21	.19	2.2	5	. 02
15	7.9	27	.60	3.4	32	.28	2.2	3	.02
16	13	68	5.4	3.3	44	.38	2.4	2	.02
17	16	70	3.7	3.3	29	.25	2.4	2	. 02
18	6.9	25	. 45	3.2	51	.44	2.5	2	. 02
19	5.7	25	.38	3.2	45	.37	2.4	2	. 02
20	5.6	24	. 35	3.1	38	.30	2.5	3	. 02
21	5.2	23	.31	2.9	38	.30	2.9	3	.03
22	4.9	22	.29	3.6	47	.45	3.6	4	. 04
23	4.6	23	. 27	3.9	54	. 53	2.9	7	.06
24	4.6	24	. 28	2.8	48	.36	2.8	10	.08
25	4.3	15	. 19	2.8	33	.24	2.8	10	.08
26	4.5	25	.29	3.0	20	.15	2.8	10	.08
27	4.0	24	. 25	2.9	14	.11	2.8	10	.08
28	3.7	20	. 19	2.8	10	.08	3.1	10	.09
29	3.6	17	. 17	2.6	9	.06	19	115	13
30	3.7	18	.18				10	37	1.4
31	3.8	21	.21				16	80	7.7
TOTAL	1330.26		26463.08	113.0		7.65	117.7		24.00

390 RIO JACAGUAS BASIN

50110900 RIO TOA VACA ABOVE LAGO TOA VACA, PR--Continued
SEDIMENT DISCHARGE, SUSPENDED (TONS/DAY), WATER YEAR OCTOBER 1991 TO SEPTEMBER 1992

	mean				mran		MRAN			
DAY	MRAN DISCHARGE (CFS)	CONCEN- TRATION (MG/L)	SEDIMENT DISCHARGE (TONS/DAY)	MEAN DISCHARGE (CFS)	CONCEN- TRATION (MG/L)	SEDIMENT DISCHARGE (TONS/DAY)	MEAN DISCHARGE (CFS)	CONCEN- TRATION (MG/L)	SEDIMENT DISCHARGE (TONS/DAY)	
		APRIL	,,	,===,	MAY	(22-1-7-1-7	,,	JUNE	,,	
1	17	79	5.6	4.2	17	.18	174	819	955	
2	11	40	1.4	3.7	15	.15	93	265	77	
3	7.4	19	.41	3.4	14	.13	67	32	5.9	
4	5.0	17	. 23	3.2	13	.11	55	25	3.8	
5	4.1	14	. 16	3.2	11	.09	45	18	2.1	
6	3.9	12	. 12	3.6	82	.72	39	17	1.7	
7	3.6	11	.10	4.3	4	.05	35	16	1.5	
8	3.5	12	.11	3.2	2	.02	60	338	166	
9	3.2	12	.10	3.1	2	.02	34	125	13	
10	5.6	11	.17	3.0	2	.02	26	33	2.5	
11	4.2	10	.10	3.2	6	.05	27	12	.84	
12	4.0	10	.10	4.7	15	. 37	32	9	.81	
13	3.6	8	.08	8.3	17	.50	28	9	. 69	
14	3.4	5	. 05	27	167	63	27	11	.80	
15	3.8	3	.04	37	183	21	28	16	1.1	
16	17	73	9.1	30	149	16	25	19	1.3	
17	26	117	9.8	21	96	6.3	24	16	1.0	
18	13	52	2.3	16	66	3.8	22	10	. 59	
19	21	92	7.3	18	116	6.5	21	6	.36	
20	62	1090	510	14	73	3.0	20	8	.46	
21	39	93	12	8.1	30	.75	21	16	. 84	
22	21	15	. 88	3.8	12	.14	19	21	1.1	
23	13	10	.38	212	1870	3760	19	19	. 95	
24	9.2	5	.15	137	803	312	18	12	.57	
25	6.9	3	.06	92	570	147	18	5	. 24	
26	5.7	4	.06	380	2650	10800	18	3	.14	
27	5.1	5	. 07	78	457	103	17	6	.29	
28	4.5	8	. 09	55	333	50	17	10	.42	
29	4.1	11	. 12	46	222	27	17	10	. 44	
30	4.4	15	. 17	40	205	23	16		.38	
31				39	188	20				
TOTAL	335.2		561.25	1305.0		15364.90	1062		1241.82	

50110900 RIO TOA VACA ABOVE LAGO TOA VACA, PR--Continued

SEDIMENT DISCHARGE, SUSPENDED (TONS/DAY), WATER YEAR OCTOBER 1991 TO SEPTEMBER 1992

		MEAN			mban			MEAN	
	MRAN	CONCEN-	SEDIMENT	MEAN	CONCEN-	SEDIMENT	MRAN	CONCEN-	SEDIMENT
	DISCHARGE	TRATION	DISCHARGE	DISCHARGE	TRATION	DISCHARGE	DISCHARGE	TRATION	DISCHARGE
DAY	(CFS)	(MG/L)	(TONS/DAY)	(CFS)	(MG/L)	(TONS/DAY)	(CFS)	(MG/L)	(TONS/DAY)
		JULY			AUGUST		S	SPTEMBER	
1	15	7	.30	8.7	34	.85	3.2	3	.03
2	15	7	.30	6.8	14	.27	3.0	6	. 05
3	15	8	.34	7.1	15	.28	3.0	8	. 07
4	18	10	. 47	9.1	34	1.2	3.0	10	.08
5	20	10	. 53	21	112	16	3.0	10	.08
6	19	10	.50	18	148	9.6	3.4	10	.08
7	18	10	. 49	6.7	42	.80	4.5	13	.20
8	19	11	.56	5.8	18	.26	31	195	58
9	19	10	. 52	5.8	19	.32	15	62	3.6
10	17	10	.45	16	460	35	4.9	13	. 18
11	17	10	.44	10	43	1.4	3.4	9	.08
12	17	10	.46	7.9	26	.56	2.8	5	. 04
13	16	10	. 4 4	6.5	21	.34	2.7	1	.01
14	16	13	. 53	5.7	19	.29	2.4	1	.00
15	15	18	.70	5.9	17	.26	2.3	1	.00
16	15	19	.76	5.2	14	.19	2.5	1	.00
17	13	24	.86	4.5	12	. 14	2.9	1	.00
18	14	29	1.1	4.3	12	. 14	2.6	1	.00
19	13	22	.78	4.0	17	.18	2.4	1	.00
20	12	13	.41	11	60	7.2	3.8	1	.01
21	13	4	. 13	16	56	4.0	4.2	1	.01
22	12	1	. 03	8.0	3	.09	3.0	4	. 03
23	11	1	.02	5.3	2	.03	3.4	11	. 12
24	12	1	. 03	4.4	2	.02	4.6	13	. 18
25	12	1	. 03	4.0	2	.02	3.6	11	. 12
26	11	1	. 02	3.8	2	.02	3.7	10	.10
27	9.2	2	. 05	3.9	2	.02	3.2	8	. 07
28	8.9	5	. 13	3.7	1	.02	3.1	9	.08
29	8.0	10	.21	3.9	1	.01	6.3	20	.41
30	7.8	15	.31	3.5	1	.00	62	996	705
31	17	75	7.0	3.3	1	.01			
TOTAL	444.9		18.90	229.8		79.52	198.9		768.63
YEAR	5389.36		44625.96						

RIO JACAGUAS BASIN

50110900 RIO TOA VACA ABOVE LAGO TOA VACA, PR--Continued WATER QUALITY DATA, WATER YEAR OCTOBER 1991 TO SEPTEMBER 1992

PARTICLE-SIZE DISTRIBUTION OF SUSPENDED SEDIMENT

DATE	TIMB	DIS- CHARGE, INST. CUBIC FEST PER SECOND	SEDI - MENT, SUS- PENDED (MG/L)	SEDI- MENT, DIS- CHARGE, SUS- PENDED (T/DAY)	SED. SUSP. FALL DIAM. PERCENT FINER THAN .002 MM	SED. SUSP. FALL DIAM. PERCENT FINER THAN .004 MM	SED. SUSP. FALL DIAM. PERCENT FINER THAN .008 MM
JAN 1992							
05	1715	320	6480	5600	43	50	64
05	1750	488	6230	8200	41	52	60
05	1910	2950	13800	110000	22	28	35
MAR			2000				
31	1555	24	2720	176	42	58	64
APR							
20	1635	247	6950	4630	23	30	34
MAY							
26	0345	3000	11100	89900	8	10	12
JUN							
01	1420	404	5310	5800	25	28	33
SEP							
09	1535	235	8330	5280	11	15	19
DATE	SED. SUSP. FALL DIAM. PERCENT FINER THAN .016 MM	SED. SUSP. FAIL DIAM. PERCENT FINER THAN .031 MM	SED. SUSP. SIEVE DIAM. PERCENT FINER THAN .062 MM	SED. SUSP. SIEVE DIAM. PERCENT FINER THAN .125 MM	SED. SUSP. SIEVE DIAM. PERCENT FINER THAN .250 MM	SED. SUSP. SIEVE DIAM. PERCENT FINER THAN .500 MM	SED. SUSP. SIEVE DIAM. PERCENT FINER THAN 1.00 MM
JAN 1992							
05	73	84	96	99	99.9	100	100
05	72	76	95	97	99	99.7	
05	43	53	65	74	84	93	98
MAR	13	55	43	/•	04	,,	30
31	72	78	98	98.4	99.2	99.7	99.8
APR		,,	70	,	,,		, ,,,,
20 MAY	49	59	71	85	94	98	99
26 JUN	15	19	26	35	52	83	99
01 SEP	40	50	68	81	92	99	99.8
09	31	39	51	74	88	96	98

RIO JACAGUAS BASIN

50110900 RIO TOA VACA ABOVE LAGO TOA VACA, PR--Continued WATER QUALITY DATA, WATER YEAR OCTOBER 1991 TO SEPTEMBER 1992 SILT AND CLAY PERCENT OF SUSPENDED SEDIMENT

DATE	TIME	STREAM- FLOW, INSTAN- TANEOUS (CFS)	SRDI- MENT, SUS- PENDRD (MG/L)	SEDI- MENT, DIS- CHARGE, SUS- PENDED (T/DAY)	SED. SUSP. SIEVE DIAM. PERCENT FINER THAN .062 MM
OCT 1991					
15	1740	2.6	75	0.5	88
JAN 1992					
05	1655	393	7840	8320	78
05	1800	704	7300	13800	92
MAR					
2 7	1530	2.8	436	3.3	96
MAY					
16	1756	41	200	22	99
23	0945	116	805	252	88
23	1817	381	1780	1830	79
24	0127	195	1100	577	74
26	0240	436	2640	3110	80
26	0915	240	773	501	83
26	1130	202	305	167	84
JUN					
01	1505	1560	2100	8860	94
SEP					
30	1520	274	8120	6000	56
30	1635	432	3880	4520	91
30	1705	239	5300	3420	87

394 RIO JACAGUAS BASIN

50111500 RIO JACAGUAS AT JUANA DIAZ, PR

LOCATION.--Lat 18°03'16", long 66°30'40", Hydrologic Unit 21010004, on Highway 14 bridge, 0.4 mi (0.6 km) west of Juana Diaz plaza, and 4.0 mi (6.4 km) downstream from Lago Guayabal.

DRAINAGE AREA. -- 49.8 mi 2 (129.0 km2).

WATER-DISCHARGE RECORDS

PERIOD OF RECORD. -- March 1984 to current year.

GAGE. -- Water-stage recorder. Elevation of gage is 131 ft (40 m), from topographic map.

REMARKS.--Records poor. Flow regulation from Lago Guayabal. Gage-height and precipitation satellite telemetry at station.

	corly ac	beation.										
		DISCUL	OP ONE	SIC FEET PE	B GBGOVED I	WAMED V	DID COMODE	ID 1001 MO	COMPANO	D 1002		
		DISCAR	GE, CUE	SIC FEET PE		MEAN V		SK 1991 10	SEF I SEDE	R 1992		
DAY	OCT	NOV	DEC	JAN	FEB	MAR	APR	MAY	JUN	JUL	AUG	SEP
1	e12	e29	e45	e.86	e10	3.8	4.3	31	282	16	11	7.7
2	e16	e19	e41	e.54	e11	3.6	5.1	49	222	14	9.3	7.6
3	e17	e8.2	e43	e.24	e6.4	3.7	3.8	22	162	14	8.9	6.4
4 5	e17 e27	e5.6 e5.1	e44 e41	e1.3 e93	e6.4 5.9	3.8 3.4	4.0	11 8.4	136 120	31 4 7	8.7 48	6.0 5.9
•	64/	63.1	94 T	633	5.5	3.4	4.3	0.4	120	•/	40	3.,
6	e30	e9.3	e38	e3170	6.3	3.0	4.7	8.4	107	58	144	7.6
7	e34	e26	e34	e57	28	2.1	5.1	8.3	88	56	65	8.5
8 9	e69	e31	e31	e39	42	1.3	4.8	7.8	134	60 55	43 38	21 40
10	e65 e72	e34 e29	e32 e34	e42 e62	26 24	1.7 2.1	5.4 31	7.7 7.5	143 110	50	145	13
				002			31					
11	e74	e13	e30	e100	25	2.8	25	7.6	105	52	105	8.9
12	e76	e9.7	e26	e150	29	3.3	24	7.2	151	47	32	6.9
13 1 4	e85 e73	e7.8 e48	e23 e24	e103 e75	37 29	3.1 3.2	11 6.5	7.2 31	121 91	40 39	16 11	8.0 6.5
15	e19	e69	e22	e72	27	3.1	7.4	33	70	36	9.3	5.8
					_,							
16	e9.3	e58	e23	e72	17	3.3	31	116	57	36	13	5.6
17	e9.9	e47	e24	e 86	14	3.4	70	78	47	32	8.9	5.6
18	e3.4	e43	e23	e68	11	3.5	21	63	36 29	26 23	8.1 7.6	5.4 6.4
19 20	e2.0 e1.5	e31 e77	e21 e20	e71 e57	5.7 6.0	3.1 3.1	17 190	46 17	24	24	7.4	12
	41.5	• , ,		03,	0.0	3.1	130				,	
21	e1.3	e108	e17	e4 3	5.6	4.1	191	15	46	25	96	50
22	e16	e112	e11	e 16	4.9	4.6	84	14	47	29	105	35
23	e17	e80	e9.3	e13	5.8	3.3	55	1010	28	14	36	33
24	e9.0	e49	e2.7	e17	4.9	3.2	41	542	27 25	8.7	24	39 31
25	e3.4	e60	e2.1	e15	4.1	3.2	34	293	45	7.0	16	31
26	e2.4	e116	e1.7	e9.7	4.2	3.1	28	2230	27	6.6	12	32
27	e2.3	e88	e2.0	e5.8	4.3	3.1	38	316	27	6.7	12	26
28	e4 .6	e 65	e2.5	e5.4	4.2	3.1	38	244	27	6.7	11	26
29	e14	e59	e3.9	e7.0	4.0	3.2	30	214	20	7.0	8.9	61
30	e22	e59	e3.5	e11		3.3	28	197	19	6.8	11 7.4	35
31	e32		e1.5	e 13		3.3		166		11	/.4	
TOTAL	836.1	1395.7	676.2	4475.84	408.7	97.9	1042.4	5808.1	2528	884.5	1078.5	562.8
MRAN	27.0	46.5	21.8	144	14.1	3.16	34.7	187	84.3	28.5	34.8	18.8
MAX	85	116	45	3170	42	4.6	191	2230	282	60	145	61
MIN	1.3	5.1	1.5	.24	4.0	1.3	3.8	7.2	19	6.6	7.4	5.4
AC-FT CFSM	1660 .54	2770 .93	1340 .44	8880 2.90	811 .28	194	2070 .70	11520 3.76	5010 1.69	1750 .57	2140 .70	1120 .38
IN.	.62	1.04	.51	3.34	.31	. 06 . 07	.78	4.34	1.89	. 66	.81	.42
	• • •										_	
e R	stimated											
OT A TO T	NT OR OP 1	MONTHLY MOI		BOD WAMED	VELDA 1004	1000	DV MARON	WHAD (MY)				
BIATIST	rics or i	MONITEI MEN	M DATA	FOR WATER	IRAKS 1984	- 1332	, DI WATEI	K IBAK (WI)				
MRAN	157	115	43.3	32.1	9.11	5.24	9.20	81.0	45.4	24.6	21.3	40.0
MAX	445	287	151	144	16.9	7.94	34.7	215	198	82.4	41.1	164
(WY)	1986	1988	1988	1992	1991	1988	1992	1985	1987	1987	1985	1985
MIN	8.65	10.5	9.99	5.88	4.82	3.16	3.19	2.68	2.72	2.94	2.25	5.32
(WY)	1987	1987	1989	1987	1990	1992	1991	1984	1984	1990	1990	1986
SUMMARY	'STATIS	TICS	FOR	R 1991 CALE	NDAR YEAR	1	FOR 1992 V	NATER YEAR		WATER :	YEARS 1984	- 1992
ANNUAL				8327.6			19794.7			50.		
	MEAN L'ANNUAL	MEAN		22.8			54.1	L		80.		1986
	ANNUAL									13.		1989
	DAILY			454	Jul 16		3170	Jan 6		4530		27 1987
	DAILY M			1.3	Oct 21 May 1			24 Jan 3		•:	24 Jan	3 1992
		MUMINIM YA		1.9	May 1			7 Dec 29		1.:	3 Sep	7 1990
		PEAK FLOW					20500			40000	Oct 42 Oct	7 1985
		PRAK STAGE (AC-FT)		16520			39260	81 Jan 6		36620		, 1303
	RUNOFF			.4			1.0			1.		
		(INCHES)		6.2			14.7			13.		
10 PERG	CENT EXC	EEDS		61			94			110		
	CENT EXC			9.4			21	_		8.		
90 PER	CENT EXC	erd s		2.8	:		3.3	3		3.	4	




Figure 24:-South coast river basins the Río Inabón to Río Loco basins.

RIO INABON BASIN

50112500 RIO INABON AT REAL ABAJO, PR

LOCATION.--Lat 18°05'10", long 66°33'46", Hydrologic Unit 21010004, at bridge on private road, off Highway 511 at Hacienda La Concordia, 0.4 mi (0.6 km) upstream from diversion canal, 0.5 mi (0.8 km) north of Real Abajo, and 6.1 mi (9.8 km) northeast of Plaza Degetau in Ponce.

DRAINAGE ARRA. -- 9.70 mi 2 (25.12 km2).

WATER-DISCHARGE RECORDS

PERIOD OF RECORD, --1962-63 (annual low-flow measurements only), February to June 1964 (monthly measurements only), July 1964 to July 1970, April 1971 to current year.

GAGE.--Water-stage recorder. Elevation of gage is 410 ft (125 m), from topographic map. Prior to April 1971 nonrecording gage and crest-stage gage at different datum.

RRMARKS.--Records fair except those for estimated daily discharges, which are poor. Gage-height and precipitation satellite telemetry at station.

satel	lite tele	metry at st	ation.			OC-						
		DISCHARGE	, CUBIC	FEET PER		WATER Y MEAN	YEAR OCTOBER VALUES	1991 TO	September	1992		
DAY	OCT	NOV	DEC	JAN	FRB	MAR	APR	MAY	JUN	JUL	AUG	SEP
1	16	55	11	8.4	8.3	4.9	25	13	9.8	11	16	10
2	14	31	9.9	12	7.7	4.5		11	9.9	10	12	9.9
3	11		11	10	7.2	4.5		10	9.8	9.9	11	9.6
4	9.9		13	13	7.5	4.9		9.6	9.1	8.5	16	9.9
5	9.7		11	173	7.1	4.8	7.3	9.9	7.5	8.0	41	9.6
6	11 19	18 18	9.5	686 89	e32	4.6		16 12	6.5 7.3	8.2	22 11	12 62
8	18	16	9.0	44	e23	4.7		8.1	13	8.7	11	42
9	21	29	8.7	33	14	6.5		7.1	22	8.4	15	23
10	14	23	8.2	27	11	8.4	9.3	7.6	8.5	7.6	52	20
11	11	16	8.1	30	10	5.1		7.6	12	7.3	33	17
12	11	15	7.3	34	9.8	4.5		15	23	7.7	20	13
13	10	15	7.1	24	8.4	4.4	6.5	9.6	17	7.2	15	11
14 15	9.4	15 15	7.2	21 19	7.6	4.3		11 12	8.3	7.1	12 11	11 26
16	8.6	15	7.4	18	7.3	4.2	16	10	6.6	6.9	10	17
17	8.3	15	7.4	16	7.0	4.4		7.4	5.7	6.9	9.6	14
18	11	14	6.7	14	6.0	5.0	16	6.1	5.1	11	9.8	11
19	12	15	6.6	13	6.0	5.0		4.9	6.6	10	8.7	10
20	9.4	15	9.8	12	6.2	5.1	89	4.3	8.6	7.2	8.1	17
21	24	15	11	12	6.0	5.8	67	4.1	14	6.5	36	14
22	38	16	5.9	11	5.6	5.3		4.0	9.3	5.6	18	12
23	22	16	5.9	11	5.3	4.4	25	146	8.3	5.5	11	21
24 25	15 13	15 12	5.6	11 11	6.0	4.6		96 64	13 15	6.0	8.5	17 21
26	12	12	5.2	11	6.1	4.5	15	198	13	5.6	8.4	21
27	11	14	5.1	9.8	6.1	8.0		40	12	5.3	10	16
28	10	12	4.5	9.6	5.7	11	13	22	9.5	5.1	7.9	31
29 30	25 26	12	4.0	9.6	5.2	21	12	16	12	4.6	9.7	25
31	50	12	3.8 5.9	9.1 8.6		12 27	12	12 17	12	4.5	10 11	53
TOTAL	490.3	540 2:	37.2	1410.1	268.3	206.9	574.8	811.3	325.4	239.9	483.2	586.0
MBAN	15.8		7.65	45.5	9.25	6.67		26.2	10.8	7.74	15.6	19.5
MAX	50	55	13	686	32	27		198	23	19	52	62
MIN	8.3	12	3.8	8.4	5.2	4.2		4.0	5.1	4.5	7.9	9.6
AC-FT CFSM	973	1070	470	2800	532	410		1610	645	476	958	1160
IN.	1.63	1.86	.79	4.69 5.41	.95 1.03	. 69		2.70 3.11	1.12	. 80	1.61	2.01
e R	stimated											
STATIST	TCS OF W	ONTHILV MEAN	DATA FO	D WATED V	PARS 196	4 - 100	2, BY WATER	VRAD (WV)				
										20.00	12.2	1222
MEAN	48.5		12.9	8.71	5.28	5.72		19.5	16.5	12.4	17.6	33.7
MAX (WY)	148 1986		26.5 1966	45.5 1992	9.25 1992	16.4 1972		76.7 1969	49.8 1969	32.7 1979	46.1 1979	119 1975
MIN	15.4		4.43	4.11	3.05	1.85		1.94	2.75	1.77	4.47	7.70
(WY)	1983		1977	1989	1977	1977		1967	1967	1990	1974	1986
SUMMAR	Y STATIST	ics	FOR 1	991 CALEN	DAR YEAR		FOR 1992 WA	TER YEAR		WATER YE	ARS 1964	- 1992
ANNUAL	TOTAL			4662.1			6173.4					
ANNUAL		202		12.8			16.9			18.6		
	T ANNUAL I									30.9		1969
	ANNUAL MI			115	Jul 16		686	Jan 6		9.57 2500		1974 16 1975
	DAILY ME			3.2	Apr 26		3.8	Dec 30		.80		23 1977
		MINIMUM		3.5	Apr 24		4.4			1.1		31 1977
	TANEOUS PI				5.6.63		5650	Jan 6		19000	Oct	7 1985
		BAK STAGE		6.00				Jan 6		25.30	Oct	7 1985
	RUNOFF ()			9250			12240			13460		
	RUNOFF (1.32			1.74			1.92		
	RUNOFF ()			17.88			23.68 25			26.02 41		
	CENT EXCE			9.9			11			9.1		
	CENT EXCE			4.8			5.2			3.1		

50113800 RIO CERRILLOS ABOVE LAGO CERRILLOS NEAR PONCE, PR

LOCATION.--Lat 18°07'01", long 66°36'17", Hydrologic Unit 21010004, on right bank, 0.3 mi (0.5 km) downstream from confluence with Río San Patricio, 0.1 mi (0.2 km) southwest of Hwy 139 and 2.4 mi (3.7 km) northwest of Maragüez.

DRAINAGE AREA. -- 15.4 mi2 (39.9 km2).

WATER-DISCHARGE RECORDS

PERIOD OF RECORD. -- December 1988 to current year.

GAGE.--Water-stage recorder and crest-stage gage. Elevation of gage is 720 ft (210 m), from topographic map.

REMARKS.--Records fair except those for estimated daily discharges, which are poor. Gage-height and precipitation satellite telemetry at station.

satel.	lite tele	metry at	station.									
		DISCHAI	RGE, CUBI	C FERT PER		WATER Y	BAR OCTOBER ALUES	1991 T O	SEPTEMBER	1992		
DAY	OCT	NOV	DEC	JAN	FRB	MAR	APR	MAY	JUN	JOL	AUG	SEP
1	32	34	18	9.0	14	9.2	28	13	51	17	19	16
2	26	18	18	10	13	8.8	69	13	44	16	16	15
3	23	13	e25	7.8	13	8.8	29	12	40	16	15	14
4	21	12	e 29	7.1	12	8.5	15	11	36	15	39	14
5	19	11	e2 6	331	12	9.1	14	11	32	14	75	14
_												
6	19	13	e25	717	34	8.5	12	15	29	14	56	51
7	30	13	e24	136	24	8.4	11	13	27	14	24	168
8	22	13	e25	64	23	9.1	10	11	34	14	21	81
9	38	26	e22	50	16	34	11	12	33	13	37	43 96
10	20	19	21	41	15	20	12	12	29	12	102	90
11	17	15	20	43	16	11	14	12	38	12	64	68
12	15	13	19	49	15	9.3	14	17	62	12	52	40
13	14	13	18	33	13	9.4	11	17	54	12	41	34
14	17	14	18	27	12	9.3	12	17	46	12	38	29
15	15	14	16	26	12	9.4	26	21	40	12	30	57
							- -					
16	13	14	16	24	11	9.3	21	23	35	12	23	44
17	12	15	16	23	11	9.4	28	19	34	12	20	34
18	42	15	15	20	11	10	19	18	32	49	18	34
19	18	15	15	20	10	9.3	52	19	30	22	16	34
20	14	15	17	19	10	9.7	65	18	27	19	15	33
21	16	15	20	18	10	9.7	49	13	37	17	64	32
22	33	15	14	18	9.7	10	27	12	25	16	27	32
23	18	15	13	16	9.7	9.7	20	281	23	15	18	51
24	14	15	12	16	9.3	10	17	207	21	15	16	38
25	13	15	12	16	9.3	10	15	206	21	15	15	33
											4.0	
26	12	17	11	17	9.5	12	14	205	21	14	18	31 26
27	12	18	11	16	9.9	15	13	108	20	15 15	18 16	46
28	11	19	10	14	9.8	15	13 13	68 55	19 18	15	19	37
29 30	48 83	19 18	9.6 8.8	14 14	9.3	15 12	13	48	18	15	17	30
31	77		8.5	14		16		54		43	16	
31	,,		6.5	14		10		34				
TOTAL	764	481	532.9	1829.9	383.5	354.9	667	1561	976	514	965	1275
MEAN	24.6	16.0	17.2	59.0	13.2	11.4	22.2	50.4	32.5	16.6	31.1	42.5
MAX	83	34	29	717	34	34	69	281	62	49	102	168
MIN	11	11	8.5	7.1	9.3	8.4	10	11	18	12	15	14
AC-FT	1520	954	1060	3630	761	704	1320	3100	1940	1020	1910	2530
CFSM	2.07	1.35	1.44	4.96	1.11	. 96	1.87	4.23	2.73	1.39	2.62	3.57
IN.	2.39	1.50	1.67	5.72	1.20	1.11	2.09	4.88	3.05	1.61	3.02	3.99
e Es	timated											
TRITATE	ICS OF MO	NTHLY ME	AN DATA E	OR WATER)	TEARS 1989	- 1992	, BY WATER	YEAR (WY)			
MBAN	89.9	34.8	16.4	22.0	8.83	13.0	15.4	20.9	22.6	15.0	31.0	58.5
MAX	154	50.2	18.2	59.0	13.2	27.5	24.3	50.4	36.5	26.7	53.1	88.0
(WY)	1991	1991	1991	1992	1992	1989	1989	1992	1989	1991	1991	1989
MIN	24.6	16.0	13.3	7.46	6.34	4.77	6.38	4.58	6.37	4.66	11.4	30.4
(WY)	1992	1992	1989	1989	1990	1990	1990	1990	1990	1990	1990	1991
SUMMARY	STATISTI	CS	FOR	1991 CALEN	DAR YEAR		FOR 1992 WAT	TER YEAR		WATER YE	ARS 1989	- 1992
ANNUAL	TOTAL			7118.4			10304.2					
ANNUAL	mran			19.5			28.2			28.2		
HI GHEST	ANNUAL M	(RAN								33.4		1991
LOWEST	ANNUAL ME	AN								22.9		1990
	DAILY ME			163			717	Jan 6		717		6 1992
	DAILY MEA				Mar 13		7.1			3.3		16 1990
	SEVEN-DAY			4.8	Mar 13		8.7			3.5		L4 1990
	ANEOUS PE						8140	Jan 5		8140		5 1992
	ANBOUS PE						9.65			9.69		5 1992
	ANBOUS LO						7.0	Jan 4		3.3	Aug 1	L6 1990
	RUNOFF (A			14120			20440			20410	_	
	RUNOFF (C			1.64			2.37			2.37		
	RUNOFF (1			22.25	5		32.21			32.10		
	ENT EXCEE			36			49			64		
	BNT BXCBE			14			16			14		
YU PERC	ENT EXCEE	SUS		5.7			10			4.9		

RIO BUCANA BASIN

50114000 RIO CERRILLOS NEAR PONCE, PR

LOCATION.--Lat 18°04'15", long 66°34'51", Hydrologic Unit 21010004, on right bank off Highway 139, 0.8 mi (1.3 km) below Lago Cerrillos Dam, 2.3 mi (3.7 km) upstream from Quebrada Ausubo and 4.6 mi (7.4 km) northeast of Plaza Degetau

DRAINAGE AREA. -- 17.8 mi² (46.1 km²), excludes 17.4 mi² (45.1 km²), upstream from Lago Cerrillos Dam.

WATER-DISCHARGE RECORDS

PERIOD OF RECORD. -- February to April 1964 (monthly measurements only), May 1964 to June 1985, July 1985 to April 1991 (semi-monthly measurements only), May 1991 to current year.

GAGE.--Water-stage recorder. Datum of gage is 253.10 ft (77.145 m), above mean sea level. Prior to March 22, 1977 at site 0.15 mi (0.24 km) upstream and datum 9.90 ft (3.018 m) higher.

REMARKS. -- Records poor. Flow regulated by Lago Cerrillos Dam since May 1991. Gage-height and precipitation satellite kmarks.--kecords poor. Flow regulated by Lago Cerrillos Dam since may 1991. Gage-Height and precipitation sate like telemetry at station. Prior to June 1985 some low-flow regulation by construction upstream. Maximum discharge prior to regulation, 22,400 ft³/s (6.34 m³/s), Sept. 16, 1975, gage-height, 11.2 ft (3.414 m), site and datum them in use from floodmarks, from rating curve extended above 150 ft³/s (4.25 m³/s), on basis of slope-area measurements of peak flow; minimum discharge prior to regulation, 2.2 ft³/s (0.062 m³/s), May 28, 1967.

minim	um disch	arge prio	r to regu	ilation, 2	.2 It'/# ((U.U62 m²/	s), May 2	18, 1967.				
		DISCHA	RGE, CUB	IC FERT PE		WATER YE Y MEAN VA		RR 1991 TO	SEPTEMBE	R 1992		
DAY	OCT	NOV	DEC	Jan	FRB	MAR	APR	MAY	JUN	JUL	AUG	SEP
1	e41	e35	e12	e8.4	15	8.1	26	9.9	51	17	20	20
2	e33	e21	e12	e 10	14	7.8	19	10	46	16	12	1.8
3	e2 9	e16	e16	e9.2	14	7.8	84	8.8	42	16	11	1.9
4	e26	e15	e19	e 8.6	14	8.1	16	7.8	38	16	22	1.9
5	e24	e13	e17	e450	13	8.5	11	7.5	32	17	80	1.7
6	e24	e16	e15	e900	34	7.5	9.3	10	31 29	15 14	71 24	2.0 2.0
7 8	e39 e28	e17 e17	e13 e15	e150 e78	32 30	7.5 7.8	8.1 7.2	13 7.9	33	12	18	57
9	e45	e33	e13	e60	19	23	6.9	7.5	62	15	32	118
10	e25	e25	e11	e52	16	38	11	6.5	35	14	103	79
11	e22	e19	e 10	e54	16	12	8.1	6.2	39	14	65	83
12	e19	e15	e9.6	e 62	19	10	15	6.6	74	16	46	123
13	·18	e14	e9.4	e40	15	9.9	8.5	18	62	12	42	114
14	22	e14	e9.4	e35	14	9.6	9.2	16	47	9.6	32	78
15	19	e 12	e9.0	e33	14	9.8	26	24	44	12	29	83
16	16	e13	e9.0	e31	13	9.7	33	25	32	12	24	90 60
17	:15	e12	e9.0	e29	12	9.3	32	17	29 28	11 51	20 11	2.1
18 19	e48 e22	e12 e11	e8.6 e8.6	e25 e25	12 11	10 9.2	23 55	18 13	26	28	.64	2.2
20	a18	e12	e9.6	e24	11	7.6	102	17	24	22	1.1	2.6
21	e20	e12	e15	e23	11	11	81	11	35	16	4.2	2.1
22	e42	e11	e13	e23	10	10	37	10	25	14	3.0	1.9
2'	e23	e12	e12	e 20	10	8.8	22	366	22	12	2.3	2.0
45	e18 e17	e11 e10	e11 e11	e20 e20	10 9.5	9.6 9.9	17 15	262 185	21 19	11 11	1.7 1.6	2.1 2.2
									••			
26	e15	e9.8	e10	e22	10	10	12	317	18	11 13	1.6 1.6	2.3 2.1
27 28	e15 e14	e12	e10	e21 e18	9.9 9.9	11 15	12 11	122 76	18 17	11	1.7	2.0
29	e60	e13 e13	e9.4 e9.0	e18	8.8	9.9	9.9	55	16	9.5	2.0	2.0
30	e102	e12	e8.6	e16		7.6	9.9	49	16	8.9	1.9	2.4
31	e97		e8.0	15		5.2		53		39	2.2	
TOTAL	956	457.8	352.2	2300.2	427.1	329.2	737.1	1755.7	1011	496.0	687.54	944.3
MBAN	30.8	15.3	11.4	74.2	14.7	10.6	24.6	56.6	33.7	16.0	22.2	31.5
MAX	102	35	19	900	34	38	102	366	74	51	103	123
MIN	14	9.8	8.0	8.4	8.8	5.2	6.9	6.2	16	8.9	. 64	1.7
AC-FT	1900	908	699	4560	847	653	1460	3480	2010	984	1360	1870 1.77
CFSM IN.	1.73 2.00	.86 .96	.64 .74	4.17 4.81	.83 .89	. 60 . 69	1.38 1.54	3.18 3.67	1.89 2.11	.90 1.04	1.25 1.44	1.97
e Rs	timated											
		OMBUTY ME	AN DAMA	ממידע מחק	VPIDE 100	1 - 1002	DV WAMPI	R YEAR (WY)				
						-						
MBAN	30.8	15.3	11.4	74.2	14.7	10.6	24.6	35.6	24.1	20.3	22.6 23.1	23.5 31.5
MAX	30.8	15.3	11.4	74.2	14.7	10.6	24.6	56.6 1992	33.7 1992	24.6 1991	1991	1992
(WY) MIN	1992 30.8	1992 15.3	1992 11.4	1992 74.2	1992 14.7	1992 10.6	1992 24.6	14.5	14.5	16.0	22.2	15.4
(WY)	1992	1992	1992	1992	1992	1992	1992	1991	1991	1992	1992	1991
SUMMARY	STATIST	ics			FOR 1	992 WATER	R YEAR			WATER	YRARS 1991	- 1992
ANNUAL	TOTAL				104	54.14						
ANNUAL	mban					28.6				28.		
	' ANNUAL									28.		1992
	ANNUAL M				_					28.		1992
	DAILY ME				9		Jan 6			900		6 1992 19 1992
		KAN LY MINIMUR					Aug 19 Aug 24			1.		24 1992
		BAK FLOW	•		11		Jan 6			1100		6 1992
		PEAK STAGE	3				Jan 6			6.		6 1992
ANNUAL	RUNOFF ((AC-FT)			207	40				20690		
	RUNOFF (1.60				1.		
	RUNOFF (21.85				21.	80	
	ENT BXCE					55 15				45 14		
	ENL RYCE					6.8				7.	8	
JO PERC	BACE	313 20				J. 0					-	

50114000 RIO CERRILLOS NEAR PONCE, PR--Continued

WATER-QUALITY RECORDS

PERIOD OF RECORD. -- Water years 1964 to current year.

WATER-QUALITY DATA, WATER YEAR OCTOBER 1991 TO SEPTEMBER 1992

		DIS-	WILDY-GON	PH	, MAISK I	EAR OCIOE	- T.C.T.	OXYGEN,	OXYGEN	COLI-		
		CHARGE,	SPE-	WATER				DIS-	DEMAND,	FORM,	STREP-	HARD-
		INST. CUBIC	CIFIC CON-	WHOLE FIELD	TEMPER-	TUR-	OXYGEN.	SOLVED (PER-	CHEM-	FECAL, 0.45	TOCOCCI FECAL,	ness Total
		FEET	DUCT-	(STAND-	ATURE	BID-	DIS-	CENT	(HIGH	UM-MP	(COLS.	(MG/L
DATE	TIME	PER	ANCE	- ARD -	WATER	ITY	SOLVED	SATUR-	LEVEL)	(COLS./	PER	AS
		SECOND	(US/CM)	UNITS)	(DEG C)	(NTU)	(MG/L)	ATION)	(MG/L)	100 ML)	100 ML)	CACO3)
OCT 1991 09	1515	33	360	8.2	25.5	15	7.8	95	<10	K930	550	120
DEC	1313	33	300	0.2	23.3	13	,	,,	110	K730	330	1.0
18	1200	8.4	309	8.2	23.5	1.3	9.0	107	<10	20	70	
FEB 1992	4055											
18 May	1055	12	343	8.0	26.0	1.6	9.4	112	<10	10	20	
07	1100	14	300	7.9	24.5	2.1	8.6	103	<10	K150	K160	130
JUN												
23 AUG	1130	24	315	7.0	27.5	1.9	9.0	109	<10	K10	40	
27	1030	1.6	784	7.9	26.0	8.0	6.4	7 B	<10	370	210	330
						ALKA-						SOLIDS,
		magne-		SODIUM	POTAS-	LINITY			CHLO-	FLUO-	SILICA,	SUM OF
	CALCIUM	SIUM,	SODIUM,	λD-	SIUM,	WAT WH		SULFATE	RIDE,	RIDE,	DIS-	CONSTI-
	DIS-	DIS-	DIS-	SORP-	DIS-	TOT FET	SULFIDE	DIS-	DIS-	DIS-	SOLVED	TUENTS,
	SOLVED	SOLVED	SOLVED	TION	SOLVED	FIELD	TOTAL	SOLVED	SOLVED	SOLVED	(MG/L	DIS-
DATE	(MG/L	(MG/L	(MG/L	RATIO	(MG/L	MG/L AS	(MG/L	(MG/L	(MG/L	(MG/L	AS	SOLVED
	AS CA)	As MG)	AS NA)		AS K)	CACO3	AS S)	AS SO4)	AS CL)	AS F)	SIO2)	(MG/L)
OCT 1991												
09	39	6.6	9.9	0.4	1.1	140	<0.5	22	13	<0.10	24	200
DEC												
18 FEB 1992						130						
18						140						
MAY												
07	40	6.5	12	0.5	1.2	150	<0.5	22	7.8	0.10	19	199
JUN 23						130						
AUG						150						
27	110	13	32	0.B	1.5	180		160	16	0.20	25	471
		n										
	SOLIDS,	RESIDUE TOTAL	NITRO-	NITRO-	MTMDA	MITMO	NITRO-			DARTIN	DODO"	CADMIUM
	DIS-	AT 105	GEN,	GEN,	NITRO- GEN,	NITRO- GEN,	GEN, AM- MONIA +	BHOG		BARIUM, TOTAL	BORON, TOTAL	TOTAL
	SOLVED	DEG. C.	NITRATE	NITRITE	NO2+NO3	AMMONIA	ORGANIC	PHOS- PHORUS	ARSENIC	RECOV-	RECOV-	RECOV-
	(TONS	SUS-	TOTAL	TOTAL	TOTAL	TOTAL	TOTAL	TOTAL	TOTAL	ERABLE	ERABLE	ERABLE
DATE	PER	PENDED	(MG/L	(MG/L	(MG/L	(MG/L	(MG/L	(MG/L	(UG/L	(UG/L	(UG/L	(UG/L
	DAY)	(MG/L)	AS N)	AS N)	AS N)	AS N)	AS N)	AS P)	AS AS)	AS BA)	AS B)	AS CD)
00M 1001												
OCT 1991 09	18.0	13		<0.010	0.440	0.020	<0.20	0.040	1	<100	30	3
DEC	10.0	13		10.010	0.440	0.020	10.20	0.040	-	(100	30	•
18		1		<0.010	0.290	<0.010	<0.20	0.020			••	
FEB 1992												
18		5		<0.010	0.670	0.030	<0.20	0.030				
MAY 07	7.61	<1	0.400	0.010	0.410	<0.010	<0.20	0.020	<1	<100	30	<1
אטע	,	**	0.400	0.010	0.410	(0.010	10.20	0.020	**	7200	30	**
23		14		<0.010	0.500	0.040	<0.20	0.040				
AUG												
27	2.03	14	11.0	0.040	11.0	0.060	<0.20	<0.010				

K = non-ideal count

RIO BUCANA BASIN

50114000 RIO CERRILLOS NEAR PONCE, PR--Continued WATER-QUALITY DATA, WATER YEAR OCTOBER 1991 TO SEPTEMBER 1992

DATE	CHRO- MIUM, TOTAL RECOV- ERABLE (UG/L AS CR)	COPPER, TOTAL RECOV- ERABLE (UG/L AS CU)	IRON, TOTAL RECOV- ERABLE (UG/L AS FE)	LEAD, TOTAL RECOV- ERABLE (UG/L AS PB)	MANGA- NESE, TOTAL RECOV- ERABLE (UG/L AS MN)	MERCURY TOTAL RECOV- ERABLE (UG/L AS HG)	SELE- NIUM, TOTAL (UG/L AS SE)	SILVER, TOTAL RECOV- ERABLE (UG/L AS AG)	ZINC, TOTAL RECOV- ERABLE (UG/L AS ZN)	CYANIDE TOTAL (MG/L AS CN)	PHENOLS TOTAL (UG/L)	METHY- LENE BLUE ACTIVE SUB- STANCE (MG/L)
OCT 1991												
09	<1	<10	1300	5	BO	<0.10	<1	<1	<10	<0.010	2	0.02
DEC												
18												
FEB 1992												
18												
MAY							_	_			_	
07	<1	<10	260	<1	BO	<0.10	<1	<1	<10	<0.010	3	0.02
JUN												
23												
AUG 27												
27												

50114390 RIO BUCANA AT HWY 14 BRIDGE NEAR PONCE, PR

LOCATION.--Lat 18°02'29", long 66°34'58", Hydrologic Unit 21010004, on left bank, 200 ft (61 m) upstream from bridge on Highway 14 and 4.0 mi (6.4 km) downstream from Lago Cerrillos Dam, 2.8 mi (4.5 km) northeast of Degetau Plaza in Ponce.

DRAINAGE AREA. -- 24.9 mi 2 (64.5 km2).

WATER-DISCHARGE RECORDS

PERIOD OF RECORD. --October 1985 to September 1986 (maximum only), published as "Río Bucaná Floodway Channel at Highway 14 bridge", October 1986 to July 1987 (maximum only), August 1987 to current year.

GAGE.--Water-stage recorder and crest-stage gage. Datum of gage is 116.40 ft (35.500 m) above mean sea level. Prior to Oct. 1, 1986, crest-stage gage located at Highway 14 bridge, at elevation of mean sea level.

REMARKS.--Records poor. Only minor regulation of low flow until Aug. 18, afterward flow regulated by Lago Cerrillos Dam 0.4 mi upstream. Gage-height and precipitation satellite telemetry at station.

	DIS	CHARGE,	CUBIC FRET		OND, WATER DAILY MEAN		TOBER 199	1 TO SEPTE	MBER 199	2		
DAY	OCT	NOA	DEC	JAN	FEB	MAR	APR	MAY	JUN	JUL	λÜĞ	SEP
1	18	250	9.1	14	14	7.3	e9.6	16	e30	e18	21	3.4
2	30	34	9.9	18	14	7.0	e11	15	e28	e17	15	5.3
3	18	20	11	16	13	6.9	86	13	e2 3	e1 7	14	3.9
4	14	17	13	15	13	7.0	17	11	e29	e17	19	3.4
5	14	21	12	107	13	8.1	e15	9.4	e22	e17	39	2.8
6 7	13 18	16 20	11 12	4340 2840	29 97	7.5 7.3	e12 e11	14 27	e20 e17	e17 e18	41 21	2.8 9.0
8	38	18	12	725	śi	7.5	e10	10	e19	e17	17	11
9	50	21	15	349	25	11	e9.0	7.3	e21	e17	23	50
10	52	49	15	233	17	127	e12	8.0	e 37	e 16	43	43
11	28	17	15	185	16	14	e13	7.2	e24	e14	38	37
12 13	28 23	13 12	15 15	438 205	23 15	11	e8.8	7.7 21	e44 e64	e17 e18	28 28	53 50
14	23	11	15	132	13	11 10	e9.8 15	e17	e48	e15	21	41
15	28	12	14	102	14	e9.6	51	e14	e32	e11	22	39
16	20	11	14	88	13	e9.6	78	e10	e30	e11	19	38
17	17	14	14	82	12	e9.4	62	e10	e28	e11	17	40
18	28	12	14	67	10	e8.6	55	e20	e26	e10	14	13
19	86	11	13	57	9.7	e8.8	42	e30	e24	e 90	8.5	3.0
20	18	11	15	57	8.9	e9.0	184	e13	e24	e69	7.6	3.9
21	25	11	22	55	8.9	e8.8	194	e12	e24	e48	14	3.3
22	44	11	16	50	9.0	e8.8	113	e9.6	e44	e28	6.B	4.0
23	89	10	15	47	9.6	e8.6	81	e9.4	e28	e15	5.7	3.0
24 25	19	11	15	42	9.7	e8.0	35	e580	e25	e14	6.4	2.8
	16	10	15	39	11	e8.6	30	e290	e23	e13	6.0	3.2
26	14	10	15	37	8.8	e8.4		e1350	e22	e1 3	5.5	3.0
27	13	28	14	32	8.6	e8.2	22	e175	e21	e13	4.B	2.8
28 29	12 13	34 29	14 14	26 23	8.6	e8.0	23	e115	e19	e12	4.3 3.7	2.5 2.6
30	218	10	14	17	8.0	e16 e24	18 17	e55 e32	e19 e19	e12 e11	3.7	4.6
31	319		14	16		e21		e32		e12	2.8	
TOTAL	1346	754	432.0	10454	502.8	426.0	1275.2	2940.6	834	628	519.4	484.3
MEAN	43.4	25.1	13.9	337	17.3	13.7	42.5	94.9	27.8	20.3	16.8	16.1
MAX	319	250	22	4340	97	127	194	1350	64	90	43	53
MIN	12	10	9.1	14	8.0	6.9	8.8	7.2	17	10	2.8	2.5
AC-FT	2670	1500	857	20740	997	845	2530	5830	1650	1250	1030	961
CFSM IN.	1.74 2.01	1.01 1.13	.56 .65	13.5 15.62	.70 .75	. 55 . 64	1.71 1.91	3.81 4.39	1.12 1.25	.81 .94	.67 .78	. 65 . 72
	timated			23.02	•••		2.72	1.05		• • • • • • • • • • • • • • • • • • • •	• • • • • • • • • • • • • • • • • • • •	
Statist	ICS OF MC	MTHLY M	BAN DATA FO	R WATER	YEARS 1987	- 1992	, BY WATER	YEAR (WY)				
MRAN	216	98.9	23.4	78.9	11.4	18.0	21.4	30.0	36.3	25.1	62.4	98.3
MAX	527	222	49.1	337	17.3	48.0	42.5	94.9	80.5	51.4	169	265
(WY)	1991	1988	1988	1992	1992	1989	1992	1992	1989	1991	1988	1989
MIN	43.4	25.1	13.9	9.84	7.39	5.81	9.58	5.89	8.09	6.08	16.8	16.1
(WY)	1992	1992	1992	1989	1989	1990	1991	1990	1990	1990	1992	1992
SUMMARY	STATIST	cs	FOR 1	.991 CALE	NDAR YEAR	;	FOR 1992 W	ATER YEAR		WATER Y	EARS 1987	- 1992
ANNUAL	TOTAL			10831.7			20596.3					
ANNUAL				29.7			56.3			62.2		
	ANNUAL N									78.0		1991
	ANNUAL ME			531	22		4240	7 6		52.1		1990 6 1992
	DAILY MR			531 4.8	Aug 22 Apr 17		4340 2.5	Jan 6 Sep 28		4340 2.5		28 1992
	SEVEN-DAY		DM .	5.4			2.8			2.8		23 1992
	ANBOUS PE						9890	Jan 6		17400		7 1985
	ANEOUS PE						12.4			13.4		7 1985
	RUNOFF ()			21480			40850			45040		
	RUNOFF (1.1			2.2			2.5		
	RUNOFF (1			16.1	R		30.7	7		33.9	2	
	ENT EXCE			54 13			58 15			122 15		
	ENT BACE			6.B			7.5			6.5		
marc				٧. ٥			,,,			v.5		

RIO PORTUGUES BASIN

50115000 RIO PORTUGUES NEAR PONCE, PR

LOCATION.--Lat 18°04'45", long 66°38'01", Hydrologic Unit 21010004, on right bank 30 ft (9 m) upstream from bridge on Highway 504, 0.2 mi (0.3 km) upstream from small unnamed tributary, 4.4 mi (7.1 km) upstream from Río Chiquito, and 4.7 mi (7.6 km) north of Plaza Degetau in Ponce.

DRAINAGE AREA, -- 8.82 mi2 (22.84 km2).

WATER-DISCHARGE RECORDS

PERIOD OF RECORD. -- February to June 1964 (monthly measurements only), July 1964 to current year.

GAGE.--Water-stage recorder. Elevation of gage is 470 ft (143 m), from topographic map. Prior to Dec. 4, 1964, non-recording gage at same site and datum.

REMARKS.--Records fair except those for estimated daily discharges, which are poor. Some low-flow regulation due to unknown activity upstream. Gage-height and precipitation satellite telemetry at station.

	DI	SCHARGE,	CUBIC FEET		OND, WATER DAILY MEAN		TOBER 199	1 TO SEPT	EMBER 199	2		
DAY	OCT	NOV	DEC	JAN	FRB	MAR	APR	MAY	JUN	JUL	AUG	SEP
1	10	12	3.3	14	e3.6	3.2	36	e3.2	13	7.8	8.2	6.6
2	8.0	8.0	3.2	6.8	e 3.3	3.3	46	e 3.1	10	7.7	5.5	6.5
3	6.8	6.6	3.4	2.6	e 3.3	3.4	26	e 3.0	13	7.8	5.3	5.9
4	5.3	5.9	3.9	2.0	e3.3	3.6	8.3	e2.8	9.8	7.8	13	5.6
5	5.1	e 5.3	3.1	212	5.6	3.6	5.8	e3.1	8.6	8.0	37	5.5
6 7	4.8	e5.0	3.0 3.0	794 67	25 25	3.4 3.4	5.0 4.5	e4.1 4.9	7.9 8.6	8.2 7.9	28 9.1	33 59
8	6.3	e14	2.8	19	29	3.3	4.1	3.2	9.7	7.7	7.3	48
و	5.1	14	2.8	9.8	10	25	5.8	3.0	17	7.0	17	27
10	7.6	15	2.9	7.0	8.1	24	e6.4	2.9	11	6.4	31	65
11	6.1	7.6	2.9	e8.7	8.2	6.0	4.1	2.8	13	7.7	22	42 17
12	e4.9	e6.4	2.8	e31	7.7	4.8	4.9	3.0	29	8.4 6.4	35 29	22
13 14	e4.9 e 6.0	e5.2 e4.5	2.6 2.6	e58 e39	7.2 6.7	4.4	4.0 3.7	7.6 8.2	21 15	4.7	19	12
15	e4.3	e3.8	2.5	e19	6.1	4.3	6.3	e5.0	14	4.8	14	8.6
16	e3.8	e3.5	2.6	e14	6.0	4.1	7.6	e 5.0	13	4.5	10	9.5
17	e 6.7	e4 . 4	2.7	e1 3	6.0	4.2	5.9	e9.5	12	4.5	8.8	8.0
18	e1 8	e 3.9	2.6	e12	5.7	4.3	4.7	14	11	43	8.0	6.4
19	e4 .0	e3.5	2.5	e1 0	5.8	4.2	5.2	6.4	11	21	7.3	8.1
20	e 9.7	3.5	2.6	e 9.1	5.4	4.2	11	5.3	11	14	6.8	19
21	e19	3.4	3.3	e7.8	5.0	4.2	19	4.3	20	7.6	45	12
22	e14	3.3	2.4	e 7.8	4.6	4.0	11	4.3	12	6.6	21	47
23	e5.9	3.2	2.4	e7.3	4.3	3.7	5.9	252	11	5.8	11	29
24 25	e5.0 e4.4	3.1 3.0	2.4 2.5	e6.8 e6.3	3.9 3.7	4.0 3.9	4.3 3.8	123 87	10 10	5.5 5.7	8.9 8.0	15 25
26	e4.2	3.9	2.3	e5.8	3.6	3.8	3.5	104	10	5.6	7.5	24
27	e4.0	5.4	2.2	e5.3	3.7	7.1	e3.3	36	10	5.4	6.8	11
28	e3.8	5.6	2.2	e4 .8	3.8	11	e3.2	16	9.8	5.4	6.6	17
29	e 50	4.1	2.1	e4 .3	3.6	8.9	e3.2	11	10	5.3	7.8	18
30	e 70	3.5	2.2	e3.8		4.4	e3.2	9.1	9.0	5.4	7.9	8.6
31	e54		2.2	e 3.6		8.8		13		9.8	6.4	
TOTAL	368.7	175.4	84.0	1411.6	217.2	184.9	265.7	759.8	370.4	263.4	458.2	621.3
MBAN	11.9	5.85	2.71	45.5	7.49	5.96	8.86	24.5	12.3	8.50	14.8	20.7
MAX	70	15	3.9	794	29	25	46	252	29	43	.45	65
MIN	3.8	3.0	2.1	2.0	3.3 431	3.2	3.2	2.8	7.9 735	4.5 522	5.3 909	5.5 1230
ac-ft Cfsm	731 1.35	348 .66	167 .31	2800 5.16	.85	367 .68	527 1.00	1510 2.78	1.40	.96	1.68	2.35
IN.	1.56	.74	.35	5.95	.92	.78	1.12	3.20	1.56	1.11	1.93	2.62
. 2	stimated											
									_			
STATIST	rics of M	ONTHLY M	RAN DATA F	OR WATER	YEARS 1964	- 1992,	BY WATER	YEAR (WY)			
MBAN	43.4	33.5	12.5	8.81	6.13	5.74	7.08	19.3	14.9	14.6	20.7	35.3
MAX	116	80.1	27.3	45.5	13.3	13.4	27.1	72.9	48.3	54.2	87.5	132
(WY)	1991	1988	1988	1992	1976	1976	1983	1985	1979	1979	1979	1975
MIN (WY)	11.9 1992	5.85 1992	2.71 1992	3.65 1989	2.62 1989	2.08 1977	2.45 1974	1.65 1973	2.33 1974	2.65 1976	4.20 1972	7.22 1991
(41)	1772	1774	1774	1707	1707	1911	1974	1973	13/4	1970	13/2	1771
SUMMAR	Y STATIST	rics	FOR	1991 CALE	NDAR YEAR	P	OR 1992 W	ATER YEAR		WATER Y	BARS 1964	- 1992
ANNUAL				2959.6			5180.6					
ANNUAL				8.1	1		14.2			18.5		4000
	r annual									38.0		1979
	ANNUAL M									8.0		1974
	DAILY ME			75 2.1	Aug 22 Dec 29		794 2.0	Jan 6 Jan 4		2440 1.1		16 1975 29 1973
	SEVEN-DY		M	2.1			2.0			1.3		23 1973
	TANBOUS P				200 23		6790			21000		7 1985
	TANBOUS P							1 Jan 6		20.2		7 1985
Instan'	TANBOUS L	OW FLOW					2.0			1.0		29 1973
ANNUAL	RUNOFF (AC-PT)		5870	_		10280			13390	_	
	RUNOFF (.9	2		1.6			2.1		
	RUNOFF (12.4	8		21.8	5		28.4	B	
	CENT BXCE			15 5.2			25 6.4			40 8.2		
	CENT BACE			3.0			3.1			3.1		
JU PER	CENT BACE	פעם		3.0			3.1			3.1		

PH WATER WHOLE FIELD

WATER-QUALITY RECORDS

PERIOD OF RECORD. -- Water years 1964 to current year.

DIS-

K = non-ideal count

WATER-QUALITY DATA, WATER YEAR OCTOBER 1991 TO SEPTEMBER 1992

OXYGEN

OXYGEN,

COLI-

50115000 RIO PORTUGUES NEAR PONCE, PR--Continued

DATE	TIME	DI CHAR INS CUB FR PR SEC	GB, SPE T. CIE IC CON BT DUC R ANG	PIC WHO I- FIE T- (STA CB AF	TER DLE SLD TEMI AND- ATT RD WAY	URE B FER I	ry so	D SO SEN, (P IS- C LVED SA	IS- DEN LVBD CH ER- IC ENT (H TUR- LEV	GEN COI MAND, FOR MEM- FEC CAL 0.4 MIGH UM- FEL) (COI B/L) 100	M, STREP- CAL, TOCOCCI 15 FECAL, MF (COLS. 48./ PER
OCT 1991 03	1135	2	. 6	277	8.7	25.5	1.8	8.5	105	<10	310 290
DEC 31	0940		.5	310			0.60	8.6	92		130 260
FEB 1992											
MAY	0935		.3	310			0.60	9.0	114	14	K40 K240
06 Jul	0915	_	.7	309			D.60	7.9	93	<10	K10 770
01 SRP	1035	4	. 8	307	8.0	25.5 1	_	8.6	96	<10	K66 K100
01	1020	6	. 9	290	8.5	24.7	0.60	7.8	80	<10	60 K110
DATE	NE TO (1	ARD- SSS OTAL MG/L AS ACO3)	CALCIUM DIS- SOLVED (MG/L AS CA)	MAGNE- SIUM, DIS- SOLVED (MG/L AS MG)	SODIUM, DIS- SOLVED (MG/L AS NA)	SODIUM AD- SORP- TION RATIO	POTAS- SIUM, DIS- SOLVED (MG/L AS K)	ALKA- LINITY WAT WH TOT FET FIELD MG/L AS CACO3	SULFIDE TOTAL (MG/L AS S)	SULFATE DIS- SOLVED (MG/L AS SO4)	CHLO- RIDE, DIS- SOLVED (MG/L AS CL)
OCT 1991 03		120	39	6.6	9.8	0.4	1.1	130	<0.5	8.8	9.2
DEC 31								150			
FEB 1992 20								140			
MAY									0.8		10
06 JUL		140	43	7.5	14	0.5	1.8	130			
SEP								140			
01		130	40	6.5	9.6	0.4	1.3	120		7.4	9.0
DATE	R: 1 S(LUO- IDR, DIS- DLVED MG/L S F)	SILICA, DIS- SOLVED (MG/L AS SIO2)	SOLIDS, SUM OF CONSTI- TUENTS, DIS- SOLVED (MG/L)	SOLIDS, DIS- SOLVED (TONS PER DAY)	RESIDUE TOTAL AT 105 DEG. C, SUS- PENDED (MG/L)	NITRO- GEN, NITRATE TOTAL (MG/L AS N)	NITRO- GEN, NITRITE TOTAL (MG/L AS N)	NITRO- GEN, NO2+NO3 TOTAL (MG/L AS N)	GEN,	NITRO- GEN, ORGANIC TOTAL (MG/L AS N)
OCT 1991											
DEC	•	<0.10	22	174	1.22	4		<0.010	0.580		
31 FEB 1992						1		<0.010	0.610		
20 May						2		<0.010	0.310	0.030	0.17
06 JUL	•	<0.10	18	181	1.80	<1	0.440	0.010	0.450	<0.010	
01 SEP						7	0.990	0.010	1.00	0.020	0.18
01		0.10	18	173	3.22	1		<0.010	0.680	0.030	

RIO PORTUGUES BASIN 50115000 RIO PORTUGUES NEAR PONCE, PR--Continued WATER-QUALITY DATA, WATER YEAR OCTOBER 1991 TO SEPTEMBER 1992

DATE	NITRO- GEN, AM- MONIA + ORGANIC TOTAL (MG/L AS N)	NITRO- GEN, TOTAL (MG/L AS N)	NITRO- GEN, TOTAL (MG/L AS NO3)	PHOS- PHORUS TOTAL (MG/L AS P)	ARSENIC TOTAL (UG/L AS AS)	BARIUM, TOTAL RECOV- ERABLE (UG/L AS BA)	BORON, TOTAL RECOV- ERABLE (UG/L AS B)	CADMIUM TOTAL RECOV- BRABLE (UG/L AS CD)	CHRO- MIUM, TOTAL RECOV- ERABLE (UG/L AS CR)	COPPER, TOTAL RECOV- ERABLE (UG/L AS CU)
OCT 1991										
03	<0.20			0.020	<1	<100		<1	1	<10
31 FEB 1992	<0.20			0.040						
20 May	0.20	0.51	2.3	0.040						
06 JUL	<0.20			0.030	. <1	100	20	<1	<1	<10
01 SEP	0.20	1.2	5.3	0.030	***					
01	<0.20			0.020				-		
			- ADNAM				ZINC,			MRTHY- LENE
DATE	IRON, TOTAL RECOV- ERABLE (UG/L AS FE)	LEAD, TOTAL RECOV- ERABLE (UG/L AS PB)	NESE, TOTAL RECOV- ERABLE (UG/L AS MN)	MERCURY TOTAL RECOV- ERABLE (UG/L AS HG)	SELE- NIUM, TOTAL (UG/L AS SE)	SILVER, TOTAL RECOV- ERABLE (UG/L AS AG)	TOTAL RECOV- BRABLE (UG/L AS ZN)	CYANIDE TOTAL (MG/L AS CN)	PHENOLS TOTAL (UG/L)	BLUE ACTIVE SUB- STANCE (MG/L)
OCT 1991	TOTAL RECOV- ERABLE (UG/L AS FE)	TOTAL RECOV- ERABLE (UG/L AS PB)	TOTAL RECOV- BRABLE (UG/L AS MN)	TOTAL RECOV- ERABLE (UG/L AS HG)	NIUM, TOTAL (UG/L AS SE)	TOTAL RECOV- ERABLE (UG/L AS AG)	TOTAL RECOV- ERABLE (UG/L AS ZN)	TOTAL (MG/L AS CN)	TOTAL (UG/L)	BLUE ACTIVE SUB- STANCE (MG/L)
	TOTAL RECOV- ERABLE (UG/L	TOTAL RECOV- BRABLE (UG/L	TOTAL RECOV- BRABLE (UG/L	TOTAL RECOV- BRABLE (UG/L	NIUM, TOTAL (UG/L	TOTAL RECOV- BRABLE (UG/L	TOTAL RECOV- BRABLE (UG/L	TOTAL (MG/L	TOTAL	BLUE ACTIVE SUB- STANCE
OCT 1991 03	TOTAL RECOV- ERABLE (UG/L AS FE)	TOTAL RECOV- ERABLE (UG/L AS PB)	TOTAL RECOV- BRABLE (UG/L AS MN)	TOTAL RECOV- ERABLE (UG/L AS HG)	NIUM, TOTAL (UG/L AS SE)	TOTAL RECOV- ERABLE (UG/L AS AG)	TOTAL RECOV- ERABLE (UG/L AS ZN)	TOTAL (MG/L AS CN)	TOTAL (UG/L)	BLUE ACTIVE SUB- STANCE (MG/L)
OCT 1991 03 DEC 31	TOTAL RECOV- ERABLE (UG/L AS FE)	TOTAL RECOV- ERABLE (UG/L AS PB)	TOTAL RECOV- BRABLE (UG/L AS MN)	TOTAL RECOV- ERABLE (UG/L AS HG)	NIUM, TOTAL (UG/L AS SE)	TOTAL RECOV- ERABLE (UG/L AS AG)	TOTAL RECOV- ERABLE (UG/L AS ZN)	TOTAL (MG/L AS CN)	TOTAL (UG/L)	BLUE ACTIVE SUB- STANCE (MG/L)
OCT 1991 03 DEC 31 FEB 1992 20	TOTAL RECOV- ERABLE (UG/L AS FE)	TOTAL RECOV- ERABLE (UG/L AS PB)	TOTAL RECOV- BRABLE (UG/L AS MN) <10	TOTAL RECOV- ERABLE (UG/L AS HG)	NIUM, TOTAL (UG/L AS SE)	TOTAL RECOV- ERABLE (UG/L AS AG)	TOTAL RECOV- ERABLE (UG/L AS ZN)	TOTAL (MG/L AS CN) <0.010	TOTAL (UG/L)	BLUE ACTIVE SUB- STANCE (MG/L) 0.02
OCT 1991 03 DEC 31 FEB 1992 20 MAY 06	TOTAL RECOV- ERABLE (UG/L AS FE)	TOTAL RECOV- ERABLE (UG/L AS PB)	TOTAL RECOV- BRABLE (UG/L AS MN) <10	TOTAL RECOV- BRABLE (UG/L AS HG) <0.10	NIUM, TOTAL (UG/L AS SE) <1	TOTAL RECOV- BRABLE (UG/L AS AG)	TOTAL RECOV- BRABLE (UG/L AS ZN) <10	TOTAL (MG/L AS CN) <0.010	TOTAL (UG/L) <1	BLUE ACTIVE SUB- STANCE (MG/L) 0.02

50116200 RIO PORTUGUES AT PONCE, PR

WATER-QUALITY RECORDS

LOCATION.--Lat 18°00'20", long 66°36'28", 1,300 ft (400 m) south of Las Americas Avenue Bridge, 1.2 mi (1.9 km) south of CSC 50115900, 0.8 mi (1.3 km) west of Highways 1 and 2 junction, and 0.7 mi (1.1 km) southeast of Ponce.

DRAINAGE AREA. -- 18.9 mi2 (49.0 km2).

PERIOD OF RECORD. -- Water years 1979 to current year.

WATER-QUALITY DATA, WATER YEAR OCTOBER 1991 TO SEPTEMBER 1992

DATE	TIME	DIS- CHARGE, INST. CUBIC FEET PER SECOND	SPB- W CIFIC W CON- F DUCT- (S ANCE	TAND- A'	MPER- TURE ATER EG C)	TUR- BID- ITY (NTU)	OXYGEN DIS- SOLVE (MG/L	CENT D SATUR	DEMAN CHEM ICAL (HIG - LEVEL	D, FORM, - FECAL, 0.45 H UM-MF) (COL8./	STREP- TOCOCCI FECAL, (COLS. PER 100 ML)
NOV 1991											
04 Jan 1992	1035	3.2	470	7.5	24.5	4.0	5.	7 6	3	15 2800	590
02 FEB	1055	7.3	410	7.4	23.0	14	6.	6 7:)	11 3300	K17000
19	1110	2.6	515	7.8	24.5	1.9	6.	6 7	1	14 K7600	300
MAY 06 JUL	1120	4.8	672	7.1	27.0	13	3.	3 4:	l	18 K7400	570
01	1145	7.5	485	7.7	27.5	16	7.	9 9	5	10 2900	290
01	1140	3.4	485	8.0	27.0	2.0	6.	7 8:	L	13 K7000	60
	NE	LRD- SS CALC TAL DIS		, SODIUM		ND-	OTAS- L SIUM, W	ALKA- INITY AT WH OT FRT 81	TLFIDE	SULFATR P	HLO- IDR, IS-

DATE	HARD- NESS TOTAL (MG/L AS CACO3)	CALCIUM DIS- SOLVED (MG/L AS CA)	MAGNE- SIUM, DIS- SOLVED (MG/L AS MG)	SODIUM, DIS- SOLVED (MG/L AS NA)	SODIUM AD- SORP- TION RATIO	POTAS- SIUM, DIS- SOLVED (MG/L AS K)	ALKA- LINITY WAT WH TOT FET FIELD MG/L AS CACO3	SULFIDE TOTAL (MG/L AS S)	SULFATE DIS- SOLVED (MG/L AS SO4)	CHLO- RIDE, DIS- SOLVED (MG/L AS CL)
NOV 1991										
04	160	48	10	37	1	1.6	150	<0.5	63	40
JAN 1992 02							105			
FEB							103			
19							180			
MAY 06	190	57	12	58	2	2.4	160	0.6	85	54
JUL	190	37	14	38	4	2.4	100	0.6	65	34
01							145			
SEP 01	160	46	10	35	1	1.6	140		57	34
			SOLIDS,		DOSTINID					
DATE	FLUO- RIDB, DIS- SOLVED (MG/L AS F)	SILICA, DIS- SOLVED (MG/L AS SIO2)	SUM OF CONSTI- TUENTS, DIS- SOLVED (MG/L)	SOLIDS, DIS- SOLVED (TONS PER DAY)	RESIDUE TOTAL AT 105 DEG. C, SUS- PENDED (MG/L)	NITRO- GEN, NITRATE TOTAL (MG/L AS N)	NITRO- GEN, NITRITE TOTAL (MG/L AS N)	NITRO- GEN, NO2+NO3 TOTAL (MG/L AS N)	NITRO- GEN, AMMONIA TOTAL (MG/L AS N)	NITRO- GEN, ORGANIC TOTAL (MG/L AS N)
NOV 1991										
04	0.20	22	312	2.65	7	0.390	0.010	0.400	0.070	0.23
JAN 1992 02					17	0.660	0.030	0.690	0.070	0.43
FRB					1,	0.000	0.030	0.030	0.070	0.43
19 MAY					3	0.250	0.040	0.290	0.130	0.37
06	0.20	20	385	4.98	29	0.470	0.120	0.590	0.660	0.44
01 SEP					33	0.043	0.010	0.530	0.030	0.27
01	0.20	17	288	2.64	<1	0.056	0.040	0.096	0.180	0.42

K = non-ideal count

RIO PORTUGUES BASIN

50116200 RIO PORTUGUES AT PONCE, PR--Continued WATER-QUALITY DATA, WATER YEAR OCTOBER 1991 TO SEPTEMBER 1992

DATE	NITRO- GEN, AM- MONIA + ORGANIC TOTAL (MG/L AS N)	NITRO- GEN, TOTAL (MG/L AS N)	NITRO- GEN, TOTAL (MG/L AS NO3)	PHOS- PHORUS TOTAL (MG/L AS P)	ARSENIC TOTAL (UG/L AS AS)	BARIUM, TOTAL RECOV- ERABLE (UG/L AS BA)	BORON, TOTAL RECOV- ERABLE (UG/L AS B)	CADMIUM TOTAL RECOV- ERABLE (UG/L AS CD)	CHRO- MIUM, TOTAL RECOV- ERABLE (UG/L AS CR)	COPPER, TOTAL RECOV- ERABLE (UG/L AS CU)
NOV 1991	0.20	0.70	2 1	0 020		-100	140	<1		50
04 JAN 1992	0.30	0.70	3.1	0.020	<1	<100	140	<1	1	
02 Feb	0.50	1.2	5.3	0.080						
19 May	0.50	0.79	. 3.5	0.080						
06 Jul	1.1	1.7	7.5	0.150	<1	<100	160	<1	1	<10
01 SEP	0.30	0.35	1.6	0.010						
01	0.60	0.70	3.1	0.150						
DATE	IRON, TOTAL RECOV- ERABLE (UG/L AS FE)	LEAD, TOTAL RECOV- ERABLE (UG/L AS PB)	MANGA- NESE, TOTAL RECOV- ERABLE (UG/L AS MN)	MERCURY TOTAL RECOV- ERABLE (UG/L AS HG)	SELE- NIUM, TOTAL (UG/L AS SE)	SILVER, TOTAL RECOV- ERABLE (UG/L AS AG)	ZINC, TOTAL RECOV- ERABLE (UG/L AS ZN)	CYANIDR TOTAL (MG/L AS CN)	PHENOLS TOTAL (UG/L)	METHY- LENE BLUE ACTIVE SUB- STANCE (MG/L)
NOV 1991	200		4.0	.0.10		. •		.0.010		0.00
04 JAN 1992	380	3	40	<0.10	<1	<1	<10	<0.010	1	0.03
02 FRB										
19 MAY										
06 JUL	1400	2	190	<0.10	<1	<1	20	<0.010	2	0.07
01 SRP										
01										
			P	ESTICIDE	ANALYSES					
D AT E	TIME	PCB, TOTAL (UG/L)	ALDRIN, TOTAL (UG/L)	CHLOR- DANE, TOTAL (UG/L)	DDD, TOTAL (UG/L)	DDE, TOTAL (UG/L)	DDT, TOTAL (UG/L)	DI- AZINON, TOTAL (UG/L)	DI- BLDRIN TOTAL (UG/L)	ENDO- SULFAN, TOTAL (UG/L)
JUL 1992 01	1145	<0.1	<0.010	<0.1	<0.010	<0.010	<0.010	<0.01	<0.010	<0.010
DAT	ENDR WAT UNFL E RE (UG/	ER TRD ETHI C TOT	AL TOT	TA- CHI OR, BPOX AL TOT	INL TOT	'AL TOT	ON, CHI	CY- PAR LOR, THI TAL TOT	ON, MIR	EX, TAL /L)
JUL 199 01		010 <0	.01 <0.	010 <0.	010 <0.	010 <0	0.01 <0	0.01 <0	.01 <0	.01
DAT		LEN A- POL ON, CHI	A- RS, Y- PB OR. THA AL TOT	NE APHE	TAL THI	I- 2,4 ON TOT	'AL TO	5-T 2, 4 FAL TOT 5/L) (UG/	AL TOT	λL
JUL 199 01		.01 <0	.10 <	0.1	1 < 0	.01 <0	0.01 <0	0.01 <0	.01 <0	.01

RIO GUAYANILLA BASIN

50124200 RIO GUAYANILLA NEAR GUAYANILLA, PR

LOCATION.--Lat 18°02'40", long 66°47'53", Hydrologic Unit 21010004, on left bank, 0.7 mi (1.1 km) north of junction of Highways 2 and 132, 0.6 mi (1.0 km) downstream from Quebrada Consejo, 1.8 mi (2.9 km) north-northwest from Plaza de Guayanilla.

DRAINAGE AREA. ~~ 18.9 mi2 (49.0 km2).

WATER-DISCHARGE RECORDS

PERIOD OF RECORD. -- March 1981 to current year.

GAGE.--Water-stage recorder. Elevation of gage is 80 ft (24 m), from topographic map.

REMARKS.--Records fair except those for estimated daily discharges, which are poor. Gage-height and precipitation satellite telemetry at station.

satel	lite tele	metry at st	ation.									
		DI SCHARGE	R, CUBIC	FBET PER		WATER Y	TEAR OCTOBER	1991 TO	Septembe	R 1992		
DAY	ОСТ	NOV	DEC	JAN	FEB	MAR	APR	MAY	JUN	JUL	AUG	SEP
1	22	33	19	14	5.4	4.8	e20	e6. 6	23	30	10	6.3
2	29	30	18	14	5.4	5.0	e19	e7.0	25	27	6.1	6.1
3	23	25	18	12	5.2	4.4	e30	e6.0	21	30	7.3	5.3
4	22	24	21	11	5.2	4.2	e 11	e5.6	19	21	5.9	4.9
5	22	24	19	69	5.4	4.5	e6.0	e5.4	17	20	50	12
6 7	25 33	70 36	17	408 53	5.4	4.9	e5.0	e9.0 e6.0	16 15	17 15	80 21	21 59
8	23	30	17 18	32	e5.4 e5.9	5.7 5.4	e4.0 e3.4	e5.0	16	16	14	44
ğ	21	28	19	21	e6.3	5.2	e5.0	e3.9	62	15	23	17
10	27	27	18	16	e6.3	e5.4	e6.6	e4.0	33	10	22	10
11	24	26	16	16	6.1	e6.4	e7.0	e4.0	35	8.4	15	7.8
12	21	25	15	22	6.5	e6.8	e4.5	e4.5	49	13	134	7.8
13	19	24	14	12	e6.8	e3.5	e4.8	10	43	7.3	111	5.8
14	20	28	15	9.8	e6.1	e3.3	e5.0	21	34	57	42	35
15	30	24	16	8.6	6.3	e3.3	e7.0	37	30	50	28	28
16	22	26	17	9.4	6.3	e3.2	e10	12	29	12	25	21
17	20	38	18	19	6.0	e3.2	e12	13	28	7.3	18	41
18	24 33	27	18	11	5.4	e3.4	014	9.9	27	7.5	14	29 14
19 20	28	22 20	18 18	9.5 8.6	5.4 5.4	e3.8 e3.8	e12 e25	6.0 4.6	27 27	12 20	11 9.9	15
21	39	20	22	8.6	5.5	e4.0	e 62	4.0	74	9.3	23	20
22	35	19	19	8.4	5.4	e4.3	e4 0	3.7	42	8.1	28	34
23	43	19	19	8.4	5.0	e3.6	e19	270	37	7.3	13	31
24	44	19	18	7.0	4.9	e3.4	e14	211	34	6.7	10	19
25	55	20	18	6.8	4.6	e 3.6	e12	167	34	6.2	9.1	23
26	46	26	17	6.8	4.4	e3. 6	e 10	127	35	5.8	8.0	31
27	35	23	17	6.2	4.5	e5.0	e8.4	70	35	5.3	7.6	13
28	34	22	16	5.9	4.1	e9.0	e8.0	42	34	5.2	7.2	58
29	32	23	16	5.9	4.1	e15	e7.0	32	34	5.3	9.7	42
30 31	32 36	20	16 16	5.9 5.5		e13 e10	e6.6	25 21	34	5.2 6.3	13 7.6	81
TOTAL	919	798	543	851.3	158.7	164.7	398.3	1153.2	969	466.2	783.4	742.0
MRAN	29.6	26.6	17.5	27.5	5.47	5.31	13.3	37.2	32.3	15.0	25.3	24.7
MAX	55	70	22	408	6.8	15	62	270	74	57	134	81
MIN	19	19	14	5.5	4.1	3.2	3.4	3.7	15	5.2	5.9	4.9
AC-FT	1820	1580	1080	1690	315	327	790	2290	1920	925	1550	1470
CFSM	1.57	1.41	.93	1.45	.29	.28	.70	1.97	1.71	. 80	1.34	1.31
IN.	1.81	1.57	1.07	1.68	.31	.32	.78	2.27	1.91	. 92	1.54	1.46
e Es	timated											
STATIST	ICS OF MC	NTHLY MEAN	DATA FO	R WATER Y	EARS 1981	- 1992	, BY WATER	YBAR (WY)			
MRAN	64.7	53.2	20.1	11.1	7.18	6.20	10.7	28.7	14.9	12.2	18.4	42.0
MAX	167	110	41.9	27.5	11.4	13.2	26.6	80.4	41.0	25.9	48.5	102
(WY)	1986	1988	1988	1992	1985	1989	1983	1985	1987	1986	1988	1981
MIN	16.0	21.5	11.9	6.97	3.10	2.85	4.39	5.83	3.28	5.22	6.72	7.46
(WY)	1983	1989	1989	1991	1990	1981	1984	1988	1991	1990	1985	1983
SUMMARY	STATIST	CS	FOR 1	.991 CALEN	DAR YEAR		FOR 1992 WA	TER YEAR		WATER Y	EARS 1981	- 1992
ANNUAL				5487.6			7946.8					
ANNUAL	, YNNAT I	(PAN		15.0			21.7			23.7 33.1		1986
	ANNUAL ME									16.3		1983
	DAILY ME			107	Sep 17		408	Jan 6		1500		7 1985
	DAILY ME			2.0	Jun 26		3.2			.9		21 1990
	SEVEN-DAY			2.3	Apr 25		3.4	Mar 13		1.7		15 1990
	ANEOUS PE						2170	Jan 6		14700		12 1982
	ANEOUS PE							Jan 6		20.4		12 1982
	RUNOFF ()			10880			15760			17150	_	
	RUNOFF (.80			1.15			1.2		
	RUNOFF (10.80	•		15.64			17.0	1	
	ENT EXCE			31			37			51		
	ENT EXCE			9.0			16			10		
JU PERC	ENT EXCE	s u s		3.0			4.9			3.8		

RIO GUAYANILLA BASIN

50124700 RIO GUAYANILLA AT CENTRAL RUPINA, PR

WATER-QUALITY RECORDS

LOCATION.--Lat 18°00'40", long 66°46'49", at dirt road bridge, 0.7 mi (1.1 km) from mouth, 0.9 mi (1.4 km) east of Central Rufina and 0.9 mi (1.4 km) southeast of Guayanilla.

TEMPER-

ATURE

DRAINAGE AREA. -- 22.8 mi 2 (59.1 km2).

PERIOD OF RECORD. -- Water years 1960-65, 1974 to current year.

SPR-

CIFIC CON-

DUCT-

PH WATER WHOLE FIELD

(STAND-

DIS-

CHARGE,

INST.

PERT

WATER-QUALITY DATA, WATER YEAR OCTOBER 1991 TO SEPTEMBER 1992

TUR-

BID-

OXYGEN,

DIS-SOLVED (PER-

CENT

OXYGEN,

DIS-

OXYGEN

DEMAND,

CHEM-

(HIGH

COLI-

PORM, PECAL, 0.45

UM-MP

STREP-

TOCOCCI FECAL,

(COLS.

DATE	TIME		R A	NCE	ARD UNITS)	WAT (DEG	ER	ITY (NTU	SOL	VED SAT	rur - Eon)	LEVEL (MG/L) (COL	8./	PER 100 ML)
OCT 1991	1145	12	.6	450	7.3	2	9.5	430		5.5	72		71 42	000	2600 0
JAN 1992 02	0950	0	.90	784	7.7	2	6.0	2.	5	2.4	35		20	K50	K80
PRB 19	0950	0	. 98	722	7.3	2	7.5	1.	2	3.8	48		22	K10	K10
MAY 20 JUL	1135	1	. 8	668	7.2	3	0.5	2.	5	6.2	82		24	410	350
01 SEP	1250	2	.7	255	7.2	3	2.5	1.	6	8.0	97		16	250	200
02	1300	2	.1	704	7.7	3	1.0	1.	3	7.1	92		13	260	260
		HARD- NESS TOTAL	CALCIU	MAGN M SIU DIS	M, SOI	OIUM,		DIUM AD- RP-	POTAS- SIUM, DIS-	ALKA- LINITY WAT WH TOT PET	SULI	!IDR	SULFATE DIS-		LO- DE, S-
DATE		(MG/L AS CACO3)	SOLVE (MG/L AS CA	D SOLV (MG/	RD SOI L (1	LVRD (G/L S NA)	T	ion Pio	SOLVED (MG/L AS K)	FIRLD MG/L AS CACO3	TOT (MC	T al 3/L	SOLVED (MG/L AS SO4)	SOI (M	CL)
OCT 1991 30 JAN 1992		240	51	28	1!	50		4	8.0	150	•	<0.5	49	;	28
02 FEB										260					
19 MAY		- -								220					
20 JUL		240	65	18		55		2	5.6	170	•	٥.5	71	5	4
01 SRP										180					
02		230	64	19	:	39		1	5.3	170	•		34	5	3
DATE		FLUO- RIDE, DIS- SOLVED (MG/L	SILICA DIS- SOLVE (MG/L AS	CONST D TUENT DIS SOLV	P SOI PI - I PS, SOI I- (T PRD I	LIDS, DIS- DLVED PONS PER	TOT. AT DEG SU: PEN	105 . C, S- D ed	NITRO- GEN, NITRATE TOTAL (MG/L	NITRO- GEN, NITRITE TOTAL (MG/L	NO2 - TO! (MC	IAL 3/L	NITRO- GEN, AMMONIA TOTAL (MG/L	GI ORGI TO:	FRO- EN, ANIC FAL 3/L
1001		AS F)	SIO2)	(MG/	L) I	DAY)	(M	G/L)	AS N)	AS N)	AS	N)	AS N)	AS	N)
OCT 1991 30 JAN 1992		0.20	18	4	22	2.92		978	2.06	0.740	2	. 80	0.160	•	0.84
02 FRB								3	0.070	0.770	0	840	8.70	(0.80
19 MAY								7	2.10	1.10	3 .	.20	2.80	(0.70
20 JUL		<0.10	25	3	96	1.90		4	7.53	0.070	7.	. 60	0.080	(0.72
01 SEP								18	0.66	0.540	1.	.20	3.10	:	1.3
02		0.20	30	4	06	2.30		4	8.98	0.020	9.	.00	0.070	•	0.63

K = non-ideal count

RIO GUAYANILLA BASIN 409

50124700 RIO GUAYANILLA AT CENTRAL RUFINA, PR--Continued WATER-QUALITY DATA, WATER YEAR OCTOBER 1991 TO SEPTEMBER 1992

DATE	NITRO- GEN, AM- MONIA + ORGANIC TOTAL (MG/L AS N)	NITRO- GEN, TOTAL (MG/L AS N)	NITRO- GEN, TOTAL (MG/L AS NO3)	PHOS- PHORUS TOTAL (MG/L AS P)	ARSENIC TOTAL (UG/L AS AS)	BARIUM, TOTAL RECOV- ERABLE (UG/L AS BA)	BORON, TOTAL RECOV- ERABLE (UG/L AS B)	CADMIUM TOTAL RECOV- ERABLE (UG/L AS CD)	CHRO- MIUM, TOTAL RECOV- ERABLE (UG/L AS CR)	COPPER, TOTAL RECOV- ERABLE (UG/L AS CU)
OCT 1991										
30	1.0	3.8	17	0.890	3	200	60	<1	66	150
JAN 1992 02	9.5	10	46	3.20						
FEB 19	3.5	6.7	30	2.70						
MAY										
20 JUL	0.80	8.4	-37	2.70	1	<100	150	<1	<1	20
01 SEP	4.4	5.6	25	0.54						
02	0.70	9.7	43	2.50		***				
DATE	IRON, TOTAL REĈOV- ERABLE (UG/L AS FE)	LEAD, TOTAL - RECOV- ERABLE (UG/L AS PB)	MANGA- NESE, TOTAL RECOV- ERABLE (UG/L AS MN)	MERCURY TOTAL RECOV- ERABLE (UG/L AS HG)	SELE- NIUM, TOTAL (UG/L AS SE)	SILVER, TOTAL RECOV- ERABLE (UG/L AS AG)	ZINC, TOTAL RECOV- ERABLE (UG/L AS ZN)	CYANIDE TOTAL (MG/L AS CN)	PHENOLS TOTAL (UG/L)	METHY- LENE BLUE ACTIVE SUB- STANCE (MG/L)
OCT 1991		4.5			_	_			_	
30 Jan 1992	40000	17	1200	0.10	2	<1	90	<0.010	<1	0.03
02 FRB										
19										
MAY 20	150 ~	1	210	<0.10	<1	<1	20	<0.010	<1	0.14
JUL 01										
SRP 02										
			_							
			P	RSTICIDE .	VNY TA SR 8					
DATE	TIME	PCB, TOTAL (UG/L)	ALDRIN, TOTAL (UG/L)	CHLOR- DANE, TOTAL (UG/L)	DDD, TOTAL (UG/L)	DDE, TOTAL (UG/L)	DDT, TOTAL (UG/L)	DI- AZINON, TOTAL (UG/L)	DI- ELDRIN TOTAL (UG/L)	ENDO- SULFAN, TOTAL (UG/L)
JUL 1992										
01	1250	<0.1	<0.010	<0.1	<0.010	<0.010	<0.010	0.03	<0.010	<0.010
DAT	(VG/1	er Trd ethi C Tot	AL TOT	OR, RPOX AL TOT	OR IDE LINDA AL TOTA	AL TOTA	ON, CHL	Y- PAR OR, THI AL TOT	A- ON, MIR AL TO	TAL
01		010 <0 NAP TH LEN	A -	010 <0.	010 <0.	010 <0.	01 <0	.01 <0	.01 <0	.01
DAT	(VG,	ON, CHL	OR. THA AL TOT	NB APHE AL TOTA	NR, TRI AL THIC	I- 2,4- ON TOTA	L TOT	AL TOT	AL TOT	AL
JUL 199		.01 <0	.10 <	0.1 <	1 <0	.01 <0.	01 <0	.01 <0	.01 <0	.01

410 RIO YAUCO BASIN

50125780 LAGO LUCCHETTI AT DAMSITE, PR

LOCATION.--Lat 18°05'37", long 66°51'54", Hydrologic Unit 21010004, at Antonio Lucchetti Dam on Río Yauco, 3.9 mi (6.3 km) north of Yauco.

DRAINAGE AREA. -- 17.4 mi2 (45.1 km2).

ELEVATION RECORDS

PERIOD OF RECORD. -- December 1989 to current year.

GAGE. -- Water-stage recorder. Datum of gage is mean sea level.

RRMARKS.--Lago Lucchetti was completed in 1952. The dam is on Río Yauco and is a unit of the Southwestern Puerto Rico Project. It provides 16,500 acre-feet (20.3 hm²) of usable storage for power generation and irrigation. The dam is a concrete gravity structure with a total length of 591 ft (180 m), a maximum height of 178 ft (54 m), and a maximum width at the base of 150 ft (46 m). An ungated, overflow type spillway with a clear length of 171 ft (52 m) and a crest elevation of 570 ft (174 m), occupies the central portion of the dam. The spillway was designed for a maximum capacity of 62,800 ft³/s (1,778 m³/s) at a design head of 20 ft (6 m). The dam is owned by Puerto Rico Electric Power Authority. Gage-height and precipitation setellite telemetry at station.

EXTREMES OBSERVED FOR PERIOD OF RECORD.--Maximum elevation, 571.54 ft (174.21 m), Oct. 25, 1990 minimum elevation, 519.85 ft (158.45 m), Oct. 23, 1991 but may have been less during period of no gage-height record.

EXTREMES OBSERVED FOR CURRENT YEAR.--Maximum elevation, 566.85 ft (172.77 m), June 28; minimum elevation, 519.85 ft (158.45 m), Oct. 23, but may have been less during period of no gage-height record.

Capacity Table (based on data from Puerto Rico Water Resources Authority)

Elevation, in feet	Contents, in acre-feet	Elevation, in feet	Contents, in acre-feet
519	2,275	540	5,165
520	2,385	550	7,020
525	2,965	561	9,600
527	3,255	5 6 3	10,125
530	3,695	571	12,125
532	3,975	573	12,645

ELEVATION (FERT NGVD), WATER YEAR OCTOBER 1991 TO SEPTEMBER 1992 DAILY OBSERVATION AT 24:00 VALUES

DAY	OCT	NOA	DBC	JAN	FBB	MAR	APR	MAY	JUN	JUL	AUG	SEP
1	533.15	λ	536.92	λ	A	545.65	556.43	554.28	λ	566.37	560.52	550.33
2	533.18	A	538.37	λ	A	546.34	556.43	554.25	A	565.66	A	549.12
3	531.76	λ	538.37	λ	λ	546.45	556.07	554.02	λ	565.25	λ	548.41
4	531.70	A	538.63	λ	545.47	547.78	556.00	553.67	λ	565.39	λ	548.18
5	531.70	A	538.66	A	545.43	549.42	555.96	553.63	A	565.50	A	547.47
6	531.72	λ	538.53	A	547.15	549.03	555.30	553.33	λ	565.07	λ	549.18
7	532.07	λ	538.38	λ	547.47	548.98	555.25	553.03	A	564.55	λ	554.71
8	529.78	λ	538.36	534.00	547.71	548.92	555.19	552.61	λ	564.53	λ	555.61
9	529.00	λ	538.32	536.10	546.91	549.45	555.15	552.56	564.57	564.18	λ	554.08
10	530.11	λ	538.29	537.22	546.87	550.00	553.97	552.50	563.94	564.80	λ	553.42
11	530.20	A	538.22	537.30	547.39	550.94	554.68	552.20	562.93	564.77	A	551.99
12	527.50	λ	537.42	537.66	547.99	551.57	554.47	551.89	563.17	565.21	λ	551.52
13	527.50	λ	536.95	539.58	547.98	552.87	554.35	551.18	563.04	564.41	λ	551.63
14	527.50	λ	535.80	540.32	547.93	554.17	554.45	551.01	563.64	564.91	λ	552.08
15	527.52	λ	535.74	541.46	547.87	556.10	554.46	550.13	563.75	564.21	λ	552.28
16	527.70	A	535.68	542.27	547.82	557.36	554.21	550.15	563.59	564.21	λ	550.94
17	525.08	λ	535.68	542.25	547.75	557.39	554.27	550.20	563.27	564.19	λ	549.29
18	525.03	λ	λ	542.47	546.95	557.33	554.55	548.64	563.12	564.20	A	547.88
19	525.02	λ	λ	542.48	546.89	556.93	554.88	549.44	563.41	564.58	556.53	547.17
20	524.08	λ	A	542.48	545.69	556.91	556.42	549.47	563.47	564.00	555.62	546.93
21	524.08	533.55	A	542.48	545.78	557.51	557.19	549.56	565.32	563.93	555.40	A
22	520.96	536.85	λ	542.48	545.72	557.53	557.48	549.00	565.79	563.07	555.08	λ
23	519.85	538.44	λ	543.14	545.66	557.52	557.50	553.84	566.26	561.66	554.43	A
24	A	539.09	λ	λ	545.90	557.53	557.36	555.89	566.16	561.65	553.86	λ
25	A	539.06	λ	λ	544.97	557.52	557.38	557.27	565.98	561.62	552.25	λ
26	λ	539.05	A	λ	545.17	557.49	557.38	557.35	565.99	A	552.26	A
27	A	537.47	λ	λ	545.13	557.49	557.39	λ	566.79	561.46	552.22	λ
28	λ	537.43	λ	λ	545.31	557.47	556.93	λ	566.74	561.42	552.24	λ
29	A	537.42	λ	λ	545.25	557.45	555.87	λ	λ	561.38	551.30	λ
30	A	537.01	λ	λ		557.42	555.02	λ	566.37	560.78	551.35	λ
31	λ		λ	λ		556.40		λ		560.98	550.30	
TOTAL							16671.99					
MEAN						553.71	555.73					
MAX						557.53	557.50					
ити						545.65	553. 9 7					

A No gage-height record.

RIO LOCO BASIN 411

50129700 RIO LOCO AT GUANICA, PR

WATER-QUALITY RECORDS

LOCATION.--Lat 17°58'33", long 66°54'52", 0.6 mi (1.0 km) northwest of Guánica and 1.2 mi (1.9 km) northeast of Ensenada.

DRAINAGE AREA. -- Indeterminate.

PERIOD OF RECORD. -- Water years 1975 to current year.

WATER-QUALITY DATA, WATER YEAR OCTOBER 1991 TO SEPTEMBER 1992

	•	gon	Dain,	WALLER 12	AR OCTOBE	. IJJI 10	, cerianne	K 2332		
DATE	TIME	SPE- CIFIC CON- DUCT- ANCE (US/CM)	PH WATER WHOLE FIELD (STAND- ARD UNITS)	TEMPER- ATURE WATER (DEG C)	TUR- BID- ITY (NTU)	OXYGRN, DIS- SOLVED (MG/L)	DIS- SOLVED (PER- CENT	OXYGEN DEMAND, CHEM- ICAL (HIGH LEVEL) (MG/L)	COLI- FORM, FECAL, 0.45 UM-MF (COLS./ 100 ML)	STREP- TOCOCCI FECAL, (COLS. PER 100 ML)
OCT 1991 30	1025	9700	7.5	30.5	6.4	1.8	24	140	210	230
DEC 18	1345	6900	7.7	25.5	2.6	3.1	39	120	K80	360
FEB 1992 19	0830	10000	7.2	25.5	2.2	1.9	21	190	K140	460
MAY										
20 Jun	0925	17000	7.3	28.0	6.5	1.9	24	18	580	460
26 Sep	0845	9500	7.7	29.0	4.0	0.7	18	200	290	310
02	1120	44000	7.8	31.0	2.0	1.8	20	110	230	K145
DATE	HARD- NESS TOTAL (MG/L	CALCIUM DIS- SOLVED	MAGNE- SIUM, DIS- SOLVED	SODIUM, DIS- SOLVED	SODIUM AD- SORP- TION	SIUM, DIS- SOLVED	ALKA- LINITY WAT WH TOT FET FIELD	SULFIDE	SULFATE DIS- SOLVED	CHLO- RIDE, DIS- SOLVED
DATE	AS CACO3)	(MG/L AS CA)	(MG/L AS MG)	(MG/L AS NA)	RATIO	(MG/L AS K)	MG/L AS CACO3	(MG/L AS S)	(MG/L AS SO4)	(MG/L AS CL)
OCT 1991	970	92	180	1400	20	50	250	<0.5	420	2600
DEC 18 FRB 1992							190			
19							260			
MAY 20	190	35	24	130	4	7.3	110	<0.5	46	220
JUN 26							255			
SEP 02	1000	94	190	1500	20	57	220		460	2700
02	1000	34	190	1500	20	57	220		460	2700
	FLUO- RIDE,	SILICA, DIS-	SOLIDS, SUM OF CONSTI-	RESIDUE TOTAL AT 105	NITRO- GEN,	NITRO- GEN,	NITRO- GEN,	NITRO- GEN,	NITRO- GEN,	NITRO- GEN, AM- MONIA +
	DIS-	SOLVED	TUENTS,	DEG. C,	NITRATE	NITRITE		AMMONIA	ORGANIC	ORGANIC
DATE	SOLVED (MG/L	(MG/L As	DIS- SOLVED	SUS- PENDED	TOTAL (MG/L	TOTAL (MG/L	TOTAL (MG/L	TOTAL (MG/L	TOTAL (MG/L	TOTAL (MG/L
DAIG	AS F)	SIO2)	(MG/L)	(MG/L)	AS N)	AS N)	AS N)	AS N)	AS N)	AS N)
(00950)	(00955)									
OCT 1991										
30	1.1	28	4920	30		<0.010	0.085	0.050	0.45	0.50
18 FEB 1992				5		<0.010	0.057	0.030	0.27	0.30
19 MAY			- -	18		<0.010	0.082	0.090	0.31	0.40
20	<0.10	22	550	<1	0.076	0.010	0.086	0.040	0.26	0.30
JUN 26				28	0.087	0.010	0.097	0.060	0.84	0.90
02	0.80	27	5180	26		<0.010	0.098	0.050	0.25	0.30

K = non-ideal count

RIO LOCO BASIN

50129700 RIO LOCO AT GUANICA, PR--Continued WATER-QUALITY DATA, WATER YEAR OCTOBER 1991 TO SEPTEMBER 1992

DA OCT 19	.TE	NITRO- GEN, TOTAL (MG/L AS N)	NITRO- GEN, TOTAL (MG/L AS NO3)	PHOS- PHORUS TOTAL (MG/L AS P)	ARSEN TOTA (UG/ AS A	TO RIC RI L EI 'L (1	RIUM, DTAL BCOV- RABLE UG/L S BA)	BORG TOTA RECG ERAL (UG/ AS I	AL TOV- RISLE RIVL (1	DMIUM OTAL BCOV- RABLE UG/L S CD)	CHRO- MIUM, TOTAL RECOV- ERABLE (UG/L AS CR)	COPPER, TOTAL RECOV- ERABLE (UG/L AS CU)	IRON, TOTAL RECOV- ERABLE (UG/L AS FE)
30		0.59	2.6	0.150		2	200	7	700	<1	5	60	1000
DEC		0.26											
18 FEB 19		0.36	1.6	0.060		•			-				
19	•	0.48	2.1	0,150					-				
MAY 20		0.39	1.7	0.030		<1	<100		70	<1	3	10	520
JUN 26		1.0		0 070									
SEP		1.0	4.4	0.270		•			-				
02	•	0.40	1.8	0.100		•			-				
	DATE	LEAE TOTA RECO ERAE (UG/ AS P	L TOT V- REC LE ERA L (UG	E, MERC AL TOT OV- REC BLE ERA /L (UG	AL OV- BLE /L	SRLB- NIUM, TOTAL (UG/L AS SE)	SILVE TOTA RECO ERAE (UG/ AS A	L OV- SLE L	ZINC, TOTAL RECOV- ERABLE (UG/L AS ZN)	CYANII TOTAI (MG/I AS CI	PHEN TOT	al sta	IAE OB WB
oc	T 1991												
DE	30		<1	140 <0	.10	<1		<1	<10	<0.03	LO	<1 0	.32
	18		-		-						-		-
	B 1992		_		_						_		_
М	Y												
JU	20		<1	80 <0	.10	<1		<1	<10	<0.03	LO	<1 0	.06
	26		_		-						-		-
SE	02		_	- -	_						_		_
					PORTO	DR ANA	vepe						
					B511C1	DE ANA	LI SES						
DA	lte	TIME	PCB, TOTAL (UG/L)	ALDRIN, TOTAL (UG/L)	CHLC DANE TOTA (UG/I	8, 1 AL T C	DDD, DTAL JG/L)	DDI TOTA (UG/	L T	DDT, A OTAL UG/L)	DI- AZINON, TOTAL (UG/L)	DI- ELDRIN TOTAL (UG/L)	ENDO- SULFAN, TOTAL (UG/L)
JUN 19 26		0845	<0.1	<0.010	<0).1 <	0.010	<0.6	010 <	0.010	<0.01	<0.010	<0.010
.77	DATE	ENDRI WATE UNFLI REC (UG/I	R RD ETHI TOT	AL TOT	OR, E	HEPTA- CHLOR POXIDE TOTAL (UG/L)	LINDA TOTA (UG/	I.	MALA- THION, TOTAL (UG/L)	METH- OXY- CHLOI TOTAI (UG/)	PAR. THI	A- ON, MIR AL TO	EX, TAL /L)
30	N 1992 26	<0.0	10 <0	.01 <0.	010	<0.010	<0.0	10	<0.01	<0.0	01 <0	.01 <0	.01
	DATE	PARA THIC TOTA (UG/	N, CHL	A- ES, Y- PE OR. THA AL TOT		TOX- APHENB, TOTAL (UG/L)	TOTA TRI THIC (UG/	- W	2,4-D, TOTAL (UG/L)	2,4,5 TOTAI (UG/I	L TOT	AL TOT	
JT	Л 1992												
	26	<0.	01 <0	.10 <	0.1	<1	<0.	01	0.11	<0.0	01 <0	.01 <0	.01




Figure 25:-Río Guanajibo basin.

414

RIO GUANAJIBO BASIN

50131990 RIO GUANAJIBO AT HWY 119 AT SAN GERMAN, PR

LOCATION.--Lat 18°05'06", long 67°02'02", Hydrologic Unit 21010003, on right bank, at bridge on Hwy 119, 0.6 mi (1.0 km) southwest of junction of Highways 119 and 2, 0.22 mi (0.35 km) northeast of junction of Highways 119 and 102, 0.74 mi (1.19 km) east from public Plaza of San Germán.

DRAINAGE AREA. -- 34.6 mi 2 (89.6 km2).

WATER-DISCHARGE RECORDS

PERIOD OF RECORD. -- April 1991 to current year.

GAGE .-- Water-stage recorder. Elevation of gage is 148 ft (45.0 m), from topographic map.

REMARKS.--Records fair except those for estimated daily discharges, which are poor. Gage-height and precipitation satellite telemetry at station.

satel	lite tele	metry at	station.			4.00						
	DIS	CHARGE,	CUBIC FEET	PER SEC	COND, WATER		TOBER 199	1 TO SEPT	EMBER 199	2		
DAY	OCT	NOV	DRC	JAN	FEB	MAR	APR	MAY	JUN	JUL	AUG	SEP
1	21	26	12	5.8	5.1	e3.6	6.7	e7.0	35	2.0	5.7	12
2	15	19	11	5.7	5.3	e4.2	6.8	e5.6	30	2.3	4.3	29
3	12	16	10	5.6	5.1	e3.7	10	e4.3	25	3.0	4.3	59
4	10	14	10	5.4	4.8	e3.7	4.4	e3.4	23	2.7	8.6	58
5	11	14	13	6.8	4.7	e3.6	3.7	e2.9	18	2.4	46	60
6	26 42	19 16	11 16	817 73	5.5 6.2	e3.3	9.1	e2.4 e2.0	15 13	2.0	89 47	162 206
8	22	15	12	34	5.6	e3.3	4.7	e1.8	11	4.7	32	80
9	17	14	12	22	5.2	e3.0	4.9	e1.5	32	10	23	46
10	15	13	10	16	4.7	e2.9	4.4	e1.7	29	12	25	30
11	14	13	8.8	14	4.2	e3.0	3.4	e1.5	15	6.3	17	50
12	13	12	8.3	14	4.2	e3.0	3.2	e1.9	17	11	16	29
13	13	12	7.8	12	4.4	3.2	2.8	e2.4	13 9.1	22 108	21 13	44 52
14 15	12 12	13 12	7.9 8.0	9.5	4.3	3.4	2.6	e2.7	6.9	93	15	44
16	11	14	6.9	9.0	4.2	3.1	10	e4.1	6.0	37	15	28
17	9.8	15	6.1	8.7	3.9	2.8	20	e7.6	5.5	14	8.2	29
18	8.7	27	6.0	8.3	3.7	2.8	7.7	e5.6	4.9	6.4	6.7	34
19 20	22 32	28 16	5.9 6.4	7.9	e3.6 e3.5	2.7	12 74	e3.0 e21	4.5	15 38	6.3 5.8	35 126
	19							e8.2	5.9	13	41	52
21 22	71	16 15	6.7	7.2 6.8	e3.5 e3.7	4.3	41 e35	24	4.5	3.8	58	42
23	42	13	5.6	6.4	e3.6	2.8	e20	539	3.6	2.4	39	38
24	20	13	5.4	6.1	e3.5	2.3	e15	199	3.4	2.0	25	29
25	15	18	5.6	6.1	e3.7	2.3	e11	140	3.3	1.8	16	41
26	13	15	5.6	6.1	e3.8	2.4	e8.8	120	3.2	2.0	13	29
27	12	15	5.8	6.1	e3.7	2.5	e7.0	87	3.1	2.0	11	29
28	11	15	5.8	5.2	e3.6	2.6	e5.6	68	3.1	2.0	11	36
29	11	13	6.3	4.8	e3.6	5.6	e4.6	56	2.8	1.9	23	46 57
30 31	38 42	13	6.1	4.8		3.3	e4.6	48	2.3	2.3 7.3	21 16	
TOTAL	632.5	474	254.5	1157.6	125.2	109.1	349.6	1414.9	352.4	434.8	682.9	1612
MEAN	20.4	15.8	8.21	37.3	4.32	3.52	11.7	45.6	11.7	14.0	22.0	53.7
MAX	71	28	16	817	6.2	12	74	539	35	108	89	206
MIN	8.7	12	5.4	4.8	3.5	2.3	2.4	1.5	2.3	1.8	4.3	12
MED	15	15	6.9	7.2	4.2	3.1	6.7	5.6	6.4	3.8 862	16 1350	43 3200
AC-FT CFSM	1250 .59	940 .46	505 .24	2300 1.08	.12	216 .10	693	2810 1.32	.34	.41	.64	1.55
IN.	.68	.51	.27	1.24	.13	. 12	.38	1.52	.38	.47	.73	1.73
e Bi	stimated											
STATTS.	TICS OF M	ONTHILY ME	BAN DATA FO	OP WATER	VRADE 199	1 - 1992	RV WATER	R VRAR (WY	2)			
										44.0	01.0	22.2
MEAN	20.4	15.8	8.21	37.3	4.32	3.52	11.7	39.2	8.38	14.2	21.8	33.3 53.7
MAX (WY)	20.4 1992	15.8 1992	8.21 1992	37.3 1992	4.32 1992	3.52 1992	11.7 1992	45.6 1992	1992	1991	1992	1992
MIN	20.4	15.8	8.21	37.3	4.32	3.52	11.7	32.8	5.01	14.0	21.7	12.9
(WY)	1992	1992	1992	1992	1992	1992	1992	1991	1991	1992	1991	1991
SUMMAR	Y STATIST	ics			FOR 1	992 WATER	R YEAR			WATER YE	ARS 1991	- 1992
ANNUAL						99.5						
ANNUAL						20.8				20.8		
	T ANNUAL I	MRAN								20.8		1992
	ANNUAL M									20.8	142.6	1992
	T DAILY M	7777					Jan 6			817		6 1992
	DAILY ME		wi:				May 9			1.5		9 1992 6 1992
	SEVEN-DAY				66		Jan 6			6610		6 1992
	TANEOUS P						Jan 6			13.23		6 1992
	RUNOFF (150		-			15040		
ANNUAL	RUNOFF (CFSM)				. 60				.60		
	RUNOFF (8.17				8.15		
	CENT EXCE					42				10		
	CENT EXCE					8.8				3.2		
JU FER	CDITE BACK					4.0						

50133600 RIO GUANAJIBO NEAR SAN GERMAN, PR

WATER-QUALITY RECORDS

LOCATION.--Lat 18°07'18", long 67°03'56", at bridge on Highway 347, 2.2 mi (3.5 km) northwest of San Germán. DRAINAGE ARRA.--45.5 mi² (117.8 km²).

PERIOD OF RECORD.--Water years 1979 to current year.

WATER QUALITY DATA, WATER YEARS OCTOBER 1991 TO SEPTEMBER 1992

DATE	TIME	DIS- CHARGE, INST. CUBIC FEET PER SECOND	SPR- CIFIC CON- DUCT- ANCR (US/CM)	PH WATER WHOLE FIELD (STAND- ARD UNITS)	TEMPER- ATURE WATER (DEG C)	TUR- BID- ITY (NTU)	OXYGEN, DIS- SOLVED (MG/L)	CENT SATUR-	OXYGEN DEMAND, CHEM- ICAL (HIGH LEVEL) (MG/L)	COLI- FORM, FECAL, 0.45 UM-MF (COLS./ 100 ML)	STREP- TOCOCCI FECAL, (COLS. PER 100 ML)
OCT 1991											
11 DEC	1135	4.1	646	7.9	27.5	40	5.3	19	13	530	480
20 FRB 1992	0840	5.6	660	8.0	24.5	4.2	5.2	38	19	K140	2200
26 May	1430	5.9	720	7.5	29.0	0.80	6.0	72	18	10	230
19 JUN	1130	4.6	517	7.1	28.0	2.3	4.3	55	23	K180	390
26 AUG	0800	8.0	665	7.7	24.5	0.70	3.1	44	13	430	210
13	1030	8.7	556	7.4	27.0	2.0	3.0	41	<10	2000	280
	NI	ARD- SSS CALC		UM, SODI	OM, A	AD- S	TAS- LI IUM, WA	LKA- NITY T WH T FRT SUI		FATE RI	ILO- IDR,

DATE	HARD- NESS TOTAL (MG/L AS CACO3)	CALCIUM DIS- SOLVED (MG/L AS CA)	MAGNE- SIUM, DIS- SOLVED (MG/L AS MG)	SODIUM, DIS- SOLVED (MG/L AS NA)	SODIUM AD- SORP- TION RATIO	POTAS- SIUM, DIS- SOLVED (MG/L, AS K)	ALKA- LINITY WAT WH TOT FRT FIRLD MG/L AS CACO3	SULFIDE TOTAL (MG/L AS S)	SULFATE DIS- SOLVED (MG/L AS SO4)	CHLO- RIDE, DIS- SOLVED (MG/L AS CL)
OCT 1991							•			
11 DRC	220	23	39	43	1	3.1	215	<0.5	64	47
20							120			
FRB 1992 26							230			
MAY										
19 JUN	200	22	35	31	1	3.2	190	<0.5	31	42
26							240			
λUG 13	210	22	37	27	0.8	2.6	190		37	35
DATE	FLUO- RIDE, DIS- SOLVED (MG/L AS F)	SILICA, DIS- SOLVED (MG/L AS SIO2)	SOLIDS, SUM OF CONSTI- TUENTS, DIS- SOLVED (MG/L)	SOLIDS, DIS- SOLVED (TONS PER DAY)	RESIDUR TOTAL AT 105 DEG. C, SUS- PENDED (MG/L)	NITRO- GEN, NITRATE TOTAL (MG/L AS N)	NITRO- GEN, NITRITE TOTAL (MG/L AS N)	NITRO- GEN, NO2+NO3 TOTAL (MG/L AS N)	NITRO- GEN, AMMONIA TOTAL (MG/L AS N)	NITRO- GEN, ORGANIC TOTAL (MG/L AS N)
OCT 1991										
11 DEC	0.30	34	382	4.25	6	2.10	0.200	2.30	0.490	0.51
20					1	2.54	0.160	2.70	0.340	0.46
FRB 1992 26					1	1.46	0.040	1.50	0.060	0.34
MAY 19 JUN	<0.10	31	309	3.84	<1	1.47	0.130	1.60	0.150	0.45
26 AUG					7	2.07	0.230	2.30	0.260	0.44
13	0.10	32	302	7.09	1	1.33	0.270	1.60	1.00	0.50
	1									

R = non-ideal count

50133600 RIO GUANAJIBO NEAR SAN GERMAN, PR--Continued WATER QUALITY DATA, WATER YEAR OCTOBER 1991 TO SEPTEMBER 1992

DATE	NITRO- GEN, AM- MONIA + ORGANIC TOTAL (MG/L AS N)	NITRO- GEN, TOTAL, (MG/L AS N)	NITRO- GEN, TOTAL (MG/L AS NO3)	PHOS- PHORUS TOTAL (MG/L AS P)	ARSENIC TOTAL (UG/L AS AS)	BARIUM, TOTAL RECOV- ERABLE (UG/L AS BA)	BORON, TOTAL RECOV- ERABLE (UG/L AS B)	CADMIUM TOTAL RECOV- ERABLE (UG/L AS CD)	CHRO- MIUM, TOTAL RECOV- ERABLE (UG/L AS CR)	COPPER, TOTAL RECOV- ERABLE (UG/L AS CU)
OCT 1991										
11 DBC	1.0	3.3	15	1.50	<1	100	650	<1	4	20
20 FRB 1992	0.80	3.5	15	1.40						
26 May	0.40	1.9	8.4	1.20						
19	0.60	2.2	9.7	0.770	1	<100	90	<1	2	30
26	0.70	3.0	13	0.840						
13	1.5	3.1	14	0.670						
DATE	IRON, TOTAL RECOV- ERABLE (UG/L AS FE)	LBAD, TOTAL RECOV- ERABLE (UG/L AS PB)	MANGA- NESE, TOTAL RECOV- ERABLE (UG/L AS MN)	MERCURY TOTAL RECOV- ERABLE (UG/L AS HG)	SELE- NIUM, TOTAL (UG/L AS SE)	SILVER, TOTAL RECOV- ERABLE (UG/L AS AG)	ZINC, TOTAL RECOV- ERABLE (UG/L AS ZN)	CYANIDE TOTAL (MG/L AS CN)	PHENOLS TOTAL (UG/L)	METHY- LENE BLUE ACTIVE SUB- STANCE (MG/L)
OCT 1991 11 DEC	520	7	80	<0.10	<1	<1	30	<0.010	1	0.07
20										
26										
19	220	<1	70	<0.10	<1	<1	30	<0.010	2	0.08
26 AUG										

FEB 1992 26 MAY 19 JUN										

50136400 RIO ROSARIO NEAR HORMIGUEROS, PR

LOCATION.--Lat 18°09'36", long 67°05'08", Hydrologic Unit 21010003 at bridge on Highway 348, 0.5 mi (0.8 km) southwest of Rosario plaza.

DRAINAGE AREA. -- 18.3 mi2 (47.4 km2).

WATER-DISCHARGE RECORDS

PERIOD OF RECORD. -- October 1985 to current year.

GAGE .-- Water-stage recorder. Elevation of gage is 50.0 ft (15.2 m), from topographic map.

RRMARKS.--Records fair except those for estimated daily discharges, which are poor. Gage-height and precipitation satellite telemetry at station.

	DIS	CHARGE,	CUBIC FEET		OND, WATER DAILY MEAN		TOBER 1991	TO SEPTI	MBRR 199	2		
DAY	OCT	NOV	DEC	Jan	PBB	MAR	APR	MAY	JUN	JOL	AUG	SEP
1	59	36	11	12	9.3	7.5	27	6.5	27	6.8	17	24
2	34	23	11	10	8.7	7.9	19	6.3	18	7.4	13	71
3	27	20	11	9.0	8.8	8.1	11	5.2	14	13	12	81
4	23	19	12	8.8	9.1	8.2	7.5	4.8	12	7.8	113	198
5	21	21	11	9.7	9.2	8.7	6.1	4.5	10	7.5	94	107
6	42	20	11	163	11	7.9	5.4	4.4	9.5	7.1	148	158
7	68	18	10	27	14	7.7	5.6	4.1	8.9	7.0	69	135
8	117	17	10	16	11	9.5	6.7	4.2	9.8	7.5	167	122
9 10	65 36	16 16	9.8 9.7	13 12	9.1 8.7	7.3 7.5	8.6 11	3.9 4.1	28 35	13 13	189 169	109 84
11	28	16	10	13	9.3	7.4	8.1	4.1	18	14	89	145
12	25	15	9.4	14	8.7	7.3	6.8	4.4	13	10	77	100
13	23	15	9.3	12	8.4	7.3	6.6	4.7	11	79	76	281
14	26	15	9.0	11	8.4	7.0	5.5	4.6	10	129	51	199
15	28	15	8.7	11	8.7	6.9	35	5.5	10	91	54	128
16	21	15	8.8	11	8.3	6.9	46	9.7	9.8	50	37	91
17	19	15	9.5	12	8.2	7.1	27	8.4	9.7	28	31	71
18	20	15	9.7	11	8.1	8.6	11	5.4	9.5	15	27	58
19	27	14	9.9	11	7.9	7.7	9.8	47	9.2	105	24	79
20	32	13	10	11	7.6	7.3	43	33	8.5	93	23	225
21	32	13	13	11	7.7	7.3	45	10	8.7	28	23	136
22	26	12	9.7	11	7.6	7.2	27	15	8.7	18	25	187
23	21	16	9.7	11	7.5	6.4	12	275	8.0	15	22	136
24	19	15	9.7	e 10	7.4	6.2	8.3	196	7.9	68	20	76
25	19	13	9.5	e10	7.3	6.5	6.6	85	7.8	31	37	71
26	18	13	9.3	e10	7.1	6.7	6.0	45	7.8	17	28	58
27	17	13	9.3	e10	7.0	8.3	5.8	26	7.5	13	19	47
28	31	12	9.2	e10	6.9	21	5.2	18	7.5	12	17	113
29	26	12	9.1	e10	7.0	15	4.9	18	7.7	11	30	81
30	27	11	9.1	9.5		16	6.0	30	7.1	30	73	502
31	53		9.1	9.4		60		40		23	41	
TOTAL	1030	484	307.5	509.4	248.0	314.4	433.5	932.8	359.6	970.1	1815	3873
MEAN	33.2	16.1	9.92	16.4	8.55	10.1	14.4	30.1	12.0	31.3	58.5	129
MAX	117	36	13	163	14	60	46	275	35	129	189	502
MIN	17	11	8.7	8.8	6.9	6.2	4.9	3.9	7.1	6.8	12	24
AC-FT	2040	960	610	1010	492	624	860	1850	713	1920	3600	7680
CPSM	1.82	. 88	.54	. 90	.47	. 55	.79	1.64	. 66	1.71	3.20	7.05
IN.	2.09	. 98	. 63	1.04	.50	. 64	.88	1.90	.73	1.97	3.69	7.87
e Rs	timated											
STATIST	ICS OF MO	NTHLY M	RAN DATA FO	R WATER	TRARS 1986	- 1992,	BY WATER	YEAR (WY)			
100111			22.5	24 -	45.5					42.4		
MBYN	105	74.2	30.6	20.5	15.2	22.3	23.5	4 0.5 99.1	44.3	43.8	61.2 102	94.1 143
MAX	206	117	43.2	31.8	19.1	77.0	57.7 1989		79.0 1989	75.2 1989	1989	1989
(WY) MIN	1986 33.2	1990 16.1	1990 9.92	1990 15.9	1987 8.55	1989 10.1	11.9	1986 15.8	12.0	23.2	25.1	32.7
(MA)	1992	1992	1992	1991	1992	1992	1991	1990	1992	1990	1991	1986
SUMMARY	STATISTI	CS.	FOR 1	991 CALE	NDAR YEAR	F	OR 1992 WA	TER YEAR		WATER YE	ARS 1986	- 1992
ANNUAL	TOTAL			9427.0			11277.3					
ANNUAL	MEAN			25.8			30.8			48.1		
	' ANNUAL M									67.9		1989
	ANNUAL ME			_			_			30.8		1992
	DAILY ME			362			502	Sep 30		1550		7 1985
	DAILY MEA		n.,	6.8				May 9		3.9		9 1992
	SEVEN-DAY			7.5	Apr 24		4.2			4.2		6 1992
	'ANEOUS PE						5640	Sep 30 Sep 30		7480 13.64		14 1988
	ANEOUS LO		-6				3.7			3.7		9 1992
	RUNOFF (A			18700			22370			34830		//4
	RUNOFF (C			1.4	1		1.68			2.63	l	
	RUNOFF (I			19.1			22.92			35.70		
	BNT BXCEE			52			81			112		
	ENT BACES			16			12			26		
90 PERC	ENT EXCRE	EDS		9.8			6.9			10		

50136400 RIO ROSARIO NEAR HORMIGUEROS, PR--Continued

WATER-QUALITY RECORDS

PERIOD OF RECORD. -- WATER YEARS 1979 TO CURRENT YEAR.

PERIOD OF DAILY RECORD. --

SUSPENDED-SEDIMENT DISCHARGE: OCTOBER 1985 TO SEPTEMBER 1986

INSTRUMENTATION .-- US D-49 SEDIMENT SAMPLER SINCE OCTOBER 1985. AUTOMATIC SEDIMENT SAMPLER SINCE 1986

REMARKS.--sediment samples were collected by a local observer once daily during low flow and more than once daily during high flow events for concentration and particle size analyses. Sediment samples are collected periodically by survey staff. Automatic sediment sampler set to collect samples above 200 cfs.

EXTREMES FOR PERIOD OF DAILY RECORD.-SEDIMENT CONCENTRATIONS: Maximum daily mean, 8,150 mg/L October 7, 1985; Minimum daily mean, 1 mg/L

January 28, 1990.
SEDIMENT LOADS: Maximum daily, 74,700 tons (67,800 tonnes) October 7, 1985; Minimum daily, 0.05 ton (0.04 Tonne) several days.

EXTREMES FOR CURRENT YEAR.-SEDIMENT CONCENTRATIONS: Maximum daily mean, 3,540 mg/L September 30, 1992; Minimum daily mean, 2.0 mg/L

several days.

SEDIMENT LOADS: Maximum daily, 24,300 tons (22,000 tonnes) September 30, 1992; Minimum daily 0.04 ton (0.08 tonne) few days.

WATER-QUALITY DATA, WATER YEAR OCTOBER 1991 TO SEPTEMBER 1992

DATE	TIME	DIS- CHARGE, INST. CUBIC FEET PER SECOND	SPE- CIFIC CON- DUCT- ANCE (US/CM)	PH WATER WHOLE FIELD (STAND- ARD UNITS)	TEMPER- ATURE WATER (DEG C)	TUR- BID- ITY (NTU)	OXYGEN, DIS- SOLVED (MG/L)	OXYGEN, DIS- SOLVED (PER- CENT SATUR- ATION)	OXYGEN DEMAND, CHEM- ICAL (HIGH LEVEL) (MG/L)	COLI- FORM, FECAL, 0.45 UM-MF (COLS./ 100 ML)	STREP- TOCOCCI FECAL, (COLS. PER 100 ML)	HARD- NESS TOTAL (MG/L AS CACO3)
OCT 1991												
11	0915	30	268	8.3	23.5	2.5	8.4	72	<10	4200	5000	130
19 FEB 1992	1150	9.8	291	7.3	23.0	1.5	9.7	89	<10	310	K110	
26 MAR	1310	7.3	287	8.4	25.5	1.1	4.7	64	<10	70	60	
31	1355	6.1	255	7.0	26.0	18	7.4	53	<10	K760	K410	110
JUN 25 AUG	1230	7.6	260	8.0	28.0	9.4	9.1	81	<10	580	430	
14	0825	47	270	7.6	23.5	15	8.0	72	<10	460	660	120
DATE	CALCIUM DIS- SOLVED (MG/L AS CA)	MAGNE- SIUM, DIS- SOLVED (MG/L AS MG)	SODIUM, DIS- SOLVED (MG/L AS NA)	SODIUM AD- SORP- TION RATIO	POTAS- SIUM, DIS- SOLVED (MG/L AS K)	ALKA- LINITY WAT WH TOT FET FIELD MG/L AS CACO3	SULFIDE TOTAL (MG/L AS S)	SULFATE DIS- SOLVED (MG/L AS SO4)	CHLO- RIDE, DIS- SOLVED (MG/L AS CL)	FLUO- RIDE, DIS- SOLVED (MG/L AS F)	SILICA, DIS- SOLVED (MG/L AS SIO2)	SOLIDS, SUM OF CONSTI- TUENTS, DIS- SOLVED (MG/L)
OCT 1991												
11 DEC	22	18	7.0	0.3	1.8	130	<0.5	6.8	13	<0.10	29	176
19						52						
FEB 1992 26 MAR						120						
31 JUN	21	15	9.9	0.4	1.4	100	<0.5	11	13	<0.10	27	158
25						135						
AUG												

K = non-ideal count

50136400 RIO ROSARIO NEAR HORMIGUEROS, PR--Continued

WATER QUALITY DATA, WATER YEAR OCTOBER 1991 TO SEPTEMBER 1992

DATE	SOLIDS, DIS- SOLVED (TONS PER DAY)	RESIDUE TOTAL AT 105 DEG. C, SUS- PENDED (MG/L)	NITRO- GEN, NITRATE TOTAL (MG/L AS N)	NITRO- GEN, NITRITE TOTAL (MG/L AS N)	NITRO- GEN, NO2+NO3 TOTAL (MG/L AS N)	NITRO- GEN, AMMONIA TOTAL (MG/L AS N)	NITRO- GEN, AM- MONIA + ORGANIC TOTAL (MG/L AS N)	PHOS- PHORUS TOTAL (MG/L AS P)	ARSENIC TOTAL (UG/L AS AS)	BARIUM, TOTAL RECOV- ERABLE (UG/L AS BA)	BORON, TOTAL RECOV- ERABLE (UG/L AS B)	CADMIUM TOTAL RECOV- ERABLE (UG/L AS CD)
OCT 1991												
11	14.3	<1		<0.010	0.320	<0.010	<0.20	0.010	<1	<100	40	<1
19 PEB 1992		1	0.480	0.010	0.490	0.010	<0.20	0.040				
26		1		<0.010	0.200	0.020	<0.20	0.040				
MAR 31	2.59	12	0.640	0.020	0.660	0.050	<0.20	0.050	<1	<100	<10	<1
JUN 25		20	0.210	0.010	0.220	0.020	<0.20	0.030				
AUG 14	20.6	25	0.710	0.010	0.720	0.030	<0.20	0.020				
DATE	CHRO- MIUM, TOTAL RECOV- ERABLE (UG/L AS CR)	COPPER, TOTAL RECOV- ERABLE (UG/L AS CU)	IRON, TOTAL RECOV- ERABLE (UG/L AS FE)	LEAD, TOTAL RECOV- ERABLE (UG/L AS PB)	MANGA- NESE, TOTAL RECOV- ERABLE (UG/L AS MN)	MERCURY TOTAL RECOV- ERABLE (UG/L AS HG)	SELE- NIUM, TOTAL (UG/L AS SE)	SILVER, TOTAL RECOV- ERABLE (UG/L AS AG)	ZINC, TOTAL RECOV- ERABLE (UG/L AS ZN)	CYANIDE TOTAL (MG/L AS CN)	PHENOLS TOTAL (UG/L)	METHY- LENE BLUE ACTIVE SUB- STANCE (MG/L)
OCT 1991	MIUM, TOTAL RECOV- ERABLE (UG/L AS CR)	TOTAL RECOV- ERABLE (UG/L AS CU)	TOTAL RECOV- ERABLE (UG/L AS FE)	TOTAL RECOV- ERABLE (UG/L	NESE, TOTAL RECOV- ERABLE (UG/L AS MN)	TOTAL RECOV- ERABLE (UG/L AS HG)	NIUM, TOTAL (UG/L AS SE)	TOTAL RECOV- ERABLE (UG/L AS AG)	TOTAL RECOV- ERABLE (UG/L AS ZN)	TOTAL (MG/L AS CN)	TOTAL (UG/L)	LENE BLUE ACTIVE SUB- STANCE (MG/L)
OCT 1991 11 DEC	MIUM, TOTAL RECOV- ERABLE (UG/L AS CR)	TOTAL RECOV- ERABLE (UG/L	TOTAL RECOV- ERABLE (UG/L	TOTAL RECOV- ERABLE (UG/L AS PB)	NESE, TOTAL RECOV- ERABLE (UG/L	TOTAL RECOV- ERABLE (UG/L	NIUM, TOTAL (UG/L	TOTAL RECOV- ERABLE (UG/L	TOTAL RECOV- ERABLE (UG/L	TOTAL (MG/L	TOTAL	LENE BLUE ACTIVE SUB- STANCE
OCT 1991 11 DEC 19 FEB 1992	MIUM, TOTAL RECOV- ERABLE (UG/L AS CR)	TOTAL RECOV- ERABLE (UG/L AS CU)	TOTAL RECOV- ERABLE (UG/L AS FE)	TOTAL RECOV- ERABLE (UG/L AS PB)	NESE, TOTAL RECOV- ERABLE (UG/L AS MN)	TOTAL RECOV- ERABLE (UG/L AS HG)	NIUM, TOTAL (UG/L AS SE)	TOTAL RECOV- ERABLE (UG/L AS AG)	TOTAL RECOV- ERABLE (UG/L AS ZN) <10	TOTAL (MG/L AS CN) <0.010	TOTAL (UG/L)	LENE BLUE ACTIVE SUB- STANCE (MG/L)
OCT 1991 11 DEC 19 FEB 1992 26	MIUM, TOTAL RECOV- ERABLE (UG/L AS CR)	TOTAL RECOV- ERABLE (UG/L AS CU)	TOTAL RECOV- ERABLE (UG/L AS FE)	TOTAL RECOV- ERABLE (UG/L AS PB)	NESE, TOTAL RECOV- ERABLE (UG/L AS MN)	TOTAL RECOV- ERABLE (UG/L AS HG)	NIUM, TOTAL (UG/L AS SE)	TOTAL RECOV- ERABLE (UG/L AS AG)	TOTAL RECOV- ERABLE (UG/L AS ZN)	TOTAL (MG/L AS CN) <0.010	TOTAL (UG/L)	LENE BLUE ACTIVE SUB- STANCE (MG/L)
OCT 1991 11 DEC 19 FEB 1992 26 MAR 31	MIUM, TOTAL RECOV- ERABLE (UG/L AS CR)	TOTAL RECOV- ERABLE (UG/L AS CU)	TOTAL RECOV- ERABLE (UG/L AS FE)	TOTAL RECOV- ERABLE (UG/L AS PB)	NESE, TOTAL RECOV- ERABLE (UG/L AS MN)	TOTAL RECOV- ERABLE (UG/L AS HG)	NIUM, TOTAL (UG/L AS SE)	TOTAL RECOV- ERABLE (UG/L AS AG)	TOTAL RECOV- ERABLE (UG/L AS ZN) <10	TOTAL (MG/L AS CN) <0.010	TOTAL (UG/L)	LENE BLUE ACTIVE SUB- STANCE (MG/L)
OCT 1991 11 DEC 19 FEB 1992 26	MIUM, TOTAL RECOV- ERABLE (UG/L AS CR)	TOTAL RECOV- ERABLE (UG/L AS CU)	TOTAL RECOV- ERABLE (UG/L AS FE)	TOTAL RECOV- ERABLE (UG/L AS PB)	NESE, TOTAL RECOV- ERABLE (UG/L AS MN)	TOTAL RECOV- ERABLE (UG/L AS HG)	NIUM, TOTAL (UG/L AS SE)	TOTAL RECOV- ERABLE (UG/L AS AG)	TOTAL RECOV- ERABLE (UG/L AS ZN)	TOTAL (MG/L AS CN) <0.010	TOTAL (UG/L)	LENE BLUE ACTIVE SUB- STANCE (MG/L)

RIO GUANAJIBO BASIN 50136400 RIO ROSARIO NEAR HORMIGUEROS, PR--Continued

SEDIMENT DISCHARGE, SUSPENDED (TONS/DAY), WATER YEAR OCTOBER 1991 TO SEPTEMBER 1992

DAY	MRAN DISCHARGE (CFS)	MEAN CONCEN- TRATION (MG/L)	SEDIMENT DISCHARGE (TONS/DAY)	MEAN DISCHARGE (CFS)	MEAN CONCEN- TRATION (MG/L)	SEDIMENT DISCHARGE (TONS/DAY)	MRAN DISCHARGE (CFS)	MEAN CONCEN- TRATION (MG/L)	SEDIMENT DISCHARGE (TONS/DAY)
		OCTOBER		Þ	OVEMBER		1	BCEMBER	
1	59	124	22	36	81	9.5	11	5	. 15
2	34	41	3.9	23	18	1.2	11	5 3	.14
3	27	15	1.1	20	8	.44	11	3	. 09
4	23	10	. 62	19	12	.61	12	3	.10
5	21	10	. 57	21	18	1.5	11	5	. 14
6	42	105	57	20	36	4.1	11	11	.33
7	68	208	53	18	8	.41	10	13	.37
8	117	304	236	17	5	.21	10	5	. 15
9	65	32	7.5	16	4	.16	9.8	3	.08
10	36	8	.81	16	4	.19	9.7	3	. 08
11	28	7	. 52	16	5	.22	10	3	.08
12	25	4	. 26	15	4	.18	9.4	3	.08
13	23	3	. 16	15	4	.18	9.3	3	.09
14	26	17	2.3	15	6	.25	9.0	4	.10
15	28	31	3.4	15	5	.20	8.7	4	.10
16	21	3	. 20	15	6	.23	8.8	4	. 09
17	19	2	. 10	15	6	.25	9.5	10	. 27
18	20	5	. 32	15	5	.19	9.7	13	.34
19	27	31	3.7	14	12	.45	9.9	7	. 17
20	32	57	9.0	13	8	.29	10	28	.78
21	32	49	6.3	13	6	.20	13	15	. 57
22	26	33	3.0	12	6	.20	9.7	4	.10
23	21	10	. 57	16	14	.79	9.7	5	. 13
24	19	5	.26	15	13	.56	9.7	5	. 12
25	19	9	.46	13	12	.45	9.5	5	. 13
26	18	11	. 53	13	9	.31	9.3	4	.09
27	17	8	. 35	13	7	.26	9.3	4	. 10
28	31	48	11	12	7	.25	9.2	3	.08
29	26	51	4.0	12	7	.23	9.1	13	. 32
30	27	41	8.4	11	5	.16	9.1	5	. 12
31	53	92	21				9.1	4	. 09
TOTAL	1030		458.33	484		24.17	307.5		5.58

50136400 RIO ROSARIO NEAR HORMIGUEROS, PR--Continued

SEDIMENT DISCHARGE, SUSPENDED (TONS/DAY), WATER YEAR OCTOBER 1991 TO SEPTEMBER 1992

DAY	MRAN DISCHARGE (CFS)	MEAN CONCEN- TRATION (MG/L)	SEDIMENT DISCHARGE (TONS/DAY)	MEAN DISCHARGE (CFS)	MEAN CONCEN- TRATION (MG/L)	SEDIMENT DISCHARGE (TONS/DAY)	MEAN DISCHARGE (CFS)	MEAN CONCEN- TRATION (MG/L)	SEDIMENT DISCHARGE (TONS/DAY)
		JANUARY		1	BBRUARY			MARCH	
1	12	19	. 83	9.3	3	.08	7.5	5	.11
2	10	16	.48	8.7	4	.11	7.9	3	. 06
3	9.0	7	. 17	8.8	15	.37	8.1	4	.08
4	8.8	10	.24	9.1	8	.20	8.2	8	.20
5	9.7	10	.27	9.2	7	.17	8.7	10	. 24
6	163	1290	1180	11	7	.22	7.9	5	. 11
7	27	39	3.5	14	4	.19	7.7	4	.08
8	16	9	.41	11	4	.12	9.5	2	.06
9	13	5	. 19	9.1	5	.12	7.3	3	.06
10	12	4	. 14	8.7	6	.15	7.5	10	.21
11	13	6	.21	9.3	10	.25	7.4	6	. 12
12	14	7	.27	8.7	9	.21	7.3	6	, 12
13	12	8	.25	8.4		.11	7.3	6	. 12
14	11	5	. 16	8.4	4	.10	7.0	5	.09
15	11	10	.30	8.7	3	.08	6.9	6	. 11
16	11	7	.22	8.3	2	.06	6.9	8	. 15
17	12	4	. 14	8.2	2	.04	7.1	4	.09
18	11	4	.11	8.1	2	.04	8.6	29	.66
19	11	3	. 10	7.9	2	.05	7.7	42	. 90
20	11	6	.18	7.6	3	.06	7.3	12	.24
21	11	5	. 17	7.7	8	.18	7.3	4	.08
22	11	3	.09	7.6	5	.12	7.2	10	. 19
23	11	3	.09	7.5	3	.08	6.4	10	.18
24	e10	3	e. 08	7.4	9	.18	6.2	10	. 18
25	e 10	3	e.07	7.3	4	.09	6.5	6	.11
26	e10	2	e.06	7.1	3	.06	6.7	4	. 07
27	e10	2	e.05	7.0	3	.05	8.3	6	. 37
28	e10	3	e.07	6.9	5	.09	21	33	3.0
29	e10	3	e.08	7.0	5	.11	15	35	2.8
30	9.5	3	. 08				16	24	1.6
31	9.4	11	.26				60	208	120
TOTAL	509.4		1189.27	248.0		3.69	314.4		132.39

e Estimated

RIO GUANAJIBO BASIN
50136400 RIO ROSARIO NEAR HORMIGUEROS, PR--Continued

SEDIMENT DISCHARGE, SUSPENDED (TONS/DAY), WATER YEAR OCTOBER 1991 TO SEPTEMBER 1992

DAY	MEAN DISCHARGE (CFS)	MEAN CONCEN- TRATION (MG/L)	SEDIMENT DISCHARGE (TONS/DAY)	MEAN DISCHARGE (CFS)	MEAN CONCEN- TRATION (MG/L)	SEDIMENT DISCHARGE (TONS/DAY)	MEAN DISCHARGE (CFS)	MEAN CONCEN- TRATION (MG/L)	SEDIMENT DISCHARGE (TONS/DAY)
		APRIL			MAY			JUNE	
1	27	200	18	6.5	17	.29	27	38	3.1
2	19	154	9.1	6.3	24	.39	18	24	1.2
3	11	88	2.6	5.2	23	.33	14	16	. 60
4	7.5	157	3.2	4.8	19	.25	12	14	. 44
5	6.1	88	1.5	4.5	16	.20	10	12	. 32
6	5.4	40	. 62	4.4	24	.28	9.5	10	.25
7	5.6	39	. 59	4.1	16	.18	8.9	9	.21
8	6.7	30	. 52	4.2	18	.19	9.8	21	. 56
9	8.6	36	. 85	3.9	18	.19	28	59	13
10	11	38	1.1	4.1	19	.21	35	71	12
11	8.1	26	. 58	4.1	24	.27	18	26	1.3
12	6.8	20	. 39	4.4	25	.31	13	45	1.5
13	6.6	21	.36	4.7	25	.32	11	47	1.4
14	5.5	19	.30	4.6	24	.29	10	75	2.1
15	35	108	40	5.5	24	.36	10	62	1.7
16	46	109	26	9.7	38	1.2	9.8	58	1.5
17	27	69	6.2	8.4	17	.44	9.7	61	1.6
18	11	79	2.4	5.4	8	. 12	9.5	60	1.6
19	9.8	60	1.6	47	221	178	9.2	67	1.6
20	43	233	93	33	64	13	8.5	64	1.5
21	45	97	18	10	13	.34	8.7	63	1.5
22	27	59	4.7	15	21	1.9	8.7	30	.72
23	12	31	1.1	275	1380	1430	8.0	18	.40
24	8.3	20	.46	196	757	485	7.9	18	.38
25	6.6	29	. 52	85	203	54	7.8	16	.34
26	6.0	21	.35	45	74	9.5	7.8	17	.35
27	5.8	25	.39	26	37	2.8	7.5	16	. 34
28	5.2	29	.42	18	23	1.1	7.5	22	.46
29	4.9	33	.45	18	24	1.2	7.7	22	.46
30	6.0	21	.30	30	68	14	7.1	19	. 37
31				40	74	13			
TOTAL	433.5		235.60	932.8		2209.66	359.6		52.80

50136400 RIO ROSARIO NEAR HORMIGUEROS, PR--Continued

SEDIMENT DISCHARGE, SUSPENDED (TONS/DAY), WATER YEAR OCTOBER 1991 TO SEPTEMBER 1992

		MEAN			MRAN			MRAN	
DAY	MRAN DISCHARGE (CFS)	CONCEN- TRATION (MG/L)	SEDIMENT DISCHARGE (TONS/DAY)	MEAN DISCHARGE (CFS)	CONCEN- TRATION (MG/L)	SEDIMENT DISCHARGE (TONS/DAY)	MRAN DISCHARGE (CFS)	CONCEN- TRATION (MG/L)	SEDIMENT DISCHARGE (TONS/DAY)
		JULY			AUGU ST		SI	SPTEMBER	
1	6.8	19	.35	17	63	3.3	24	63	4.2
2	7.4	18	.38	13	15	.50	71	377	233
3	13	55	1.8	12	24	.81	81	298	78
4	7.8	43	. 93	113	985	1500	198	649	827
5	7.5	24	.50	94	283	116	107	201	75
6	7.1	22	. 42	148	504	253	158	1260	1180
7	7.0	20	. 37	69	149	32	135	347	154
8	7.5	21	. 44	167	993	1760	122	392	283
9	13	34	1.4	189	719	428	109	242	85
10	13	86	3.1	169	469	270	84	183	80
11	14	74	2.9	89	202	57	145	818	614
12	10	62	1.8	77	184	49	100	118	39
13	79	493	420	76	168	47	283	1920	5820
14	129	763	834	51	62	9.6	199	974	584
15	91	303	125	54	81	13	128	263	102
16	50	174	47	37	31	3.1	91	199	50
17	28	127	10	31	26	2.1	71	51	10
18	15	105	4.2	27	29	2.1	58	30	4.9
19	105	556	463	24	24	1.6	79	207	73
20	93	281	109	23	18	1.1	225	725	844
21	28	46	3.8	23	24	1.6	136	453	191
22	18	23	1.1	25	31	2.1	187	912	1290
23	15	18	. 69	22	25	1.5	136	240	110
24	68	219	103	20	23	1.2	76	19	3.9
25	31	52	5.8	37	103	29	71	104	24
26	17	21	.96	28	133	10	58	65	12
27	13	36	1.3	19	61	3.2	47	12	1.5
28	12	24	.79	17	24	1.1	113	357	347
29	11	17	. 52	30	135	21	81	184	49
30	30	68	18	73	248	91	506	3540	24300
31	23	97	5.5	41	123	14			
TOTAL	970.1		2168.05	1815		4724.91	3879		37468.5
YEAR	11283.3		48672.95						

50136400 RIO ROSARIO NEAR HORMIGUEROS, PR--Continued WATER QUALITY DATA, WATER YEAR OCTOBER 1991 TO SEPTEMBER 1992

PARTICLE-SIZE DISTRIBUTION OF SUSPENDED SEDIMENT

					SED.	SED.	SED.
		DIS-		SEDI-	SUSP.	SUSP.	SUSP.
		CHARGE,		MENT,	FALL	FALL	FALL
		INST.	SEDI-	DIS-	DIAM.	DIAM.	DIAM.
		CUBIC	MENT,	CHARGE,	PERCENT	PERCENT	PERCENT
		FERT	SUS-	SUS-	FINER	FINER	FINER
DATE	TIME	PER	PENDED	PENDED	THAN	THAN	THAN
		SECOND	(MG/L)	(T/DAY)	.002 MM	.004 MM	.008 MM
JAN 1992							
06	0410	605	5600	9150	36	49	58
APR							
02	1934	33	2020	180	46	58	64
МХХ							
23	1115	552	4170	6200	41	46	62
JOL							
14	2055	520	4000	5620	38	48	59
λUG							
04	1708	855	20300	46900	28	41	56
04	1710	859	19600	45400	29	41	55
08	1703	57	15300	2360	16	30	36
SEP							
30	1826	1085	23900	70000	6	8	10

DATE	SED. SUSP. FALL DIAM. PERCENT FINER THAN .016 MM	SED. SUSP. FALL DIAM. PERCENT FINER THAN .031 MM	SED. SUSP. SIEVE DIAM. PERCENT FINER THAN .062 MM	SED. SUSP. SIEVE DIAM. PERCENT FINER THAN .125 MM	SED. SUSP. SIEVE DIAM. PERCENT FINER THAN .250 MM	SED. SUSP. SIEVE DIAM. PERCENT FINER THAN .500 MM	SED. SUSP. SIEVE DIAM. PERCENT FINER THAN 1.00 MM
JAN 1992							
06	69	79	94	98	99	99.6	700
APR							
02	78	80	96	97	99	99.6	100
MAY							
23	72	79	95	99	100	10 0	100
JOL							
14	69	79	97	99	100	10 0	100
AUG							
04	70	83	95	99	99.8	100	100
04	68	77	92	98	99	99.7	100
08	46	62	77	94	98	99	99
SEP							
30	12	14	19	22	26	31	45

50136400 RIO ROSARIO NEAR HORMIGUEROS , PR--Continued WATER QUALITY DATA, WATER YEAR OCTOBER 1991 TO SEPTEMBER 1992 SILT AND CLAY PERCENT OF SUSPENDED SEDIMENT

DATE	TIME	STREAM- FLOW, INSTAN- TANEOUS (CFS)	SEDI- MENT, SUS- PENDED (MG/L)	SEDI- MENT, DIS- CHARGE, SUS- PENDED (T/DAY)	SED. SUSP. SIEVE DIAM. PERCENT FINER THAN .062 MM
OCT 1991					
08	1731	238	233	149	93
01	1825	28	41.6	3.1	100
DEC					
20	1920	11	43.7	1.3	100
JAN 1992 06	0440	504	4670	6350	95
MAR	0440	304	4070	0330	23
28	1540	12	123	14	86
APR					
16	1908	98	302	80	97
20 May	1955	234	2440	1540	99
23	0945	475	3580	4590	95
23	1430	393	2000	2120	98
JOL	1450	3,33	2000	-1-0	30
14	1956	525	6980	9890	97
14	2010	512	6750	9330	98
30	1907	138	430	160	97
AUG					
04	1725	681	12200	22400	93
04	1740	563	12100	18400	88
08	1710	1140	15300	47000	78 88
10 Sep	1846	364	1110	1090	88
02	1848	395	3180	3390	80
04	1500	475	10100	12900	79
20	1602	755	7180	14650	67
27	1816	45	6250	759	48
30	1834	1020	9070	24900	49

50138000 RIO GUANAJIBO NEAR HORMIGUEROS, PR

LOCATION.--Lat 18°08'36", long 67°08'57", Hydrologic Unit 21010003, at bridge on Highway 100, 1.4 mi (2.3 km) west of Hormigueros, and 2.0 mi (3.2 km) downstream from Río Rosario.

DRAINAGE ARRA. -- 120 mi2 (311 km2).

WATER-DISCHARGE RECORDS

PERIOD OF RECORD.--Annual low-flow measurements 1959, monthly measurements April 1959 to November 1967, January 1973 to current year.

GAGE.--Water-stage recorder. Datum of gage is at mean sea level. Previous to Nov. 7, 1980, at site 0.3 mi (0.5 km) upstream at datum 7.36 ft (2.243 m) higher.

REMARKS.--Records fair. Gage-height and precipitation satellite telemetry at station. Daily discharges affected by sewage treatment plant about 2.1 mi (3.4 km) upstream from gage.

	DIS	CHARGE,	CUBIC FEET		ND, WATER AILY MEAN		TOBER 199	1 TO SEPTE	GBER 199	92		
DAY	OCT	NOV	DRC	JAN	FRB	MAR	APR	MAY	JUN	JUL	AUG	SEP
1	164	97	22	14	20	20	119	29	196	16	60	52
2	102	73	19	18	20	19	44	23	156	15	45	56
3	87	64	17	10	22	23	69	18	105	26	41	150
4	80	61	19	11	22	20	30	14	89	19	93	450
5	73	60	17	12	24	20	18	12	74	17	118	514
6 7	73 165	71 64	24	939 555	25 36	20	13	9.9 8.2	63 57	15 14	192 127	588 888
8	170	57	29 22	210	32	18	28 42	7.5	57 52	26	140	576
و	146	51	19	162	27	18 17	28	6.3	85	60	247	448
10	92	48	19	130	23	16	43	7.0	145	69	204	299
11	78	45	15	110	29	17	25	6.2	99	41	134	425
12	69	43	13	97	31	15	17	8.0	73	37	126	326
13	63	41	12	82	26	14	14	9.7	64	83	186	493
14	60	32	13	69	26	14	11	11	52	267	107	877
15	69	32	11	62	24	14	9.1	9.5	45	448	104	604
16	61	27	9.8	58	23	14	65	18	40	119	86	399
17	53	38	8.8	55	21	14	111	32	35	97	68	327
18	49	31	7.5	52	21	16	52	23	32	62	61	274
19	62	50	13	47	20	17	49	12	29	78	54	252
20	135	32	15	43	19	15	139	87	26	248	49	598
21	139	32	19	39	19	15	313	34	26	101	51	646
22	174	25	16	36	20	22	202	109	24	71	100	409
23	191	26	14	33	20	15	85	1550	20	84	64	407
24	103	36	12	30	19	10	61	2170	16	90	54	276
25	84	27	14	28	20	11	46	950	17	88	49	648
26	73	29	12	30	21	13	36	654	18	52	67	532
27	66	23	12	27	20	12	28	423	17	42	45	283
28	66	23	12	24	20	35	23	284	17	39	40	327
29	80	22	14	23	19	20	19	219	16	35	49	33 7
30	61	21	13	21		50	19	185	17	37	102	497
31	136		13	19		13		180		67	99	
TOTAL	3024	1281	476.1	3046	669	557	1758.1	7109.3	1705	2463	2962	12958
MEAN	97.5	42.7	15.4	98.3	23.1	18.0	58.6	229	56.8	79.5	95.5	432
MAX	191	97	29	939	36	50	313	2170	196	448	247	888
MIN	49	21	7.5	10	19	10	9.1	6.2	16	14	40	52
AC-FT	6000	2540	944	6040	1330	1100	3490	14100	3380	4890	5880	25700
CFSM	.81	.36	.13	. 82	.19	. 15	.49	1.91	.47	. 66	.80	3.60
IN.	.94	.40	.15	. 94	.21	. 17	.55	2.20	.53	.76	.92	4.02
Statist	rics of Mo	NTHLY M	BAN DATA FO	R WATER Y	BARS 1973	- 1992,	BY WATER	YEAR (WY)				
MEAN	489	442	130	56.8	44.8	45.0	71.0	182	111	107	233	507
MAX	1254	1518	422	108	95.9	244	316	636	504	240	757	2075
(WY)	1986	1978	1976	1982	1974	1989	1989	1980	1979	1984	1988	1975
MIN	97.5	42.7	15.4	13.8	13.9	10.6	16.1	12.7	9.23	26.4	42.3	95.4
(WY)	1992	1992	1992	1973	1977	1977	1977	1977	1977	1976	1976	1991
SUMMARY	(STATISTI	CS	FOR 1	.991 CALEN	DAR VRAR	1	FOR 1992 F	ATER YEAR		WATER YEA	RS 1973	- 1992
ANNUAL				23702.1		•	38008.5			***************************************		
ANNUAL				64.9			104	•		204		
	PANNUAL M	ID AM		04.3			104			402		1979
	ANNUAL ME									104		1992
	DAILY ME			572	May 8		2170	May 24		35000	Sen	16 1975
	DAILY MEA				Dec 18			May 11		5.0		18 1977
	SEVEN-DAY		M	11	Dec 12		7.6			5.5		17 1977
	ANBOUS PE						2760			128000		16 1975
	CANBOUS PE							14 May 23		28.50		16 1975
	TANBOUS LO							-		4.6	Jun	22 1977
	RUNOFF (A			47010			75390			148000		
	RUNOFF (C			.54			. 6			1.70		
	RUNOFF (I			7.35			11.7	78		23.14		
	CENT BXCEE			130			269			450		
	CENT BXCEE			47			39			76		
90 PERC	CENT BXCER	DS		18			13			20		

50138000 RIO GUANAJIBO NEAR HORMIGUEROS, PR--Continued

WATER-QUALITY RECORDS

PERIOD OF RECORD. -- Water years 1958 to current year.

WATER-QUALITY DATA, WATER YEAR OCTOBER 1991 TO SEPTEMBER 1992

DATE	TIME	DIA CHARC INS CUB: FRI PRI SECC	GR, SPE T. CIE IC CON BT DUC R ANG	PIC WHO I- FIE TT- (STA CR AF	'ER OLE LLD TEM IND- AT ID WA	(PER- URE TER (G C)	TUR BID ITY (NTU	- DI SOL	SEN, (S- VED S	YGEN, DIS- OLVED PER- CENT ATUR- TION)	OXYG DEMAI CHE ICA (HIC LEVE)	ND, FOI M- FR L 0.0 GH UM L) (COI	LI- RM, CAL, 45 -MF LS./ ML)	STREP- TOCOCCI FECAL, (COLS. PER 100 ML)
OCT 1991 10	1015	97		350	7.8	25.0	15		6.9	83		17 1	K640	K880
DEC 19	0925	16		446	7.0	22.5	5.	0	6.4	70		15	K850	420
FRB 1992 26	1015	24		484	7.6	24.0	1.	7	6.5	78		14 1	K170	440
MAR 31	1125	15		410	7.4	25.0	5.	9	6.5	80		11	500	380
JUN 25 AUG	1100	24		470	7.4	25.5	3.	3	7.0	91		11	520	30 0
14	1010	145		343	7.4	26.0	17		5.7	74		<10	2200	K900
DATE OCT 1991 10 DEC 19 FEB 1992 26 MAR 31 JUN 25 AUG 14	N: T: ()	ARD- ESS ESS MG/L AS ACO3) 170 170 150	CALCIUM DIS- SOLVED (MG/L AS CA) 26 24 25	MAGNE- SIUM, DIS- SOLVED (MG/L AS MG) 25 -7 27	SODIUM, DIS- SOLVED (MG/L AS NA) 13 20 11	SO T	DIUM AD- RP- ION TIO 0.4 0.7	POTAS- SIUM, DIS- SOLVED (MG/L AS K) 1.8 2.4 2.2	ALKA- LINITY WAT WH TOT FEE FIRLD MG/L A CACO3 17 10 20 16 22	T SULL TO S (M AS AS O O O O O O	FIDE TAL G/L S) <0.5 <0.5	SULFATE DIS- SOLVED (MG/L AS SO4) 13 27 15	RII DII: SOII (MI AS	LVED G/L CL) 6 7
DATE	R S (1	LUO- IDR, DIS- OLVED MG/L S F)	SILICA, DIS- SOLVED (MG/L AS SIO2)	SOLIDS, SUM OF CONSTI- TUENTS, DIS- SOLVED (MG/L)	SOLIDS, DIS- SOLVED (TONS PER DAY)	TOT. AT DEG SU: PEN	105 . C, 1 s-	NITRO- GEN, NITRATE TOTAL (MG/L AS N)	NITRO GEN, NITRIT TOTAL (MG/L AS N)	G E NO2 TO (M	TRO- EN, +NO3 TAL G/L N)	NITRO- GEN, AMMONIA TOTAL (MG/L AS N)	GI ORGI TO' (M	IRO- EN, ANIC TAL G/L N)
OCT 1991		-0 40	20	20-	E				-0.05		E00	0.000		n 10
DEC		<0.10	29	226	59.2		<1		<0.01		.590	0.020		0.18
19 FRB 1992							2		<0.01	0 0	.610	0.010	•	-
26 MAR							1		<0.01	0 0	.120	0.020	1	0.18
31 JUN		<0.10	30	253	10.4		15	0.310	0.01	0 0	.320	0.020	(0.18
25							8	0.710	0.01	0 0	.720	0.030		0.17
AUG 14		0.10	26	200	78.3		40	0.520	0.02	0 0	.540	0.040		0.36

K = non-ideal count

50138000 RIO GUANAJIBO NEAR HORMIGUEROS, PR--Continued WATER-QUALITY DATA, WATER YEAR OCTOBER 1991 TO SEPTEMBER 1992

DATE	NITRO- GEN, AM- MONIA + ORGANIC TOTAL (MG/L AS N)	NITRO- GEN, TOTAL (MG/L AS N)	NITRO- GEN, TOTAL (MG/L AS NO3)	PHOS- PHORUS TOTAL (MG/L AS P)	ARSENIC TOTAL (UG/L AS AS)	BARIUM, TOTAL RECOV- ERABLE (UG/L AS BA)	BORON, TOTAL RECOV- ERABLE (UG/L AS B)	CADMIUM TOTAL RECOV- ERABLE (UG/L AS CD)	CHRO- MIUM, TOTAL RECOV- ERABLE (UG/L AS CR)	COPPER, TOTAL RECOV- ERABLE (UG/L AS CU)
OCT 1991										
10 Dec	0.20	0.79	3.5	0.180	<1	<100	60	1	10	10
19 FRB 1992	<0.20			0.390						
26 MAR	0.20	0.32	1.4	0.320						
31	0.20	0.52	2.3	0.280	<1	<100	40	<1	3	<10
25	0.20	0.92	4.1	0.340						
AUG 14	0.40	0.94	4.2	0.270						
DATE	IRON, TOTAL RECOV- ERABLE (UG/L AS FE)	LEAD, TOTAL RECOV- ERABLE (UG/L AS PB)	MANGA- NESE, TOTAL RECOV- ERABLE (UG/L AS MN)	MERCURY TOTAL RECOV- ERABLE (UG/L AS HG)	SELE- NIUM, TOTAL (UG/L AS SE)	SILVER, TOTAL RECOV- ERABLE (UG/L AS AG)	ZINC, TOTAL RECOV- ERABLE (UG/L AS ZN)	CYANIDE TOTAL (MG/L AS CN)	PHENOLS TOTAL (UG/L)	MRTHY- LENE BLUE ACTIVE SUB- STANCE (MG/L)
OCT 1991 10	1200	3	70	<0.10	<1	<1	<10	<0.010	<1	0.02
DEC 19										
FRB 1992										
26 MAR										
31 Jun	540	6	70	<0.10	<1	<1	20	<0.010	1	0.02
25 Aug										
14										
			P	ESTICIDE	analyses					
DATE	TIME	PCB, TOTAL (UG/L)	ALDRIN, TOTAL (UG/L)	CHLOR- DANE, TOTAL (UG/L)	DDD, TOTAL (UG/L)	DDE, TOTAL (UG/L)	DDT, TOTAL (UG/L)	DI- AZINON, TOTAL (UG/L)	DI- BLDRIN TOTAL (UG/L)	ENDO- SULFAN, TOTAL (UG/L)
JUN 1992 25	1100	40.1	-0.010	-0.1	-0.010	-0.010	-0.010	-0.01	40 010	-0.010
23	1100	<0.1	<0.010	<0.1	<0.010	<0.010	<0.010	<0.01	<0.010	<0.010
DA?	ENDR WAT UNFL FB RE (UG/	er Trd ethi C Tot	ON, CHI	TA- CHI OR, EPOX AL TOT	IDB LINE	'AL TOT	ON, CHI	Y- PAR LOR, THI TAL TOT	ON, MIR	EX, TAL /L)
JUN 199 25		010 <0).01 <0.	010 <0.	010 <0.	010 <0	.01 <	0.01 <0	.01 <0	.01
DA7 JUN 19:	PAR THI FB TOT (UG	NAE TH LEN A- POI ON, CHI AL TOI (/L) (UG/	PH- IA- IES, JY- PE JOR. THA PAL TOT L) (UG	R- TC NB APHE AL TOI /L) (UG	OX- TOT INB, TR PAL THI B/L) (UG	AL I- 2,4 ON TOT ;/L) (UG	-D, 2,4, AL TO: /L) (UC	.5-T 2, 4 FAL TOT 3/L) (UG/	-DP SILV AB TOI L) (UG	AL :/L)
25	. <0	.01 <0	.10 <	0.1	:1 <0	.01 0	.06 <0	.01 <0	.01 <0	.01




Figure 26;-Río Yagüez and Río Grande de Añasco basins.

RIO YAGŪRZ BASIN

50138800 RIO YAGŪEZ NEAR MAYAGŪEZ, PR

WATER-QUALITY RECORDS

LOCATION.--Lat 18°12'31", long 67°07'07", at steel-truss bridge on unnumbered paved road about 800 ft (244 m) south of Highway 106, 1.8 mi (2.9 km) west of Highways 106 and 352 junction, and 1.4 mi (2.3 km) east-northeast from Mayagüez plaza.

DRAINAGE AREA. -- 6.7 mi 2 (17.3 km2).

PERIOD OF RECORD. -- Water years 1979 to current year.

WATER-QUALITY DATA, WATER YEAR OCTOBER 1991 TO SEPTEMBER 1992

DATE	TIME	DIS- CHARGE, INST. CUBIC FEET PER	SPE- CIFIC CON- DUCT- ANCE	PH WATER WHOLE FIELD (STAND- ARD	TEMPER- ATURE WATER	TUR- BID- ITY	OXYGEN, DIS- SOLVED	OXYGEN, DIS- SOLVED (PER- CENT SATUR-	OXYGEN DEMAND, CHEM- ICAL (HIGH LEVEL)	COLI- FORM, FECAL, 0.45 UM-MF (COLS./	STREP- TOCOCCI FECAL, (COLS. PER	HARD- NESS TOTAL (MG/L AS
		SECOND	(US/CM)	UNITS)	(DEG C)	(NTU)	(MG/L)	ATION)	(MG/L)	100 ML)	100 ML)	CACO3)
OCT 1991 10	1350	4.1	294	8.0	26.0	2.0	7.6	93	<10	350	690	120
19 FBB 1992	1430	1.3	227	7.4	25.5	0.60	6.8	82	<10	240	280	175
26	1130	1.2	322	7.8	23.0	0.50	8.8	106	<10	220	360	
19	0910	1.6	314	8.2	25.5	2.0	6.9	80	<10	280	340	140
24 AUG	1300	2.2	300	7.8	26.0	1.5	6.8	79	<10	210	200	
13	1240	4.4	273	7.1	24.5	1.3	7.7	98	<10	290	K190	120
DATE	CALCIUM DIS- SOLVED (MG/L AS CA)	MAGNE- SIUM, DIS- SOLVED (MG/L AS MG)	SODIUM, DIS- SOLVED (MG/L AS NA)	SODIUM AD- SORP- TION RATIO	POTAS- SIUM, DIS- SOLVED (MG/L AS K)	ALKA- LINITY WAT WH TOT FET FIRLD MG/L AS CACO3	SULFIDE TOTAL (MG/L AS S)	SULFATE DIS- SOLVED (MG/L AS SO4)	CHLO- RIDE, DIS- SOLVED (MG/L AS CL)	FLUO- RIDE, DIS- SOLVED (MG/L AS F)	SILICA, DIS- SOLVED (MG/L AS SIO2)	SOLIDS, SUM OF CONSTI- TUENTS, DIS- SOLVED (MG/L)
OCT 1991												
DEC DEC	33	10	11	0.4	2.7	130	<0.5	14	15	<0.10	30	194
19 FRB 1992						120						
26						140						
19 JUN	35	9.5	14	0.5	2.5	110	<0.5	9.9	12	<0.10	30	196
AUG						200						
13	33	9.1	10	0.4	2.0	110		7.8	9.0	<0.10	29	171
DATE	SOLIDS, DIS- SOLVED (TONS PER DAY)	RESIDUR TOTAL AT 105 DEG. C, SUS- PENDED (MG/L)	NITRO- GEN, NITRITE TOTAL (MG/L AS N)	NITRO- GEN, NO2+NO3 TOTAL (MG/L AS N)	NITRO- GEN, AMMONIA TOTAL (MG/L AS N)	NITRO- GEN, AM- MONIA + ORGANIC TOTAL (MG/L AS N)	PHOS- PHORUS TOTAL (MG/L AS P)	ARSENIC TOTAL (UG/L AS AS)	BARIUM, TOTAL RECOV- BRABLE (UG/L AS BA)	BORON, TOTAL RECOV- ERABLE (UG/L AS B)	CADMIUM TOTAL RECOV- ERABLE (UG/L AS CD)	CHRO- MIUM, TOTAL RECOV- ERABLE (UG/L AS CR)
OCT 1991												
DRC	2.15	<1	<0.010	0.670	<0.010	<0.20	0.040	<1	100	50	<1	<1
19 FRB 1992		4	<0.010	0.480	<0.010	<0.20	0.050		-57			
26 MAY		1	<0.010	0.320	0.020	<0.20	0.040					17.
19	0.85	2	<0.010	0.260	<0.010	<0.20	0.050	<1	<100	40	<1	<1
28	20.2	3	<0.010	0.360	<0.010	<0.20	0.040		5.00			
13	20.3	11	<0.010	0.820	0.030	<0.20	0.030					111

K = non-ideal count

RIO YAGUEZ BASIN

50138800 RIO YAGUEZ NRAR MAYAGUEZ, PR--Continued WATER-QUALITY DATA, WATER YEAR OCTOBER 1991 TO SEPTEMBER 1992

DATE	COPPER, TOTAL RECOV- ERABLE (UG/L AS CU)	IRON, TOTAL RECOV- ERABLE (UG/L AS FE)	LEAD, TOTAL RECOV- ERABLE (UG/L AS PB)	MANGA- NESE, TOTAL RECOV- BRABLE (UG/L AS MN)	MERCURY TOTAL RECOV- ERABLE (UG/L AS HG)	SELE- NIUM, TOTAL (UG/L AS SE)	SILVER, TOTAL RECOV- ERABLE (UG/L AS AG)	ZINC, TOTAL RECOV- ERABLE (UG/L AS ZN)	CYANIDE TOTAL (MG/L AS CN)	PHENOLS TOTAL (UG/L)	METHY- LENE BLUE ACTIVE SUB- STANCE (MG/L)
OCT 1991											
10	<10	90	3	20	<0.10	<1	<1	<10	<0.010	1	0.02
DEC											
19											
FEB 1992											
26											
MAY											
19	20	130	<1	20	<0.10	<1	<1	20	<0.010	<1	0.02
JUN											
28											
AUG											
13											

50141500 LAGO GUAYO NEAR CASTANER, PR

LOCATION.--Lat 18°12'46", long 66°50'06", Hydrologic Unit 21010003, at Guayo Dam on Río Guayo, 1.1 mi (1.8 km) southwest of Lago Yahuecas, 2.6 mi (4.2 km) southwest of Lago Prieto, 2.1 mi (3.4 km) north of Castafier, and 6.0 mi (9.6 km) west of Adjuntas.

DRAINAGE AREA. -- 9.60 mi 2 (24.86 km2).

Elevation, in feet

1415

1449

ELEVATION RECORDS

PERIOD OF RECORD. -- April 1980 to January 1985, June 1989 to current year.

GAGE. -- Water-stage recorder. Datum of gage is mean sea level.

REMARKS.--Lago Guayo was completed in 1956. The dam is on Río Guayo and is the largest in the southwestern Puerto Rico project. The maximum storage is 17,400 ac-ft (21.5 hm²) for power and irrigation. The dam is a concrete gravity structure with a total length of 555 ft (169 m), a maximum structural height of 190 ft (58 m), and a maximum width at the base of 165 ft (44 m). The ungated overflow spillway with a crest elevation of 60.00 ft (18.29 m) and a crest length of 220 ft (67 m) was designed to pass a maximum flood of 30,200 ft³/s (855 m³/s) at a reservoir elevation of 70.00 ft (21.34 m). Timber flashboards that were added to increase storage capacity were subsequently removed and their use discontinued. Gage-height and precipitation satellite telemetry at station.

EXTREMES OBSERVED FOR PERIOD OF RECORD.--Maximum elevation, 1462.43 ft (445.75 m), May 27, 1980; minimum elevation recorded, 1415.43 ft (431.42 m), June 2, 1990, but may have been less during period of no gage-height record June 2-5, 1990.

EXTREMES OBSERVED FOR CURRENT YEAR.--Maximum elevation, 1455.96 ft (443.78 m), May. 27; minimum elevation recorded 1434.06 ft (437.10 m), Aug. 24.

Elevation, in feet Contents, in acre-feet

13,550

15,000

1460

1465

Capacity Table (based on data from Puerto Rico Water Resources Authority)

Contents, in acre-feet

3,960

10,660

ELEVATION (FERT NGVD), WATER YEAR OCTOBER 1991 TO SEPTEMBER 1992 DAILY OBSERVATION AT 24:00 VALUES												
DAY	OCT	NOV	DEC	JAN	FEB	MAR	APR	MAY	JUN	JUL	AUG	SEP
1	1436.28	λ	1444.84	1445.05	1449.25	1448.07	λ	λ	1453.26	λ	λ	1437.97
2	1436.82	λ	1443.34	1444.92	1449.47	1447.97	À	À	1453.00	λ	λ	1438.25
3	1437.04	À	1443.52	1444.98	1449.62	1447.96	λ	λ	λ	λ	λ	1438.52
4	1436.81	λ	1443.50	1445.11	1449.78	1447.92	λ	λ	λ	λ	λ	1439.04
5	1437.12	λ	1443.60	1446.38	1449.95	1444.30	λ	λ	λ	λ	λ	1439.47
6	1438.33	λ	1443.65	λ	1449.00	1443.28	λ	1437.00	λ	λ	λ	1440.83
7	1439.19	λ	1443.71	λ	1449.13	1443.40	λ	1437.12	λ	λ	λ	1441.68
8	1440.49	λ	1443.56	λ	1449.29	1444.69	λ	1437.10	λ	λ	λ	1442.26
9	1440.91	λ	1443.67	1452.50	1449.43	1444.69	λ	1436.86	λ	λ	λ	1442.63
10	1440.92	λ	λ	1452.31	1449.61	1443.92	λ	1437.00	λ	λ	λ	1442.90
11	1441.30	λ	λ	1452.48	1448.84	1443.35	λ	1437.03	λ	A	λ	1443.14
12	1441.63	λ	λ	1452.59	1447.87	1442.22	λ	1437.03	λ	λ	λ	1443.34
13	1441.94	λ	λ	1451.77	1448.00	1440.62	λ	1436.91	λ	λ	λ	1443.94
14	1442.51	1445.60	λ	1451.54	1448.20	λ	λ	1436.95	λ	λ	λ	1444.31
15	1442.91	1445.97	λ	1450.99	1448.36	λ	λ	1437.33	λ	λ	λ	1444.52
16	1443.26	1446.17	λ	λ	1448.54	λ	λ	1437.85	λ	λ	λ	1444.76
17	1443.51	1446.41	λ	λ	1448.70	λ	λ	1440.10	λ	λ	λ	1444.97
18	1443.93	1446.69	λ	λ	1448.87	λ	λ	λ	λ	λ	λ	1446.73
19	1444.47	1446.87	λ	λ	1448.98	λ	λ	λ	λ	λ	1437.50	1447.54
20	1444.89	1446.75	λ	λ	1449.11	λ	A	λ	λ	λ	1436.89	1448.41
21	1444.97	1446.00	λ	λ	1449.17	λ	λ	λ	λ	λ	1435.55	1449.02
22	1444.98	1445.42	λ	λ	1449.30	λ	λ	λ	λ	λ	1434.60	1449.52
23	1446.23	1444.38	λ	λ	1449.50	λ	A	λ	λ	λ	1434.24	1449.95
24	1445.96	1443.71	λ	1450.30	1449.34	λ	λ	λ	λ	λ	1434.29	1450.23
25	1445.27	1443.94	λ	1450.59	1449.52	λ	λ	1454.69	λ	λ	1434.88	1450.55
26	1445.63	1444.15	1446.37	1450.75	1449.48	λ	λ	1455.50	λ	λ	1435.38	1450.86
27	1445.88	1444.36	1446.36	1450.94	1448.91	λ	λ	1455.27	λ	λ	1435.84	1451.05
28	1445.89	1444.58	1446.32	1451.15	1448.15	λ	λ	1455.08	λ	λ	1436.21	1452.32
29	1446.34	1444.79	1446.22	1450.27	1448.27	λ	λ	1454.97	λ	λ	1436.59	1452.78
30	1446.16	1444.68	1446.20	1449.48		λ	λ	1454.43	λ	λ	1437.11	1454.54
31	1446.18		1446.02	1449.20		λ	λ	1453.93		λ	1437.55	
MBYN	1442.51				1449.02							1445.53
MAX	1446.34				1449.95							1454.54
MIN	1436.28				1447.87							1437.97

A No gage-height record

50143000 RIO GRANDE DE AÑASCO NEAR LARES, PR

WATER-QUALITY RECORDS

LOCATION.--Lat 18°15'26", long 66°55'00", at bridge on Highway 124, 0.7 mi (1.1 km) downstream from confluence of Río Blanco and Río Prieto, and 3.7 mi (6.0 km) southwest of Lares plaza.

DRAINAGE AREA.--26.3 mi² (68.1 km²) this does not include 36.2 mi² (93.8 km²) which contributes only during high floods, and 3.5 mi² (9.1 km²) which contributes only part of its storm runoff.

PERIOD OF RECORD. -- Water years 1959-68, 1970 to current year.

WATER-QUALITY DATA, WATER YEAR OCTOBER 1991 TO SEPTEMBER 1992

		WATER-QUA	LITY DATA	, WATER Y	EAR OCTOR	BR 1991 T	O SEPTEME	ER 1992		
DATE	TIME	DIS- CHARGE, INST. CUBIC FEET PER SECOND	SPE- CIFIC CON- DUCT- ANCE (US/CM)	PH WATER WHOLE FIELD (STAND- ARD UNITS)	TEMPER- ATURE WATER (DEG C)	TUR- BID- ITY (NTU)	OXYGEN, DIS- SOLVED (MG/L)	OXYGEN DEMAND, CHEM- ICAL (HIGH LEVEL) (MG/L)	COLI- FORM, FECAL, 0.45 UM-MF (COL8./ 100 ML)	STREP- TOCOCCI FECAL, (COLS. PER 100 ML)
OCT 1991										
22	1145	153	220	7.7	26.0	54	8.2	14	200000	5700
JAN 1992	1430	23	322	8.0	25.5	2.7	7.4	<10	280	340
FEB 19	1500	13	298	8.4	27.0	1.5	9.4	<10	410	470
APR 07	0930	16	318	7.8	24.5	3.5	10.0	<10	K27	58
JUL 02 SEP	0835	18	304	7.6	26.0	0.90	7.0	<10	K4 5	K91
03	0845	31	286	7.2	24.0	13	7.0	<10	1400	230
DATE	HARD- NESS TOTAL (MG/L AS CACO3)	CALCIUM DIS- SOLVED (MG/L AS CA)	MAGNE- SIUM, DIS- SOLVED (MG/L AS MG)	SODIUM, DIS- SOLVED (MG/L AS NA)	SODIUM AD- SORP- TION RATIO	POTAS- SIUM, DIS- SOLVED (MG/L AS K)	ALKA- LINITY WAT WH TOT FET FIELD MG/L AS CACO3	SULFIDE TOTAL (MG/L AS S)	SULFATE DIS- SOLVED (MG/L AS SO4)	CHLO- RIDE, DIS- SOLVED (MG/L AS CL)
OCT 1991										
22 Jan 1992	85	23	6.8	9.0	0.4	2.3	72	<0.5	22	11
10							110			
18 APR		.=-					120			
07	130	35	9.6	14	0.5	2.3	120	<0.5	27	17
02 SEP							130			
03	120	33	8.9	12	0.5	2.4	100		24	13
DATE	FLUO- RIDE, DIS- SOLVED (MG/L AS F)	SILICA, DIS- SOLVED (MG/L AS SIO2)	SOLIDS, SUM OF CONSTI- TUENTS, DIS- SOLVED (MG/L)	SOLIDS, DIS- SOLVED (TONS PER DAY)	RESIDUE TOTAL AT 105 DEG. C, SUS- PENDED (MG/L)	NITRO- GEN, NITRATE TOTAL (MG/L AS N)	NITRO- GEN, NITRITE TOTAL (MG/L AS N)	NITRO- GEN, NO2+NO3 TOTAL (MG/L AS N)	NITRO- GEN, AMMONIA TOTAL (MG/L AS N)	NITRO- GEN, ORGANIC TOTAL (MG/L AS N)
OCT 1991										
22 JAN 1992	0.10	28	145	60.1	32	1.57	0.030	1.60	0.060	0.44
10 FEB					4	1.28	0.020	1.30	0.020	
18 APR					4		<0.010	0.480	0.030	
07 JUL	0.20	31	208	8.99	14	0.540	0.020	0.560	0.060	0.14
02 Sep		~-			32	0.790	0.010	0.800	0.020	1.3
03	0.10	29	187	10.6	<1		<0.010	1.10	0.020	0.18

K = non-ideal count

RIO GRANDE DE AÑASCO BASIN 50143000 RIO GRANDE DE AÑASCO NEAR LARES, PR--Continued WATER-QUALITY DATA, WATER YEAR OCTOBER 1991 TO SEPTEMBER 1992

DATE	NITRO- GEN, AM- MONIA + ORGANIC TOTAL (MG/L AS N)	NITRO+ GEN, TOTAL (MG/L AS N)	NITRO- GEN, TOTAL (MG/L AS NO3)	PHOS- PHORUS TOTAL (MG/L AS P)	ARSENIC TOTAL (UG/L AS AS)	BARIUM, TOTAL RECOV- ERABLE (UG/L AS BA)	BORON, TOTAL RECOV- ERABLE (UG/L AS B)	CADMIUM TOTAL RECOV- BRABLE (UG/L AS CD)	CHRO- MIUM, TOTAL RECOV- ERABLE (UG/L AS CR)	COPPER, TOTAL RECOV- ERABLE (UG/L AS CU)
OCT 1991										
22 JAN 1992	0.50	2.1	9.3	0.100	2	<100	50	<1	1	10
10	<0.20			0.050						
18	<0.20			0.050						
APR 07 JUL	0.20	0.76	3.4	0.020	<1	<100	10	<1	1	10
02 SEP	1.3	2.1	6.3	0.050						
03	0.20	1.3	5.8	0.050						
DATE	IRON, TOTAL RECOV- ERABLE (UG/L AS FE)	LEAD, TOTAL RECOV- ERABLE (UG/L AS PB)	MANGA- NESE, TOTAL RECOV- ERABLE (UG/L AS MN)	MERCURY TOTAL RECOV- ERABLE (UG/L AS HG)	SELE- NIUM, TOTAL (UG/L AS SE)	SILVER, TOTAL RECOV- ERABLE (UG/L AS AG)	ZINC, TOTAL RECOV- BRABLE (UG/L AS ZN)	CYANIDE TOTAL (MG/L AS CN)	PHENOLS TOTAL (UG/L)	METHY- LENE BLUE ACTIVE SUB- STANCE (MG/L)
OCT 1991	TOTAL RECOV- BRABLE (UG/L AS FE)	TOTAL RECOV- ERABLE (UG/L AS PB)	NESE, TOTAL RECOV- ERABLE (UG/L AS MN)	TOTAL RECOV- ERABLE (UG/L AS HG)	NIUM, TOTAL (UG/L AS SE)	TOTAL RECOV- ERABLE (UG/L AS AG)	TOTAL RECOV- BRABLE (UG/L AS ZN)	TOTAL (MG/L AS CN)	TOTAL (UG/L)	LENE BLUE ACTIVE SUB- STANCE (MG/L)
	TOTAL RECOV- ERABLE (UG/L	TOTAL RECOV- BRABLE (UG/L	NESB, TOTAL RECOV- ERABLE (UG/L	TOTAL RECOV- BRABLE (UG/L	NIUM, TOTAL (UG/L	TOTAL RECOV- BRABLE (UG/L	TOTAL RECOV- BRABLE (UG/L	TOTAL (MG/L	TOTAL	Lene Blue Active Sub- Stance
OCT 1991 22 JAN 1992 10	TOTAL RECOV- BRABLE (UG/L AS FE)	TOTAL RECOV- ERABLE (UG/L AS PB)	NESE, TOTAL RECOV- ERABLE (UG/L AS MN)	TOTAL RECOV- ERABLE (UG/L AS HG)	NIUM, TOTAL (UG/L AS SE)	TOTAL RECOV- ERABLE (UG/L AS AG)	TOTAL RECOV- BRABLE (UG/L AS ZN)	TOTAL (MG/L AS CN)	TOTAL (UG/L)	LENE BLUE ACTIVE SUB- STANCE (MG/L)
OCT 1991 22 JAN 1992 10 FRB 18	TOTAL RECOV- ERABLE (UG/L AS FE)	TOTAL RECOV- ERABLE (UG/L AS PB)	NESE, TOTAL RECOV- ERABLE (UG/L AS MN)	TOTAL RECOV- ERABLE (UG/L AS HG)	NIUM, TOTAL (UG/L AS SE)	TOTAL RECOV- ERABLE (UG/L AS AG)	TOTAL RECOV- BRABLE (UG/L AS ZN)	TOTAL (MG/L AS CN)	TOTAL (UG/L)	LENE BLUE ACTIVE SUB- STANCE (MG/L)
OCT 1991 22 JAN 1992 10 FEB 18 APR 07	TOTAL RECOV- ERABLE (UG/L AS FE)	TOTAL RECOV- ERABLE (UG/L AS PB)	NESE, TOTAL RECOV- ERABLE (UG/L AS MN)	TOTAL RECOV- ERABLE (UG/L AS HG)	NIUM, TOTAL (UG/L AS SE)	TOTAL RECOV- ERABLE (UG/L AS AG)	TOTAL RECOV- BRABLE (UG/L AS ZN)	TOTAL (MG/L AS CN) <0.010	TOTAL (UG/L)	LENE BLUE ACTIVE SUB- STANCE (MG/L)
OCT 1991 22 JAN 1992 10 FBB 18	TOTAL RECOV- BRABLE (UG/L AS FE) 2800	TOTAL RECOV- ERABLE (UG/L AS PB)	NESE, TOTAL RECOV- ERABLE (UG/L AS MN)	TOTAL RECOV- BRABLE (UG/L AS HG) <0.10	NIUM, TOTAL (UG/L AS SE)	TOTAL RECOV- RRABLE (UG/L AS AG) <1	TOTAL RECOV- BRABLE (UG/L AS ZN) <10	TOTAL (MG/L AS CN) <0.010	TOTAL (UG/L)	LENE BLUB ACTIVE SUB- STANCE (MG/L)

50144000 RIO GRANDE DE AÑASCO NEAR SAN SEBASTIAN, PR

LOCATION.--Lat 18°17'05", long 67°03'05", Hydrologic Unit 21010003, on right bank, at downstream side of bridge on Highway 108, 0.4 mi (0.6 km) downstream from Quebrada La Zumbadora, 4.4 mi (7.1 km) northwest of Las Marías, 5.4 mi (8.7 km) southwest of San Sebastián.

DRAINAGE AREA.--94.3 mi² (244.2 km²), does not include 36.2 mi² (93.8 km²) which contributes only during high floods, and 3.5 mi² (9.1 km²) which contributes only part of its storm runoff.

WATER-DISCHARGE RECORDS

PERIOD OF RECORD. -- March 1963 to current year.

GAGE.--Water-stage recorder. Datum of gage is 103.72 ft (31.614 m) above mean sea level (Puerto Rico Department of Public Works bench mark). Previous to Oct. 30, 1975, at site 600 ft (180 m) upstream at same datum.

REMARKS.--Records fair except those for estimated daily discharges, which are poor. Transbasin diversion (except during floods) to Río Yauco basin for hydroelectric power and irrigation above Lago Guayo, Yahuecas, and Prieto, combined useable storage 17,300 acre-ft (21.3 hm³). Limited storm runoff is contributed to basin by 3.5 mi² (9.1 km²) above Río Toro Diversion dam. Gage-height and precipitation satellite telemetry at station.

		DI SCHA RO	ER, CUBIC	C FERT PR		ATER YE MEAN VA	AR OCTOBER	1991 TO	SEPTEMBE	R 1992		
DAY	OCT	NOV	DEC	JAN	FEB	MAR	APR	MAY	JUN	JUL	AUG	SEP
1	273	565	121	103	73	60	324	69	563	67	403	782
2	240	317	119	106	69	60	221	80	388	67	184	354
3	231	271	117	85	68	54	122	76	249	94	136	206
4	210	270	118	82	68	54	83	64	192	107	364	162
5	200	247	114	83	68	57	65	59	170	104	410	170
6	200	236	111	1940	67	57	56	56	292	66	494	640
7	360	219	109	256	81	57	5 4	71	563	62	455	1480
8	343	209	109	137	71	75	5 9	56	1400	59	231	2150
9	382	203	107	112	65	60	173	52	466	66	338	772
10	239	254	105	103	58	62	421	52	1230	71	345	1570
11	210	210	105	101	57	63	428	81	511	75	280	621
12	196	194	103	100	57	62	160	139	244	87	173	367
13	268	188	101	96	56	56	126	173	173	75	164	449
14	238	185	101	92	54	50	93	85	349	285	174	676
15	261	179	e1 00	88	52	49	85	75	185	974	139	337
16	196	176	98	94	55	47	161	77	160	175	126	423
17	178	174	98	90	57	49	212	99	134	97	128	312
18	958	168	98	89	56	57	152	616	116	202	123	370
19	886	161	96	86	55	51	593	1990	107	101	110	345
20	669	156	98	86	e54	47	283	911	101	526	154	493
21	1240	156	138	85	67	47	157	312	105	207	549	348
22	1100	148	104	82	65	45	175	277	103	123	489	224
23	779	138	98	81	62	43	109	2260	89	102	256	533
24	343	136	95	79	62	41	89	1870	94	257	221	321
25	395	134	94	81	62	43	78	856	. 82	278	515	376
26	268	134	92	81	64	46	71	604	78	126	378	243
27	234	129	91	80	65	47	68	380	76	128	185	204
28	239	132	90	77	60	92	64	552	72	149	138	469
29	224	142	86	79	59	292	59	715	72	121	125	701
30	379	126	84	79		265	60	485	68	90	128	4510
31	722		84	74		151		835		1310	128	
TOTAL	12661	5957	3184	4807	1807	2239	4801	14027	8432	6151	8043	20608
MEAN	408	199	103	155	62.3	72.2	160	452	281	198	259	687
MAX	1240	565	138	1940	81	292	593	2260	1400	1310	549	4510
MIN	178	126	84	74	52	41	54	52	68	59	110	162
AC-FT	25110	11820	6320	9530	3580	4440	9520	27820	16720	12200	15950	40880
CFSM	4.33	2.11	1.09	1.64	.66	.77	1.70	4.80	2.98	2.10	2.75	7.28
IN.	4.99	2.35	1.26	1.90	.71	.88	1.89	5.53	3.33	2.43	3.17	8.13
e Ba	timated											
STATIST	CICS OF M	ONTHLY MEA	N DATA F	OR WATER	YEARS 1963	- 1992,	BY WATER	YBAR (WY)				
MESM	647	450	222	120	105	00 1	144	257	284	282	366	611
MEAN MAX	1094	746	223 482	139 215	161	98.1 271	144 313	357 108 4	284 815	657	936	1422
(WY)	1991	1982	1966	1970	1981	1972	1971	1986	1979	1979	1979	1984
MIN	344	199	103	83.6	62.3	54.4	49.3	63.7	71.2	111	152	206
(WY)	1983	1992	1992	1965	1992	1965	1968	1967	1977	1990	1967	1983
SUMMARY	STATIST	ıcs	FOR	1991 CALE	NDAR YEAR	I	OR 1992 WA	TER YEAR		WATER YE	ARS 1963	3 - 1992
ANNUAL	тотат.			94938			92717					
ANNUAL				260			253			308		
	' ANNUAL	MEAN		200			233			460		1979
	ANNUAL M									189		1967
	DAILY M			2690	Aug 5		4510	Sep 30		19400	Car	16 1975
	DAILY ME			2690 58	Aug 5 Apr 23		4510	Mar 24		32		18 1965
		Y MINIMUM		66	Apr 18		45	Mar 20		35		14 1965
	TANEOUS P			00	Whr To		21400	Sep 30		140000		16 1975
		BAK STAGE					13.35			33.90		16 1975
	TANBOUS L						40	Mar 24		33.90		19 1965
	RUNOFF (188300			183900	****		223300	vAr	_, _,,,,
	RUNOFF (2.7	6		2.69	1		3.27		
		,		,	-		2.03			J /		

50144000 RIO GRANDE DE AÑASCO NEAR SAN SEBASTIAN, PR--Continued (National stream-quality accounting network station)

WATER-QUALITY RECORDS

PERIOD OF RECORD. -- Water years 1963 to current year

WATER QUALITY DATA, WATER YEAR OCTOBER 1991 TO SEPTEMBER 1992

DATE	TIME	DIS- CHARGE, INST. CUBIC FRET PER SECOND	SPE- CIFIC CON- DUCT- ANCE (US/CM)	PH WATER WHOLE FIELD (STAND- ARD UNITS)	TEMPER- ATURE WATER (DEG C)	TUR- BID- ITY (NTU)	OXYGEN, DIS- SOLVED (MG/L)	OXYGEN, DIS- SOLVED (PER- CENT SATUR- ATION)	COLI- FORM, FECAL, 0.7 UM-MF (COLS./ 100 ML)	STREP- TOCOCCI FECAL, KF AGAR (COLS. PER 100 ML)	HARD- NESS TOTAL (MG/L AS CACO3)
OCT 1991 31	0950	351	175	7.4	22.0	780	8.4	92	33000	30000	74
JAN 1992											
29 APR	1035	73	260	8.2	25.0	3.5	8.8	95	K680	440	110
23 JUL	1020	107	245	7.6	25.0	65	10.0	119	5400	5700	72
15	1005	420	230	7.5	25.0	190	7.2	88	4100	3000	81
DATE	HARD- NESS NONCARB WH WAT TOT FLD MG/L AS CACO3	CALCIUM DIS- SOLVED (MG/L AS CA)	MAGNE- SIUM, DIS- SOLVED (MG/L AS MG)	SODIUM, DIS- SOLVED (MG/L AS NA)	SODIUM AD- SORP- TION RATIO	POTAS- SIUM, DIS- SOLVED (MG/L AS K)	ALKA- LINITY WAT WH TOT FET FIBLD MG/L AS CACO3	SULFATE DIS- SOLVED (MG/L AS SO4)	CHLO- RIDE, DIS- SOLVED (MG/L AS CL)	FLUO- RIDE, DIS- SOLVED (MG/L AS F)	SILICA, DIS- SOLVED (MG/L AS SIO2)
OCT 1991 31		19	6.4	6.7	0.3	2.1	70	9.1	6.1	<0.10	22
JAN 1992 29		29	9.7	10	0.4	1.5	110	11	9.5	0.20	30
APR 23		20	5.4	8.2	0.4	2.1	110	7.8	11	0.20	18
JUL 15		20	7.5	6.2	0.3	1.8		10	6.6	<0.10	21
DATE	SOLIDS, RESIDUR AT 180 DEG. C DIS- SOLVED (MG/L)	SOLIDS, SUM OF CONSTI- TUENTS, DIS- SOLVED (MG/L)	SOLIDS, DIS- SOLVED (TONS PER DAY)	NITRO- GEN, NO2+NO3 DIS- SOLVED (MG/L AS N)	NITRO- GEN, AMMONIA DIS- SOLVED (MG/L AS N)	NITRO- GEN, AMMONIA DIS- SOLVED (MG/L AS NH4)	NITRO- GEN, AM- MONIA + ORGANIC TOTAL (MG/L AS N)	PHOS- PHORUS TOTAL (MG/L AS P)	PHOS- PHORUS DIS- SOLVED (MG/L AS P)	PHOS- PHORUS ORTHO, DIS- SOLVED (MG/L AS P)	PHOS- PHATE, ORTHO, DIS- SOLVED (MG/L AS PO4)
OCT 1991 31	127	120	114	1.30	0.050	0.06	1.3	0.470	0.040	0.030	0.09
JAN 1992 29	151	169	33	0.330	0.010	0.01	<0.20	0.040	0.040	0.030	0.09
APR 23	108	143	41	0.890	0.060	0.08	0.50	0.140	0.060	0.050	0.15
JUL											
15	124	121	137	0.940	0.060	0.08	1.0	0.270	<0.010	0.030	0.09
DATE	ALUM- INUM, DIS- SOLVED (UG/L AS AL)	ARSENIC DIS- SOLVED (UG/L AS AS)	BARIUM, DIS- SOLVED (UG/L AS BA)	BERYL- LIUM, DIS- SOLVED (UG/L AS BE)	CADMIUM DIS- SOLVED (UG/L AS CD)	CHRO- MIUM, DIS- SOLVED (UG/L AS CR)	COBALT, DIS- SOLVED (UG/L AS CO)	COPPER, DIS- SOLVED (UG/L AS CU)	IRON, DIS- SOLVED (UG/L AS PE)	LEAD, DIS- SOLVED (UG/L AS PB)	LITHIUM DIS- SOLVED (UG/L AS LI)
OCT 1991 31	100		30				<3		100		<4
JAN 1992 29	<10		32			~-	∢3	~-	12		<4
APR 23	80		32				∢3	~-	87		<4
JUL 15	90		28				<3		150		<4

50144000 RIO GRANDE DE AÑASCO NR SAN SEBASTIAN, P.R. (National stream-quality accounting network station)

WATER-QUALITY DATA

DATE	MANGA- NESE, DIS- SOLVED (UG/L AS MN)	MERCURY DIS- SOLVED (UG/L AS HG)	MOLYB- DENUM, DIS- SOLVED (UG/L AS MO)	NICKEL, DIS- SOLVED (UG/L AS NI)	SELE- NIUM, DIS- SOLVED (UG/L AS SE)	SILVER, DIS- SOLVED (UG/L AS AG)	STRON- TIUM, DIS- SOLVED (UG/L AS SR)	VANA- DIUM, DIS- SOLVED (UG/L AS V)	ZINC, DIS- SOLVED (UG/L AS ZN)	SEDI- MENT, SUS- PENDED (MG/L)	SEDI- MENT, DIS- CHARGE, SUS- PENDED (T/DAY)
OCT 1991 31	3		<10	2	1	<1.0	98	<6			
JAN 1992 29 APR	13		20	<1	<1	<1.0	140	<6			
23 JUL	14		<10	3	<1	<1.0	110	<6			
15	13		<10	6	<1	<1.0	94	<6			

PARTICLE-SIZE DISTRIBUTION OF SUSPENDED SEDIMENT

DATE	TIME	STREAM- FLOW, INSTAN- TANEOUS	SEDI- MENT, SUS- PENDED	SEDI- MENT, DIS- CHARGE, SUS- PENDED	SED. SUSP. SIEVE DIAM. PERCENT FINER THAN
OCT 1991		(CFS)	(MG/L)	(T/DAY)	.062 MM
31	0950	351	1150	1089	99
JAN 1992	0330	331	1150	1003	
29	1035	73	37.8	7.5	95
APR					
23	1020	107	43	12.4	88
JUL					
15	1005	420	369	418	47

50146000 RIO GRANDE DE AÑASCO NEAR AÑASCO, PR

WATER-QUALITY RECORDS

LOCATION.--Lat 18°16'00", long 67°08'05", at bridge on Highway 430, 0.2 mi (0.3 km) south of Highway 109 at El Espino and 1.4 mi (2.3 km) east-southeast from Añasco plaza.

DRAINAGE AREA.--139 mi2 (360 km2) this does not include 39.7 mi2 (102.8 km2), flow is diverted to south coast.

PERIOD OF RECORD .-- Water years 1979 to current year.

K = non-ideal count

WATER-QUALITY DATA, WATER YEAR OCTOBER 1991 TO SEPTEMBER 1992

		1	WATER-QUA	LITY DATA	, WATER	YEAR	OCTOBE	R 1991 T	O SEPTEM	BER 1992			
DATE	TIME	CHARC INS' CUB: FEI PEI SECC	GR, SPE T. CIF IC CON BT DUC R ANC	PIC WHO I- PIE T- (ST) E AF	TER OLB HLD TEM NND- AT ND WA	PER- URE TER G C)	TUR BID ITY (NTU	- DI	D SO EN, (P S- C VED SA	IS- DEL LVED CE ER- IC ENT (F TUR- LEV	(AND, IEM- CAL IIGH /EL) (COLI- FORM, FECAL, 0.45 UM-MF COLS./ 00 ML)	STREP- TOCOCCI FECAL, (COLS. PER 100 ML)
NOV 1991 08	0715	235		252	7.8	24.5	9.	1	7.4	82	<10	400	530
18	0800	129		258	7.8	23.5	6.	0	7.0	74	11	270	K180
FEB 1992 19 APR	0855	74		268	7.5	23.5	2.	5	7.2	79	<10	230	K150
08	0905	69		258	7.0	24.5	20		7.3	86	10	K740	270
JUL 07	0845	110		230	6.9	28.0	8.	0	6.6	54	<10	K130	480
92	0930	350		150	6.8	25.0	250		5.4	61	29	37000	58000
DATE	N1 T0 (1	ARD- BSS OTAL MG/L AS ACO3)	CALCIUM DIS- SOLVED (MG/L AS CA)	MAGNE- SIUM, DIS- SOLVED (MG/L AS MG)	SODIUM, DIS- SOLVED (MG/L AS NA)	SO	DIUM AD- RP- ION TIO	POTAS- SIUM, DIS- SOLVED (MG/L AS K)	ALKA- LINITY WAT WH TOT FET FIELD MG/L AS CACO3	SULFIDE TOTAL (MG/L AS S)	SULFA DIS- SOLV (MG/ AS SO	Te ri Di ED so L (M	LO- DE, S- LVED G/L CL)
NOV 1991 08		110	28	9.4	11		0.5	1.7	100	<0.5	12	1	.0
DEC 18									100		, 1 <u>-</u>	_	
FEB 1992									100				
19 APR													
JUL 08		110	28	9.3	10		0.4	2.4	100	<0.5			5
07 Sep									95				
02		63	17	4.9	6.4		0.4	2.8	70		8.	5	6.2
DATE	R: Sc (1	LUO- IDE, DIS- OLVED MG/L S F)	SILICA, DIS- SOLVED (MG/L AS SIO2)	SOLIDS, SUM OF CONSTI- TUENTS, DIS- SOLVED (MG/L)	SOLIDS, DIS- SOLVED (TONS PER DAY)	TOT AT DEG SU PEN	105 . C,	NITRO- GEN, NITRATE TOTAL (MG/L AS N)	NITRO- GEN, NITRITE TOTAL (MG/L AS N)	NITRO- GEN, NO2+NO3 TOTAL (MG/L AS N)	GEN	, G IA ORG L TO L (M	TRO- EN, ANIC TAL G/L
NOV 1991													
08 Dec	•	<0.10	32	164	104		167		<0.010	0.790	0.0	20	
18 FEB 1992							2	0.510	0.010	0.520	0.0	20	
19 APR							11		<0.010	0.140	0.0	20	
08		0.20	31	173	32.3		50	0.470	0.030	0.500	0.0	80	
07 SEP							28	0.380	0.010	0.390	0.0	40	
02	•	<0.10	18	99	93.5		540	0.890	0.060	0.950	0.1	00	0.40

50146000 RIO GRANDE DE AÑASCO NEAR AÑASCO, PR--Continued WATER-QUALITY DATA, WATER YEAR OCTOBER 1991 TO SEPTEMBER 1992

DATE	NITRO- GEN, AM- MONIA + ORGANIC TOTAL (MG/L AS N)	NITRO- GEN, TOTAL (MG/L AS N)	NITRO- GEN, TOTAL (MG/L AS NO3)	PHOS- PHORUS TOTAL (MG/L AS P)	ARSENIC TOTAL (UG/L AS AS)	BARIUM, TOTAL RECOV- ERABLE (UG/L AS BA)	BORON, TOTAL RECOV- ERABLE (UG/L AS B)	CADMIUM TOTAL RECOV- ERABLE (UG/L AS CD)	CHRO- MIUM, TOTAL RECOV- ERABLE (UG/L AS CR)	COPPER, TOTAL RECOV- ERABLE (UG/L AS CU)
NOV 1991										
08	<0.20			0.040	1	<100	40	<1	<1	60
DEC 18	<0.20			0.050						
FBB 1992										
19 APR	<0.20			0.040						
08 JUL	<0.20			0.020	<1	<100	20	<1	<1	<10
07 SEP	<0.20			0.030						
02	0.50	1.5	6.4	0.100		*-				
DATE	IRON, TOTAL RECOV- ERABLE (UG/L AS FE)	LEAD, TOTAL RECOV- ERABLE (UG/L AS PB)	MANGA- NESE, TOTAL RECOV- ERABLE (UG/L AS MN)	MERCURY TOTAL RECOV- ERABLE (UG/L AS HG)	SELE- NIUM, TOTAL (UG/L AS SE)	SILVER, TOTAL RECOV- ERABLE (UG/L AS AG)	ZINC, TOTAL RRCOV- ERABLE (UG/L AS ZN)	CYANIDE TOTAL (MG/L AS CN)	PHENOLS TOTAL (UG/L)	METHY- LENE BLUE ACTIVE SUB- STANCE (MG/L)
NOV 1991		_							_	
08 Dec	650	3	70	<0.10	<1	<1	20	<0.010	<1	0.02
18										
FEB 1992 19										
APR 08	1500	<1	170	<0.10	<1	<1	10	<0.010	3	0.02
JUL		_	1,0		•				_	
07 Sep										
02										
			P	ESTICIDE	analyses					
DATE	TIME	PCB, TOTAL (UG/L)	ALDRIN, TOTAL (UG/L)	CHLOR- DANE, TOTAL (UG/L)	DDD, TOTAL (UG/L)	DDE, TOTAL (UG/L)	DDT, TOTAL (UG/L)	DI- AZINON, TOTAL (UG/L)	DI- BLDRIN TOTAL (UG/L)	ENDO- SULFAN, TOTAL (UG/L)
JUL 1992										
07	0845	<0.1	<0.010	<0.1	<0.010	<0.010	<0.010	<0.01	<0.010	<0.010
DA:	(VG/	er TRD ethi C Tot		OR, EPOX AL TOT	OR IDE LIND AL TOT		ON, CHL AL TOT	Y- PAR OR, THI AL TOT	A- ON, MIR AL TO	EX, TAL /L)
07		010 <0	.01 <0.	010 <0.	010 <0.	010 <0	.01 <0	.01 <0	.01 <0	.01
DA?	PAR THI TR TOT (UG	ON, CHL	A- ES, Y- PE OR. THA AL TOT	NE APHE AL TOT	NB, TR AL THI	I- 2,4	AL TOT		AL TOT	AL
JUL 199			, ,,,	, ,,	,	, , , , , ,		. =, (,	_, ,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,	<i>-</i>
07		.01 <0	.10 <	0.1 <	1 <0	.01 0	.09 <0	.01 <0	.01 <0	.01

THIS PAGE WAS LEFT BLANK INTENTIONALLY




Figure 27.-Río Culebrinas basin.

442 RIO CULEBRINAS BASIN

50147600 RIO CULEBRINAS NEAR SAN SEBASTIAN, PR

WATER-QUALITY RECORDS

LOCATION.--Lat 18°20'51", long 67°02'40", at bridge on Highway 423, 1.3 mi (2.1 km) south of Quebrada El Salto Bridge on Highway 111, and 2.1 mi (3.4 km) west of Central La Plata.

DRAINAGE AREA. -- 58.2 mi2 (150.7 km2).

PERIOD OF RECORD. -- Water years 1979 to current year.

WATER-QUALITY DATA, WATER YEAR OCTOBER 1991 TO SEPTEMBER 1992

DATE	TIME	DIS- CHARGE, INST. CUBIC FERT PER	SPE- CIFIC CON- DUCT-	PH WATER WHOLE FIELD (STAND-	TEMPER-	TUR- BID- ITY	OXYGEN, DIS- SOLVED	OXYGEN, DIS- SOLVED (PER- CENT SATUR-	OXYGEN DEMAND, CHEM- ICAL (HIGH LEVEL)	COLI- FORM, FECAL, 0.45 UN-MF	
DATE	TIME	SECOND	ANCE (US/CM)	ARD UNITS)	WATER (DEG C)	(NTU)	(MG/L)	ATION)	(MG/L)	100 ML)	
NOV 1991				A							
08	1145	123	270	7.9	25.0	36	8.0	78	<10	24000	
DEC									4.0		
18 FEB 1992	1240	44	280	8.2	24.0	6.1	9.6	116	<10	430	
19	1415	18	289	7.2	26.0	5.6	9.6	107	<10	K70	
APR	4 3 3 3 3	-	715					-	1	347.4	
07	1205	36	325	7.6	25.0	6.5	8.2	97	<10	440	
JUL						4.4				0540	
08	1030	66	276	7.6	26.5	8.4	8.3	91	<10	2500	
27	1100	250	315	7.4	25.0	110	7.4	69	11	20000	
	STREP- TOCOCCI	HARD- NESS	CALCIUM	MAGNE- SIUM,	SODIUM,	SODIUM AD-	POTAS- SIUM,	ALKA- LINITY WAT WH		SULFATE	
	FECAL,	TOTAL (MG/L	DIS-	DIS-	DIS-	SORP-	DIS-	TOT FET	SULFIDE	DIS-	
DATE	(COLS. PER	AS	SOLVED (MG/L	SOLVED (MG/L	SOLVED (MG/L	TION RATIO	SOLVED (MG/L	FIRLD MG/L AS	TOTAL (MG/L	(MG/L	
DAID	100 ML)	CACO3)	AS CA)	AS MG)	AS NA)	KATIO	AS K)	CACO3	AS S)	AS SO4)	
	100 1111,	,	,						,	,	
NOV 1991											
08	20000	130	42	4.9	8.6	0.2	2.9	110	<0.5	18	
18	240						- 22	100			
FRB 1992	240				Jes			100			
19 APR	700							100	12		
07	560	120	40	5.4	16	0.6	4.1	110	<0.5	21	
JUL	630			2.5	12			110			
AUG											
27	K13000	140	48	4.7	7.9	0.3	2.4	140		14	
				SOLIDS,		RESIDUE					
	CHLO-	FLUO-	SILICA,	SUM OF	solids,	TOTAL	NITRO				NITRO-
	RIDE, DIS-	RIDE, DIS-	DIS- SOLVED	CONSTI-	DIS- SOLVED	DEG. C.	GEN, NITRAT	GEN, B NITRITE	GEN, B NO2+NO3	GEN, AMMONIA	GEN, ORGANIC
	SOLVED	SOLVED	(MG/L	DIS-	(TONS	SUS-	TOTAL	TOTAL	TOTAL	TOTAL	TOTAL
DATE	(MG/L	(MG/L	AS	SOLVED	PER	PENDED	(MG/L	(MG/L	(MG/L	(MG/L	(MG/L
	AS CL)	AS F)	SI02)	(MG/L)	DAY)	(MG/L)	AS N)	AS N)	AS N)	AS N)	AS N)
NOV 1991 08	11	0.10	21	190	19.8	46	1.17	0.030	1.20	0.060	0.54
DEC	11	0.10	41	190	17.0	40	1.17	0.030	1.20	0.000	0.54
18 FEB 1992						1	1.47	0.030	1.50	0.050	0.25
19 APR					4-	10	1.28	0.020	1.30	0.020	0.18
07 JUL	17	0.10	34	204	125	13	1.42	0.080	1.50	0.060	0.24
08			44			14	1.16	0.040	1.20	0.060	
27	9.5	0.10	16	185	63	138		<0.010	0.980	0.040	0.16
K = non-id	eal count										

RIO CULEBRINAS BASIN

50147600 RIO CULEBRINAS NEAR SAN SEBASTIAN, PR--Continued WATER-QUALITY DATA, WATER YEAR OCTOBER 1991 TO SEPTEMBER 1992

DATE	NITRO- GEN, AM- MONIA + ORGANIC TOTAL (MG/L AS N)	NITRO- GEN, TOTAL (MG/L AS N)	NITRO- GEN, TOTAL (MG/L AS NO3)	PHOS- PHORUS TOTAL (MG/L AS P)	ARSENIC TOTAL (UG/L AS AS)	BARIUM, TOTAL RECOV- ERABLE (UG/L AS BA)	BORON, TOTAL RECOV- ERABLE (UG/L AS B)	CADMIUM TOTAL RECOV- ERABLE (UG/L AS CD)	CHRO- MIUM, TOTAL RECOV- ERABLE (UG/L AS CR)	COPPER, TOTAL RECOV- ERABLE (UG/L AS CU)
NOV 1991										
08 Dec	0.60	1.8	8.0	0.110	1	<100	10	<1	<1	10
18	0.30	1.8	8.0	0.170						
FEB 1992 19	0.20	1.5	6.6	0.250						
APR 07	0.30	1.8	8.0	0.210	1	<100	40	<1	<1	10
JUL		1.0	0.0			4100	40	~-	•	**
08 Aug	<0.20			0.120						
27	0.20	1.2	5.2	0.050						
DATE	IRON, TOTAL RECOV- ERABLE (UG/L AS FE)	LEAD, TOTAL RECOV- ERABLE (UG/L AS PB)	MANGA- NESE, TOTAL RECOV- ERABLR (UG/L AS MN)	MERCURY TOTAL RECOV- ERABLE (UG/L AS HG)	SELE- NIUM, TOTAL (UG/L AS SE)	SILVER, TOTAL RECOV- ERABLE (UG/L AS AG)	ZINC, TOTAL RECOV- ERABLE (UG/L AS ZN)	CYANIDE TOTAL (MG/L AS CN)	PHENOLS TOTAL (UG/L)	METHY- LENE BLUE ACTIVE SUB- STANCE (MG/L)
NOV 1991	TOTAL RECOV- ERABLE (UG/L AS FE)	TOTAL RECOV- ERABLE (UG/L AS PB)	NESE, TOTAL RECOV- ERABLE (UG/L AS MN)	TOTAL RECOV- ERABLE (UG/L AS HG)	NIUM, TOTAL (UG/L AS SR)	TOTAL RECOV- ERABLE (UG/L AS AG)	TOTAL RECOV- ERABLE (UG/L AS ZN)	TOTAL (MG/L AS CN)	TOTAL (UG/L)	LENE BLUE ACTIVE SUB- STANCE (MG/L)
	TOTAL RECOV- ERABLE (UG/L	TOTAL RECOV- ERABLE (UG/L	NESE, TOTAL RECOV- ERABLE (UG/L	TOTAL RECOV- ERABLE (UG/L	NIUM, TOTAL (UG/L	TOTAL RECOV- ERABLE (UG/L	TOTAL RECOV- ERABLE (UG/L	TOTAL (MG/L	TOTAL	Lene Blue Active Sub- Stance
NOV 1991 08 DEC 18	TOTAL RECOV- ERABLE (UG/L AS FE)	TOTAL RECOV- ERABLE (UG/L AS PB)	NESE, TOTAL RECOV- ERABLE (UG/L AS MN)	TOTAL RECOV- ERABLE (UG/L AS HG)	NIUM, TOTAL (UG/L AS SR)	TOTAL RECOV- ERABLE (UG/L AS AG)	TOTAL RECOV- ERABLE (UG/L AS ZN)	TOTAL (MG/L AS CN)	TOTAL (UG/L)	LENE BLUE ACTIVE SUB- STANCE (MG/L)
NOV 1991 08 DBC 18 FEB 1992 19	TOTAL RECOV- ERABLE (UG/L AS FE)	TOTAL RECOV- ERABLE (UG/L AS PB)	NESE, TOTAL RECOV- ERABLE (UG/L AS MN)	TOTAL RECOV- ERABLE (UG/L AS HG)	NIUM, TOTAL (UG/L AS SR)	TOTAL RECOV- ERABLE (UG/L AS AG)	TOTAL RECOV- ERABLE (UG/L AS ZN)	TOTAL (MG/L AS CN)	TOTAL (UG/L)	LENE BLUE ACTIVE SUB- STANCE (MG/L)
NOV 1991 08 DEC 18 FEB 1992 19 APR 07	TOTAL RECOV- ERABLE (UG/L AS FR)	TOTAL RECOV- ERABLE (UG/L AS PB)	NESE, TOTAL RECOV- ERABLE (UG/L AS MN)	TOTAL RECOV- ERABLE (UG/L AS HG) <0.10	NIUM, TOTAL (UG/L AS SR)	TOTAL RECOV- ERABLE (UG/L AS AG)	TOTAL RECOV- ERABLE (UG/L AS ZN)	TOTAL (MG/L AS CN) <0.010	TOTAL (UG/L)	LENE BLUE ACTIVE SUB- STANCE (MG/L) 0.02
NOV 1991 08 DEC 18 FEB 1992 19	TOTAL RECOV- ERABLR (UG/L AS FR)	TOTAL RECOV- ERABLE (UG/L AS PB) <1	NESE, TOTAL RECOV- ERABLE (UG/L AS MN)	TOTAL RECOV- BRABLE (UG/L AS HG) <0.10	NIUM, TOTAL (UG/L AS SE) <1	TOTAL RECOV- REABLE (UG/L AS AG) <1	TOTAL RECOV- ERABLE (UG/L AS ZN)	TOTAL (MG/L AS CN) <0.010	TOTAL (UG/L)	LENE BLUE ACTIVE SUB- STANCE (MG/L) 0.02

444

RIO CULEBRINAS BASIN

50147800 RIO CULEBRINAS AT HIGHWAY 404 NEAR MOCA, PR

LOCATION.--Lat 18°21'42", long 67°05'33", Hydrologic Unit 21010003, on right bank, at bridge on Highway 404, 0.3 mi (0.5 km) downstream from Quebrada Yagruma, and 2.8 mi (4.5 km) southeast of Moca.

DRAINAGE AREA. -- 71.2 mi2 (184.4 km2).

WATER-DISCHARGE RECORDS

PERIOD OF RECORD .-- July 1967 to current year.

GAGE.--Water-stage recorder. Elevation of gage is 45 ft (14 m), from topographic map.

REMARKS.--Records fair except those for estimated daily discharges, which are poor. Gage-height and precipitation satellite telemetry at station.

-		DI SCHARG	E, CUBIC	PERT PER		WATER YI MEAN V	BAR OCTOBER	1991 T O	september	1992		
DAY	OCT	NOV	DRC	JAN	FRB	MAR	APR	MAY	JUN	JUL	AUG	SEP
1	266	297	92	79	46	29	116	66	e700	129	688	240
2	261	198	89	81	e4 3	28	92	65	e4 80	124	357	236
3	237	179	86	61	e4 2	28	61	65	e300	133	174	187
4	189	183	87	57	e4 0	29	52	61	e220	e258	135	171
5	175	166	85	89	41	29	44	59	e200	e270	130	163
6 7	167 160	155	84 81	208 99	42	28	39 40	99 84	e350 e800	e250 e190	153 191	181 179
8	438	286 e200	81	80	44 42	27 33	42	62	e1800	e160	155	e2700
š	530	e160	78	75	40	31	297	59	e500	e170	128	e940
10	322	e155	76	71	40	27	341	65	e1600	e1 80	144	e1900
11	218	e150	76	72	41	28	473	93	e600	e 190	108	e 800
12	209	e145	75	74	39	36	184	276	e4 00	e23 0	96	e4 50
13	669	e140	71	71	38	42	117	189	e200	e170	107	e 560
14	263	e140	71	68	39	29	124	173	e600	e620	1080	e860
15	272	e 127	71	65	38	30	100	216	e480	e 1100	238	e41 0
16	199	124	73	69	37	28	86	139	e350	e 220	184	e 520
17	172	119	82	60	36	30	e400	152	e300	e180	e153 e160	e390 e460
18 19	540 2910	116 113	71 67	57 56	34 34	34 32	e170 e820	103 625	e350 323	e270 e180	e140	e420
20	658	107	68	55	33	28	e350	304	248	e680	e190	e620
21	379	107	76	56	32	27	e180	165	216	e220	e 680	e41 0
22	257	102	67	57	31	29	e220	165	198	e170	e600	e27 0
23	214	97	65	56	32	25	e110	3090	182	e 160	e 300	e 680
24	190	97	62	54	31	26	92	686	249	e3 30	e270	e4 00
25	1780	95	61	54	31	27	85	426	187	e 330	e 640	e4 70
26	351	103	59	55	31	62	78	409	160	e 160	e1400	e 300
27	237	103	58	54	31	45	74	323	151	e150	744	e250
28 29	445 272	104	56	50	33	104	72 68	1350 e600	143 139	e240 e190	360 286	e 600 e 800
30	218	100 95	55 55	49 47	31	175 442	68	e350	135	e140	250	e2700
31	729		56	45		260		e1100		139	232	
TOTAL	13927	4263	2234	2124	1072	1828	4995	11619	12561	7933	10473	19267
MBAN	449	142	72.1	68.5	37.0	59.0	166	375	419	256	338	642
MAX	2910	297	92	208	46	442	820	3090	1800	1100	1400	2700
min AC-PT	160 27620	95 8460	55 4430	45 4210	31 2130	25 3630	39 9910	59 23050	135 24910	124 15740	96 2077 0	163 38220
CFSM	6.31	2.00	1.01	.96	.52	. 83	2.34	5.26	5.88	3.59	4.74	9.02
IN.	7.28	2.23	1.17	1.11	.56	. 96	2.61	6.07	6.56	4.14	5.47	10.07
e E	stimated											
STATIS'	TICS OF M	ONTHLY MEAN	DATA FO	R WATER Y	BARS 1967	- 1992	, BY WATER Y	BAR (WY)			
MEAN	625	354	145	77.1	69.8	65.9	135	471	389	321	344	520
MAX	1086	799	424	151	243	319	621	2054	769	847	831	1350
(WY)	1973	1982	1982	1971	1981	1981	1986	1986	1984	1979	1979	1978
MIN	231	108	72.1	51.2	37.0	30.4	26.4	96.7	82.7	91.8	119	145
(WY)	1968	1979	1992	1979	1992	1979	1970	1973	1974	1983	1970	1986
SUMMAR	Y STATIST	ICS	FOR 1	991 CALEN	DAR YEAR	1	FOR 1992 WAT	TER YBAR		WATER Y	TEARS 1967	7 - 1992
ANNUAL				89250			92296					
HIGHES	MEAN TANNUAL 1	MBAN		245			252			295 457		1986
	ANNUAL M									179		1977
	T DAILY M			5060	May 17		3090	May 23		13300		21 1972
	DAILY ME			27	Apr 1		25	Mar 23		19		16 1979
	SEVEN-DA			29	Mar 15		28 16600	Mar 19 Oct 19		20 69000		13 1979 16 1975
	TANEOUS PI TANEOUS PI							Oct 19		36.6		16 1975
	TANEOUS L						24	Mar 23		16		17 1979
	RUNOFF (177000			183100			213900	_	
	RUNOFF (3.43			3.54			4.1		
	RUNOFF (46.63			48.22			56.3	4	
	CENT EXCE			490 113			600 141			600 138		
	CENT BXCE			38			36			42		
2 - E 10 K				50								

RIO CULBBRINAS BASIN 445

50149100 RIO CULEBRINAS NEAR AGUADA, PR

WATER-QUALITY RECORDS

LOCATION.--Lat 18°24'03", long 67°09'40", at bridge on Highway 2, and 2.3 mi (3.7 km) northeast of Aguada plaza.

DRAINAGE AREA. -- 97.0 mi2 (251.2 km2).

PERIOD OF RECORD. -- Water years 1958, 1970 to current year.

WATER-QUALITY DATA, WATER YEAR OCTOBER 1991 TO SEPTEMBER 1992

DATE	TIMR	CHARCE INSTACTOR OF THE PROPERTY OF THE PROPER	GB, SPE T. CIF IC CON ET DUC R ANC	IC WHO - FIE T- (STA B AR	er Ole Ild tem Ind- at Id wa	PER- URB TER G C)	TUR- BID- ITY (NTU)	SOL SOL	SPN, (S- VED S	YGEN, DIS- OLVED PBR- CENT ATUR- TION)	OXYGE DEMAN CHEN ICAI (HIG LEVEI (MG/I	ND, FOR 4- FRO 5 0.4 3H UM- 5) (COL	M, STREP- AL, TOCOCCI 5 FECAL, MF (COLS. S./ PER
NOV 1991 08	0930	438		263	7.6	24.5	270		5.4	70		62 K86	000 55000
DEC 18 FRB 1992	1045	110		304	8.0	23.5	4.7	,	4.8	62		13 K	140 K110
19 APR	1145	47		330	7.7	24.5	4.0	5	6.3	79	•	:10	K60 K60
08 JUL	1100	50		312	7.3	27.0	9.7	7	7.2	86		16 K2	000 920
07 SEP	0945	150		320		26.5	29		6.6	82		11	250 730
02	1045	250		326	6.6	27.0	9.3	3	3.6	46		18 29	000 76000
DATE	N T((1	ARD- BSS OTAL MG/L AS ACO3)	CALCIUM DIS- SOLVED (MG/L AS CA)	MAGNE- SIUM, DIS- SOLVED (MG/L AS MG)	SODIUM, DIS- SOLVED (MG/L AS NA)	SOI T	DIUM AD- RP- ION PIO	POTAS- SIUM, DIS- SOLVED (MG/L AS K)	ALKA- LINITY WAT WH TOT FE FIELD MG/L A CACO3	T SUL TO TO	FIDE TAL (G/L (S)	SULFATE DIS- SOLVED (MG/L AS SO4)	CHLO- RIDE, SIS- SOLVED (MG/L AS CL)
NOV 1991 08		120	38	5.4	8.5		0.3	2.6	14	0	<0.5	11	11
DEC 18									12	0			
FRB 1992 19									13	0			
λPR 08		130	44	5.8	14		0.5	2.9	13	0	<0.5	17	15
JUL 07 Srp									13	0			
02		130	45	5.4	11		0.4	2.4	13	0		14	15
DATE	R: S: (i	LUO- IDR, DIS- OLVED MG/L S F)	SILICA, DIS- SOLVED (MG/L AS SIO2)	SOLIDS, SUM OF CONSTI- TUENTS, DIS- SOLVED (MG/L)	SOLIDS, DIS- SOLVED (TONS PER DAY)	TOTA AT 1 DEG. SU:	105 . C, 1 8-	NITRO- GEN, NITRATE TOTAL (MG/L AS N)	NITRO GEN, NITRIT TOTAL (MG/L AS N)	E NO2 TO	TRO- EN, +NO3 TAL (G/L	NITRO- GEN, AMMONIA TOTAL (MG/L AS N)	NITRO- GEN, ORGANIC TOTAL (MG/L AS N)
NOV 1991 08		0.10	16	177	209		21	0.620	0.05	.0 0	.670	0.090	1.0
DEC 18							1		<0.03		.890	0.040	0.16
FEB 1992 19							11		<0.01		.590	0.030	0.17
APR 08		0.10	36	213	28.8		21	0.750	0.04		.790	0.100	0.20
JUL 07							38	0.800	0.03	0 0	.830	0.070	0.13
SEP 02		0.10	26	203	137		192	0.840	0.02	0 0	.860	0.080	0.42

K = non-ideal count

RIO CULEBRINAS BASIN

50149100 RIO CULEBRINAS NEAR AGUADA, PR--Continued WATER-QUALITY DATA, WATER YEAR OCTOBER 1991 TO SEPTEMBER 1992

DATE	NITRO- GEN,AM- MONIA + ORGANIC TOTAL (MG/L AS N)	NITRO- GEN, TOTAL (MG/L AS N)	NITRO- GEN, TOTAL (MG/L AS NO3)	PHOS- PHORUS TOTAL (MG/L AS P)	ARSENIC TOTAL (UG/L AS AS)	BARIUM, TOTAL RECOV- ERABLE (UG/L AS BA)	TOTAL RECOVERABLE (UG/L	TOTAL - RECOV- B BRABLI	TOTAL RECOV- RRABLE (UG/L	COPPER, TOTAL RECOV- ERABLE (UG/L AS CU)
NOV 1991										
08	1.1	1.8	7.8	0.130	2	200	4	0 1	29	100
DRC 18	0.20		4.8	0.090						
FRB 1992	0.20	1.1	4.0	0.030						
19	0.20	0.79	3.5	0.080						
APR 08	0.30	1.1	4.8	0.080	1	<100) 3	0 <:	1 <1	<10
JUL										
07 SRP	0.20	1.0	4.6	0.050						
02	0.50	1.4	6.0	0.080						
DATE	IRON, TOTAL RECOV- ERABLE (UG/L AS FR)	LEAD, TOTAL RECOV- ERABLE (UG/L AS PB)	MANGA- NESE, TOTAL RECOV- ERABLE (UG/L AS MN)	MERCURY TOTAL RECOV- ERABLE (UG/L AS HG)	SELE- NIUM, TOTAL (UG/L AS SE)	SILVER, TOTAL RECOV- ERABLI (UG/L AS AG)	TOTAL RECOV BRABL (UG/L	- CYANID B TOTAL (MG/L	PHENOLS TOTAL	METHY- LENE BLUE ACTIVE SUB- STANCE (MG/L)
NOV 1991										
08	18000	18	660	0.10	<1	<1	12	0 <0.01	0 1	0.01
DRC 18										
FEB 1992										
19 APR										
08	570	<1	30	<0.10	<1	<1	<1	0 <0.01	0 3	0.03
JUL 07										
SEP 02										
			_							
			P	RSTICIDE	ANALYSES					
DA	TR TI	PCB TOT (UG/	AL TOT		R, DE	AL TO	TAL T	DDT, R	LDRIN SUL OTAL TO	DO- FAN, TAL G/L)
JUL 19	92									
07	. 094	45 <	0.1 <0.	010 <	0.1 <0.	010 <	.010 <	0.010 <	0.010 <0	.010
DA [,]	ENDR: WATI UNFL' TE REG (UG/1	er TRD ethi C tot	AL TOT	OR, RPOX	OR IDE LINE AL TOI	ANE T	ALA- IION, C TAL T	OXY- P. HLOR, T OTAL T	OTAL T	REX, OTAL G/L)
JUL 19	92									
07		010 <0	.01 <0.	010 <0.	010 <0.	010	0.01	<0.01	<0.01 <	0.01
DA	PARI THIC TB TOTA	ON, CHL	A- BS, Y- PB OR. THA AL TOT	NE APHE	AL THI	I- 2,		OTAL T	OTAL TO	VEX, TAL
	(DG)	/L) (UG/	L) (UG	/L) (UG	(UG	(T) (T	JG/L) (UG/L) (U	G/L) (U	G/L)
JUL 19 07		.01 <0	.10 <	0.1 <	1 <0	.01	0.12	<0.01	<0.01 <	0.01

CULEBRA, PR 447

50214500 QUEBRADA RESACA NEAR MONTE RESACA, CULEBRA, PR

LOCATION.--Lat 18°19'11", long 65°18'10", Hydrologic Unit 21010006, on right bank, 1.0 mi (1.6 km), north of Culebra City Hall, 0.9 mi (1.4 km) southwest of Monte Resaca, and 1.0 mi (1.6 km) east of Bahia Tamarindo.

DRAINAGE ARRA. -- 0.23 mi2 (0.60 km2).

WATER-STAGE RECORDS

PERIOD OF RECORD. -- October 1991 to September 1992 (gage-height only).

GAGE. -- Water-stage recorder. Elevation of gage is 66 ft (20 m), from topographic map.

REMARKS.--Gage-height and precipitation satellite telemetry at station. All gage-heights of 5.30 ft or lower are considered zero flow.

EXTREMES FOR CURRENT YEAR.--Maximum gage-height 7.49 ft (2.283 m), May 26; minimum, 4.78 ft (1.457 m), June 8,13,15.

GAGE HEIGHT, FEET, WATER YEAR OCTOBER 1991 TO SEPTEMBER 1992 DAILY MEAN VALUES												
DAY	OCT	NOV	DBC	Jan	FBB	MAR	APR	MAY	JUN	JUL	AUG	SEP
1		4.91	4.90	4.91	4.91	4.90	4.88	4.89	4.83	4.81	4.82	4.81
2		4.90	4.99	4.92	4.91	4.89	4.88	4.89	4.83	4.81	4.82	4.82
2 3 4		4.90	5.07	4.92	4.91	4.89	4.88	4.89	4.82	4.82	4.82	4.81
4		4.90	4.92	4.92	5.10	4.89	4.88	4.89	4.82	4.82	4.83	4.81
5		4.91	4.97	5.15	4.91	4.88	4.88	4.89	4.81	4.82	4.84	4.81
6 7		4.91	4.90	5.72	4.92	4.88	4.88	4.89	4.81	4.82	4.83	4.81
7		5.06	4.90	5.40	4.90	4.88	4.88	4.89	4.80	4.82	4.83	4.81
8	5.30	5.19	4.90	5.21	4.90	4.88	4.89	4.89	4.80	4.82	4.83	4.81
9	5.39	5.06	4.90	5.32	4.90	4.88	4.89	4.90	4.80	4.82	4.83	4.84
10	5.29	5.17	4.89	5.72	4.91	4.88	4.89	4.89	4.81	4.82	4.83	4.82
11	5.18	4.94	4.88	5.58	4.91	4.88	4.89	4.90	4.80	4.82	4.83	4.82
12	5.08	4.91	4.89	5.46	4.91	4.87	4.89	4.90	4.80	4.82	4.83	4.84
13	5.03	4.91	4.89	5.45	4.91	4.88	4.89	4.90	4.79	4.82	4.83	4.83
14	4.95	4.91	4.89	5.41	4.91	4.89	4.89	4.90	4.79	4.82	4.82	4.83
15	4.91	4.90	4.90	5.37	4.91	4.88	4.89	4.89	4.79	4.81	4.82	4.84
16	4.91	4.98	4.94	5.31	4.91	4.89	4.90	4.89	4.80	4.80	4.82	4.83
17	4.91	4.90	4.95	5.20	4.91	4.88	4.89	4.89	4.81	4.80	4.82	4.83
18	4.91	4.90	4.91	4.96	4.91	4.89	4.89	4.89	4.80	4.80	4.82	4.81
19	4.92	4.90	4.90	4.91	4.91	4.89	4.89	4.88	4.80	4.80	4.82	4.83
20	4.91	4.90	4.98	4.92	4.90	4.89	4.89	4.88	4.81	4.80	4.82	4.82
21	4.91	4.93	4.90	4.92	4.90	4.89	4.89	4.88	4.80	4.81	4.82	4.82
22	4.91	4.92	4.94	4.91	4.90	4.89	4.89	4.88	4.80	4.83	4.82	4.83
23	4.94	4.90	4.93	4.91	4.90	4.89	4.89	5.11	4.79	4.81	4.82	4.82
24	4.92	4.98	4.92	4.91	4.90	4.89	4.89	5.64	4.80	4.81	4.82	4.83
25	4.91	4.90	4.91	4.92	4.90	4.89	4.89	5.51	4.80	4.81	4.82	4.82
26	4.91	4.90	4.90	4.91	4.90	4.89	4.89	5.67	4.81	4.81	4.82	4.82
27	4.91	4.90	4.90	4.91	4.90	4.89	4.89	5.30	4.81	4.81	4.81	4.83
28	4.91	4.90	4.91	4.91	4.89	4.88	4.88	5.15	4.81	4.81	4.81	4.82
29	4.91	4.95	4.91	4.91	4.89	4.88	5.01	5.01	4.81	4.81	4.82	4.82
30	4.90	4.90	4.91	4.91		4.87	4.90	4.89	4.81	4.82	4.81	4.82
31	4.91		4.91	4.91		4.88		4.84		4.82	4.81	
MEAN		4.94	4.92	5.12	4.91	4.88	4.89	4.99	4.81	4.81	4.82	4.82
MAX		5.19	5.07	5.72	5.10	4.90	5.01	5.67	4.83	4.83	4.84	4.84
MIN		4.90	4.88	4.91	4.89	4.87	4.88	4.84	4.79	4.80	4.81	4.81

CULEBRA, PR

50215000 DRAINAGE CANAL AT CULEBRA AIRPORT, CULEBRA, PR

LOCATION.--Lat 18°19'06", long 65°18'32", Hydrologic Unit 21010006, on right bank, 0.5 mi (0.8 km), northwest of Culebra City Hall, 0.9 mi (1.4 km) northwest of desalination plant, 0.3 mi (0.5 km) northeast of Playa Sardinas I, and of Highway 251 at airport south perimeter fence.

DRAINAGE AREA. -- 0.08 mi 2 (0.20 km2).

WATER-STAGE RECORDS

PERIOD OF RECORD. -- October 1991 to September 1992 (gage-height only).

GAGE.--Water-stage recorder. Elevation of gage is 66 ft (22 m), from topographic map.

REMARKS.--Gage-height and precipitation satellite telemetry at station. All gage-heights of 10.25 ft or lower are considered zero flow.

EXTREMES FOR CURRENT YEAR. -- Maximum gage-height recorded, 10.27 ft (3.130 m), Nov. 16, but may have been higher during period of no gage-height record Jan. 5,6; minimum, 9.73 ft (2.966 m), March 6.

GAGE HEIGHT, FEET, WATER YEAR OCTOBER 1991 TO SEPTEMBER 1992 DAILY MEAN VALUES												
DAY	OCT	NOV	DEC	JAN	FEB	MAR	APR	MAY	JUN	JUL	AUG	SEP
1		10.22	10.20		10.11		10.08	10.05	10.02	10.06	10.25	
2		10.20	10.21		10.12	10.12	10.08	10.05	10.02	10.06	10.25	
3		10.21	10.20		10.14	10.12	10.08		10.01	10.06	10.25	
4		10.21	10.19		10.16	10.15	10.09	10.02	10.02	10.06	10.25	
5		10.21	10.20		10.16	10.12	10.08	10.03	10.02	10.05	10.25	
6		10.23	10.18		10.16		10.07	10.03	10.02		10.25	
7		10.24	10.16		10.17		10.07	10.03	10.02	10.23	10.25	
8		10.24	10.20		10.17	10.13		10.03	10.04	10.25	10.25	
9		10.24	10.19		10.16	10.13	10.02	10.03	10.04	10.24	10.25	10.25
10	10.24	10.24	10.18		10.16	10.13	10.02	10.03	10.07		10.25	10.25
11	10.23	10.23	10.17		10.14	10.13	10.02	10.04	10.09	10.22	10.25	10.25
12	10.23	10.24	10.16		10.12	10.13	10.02	10.04	10.05	10.22	10.25	10.25
13	10.23	10.23	10.15		10.11	10.13	10.02	10.04	10.04	10.24		10.25
14	10.23	10.23			10.11	10.14	10.02	10.04	10.04	10.25		10.25
15	10.23	10.21		10.16	10.11	10.14	10.02	10.04	10.07	10.25		10.25
16	10.23	10.23		10.16	10.12	10.14	10.02	10.04	10.06	10.25		10.25
17	10.23	10.23		10.15	10.11	10.15	10.02	10.04	10.05	10.25		10.25
18	10.23	10.22		10.15	10.11	10.16	10.02	10.04	10.05	10.25		10.25
19	10.23	10.22		10.12	10.13	10.18	10.03	10.05	10.05	10.25		10.25
20	10.21	10.19		10.10	10.12	10.18	10.04	10.04	10.06	10.25		10.25
21	10.19	10.21		10.10	10.12	10.18	10.05	10.04	10.08	10.25		10.25
22	10.21	10.22		10.10	10.13	10.19	10.04	10.04	10.03	10.25		10.25
23	10.22	10.21		10.10	10.12	10.20	10.05	10.05	10.04	10.25		10.25
24	10.23	10.21		10.11	10.11	10.20	10.05	10.05	10.04	10.25		10.25
25	10.23	10.21		10.13	10.10	10.20	10.05	10.04	10.04	10.25		10.25
26	10.23	10.22		10.15	10.10	10.20	10.05	10.04	10.05	10.25		10.25
27	10.23	10.22		10.13	10.09	10.14	10.05	10.05	10.05	10.25		10.25
28	10.23	10.19		10.12	10.09	10.08	10.05	10.03	10.06	10.25		10.25
29	10.23	10.20		10.12	10.09	10.08	10.05	10.07	10.06	10.25		10.25
30	10.23	10.21		10.12		10.07	10.05	10.02	10.06	10.25		10.25
31	10.23			10.11		10.07		10.02		10.25		
MBAN		10.22			10.13				10.04			
MAX		10.24			10.17				10.09			
MIN		10.19			10.09				10.01			

VIRQUES, PR 449

50231000 QUEBRADA COFRESI TRUBUTARY NEAR ISABEL SEGUNDA, VIEQUES, PR

LOCATION.--Lat 18°08'21", long 65°26'06", Hydrologic Unit 21010006, on right bank, 1.0 mi (1.6 km), southsouthwest of Isabel Segunda Plaza, 0.5 mi (0.8 km) north of Destino school, and 1.5 mi (2.4 km) southeast of junction of Highways 200 and 201.

DRAINAGE AREA. -- 0.28 mi 2 (0.72 km2).

WATER-STAGE RECORDS

PERIOD OF RECORD. -- July 1991 to current year (gage-height only).

GAGE.--Water-stage recorder. Elevation of gage is 196 ft (60 m), from topographic map.

REMARKS.--Gage-height and precipitation satellite telemetry at station. All gage-heights of 8.20 ft or lower are considered zero flow.

EXTREMES FOR CURRENT PERIOD.--JULY TO SEPTEMBER 1991: Maximum gage-height, 9.75 ft (2.972 m), Aug. 27; minimum, 7.95 ft (2.423 m), Aug. 19, 20.

WATER YRAR 1992: Maximum gage-height, 10.51 ft (3.20 m), Jan. 5, 1992; minimum, 7.69 ft (2.344 m), Aug. 28.

GAGE HEIGHT, FEET, WATER YEAR OCTOBER 1990 TO SEPTEMBER 1991 DAILY MEAN VALUES

1	DAY	OCT	NOV	DEC	JAN	FRB	MAR	APR	MAY	JUN	JUL	AUG	SEP
2	1											8.50	8.64
\$ 8.45 8.62 6 8.47 8.63 7 8.48 8.65 8 9.44 8.63 9 10 8.32 8.63 12 8.27 8.60 13 8.23 8.59 14 8.20 8.16 8.55 16 8.14 8.54 17 8.11 8.53 19 8.08 8.59 20 8.64 21 8.61 8.53 21 8.63 8.64 22 8.64 23 8.59 24 8.56 25 8.57 26 8.56 8.57 27 8.54 8.77 28 8.54 8.77 29 8.54 8.77 20 8.55 8.77 21 8.56 22 8.56 23 8.56 24 8.56 25 8.57 26 8.58 8.77 27 8.54 8.77 28 8.54 8.77 29 8.54 8.77 20 8.55 8.57 21 8.56 22 8.56 23 8.56 24 8.56 8.57 25 8.57 26 8.56 8.57 27 8.54 8.77 28 8.54 8.77 29 8.54 8.77 28 8.56 8.57 29 8.56 8.57 20 8.55 8.57 21 8.56 8.57 22 8.56 8.57 23 8.56 8.57 24 8.56 8.57 25 8.56 26 8.56 8.57 27 8.54 8.77 28 8.54 8.77 29 8.54 8.74 29 8.55 8.57 20 8.55 8.57 20 8.55 8.57 21 8.55 8.57 22 8.55 8.57 23 8.55 8.57 24 8.56 8.57 25 8.57 26 8.56 8.57 27 8.58 8.77 28 8.58 8.77 29 8.58 8.77 20 8.59 8.57 20 8.55 8.57 20 8.55 8.57 20 8.55 8.57 20 8.55 8.57 20 8.55 8.57 21 8.55 8.57 22 8.55 8.57 23 8.55 8.57 24 8.56 8.57 25 8.57 26 8.57 8.57 27 8.58 8.57 28 8.58 8.71 29 8.58 8.77 20 8.59 8.57 20 8.50 8.57	2												
\$ 8.45 8.62 6 8.47 8.63 7 8.48 8.65 8 9.44 8.63 9 10 8.32 8.63 12 8.27 8.60 13 8.23 8.59 14 8.20 8.16 8.55 16 8.14 8.54 17 8.11 8.53 19 8.08 8.59 20 8.64 21 8.61 8.53 21 8.63 8.64 22 8.64 23 8.59 24 8.56 25 8.57 26 8.56 8.57 27 8.54 8.77 28 8.54 8.77 29 8.54 8.77 20 8.55 8.77 21 8.56 22 8.56 23 8.56 24 8.56 25 8.57 26 8.58 8.77 27 8.54 8.77 28 8.54 8.77 29 8.54 8.77 20 8.55 8.57 21 8.56 22 8.56 23 8.56 24 8.56 8.57 25 8.57 26 8.56 8.57 27 8.54 8.77 28 8.54 8.77 29 8.54 8.77 28 8.56 8.57 29 8.56 8.57 20 8.55 8.57 21 8.56 8.57 22 8.56 8.57 23 8.56 8.57 24 8.56 8.57 25 8.56 26 8.56 8.57 27 8.54 8.77 28 8.54 8.77 29 8.54 8.74 29 8.55 8.57 20 8.55 8.57 20 8.55 8.57 21 8.55 8.57 22 8.55 8.57 23 8.55 8.57 24 8.56 8.57 25 8.57 26 8.56 8.57 27 8.58 8.77 28 8.58 8.77 29 8.58 8.77 20 8.59 8.57 20 8.55 8.57 20 8.55 8.57 20 8.55 8.57 20 8.55 8.57 20 8.55 8.57 21 8.55 8.57 22 8.55 8.57 23 8.55 8.57 24 8.56 8.57 25 8.57 26 8.57 8.57 27 8.58 8.57 28 8.58 8.71 29 8.58 8.77 20 8.59 8.57 20 8.50 8.57	3												8.64
\$ 8.45 8.62 6 8.47 8.63 7 8.48 8.65 8 9.44 8.63 9 10 8.32 8.63 12 8.27 8.60 13 8.23 8.59 14 8.20 8.16 8.55 16 8.14 8.54 17 8.11 8.53 19 8.08 8.59 20 8.64 21 8.61 8.53 21 8.63 8.64 22 8.64 23 8.59 24 8.56 25 8.57 26 8.56 8.57 27 8.54 8.77 28 8.54 8.77 29 8.54 8.77 20 8.55 8.77 21 8.56 22 8.56 23 8.56 24 8.56 25 8.57 26 8.58 8.77 27 8.54 8.77 28 8.54 8.77 29 8.54 8.77 20 8.55 8.57 21 8.56 22 8.56 23 8.56 24 8.56 8.57 25 8.57 26 8.56 8.57 27 8.54 8.77 28 8.54 8.77 29 8.54 8.77 28 8.56 8.57 29 8.56 8.57 20 8.55 8.57 21 8.56 8.57 22 8.56 8.57 23 8.56 8.57 24 8.56 8.57 25 8.56 26 8.56 8.57 27 8.54 8.77 28 8.54 8.77 29 8.54 8.74 29 8.55 8.57 20 8.55 8.57 20 8.55 8.57 21 8.55 8.57 22 8.55 8.57 23 8.55 8.57 24 8.56 8.57 25 8.57 26 8.56 8.57 27 8.58 8.77 28 8.58 8.77 29 8.58 8.77 20 8.59 8.57 20 8.55 8.57 20 8.55 8.57 20 8.55 8.57 20 8.55 8.57 20 8.55 8.57 21 8.55 8.57 22 8.55 8.57 23 8.55 8.57 24 8.56 8.57 25 8.57 26 8.57 8.57 27 8.58 8.57 28 8.58 8.71 29 8.58 8.77 20 8.59 8.57 20 8.50 8.57	4												8.63
6 8.47 8.63 7 8.48 8.65 8 8.44 8.65 9 8.40 8.67 10 8.36 8.66 11 8.32 8.66 11 8.32 8.27 8.60 13 8.23 8.29 8.59 14 8.54 8.16 8.53 19 8.04 8.53 19 8.04 8.53 19 8.04 8.53 19 8.04 8.53 19 8.04 8.53 19 8.04 8.53 19 8.05 8.16 8.55 21 8.61 8.53 22 8.64 23 8.64 25 8.65 26 8.56 8.57 27 8.54 8.77 28 8.54 8.77 28 8.54 8.77 29 8.54 8.74 30 8.55 8.57 31 8.54 8.77 31 8.55 8.57 31 8.56 8.57 31 8.57 31 8.54 8.77 31 8.54 8.77 31 8.55 8.67 31 8.54 8.71 31 8.55 8.67 31 8.54 8.71 31 8.55 8.67 31 8.54 8.71 31 8.54 8.71 31 8.57 31 8.57 31 8.57 31 8.57 31 8.57 31 8.57 31 8.57 31 8.57	5												8.62
7 8													
7 8	6											8.47	8.63
11	7												8.65
11	8												8.63
11	9												8.67
12 13 14 16 15 16 17 18 18 18 19 19 20 8.55 19 18 18 18 18 18 19 20 8.64 8.53 19 21 21 21 22 8.64 8.53 24 25 25 26 27 28 8.54 8.77 28 8.54 8.77 29 8.54 8.77 29 8.54 8.71 29 8.54 8.77 29 8.54 8.77 29 8.54 8.77 29 8.54 8.77 29 8.54 8.77 29 8.54 8.77 29 8.54 8.77 29 8.54 8.77 29 8.54 8.77 29 8.54 8.77 29 8.55 8.57 20 8.58 8.77 20 8.58 8.77 20 8.58 8.77 20 8.58 8.77 20 8.59 20 8.50 8.50 8.50 8.50 8.50 8.50 8.50 8.5	10											8.36	8.66
12 13 14 16 15 16 17 18 18 18 19 19 20 8.55 19 18 18 18 18 18 19 20 8.64 8.53 19 21 21 21 22 8.64 8.53 24 25 25 26 27 28 8.54 8.77 28 8.54 8.77 29 8.54 8.77 29 8.54 8.71 29 8.54 8.77 29 8.54 8.77 29 8.54 8.77 29 8.54 8.77 29 8.54 8.77 29 8.54 8.77 29 8.54 8.77 29 8.54 8.77 29 8.54 8.77 29 8.54 8.77 29 8.55 8.57 20 8.58 8.77 20 8.58 8.77 20 8.58 8.77 20 8.58 8.77 20 8.59 20 8.50 8.50 8.50 8.50 8.50 8.50 8.50 8.5													
14 15 16 16 17 18 11 18 18	11												8.63
14 15 16 16 17 18 11 18 18	12												8.60
15 16 17 18.14 8.14 8.15 18 19 8.08 8.53 19 8.04 8.53 20 8.61 8.53 21 8.61 8.53 22 8.64 8.59 8.56 8.56 8.57 25 26 8.56 8.57 27 8.56 8.57 29 8.54 8.77 29 8.54 8.71 29 8.54 8.71 29 8.54 8.71 29 8.54 8.71 29 8.54 8.71 29 8.54 8.71 29 8.54 8.71 29 8.54 8.71 29 8.54 8.71 29 8.54 8.71 29 8.54 8.71 29 8.55 8.56 29 8.56 8.57 20 8.58 8.57 20 8.58 8.58 8.79 8.59 8.50 8	13												8.59
16 17 18 18 19 20 8.08 8.53 19 20 8.61 8.53 21 21 8.61 8.53 22 8.61 8.59 24 8.59 25 8.56 8.57 26 8.57 28 8.54 8.74 29 8.54 8.74 31 MEAN MAX	16												0.30
17 18 19 20 8.08 8.53 20 8.04 8.53 21 21 8.61 8.53 22 8.64 23 8.59 24 25 8.57 26 8.56 8.57 28 8.54 8.77 28 8.54 8.74 29 8.54 8.74 31 MEAN MAX	13											0.10	0.55
17 18 19 20 8.08 8.53 20 8.04 8.53 21 21 8.61 8.53 22 8.64 23 8.59 24 25 8.57 26 8.56 8.57 28 8.54 8.77 28 8.54 8.74 29 8.54 8.74 31 MEAN MAX	16											8.14	8.54
19 20 8.04 8.53 21 21 8.61 8.53 22 8.64 8.56 8.56 8.56 25 8.56 8.57 27 28 8.54 8.77 28 8.54 8.74 29 8.54 8.74 29 30 8.54 8.71 29 30 8.54 8.71 29 30 8.54 8.71 29 30 8.54 8.71 29 30 30 30 30 30 30 30 30 30 30 30 30 30	17												8.53
19 20 8.04 8.53 21 21 8.61 8.53 22 8.64 8.56 8.56 8.56 25 8.56 8.57 27 28 8.54 8.77 28 8.54 8.74 29 8.54 8.74 29 30 8.54 8.71 29 30 8.54 8.71 29 30 8.54 8.71 29 30 8.54 8.71 29 30 30 30 30 30 30 30 30 30 30 30 30 30	18												8.53
21	19												8.53
21	20											8.16	8.53
22													
23 24 25 26 27 28 27 28 29 30 30 31 MEAN MAX 8.59 8.56 8.57 8.57 8.54 8.77 8.54 8.74 8.54 8.71 8.65 8.65 8.43 8.77 8.77												8.61	8.53
24 25 8.56 8.57 26 8.56 8.57 27 8.54 8.77 28 8.54 8.74 30 8.54 8.71 31 MRAN MRAN 8.43 8.77 8.77	22											8.64	
25 26 27 28 8.54 8.77 28 8.54 8.74 29 8.54 8.71 31 8.52 8.67 31 MEAN MAX 8.43 8.77 8.77	23											8.59	
26 8.56 8.57 27 8.54 8.77 28 8.54 8.74 29 8.54 8.71 31 8.52 8.67 31 8.65 MEAN MAX 8.43 8.77	24												
27 28 8.54 8.77 29 8.54 8.74 30 8.52 8.67 31 MRAN MAX 8.43 8.77 8.77	25											8.57	
27 28 8.54 8.77 29 8.54 8.74 30 8.52 8.67 31 MRAN MAX 8.43 8.77 8.77	26										0.56	0 57	
28 8.54 8.74 29 8.54 8.71 31 8.52 8.67 31 8.65 MEAN 8.43 8.47 8.77	27												
29 30 8.54 8.71 31 8.52 8.67 8.65 MEAN MAX 8.77 8.77													
30 8.52 8.67 8.65 8.65 MEAN 8.43 8.77													
31 8.65 MRAN 8.43 MAX 8.77											8.52	8.67	
MEAN 8.43 MAX 8.77	31												
MAX 8.77											-	0.03	
MAX 8.77	MRAN											8.43	

VIEQUES, PR
50231000 QUEBRADA COFRESI TRUBUTARY NEAR ISABEL SEGUNDA, VIEQUES, PR-Continued

GAGE HEIGHT, FEET, WATER YEAR OCTOBER 1991 TO SEPTEMBER 1992
DAILY MEAN VALUES

					DAIL	I WRAN VA	LUES					
DAY	OCT	NOV	DBC	JAN	FRB	MAR	APR	MAY	JUN	JUL	AUG	SEP
1			8.53	8.49	8.69	8.46		7.97	8.64	8.52	8.01	7.71
2			8.53	8.47	8.66	8.53		8.26	8.65	8.50	7.96	7.71
3			8.56	8.44	8.66	8.52		8.36	8.65	8.47	7.93	7.71
4	8.55		8.52	8.43	8.69	8.50		8.33	8.64	8.45	7.86	7.72
5	8.49		8.55	8.64	8.66	8.45		8.27	8.63	8.40	8.19	7.72
6	8.47		8.52	8.87	8.67	8.43		8.21	8.63	8.36	8.51	7.72
7	8.44		8.51	8.72	8.66	8.45	8.44	8.19	8.64	8.31	8.50	7.92
8	8.44		8.56	8.70	8.65	8.53	8.40	8.14	8.64	8.25	8.51	8.48
9	8.43		8.51	8.73	8.65	8.47	8.39	8.08	8.64	8.22	8.51	8.50
10	8.43		8.51	8.73	8.64	8.44	8.35	8.01	8.64	8.17	8.50	8.51
11	8.43		8.50	8.72	8.62	8.44	8.31	7.96	8.64	8.15	8.43	8.53
12	8.41		8.48	8.70	8.61	8.43	8.28	7.91	8.64	8.31	8.34	8.51
13	8.41		8.47		8.61	8.42	8.26	7.86	8.65	8.36	8.26	8.51
14	8.38		8.47		8.62	8.47	8.22	7.82	8.65	8.33	8.23	8.55
15	8.31		8.48		8.60	8.51	8.18	7.77	8.65	8.28	8.47	8.49
16	8.30		8.60		8.58	8.46	8.14	7.76	8.64	8.22	8.50	8.56
17			8.53		8.58	8.48	8.10	7.77	8.63	8.39	8.47	
18			8.49		8.58	8.50	8.04	7.76	8.63	8.56	8.44	
19			8.47		8.57	8.47	8.01	7.75	8.62	8.54	8.36	
20			8.50		8.56	8.45	8.00	7.77	8.65	8.52	8.29	
21		8.50	8.51		8.56	8.46	7.99	7.91	8.65	8.54	8.20	
22		8.60	8.48		8.57	8.52	7.98	7.96	8.65	8.59	8.11	
23		8.61	8.45	8.71	8.55	8.49	7.95	8.14	8.65	8.57	8.02	
24		8.56	8.45	8.77	8.54	8.48	7.90	8.78	8.64	8.55	7.97	
25		8.56	8.46	8.75	8.53		7.87	8.63	8.63	8.50	7.91	
26		8.58	8.46	8.75	8.52		7.82	8.65	8.61	8.43	7.83	
27		8.56	8.45	8.72	8.50		7.79	8.65	8.60	8.34	7.77	
28		8.54	8.42	8.71	8.50		7.78	8.63	8.59	8.28	7.71	
29		8.54	8.42	8.69	8.48		7.78	8.64	8.56	8.20	7.71	
30		8.54	8.40	8.69			7.78	8.64	8.54	8.12	7.71	
31			8.52	8.69				8.64		8.05	7.71	
MEAN			8.49		8.60			8.17	8.63	8.37	8.16	
MAX			8.60		8.69			8.78	8.65	8.59	8.51	
MIN			8.40		8.48			7.75	8.54	8.05	7.71	

50232000 QUEBRADA LA MINA NEAR ESPERANZA, VIEQUES, PR

LOCATION.--Lat 18°06'54", long 65°28'15", Hydrologic Unit 21010006, on left bank 300 ft (91 m) west from state road 996, 1.4 mi (2.2 km) south of Cerro Martineau, 0.7 mi (1.1 km) east-northeast of Colonia Puerto Real on road 201 and 1.2 mi (1.9 km) north of Esperanza.

DRAINAGR ARRA. -- 0.68 mi 2 (1.76 km2).

WATER-STAGE RECORDS

PERIOD OF RECORD. -- July 1991 to current year (gage-height only).

GAGR.--Water-stage recorder. Rlevation of gage is 98 ft (30 m), from topographic map.

REMARKS.--Gage-height and precipitation satellite telemetry at station. All gage-heights of 9.20 ft or lower are considered zero flow.

EXTREMES FOR CURRENT PERIOD.--JULY TO SEPTEMBER 1991: Maximum gage-height, 9.18 ft (2.798 m), Aug. 27; minimum, 8.92 ft (2.719 m), July 24-26.

WATER YEAR 1992: Maximum gage-height, 9.51 ft (2.899 m), Jan 5; minimum, 8.81 ft (2.685 m), many days.

GAGE HRIGHT, FERT, WATER YEAR OCTOBER 1990 TO SEPTEMBER 1991 DAILY MEAN VALUES

DAY	OCT	NOV	DEC	JAN	FRB	MAR	APR	МАУ	JUN	JUL	AUG	SRP
1											8.94	8.94
1 2 3 4 5											8.95	8.94
3											8.95	8.94
4											8.94	8.94
5											8.94	8.94
6 7 8 9 10											8.95	8.94
7											8.96	8.94
8											8.96	8.94
9											8.96	8.94
10											8.96	8.94
11											8.97	8.94
12											8.97	8.94
13											8.97	8.94
14											8.97	8.94
15											8.97	8.94
16											8.96	8.94
17											8.96	8.95
18											8.96	8.95
19 20											8.96	8.94
20											8.96	8.94
21											8.95	8.94
22											8.99	8.94
23											8.96	8.94
24											8.96	8.94
25										8.93	8.96	8.94
26										8.93	8.96	8.94
27										8.94	9.01	8.94
28										8.93	8.95	8.94
29										8,94	8.94	8.96
30										8.94	8.94	8.94
31										8.94	8.94	
MBAN											8.96	8.94
MAX											9.01	8.96
MIN											8.94	8.94

VIEQUES, PR
50232000 QUEBRADA LA MINA NEAR ESPERANZA, VIEQUES, PR-Continued
GAGE HEIGHT, FRET, WATER YEAR OCTOBER 1991 TO SEPTEMBER 1992
DAILY MEAN VALUES

					DAIL	I MEAN VA	5000					
DAY	OCT	NOV	DEC	JAN	FRB	MAR	APR	MAY	JUN	JUL	AUG	SEP
1	8.93	8.97	8.84	8.83	8.82	8.83	8.82	8.84	8.82	8.84	8.85	8.85
2	8.93	8.88	8.84	8.83	8.82	8.82	8.82	8.83	8.82	8.84	8.85	8.85
3	8.92	8.88	8.84	8.83	8.82	8.82	8.82	8.83	8.82	8.84	8.85	8.85
4	8.91	8.87	8.84	8.83	8.82	8.81	8.82	8.85	8.82	8.84	8.85	8.85
5	8.91	8.87	8.84	8.90	8.82	8.81	8.82	8.85	8.83	8.84	8.90	8.85
6	8.91	8.87	8.83		8.82	8.81	8.83	8.86	8.83	8.85	8.85	8.85
7	8.91	9.07	8.83		8.82	8.81	8.84	8.85	8.83	8.85	8.85	8.85
8	8.91	9.18	8.83	8.87	8.82	8.81	8.84	8.85	8.83	8.85	8.85	8.85
9	8.93	9.13	8.83	8.83	8.82	8.81	8.84	8.85	8.83	8.85	8.85	8.85
10	8.91	9.00	8.83	8.87	8.82	8.81	8.84	8.85	8.83	8.85	8.85	8.85
11	8.90	8.86	8.83	8.82	8.82	8.81	8.84	8.85	8.83	8.85	8.85	8.85
12	8.90	8.86	8.83	8.82	8.82	8.81	8.84	8.84	8.83	8.85	8.85	8.85
13	8.90	8.86	8.83	8.81	8.82	8.81	8.84	8.85	8.83	8.85	8.85	8.86
14	8.90	8.85	8.83	8.82	8.82	8.82	8.84	8.85	8.83	8.85	8.85	8.86
15	8.90	8.86	8.83	8.82	8.82	8.81	8.85	8.85	8.84	8.85	8.85	8.86
16	8.90	8.86	8.83	8.82	8.82	8.81	8.85	8.85	8.84	8.85	8.85	8.85
17	8.90	8.86	8.83	8.82	8.82	8.81	8.85	8.85	8.84	8.85	8.85	8.85
18	8.90	8.85	8.83	8.82	8.82	8.81	8.85	8.85	8.84	8.85	8.85	8.85
19	8.90	8.85	8.83	8.82	8.82	8.81	8.85	8.85	8.84	8.85	8.85	8.85
20	8.89	8.85	8.83	8.82	8.82	8.81	8.85	8.85	8.84	8.85	8.85	8.88
21	8.89	8.96	8.83	8.82	8.83	8.81	8.85	8.85	8.84	8.85	8.85	8.92
22	8.89	9.12	8.83	8.82	8.85	8.81	8.85	8.85	8.84	8.85	8.85	8.92
23	8.89	9.09	8.83	8.82	8.85	8.81	8.85	8.87	8.84	8.85	8.85	8.90
24	8.89	9.08	8.83	8.82	8.85	8.81	8.85	9.08	8.84	8.85	8.85	8.90
25	8.88	9.00	8.83	8.82	8.85	8.82	8.85	8.98	8.84	8.85	8.85	8.90
26	8.88	9.12	8.83	8.82	8.85	8.82	8.85	8.96	8.85	8.85	8.85	8.90
27	8.88	9.08	8.83	8.82	8.83	8.82	8.85	9.04	8.84	8.85	8.85	8.90
28	8.88	8.95	8.83	8.82	8.83	8.82	8.85	8.90	8.84	8.85	8.85	8.90
29	8.88	8.84	8.83	8.82	8.83	8.82	8.85	8.84	8.84	8.85	8.85	8.90
30	8.88	8.84	8.83	8.82		8.82	8.84	8.82	8.84	8.85	8.85	8.90
31	8.88		8.83	8.82		8.82		8.82		8.85	8.85	
MEAN	8.90	8.95	8.83		8.83	8.81	8.84	8.87	8.83	8.85	8.85	8.87
MAX	8.93	9.18	8.84		8.85	8.83	8.85	9.08	8.85	8.85	8.90	8.92
MIN	8.88	8.84	8.83		8.82	8.81	8.82	8.82	8.82	8.84	8.85	8.85

VIEQUES, PR 453

50233000 QUEBRADA PILON AT COLONIA PUERTO REAL, VIEQUES, PR

LOCATION.--Lat 18°06'37", long 65°28'51", Hydrologic Unit 21010006, on left bank 1.2 mi (1.9 km) southeast of Cerro Sonadora, 1.2 mi (1.9 km) northwest of Esperanza, 0.4 mi (0.6 km) south of junction of Highways 895 and 201.

DRAINAGE ARRA. -- 0.67 mi 2 (1.74 km2).

WATER-STAGE RECORDS

PERIOD OF RECORD. -- July 1991 to current year (gage-height only).

GAGE.--Water-stage recorder. Elevation of gage is 131 ft (40 m), from topographic map.

REMARKS.--Gage-height and precipitation satellite telemetry at station. All gage-heights of 7.20 ft or lower are considered zero flow.

EXTREMES FOR CURRENT PERIOD.--JULY TO SEPTEMBER 1991: Maximum gage-height, 7.33 ft (2.234 m), Aug. 20; minimum, 7.08 ft (2.158 m), Sept. 24-27.

WATER YEAR 1992: Maximum gage-height, 7.36 ft (2.243 m), Aug. 16; minimum, 6.89 ft (2.100 m), Apr 9-13.

GAGE HEIGHT, FEET, WATER YEAR OCTOBER 1990 TO SEPTEMBER 1991 DAILY MEAN VALUES

DAY	OCT	NOV	DEC	JAN	FEB	MAR	APR	MAY	JUN	JOL	AUG	SEP
1 2 3 4 5											7.29 7.29 7.28 7.28 7.28	7.23 7.23 7.21 7.21 7.21
6 7 8 9 10											7.29 7.28 7.27 7.27 7.29	7.21 7.19 7.20 7.19 7.18
11 12 13 14 15											7.29 7.28 7.27 7.28 7.28	7.18 7.17 7.16 7.15 7.14
16 17 18 19 20											7.28 7.26 7.25 7.22 7.27	7.14 7.15 7.15 7.15 7.14
21 22 23 24 25											7.31 7.30 7.28 7.26 7.26	7.14 7.16 7.15 7.11 7.10
26 27 28 29 30 31										7.30 7.30 7.30 7.30 7.30 7.29	7.26 7.26 7.25 7.24 7.24 7.23	7.11 7.12 7.12 7.14 7.12
MIN MAX MEAN											7.27 7.31 7.22	7.16 7.23 7.10

MRAN

MAX

MIN

7.13

7.19

7.29

7.32 7.08 7.32

7.33 7.30

VIBQUES, PR
50233000 QUEBRADA PILON AT COLONIA PUERTO REAL, VIEQUES, PR--Continued

GAGE HRIGHT, FRET, WATER YEAR OCTOBER 1991 TO SEPTEMBER 1992 DAILY MEAN VALUES DAY JUN JUL AUG SEP OCT NOV DRC JAN FRB MAR APR MAY 7.12 7.11 7.08 7.12 7.12 7.08 7.30 7.30 ---7.17 6.96 7.15 7.16 2 7.29 7.28 7.31 7.31 ------7.11 7.15 7.13 6.96 7.12 6.96 7.16 ------7.31 ---7.31 7.31 7.14 7.29 7.08 6.96 7.22 7.16 7.16 ------------7.30 ---7.08 5 7.03 7.16 7.16 7.16 7.30 7.05 7.07 ---7.05 7.13 7.10 ------7.05 7.01 7.02 7.04 7.19 7.15 7.29 7.32 7.30 7.03 ---------7.29 7.29 7.32 7.32 7.29 7.28 7.02 7.01 8 7.14 6.98 ---7.03 10 7.14 7.28 7.32 7.28 ---6.98 6.99 ---6.98 7.06 7.16 11 7.26 7.27 6.96 6.99 7.10 7.04 7.16 7.16 7.14 7.32 ---12 7.15 7.26 7.33 7.25 6.94 7.00 7.19 7.16 7.19 7.33 7.33 7.24 7.23 ------7.00 7.16 7.28 7.16 7.07 13 7.26 6.93 6.98 ------7.25 ---6.94 6.96 14 15 7.19 7.31 7.33 7.25 6.95 7.00 ---6.96 7.31 6.95 16 17 7.00 7.01 ---6.95 7.17 7.15 7.33 7.33 6.93 7.02 7.15 7.32 7.25 ------7.28 6.95 7.14 6.96 6.95 7.23 7.23 7.23 ---7.18 ---7.31 7.33 7.07 7.14 7.31 ------7.01 7.23 7.15 7.13 7.30 7.01 7.13 7.16 19 ---7.23 7.02 7.12 ---7.23 7.05 7.16 20 7.30 7.32 7.22 7.05 7.01 7.16 21 7.12 7.31 7.32 7.22 ---___ 7.01 7.02 7.23 7.01 ------7.12 7.12 7.02 7.04 7.23 7.22 22 23 7.31 7.30 7.32 7.32 7.22 7.24 6.96 7.16 7.16 ------7.12 7.16 ___ 24 25 7.11 7.31 7.31 7.24 ---6.95 7.16 7.21 7.21 7.13 7.16 7.16 7.10 7.33 ---___ 6.96 7.14 26 7.10 7.31 7.33 7.24 ---7.27 6.96 7.17 7.21 7.03 7.16 ------27 7.09 7.31 7.31 7.33 7.32 7.23 7.23 7.26 7.21 6.95 6.95 7.18 7.17 7.17 7.21 7.20 6.98 7.15 7.15 28 ---------29 7.09 7.31 7.32 7.23 7.18 6.97 7.20 6.96 7.16 7.09 7.32 ___ 7.15 7.16 30 7.31 7.17 7.11 7.18 7.19 6.96 ------------31 7.19 6.96 7.15

7.01

7.11 6.93 7.06


7.19 6.98 7.05

7.17 6.95

7.14

7.31

6.96



Discharge at Parcial-Record Stations in Puerto Rico

STATION

STATION

As the number of streams on which streamflow information is likely to be desired far exceeds the number of stream-gaging stations feasible to operate at one time, the Geological Survey collects limited streamflow data at sites other than stream-gaging stations. When limited streamflow data are collected on a systematic basis over a period of years for use in hydrologic analyses, the site at which the data are collected is called a partial-record station. Data collected at these partial-record stations are useable in low-flow or floodflow analyses, depending on the type of data collected. In addition, discharge measurements are made at other sites not included in the partial-record program. These measurements are generally made in times of drought or flood to give better areal coverage to those events. Those measurements and others collected for some special reason are called measurements at miscellaneous sites.

Low-flow partial-record stations

Measurements of streamflow in the areas covered by this report made at low-flow partial-record stations are given in the following table. These measurements were made during periods of base flow when streamflow is primarily from ground-water storage. These measurements, when correlated with the simultaneous discharge of nearby stream when continuous records are available, will give a picture of the low-flow potentiality of stream.

Discharge measurements made at low-flow partial-records stations during water year 1992

PUBLICATION RECORD

LOCATION

DRAINAGE

STREAM-

STATION NUMBER	STATION NAME	LOCATION	DRAINAGE AREA			stream- Flow	
		AND	mi² (km²)	DATE	TIME	ft ³ /s (m ³ /s)	
		Basin					
		Río Melanía basin					
50095900	Quebrada Melanía near Jobos, PR	Lat 17°57'51", long 66°59'30". Hydrologic unit 21010004.	2.75 (7.13)	1/28/92	0715	0.52 (0.015)	
		0.6 mi (1.0 km) upstream from bridge on Hwy 3.		6/19/92	0955	0.32 (0.009)	
50097000	Quebrada Cimarrona near Jobos, PR	Lat 17°59'18", long 66°10'59". Hydrologic unit 21010004.	3.09 (8.00)	1/28/92	0815	0.00	
	Heat Cobos, FR	Barrio Poso Hondo, 2.4 mi (3.7 km) north from Puerto de Jobos, and 4.0 mi (6.4 km) northwest from Guayama Plaza.	(8.00)	6/19/92	0915	0.11 (0.003)	
		Rio Seco basin					
50097800	Río Seco near Central Guamaní, PR	Lat 17°58'06", long 66°10'52". Hydrologic unit 21010004. At	11.2 (29.0)	1/28/92	0745	0.00	
		Bridge on Hwy 3, .2 mi (0.3 (0.3 km) north of Central Guamaní, and 1.2 mi (1.9 km) northwest of Jobos.	(2310)	6/19/92	0942	0.00	
		Río Salinas (Nigua) basin					
50100200	Río Lapa near Rabo del Buey, PR	Lat 18°03'36", long 66°14'28". Hydrologic unit 21010004.	10.0 (25.8)	1/28/92	1300	4.49 (0.127)	
		Barrio Lapa, at Hwy 1, 1.6 mi (2.6 km) upstream from conflu-		6/04/92	0940	17.2 (0.487)	
		ence with Río Majada, and 6.2 mi (10 km) southwest from		6/30/92	0730	4.19 (0.119)	
		Cayey Plaza.		9/29/92	1335	1.15 (0.32)	
50100300	Río Jájome at Jájome, PR	Lat 18°03'49", long 66°09'38". Hydrologic unit 21010004.	4.56 (11.8)	1/28/92	0850	1.54 (0.044)	
		Barrio Jájome Bajo, at Hwy 708, 3.5 mi (5.6 km) south	,	6/04/92	1050	3.63 (0.102)	
		from Cayey Plaza.		6/30/92	0820	2.18 (0.062)	
				9/29/92	1135	2.09 (0.059)	
50100450	Río Majada at La Plena, PR	Lat 18°02'40", long 66°12'27". Hydrologic unit 21010004.	16.7 (43.2)	1/28/92	1005	3.91 (0.111)	
		Barrio Quebrada Yegua, at Hwy 712, 2.0 mi (3.2 km) northeast	(2012)	6/04/92	1135	16.3 (0.462)	
		from Albergue Olímpico, and 5.5 mi (8.8 km) southwest fron		6/30/92	0910	6.66 (0.189)	
		Cayey Plaza.		9/29/92	1215	3.86 (0.109)	
50100700	Río Majada at Rabo del Buey, PR	Lat 18°02'17", long 66°14'27".	22.2 (57.5)	1/28/92	1105	3.51 (0.099)	
	det mest, ty	Hydrologic unit 21010004. Barrio Lapa, 0.2 mi (0.3 km) upstream from confluence with	(3/.3)	6/04/92	1225	20.3 (0.575)	
		Río Lapa, 400 ft upstream from intersection of Hwy's 1 and 712,		6/30/92	1000	6.91 (0.196)	
		and 0.2 mi (0.3 km) nortwest from Albergue Olímpico.		9/29/92	1300	3.21 (0.091)	

		DW-110W Partial-record Stations				
STATION NUMBER	STATION NAME	LOCATION AND	DRAINAGE AREA mi³	DĀTE	TIME	STREAM FLOWS ft ³ /s
		BASIN	(km²)			(m³/s)
50102000	Río Salinas at Salinas, PR	Lat 17°58'42", long 66°18'17". Hydrologic unit 21010004. At Bridge on Hwy 1, and 0.4 mi	52.4 (136)	1/28/92 6/30/92	121 0 105 0	0.45 (0.013) 4.59
		(0.6 km) west from Salinas Plaza.				(0.130)
		Río Jueyes basin				
50102400	Río Jueyes at Río Jueyes, PR	Lat 18°01'17", long 66°19'51". Hydrologic unit 21010004.	3.50 (9.06)	1/29/92	1100	0.24 (0.007)
	oudyds, ra	Barrio Río Jueyes, at Hwy 154, 1.3 mi (2.1 km) upstream from Hwy 52, and 4.5 mi (7.2 km) Southeast from Coamo Plaza.	(3.00)	6/05/92	0730	0.50 (0.014)
50103000	Río Jueyes near	Lat 17°58'45", long 66°20'20".	8.56	1/29/92	1130	0.00
	Jauca, PR	Hydrologic unit 21010004. At bridge on Hwy 1, 1.8 mi (2.9 km) east of Jaucas, and 2.7 mi (4.3 km) west of Salinas Plaza.	(22.2)	6/05/92	0800	0.00
		Río Coamo basin				
50104000	Río Coamo near	Lat 18°07'08", long 66°21'52".	9.05	1/30/92	1130	5.98 (0.169)
	Pasto, PR	Hydrologic unit 21010004. Barrio Pasto, at Hwy 555, 2.6 mi (4.2 km) northwest from Coamo Plaza.	(23.4)	6/04/92	1520	31.0 (0.878)
50105400	Río Cuyón at La	Lat 18°05'20", long 66°16'17".	4.33	1//28/92	1355	1.09
	Guava, PR	Hydrologic unit 21010004. Barrio Algarrobo, at Hwy 717,	(11.2)	6/04/92	0845	(0.031)
		1.0 mi (1.6 km) southwest from Cerro Verdún, and 5.6 mi (9.0 km) east from Coamo Plaza.		6/30/92	0650	(0.093) 0.92 (0.026)
		(5.0 km) eqst 110m count riasa.		9/29/92	1430	0.41 (0.012)
50105600	Río Cuyón near Coamo, PR	Lat 18°05'25", long 66°18'50". Hydrologic unit 21010004.	18.1 (46.8)	1/29/92	0655	5.52 (0.156)
	Councy, FA	Barrio Cuyón, at Hwy 14, 0.8 mi (1.3 km) southeast from Cerro Santa Ana, and 2.8 mi (4.5 km) northeast from Coamo Plaza.	(2010)	6/03/92	0650	22.3 (0.632)
50105900	Quebrada Montería	Lat 18°05'13", long 66°21'04".	7.12	1/29/92	0840	2.23 (0.063)
	near Coamo, PR	Hydrologic unit 21010004. Barrio Pasto, at confluence with Río Cuyón, and 0.5 mi (0.8 km) northeast from Coamo Plaza.	(18.4)	6/03/92	0740	14.4 (0.408)
50106100	Río Coamo at	Lat 18°05'00", long 66°21'16". Hydrologic unit 21010004.	43.5 (113)	1/29/92	0750	17.5 (0.496)
	Coamo, PR	Coamo, at Hwy 14, 500 ft (152 m) downstream from con-	(113)	6/03/92	0835	104 (2.945)
		fluence with Río Cuyón, and 0.2 mi (0.3 km) east from Coamo Plaza.		6/12/92	0840	45.0 (1.274)
50106600	Río de La Mina near Coamo, PR	Lat 18°05'04", long 66°23'22". Hydrologic Unit 21010004.	2.62 (6.78)	1/30/92	0950	0.86 (0.024)
	a. Cumm, FR	Barrio Santa Catalina, at Hwy 150, 2.2 mi (3.5 km) west from Coamo Plaza.	(0.70)	6/03/92	1420	3.02 (0.086)
50106650	Río del Pasto near Coamo, PR	Lat 18°04'49", long 66°22'32". Hydrologic unit 21010004.	1.80 (4.67)	1/30/92	0915	1.28 (0.036)
	engine, tu	Barrio San Idelfonso, at Hwy 150, 1.3 mi (2.1 km) west from Coamo Plaza.	(=-0/)	6/03/92	1455	4.14 (0.117)

STATION NUMBER	STATION NAME	LOCATION	DRAINAGE ARBA			STREAM FLOWS
NONDEK	NAME	AND	mi ² (km ²)	DATE	TIME	ft ³ /s (m ³ /s)
		BASIN	(KM°)			(= / = /
50106700	Río de La Mina at Coamo, PR	Lat 18°03'56", long 66°22'29". Hydrologic unit 21010004.	5.88 (15.2)	1/30/92	0810	2.69 (0.076)
	COAD, FR	Harrio San Idelfonso, at Hwy 14, 0.2 mi (0.3 km) upstream from confluence with Río Coamo, and 1.7 mi (2.7 km) from Coamo Plaza.	(15.4)	6/03/92	1245	9.61 (0.272)
50106820	Río Coamo at Baños de Coamo, PR	Lat 18°02'23", long 66°22'31". Hydrologic unit 21010004.	58.5 (152)	1/29/92	1000	22.5 (0.637)
	de Coamb, FR	Barrio San Idelfonso, at the end of Hwy 546, 3.3 mi (5.3 km)	(132)	6/03/92	0940	80.1 (2.268)
		southwest from Coamo Plaza.		6/12/92	0940	50.2 (1.422)
50107000	Río Coamo near Santa Isabel, PR	Lat 17°58'36", long 66°25'10". Hydrologic unit 21010004. At	69.3 (179)	1/29/92	1150	17.6 (0.498)
	Isabet, ra	bridge on Hwy 1 at Velásques, 1.1 mi (1.8 km) northwest of Santa Isabel Plaza.	(177)	6/19/92	0720	36.2 (1.025)
		Río Descalabrado basin				
50107800	Río Descalabrado near Sanja Blanca, PR	Lat 18°05'24", long 66°24'30". Hydrologic unit 21010004.	4.27 (11.0)	1/30/92	1030	1.80 (0.051)
	Sanja Branca, PR	Barrio Santa Catalina, at Hwy 150, 2.0 mi (3.2 km) southeast	(11.0)	6/03/92	1335	9.17 (0.260)
		from Lago Toa Vaca, and 3.4 mi (5.5 km) northwest from Coamo Plaza.				(0.200)
50108200	Río Descalabrado at Las Ollas, PR	Lat 18°02'10", long 66°25'36". Hydrologic unit 21010004.	13.9 (36.0)	1/30/92	0710	2.62 (0.074)
	DAD VIILE, FA	Barrio Descalabrado, at Hwy 536, 0.6 mi (1.0 km) upstream from Hwy 52, and 2.2 mi (3.5 km) northwest from Cerro del Muerto.	(30.0)	6/05/92	1000	20.2 (0.572)
50108500	Río Descalabrado near Santa Isabel, PR	Lat 17°58'45", long 66°26'35". Hydrologic unit 21010004. At	18.1 (46.9)	1/29/92	1240	0.34 (0.010)
	Saute Isebel, FK	bridge on Hwy 1, 0.9 mi (1.4 km) upstream from mouth, and 3.1 mi (5.0 km) northwest of Santa Isabel.	(40.3)	6/05/92	0820	13.2 (0.374)
		Río Cañas basin				
50109000	Río Cañas near Juana Díaz, PR	Lat 18°02'41", long 66°27'26". Hydrologic unit 21010004.	2.88 (7.47)	1/29/92	1335	0.03 (0.001)
		Barrio Río Cañas Arriba, at Hwy 14, 3.3 east from Juana Díaz Plaza.		6/03/92	1150	3.50 (0.099)
50109500	Río Cañas near Santa Isabel, PR	Lat 17°59'39", long 66°28'33". Hydrologic unit 21010004. At	6.38 (16.5)	1/29/92	1310	0.00
	THE TAX TAX	bridge on Hwy 1, 0.5 mi (0.8 km) from mouth, 0.6 mi (1.0 km) east of Pastillo, and 5.1 mi (8.2 km) northwest of Santa Isabel Plaza.	(20.5)	6/05/92	0910	2.46 (0.070)
		Río Jacaguas basin				
50110550	Río Jacaguas at Villalba, PR	Lat 18°07'37", long 66°29'42". Hydrologic unit 21010004.	12.2 (31.7)	2/06/92	1100	40.2 (1.138)
	12222, 21	Barrio Hato Puerco Arriba, upstream from Water Treatment	(02)	6/09/92	0955	109 (3.087)
		Plant, 100 ft (30 m) downstream from confluence with Quebrada Achiote, 0.2 mi (0.3 km) south- west from Villalba.				
50110700	Río Toa Vaca at Pedro García, PR	Lat 18°08'11", long 66°23'47". Hydrologic unit 21010004.	3.09 (8.00)	2/06/92	1412	4.37 (0.124)
	,	Barrio Pedro García, 2.1 mi (3.4 km) southeast from inter- section of Hwy's 143 and 155, and 4.1 mi (6.6 km) northeast Lago Toa Vaca.	(0.00)	6/09/92	0720	4.37 (0.124)

Tan-flas	 	laneCont	4 money

STATION NUMBER	STATION NAME	LOCATION AND	DRAINAGE AREA mi²	DATE	TIME	STREAM FLOWS ft ³ /s
		BASIN	(km²)	*****		(m³/s)
50110900	Río Toa Vaca upstream	Lat 18°07'36", long 66°27'25".	14.2	2/06/92	1249	11.8
	from Lago Toa Vaca, PR	Hydrologic unit 21010004. Barrio Caonillas Arriba, at Hwy 553, 0.5 mi (0.8 km) upstream Lago Toa Vaca, and 2.4 mi (3.9 km) east from Villalba.	(36.8)	6/09/92	0850	(0.334) 37.5 (1.062)
50111720	Quebrada Guanábana	Lat 18°03'12", long 66°29'02".	1.72	2/04/92	0920	0.00
	near Juana Díaz, PR	Hydrologic unit 21010004. Barrio Tijeras, at Hwy 14, 1.5 mi (2.4 km) east from Juana Díaz Plza.	(4.46)	6/09/92	1100	0.00
		Río Inabón basin				
50112400	Río Inabón at Real	Lat 18°07'22", long 66°34'20".	6.00	2/05/92	1503	6.08
	Anón, PR	Hydrologic unit 21010004. Barrio Anón, at Hwy 511, 1.0 mi (1.6 km) northeast from Cerro Santo Domingo, and 4.5 mi (7.2 km) northwest from Lago Guayabal.	(15.4)	6/10/92	0740	(0.172) 15.8 (0.447)
50112700	Río Guayo near	Lat 18°07'24", long 66°33'27".	1.67	2/05/92	1324	1.47
	Collores, PR	Hydrologic unit 21010004. Barrio Collores, at Hwy 5.17 about 400 ft (122 m) west from escuela Guaraguao 0.9 mi (1.4 km) northwest from inter- section of Hwy's 517 and 5.12, and 3.5 mi (5.6 km) northwest from Lago Toa Vaca.	(4.34)	6/09/92	1235	(0.042) 5.15 (0.146)
50112750	Quebrada Indalecia	Lat 18°06'33", long 66°32'20".	3.52	2/05/92	1258	0.00
	at Collores, PR	Hydrologic unit 21010004. Barrio Collores, 200 ft (61 m) upstream from confluence with Río Guayo, 0.9 mi (1.4 km) northeast from Cerro Agustinillo, and 2.2 mi (3.5 km) northwest from Lago Guayabal.	(9.11)	6/09/92	1140	5.65 (0.160)
50112800	Río Guayo upstream	Lat 18°05'10", long 66°32'24".	9.55	2/05/92	1410	4.80
	from Diversion at Collores, PR	Hydrologic unit 21010004. Barrio Collores, 2.1 mi (3.4 km) southwest from Lago Guayabal, and 3.1 mi (5.0 km) northwest from Juana Diaz Plaza.	(24.7)	6/09/92	1325	(0.136) 15.9 (0.450)
	26. 20. 24.4	Río Bucaná basin	.	0.04.00	1100	
50113790	Río San Patricio upstream from Lago	Lat 18°07'12", long 66°36'27". Hydrologic unit 21010004. Barrio	5.84 (15.1)	2/04/92	1129	4.68 (0.132)
	Cerrillos, PR	Maragüez, 1.5 mi (2.4 km) north- west from Cerro Santo Domingo, 3.6 mi (5.8 km) northwest from Lago Cerrillos, and 7.3 mi from (12 km) Degetau Plaza, Ponce.		6/10/92	1025	10.3 (0.292)
50113800	Río Cerrillos upstream from Lago	Lat 18°07'01", long 66°36'17". Hydrologic unit 21010004. At	11.9 (30.7)	2/04/92	1212	11.8 (0.334)
	Cerrillos, PR	barrio Maragüez, 1.3 mi (2.1 km) west from Cerro Santo Domingo, 3.3 mi (5.3 km) northwest from Lago Cerrillos, and 7.2 mi (12 km) from Degetau Plaza, Ponce.	(30.7)	6/10/92	1115	26.3 (0.745)
50114150	Quebrada Ausubo near Ponce, PR	Lat 18°03'09", long 66°35'08". Hydrologic unit 21010004. At	1.18 (3.05)	2/03/92	1432	0.00
		Barrio Machuelo Arriba, 2.4 mi (3.9 km) west from Coto Laurel, 1.5 mi (2.4 km) south from Lago Cerrillos, and 3.8 mi (6.1 km) northeast from Degetau Plaza, Ponce.	,,	6/10/92	1315	0.00

STATION NUMBER	STATION NAME	LOCATION	DRAINAGE AREA			Strram Flows
		AND	mi² (km²)	DATE	TIME	ft³/s (m³/s)
		Basin				
50114200	Río Bayagán near Ponce, PR	Lat 18°02'51", long 66°35'12". Hydrologic unit 21010004. At Barrio Machuelo Arriba, 2.5 mi (4.0 Km) west of Coto Laurel, 1.9 mi (3.0 km) south from Lago	3.82 (9.88)	2/03/92 6/10/92	1546 1330	0.00
50114600	Die Brend at Dance	Cerrillos, and 3.0 mi (4.8 km) northeast from Degetau Plaza, Ponce.	27.3	2/03/92	0647	57.9
50114600	Río Bucaná at Ponce, PR	Lat 18°00'28", long 66°35'36". Hydrologic unit 21010004. At	(70.7)	6/10/92	1440	(1.640) 43.5
		bridge on Hwy 1, 0.2 mi (0.3 km) east of intersection of Hwys 1 and 2, 1.5 mi (2.4 km) east of Degetau Plaxa in Ponce, 3.1 mi (5.0 km) upstream from mouth.		6,10,52	1440	(1.232)
		Río Portugués basin				
50114900	Río Portugués near Tibes, PR	Lat 18°04'26", long 66°38'35". Hydrologic unit 21010004. At	7.27 (18.8)	2/03/92	1225	5.41 (0.153)
		barrio Tibes, 0.5 mi (0.8 km) southwest from Cerro del Diablo, 6.0 mi (9.6 km) northeast from Peñuelas, and 6.2 mi (10 km) north from Ponce.		6/11/92	1450	11.7 (0.331)
50115400	Río Portugués near Ponce, PR	Lat 18°02'27", long 66°36'41". Hydrologic unit 21010004. At	12.2 (31.6)	2/03/92	1123	7.10 (0.201)
	rolled, FR	barrio Portugués, 1.0 mi (1.6 km) west from Jardines de Ponce, 0.4 mi (0.6 km) north from confluence with Rio Chi- quito, and 1.9 mi (3.0 km) north from Degetau Plaza, Ponce.	(31.0)	6/11/92	1135	13.3 (0.377)
50115450	Río Chiquito at Portugués, PR	Lat 18°04'11", long 66°37'00". Hydrologic unit 21010004. At	3.12 (8.09)	2/13/92	1342	0.87 (0.025)
	Torceyada, FA	barrio Portugués, 2.1 mi (3.4 km) northwest from Jardines de Ponce, 1.7 mi (2.7 km) southwest from Pico Pinto, and 2.8 mi (4.5 km) north from Degetau Plaza, Ponce.	(0.05)	6/11/92	1230	2.11 (0.060)
50115600	Río Chiquito near Ponce, PR	Lat 18°02'37", long 66°36'31'. Hydrologic unit 21010004. At	4.43 (11.5)	2/03/92	1414	2.40 (0.068)
	rolled, FR	barrio Portugués, 0.6 mi (1.0 km) west from Jardines de Ponce, 0.8 mi (1.3 km) South from Cerro El Gato, and 2.1 mi (3.4 km) north from Degetau Plaza, Ponce.	(11.3)	6/11/92	1055	2.04 (0.058)
50116500	Río Portugués at Hwy 2 By-Pass at	Lat 17°59'52", long 66°36'52". Hydrologic unit 21010004. At	20.5 (53.1)	2/03/92	0752	4.29 (0.121)
	Ponce, PR	bridge on Hwy 2 By-Pass, 1.1 mi (1.8 km) south of Degetau		6/11/92	0720	14.2 (0.402)
		Plaza, and 2.0 mi (3.2 km) upstream from mouth.		6/29/92	1240	6.66 (0.189)
				7/07/92	1000	5.10 (0.144)
PB4440	B(,	Río Matilde basin				£ 0=
50116800	Río Cañas at Magueyes PR	Lat 18°04'26", long 66°39'07". Hydrologic unit 21010004. At	4.00 (10.3)	2/03/92	1002	5.27 (0.149)
		barrio Magueyes, 2.4 mi (3.9 km) southwest from Cerro del Diablo, 4.7 mi (7.6 km) northwest from Pefiuelas, and (6.4 km) northwest from Ponce.		6/11/92	0940	4.85 (0.137)
50116970	Río Cañas downstream from Las Américas	Lat 18°00'37", long 66°38'26". Hydrologic unit 21010004. 0.5	8.50 (22.0)	2/03/92	0846	7.59 (0.215)
	Ave., PR	mi (0.8 km) upstream from con- fluence with Rio Pastillo.	(==,	6/11/92	0840	12.2 (0.346)

STATION NUMBER	STATION NAMB	LOCATION	dra inage Arba			STREAM FLOWS
		and Basin	mi ² (km ²)	DATE	TIME	ft ³ /s (m ³ /s)
50117800	Río Pastillo at	Lat 18°02'53", long 66°39'52".	4.32	2/03/92	0915	0.85
	Pastillo, PR	Hydrologic unit 21010004. Barrio Quebrada Limón at Hwy 502, 0.8 mi (1.3 km) northwest of Hwy's 502 and 132 inter- section, 0.9 mi (1.4 km) west of Magueyes and 3.1 mi (5.0 km) northwest from Ponce.	(11.2)	6/15/92	1250	(0.024) 2.01 (0.057)
50118300	Río Pastillo near Ponce, PR	Lat 18°00'31", long 66°38'39".	10.6	2/03/92	0900	0.00
	Fonce, PR	Hydrologic unit 21010004. Canas Urbano, on bridge, 0.7 mi (1.1 km) downstream from Jardines del Caribe and 1.1 mi (1.7 km) west of Escuela Dr. Pila, Ponce.	(27.6)	6/15/92	1205	2.28 (0.064)
50119000	Río Matilde at Ponce, PR	Lat 17°59'53", long 66°38'06". Hydrologic unit 21010004. At	20.5 (53.2)	2/03/92	0820	7.14 (0.202)
	FORCE, PA	Hwy 2, 1.1 mi (1.8 km) upstream from mouth.	(33.2)	6/15/92	1120	13.1 (0.371)
50119200	Quebrada del Agua at	Lat 17°59'13", long 66°38'22".	6.45	2/03/92	1415	0.00
	Playa de Ponce, PR	Hydrologic unit 21010004. 700 ft (213 m) upstream from confluence with Río Matilde.	(16.7)	6/18/92	1410	0.00
		Río Tallaboa basin				
50120550	Río Tallaboa near Quebrada Ceiba, PR	Lat 18°04'18", long 66°42'03". Hydrologic unit 21010004.	8.41 (21.8)	2/03/92	1005	4.62 (0.131)
		Barrio Quebrada Ceiba, on bridge, 0.06 mi (0.1 km) west from Hwy 391, 1.2 mi (2.0 km) north from Tallaboa Alta and 1.7 mi (2.7 km) northeast from Peñuelas Plaza.		6/15/92	1345	11.1 (0.314)
50120700	Río Guayanés near	Lat 18°04'03", long 66°43'36".	7.29	2/03/92	1110	22.7 (0.643)
	Peñuelas, PR	Hydrologic unit 21010004. Barrio Jaguas, on Hwy 386, 0.2 mi (0.4 km) northeast from Hwy's 386 and 132 intersection, 0.6 mi (1.0 km) northeast from Peffuelas Plaza.	(18.9)	6/17/92	0715	3.80 (0.108)
50121000	Río Tallaboa at	Lat 18°03'02", long 66°43'19".	24.2 (62.7)	2/03/92	1150	21.4 (0.606)
	Peñuelas, PR	Hydrologic unit 21010004. 350 ft (106.7 m) downstream from Hwy 132 bridge, 0.6 mi (1.0 km) south of Pefiuelas.	(62.7)	6/15/92	1435	20.4 (0.578)
50122000	Río Tallaboa at Tallaboa, PR	Lat 18°00'31", long 66°43'49". Hydrologic unit 21010004. At	31.6 (81.7)	2/03/92	1245	7.60 (0.215)
	Tallaboa, FR	bridge at Hacienda Dolores, 700 ft (213 m) upstream from Hwy 127, 0.8 mi (1.3 km) north- west of Tallaboa, and 7.6 mi (12.2 km) west of Degetau Plaza, Ponce.	(61.7)	6/17/92	0805	16.0 (0.453)
		Río Macaná basin				
50122500	Río Macaná near Peñuelas, PR	Lat 18°03'40", long 66°46'12". Hydrologic unit 21010004.	2.77 (7.17)	2/05/92	0945	0.31 (0.009)
		Barrio Macaná at Hwy's 131 and 132 intersection, 5.5 mi (8.8 km) northeast from Yauco, and 2.8 (4.5 km) northeast from Guayanilla Plaza.		6/17/92	1050	1.24 (0.035)
50122900	Río Macaná at Magas Arriba, PR	Lat 18°01'00", long 66°45'57". Hydrologic unit 21010004. 1.8	8.98 (23.2)	2/05/92	0830	0.00
		mi (2.8 km) east of Guayanilla Plaza, 200 ft (60 m) upstream from bridge on Hwy 2, and 0.6 mi (1.0 km) upstream from mouth.	,==.2,	6/17/92	0855	0.00

STATION NUMBER	STATION NAME	LOCATION AND	DRAINAGE AREA mi ² (km ²)	DATE	TIME	STREAM FLOWS ft ³ /s (m ³ /s)
		BASIN				
		Río Guayanilla basin				
50123100	Río Guayanilla at Pasto, PR	Lat 18°05'53", long 66°47'38". Hydrologic unit 21010004. At barrio Pasto, 1.8 mi (2.9 km) southeast from Pico Rodadero, 1.8 mi (2.9 km) west from Cerro El Peligro, and 5.2 mi	6.45 (16.7)	2/05/92 6/17/92	1025 1140	4.59 (0.130) 9.36 (0.265)
		(8.4 km) north from Guayanilla Plaza.				
50124600	Río Guayanilla near Central Rufina, PR	Lat 18°01'00", long 66°47'01". Hydrologic unit 21010004. At	23.0 (59.5)	2/05/92	0845	0.20 (0.006)
	COLORES ACTION, TX	Guayanilla, 1.2 mi (1.9 km) upstream from mouth, 0.8 mi (1.3 km) northeast from Central Rufina, and 0.6 mi (1.0 km) southeast from Guayanilla Plaza.	(57.2)	6/17/92	0910	5.72 (0.162)
		Río Yauco basin				
50125000	Río Yauco near Lago Lucchetti Damsite, PR	Lat 18°06'40", long 66°52'38". Hydrologic unit 21010004.	8.05 (20.8)	2/05/92	1310	2.80 (0.079)
		Barrio Vegas, 300 ft (91 m) from mouth, 1.5 mi (2.4 km) northwest from spillway, and 5.4 mi (8.7 km) northwest from Yauco Plaza.		6/18/92	1230	4.77 (0.135)
50125500	Río Naranjo near Lago Lucchetti Damsite, PR	Lat 18°06'20", long 66°51'37". Hydrologic unit 21010004.	1.92 (4.97)	2/05/92	1240	0.21 (0.006)
		Barrio Naranjo at Hwy 128, 0.3 mi (0.5 km) from mouth and 0.9 mi (1.4 km) from spillway.	,,,,,	6/18/92	1110	0.70 (0.020)
50125600	Quebrada Grande near Lago Lucchetti	Lat 18°06'20", long 66°50'56". Hydrologic unit 21010004.	2.83 (7.33)	2/05/92	1210	0.56 (0.016)
	Damsite, PR	Barrio Naranjo, 0.6 mi (1.0 km) west from Hacienda Roig, 0.9 mi (1.4 km) from mouth, and 1.3 mi (2.1 km) from spillway.		6/18/92	1025	1.18 (0.033)
50125860	Río Duey at Duey, PR	Lat 18°05'44", long 66°50'06". Hydrologic unit 21010004.	4.55 (11.8)	2/05/92	1130	2.55 (0.072)
		Barrio Duey, 0.8 mi (1.3 km) southeast from Hacienda Rolg, 1.2 mi (1.9 km) east from Lago Lucchetti, and 4.1 mi (6.6 km) from Yauco Plaza.		6/17/92	1240	3.35 (0.095)
		Río Loco basin				
50128450	Quebrada Grande upstream from	Lat 18°03'45", long 66°53'10". Hydrologic unit 21010004.	2.72 (7.03)	2/06/92	0935	0.66 (0.019)
	Lago Loco, PR	Barrio Almácigo Alto, 800 ft (244 m) upstream from confluene with Río Loco, 1.2 mi (1.9 km) north from spillway, and 3.0 mi (4.8 km) northwest from Yauco Plaza.		6/18/92	0910	1.23 (0.035)
50128500	Río Loco upstream from Lago Loco, PR	Lat 18°03'22", long 66°53'08". Hydrologic unit 21010004. At	7.66 (19.8)	2/06/92	0850	1.30 (0.037)
		barrio Susúa Alta, 0.2 mi (0.3 km) upstream from Lago Loco, 1.9 mi (3.0 km) north- east from Cerro La Torre, and 5.2 mi (8.4 km) southeast from Sabana Grande Plaza.	,,	6/18/92	0830	3.66 (0.104)
50129200	Quebrada Susúa at Palomas, PR	Lat 18°01'19", long 66°52'28". Hydrologic unit 21010004. At	3.23 (8.37)	2/06/92	0800	1.20 (0.034)
		bridge on Hwy 2, 0.5 mi (0.8 km) north of Palomas, and 1.9 mi (3.1 km) southwest of Yauco.	-	6/18/92	0745	0.78 (0.022)

STATION NUMBER	Station Name	LOCATION	DRAINAGE AREA			STREAM FLOWS
		AND	mi² (km²)	DATE	TIME	ft³/s (m³/s)
		BASIN				
		Río Guanajibo basin				
50130400	Río Grande near Sabana Grande, PR	Lat 18°05'53", long 66°56'18". Hydrologic unit 21010003.	6.45 (16.7)	2/03/92	0907	0.42 (0.012)
		Barrio Rín at Hwy 364, 0.5 mi (0.8 km) northeast from Capilla del Poso de la Virgen, and 1.8 mi (2.9 km) northeast from Sabana Grande Plaza.	,	6/15/92	1009	1.31 (0.037)
50130500	Río Guanajibo at	Lat 18°04'11", long 66°57'29".	14.7	2/03/92	0821	0.82 (0.023)
	La Pica, PR	Hydrologic unit 21010003. Barrio Rayo at Hwy 2, 1.0 mi (1.6 km) north from Cerro de de los Bonelli, and 0.8 mi (1.3 km) southeast from Sabana Grande Plaza.	(38.2)	6/15/92	0926	4.47 (0.126)
50130800	Río Flores near	Lat 18°04'02", long 66°58'25".	1.98	2/03/92	0950	0.05 (0.001)
	Sabana Grande, PR	Hydrologic unit 21010003. Barrio Santana at Hwy 2, 0.2 mi (0.3 km) east from Hwy's 2 and 363 intersection, and 0.9 mi (1.4 km) west from Sabana Grande Plaza.	(5.13)	6/15/92	1054	0.51 (0.014)
50131010	Río Cruces near	Lat 18°04'54", long 66°58'37".	4.68	2/03/92	1007	1.40 (0.040)
	Sabana Grande, PR	Hydrologic unit 21010003. Barrio Santana at Hwy 2, 400 ft (122 m) west from Hwy 2 and 363 intersection, 1.1 mi (1.8 km) west from Sabana Grande Plaza.	(12.1)	6/15/92	1118	1.86 (0.053)
50131800	Río Cupeyes near San Germán, PR	Lat 18°04'48", long 67°00'24". Hydrologic unit 21010003.	4.16 (10.8)	2/03/92	1045	0.68 (0.019)
	San German, PK	Barrio Guamá, 0.2 mi (0.3 km) downstream from Hwy 2, and 2.5 mi (4.0 km) east from San Germán Plaza.	(10.0)	6/15/92	1152	1.19 (0.034)
50132010	Río Guanajibo below San Germán, PR	Lat 18°05'28", long 67°02'38". Hydrologic unit 21010003. 0.5	36.1 (93.5)	2/04/92	1050	4.45 (0.126)
	,	mi (0.8 km) north of San Germán Plaza and 1500 ft (457m) downstream from Hwy 360 bridge.	,,	6/17/92	1043	10.3 (0.292)
50133000	Río Caín near San Germán, PR	Lat 18°06'06", long 67°02'26". Hydrologic unit 21010003.	6.32 (16.4)	2/04/92	0730	0.00
	,	Barrio Caín, at Hwy 361, 600 ft (183 m) upstream from Hwy 2, and 1.3 mi (2.1 km) north from San Germán Plaza.	(2000)	6/15/92	1235	0.43 (0.012)
50133800	Río Duey near Rosario, PR	Lat 18°08'57", long 67°03'15". Hydrologic unit 21010003.	4.17 (10.8)	2/04/92	0852	1.21 (0.034)
	ACCESSOR OF THE SECOND	Barrio Duey Alto, 200 ft (61 m) downstream from Hwy 348, 100 ft (30 m) downstream from confluence with Río Nueve Pasos, and 2.0 mi (3.2 km) southeast from Rosario Plaza.	(2010)	6/16/92	0908	1.95 (0.055)
50134600	Río Hoconuco near San Germán, PR	Lat 18°07'08", long 67°04'27". Hydrologic unit 21010003.	5.18 (13.4)	2/04/92	0830	0.00
	edit Carment, EK	Barrio Hoconuco Bajo, 0.2 mi (0.3 km) downstream from Hwy	(13.4)	6/15/92	1305	0.34 (0.010)
		(0.3 km) downstream from nwy 358, 200 ft upstream from confluence with Río Duey, and 3.2 mi (5.1 km) northwest from San Germán Plaza.		7/01/92	0930	0.13
50135000	Río Hoconuco (Duey) near San Germán, PR	Lat 18°07'10", long 67°04'48'. Hydrologic unit 21010003.	13.2 (34.3)	2/04/92	1145	0.79 (0.022)
	THE WILL WILLIAM EN	Barrio Duey Bajo, 200 ft (61 m) downstream from Hwy 2, and 3.4 mi (5.5 km) northwest from San Germán Plaza	(31.5)	6/17/92	1133	2.23 (0.063)

STATION NUMBER	STATION NAME	LOCATION AND BASIN	DRAINAGE AREA mi² (km²)	DATE	TIME	STREAM FLOWS ft ³ /s (m ³ /s)
50135700	Río Maricao at Maricao, PR	Lat 18°11'22", long 66°59'37". Hydrologic unit 21010003.	3.80 (9.85)	2/04/92	0707	3.43 (0.097)
		Barrio Maricao Afuera, at Hwy 357, 0.4 mi (0.6 km) east from Hacienda San Antonio, and 1.0 mi (1.6 km) northwest from Maricao Plaza.		6/16/92	0718	4.24 (0.120)
50135800	Río Rosario at Las Vegas, PR	Lat 18°11'13", long 67°01'52". Hydrologic unit 21010003.	8.33 (21.6)	2/04/92	0802	6.08 (0.172)
	nas vegas, ra	Barrio Montoso, at Hwy 119, 0.1 mi (0.2 km) southeast from intersection with Hwy 105, and 3.6 (5.8 km) northeast from Rosario Plaza.	(21.0)	6/16/92	0810	7.41 (0.210)
50136400	Río Rosario near Hormigueros, PR	Lat 18°09'36", long 67°05'08". Hydrologic unit 21010003. At	18.3 (47.4)	2/03/92	1210	9.36 (0.265)
	normiguetos, 18	Bridge on Hwy 348, 0.5 mi (0.8 km) Southwest of Rosario Plaza.	(4,	6/16/92	1020	12.6 (0.357)
50136500	Río Rosario at Hwy 2 near Hormigueros, PR	Lat 18°07'35", long 67°05'39". Hydrologic unit 21010003.	22.8 (58.9)	2/04/92	1012	7.24 (0.205)
	near normyderos, ra	Barrio Benavente, at Hwy 2, 2.7 mi (4.3 km) southwest from Rosario, and 2.5 mi (4.0 km) southeast from Hormigueros Plaza.	(30.2)	6/16/92	1132	16.4 (0.464)
50137800	Río Viejo near Cabo Rojo, PR	Lat 18°06'04", long 67°07'48". Hydrologic unit 21010003.	12.3 (31.9)	2/05/92	1147	1.35 (0.038)
	- '	Barrio Bajura, at Hwy 103, 1.0 mi (1.6 km) northeast	(00.07)	6/17/92	1317	3.15 (0.089)
		from intersection with Hwy 102, and 1.4 mi (2.2 km) from Cabo Rojo Plaza.		7/01/92	1205	1.53 (0.043)
		Quebrada Maga basin				
50138100	Quebrada Maga near Guanajibo, PR	Lat 18°09'18", long 67°08'07" Hydrologic unit 21010003.	0.76 (1.96)	2/05/92	1115	0.00
		Barrio Guanajibo, 0.3 mi (0.5 km) southeast from Mayagüez Mall, and 1.2 mi (1.9 km) northwest from Hormigueros Plaza.		6/18/92	1143	0.11 (0.003)
		Río Hondo basin				
50138200	Río Hondo near Guanajibo, PR	Lat 18°09'45", long 67°09'00". Hydrologic unit 21010003.	3.16 (8.18)	2/07/92	0805	2.02 (0.057)
	•	Barrio Guanajibo, at Hwy 114, 1.8 mi (2.9 km) east from Cerro Cornelia, and 2.0 mi (3.2 km) northwest from Hormigueros Plaza.		6/18/92	1208	0.57 (0.016)
		Quebrada Sábalos basin				
50138300	Quebrada Sábalos near Mayagüez, PR	Lat 18°10'47", long 67°08'58". Hydrologic unit 21010003.	2.47 (6.40)	2/07/92	0736	0.64 (0.018)
		Barrio Sábalos, at Hwy 2R, 2.9 mi (4.7 km) northwest from Hormigueros, and 1.7 mi (2.7 km) southwest from Mayagüez Plaza.		6/18/92	1224	1.02 (0.029)
		Río Yagüez basin				
50138900	Río Yagüez at Balboa, PR	Lat 18°12'13", long 67°07'55". Hydrologic unit 21010003. 1200	12.2 (31.6)	2/07/92	0657	3.59 (0.102)
		ft (366 m) upstream from bridge on Balboa St. and 1.6 mi (2.6 km) upstream from mouth.		6/18/92	1257	5.11 (0.145)

Station Number	STATION NAME	LOCATION AND	DRAINAGE ARRA mi² DATE TIME (km²)				
		BASIN					
		Río Grande de Añasco basin					
50140300	Río Guilarte near Adjuntas, PR	Lat 18°10'58", long 66°46'09". Hydrologic unit 21010003.	2.62 (6.78)	2/04/92	0955	2.97 (0.084)	
		Barrio Guilarte at Hwy 131, 0.4 mi (0.6 km) southwest from		6/16/92	0840	3.47 (0.098)	
		Hwy's 130 and 131 intersection, and 4.3 mi (6.9 km) east from Castañer.		7/07/92	1300	2.34 (0.066)	
50140800	Río Limani near Yahuecas, PR	Lat 18°12'01", long 66°47'50". Hydrologic unit 21010003.	7.38 (19.1)	2/04/92	1400	4.85 (0.137)	
	Idiidecas, PR	Barrio Yahuecas, 200 ft (61 m)	(19.1)	6/16/92	1035	8.37	
		upstream with Río Guilarte, and 500 ft (152 m) southwest from Hwy's 129 and 135 intersection.		7/07/92	1445	(0.237) 5.57 (0.158)	
50141400	Río Guayo at Guayo,	Lat 18°10'49", long 66°49'40".	4.15	2/04/92	1250	2.47	
	PR	Hydrologic unit 21010003.	(10.7)			(0.070)	
		Barrio Guayo at Hwy 131, 1.0 mi (1.6 km) upstream from Lago		6/16/92	1130	4.95 (0.140)	
		Guayo, 0.4 mi (0.6 km) southeast from Castañer.		7/07/92	1530	3.64 (0.103)	
50142000	Río Blanco at La	Lat 14°18'34", long 66°51'49".	33.2	2/03/92	1115	4.24	
	Torre, PR	Hydrologic unit 21010003. Barrio La Torre, at Hwy 128,	(86.0)	6/16/92	1253	(0.120) 19.7	
		2.7 mi (4.3 km) northwest from Lago Guayo, and 4.5 mi (7.2 km) northwest from Castañer.				(0.558)	
50142100	Quebrada de Los	Lat 18°15'41", long 66°51'22".	0.57	2/03/92	1033	0.41	
	Plátanos at Marisol, PR	Hydrologic unit 21010003. Barrio Marisol, at Hwy 128,	(1.47)	6/16/92	1337	(0.012) 0.42	
	,	0.3 mi (0.5 km) south from Hwy's 128 and 129 intersection.		.,,		(0.012)	
50142300	Río Prieto at Indiera Alta, PR	Lat 18°10'07", long 66°51'49". Hydrologic unit 21010003.	7.47 (19.3)	2/03/92	1230	4.41 (0.125)	
		Barrio Indiera Alta, at Hwy 128,	(2002)	6/16/92	1050	2.39	
		2.3 mi (3.7 km) southwest from Lago Guayo, and 2.2 mi (3.5 km) southwest from Castañer.				(0.068)	
50142710	Río Prieto at Río	Lat 18°12'06', long 66°53'05".	15.1	2/03/92	1342	1.04	
	Prieto, PR	Hydrologic unit 21010003. Barrio Río Prieto, at Hwy 431,	(39.0)	6/16/92	1120	(0.029) 0.44	
		3.7 mi (5.6 km) west from Lago Guayo, and 6.4 mi (10 km) northeast from Maricao Plaza.				(0.012)	
50142900	Río Prieto at	Lat 18°15'17", long 66°54'25".	26.1	2/03/92	1522	10.4	
	Pezuela, PR	Hydrologic unit 21010003. Barrio Pezuela, 400 ft (122 m)	(67.7)	6/16/92	1501	(0.294) 0.78	
		upstream from confluence with Río Grande de Añasco, and 3.4 mi (5.5 km) southwest from Lares Plaza.				(0.022)	
50143000	Río Grande de Añasco	Lat 18°15'28", long 66°55'05". Hydrologic unit 21010003. At	26.3	2/04/92	1420	16.2 (0.459)	
	near Lares, PR	bridge on Hwy 124, 0.7 mi (1.1	(68.1)	6/16/92	1419	143	
		km) from confluence with Río Blanco and Río Prieto, and 3.7 mi (6.0 km) southwest from Lares Plaza.				(4.050)	
50143104	Río Lajas near	Lat 18°10'54", long 66°57'39".	5.79	2/04/92	0700	2.79	
	Maricao, PR	Hydroloigc unit 21010003. Barrio Indiera Fría, at Hwy 105,	(15.0)	6/16/92	0837	(0.079) 6.25	
		0.3 mi (0.5 km) upstream from confluence with Río Guaba, 0.7 mi (1.1 km) Maricao Plaza.				(0.177)	

STATION NUMBER	STATION NAME	LOCATION	DRAINAGE AREA mi ² (km ³)	DATE	TIME	STREAM FLOWS ft ³ /s (m ³ /s)	
		BASIN					
50143108	Río Guaba near Maricao, PR	Lat 18°11'02", long 66°57'30". Hydrologic unit 21010003. Barrio Bucarabones, at Hwy 105, 200 ft (61 m) upstream from confluence with Río Lajas, and 1.5 mi (2.4 km) from Maricao Plaza.	4.95 (12.8)	2/04/92 6/16/92	0750 0925	3.44 (0.097) 2.75 (0.078)	
50143150	Río Bucarabones near	Lat 18°13'27", long 66°56'41".	9.19	2/04/92	1327	6.30	
50143150	Las Marías, PR	Hydrologic unit 21010003. Barrio Bucarabones, 400 ft	(23.8)	6/16/92	1536	(0.178) 27.0	
		(122 m) upstream from confluence with Río Guaba, and 3.7 mi (5.6 km) northeast from Maricao Plaxa.		7/08/92	1100	(0.765) 7.45 (0.211)	
50143200	Río Guaba near Las	Lat 18°13'37", long 66°56'33".	25.4	2/04/92	1236	13.2	
	Marías, PR	Hydrologic unit 21010003. Barrio Cerrote, at Hwy 124, 0.3 mi (0.5 km) downstream from confluence with Río Bucarabones, and 3.9 mi (6.3 km) northeast from Maricao Plasa.	(65.7)	6/16/92	1608	(0.374) 128 (3.625)	
50143400	Quebrada Las Cañas	Lat 18°16'23", long 66°56'36".	3.08	2/06/92	1054	3.95	
	at Perchas, PR	Hydrologic unit 21010003. Barrio Perchas No 2, at Hwy 434, 800 ft (244 m) upstream from confluence with Río Grande de Añnasco, and 3.5 mi (5.6 km) from Las Marías Plaza.	(7.98)	6/17/92	0908	(0.112) 8.78 (0.249)	
50143500	Río Mayagüecilla at	Lat 18°14'50", long 66°59'05".	3.30	2/04/92	1136	1.79	
	Las Marías, PR	Hydrologic unit 21010003. Barrio Palma Escrita, at Hwy 124, 2.0 mi (3.2 km) upstream from confluence with Río Grande de Añasco, and 0.7 mi (1.1 km) southeast fron Las Marías Plaza.	(8.54)	6/16/92	1654	(0.051) 8.31 (0.235)	
50143800	Río Grande de Añasco	Lat 18°16'41", long 66°58'48".	116	2/04/92	1030	53.7	
	near Las Marías, PR	Hydrologic unit 21010003. Barrio Guacio, at Hwy 119, 1.8 mi (2.9 km) northeast from Las Marías Plaza.	(299)	6/17/92	1016	(1.521) 594 (16.822)	
50143900	Río Arenas at Las Marías, PR	Lat 18°15'10", long 66°59'57". Hydrologic unit 21010003.	2.79 (7.22)	2/04/92	0910	3.15 (0.089)	
	malles, FK	Barrio Maravillas, at Hwy 119, 0.5 mi (0.8 km) southwest from Las Marías Plaza.	(/.==/	6/17/92	0736	4.70 (0.133)	
50144200	Quebrada Cerro Gordo near Cerro Gordo, PR	Lat 18°17'09", long 66°04'09". Hydrologic unit 21010003.	2.66 (6.89)	2/05/92	1037	3.86 (0.109)	
	Hear Cerro Gordo, FR	Barrio Corcovada, 600 (183 m) upstream from confluence with Rio Grande de Añasco, and 5.7 mi (9.2 km) from Las Marías, and 4.8 mi (7.7 km) east from Añasco Plaza.	(6.05)	6/18/92	0859	11.8 (0.334)	
50144900	Río Humata near	Lat 18°17'18", long 67°06'24'.	4.86	2/05/92	1140	2.95 (0.084)	
	El Espino, PR	Hydrologic unit 21010003. Barrio Carreras, at Hwy 109, 0.3 mi (0.5 km) upstream from confluence with Río Grande de Añasco, and 2.4 mi (3.9 km) east from Añasco Plaza.	(12.6)	6/18/92	1007	4.40 (0.125)	
50145000	Río Grande de Añasco	Lat 18°16′50", long 67°06′46".	108	2/05/92	1234	81.5 (2.308)	
	at Bl Espino, PR	Hydrologic unit 21010003. Barrio Espino, at Hwy 406, 400 ft (249 m) east from intersection with Hwy 109, and 1.9 mi (3.1 km) from Añasco Plaza.	(280) ~384	6/18/92	1045	356 (10.082)	

DISCHARGE AT PARTIAL-RECORD STATIONS Low-flow partial-record stations--Continued

Station Number	Station Name	LOCATION AND	DRAINAGE AREA mi²	DATE	STREAM FLOWS ft ³ /s		
		Basin	(km²)			(m³/s)	
50145400	Río Casei near	Lat 18°15'18", long 67°04'48".	8.17	2/05/92	0932	5.75	
	Mayagüez, PR	Hydrologic unit 21010003. Barrio Legüísamo, at Hwy 108, 4.6 mi (7.4 km) northeast from Mayaüéz, and 4.5 mi (7.2 km) southeast from Mayagüez Plaza.	(21.2)	6/17/92	1340	(0.163) 31.5 (0.892)	
50146000	Río Grande de Añasco at Añasco Arriba, PR	Lat 18°16'31", long 66°07'37". Hydrologic unit 21010003. 0.8	161 (416)	2/05/92	1318	89.1 (2.523)	
	at answer attibut, FA	mi (1.2 km) south of Affasco and 3.0 mi (4.8 km) upstream from mouth.	(410)	6/18/92	1207	434 (12.291)	
50146002	Río Cañas at Río Cañas Arriba, PR	Lat 18°13'37", long 67°04'01". Hydrologic unit 21010003.	3.58 (9.26)	2/05/92	0841	1.91 (0.054)	
	Column Allina, FA	Barrio Cañas Arriba, at Hwy 354, 0.2 mi (0.3 km) south from intersection with Hwy 355, and 5.1 mi (8.2 km) from Mayagüez Plaza.	(3.20)	6/17/92	1155	2.95 (0.084)	
50146005	Río Cañas at Río Cañas Abajo, PR	Lat 18°14'38", long 67°07'17". Hydrologic unit, 21010003.	11.2 (29.1)	2/05/92	0735	2.28 (0.064)	
	The state of the s	Barrio Río Cañas Abajo, at Hwy 108, and 3.1 mi (5.0 km) north- east from Mayagüez Plaza.	(=5,2)	6/17/92	1245	4.97 (0.141)	
50146075	Río Dagüey near Añasco, PR	Lat 18°17'19", long 67°08'08". Hydrologic unit 21010003.	1.06 (2.75)	2/05/92	1410	0.51 (0.014)	
		Barrio Carreras, at Hwy 405, 100 ft (30 m) east from intresection with Hwy 404, and 0.5 mi (0.8 m) northeast from Mayaguez Plaza.		6/18/92	1257	0.50 (0.014)	
50146200	Río Grande near	Lat 18°22'06", long 67°13'56".	2.83	2/06/92	0757	0.59	
	Rincón, PR	Hydrologic unit 21010003. At bridge on Hwy 115, 1.2 mi (1.9 km) upstream from mouth, and 2.2 mi (3.5 km) northeast of Rincón.	(7.33)	6/19/92	0621	(0.017) 2.71 (0.077)	
		Río Ingenio basin					
50146300	Río Ingenio at Jagüey, PR	Lat 18°20'36", long 67°11'52". Hydrologic unit 21010003.	3.18 (8.22)	2/06/92	0915	1.52 (0.043)	
		Bario Jaguey, at unmunbered Hwy, 0.3 mi (0.5 km) from Hwy 411 intersection, and 2.7 mi (4.3 km) southwest from Aguada Plaza.		6/19/92	0918	9.83 (0.278)	
50146400	Río Ingenio near Aguada, PR	Lat 18°22'48", long 67°12'35". Hydrologic unit 21010003. At	7.00 (18.1)	2/06/92	0720	2.34 (0.066)	
		bridge on unimproved road, 0.3 mi (0.5 km) upstream from con-	,,	6/19/92	0654	5.55 (0.157)	
		fluence with Río Culebra, 0.7 mi (1.1 km) upstream from mouth of Río Guayabo, and 1.4 mi (2.3 km) west of Aguada.		7/08/92	0825	3.17 (0.090)	
		Río Culebra basin					
50146600	Río Culebra near Aguada, PR	Lat 18°22'26", long 67°11'35". Hydrologic unit 21010003. At	3.75 (9.70)	2/06/92	0834	1.22 (0.034)	
		bridge on Hwy 411, 0.6 mi (1.0 km) south of Aguada, 1.5 mi (2.4 km) upstream from confluence with Río Ingenio, and 1.9 mi (3.1 km) upstream from mouth of Río Guayabo.		6/19/92	1015	3.53 (0.100)	

THIS PAGE WAS LEFT BLANK INTENTIONALLY



Water-quality partial-record stations are particular sites where chemical-quality, biological and or sediment data are collected systematically over a period of years for use in hydrological analysis. The data are collected usually less than quarterly.

WATER-QUALITY DATA, WATER YEAR OCTOBER 1991 TO SEPTEMBER 1992

DATE 50010720	TIME	LOC- ATION, TOTAL (FEET) (SPR- CIFIC CON- DUCT- ANCE US/CM)	PH WATER WHOLE FIELD (STAND- ARD UNITS) O GUAJATA	TEMPER- ATURE WATER (DEG C) ACA BASIN	TRANS- PAR- ENCY (SECCHI DISK) (IN)	OXYGEN, DIS- SOLVED (MG/L)	OXYGEN, DIS- SOLVED (PER- CENT SATUR- ATION)	COLI- FORM, FECAL, 0.7 UM-MF (COLS./ 100 ML)
-						, ,			
NOV 1991 22 MAR 1992	0740	1.00	274	7.1	26.0	104	5.8	71	K12
17 Jul	0840	1.00	254	7.6	26.5	19.0	11.6	150	230
21	0835	1.00	293	7.7	28.0	76.0	5.9	76	410
			RIO GRA	NDE DE AI	RECIBO BA	SIN			
50025110	LAGO	DOS BOCAS NO	.3 AT WE	ST BRANCI	H NR UTUA	DO, PR (LA	r 18°19′15	"N LONG	066°40'11"W)
NOV 1991 20 MAR 1992	0940	1.00	235	6.6	26.0	17.0	2.5	31	91
13 JUL	0910	1.00	252	7.3	26.0	22.0	5.1	62	200
24	0855	1.00	231	6.9	28.5	26.0	7.1	84	70
			RIO D	E LA PLA	TA BASIN				
50039900	LAGO	CARITE NO.3	ON RIO D	E LA PLA	TA NR CAY	BY, PR (LA	T 18°05′04	"N LONG	066°06′03"W)
NOV 1991 19 MAR 1992	0945	1.00	113	6.6	24.5	91.0	6.9	86	K 7
18 JUL	0940	1.00	116	6.5	23.5	71.0	7.5	93	36
22	0850	1.00	503	7.1	27.0	54.0	8.1	100	40
50044400	LAGO	LA PLATA NO.	5 NR MOU	TH NR NAI	RANJITO,	PR (LAT 1	8°19′33*N	LONG 066	°12′28°W)
NOV 1991 18 MAR 1992	0845	1.00	280	6.9	25.5	12.0	6.8	82	270
12 JUL	0850	1.00	388	7.9	26.0	37.0	6.1	75	K2
16	0850	1.00	374	7.7	29.0	18.0	7.6	97	K15
			RIO G	RANDE DE	LOIZA BA	SIN			
50057500	LAGO	LOIZA NO.4 N	R MOUTH	NR CAGUA	B, PR (LA	T 18°16'5	1"N LONG 0	66°00′35	"W)
NOV 1991 14 MAR 1992	0935	1.00	247	6.6	25.5	12.0	3.5	42	K1100
11 JUL	1120	1.00	360	7.6	27.5	36.0	8.2	100	K1900
17	0945	1.00	315	6.7	30.0	43.0	4.9	64	84

K = non-ideal count

WATER-QUALITY DATA, WATER YEAR OCTOBER 1991 TO SEPTEMBER 1992

	DATE	STREP- TOCOCCI FECAL, KF AGAR (COLS. PER 100 ML)	ALKA- LINITY WAT WH TOT FET FIELD MG/L AS CACO3	RESIDUE TOTAL AT 105 DEG. C, SUS- PENDED (MG/L)	NITRO- GEN, NITRATE TOTAL (MG/L AS N)	NITRO- GEN, NITRITE TOTAL (MG/L AS N)	TOTAL (MG/L AS N)	NITRO- GEN, AMMONIA TOTAL (MG/L AS N)	NITRO- GEN, ORGANIC TOTAL (MG/L AS N)	
50010720	LA	GO GUAJAT	ACA NO.3	NR MOUTH	NR QUEBRA	DILLAS, PR	(LAT 18°	22'05"N L	ONG 066°54'3	6"W)
	NOV 1991 22 MAR 1992	33		1		<0.010	<0.050	0.030	0.37	
	17 JUL	120		3		<0.010	<0.050	0.010	0.49	
	21	33		20		<0.010	0.920	0.020		
			RI	O GRANDE	DE ARECIE	O BASIN	Continued	l		
50025110	LA	GO DOS BO	CAS NO.3	AT WEST B	RANCH NR	UTUADO, PR	(LAT 18°	19'15"N L	ONG 066040'1	L=W)
	NOV 1991 20 MAR 1992	44		3	0.430	0.050	0.480	0.130	0.37	
	13	40		<1	0.520	0.030	0.550	0.050	0.25	
	JUL 24	310		16	0.300	0.020	0.320	0.020	0.58	
				RTO DE LA	PLATA BA	SINCont	inued			
50039900		00 01 DTMB						05/04 HW T	ONG 066°06'0:	2 8 63 1\
30033300		GO CARITE	NO.3 ON	KIO DE LA	PLATA NA	CAISI, PR	(TWI TO-	na.ne.w r	CARG DESTUS D.) - W)
	NOV 1991 19 MAR 1992	40		2		<0.010	0.098	0.030	0.27	
	18 Jul	41		1		<0.010	0.075	0.010		
	22	41		14		<0.010	<0.050	0.010	0.29	
50044400	LA	GO LA PLA	TA NO.5 N	R MOUTH N	R NARANJI	TO, PR (L	AT 18°19'	33"N LONG	066°12'28"W	,
	NOV 1991									
	18 MAR 1992	410		2	0.430	0.050	0.480	0.010	0.59	
	12	K2		<1		<0.010	<0.050	<0.010		
	JUL 16			26		<0.010	<0.050	0.030	0.47	
			RI	O GRANDE	DE LOIZA	BASINCo	ntinued			
50057500	LA	GO LOIZA	NO.4 NR M	OUTH NR C	AGUAS, PR	(LAT 18°	16'51"N I	ONG 066°0	0'35"W)	
	NOV 1991	K110		10	0.450	0.090	0.540	0.700	0.50	
	MAR 1992 11	K96		<1	0.320	0.100	0.420	1.30	0.90	
	JUL									
	17	50		20	0.320	0.130	0.450	0.850	0.45	

K = non-ideal count

ANALYSES OF SAMPLES COLLECTED AT WATER-QUALITY PARTIAL-RECORD STATION

WATER-QUALITY DATA, WATER YEAR OCTOBER 1991 TO SEPTEMBER 1992

	DATE	NITRO- GEN, AM- MONIA + ORGANIC TOTAL (MG/L AS N)	NITRO- GEN, TOTAL (MG/L AS N)	NITRO- GEN, TOTAL (MG/L AS NO3)	PHOS- PHORUS TOTAL (MG/L AS P)	CHLOR-A PHYTO- PLANK- TON CHROMO FLUOROM (UG/L)	CHLOR-B PHYTO- PLANK- TON CHROMO FLUOROM (UG/L)	PLANK- TON BIOMASS ASH WT (MG/L)	PLANK- TON BIOMASS DRY WT (MG/L)
				RIO GU	AJATACA B	ASINCon	tinued		
50010720	L	AGO GUAJATA	ACA NO.3 N	IR MOUTH I	NR QUEBRA	DIL LAS, PR	(LAT 18°	22'05"N L	ONG 066°54'36"W)
	NOV 1991 22 MAR 1992	0.40			0.030	4.50	<0.100	230	240
	17 JUL	0.50			0.020	10.0	1.40	280	290
	21	<0.20			<0.010	7.60	0.100	240	250
			RIC	GRANDE I	DE ARECIB	BASIN	Continued		
50025110	ı.	GO DOS BOO	CAS NO.3 A	at west b	RANCH NR	UTUADO, PR	(LAT 18°	19'15"N L	ONG 066°40'11"W)
	NOV 1991 20 MAR 1992	0.50	0.98	4.3	0.040	2.70	<0.100	250	250
	13	0.30	0.85	3.8	0.010	3.30	<0.100	250	260
	24	0.60	0.92	4.1	0.050	13.0	0.600	250	260
			F	SIO DE LA	PLATA BA	SINCont	inued		
50039900	I.J	GO CARITE	NO.3 ON F	IO DE LA	PLATA NR	CAYBY, PR	(LAT 18°	05'04"N L	ONG 066°06'03"W)
	NOV 1991 19	0.30	0.40	1.8	0.010	16.0	4.00	220	222
	MAR 1992				0.010	16.0			220
	18	<0.20			<0.010	4.80	1.20	240	240
	22	0.30			0.020	8.90	0.600	400	410
50044400	L	AGO LA PLAT	ra no.5 ne	NOUTH N	R NARANJI	TO, PR (L	AT 18°19'	33"N LONG	066°12′28"W)
	NOV 1991 18 MAR 1992	0.60	1.1	4.8	0.210	42.0	<0.100	230	240
	12 JUL	0.40			0.040	15.0	1.50	250	260
	16	0.50			0.100	3.70	<0.100	250	260
			RIC	GRANDE 1	DE LOIZA	BASINCo	ntinued		
50057500	ı.,	GO LOIZA N	NO.4 NR MAC	OUTH NR C	AGUAS, PR	(LAT 18°	16'51"N L	ONG 066°0	0'35"W)
	NOV 1991	1.2	1.7	7.7	0.340	1.60	<0.100	270	280
	MAR 1992 11	2.2	2.6	12	0.540	38.0	<0.100	260	260
	JUL								_
	17	1.3	1.7	7.7	0.390	2.10	0.700	260	260

DATE	TIME	DEPTH AT SAMPLE LOC- ATION, TOTAL (FEET)	SPE- CIFIC CON- DUCT- ANCE (US/CM)	PH WATER WHOLE FIELD (STAND- ARD UNITS)	TEMPER- ATURE WATER (DEG C)	TRANS- PAR- ENCY (SECCHI DISK) (IN)	OXYGEN, DIS- SOLVED (MG/L)	OXYGEN, DIS- SOLVED (PER- CENT SATUR- ATION)	COLI- FORM, FECAL, 0.7 UM-MF (COLS./ 100 ML)	STREP- TOCOCCI FECAL, RF AGAR (COLS. PER 100 ML)
				RIO GU	АЈАТАСА В	asin				
50010790	LAGO	GUAJATACA	NO.1 NR	DAM NR QU	BBRADILLA	S,PR (LAT	18°23′56	"N LONG 0	66°55′23'	W)
NOV 1991 22	0820	1.00	<274	7.4	26.5	178	6.0	74	K2	K4
22	0805	84.0	261	6.6	24.5		0.1			
MAR 1992 17	0910	1.00	264	7.8	25.5	28.0	7.8	90	54	78
17	0915	64.0	316	6.8	24.5		0.1			
JUL 21	0920	1.00	284	8.3	28.5	60.0	8.0	100	76	10
21	0925	63.0	324	7.1	26.5		2.0	21		
			R	O GRANDE	DE ARECIB	O BASIN				
50020050	LAGO	GARZAS NO	.1 NR DAI	NR ADJUN	TAS, PR (L	AT 18°08'	21"N LONG	066044'3	5"W)	
NOV 1991 21	1045	1.00	156	6.8	23.0	54.0	6.5	81	20	27
21	1040	79.0	183	6.2	20.5		0.1	2		
MAR 1992 16	1055	1.00	157	7.1	24.0	44.0	7.9	100	92	76
16 Jul	1050	67.0	159	6.4	20.0		0.1	1		
21	1410	1.00	229	7.7	25.0	104	5.2	67	K300	K10
21	1415	77.0	139	6.8	21.9		2.0	7		
50027090	LAGO	DOS BOCAS	NO.1 NR	DAM NR UT	UADO, PR (LAT 18°20	'09"N LON	G 066°40'	04 "W)	
NOV 1991										
20 20	1010 1000	1.00 64.0	215 225	6.7 6.3	27.0 25.5	60.0	3.2 0.1	40 1	 54	K11
MAR 1992								_		
13 13	0945 1010	1.00 72.0	250 218	8.1 6.5	26.0 24.0	64.0 	7.9 0.1	97 72	20	74
JUL 24 24	0935 0930	1.00 72.0	223 235	6.8 6.9	28.5 26.5	44.0	7.6 2.6	96	30	K1200
				RIO DE LA	PLATA BA	SIN				
50039950	LAGO	CARITE NO	.1 NR DAI	NR CAYBY	, P.R. (L	AT 18°04'	39"N LONG	066006'1	9 " W)	
NOV 1991 19	1035	1.00	113	6.7	24.5	65.0				
19	1035	62.0	178	6.0	22.5	65.0 	7.1 0.1	89 1	44	 46
MAR 1992 18	1030	1.00	114	7.3	23.5	80.0	8.4	100	K8	K18
18	1025	49.0	72	6.0	21.0		0.0			
JUL 22	0925	1.00	558	7.2	27.0	28.0	7.7	100	15	400
22	0920	52.0	319	6.4	25.5		0.0			
50044950	LAGO	LA PLATA I	NO.3 NR I	AM NR NAR	ANJITO, P	R (LAT 18	°20'18"N	rong 0660	14′01°W)	
NOV 1991 18	0920	1.00	309	6.6	26.0	24.0	3.2			7600
18	0910	68.0	305	5.8	24.0		0.1	39 1	4 0	K680
MAR 1992 12	0930	1.00	306	7.7	<27.0	64.0	7.2	90	K4	14
12	0935	48.0	158	6.7	22.5		0.1			14
JUL 16	0935	1.00	310	7.5	29.5	41.0	6.5	62	10	18
16	0930	27.0	215	6.7	24.5		0.4			
			RI	O GRANDE	DE LOIZA	Basin				
50058800	LAGO	LOIZA NO.	7 NR DAM	NR TRUJIL	LO ALTO,	PR (LAT 1	8°19′29*N	LONG 066	°00′47 "W)	
NOV 1991 14	0855	1.00	140	6.2	25.5	4.00	2.7	33	600	970
14 MAR 1992	0840	40.0	113	5.8	24.0		0.3	4		
11	1030	1.00	338	7.2	27.0	41.0	5.6	70	10	30
11 Jul	1040	39.0	337	7.0	26.0		0.1			
17 17	0850 0835	1.00 42.0	266 215	7.0 6.4	29.5 27.4	48.0	4.8 0.2	32	210 	770

K = non-ideal count

DATE	HARD- NESS TOTAL (MG/L AS CACO3)	HARD- NESS NONCARB WH WAT TOT FLD MG/L AS CACO3	CALCIUM DIS- SOLVED (MG/L AS CA)	MAGNE- SIUM, DIS- SOLVED (MG/L AS MG)	SODIUM, DIS- SOLVED (MG/L AS NA)	SODIUM AD- SORP- TION RATIO	POTAS- SIUM, DIS- SOLVED (MG/L AS K)	ALKA- LINITY WAT WH TOT FET FIELD MG/L AS CACO3	SULPATE DIS- SOLVED (MG/L AS SO4)
			R	IO GUAJAT	ACA BASIN	Continue	d		
50010790	LAGO	GUAJATACA	NO.1 NR	DAM NR QU	EBRADILLA	S,PR (LAT	18°23′56	"N LONG O	66°55′23 *W)
NOV 1991									
22 22	130	7 6	45	3.3	4.6	0.2	1.8	120	8.9
MAR 1992	140	•	49	3.4	5.3	0.2	2.0	130	8.5
17	150	12	54	3.9	7.1	0.3	1.8	120	10
17 JUL	130	6	45	3.7	6.2	0.2	1.8	140	13
21	120	9	42	3.6	5.5	0.2	1.8	120	10
21	160	7	57	3.1	4.6	0.2	1.6	120	10
			RIO GR	ANDR DR A	RRCIBO BA	SINConti	nued		
50020050	LAGO	GARZAS NO	.1 NR DAM	NR ADJUN	TAS, PR (L	AT 18°08'2	1"N LONG	066944'3	5 *W)
NOV 1991 21	68	0	19	4.9	6.5	0.3	1.7	50	<0.10
21	63	ŏ	18	4.5	6.0	0.3	1.3	43	3.1
MAR 1992									
16 16	60 61	0	17 17	4.3 4.5	6.8 6.0	0.4 0.3	1.6 1.5	72 70	2.6 2.7
JUL	01	v	1,	4.5	0.0	0.3	1.5	,,	•.,
21	62	0	17	4.7	5.9	0.3	1.3	80	3.1
21	61	0	17	4.4	5.1	0.3	1.8	80	1.4
50027090	LAGO	DOS BOCAS	NO.1 NR	DAM NR UT	UADO, PR (LAT 18°20'	09"N LON	G 066°40′	04 °W)
NOV 1991		_							
20 20	80	3 6	<0.02 22	<0.01 6.2	<0.20 11	0.5 0.5	2.6 2.4	74 75	13 13
MAR 1992	•	•	••	0.2		0.5	•••	,,	10
13	95	3	26	7.4	13	0.6	2.4	72	15
13 JUL	80	2	22	6.1	10	0.5	2.9	70	12
24	76	2	20	6.3	10	0.5	2.3	80	12
24	85		23	6.8	11	0.5	2.1	80	14
			RIO	DE LA PLA	TA BASIN-	-Continued	1		
50039950	LAGO	CARITE NO	.1 NR DAM	NR CAYEY	, P.R. (L	AT 18°04'3	9"N LONG	066006'1	9*W)
NOV 1991									
19	40	0	9.3	4.1	8.7	0.6	1.3	27	0.20
19	32	Ō	6.7	3.7	9.2	0.7	1.5	30	2.9
MAR 1992 18	30	0	7.5	2.8	7.7	0.6	0.80	19	2.5
18	30	ŏ	6.4	3.5	8.5	0.7	0.90	30	2.6
JUL		_							
22 22	29 30	0	6.2 5.7	3.3 3.8	6. 0 8.5	0.5 0.7	0.90 0.80	38 40	0.70 2.8
50044950	****							T 0010 ACCO	4 4 4 0 4 8883
30V4433V	TWGO	UR PLATA	MU.S NK D	na na nar	ANJITO, P	R (LAT 18°	70. TR.M	Trues 1000	TA. AT.M)
NOV 1991		_							
18 18	120 120	0	28 29	11 12	14 19	0.6 0.7	3.2 2.5	76 110	4.3 15
MAR 1992		•	• •	4.		• • •		110	15
12	120	6	29	11	17	0.7	2.9	89	13
12 JUL	56	1	14	5.1	9.2	0.5	2.2	43	8.2
16	73	5	18	6.8	12	0.6	2.6	140	10
16	100	1	25	10	16	0.7	2.4	150	17
			RIO GR	ANDR DR L	OIZA BASI	NContinu	ed		
50058800	LAGO	LOIZA NO.				PR (LAT 18		LONG 066	°00′47*W)
NOV 1991									
14	32	7	8.9	2.4	7.9	0.6	2.8	71	7.3
14	34	0	9.0	2.8	9.1	0.7	3.0	63	9.3
MAR 19 11	110	1	27	10	28	1	2.9	50	18
11	110	ì	27	10	27	i	3.0	44	18
JUL		_							10
17 17	78 87	3 0	18 21	7.0 8.5	18 22	0.9 1	2.4 3.4	98 92	12 15
	-,	-				-			

DATE	CHLO- RIDB, DIS- SOLVED (MG/L AS CL)	FLUO- RIDE, DIS- SOLVED (MG/L AS F)	SILICA, DIS- SOLVED (MG/L AS SIO2)	SOLIDS, SUM OF CONSTI- TUENTS, DIS- SOLVED (MG/L)	RESIDUR TOTAL AT 105 DEG. C, SUS- PENDED (MG/L)	NITRO- GEN, NITRATE TOTAL (MG/L AS N)	NITRO- GEN, NITRITE TOTAL (MG/L AS N)	NITRO- GEN, NO2+NO3 TOTAL (MG/L AS N)	NITRO- GEN, AMMONIA TOTAL (MG/L AS N)
			RIO GUAJ	ATACA BAS	INConti	nued			
50010790	LAGO (BUAJATACA	NO.1 NR	DAM NR QU	ebradi Lla	S,PR (LAT	18º23'56	"N LONG 0	66°55′23"W)
NOV 1991									
22 22 MAR 1992	8.6 7.4	0.10 0.10	6.3 6.3	164 153	1		<0.010 	<0.050 	0.030
17 17 JUL	10 10	0.10 0.10	3.7 7.2	150 182	5		<0.010 	<0.050 	0.010
21 21	11 9.6	0.10 0.10	1.3 4.9	142 181	50 		<0.010	<0.050 	<0.010
			RIO GR	ANDE DE A	RECIBO BA	SINCont	inued		
5000000									
50020050	LAGO (BARZAS NO	.1 NR DAM	NR ADJUN	TAS, PR (L	AT 18008,	21"N LONG	06604473	5 "W)
NOV 1991			4.5		_				
21 21	6.9 6.6	<0.10 <0.10	17 20	100	3		<0.010	<0.050 	0.040
MAR 1992	•••	(0.10	20						
16 16 JUL	6.4 6.4	<0.10 <0.10	12 17	88 94	2		<0.010 	<0.050 	0.020
21	6.3	<0.10	15	92					
21	7.2	<0.10	16	97	24		<0.010	<0.050	0.030
50027090	LAGO I	DOS BOCAS	NO.1 NR	DAM NR UT	UADO, PR (LAT 18°20	'09"N LON	G 066°40′	04 "W)
NOV 1991									
20 20 Mar 1992	10 11	0.10 0.10	21 22	137 	1	0.320	0.040	0.360	0.070
13	16	0.20	21	154	<1	0.280	0.020	0.300	<0.010
13 JUL 24	13	0.10	19	126					
24	13 11	0.10 <0.10	21 20	138 124	11	0.210	0.010	0.220	0.010
			RTO	DE LA PLA	TA BACTN_	-Continue	a		
			X10	78 M. FM.	IN DUSTM-	-COMETHER	•		
50039950	LAGO (CARITE NO	.1 NR DAM	INR CAYBY	, P.R. (L	AT 18°04'	39"N LONG	066°06′1	9 *W)
NOV 1991 19	9.9	<0.10	19	74	9		<0.010	<0.050	0.030
19	10	0.20	20	87	1				
MAR 1992									
18 18 Jul	9.3 8.0	<0.10 <0.10	17 15	69 60			<0.010 	0.064	<0.010
22 22	9.8 7.9	<0.10 <0.10	15 11	67 58			<0.010 	<0.050 	0.010
50044950	LAGO I	LA PLATA	NO.3 NR D	AM NR NAR	ANJITO, P	R (LAT 18	°20′18"N	LONG 066°	14′01°W)
NOV 1991					_				
18 18 MAR 1992	23 19	<0.10 0.10	19 20	193 178	1		<0.010	<0.050 	0.020
12 12 JUL	21 12	0.20 0.10	14 14	176 91	<1		<0.010 	<0.050 	<0.010
16	23	0.20	16	172	18		<0.010	<0.050	0.030
16	15	0.10	15	121					
			RIO GR	ANDE DE L	OIZA BASI	NContin	ued		
50058800	LAGO 1	LOIZA NO.	7 NR DAM	NR TRUJIL	LO ALTO,	PR (LAT 1	8°19′29"N	LONG 066	°00′47°W)
NOV 1991			4-		_				
14 14	11 9.1	<0.10 <0.10	15 11	80 65	2	0.430	0.250	0.680	0.140
MAR 1992	J.1	~0.10	**	69					= =
11 11 JUL	29 28	0.20 0.10	21 22	200 200	5	0.170	0.040	0.210	0.050
17 17	21 20	0.20 0.1	23 25	148 170	20	0.120	0.140	0.260	0.040

DATE	NITRO- GEN, ORGANIC TOTAL (MG/L AS N)	NITRO- GEN, AM- MONIA + ORGANIC TOTAL (MG/L AS N)	NITRO- GEN, TOTAL (MG/L AS N)	NITRO- GEN, TOTAL (MG/L AS NO3)	PHOS- PHORUS TOTAL (MG/L AS P)	CHLOR-A PHYTO- PLANK- TON CHROMO FLUOROM (UG/L)	CHLOR-B PHYTO- PLANK- TON CHROMO PLUOROM (UG/L)	PLANK- TON BIOMASS ASH WT (MG/L)	PLANK- TON BIOMASS DRY WT (MG/L)
			RIO GUA	JATACA BA	SINCont	inued			
50010790	LAGO	GUAJATACA	NO.1 NR	DAM NR QU	EBRADILLA	S, PR (LAT	18°23′56	"N LONG	66°55′23 °W)
NOV 1991									
22 22	0.27	0.30			0.020	0.700	<0.100	2.0	250
MAR 1992									
17 17	0.29	0.30			<0.010 	2.90	<0.100 	400	410
JUL 21		0.40			<0.010	3.50	0.800	250	250
21									
		RIC	GRANDE	DE ARECIE	O BASIN	Continued	Į		
50020050	LAGO	GARZAS NO.	.1 NR DAM	NR ADJUN	PTAS, PR (L	AT 18°08'	21"N LONG	06604413	15*W)
NOV 1991								242	0.50
21 21	0.36	0.40			0.010	2.90	<0.100 	240	250
MAR 1992 16	0.18	0.20			-0.010	2.80	<0.100	250	250
16					<0.010 				
JUL 21		<0.20			<0.010	8.30	0.700	240	240
21									
50027090	LAGO	DOS BOCAS	NO.1 NR	DAM NR UT	UADO, PR (LAT 18°20	'09"N LON	G 066° 4 0′	04 "W)
NOV 1991	0.22	0.40	0.76	• •		4 40	.0.100	. 240	250
20 20	0.33	0.40	0.76 	3.4	0.030	4.10	<0.100 	240	250
MAR 1992 13		0.20	0.50	2.2		F 10	.0 100	250	260
13 JUL				2.2	0.030	5.10	<0.100 		
24 24	0.29 	0.30 	0.52 	2.3	0.010	7.50 	0.400	250 	260
			RIO	DE LA PLA	TA BASIN-	-Continue	đ		
50039950	LAGO	CARITE NO.	.1 NR DAM	NR CAYEY	, P.R. (L	AT 18°04'	39"N LONG	0660061	.9 "W)
NOV 1991									
19 19	0.37	0.40			0.010	31.0	8.40	210	210
MAR 1992									
18 18		<0.20 			<0.010 	4.60	1.20	250	260
JUL 22	0.10						4 00	***	400
22	0.19	0.20			<0.010 	4.40	1.00	410	420
50044950	LAGO	LA PLATA I	NO.3 NR D	AM NR NAR	ANJITO, P	R (LAT 18	°20′18*N	LONG 066°	14'01"W)
NOV 1991									
18 18	0.38	0.40			0.070	4.10	<0.100	250	250
MAR 1992									
12 12 JUL		0.30			<0.010 	3.10	<0.100 	240	240
16	0.27	0.30			<0.010	1.20	0.300	250	260
16									
			RIO GR	ANDE DE L	OIZA BASI	NContin	ued		
50058800	LAGO	LOIZA NO.	7 NR DAM 1	NR TRUJIL	LO ALTO,	PR (LAT 1	8°19'29"N	LONG 066	900'47"W)
NOV 1991 14	0.66	0.80	1.5	6.6	0.210	3.40	<0.100	280	290
14									
MAR 1992 11	0.45	0.50	0.71	3.1	0.120	15.0	<0.100	260	260
11									
JUL 17 17	0.56	0.60	0.86	3.8	0.160	5.60	<0.100	260	270

PESTICIDE ANALYSES OF SAMPLES COLLECTED AT WATER-QUALITY PARTIAL-RECORD STATIONS WATER-QUALITY DATA, WATER YEAR OCTOBER 1991 TO SEPTEMBER 1992

DATE	TIME	PCB, TOTAL UG/L)	ALDRIN, TOTAL (UG/L)	CHLOR- DANE, TOTAL (UG/L)	DDD, TOTAL (UG/L)	DDE, TOTAL (UG/L)	DDT, TOTAL (UG/L)	DI- AZINON, TOTAL (UG/L)	DI- ELDRIN TOTAL (UG/L)	ENDO- SULFAN, TOTAL (UG/L)
				RIO GUA	JATACA B	ASINCon	tinued			
50010790	LAG	O GUAJA	TACA NO.1	NR DAM NR	QUEBRAD	ILLAS, PR	(LAT 18?2	3'56"N LO	NG 066?55	'23 "W)
JUL 21	0920	<0.1	<0.010	<0.1	<0.010	<0.010	<0.010	<0.01	<0.010	<0.010
			R	IO GRANDE	DE AREC	IBO BASIN	Continu	ıed		
5002005 0	LAC	O GARZA	S NO.1 NR	DAM NR AD	JUNTAS, P	R (LAT 18	?08'21"N	LONG 066?	14"35"W)	
JUL 21	1410	<0.1	<0.010	<0.1	<0.010	<0.010	<0.010	<0.01	<0.010	<0.010
50027090	LAG	O DOS B	OCAS NO.1	NR DAM NR	UTUADO,	PR (LAT 1	8?20'09"h	LONG 066	240'04"W)	
JUL 24	0935	<0.1	<0.010	<0.1	<0.010	<0.010	<0.010	<0.01	<0.010	<0.010
			R	IO DE LA	PLATA BA	SINCont	inued			
50044950	LAG	O LA PL	ATA NO.3 N	R DAM NR	NARANJIT	O, PR (LA	T 18720'1	L8"N LONG	066? 01W)	
JUL 16	0935	<0.1	<0.010	<0.1	<0.010	<0.010	<0.010	<0.01	<0.010	<0.010
			R	IO GRANDE	DE LOIZ	A BASIN	Continued	1		
50058800	LAG	O LOIZA	NO.7 NR D	AM NR TRU	JILLO AL	TO, PR (L	AT 18719'	29"N LONG	066700'4	7 "W)
JUL 17	0850	<0.1	<0.010	<0.1	<0.010	<0.010	<0.010	0.02	<0.010	<0.010


PESTICIDE ANALYSES OF SAMPLES COLLECTED AT WATER-QUALITY PARTIAL-RECORD STATIONS WATER-QUALITY DATA, WATER YEAR OCTOBER 1991 TO SEPTEMBER 1992

DATE	Endrin Water Unfltrd Rec (UG/L)	ETHION, TOTAL (UG/L)	HEPTA- CHLOR, TOTAL (UG/L)	HEPTA- CHLOR EPOXIDE TOTAL (UG/L)	LINDANB TOTAL (UG/L) ACA BASIN-	MALA- THION, TOTAL (UG/L)	MRTH- OXY- CHLOR, TOTAL (UG/L)	METHYL PARA- THION, TOTAL (UG/L)	MIREX, TOTAL (UG/L)
50010790	LAGO	GUAJATACA	NO.1 NR	DAM NR QU	EBRADILL A S	B,PR (LAT	18723'56'	'N LONG 06	6?55'23"W)
JUL 21	<0.010	<0.01	<0.010		<0.010			<0.01	<0.01
50020050	LAGO	GARZAS NO	.1 NR DAM	NR ADJUN	TAS, PR (LJ	AT 18708'	1"N LONG	066744*35	5*W)
JUL 21	<0.010	<0.01	<0.010	<0.010	<0.010	<0.01	<0.01	<0.01	<0.01
50027090	LAGO	DOS BOCAS	NO.1 NR	DAM NR UT	UADO, PR (I	AT 18720	09"N LONG	3 066740'0	(4 "W)
JUL 24	<0.010	<0.01			<0.010			<0.01	<0.01
50044950	T 1 00	LA PLATA						ONG 0663	0.150)
	IMGO	IM PLINTA	NO.3 NR D	AM NA MAR	ANULTO, PI	K (1791, 194	. 20. 19. N 1	JONG UBBY	UIW)
JUL 16	<0.010	<0.01	<0.010	<0.010	<0.010	<0.01	<0.01	<0.01	<0.01
			RIO	GRANDE D	e loiza b	ASINCont	inued		
50058800	LAGO	LOIZA NO.	7 NR DAM I	NR TRUJIL	LO ALTO, I	PR (LAT 1	3719'29"N	LONG 0667	00'47"W)
JUL 17	<0.010	<0.01	<0.010	<0.010	<0.010	<0.01	<0.01	<0.01	<0.01

PESTICIDE ANALYSES OF SAMPLES COLLECTED AT WATER-QUALITY PARTIAL-RECORD STATIONS WATER-QUALITY DATA, WATER YEAR OCTOBER 1991 TO SEPTEMBER 1992

DATE	PARA - THION, TOTAL (UG/L)	TOTAL	PER- THANE TOTAL (UG/L)	TOX- APHENE, TOTAL (UG/L)	TOTAL TRI- THION (UG/L)	2,4-D, TOTAL (UG/L)	2,4,5-T TOTAL (UG/L)	2, 4-DP TOTAL (UG/L)	SILVEX, TOTAL (UG/L)
			R	IO GUAJAT.	ACA BASIN	Continu	ed		
50010790	LAGO	GUAJATACA	NO.1 NR	DAM NR QU	EBRADILLA:	S,PR (LAT	18723'56	"N LONG 0	66?55'23"W)
JUL 21	<0.01	<0.10	<0.1	∢1	<0.01	0.06	<0.01	<0.01	<0.01
			RIO	GRANDE D	E ARECIBO	BASINC	ontined		
50020050	LAGO	GARZAS NO	.1 NR DAM	NR ADJUN	TAS,PR (L	AT 18708'	21"N LONG	066744"3	5*W)
JUL 21	<0.01	<0.10	<0.1	∢1	<0.01	0.06	<0.01	<0.01	<0.01
50027090	LAGO	DOS BOCAS	NO.1 NR	DAM NR UT	UADO, PR ()	LAT 18?20	'09"N LON	G 066?40'	04 "W)
JUL 24	<0.01	<0.10	<0.1	<1	<0.01	<0.01	<0.01	<0.01	<0.01
			RI	O DE LA P	LATA BASII	NContin	ued		
50044950	LAGO	LA PLATA I	NO.3 NR D	AM NR NAR	ANJITO, P	R (LAT 18	?20'18"N	LONG 066?	01W)
JUL 16	<0.01	<0.10	<0.1	<1	<0.01	<0.01	<0.01	<0.01	<0.01
			RIO	GRANDE D	E LOIZA B	ASINCon	tinued		
50058800	LAGO	LOIZA NO.	7 NR DAM	NR TRUJIL	LO ALTO,	PR (LAT 1	8?19'29"N	LONG 066	?00'47"W)
JUL									
17	<0.01	<0.10	<0.1	<1	<0.01	<0.01	<0.01	<0.01	<0.01

THIS PAGE WAS LEFT BLANK INTENTIONALLY



Ground-Water Records for Puerto Rico

RIO GUAJATACA BASIN

182422067015100. Local number, 165.

LOCATION.--Lat 18°24'22*, long 67°01'51*, Hydrologic Unit 21010003, 5.60 mi northeast of Moca plaza, 4.70 mi southeast of Aguadilla U.S. Naval Reservation Radio Antenna, and 1.63 mi northwest of La Virgen del Rosario Church. Owner: P.R. Aqueduct and Sewer Authority, Name: Saltos # 1 (Mateo Pérez).

AQUIFER.--Cibao Formation. Aguada Limestone.

MELL CHARACTERISTICS.--Drilled production water-table well, diameter 16 in (0.40 m), cased 16 in (0.40 m) 0-40 ft (0-12.2 m), cased 12 in (0.30 m) 40-200 ft (12.2-61.0 m). Depth 200 ft (61.0 m).

INSTRUMENTATION.--Digital water level recorder--60-minute punch.

DATUM.--Elevation of land-surface datum is 689 ft (210 m) above mean sea level.

Measuring point: Hole on pump base, 0.80 ft (0.24 m) above land-surface datum. Prior to November 1985, hole on top of pump base, 1.00 ft (0.30 m) above land-surface datum.

REMARKS.--Recording observation well. Formerly published as 182421067015000.


PERIOD OF RECORD.--January 1982 to March 1985, November 1985 to current year.

EXTREMES FOR PERIOD OF RECORD.--Highest water level recorded, 38.75 ft (11.8 m) below land-surface datum, June 18, 1982.

WTR YR 1992 MEAN 39.35 HIGHEST 38.75 SEPT. 23, 26, 1992 LOW 39.90 DEC. 15, 1991

WINDS IPUT IN POR DELOW INTO STEPROS DINGS WINDS VERS CONCERD 1001 NO SERMEMBED 1007

		WATER LE	VEL, IN FE		land-surf Tantanbous			YEAR OCTOBE 200	R 1991 1	ro septeme	ER 1992	
DAY	ост	NOV	DEC	JAN	FEB	MAR	APR	MAY	JUN	JUL	AUG	SEP
1	39.39	39.46	39.55	39.60	39.52	39.63	39.52	39.42	39.21	39.11	39.10	38.97
2	39.42	39.48	39.56	39.50	39.51	39.58	39.49	39.48	39.19	39.08	39.10	38.97
2 3	39.45	39.47	39.51	39.52	39.50	39.51	39.46	39.41	39.26	39.08	39.10	38.96
4	39.44	39.43	39.48	39.50	39.51	39.48	39.47	39.35	39.24	39.08	38.99	38.98
5	39.39	39.40	39.48	39.50	39.47	39.49	39.49	39.35	39.17	39.07	39.11	38.96
6	39.38	39.38	39.48	39.51	39.42	39.46	39.52	39.34	39.15	39.09	39.11	38.90
7	39.39	39.40	39.47	39.53	39.44	39.48	39.57	39.40	39.23	39.11	39.09	38.90
8	39.41	39.41	39.48	39.58	39.53	39.48	39.49	39.41	39.20	39.11	39.10	38.90
9	39.46	39.39	39.47	39.62	39.62	39.48	39.49	39.45	39.14	39.08	39.08	38.91
10	39.46	39.39	39.47	39.54	39.54	39.46	39.49	39.43	39.15	39.09	39.02	38.94
11	39.44	39.39	39.49	39.53	39.57	39.45	39.47	39.36	39.13	39.09	39.09	38.94
12	39.46	39.39	39.50	39.64	39.60	39.47	39.50	39.31	39.15		39.12	38.94
13	39.46	39.36	39.51	39.59	39.63	39.50	39.50	39.24	39.17		39.13	38.91
14	39.44	39.43	39.50	39.53	39.59	39.50	39.46	39.25	39.15		39.12	38.87
15	39.40	39.46	39.59	39.55	39.63	39.50	39.44	39.28	39.13		39.03	38.88
16	39.39	39.44	39.79	39.61	39.64	39.52	39.46	39.43	39.12		39.01	38.89
17	39.45	39.41	39.78	39.67	39.64	39.67	39.47	39.32	39.11		39.09	38.89
18	39.49	39.44	39.77	39.64	39.62	39.73	39.45	39.30	39.10		39.10	38.88
19	39.45	39.49	39.74	39.62	39.63	39.67	39.40	39.26	39.00		38.98	38.88
20	39.44	39.47	39.78	39.59	39.61	39.51	39.37	39.27	39.09		39.03	38.82
21	39.47	39.46	39.80	39.56	39.59	39.49	39.36	39.26	39.14		39.04	38.88
22	39.46	39.47	39.74	39.55	39.56	39.58	39.45	39.22	39.09		38.99	38.86
23	39.39	39.45	39.65	39.57	39.53	39.55	39.45	39.19	39.08		38.98	38.82
24	39.39	39.44	39.60	39.64	39.58	39.60	39.36	39.15	39.09	39.12	38.98	38.83
25	39.38	39.39	39.66	39.63	39.54	39.51	39.33	39.24	39.08	39.12	39.02	38.84
26	39.34	39.42	39.69	39.64	39.54	39.49	39.39	39.25	39.09	39.10	39.10	38.83
27	39.35	39.48	39.69	39.82	39.55	39.55	39.44	39.24	39.09	39.12	39.11	38.82
28	39.41	39.49	39.63	39.76	39.60	39.62	39.39	39.19	39.09	39.11	39.10	38.85
29	39.38	39.49	39.58	39.68	39.52	39.61	39.33	39.23	39.10	39.09	39.01	38.88
30	39.36	39.52	39.61	39.61		39.57	39.39	39.26	39.13	39.10	38.98	38.83
31	39.43		39.63	39.54		39.53		39.23		39.09	38.97	
MBAN	39.42	39.44	39.60	39.59	39.56	39.54	39.45	39.31	39.14	39.10	39.06	38.89



RIO GUAJATACA BASIN

182647066552400. Local number, 202.
LOCATION.--Lat 18°26'47", long 66°55'24", Hydrologic Unit 21010002, 2.22 mi southeast of Quebradillas plaza, 1.29 mi north of Escuela José de Diego, and 1.99 mi northwest of El Calvario Church. Owner: P.R. Aqueduct and Sewer

north of Escuela José de Diego, and 1.99 mi northwest of El Calvario Church. Owner: P.R. Aqueduct and Sewer Authority, Name: Carmelo Barreto Garcia well.

AQUIFER.--Aguada Limestone.

MELL CHARACTERISTICS.--Drilled water-table well, diameter 20 in (0.51 m), cased 20 in (0.51 m) 0-296 ft (0-90.2 m), diameter 13 in (0.33 m), cased 13 in (0.33 m) 0-550 ft (0-167.6 m), perforated 270-529 ft (82.3-161.2 m). Depth 550 ft (167.6 m).

INSTRUMENTATION.--Digital water level recorder--60-minute punch.

DATUM.--Elevation of land-surface datum is about 475 ft (145 m) above mean sea level, from topographic map. Measuring point: Hole on side of casing, 1.50 ft (0.46 m) above land-surface datum. Prior July 25, 1986, top of shelter floor, 3.30 ft (1.00 m) above land-surface datum.

REMARKS.--Recording observation well.


PERIOD OF RECORD.--November 1985 to current year.

EXTREMES FOR PERIOD OF RECORD.--Highest water level recorded, 409.17 ft (124.71 m) below land-surface datum, June 26, 1986.

WATER LEVEL,	IN	FRET	BELOW	LAND-SURFACE	DATUM,	WATER	YBAR	OCTOBER	1991	TO	September	1992
			TNO	PANTANDORIO OD	CDDVATT	י תוב זבר	1200					

DAY	OCT	NOV	DEC	JAN	FRB	MAR	APR	MAY	JUN	JUL	AUG	SEP
1	438.60	437.90	437.65	439.52	441.12	442.75	444.28	445.63	445.69	442.78	443.95	445.01
2	438.58	437.82	437.71	439.57	441.17	442.79	444.33	445.67	445.67	442.80	444.00	445.00
3	438.59	437.71	437.75	439.65	441.22	442.84	444.35	445.69	445.09	442.83	444.06	444.99
4	438.59	437.61	437.81	439.68	441.27	442.89	444.43	445.73	444.94	442.86	444.09	445.01
5	438.59	437.52	437.88	439.74	441.31	442.95	444.47	445.82	444.78	442.89	444.18	445.03
6	438.62	437.43	437.93	439.80	441.37	442.99	444.51	445.85	444.63	442.93	444.22	445.05
7	438.64	437.38	437.99	439.88	441.44	443.04	444.56	445.90	444.45	442.95	444.28	445.11
8	438.67	437.32	438.04	439.92	441.49	443.11	444.58	445.91	444.38	442.99	444.33	445.09
9	438.72	437.27	438.11	439.97	441.53	443.16	444.65	445.94	444.36	443.02	444.37	445.11
10	438.73	437.23	438,18	439.98	441.57	443.18	444.69	445.97	443.95	443.07	444.43	445.11
11	438.74	437.17	438.27	440.05	441.66	443.26	444.72	446.01	443.76	443.10	444.53	445.14
12	438.73	437.16	438.32	440.19	441.70	443.36	444.77	446.04	443.62	443.17	444.60	445.15
13	438.71	437.12	438.38	440.21	441.74	443.58	444.81	446.09	443.50	443.21	444.66	445.17
14	438.64	437.11	438.43	440.18	441.82	443.40	444.86	446.14	443.34	443.25	444.70	445.19
15	438.57	437.10	438.50	440.23	441.86	443.45	444.92	446.16	443.24	443.29	444.75	445.22
16	438.49	437.08	438.57	440.26	441.91	443.51	444.95	446.27	443.14	443.36	444.82	445.23
17	438.46	437.08	438.64	440.31	441.96	443.58	445.01	446.18	443.06	443.38	444.90	445.24
18	438.39	437.10	438.70	440.37	442.02	443.61	445.04	446.20	442.96	443.42	444.94	445.27
19	438.34	437.13	438.77	440.41	442.07	443.64	445.08	446.23	442.90	443.47	444.97	445.28
20	438.30	437.14	438.86	440.45	442.14	443.67	445.14	446.25	442.85	443.51	445.03	445.30
21	438.29	437.17	438.91	440.67	442.38	443.71	445.19	446.25	442.84	443.53	445.10	445.32
22	438.25	437.20	438.94	440.66	442.38	443.79	445.25	446.28	442.77	443.56	445.14	445.35
23	438.24	437.22	439.01	440.67	442.51	443.82	445.27	446.27	442.74	443.60	445.19	
24	438.22	437.26	439.06	440.87	442.54	443.88	445.28	446.25	442.74	443.62	445.26	
25	438.23	437.29	439.13	440.76	442.49	443.93	445.33	446.24	442.71	443.66	445.23	445.38
26	438.18	437.35	439.19	440.96	442.53	443.96	445.38	446.16	442.71	443.69	445.16	445.36
27	438.16	437.42	439.25	440.88	442.59	444.15	445.42	446.04	442.72	443.74	445.13	445.34
28	438.14	437.47	439.30	440.94	442.65	444.09	445.46	445.91	442.72	443.77	445.07	445.31
29	438.09	437.53	439.35	440.94	442.70	444.14	445.51	445.82	442.75	443.80	445.05	445.27
30	438.02	437.59	439.40	441.04		444.17	445.58	445.72	442.77	443.86	445.02	445.19
31	437.96		439.48	441.09		444.25		445.70		443.89	444.99	
MRAN	438.43	437.33	438.56	440.32	441.90	443.50	444.93	446.01	443.59	443.32	444.71	445.19

WTR YR 1992 MRAN 442.30 HIGHEST 437.02 NOV. 17, 1991 LOWEST 446.31 MAY 23, 1992



RIO GRANDE DE ARECIBO BASIN

182737066370900. Local number, 204.

LOCATION.--Lat 18°27'37", long 66°37'09", Hydrologic Unit 21010002, 5.26 mi west of Barceloneta plaza, 1.58 mi north of Hwy 2 km 63.7, and 3.67 mi southwest of Escuela Agustín Balseiro. Owner: Sucesión Marquez, Name: Gilberto of Hwy 2 km 63.7, and 3.67 mi southwest of Escuela Agustín Balseiro. Owner: Sucesion Marquez, Name: Gilperto Rivera well.

AQUIFER.--Aymamón Limestone.

WELL CHARACTERISTICS.--Abandoned unused water-table well, diameter 6 in (0.15 m), cased 6 in (0.15 m).

INSTRUMENTATION.--Digital water level recorder--60-minute punch.

DATUM.--Elevation of land-surface datum is 48.0 ft (14.63 m) above mean sea level.

Measuring point: Air hole on pump base, 0.50 ft (0.15 m) above land-surface datum.


REMARKS.--Recording observation well.

PERIOD OF RECORD.--October 1985 to current year.

EXTREMES FOR PERIOD OF RECORD.--Highest water level recorded, 50.00 ft (15.24 m) below land-surface datum, May 14, 1986; lowest water level recorded, 52.52 ft (16.0 m) below land-surface datum, June 9-10, 1990.

		WATER LE	VEL, IN FE		Land-Surf Pantanbous			YEAR OCTOB	BR 1991 T	O SEPTEME	ER 1992	
				INST	ANTANBOUS	OBSERVAT	ION AT 1	200				
DAY	OCT	NOA	DEC	JAN	FRB	MAR	APR	MAY	JUN	JUL	AUG	SEP
1	51.95	51.79	51.88	52.19	52.21	52.27	52.18	52.14	51.99	52.14	52.28	52.17
2	51.96	51.79	51.90	52.18	52.17	52.26	52.17	52.18	51.88	52.10	52.30	52.16
3	51.96	51.78	51.89	52.17	52.18	52.24	52.17	52.22	51.83	52.06	52.37	52.19
4	51.94	51.76	51.89	52.13	52.16	52.23	52.15	52.24	51.83	52.08	52.39	52.18
5	51.90	51.75	51.89	52.12	52.14	52.22	52.12	52.23	51.83	52.10	52.43	52.16
6	51.83	51.76	51.92	52.09	52.14	52.18	52.12	52.23	51.85	52.16	52.44	52.16
7	51.83	51.77	51.95	52.07	52.11	52.17	52.17	52.23	51.90	52.20	52.45	52.12
8	51.82	51.77	52.00	52.07	52.10	52.16	52.19	52.25	51.96	52.28	52.47	52.10
9	51.86	51.78	52.02	52.10	52.16	52.15	52.15	52.27	52.03	52.29	52.46	52.11
10	51.91	51.81	52.03	52.15	52.18	52.14	52.08	52.31	52.06	52.29	52.42	52.12
11	51.94	51.82	52.03	52.14	52.22	52.16	52.06	52.28	52.07	52.29	52.33	52.10
12	51.96	51.80	52.06	52.12	52.22	52.18	52.10	52.27	52.07	52.28	52.36	52.11
13	51.97	51.81	52.08	52.14	52.24	52.18	52.13	52.25	52.09	52.26	52.30	52.13
14	52.00	51.80	52.11	52.15	52.24	52.18	52.11	52.23	52.11	52.25	52.28	52.13
15	52.00	51.80	52.09	52.14	52.23	52.19	52.06	52.20	52.13	52.21	52.33	52.15
16	51.97	51.81	52.10	52.14	52.22	52.17	52.05	52.25	52.12	52.19	52.30	52.15
17	51.97	51.80	52.10	52.15	52.24	52.16	52.08	52.23	52.08	52.16	52.30	52.16
18	51.96	51.78	52.12	52.17	52.26	52.19	52.12	52.23	52.07	52.15	52.34	52.15
19	51.94	51.78	52.13	52.17	52.25	52.23	52.15	52.22	52.09	52.14	52.35	52.15
20	51.91	51.79	52.16	52.18	52.24	52.24	52.17	52.18	52.06	52.19	52.38	52.07
21	51.87	51.81	52.16	52.16	52.25	52.21	52.17	52.20	52.07	52.20	52.38	52.04
22	51.83	51.82	52.23	52.20	52.28	52.22	52.19	52.24	52.12	52.27	52.39	52.03
23	51.80	51.84	52.20	52.22	52.32	52.22	52.24	52.18	52.15	52.29	52.40	52.04
24	51.79	51.85	52.16	52.24	52.37	52.19	52.32	52.09	52.13	52.46	52.40	52.06
25	51.79	51.89	52.15	52.23	52.34	52.19	52.31	52.05	52.12	52.47	52.23	51.95
26	51.80	51.89	52.17	52.21	52.35	52.20	52.24	52.04	52.15	52.47	52.24	51.92
27	51.81	51.92	52.21	52.22	52.35	52.19	52.22	52.05	52.19	52.46	52.24	51.92
28	51.84	51.94	52.23	52.26	52.34	52.19	52.21	52.06	52.20	52.46	52.22	51.97
29	51.83	51.92	52.23	52.24	52.33	52.20	52.18	52.04	52.18	52.41	52.19	52.03
30	51.83	51.91	52.19	52.24		52.22	52.15	52.05	52.16	52.34	52.16	52.08
31	51.82		52.20	52.22		52.20		52.07		52.30	52.16	
MRAN	51.89	51.82	52.08	52.17	52.24	52.20	52.16	52.18	52.05	52.26	52.33	52.09

WTR YR 1992 MEAN 52.12 HIGHEST 51.72 NOV. 1, 1991 LOWEST 52.50 JULY 28, 1992



WATER YEAR

RIO GRANDE DE MANATI BASIN

182757066325600. Local number, 206.
LOCATION.--Lat 18°27'57", long 66°32'56", Hydrologic Unit 21010002, 0.84 mi northwest of Barceloneta plaza, 0.64 mi west of Central Plazuela, and 1.96 mi southeast of Escuela Agustín Balseiro. Owner: P.R. Department of Agriculture, Name: Plazuela No. 2.

AQTICULTURE, Name: Platuela No. 2.
AQUIFER. --Aymamón Limestone.
WELL CHARACTERISTICS. --Drilled unused water-table well, diameter 16 in (0.41 m), cased 16 in (0.41 m) 0-85 ft
(0-25.9 m), open hole 85-101 ft (25.9-30.8 m). Depth 101 ft (30.8 m).
INSTRUMENTATION. --Digital water level recorder -- 60-minute punch.

DATUM.--Blevation of land-surface datum is about 7.0 ft (2.1 m) above mean sea level, from topographic map.

Measuring point: Hole on side of casing, 1.30 ft (0.40 m) above land-surface datum.

MEASURING POINT: Hole on side of casing, 1.30 ft (0.80 m) above land-surface datum.


REMARKS.--Recording observation well.

PERIOD OF RECORD.--October 1985 to current year.

EXTREMES FOR PERIOD OF RECORD.--Highest water level recorded, 3.75 ft (1.14 m) below land-surface datum, Sept. 11, 1988; lowest water level recorded, 5.89 ft (1.80 m) below land-surface datum, Apr. 11-12, 1990.

		WATER LEVI	BL, IN FRE				, WATER YE		1991	TO SEPTEMBER	1992	
DAY	OCT	NOV	DEC	jan	FEB	MAR	APR	MAY	JUN	JUL	λUG	SEP
1	5.19	5.00	5.10	5.42	5.45	5.52	5.44	5.45	5.36	5.55	5.58	
2	5.19	4.99	5.11	5.42	5.42	5.51	5.43	5.47	5.08	5.53	5.60	
3	5.18	4.99	5.10	5.41	5.41	5.48	5.44	5.52	5.08	5.48	5.64	
4	5.17	4.99	5.11	5.38	5.39	5.47	5.42	5.56	5.03	5.49	5.64	
5	5.16	4.99	5.12	5.37	5.36	5.46	5.40	5.56	5.10	5.50	5.66	
6	5.08	5.00	5.14	5.28	5.37	5.44	5.41	5.56	5.25	5.55	5.68	
7	5.09	5.01	5.16	5.25	5.34	5.42	5.45	5.56	5.31	5.60	5.68	
8	5.09	5.02	5.20	5.26	5.31	5.41	5.48	5.59	5.36	5.64	5.70	
9	5.12	5.06	5.22	5.29	5.36	5.40	5.44	5.62	5.42	5.66	5.71	
10	5.16	5.06	5.23	5.34	5.39	5.39	5.37	5.63	5.47	5.65	5.67	
11	5.18	5.08	5.23	5.34	5.42	5.40	5.35	5.62	5.50	5.65	5.63	
12	5.19	5.05	5.27	5.33	5.42	5.42	5.37	5.60	5.50	5.65	5.65	
13	5.22	5.06	5.29	5.33	5.44	5.43	5.41	5.57	5.52	5.64	5.63	
14	5.23	5.04	5.31	5.36	5.45	5.43	5.40	5.55	5.54	5.63	5.62	
15	5.23	5.05	5.30	5.36	5.45	5.43	5.35	5.51	5.57	5.63	5.65	
16	5.21	5.06	5.31	5.36	5.43	5.42	5.34	5.55	5.57	5.61	5.64	
17	5.20	5.04	5.31	5.37	5.45	5.42	5.37	5.56	5.53	5.57	5.64	
18	5.19	5.01	5.34	5.40	5.48	5.46	5.42	5.56	5.52	5.55	5.67	
19	5.18	5.02	5.36	5.40	5.47	5.50	5.44	5.56	5.52	5.55	5.67	
20	5.15	5.04	5.38	5.41	5.47	5.51	5.46	5.50	5.50	5.59	5.68	
21	5.13	5.08	5.39	5.42	5.48	5.48	5.48	5.52	5.52	5.60	5.68	
22	5.11	5.07	5.44	5.43	5.50	5.48	5.50	5.57	5.56	5.61	5.70	
23	5.08	5.07	5.41	5.46	5.52	5.47	5.55	5.48	5.59	5.62	5.70	
24	5.07	5.07	5.38	5.48	5.55	5.45	5.61	5.36	5.57	5.64	5.70	
25	5.07	5.10	5.36	5.46	5.55	5.45	5.61	5.30	5.56	5.65	5.65	5.13
26	5.07	5.10	5.38	5.44	5.55	5.46	5.55	5.19	5.57	5.66		5.12
27	5.09	5.11	5.41	5.44	5.56	5.44	5.53	5.30	5.58	5.65		5.11
28	5.10	5.13	5.45	5.48	5.56	5.45	5.54	5.47	5.58	5.65		5.16
29	5.09	5.12	5.45	5.48	5.55	5.46	5.51	5.48	5.57	5.63		5.21
30	5.08	5.11	5.42	5.49		5.48	5.45	5.49	5.56	5.63		5.26
31	5.06		5.42	5.47		5.47		5.51		5.59		
MRAN	5.14	5.05	5.29	5.39	5.45	5.45	5.45	5.51	5.45	5.60	5.66	5.16

WTR YR 1992 MEAN 5.40 HIGHEST 4.95 NOV. 1, 1991 LOWEST 5.72 AUG. 9, 1992



WATER YEAR

RIO GRANDE DE MANATI BASIN

182710066303700. Local number, 207.
LOCATION.--Lat 18°27'10", long 66°30'37", Hydrologic Unit 21010002, 1.92 mi east of Barceloneta plasa, 1.35 mi north of Central Monserrate, and 2.68 mi northeast of Escuela José Cordero. Owner: P.R. Aqueduct and Sewer Authority,

of Central Monserrate, and 2.68 mi northeast of Escueia Jose Coruero. Sensit.

Name: Cantito La Luisa.

AQUIFER. --Aymam[n Limestone.

WELL CHARACTERISTICS.--Drilled unused water-table well, diameter 20 in (0.51 m), cased 20 in (0.51 m) 0-30 ft (0-9.14 m), cased 10 in (0.25 m) 0-126 ft (0-38.4 m), perforated 80-126 ft (24.4-38.4 m). Depth 126 ft (38.4 m).

INSTRUMENTATION.--Digital water level recorder--60-minute punch.

DATUM.--Elevation of land-surface datum is about 59.0 ft (18.0 m) above mean sea level, from topographic map.

Measuring point: Hole on side of casing, 2.00 ft (0.61 m) above land-surface datum.


REMARKS.--Recording observation well.

DERITOD OF RECORD.--October 1985 to current year.

PERIOD OF RECORD. -- October 1985 to current year.

EXTREMES FOR PERIOD OF RECORD. -- Highest water level recorded, 36.38 ft (11.09 m) below land-surface datum, May 15, 1986; lowest water level recorded, 89.83 ft (27.38 m) below land-surface datum, Oct. 5, 1985.

		WATER LEV	EL, IN FE	et Below Inst	Land-Surf. Pantanbous	ACE DATUM OBSERVAT	, WATER Y ION AT 12	YEAR OCTOBE 200	R 1991 1	ro septemb	ER 1992	
DAY	OCT	NOV	DEC	JAN	FEB	MAR	APR	MAY	JUN	JUL	AUG	gep
1	39.93	39.65	39.83	40.06	40.07	40.32	40.18	40.14	39.82	40.16	40.22	39.95
2	39.92	39.60	39.84	40.08	40.08	40.32	40.17	40.13	39.81	40.16	40.21	39.94
3	39.91	39.60	39.85	40.09	40.07	40.30	40.18	40.13	39.81	40.16	40.22	39.95
4	39.91	39.61	39.86	40.07	40.02	40.23	40.18	40.14	39.69	40.16	40.22	39.92
5	39.91	39.63	39.88	40.06	39.97	40.21	40.18	40.16	39.70	40.16	40.21	39.90
6	39.89	39.65	39.90	39.84	39. 9 5	40.20	40.18	40.17	39.73	40.18	40.20	39.89
7	39.90	39.67	39.94	39.77	39.95	40.20	40.19	40.19	39.76	40.20	40.19	39.88
8	39.91	39.69	39.95	39.77	39.94	40.19	40.19	40.21	39.79	40.21	40.18	39.85
9	39.94	39.70	39.95	39.77	39.98	40.18	40.17	40.23	39.82	40.22	40.17	39.82
10	39.97	39.74	39.95	39.79	39.99	40.17	40.14	40.24	39.85	40.23	40.15	39.82
11	39.98	39.76	39.96	39.80	40.00	40.17	40.13	40.24	39.88	40.24	40.14	39.80
12	39.96	39.76	39.99	39.80	40.02	40.18	40.14	40.24	39.90	40.24	40.14	39.78
13	39.96	39.76	39.99	39.83	40.03	40.20	40.16	40.24	39.93	40.24	40.14	39.78
14	39.96	39.75	40.00	39.84	40.05	40.19	40.17	40.24	39. 9 7	40.24	40.13	39.78
15	39.98	39.75	40.00	39.84	40.07	40.19	40.16	40.22	40.00	40.25	40.13	39.77
16	39.98	39.76	40.00	39.86	40.08	40.19	40.15	40.24	40.03	40.24	40.12	39.78
17	39.98	39.77	40.00	39.89	40.10	40.19	40.15	40.24	40.04	40.23	40.12	39.79
18	39.98	39.75	40.01	39.93	40.12	40.19	40.16	40.24	40.04	40.21	40.12	39.78
19	39.99	39.75	40.03	39.94	40.14	40.19	40.14	40.27	40.06	40.21	40.11	39.77
20	39.98	39.76	40.06	39.95	40.16	40.19	40.14	40.24	40.06	40.21	40.10	39.72
21	39.96	39.77	40.04	39.96	40.17	40.19	40.16	40.23	40.06	40.21	40.10	39.67
22	39.94	39.78	40.04	39.99	40.18	40.20	40.18	40.25	40.08	40.22	40.09	39.60
23	39.91	39.79	40.02	40.01	40.19	40.17	40.19	40.20	40.10	40.23	40.07	39.56
24	39.88	39.78	40.01	40.03	40.21	40.15	40.22	40.08	40.10	40.23	40.08	39.53
25	39.87	39.79	39.99	40.04	40.21	40.15	40.23	40.04	40.10	40.23	40.03	39.50
26	39.86	39.80	39.99	40.05	40.23	40.16	40.23	39.85	40.10	40.23	40.01	39.48
27	39.86	39.80	40.00	40.04	40.27	40.17	40.23	39.80	40.12	40.23	40.00	39.49
28	39.85	39.82	40.02	40.04	40.31	40.18	40.23	39.78	40.14	40.23	40.00	39.50
29	39.82	39.83	40.04	40.05	40.32	40.18	40.21	39.79	40.14	40.22	39.97	39.53
30	39.79	39.83	40.04	40.07		40.19	40.17	39.81	40.15	40.22	39.95	39.55
31	39.75		40.05	40.06		40.19		39.83		40.21	39.95	
MEAN	39.92	39.74	39.98	39.95	40.10	40.20	40.18	40.12	39.96	40.21	40.11	39.74



WTR YR 1992 MEAN 40.02 HIGHEST 39.48 SEPT. 26-28, 1992 LOWEST 40.33 FEB. 29, MAR. 1-2, 1992

WATER YEAR

RIO GRANDE DE MANATI BASIN

182308066260400. Local number, 210.
LOCATION.--Lat 18°23'08", long 66°26'04", Hydrologic Unit 21010002, 4.88 mi southeast of Manati plaza, 5.24 mi southwest of Vega Baja plaza, and 2.25 mi west of Escuela Evaristo Camacho. Owner: Gelo Martínez, Name:

78.72

78.67

southwest of Vega Baja plaza, and 2.25 mi west of Escuela Evaristo Camacho. Owner: Gelo Martinez, Name: Gelo Martinez well.

AQUIFER.--Lares Limestone.

WELL CHARACTERISTICS.--Drilled unused water-table well, diameter 8 in (0.20 m), cased 8 in (0.20 m).

INSTRUMENTATION.--Digital water level recorder--60-minute punch.

DATUM.--Elevation of land-surface datum is about 574 ft (174.9 m) above mean sea level, from topographic map.

Measuring point: Hole on side of casing, 2.00 ft (0.61 m) above land-surface datum.

REMARKS.--Recording observation well.

PERIOD OF RECORD.--October 1985 to current year.


EXTREMES FOR PERIOD OF RECORD.--Highest water level recorded, 40.56 ft (12.36 m) below land-surface datum, May 22, 1986; lowest water level recorded, 83.01 ft (25.3 m) below land-surface datum, Sept. 29, 1992.

		WATER	LEVEL, IN					YEAR OCTOBER	1991	TO SEPTEMBER	1992	
				IN	ISTANTANEC	US OBSERVA	TION AT	1200				
DAY	OCT	NO	V DEC	C JAN	FEB	MAR	APR	MAY	JUN	JUL	AUG	SEP
1	78.28	79.1	6 78.79	5 79.22	79.22	79.82						
2	78.30	79.0			79.26	79.82						
3	78.33	78.8	9 78.79	9 79.25	79.30	79.84						
4	78.36	78.6		0 79.27	79.32	79.92						
5	78.38	78.4	7 78.8	1 79.29	79.35	79.96						
6	78.40	78.3		4 79.30	79.38	79.96						
7	78.43	78.3		7 79.29	79.39	79.98						
8	78.45	78.3			79.43	79.99						
9	78.48	78.3			79.48	79.99						
10	78.51	78.3	2 78.9	3 79.27	79.5 0	79.99						
11	78.54	78.3			79.51							
12	78.57	78.3			79.52							
13	78.60	78.4			79.57							
14	78.63	78.4			79.61							
15	78.66	78.5	4 79.0	5 79.08	79.66							
16	78.70	78.5		8 79.05	79.69							
17	78.73	78.6	5 79.13	2 79.03	79.69							
18	78.77	78.7		5 79.01	79.73							
19	78.80	78.7			79.74							
20	78.83	78.8	1 79.2	1 79.00	79.75							
21	78.87	78.8	7 79.2	2 79.00	79.76							
22	78.91	78.9	1 79.22	2 79.00	79.77							
23	78.94	78.9	4 79.20	79.01	79.77							
24	78.97	78.9	6 79.1	8 79.02	79.78							82.90
25	79. 0 0	78.9	3 79.1	7 79.04	79.78							82.91
26	79.04	78.8	6 79.1	7 79.06	79.78							82.92
27	79.09	78.8	0 79.1	7 79.08	79.79							82.92
28	79.13	78.7	8 79.1	7 79.10	79.80							82.92
29	79.18	78.7	6 79.1	8 79.13	79.82							83.00
30	79.22	78.7	5 79.10	8 79.16								
31	79.21		- 79.2	1 79.19								

79.93

WTR YR 1992 MRAN 79.22 HIGHEST 78.27 OCT. 1, 1991 LOWEST 83.01 SEPT. 29, 1992

79.59



RIO CIBUCO BASIN

182647066201700. Local number, 70.

LOCATION.--Lat 18026'47", long 66°20'17", Hydrologic Unit 21010002, 1.52 mi north of Vega Alta plaza, 4.78 mi southwest of Dorado plaza, and 2.01 mi northwest of Escuela Industrial para Mujeres. Owner: P.R. Aqueduct and Sewer Authority, Name: Sabana Hoyos.

AQUIFER.--Limestone of Tertiary Age.

Depth 90 ft (27.43 m).

INSTRUMENTATION. --Digital water level recorder--60-minute punch.

DATUM.--Elevation of land-surface datum is about 49 ft (14.9 m) above mean sea level, from topographic map.

Measuring point: Top of casing wooden cover, 1.30 ft (0.40 m) above land-surface datum.

REMARKS.--Recording observation well.


PERIOD OF RECORD. -- February 1960 to current year.

EXTREMES FOR PERIOD OF RECORD.--Highest water level recorded, 21.33 ft (6.50 m) below land-surface datum, Oct. 26, 1976; lowest water level recorded, 31.10 ft (9.48 m) below land-surface datum, July 31, 1975.

WATER LEVEL, IN FEST BELOW LAND-SURFACE DATUM, WATER YEAR OCTOBER 1991 TO SEPTEMBER 1992 INSTANMANEOUS OBSERVATION AT 1200

DAY	OCT	NOA	DEC	JAN	FEB	MAR	APR	MAY	JUN	JUL	λŪG	SEP
1	29.58	29.48	29.19	29.19	29.07	29.61	29.94	30.09	29.34	29.57	29.93	29.83
2	29.54	29.45	29.18	29.20	29.09	29.63	29.94	30.08	29.33	29.60	29.94	29.83
3	29.53	29.42	29.17	29.21	29.11	29.65	29.95	30.07	29.31	29.62	29.94	29.84
4	29.53	29.40	29.14	29.23	29.12	29.67	29.95	30.07	29.31	29.65	29.94	29.86
5	29.53	29.38	29.13	29.24	29.12	29.67	29.95	30.07	29.30	29.66	29.94	29.87
6	29.50	29.36	29.12	29.20	29.12	29.68	29.96	30.07	29.30	29.68	29.92	29.88
7	29.50	29.36	29.11	29.07	29.13	29.69	29.97	30.08	29.30	29.71	29.90	29.88
8	29.50	29.35	29.10	28.97	29.15	29.70	29.97	30.10	29.29	29.73	29.87	29.87
9	29.50	29.34	29.08	28.91	29.17	29.70	29.98	30.11	29.29	29.75	29.84	29.88
10	29.51	29.34	29.05	28.85	29.18	29.71	29.98	30.12	29.28	29.78	29.82	29.88
11	29.52	29.34	29.03	28.78	29.21	29.73	29.98	30.14	29.27	29.80	29.81	29.89
12	29.52	29.34	29.02	28.73	29.23	29.74	29.98	30.15	29.26	29.81	29.81	29.89
13	29.53	29.33	29.02	28.69	29.25	29.76	29.99	30.16	29.27	29.83	29.81	29.90
14	29.54	29.34	29.02	28.66	29.27	29.78	30.00	30.16	29.26	29.85	29.80	29.89
15	29.56	29.33	29.02	28.65	29.29	29.80	30.00	30.17	29.27	29.86	29.78	29.88
16	29.57	29.34	29.03	28.64	29.31	29.82	30.00	30.16	29.28	29.86	29.76	29.89
17	29.59	29.34	29.04	28.64	29.33	29.83	30.00	30.16	29.28	29.86	29.75	29.89
18	29.60	29.35	29.05	28.65	29.35	29.83	30.01	30.15	29.29	29.86	29.74	29.89
19	29.60	29.36	29.06	28.66	29.37	29.84	30.02	30.15	29.30	29.87	29.74	29.89
20	29.59	29.37	29.07	28.67	29.39	29.86	30.03	30.12	29.32	29.88	29.74	29.80
21	29.59	29.38	29.08	28.69	29.41	29.87	30.04	30.10	29.34	29.88	29.75	29.74
22	29.59	29.36	29.09		29.43	29.87	30.05	30.09	29.35	29.87	29.74	29.73
23	29.59	29.34	29.10		29.44	29.89	30.06	29.98	29.38	29.86	29.74	29.71
24	29.58	29.28	29.10		29.47	29.90	30.08	29.86	29.40	29.86	29.75	29.70
25	29.57	29.25	29.10		29.49	29.91	30.09	29.78	29.43	29.86	29.76	29.69
26	29.56	29.22	29.11		29.51	29.92	30.10	29.68	29.45	29.87	29.77	29.69
27	29.55	29.21	29.13		29.53	29.93	30.10	29.57	29.47	29.89	29.77	29.70
28	29.55	29.20	29.13		29.56	29.92	30.11	29.49	29.50	29.90	29.79	29.70
29	29.54	29.20	29.14	29.02	29.58	29.92	30.12	29.43	29.52	29.91	29.81	29.72
30	29.53	29.19	29.16	29.02		29.93	30.10	29.39	29.54	29.92	29.82	29.74
31	29.51		29.17	29.05		29.94		29.36		29.93	29.82	
MRAN	29.55	29.33	29.09	28.90	29.30	29.80	30.01	29.97	29.34	29.81	29.82	29.82

WTR YR 1992 MEAN 29.58 HIGHEST 28.64 JAN. 15-18, 1992 LOWEST 30.18 MAY 14-16, 1992



RIO CIBUCO BASIN

182615066235300. Local number, 211.
LOCATION.--Lat 18°26'15", long 66°23'53", Hydrologic Unit 21010002, 4.46 mi southeast of Manatí plaza, 5.48 mi southwest of Vega Baja plaza, and 1.22 mi east of Hwy 155 km 58.3. Owner: P.R. Aqueduct and Sewer Authority, Name: Rosario No. 2.
AQUIFER.--Aquada Limestone.

WELL CHARACTERISTICS.-Drilled unused water-table well, diameter 14 in (0.36 m) 0-200 ft (0-61.0 m), diameter 12 in (0.30 m) 200-250 ft (61.0-76.2 m), cased 12 in (0.30 m) 0-250 ft (0-76.2 m), perforated 210-250 ft (64.0-76.2 m), diameter 10 in (0.25 m) 250-270 ft (76.2-82.3 m), open hole; concrete sealed 0-200 ft (0-61.0 m). Depth 270 ft diameter 10 in (0.25 m, 2.5 m, (82.3 m).

(82.3 m).

INSTRUMENTATION.--Digital water level recorder--60-minute punch.

DATUM.--Rlevation of land-surface datum is about 215 ft (65.5 m) above mean sea level, from topographic map.

Measuring point: Hole on side of casing, 1.15 ft (0.35 m) above land-surface datum.

REMARKS.--RECORDING ODBETVACTION Well.


PERIOD OF RECORD.--October 1985 to current year.

EXTREMES FOR PERIOD OF RECORD.--Highest water level recorded, 191.29 ft (58.30 m) below land-surface datum, May 16, 1986; lowest water level recorded, 193.73 ft (59.0 m) below land-surface datum, May 15-23, 1992.

WATER LEVEL, IN FRET BELOW LAND-SURFACE DATUM, WATER YEAR OCTOBER 1991 TO SEPTEMBER 1992 INSTANTANEOUS OBSERVATION AT 1200

DAY	OCT	NOV	DEC	JAN	FRB	MAR	APR	MAY	JUN	JUL	λŪG	SEP
1	193.26	192.99	193.11	193.18	193.09	193.67	193.68	193.63	193.48	193.58	193.63	100 50
2	193.26	192.99	193.11	193.18	193.09	193.67	193.68	193.63	193.48			193.52
3	193.26	192.99	193.11	193.18	193.09	193.67	193.68	193.60	193.48	193.64 193.64	193.63	193.50
4	193.26	192.99	193.11	193.18	193.08	193.67	193.68	193.60	193.42	193.63	193.63 193.62	193.49
5	193.26	192.99	193.12	193.17	193.06	193.67	193.67	193.60	193.42			193.49
			220125	133.17	173.00	133.07	193.07	193.63	193.42	193.62	193.62	193.50
6	193.26	193.00	193.12	193.15	193.05	193.67	193.67	193.66	193.42	193.62	193.62	193.50
7	193.26	193.00	193.13	193.06	193.03	193.67	193.67	193.66	193.42	193.65	193.62	193.50
8	193.26	193.00	193.15	193.03	193.03	193.66	193.67	193.67	193.42	193.65	193.62	193.50
9	193.26	193.00	193.15	193.03	193.02	193.66	193.68	193.70	193.42	193.65	193.62	193.48
10	193.26	193.01	193.15	193.03	193.02	193.65	193.67	193.70	193.42	193.64	193.61	193.48
11	193.26	193.02	193.15	100 00								
12	193.26	193.02		193.03	193.03	193.65	193.66	193.70	193.43	193.66	193.58	193.48
13	193.26	193.02		193.03	193.03	193.65	193.66	193.70	193.43	193.66	193.58	193.47
14	193.27	193.04		193.02	193.04	193.66	193.66	193.72	193.43	193.67	193.58	193.46
15	193.28	193.04		193.01	193.05	193.66	193.66	193.72	193.44	193.68	193.58	193.45
13	193.46	193.04		193.02	193.06	193.66	193.66	193.72	193.45	193.68	193.58	193.44
16	193.28	193.05		193.01	193.07	193.66	193.66	193.73	193.45	193.68	193.57	193.44
17	193.29	193.06		193.02	193.07	193.66	193.66	193.73	193.47	193.67	193.57	193.45
18	193.28	193.06		193.04	193.07	193.66	193.65	193.73	193.47	193.67	193.57	193.45
19	193.28	193.09		193.06	193.09	193.66	193.65	193.73	193.47	193.65	193.57	193.45
20	193.28	193.09		193.07	193.11	193.67	193.65	193.73	193.47	193.65	193.57	193.45
21	193.28	193.10		193.07	193.12	193.68	193.66	193.73	193.47	193.65	193.57	193.29
22	193.28	193.10		193.07	193.12	193.68	193.66	193.73	193.47	193.65	193.56	193.29
23	193.24	193.10		193.07		193.68	193.66	193.73	193.50	193.64	193.57	193.29
24	193.24	193.10	193.15	193.09	193.59	193.68	193.69	193.67	193.51	193.64	193.57	193.28
25	193.20	193.10	193.14	193.10	193.59	193.68	193.70	193.62	193.53	193.64	193.57	193.28
26	193.19	193.10	193.14	193.10	193.60	193.68	193.70	193.51	193.54	193.64	193.57	193.29
27	193.18	193.10	193.14	193.09	193.66	193.68	193.70	193.49	193.55	193.64		
28	193.18	193.11	193.13	193.09	193.66	193.68	193.70	193.49	193.55	193.64	193.56	193.29
29	193.17	193.11	193.14	193.09	193.67	193.68	193.70	193.48			193.55	193.30
30	193.06	193.11	193.13	193.09	193.67	193.68	193.70		193.57	193.63	193.55	193.33
31	193.01		193.17	193.09		193.68		193.48	193.58	193.63	193.54	193.41
			420.41	133.03		133.68		193.48		193.63	193.52	
MBYN	193.24	193.05	193.13	193.08	193.19	193.67	193.67	193.65	193.47	193.65	193.58	193.42

WTR YR 1992 MEAN 193.41 HIGHEST 192.99 NOV. 1-5, 1991 LOWEST 193.73 MAY 16-23, 1992



WATER YEAR

MRAN

70.02

69.72

69.36

GROUND-WATER LEVELS

RIO CIBUCO BASIN

182515066194000. Local number, 212.

LOCATION.--Lat 1825'15', long 66919'40", Hydrologic Unit 21010002, 5.15 mi southwest of Dorado plaza, 0.49 mi north of Vega Alta plaza, and 1.04 mi northwest of Escuela Industrial para Mujeres. Owner: U.S. Geological Survey, WRD, Name: Ponderosa TW-1.

AQUIFER.--Aguada Limestone-Cibao Formation.

WELL CHARACTERISTICS.--Drilled unused water-table well, diameter 4 in (0.10 m), cased 4 in (0.10 m) 0-136 ft (0-41.1 m), perforated 121-131 ft (36.9-39.9 m); bentonite packed 0.5-121 ft (0.15-36.9 m).

Depth 136 ft (39.9 m).

INSTRUMENTATION.--Digital water level recorder--60-minute punch.

DATUM.--Elevation of land-surface datum is about 98.0 ft (29.9 m) above mean sea level, from topographic map.

Measuring point: Shelter floor on top of 4 in (0.10 m) casing, 3.00 ft (0.91 m) above land-surface datum.

REMARKS.--Recording observation well. Water levels affected by nearby pumping well.

PERIOD OF RECORD.--October 1985 to current year.


EXTREMES FOR PERIOD OF RECORD.--Highest water level recorded, 63.05 ft (19.22 m) below land-surface datum, July 15, 1987; lowest water level recorded, 74.63 ft (22.75 m) below land-surface datum, Oct. 27-28, 1986.

		WATER LEV	EL, IN F	BET BELOW INST	Land-Surf Antaneous				BR 1991 T	O SEPTEME	ER 1992	
DAY	ост	NOV	DEC	JAN	FRB	MAR	APR	MAY	JUN	JUL	AUG	SEP
1	69.95	69.98	69.53	69.32		69.65	70.21	70.49	69.42	69.25	69.77	69.67
2	69.96	69.95	69.52	69.32		69.66	70.22	70.50	69.38	69.26	69.78	69.70
3	69.96	69.92	69.52	69.32		69.68	70.24	70.51	69.35	69.31	69.79	69.71
4	69.96	69.90	69.50	69.33		69.73	70.24	70.52	69.31	69.33	69.80	69.72
5	69.97	69.88	69.50	69.34		69.75	70.25	70.50	69.25	69.36	69.82	69.73
6	69.97	69.86	69.49	69.34		69.76	70.25	70.51	69.25	69.38	69.80	69.74
7	69.97	69.84	69.48	69.34		69.76	70.25	70.52	69.25	69.49	69.78	69.79
8	69.98	69.82	69.44	69.33		69.79	70.26	70.53	69.23	69.51	69.71	69.80
9	69.98	69.80	69.43	69.31		69.81	70.25	70.53	69.19	69.55	69.67	69.80
10	69.98	69.78	69.42	69.30		69.84	70.27	70.54	69.17	69.57	69.66	69.82
11	69.98	69.75	69.41	69.25		69.86	70.28	70.55	69.14	69.60	69.63	69.83
12	69.98	69.74	69.39	69.24		69.86	70.28	70.56	69.12	69.65	69.63	69.84
13	69.99	69.72	69.39	69.24		69.88	70.29	70.56	69.11	69.69	69.63	69.85
14	69.99	69.70	69.35	69.23		69.90	70.29	70.58	69.11	69.70	69.62	69.87
15	70.00	69.68	69.31	69.23		69.92	70.30	70.61	69.11	69.71	69.60	69.89
16	70.02	69.65	69.29	69.19		69.95	70.32	70.62	69.11	69.75	69.59	69.91
17	70.02	69.65	69.29	69.15		69.97	70.33	70.62	69.11	69.78	69.59	69.91
18	70.03	69.64	69.27	69.10		69.99	70.35	70.62	69.11	69.79	69.59	69.91
19	70.04	69.64	69.27	69.06		70.02	70.35	70.62	69.11	69.79	69.59	69.91
20	70.06	69.63	69.27	69.00		70.03	70.36	70.59	69.11	69.79	69.59	69.85
21	70.07	69.63	69.27	68.92		70.05	70.37	70.49	69.10	69.80	69.60	69.75
22	70.08	69.62	69.26	68.89		70.06	70.37	70.43	69.11	69.78	69.60	69.67
23	70.08	69.62	69.26	68.84		70.08	70.38	70.33	69.12	69.79	69.61	69.64
24	70.09	69.62	69.27	68.80	69.52	70.09	70.39	70.22	69.13	69.79	69.61	69.61
25	70.09	69.60	69.27	68.76	69.54	70.10	70.41	70.09	69.14	69.79	69.61	69.58
26	70.09	69.60	69.27	68.73	69.54	70.12	70.43	70.01	69.16	69.77	69.62	69.56
27	70.08	69.58	69.27	68.69	69.57	70.14	70.47	69.89	69.17	69.76	69.62	69.56
28	70.08	69.57	69.28	68.65	69.59	70.17	70.47	69.79	69.19	69.76	69.64	69.54
29	70.07	69.57	69.28		69.63	70.18	70.48	69.71	69.20	69.76	69.66	69.55
30	70.06	69.55	69.28			70.19	70.48	69.62	69.23	69.77	69.66	69.56
31	70.00		69.29			70.20		69.51		69.77	69.66	

WTR YR 1992 MEAN 69.74 HIGHEST 68.62 JAN. 29, 1992 LOWEST 70.62 MAY 15-19, 1992

69.56

69.11



69.94

70.33

69.64

70.36

69.18

69.66

RIO CIBUCO BASIN

182330066185700. Local number, 213.
LOCATION.--Lat 18°23'30", long 66°18'57", Hydrologic Unit 21010002, 1.82 mi southeast of Vega Alta plaza, 4.23 mi west of Toa Alta plaza, and 1.27 mi northwest off the intersection of Hwy 820 with Hwy 823. Owner: P.R. Aqueduct and Sewer Authority, Name: Pampano No. 2. AQUIFER. -- Rio Indio Limestone-Lares Limestone.

WELL CHARACTERISTICS. -- Drilled unused water-table well, diameter 20 in (0.51 m), cased 20 in (0.51 m) 0-130 ft (0-39.6 m), diameter 14 in (0.36 m), cased 12 in (0.30 m) 0-220 ft (0-67.1 m); open hole 220-330 ft (67.6-100.6 m). Depth 330 ft (100.6 m).

INSTRUMENTATION. --Digital water level recorder--60-minute punch.

DATUM. --Elevation of land-surface datum is about 394 ft (120 m) above mean sea level, from topographic map.

Measuring point: Hole on side of casing, 2.95 ft (0.90 m) above land-surface datum.

REMARKS.--Recording observation well.


PERIOD OF RECORD.--October 1985 to current year.

EXTREMES FOR PERIOD OF RECORD.--Highest water level recorded, 34.40 ft (10.50 m) below land-surface datum, Dec. 6, 1985; lowest water level recorded, 60.70 ft (18.5 m) below land-surface datum, Sept. 6, 1992.

WATER LEVEL, IN FRET BELOW LAND-SURFACE DATUM, WATER YEAR OCTOBER 1991 TO SEPTEMBER 1992 INSTANTANEOUS OBSERVATION AT 1200

DAY	OCT	NOV	DRC	JAN	FRB	MAR	APR	MAY	JUN	JUL	AUG	SEP
1	56.52	56.73	56.13	56.12		54.72	56.16	57.24	55.88	58.92	60.17	60.49
2	56.57	56.69	56.13	56.11		54.74	56.18	57.32	55.76	58.95	60.22	60.54
3	56.67	56.63	56.13	56.16		54.75	56.23	57.30	55.74	58.98	60.23	60.56
4	56.72	56.56	56.12	56.18		54.80	56.31	57.32	56.33	59.02	60.23	60.61
5	56.77	56.53	56.14	56.24		54.87	56.34	57.35	56.61		60.35	60.61
6	56.77	56.50	56.14	56.09		54.91	56.40	57.38	56.81		60.35	60.68
7	56.66	56.50	56.13	55.92		54.95	56.43	57.41	56.94	59.05	60.36	60.64
8	56.76	56.48	56.14	55.79		54.98	56.43	57.43	57.07	58.94	60.36	60.62
9	56.77	56.46	56.14	55.69		55.01	56.46	57.50	57.18	59.11	60.36	60.66
10	56.80	56.44	56.14	55.55		55.04	56.51	57.50	57.30	59.21	60.32	60.62
11	56.95	56.43	56.15	55.33		55.10	56.55	57.51	57.42	59.30	60.33	60.61
12	56.96	56.42	56.16	55.25		55.18	56.60	57.51	56.80	59.35	60.33	60.61
13	56.98	56.38	56.15	55.07		55.23	56.64	57.53	56.78	59.44	60.32	60.60
14	56.95	56.39	56.14	54.94		55.30	56.70	57.57	57.22	59.50	60.29	60.58
15	56.86	56.38	56.12	54.88		55.34	56.72	57.61	57.43	59.58	60.20	60.59
16	56.87	56.35	56.13	54.74		55.41	56.78	57.57	57.43	59.72	60.21	60.60
17	57.04	56.33	56.14	54.69		55.56	56.83	57.60	57.60	59.75	60.26	60.61
18	57.17	56.34	56.15	54.60		55.60	56.84	57.54	57.80	59.80	60.30	60.61
19	57.20	56.37	56.16	54.54		55.60	56.85	57.49	57.90	59.83	59.66	60.63
20	57.21	56.34	56.18	54.47		55.60	56.87	57.45	58.02	59.83	59.31	60.57
21	57.37	56.34	56.21	54.39		55.63	56.91	57.32	58.07	59.82	59.15	60.44
22	57.35	56.33	56.13	54.35		55.75	56.96	57.25	58.18	59.86	59.03	60.30
23	57.29	56.29	56.10	54.33		55.75	56.98	57.15	58.24	59.97	59.60	60.24
24	57.30	56.25	56.19	54.31	54.47	55.79	56.97	57.03	58.31	59.97	59.80	60.17
25	57.37	56.20	56.10	54.28	54.48	55.80	57.01	56.85	58.40	60.00	60.00	60.13
26	57.53	56.15	56.10	54.26	54.52	55.81	57.07	56.71	58.54	59.82	60.13	60.09
27	57.40	56.16	56.10	54.26	54.56	55.92	57.12	56.56	58.61	60.04	60.24	60.04
28	57.02	56.14	56.08	54.24	54.60	56.00	57.13	56.38	58.76	60.05	60.33	60.02
29	56.89	56.13	56.08		54.61	56.02	57.15	56.23	58.78	60.07	60.36	59.99
30	56.82	56.13	56.09			56.06	57.21	56.08	58.83	60.12	60.38	60.00
31	56.78		56.11			56.11		55.99		60.13	60.41	
MRAN	56.98	56.38	56.13	55.10	54.54	55.40	56.71	57.18	57.49	59.59	60.12	60.45

WTR YR 1992 MRAN 57.36 HIGHEST 54.15 JAN. 29, 1992 LOWEST 60.70 SEPT. 6, 1992



RIO DE LA PLATA BASIN

182746066170800. Local number, 214.
LOCATION.--Lat 18°27'46", long 66°17'08", Hydrologic Unit 210100002, 1.58 mi west of Dorado plaza, 0.59 mi southeast of Dorado Airport main gate, and 3.76 mi north of Hwy 2 km 25.2. Owner: Dorado Beach Hotel, Name: Dorado Beach No. 7.

AQUIFER. -- Aymam[n Limestone.

WELL CHARACTERISTICS. -- Drilled water-table well, diameter 18 in (0.46 m). Depth 100 ft (30.5 m).
INSTRUMENTATION. -- Digital water level recorder -- 60-minute punch.
DATUM. -- Elevation of land-surface datum is about 26.0 ft (8.0 m) above mean sea level, from topographic map. Prior to this report, elevation incorrectly used was 39.0 ft (11.9 m). Measuring point: Hole on side of casing, 1.10 ft

(0.34 m) above land-surface datum.

REMARKS.--Recording observation well. Water levels affected by nearby pumping well.


PERIOD OF RECORD.-- November 1985 to current year.

EXTREMES FOR PERIOD OF RECORD.--Highest water level recorded, 18.23 ft (5.56 m) below land-surface datum, Nov. 16, 1985; lowest water level recorded, 20.68 ft (6.30 m) below land-surface datum, May 16, 1992.

WATER LEVEL, IN FEET BELOW LAND-SURFACE DATUM, WATER YEAR OCTOBER 1991 TO SEPTEMBER 1992 INSTANTANEOUS OBSERVATION AT 1200

	INSTANTANEOUS OBSERVATION AT 1200													
DAY	OCT	Nov	DEC	JAN	FEB	MAR	APR	MAY	JUN	JUL	AUG	SEP		
1	20.17	19.91	19.85	20.04	20.15	20.41			20.13	20.25	20.38	20.26		
2	20.12	19.90	19.87	20.06	20.14	20.40			20.09	20.25	20.42	20.25		
3	20.08	19.91	19.85	20.05	20.14	20.36			20.07	20.23	20.41	20.29		
4	20.05	19.90	19.81	20.01	20.08	20.34			20.07	20.23	20.39	20.35		
5	19.98	19.89	19.79	20.04	20.05	20.35			20.07	20.25	20.41	20.33		
6	19.95	19.90	19.80	19.23	20.07	20.34			20.11	20.34	20.43	20.31		
7	19.97	19.92	19.83	19.29	20.08	20.33			20.13	20.43	20.41	20.29		
. 8	19.98	19.93	19.91	19.61	20.07	20.32			20.12	20.47	20.39	20.23		
9	20.05	19.95	19.92	19.76	20.13	20.29			20.09	20.49	20.35	20.21		
10	20.11	19.98	19.91	19.81	20.15	20.27			20.08	20.48	20.29	20.23		
11	20.14	19.99	19.91	19.78	20.19	20.30			20.03	20.48	20.24	20.23		
12	20.15	19.94	19.93	19.78	20.20	20.35			20.02	20.48	20.28	20.23		
13	20.16	19.95	19.92	19.79	20.21	20.37			20.05	20.44	20.27	20.24		
14	20.17	19.92	19.92	19.81	20.22	20.38			20.08	20.41	20.24	20.24		
15	20.18	19.92	19.91	19.82	20.24	20.38			20.10	20.40	20.24	20.27		
16	20.16	19.93	19.89	19.86	20.23	20.38		20.58	20.10	20.41	20.21	20.29		
17	20.18	19.91	19.90	19.91	20.26	20.37		20.56	20.08	20.39	20.23	20.31		
18	20.17	19.89	19.93	19.94	20.26	20.39		20.53	20.08	20.36	20.28	20.32		
19	20.12	19.91	19.94	19.95	20.27	20.43		20.52	20.11	20.38	20.29	20.36		
20	20.09	19.92	19.98	20.01	20.30	20.45		20.55	20.09	20.42	20.28	20.31		
21	20.08	19.98	19.95	20.01	20.32	20.42		20.52	20.14	20.40	20.29	20.24		
22	20.07	19.91	19.98	20.05	20.33	20.43		20.55	20.16	20.42	20.33	20.20		
23	20.06	19.88	19.97	20.07	20.35	20.38		20.42	20.19	20.44	20.32	20.15		
24	20.05	19.87	19.96	20.10	20.38	20.37		20.27	20.18	20.44	20.33	20.16		
25	20.07	19.87	19.96	20.09	20.36	20.39		20.21	20.17	20.49	20.27	20.12		
26	20.07	19.86	19.99	20.06	20.40	20.42		20.16	20.19	20.49	20.22	20.15		
27	20.10	19.88	20.01	20.07	20.41	20.42		20.08	20.25	20.45	20.21	20.19		
28	20.11	19.89	20.02	20.11	20.42	20.42		20.14	20.27	20.44	20.22	20.23		
29	20.07	19.87	20.03	20.12	20.40	20.41		20.16	20.26	20.40	20.21	20.28		
30	20.03	19.87	20.03	20.15		20.41		20.16	20.25	20.37	20.22	20.31		
31	19.98		20.04	20.15		20.41		20.18		20.36	20.22			
MBAN	20.09	19.91	19.93	19.92	20.23	20.38		20.35	20.13	20.40	20.30	20.25		

WTR YR 1992 MRAN 20.16 HIGHEST 19.03 JAN. 6, 1992 LOWEST 20.68 MAY 16, 1992



RIO DE LA PLATA BASIN

182530066135400. Local number, 216.
LOCATION.--Lat 18°25'30°, long 66°13'54°, Hydrologic Unit 21010005, 2.61 mi northeast of Toa Alta plasa, 2.73 mi southwest of Sabana Seca U.S. Naval Radio Station, and 1.76 mi southeast of Hwy 2 km 17.7. Owner: P.R. Aqueduct and Sewer Authority, Name: Pozo Navy-Campanillas.

AQUIFER . - - Aguada Limestone.

AQUIFER.--Aquada Limestone.

WELL CHARACTERISTICS.--Drilled unused water-table well, diameter 16 in (0.41 m) 0-106 ft (0-32.3 m), cased 16 in (0.41 m) 0-20 ft (0-6.10 m), cased 12 in (0.30 m) 0-106 ft (0-32.3 m), perforated 20-106 ft (6.10-32.3 m), diameter 10 in (10.25 m) 106-140 ft (32.3-42.7 m), cased 10 in (0.25 m) 106-140 ft (32.3-42.7 m), perforated 106-140 ft (32.3-42.7 m). Depth 140 ft (42.7 m).

INSTRUMENTATION.--Digital water level recorder--60-minute punch.

DATUM.--Elevation of land-surface datum is about 13.0 ft (3.96 m) above mean sea level, from topographic map.


REMARKS.--Recording observation well.

REMARKS.--Recording observation well.
PERIOD OF RECORD.--October 1985 to current year.
EXTREMES FOR PERIOD OF RECORD.--Highest water level recorded, 9.38 ft (2.86 m) below land-surface datum, June 23, 1987; lowest water level recorded, 14.72 ft (4.49 m) below land-surface datum, Apr. 28, 1986.

WATER LEVEL, IN FEET BELOW LAND-SURFACE DATUM, WATER YEAR OCTOBER 1991 TO SEPTEMBER 1992 INSTANTANEOUS OBSERVATION AT 1200

DAY	OCT	NOV	DBC	JAN	FRB	MAR	APR	MAY	JUN	JUL	AUG	SEP
1				13.31	13.00	13.52	13.76	14.41	13.03	13.27	13.27	12.70
2				13.35	12.43	13.41	13.83	14.26	12.99	13.43	13.27	12.71
3				13.35	12.77	13.40	13.87	14.22	13.02	13.49	13.17	12.73
4				13.35	12.72	13.41	14.00	14.21	13.05	13.55	13.06	12.79
5				13.54	12.74	13.43	14.11	14.22	13.08	13.56	12.99	12.74
6				11.84	12.82	13.45	14.01	14.20	13.12	13.46	12.92	12.86
7				11.95	12.90	13.49	14.00	14.20	13.15	13.64	12.92	12.89
8				12.24	12.95	13.51	13.99	14.24	13.06	13.69	12.87	
9				12.37	13.06	13.49	14.02	14.27	12.18	13.72	12.92	
10				12.30	12.99	13.49	14.00	14.30	12.67	13.77	12.90	
11				12.26	12.96	13.50	14.02	14.26	12.51	13.80	12.94	
12				12.37	12.97	13.55	14.03	14.27	12.59	13.85	12.93	
13				12.38	13.01	13.63	14.02	14.28	12.67	13.87	12.73	
14				12.38	13.04	13.68	14.03	14.30	12.69	13.83	12.51	
15				12.41	13.11	13.71	14.06	14.34	12.73	13.80	12.45	
16				12.44	13.11	13.71	14.08	14.31	12.65	13.77	12.48	
17				12.43	13.13	13.74	14.10	14.20	12.74	13.72	12.50	
18				12.54	13.14	13.75	14.15	14.18	12.78	13.73	12.52	
19				12.59	13.15	13.77	14.26	14.16	12.84	13.73	12.53	
20			12.99	12.66	13.17	13.80	14.31	14.11	12.89	13.75	12.55	
21			13.02	12.66	13.21	13.84	14.12	14.13	12.89	13.42	12.53	
22			13.01	12.43	13.21	13.83	14.11	13.61	12.86	13.21	12.58	
23			13.02	12.71	13.23	13.85	14.21	13.33	12.95	13.27	12.59	
24			13.05	12.75	13.23	13.86	14.26	12.78	12.99	13.29	12.75	12.94
25			13.07	12.78	13.24	13.88	14.35	12.99	13.02	13.13	12.63	12.96
26			13.09	12.83	13.27	13.91	14.35	13.08	13.06	13.27	12.22	13.02
27			13.16	12.85	13.31	13.86	14.36	12.85	13.11	13.30	12.47	13.06
28			13.18	12.88	13.35	13.97	14.38	12.93	13.15	13.24	12.53	13.00
29			13.18	12.89	13.37	13.84	14.00	13.01	13.18	13.22	12.69	12.97
30			12.96	12.90		13.74	14.31	12.97	13.23	13.24	12.75	12.98
31			13.28	12.94		13.70		13.00		13.26	12.70	
MEAN			13.08	12.67	13.05	13.67	14.10	13.86	12.90	13.53	12.74	12.88

WTR YR 1992 MEAN 13.28 HIGHEST 11.84 JAN. 6, 1992 LOWEST 14.51 APR. 27, 1992



RIO DE LA PLATA BASIN

182655066142400. Local number, 217.

LOCATION.--Lat 18°26'55", long 66°14'24", Hydrologic Unit 21010005, 4.00 mi northeast of Toa Alta plaza, 3.40 mi northwest of Hwy 2 km 17.7, and 3.49 mi northwest of Sabana Seca U.S. Naval Radio Station. Owner: U.S. Geological Survey, WRD, Name: Monserrate TW-2.

AQUIFER.-Alluvial Deposits.

AQUIFER.-Alluvial Deposits.

WELL CHARACTERISTICS.--Drilled unused water-table well, diameter 4 in (0.10 m), cased 4 in (0.10 m) 0-80 ft (0-24.4 m), perforated 10-80 ft (3.05-24.4 m). Depth 80 ft (24.4 m).

INSTRUMENTATION.--Digital water level recorder--60-minute punch.

DATUM.--Elevation of land-surface datum is about 3.30 ft (1.00 m) above mean sea level, from topographic map. Measuring point: Top of shelter floor, 3.50 ft (1.07 m) above land-surface datum.


REMARKS.--Recording observation well.

PERIOD OF RECORD. --November 1985 to current year.

EXTREMES FOR PERIOD OF RECORD.--Highest water level recorded, 0.02 ft (0.006 m) below land-surface datum, May 16, 1986; lowest water level recorded, 2.28 ft (0.69 m) below land-surface datum, May 16, 1992.

		WATER LEVI	RL, IN FRE		Land-Surfi Antanbous				1991	TO SEPTEMBER	1992	
DAY	OCT	NOA	DEC	JAN	PEB	MAR	APR	MAY	JUN	JUL	AUG	SEP
1	1.62	1.48	1.29	1.60		1.63	1.76	1.99	1.46	1.64	1.57	1.94
2	1.52	1.41	1.30	1.59		1.63	1.77	1.97	1.38	1.63	1.57	1.93
3	1.49	1.39	1.24	1.58		1.58	1.79	1.98	1.39	1.61	1.49	1.98
4	1.45	1.36	1.23	1.57		1.54	1.80	2.02	1.41	1.66	1.47	2.05
5	1.40	1.35	1.21	1.60		1.56	1.81	2.08	1.42	1.69	1.52	2.05
6	1.38	1.34	1.22			1.57	1.83	2.04	1.45	1.80	1.52	2.05
7	1.39	1.37	1.25			1.60	1.82	2.07	1.47	1.89	1.52	2.03
8	1.44	1.36	1.29	. 64		1.62	1.81	2.11	1.41	1.93	1.47	2.01
9	1.51	1.35	1.29	.90		1.60	1.81	2.17	1.20	1.95	1.45	2.02
10	1.55	1.38	1.25	.91		1.57	1.78	2.18	1.27	1.95	1.42	2.04
11	1.58	1.39	1.29	.93		1.60	1.79	2.18	1.14	1.95	1.35	2.07
12	1.62	1.37	1.32	. 95		1.67	1.78	2.17	1.18	1.95	1.38	2.06
13	1.65	1.38	1.34	1.02		1.73	1.82	2.16	1.25	1.94	1.38	2.06
14	1.66	1.38	1.36	1.12		1.78	1.80	2.19	1.30	1.89	1.34	2.06
15	1.67	1.41	1.39	1.17		1.80	1.77	2.22	1.34	1.87	1.26	2.09
16	1.68	1.44	1.42	1.21		1.82	1.75	2.28	1.32	1.87	1.24	2.11
17	1.70	1.46	1.45	1.23		1.81	1.79	2.16	1.33	1.85	1.31	2.13
18	1.71	1.47	1.46	1.25		1.79	1.85	2.16	1.34	1.79	1.37	2.13
19	1.67	1.51	1.48	1.28		1.81	1.88	2.10	1.37	1.80	1.39	2.15
20	1.66	1.51	1.50	1.32		1.83	1.91	2.05	1.39	1.86	1.41	2.01
21	1.66	1.55	1.47	1.38		1.83	1.95	2.08	1.43	1.74	1.43	1.97
22	1.66	1.34	1.49	1.43		1.85	1.97	2.06	1.44	1.64	1.47	1.97
23	1.64	1.26	1.47	1.46		1.82	2.00	1.77	1.48	1.68	1.48	1.94
24	1.60	1.20	1.47	1.49		1.81	2.03	1.44	1.50	1.69	2.00	1.90
25	1.60	1.22	1.47	1.50		1.84	2.07	1.38	1.52	1.67	1.95	1.90
26	1.59	1.25	1.48	1.48		1.88	2.08	1.34	1.57	1.68	1.94	1.94
27	1.63	1.30	1.52			1.89	2.12	1.22	1.63	1.69	1.93	1.97
28	1.66	1.29	1.56			1.90	2.12	1.32	1.66	1.59	1.95	2.02
29	1.62	1.26	1.58		1.61	1.74	2.05	1.37	1.66	1.52	1.95	2.06
30	1.60	1.29	1.58			1.75	2.04	1.43	1.64	1.53	1.94	2.09
31	1.56		1.58			1.75		1.49		1.54	1.94	
MEAN	1.59	1.37	1.40	1.28	1.61	1.73	1.88	1.91	1.41	1.76	1.56	2.02

WTR YR 1992 MEAN 1.63 HIGHEST 0.64 JAN. 8, 1992 LOWEST 2.28 MAY 16, 1992



GROUND-WATER RECORDS

RIO HONDO TO RIO PUERTO NUEVO BASINS

182623066111000. Local number, 218.

LOCATION.--Lat 18°26'23", long 66°11'10", Hydrologic Unit 21010005, 3.30 mi northwest of Bayamón plaza, 1.78 mi south of Hwy 165 km 26.5, and 2.38 mi northeast of Hwy 2 km 16.2. Owner: P.R. Aqueduct and Sewer Authority, Name: Levittown No. 7.

AQUIFER.--Alluvial deposits-Aymam[n Limestone.

WELL CHARACTERISTICS.--Drilled water-table well.

INSTRUMENTATION.--Digital water level recorder--60-minute punch.

DATUM.--Elevation of land surface datum is about 10.0 ft (3.05 m) above mean sea level, from topographic map.

Measuring point: Hole on pump base, 1.55 ft (0.47 m) above land-surface datum.


REMARKS.--Recording observation well. Water levels affected by nearby pumping well.

PERIOD OF RECORD.--October 1985 to current year.

EXTREMES FOR PERIOD OF RECORD.--Highest water level recorded, 5.94 ft (1.81 m) below land-surface datum, Sept. 20, 1989; lowest water level recorded, 9.77 ft (2.98 m) below land-surface datum, Mar. 23, 1986.

		WATER LEVE	L, IN FRE				, WATER YI ION AT 120		R 1991 '	TO SEPTEMBER	1992	
DAY	OCT	NOV	DEC	JAN	FEB	MAR	APR	MAY	JUN	JUL	AUG	SEP
1	7.76	7.67	7.46	7.73	7.51	7.60	8.71	8.67	8.31	7.77	7.72	7.70
2	7.71	7.61	7.46	7.72	7.53	7.60	8.72	8.67	8.22	7.80	7.73	7.79
3	7.66	7.52	7.43	7.74	7.52	7.60	8.72	8.87	8.24	7.90	7.49	7.86
4	7.64	7.49	7.42	7.75	7.51	7.60	8.74	8.88	8.26	7.9 9	7.77	8.14
5	7.58	7.46	7.42	7.76	7.51	7.94	8.75	8.88	8.25	8.02	7.82	7.86
6	7.53	7.44	7.42	7.37	7.54	8.05	8.75	8.89	8.12	7.89	7.95	8.12
7	7.53	7.46	7.43	7.14	7.57	8.22	8.55	8.90	8.10	8.07	7.83	8.15
8	7.53	7.45	7.41	7.11	7.59	8.11	8.54	8.94	8.05	8.18	7.80	8.14
9	7.53	7.29	7.44	7.16	7.60	8.12	8.53	8.91	7.83	8.25	7.78	8.11
10	7.48	7.29	7.43	7.12	7.63	8.14	8.52	8.96	7.78	8.23	7.76	8.13
11	7.49	7.27	7.43	7.10	7.67	8.18	8.53	8.95	7.70	8.32	7.69	8.13
12	7.56	7.34	7.46	7.14	7.67	8.20	8.55	8.94	7.65	8.12	7.69	8.16
13	7.68	7.31	7.45	7.13	7.71	8.48	8.56	8.90	7.67	8.10	7.70	8.18
14	7.73	7.57	7.48	7.15	7.72	8.48	8.54	8.90	7.67	8.07	7.67	8.29
15	7.76	7.77	7.72	7.16	7.74	8.53	8.52	8.91	7.68	8.04	7.56	8.30
16	7.77	7.86	7.76	7.18	7.71	8.53	8.53	8.64	7.58	8.14	7.54	8.31
17	7.80	7.92	7.78	7.19	7.58	8.55	8.54	8.91	7.69	8.16	7.55	8.33
18	7.82	7.95	7.58	7.20	7.55	8.58	8.57	8.51	7.71	8.15	7.59	8.37
19	7.81	8.00	7.58	7.23	7.56	8.61	8.59	8.66	7.73	8.18	7.60	8.42
20	7.79	7.89	7.59	7.28	7.54	8.64	8.62	8.78	7.75	8.21	7.64	8.41
21	7.79	8.07	7.56	7.30	7.57	8.65	8.44	8.81	7.78	8.19	7.59	8.43
22	7.80	7.96	7.60	7.35	7.56	8.68	8.44	8.72	7.82	8.09	7.74	8.45
23	7.74	7.66	7.58	7.37	7.55	8.69	8.85	8.42	7.84	8.06	7.74	8.44
24	7.78	7.56	7.60	7.45	7.60	8.69	8.70	8.19	7.86	8.04	7.44	8.39
25	7.77	7.48	7.62	7.44	7.59	8.69	8.88	8.10	7.87	8.03	7.56	8.37
26	7.77	7.48	7.67	7.45	7.59	8.72	8.90	8.05	7.92	8.01	7.60	8.38
27	7.78	7.49	7.70	7.46	7.59	8.48	8.83	7.92	7.95	8.01	7.64	8.40
28	7.81	7.48	7.71	7.48	7.59	8.77	8.77	7.86	7.98	7.77	7.63	8.45
29	7.79	7.45	7.72	7.50	7.58	8.75	8.75	8.11	7.81	7.72	7.66	8.56
30	7.80	7.44	7.71	7.47		8.74	8.68	8.23	7.78	7.78	7.87	8.56
31	7.79		7.73	7.50		8.74		8.30		7.74	7.88	
MRAN	7.70	7.59	7.56	7.36	7.59	8.37	8.64	8.63	7.89	8.03	7.68	8.24

WTR YR 1992 MEAN 7.94 HIGHEST 7.08 JAN, 11-13, 1992 LOWEST 8.99 MAY 7, 1992



RIO HONDO TO RIO PUERTO NUEVO BASINS

182441066082600. Local number, 219.
LOCATION.--Lat 18°24'41", long 66°08'26", Hydrologic Unit 21010005, 0.47 mi west of Fort Buchanan Military Res. main gate, 1.74 mi northeast of Bayamón plaxa, and 1.88 mi southwest of P.R. National Cementery. Owner: U.S. Department of Defense, Name: Ft. Buchanan No. 1, Buchanan Park well.
AQUIFER.--Cibao Formation.

46.12

46.66

46.49

AQUIFER. -- cibao Formation.

WELL CHARACTERISTICS. -- Drilled water-table well, diameter 10 in (0.25 m), cased 10 in (0.25 m) 0-270 ft (0-82.3 m), perforated 46-685 ft (14.0-20.7 m), 88-120 ft (26.8-36.6 m), 160-191 ft (48.8-58.2 m), 240-270 ft (73.2-82.3 m). Depth 270 ft (82.3 m).

INSTRUMENTATION. -- Digital water level recorder -- 60-minute punch.

DATUM. -- Elevation of land-surface datum is about 66.0 ft (20.1 m) above mean sea level, from topographic map.

Measuring point: Hole on side of casing, 0.75 ft (0.23 m) above land-surface datum. Prior June 30, 1986, top of shelter floor, 3.59 ft (1.09 m) above land-surface datum.

REMARKS. -- Recording observation well.

PERIOD OF RECORD. --December 1985 to current year.

EXTREMES FOR PERIOD OF RECORD.--Highest water level recorded, 34.97 ft (10.66 m) below land-surface datum, Nov. 12-14


1989; lowest water level recorded, 49.02 ft (14.9 m) below land-surface datum, Apr. 26-28, 1992.

		WATER LEV	RL, IN FR			ACE DATUM, OBSERVATI		TEAR OCTOBI	R 1991 T	O SEPTEME	ER 1992	
DAY	OCT	NOV	DEC	JAN	FRB	MAR	APR	MAY	JUN	JUL	AUG	SEP
1	45.77	46.76	46.49	46.57	46.46	47.80	48.60	49.01	47.77	48.02	47.40	47.20
2	45.72	46.74	46.54	46.56	46.52	47.82	48.62	48.99	47.71	48.06	47.40	47.22
3	45.65	46.67	46.58	46.62	46.59	47.83	48.63	48.91	47.69	48.11	47.23	47.27
4	45.61	46.62	46.53	46.65	46.65	47.86	48.67	48.86	47.68	48.16	47.08	47.35
5	45.59	46.60	46.50	46.68	46.69	47.93	48.68	48.86	47.68	48.20	47.04	47.40
6	45.58	46.61	46.49	46.18	46.70	47.96	48.71	48.85	47.70	48.29	46.91	47.45
7	45.60	46.63	46.50	45.95	46.76	48.00	48.74	48.86	47.72	48.36	46.79	47.50
8	45.66	46.65	46.52	45.84	46.85	48.03	48.74	48.84	47.51	48.41	46.75	47.57
9	45.72	46.63	46.47	45.79	46.92	48.05	48.75	48.85	47.29	48.44	46.70	47.63
10	45.77	46.63	46.40	45.61	46.94	48.07	48.77	48.84	47.21	48.50	46.67	47.72
11	45.83	46.64	46.37	45.48	46.97	48.11	48.79	48.81	47.15	48.51	46.59	47.76
12	45.88	46.67	46.50	45.38	47.03	48.17	48.80	48.80	47.16	48.57	46.57	47.80
13	45.95	46.70	46.50	45.33	47.07	48.23	48.85	48.79	47.18	48.61	46.59	47.81
14	45.98	46.77	46.49	45.31	47.12	48.26	48.83	48.83	47.20	48.63	46.63	47.82
15	46.02	46.81	46.49	45.34	47.18	48.28	48.85	48.90	47.22	48.64	46.39	47.89
16	46.10	46.83	46.47	45.42	47.22	48.32	48.88	48.89	47.24	48.63	46.27	47.94
17	46.19	46.87	46.48	45.50	47.25	48.36	48.94	48.83	47.28	48.59	46.31	47.98
18	46.24	46.89	46.52	45.54	47.27	48.42	48.94	48.76	47.32	48.41	46.37	47.98
19	46.30	46.94	46.53	45.61	47.33	48.43	48.94	48.74	47.34	48.27	46.42	47.99
20	46.34	46.95	46.56	45.67	47.37	48.41	48.94	48.77	47.39	48.22	46.51	47.96
21	46.40	46.98	46.55	45.74	47.41	48.43	48.97	48.80	47.47	48.18	46.63	47.94
22	46.43	46.89	46.45	45.83	47.43	48.49	48.99	48.77	47.49	47.96	46.69	47.91
23	46.47	46.71	46.36	45.90	47.47	48.49	49.00	48.72	47.52	47.82	46.76	47.84
24	46.53	46.51	46.40	45.99	47.52	48.52	48.99	48.45	47.56	47.73	46.79	47.73
25	46.58	46.34	46.42	46.05	47.55	48.52	48.98	48.31	47.61	47.66	46.85	47.69
26	46.55	46.29	46.45	46.17	47.60	48.54	49.01	48.20	47.71	47.58	46.93	47.66
27	46.58	46.33	46.48	46.23	47.64	48.57	49.02	47.98	47.77	47.58	47.00	47.75
28	46.63	46.35	46.47	46.27	47.67	48.60	49.01	47.86	47.84	47.50	47.03	47.81
29	46.68	46.39	46.49	46.31	47.69	48.58	49.01	47.84	47.91	47.41	47.10	47.85
30	46.69	46.43	46.53	46.47		48.58	49.01	47.84	47.97	47.41	47.15	
31	46.75		46.54	46.41		48.58		47.83		47.41	47.19	

WTR YR 1992 MRAN 47.35 HIGHEST 45.30 JAN. 14, 1992 LOWEST 49.02 APR. 26-28, 1992

47.13

45.95



48.27

48.86

48.63

47.51

48.12

46.80

RIO HONDO TO RIO PUERTO NUEVO BASINS

182413066044000. Local number, 220.

LOCATION.--Lat 18°24'13°, long 66°04'40°, Hydrologic Unit 21010005, 3.85 mi southeast of Cataño plaza, 0.86 mi east of Escuela Gabriela Mistral, and 1.26 mi south of Nemesio Canales Public Housing. Owner: P.R. Aqueduct and Sewer Authority, Name: Parque San Luis Rey-Américo Miranda

AQUIFER.--Surficial Deposits-Cibao Formation.

AQUIFEK.--SUFFICIAL Deposits-Cidao Formation.
WELL CHARACTERISTICS.--Drilled unused artesian well, diameter 10 in (0.25 m), cased 8 in (0.20 m) 0-166 ft (0-50.6 m), perforated 39-166 ft (11.9-50.6 m). Depth 166 ft (50.6 m).
INSTRUMENTATION.--Digital water level recorder--60-minute punch.
DATUM.--Elevation of land-surface datum is about 16.4 ft (5.0 m) above mean sea level, from topographic map.

Measuring point: Top of shelter floor, 3.00 ft (0.91 m) above land-surface datum.


DEMANDER --Recording observation call. Mater levels affected by pearly numering well. REMARKS. -- Recording observation well. Water levels affected by nearby pumping well. PERIOD OF RECORD. -- February 1986 to current year.

EXTREMES FOR PERIOD OF RECORD. -- Highest water level recorded, +2.99 ft (+0.91 m) above land-surface datum, Feb. 6, May 8-9, 1986; lowest water level recorded, 6.48 ft (1.98 m) below land-surface datum, Oct. 26, 1989

		WATER LEVEL,	IN FEET	BRLOW INST	Land-Surfa Antaneous	CE DATUM OBSERVAT	, WATER Y ION AT 12	YEAR OCTOBER 200	1991	TO SEPTEMBER	1992	
DAY	OCT	NOV	DEC	JAN	FEB	MAR	APR	MAY	JUN	JUL	AUG	SEP
1	+.30	.22	.44	.96	. 84	1.48	1.26	1.20	. 05	.57	+.30	.24
2	+.32	.19	.50	.92	.90	1.45	1.27	1.07	.00	.58	+.34	.28
3	+.29	.12	.49	.96	. 92	1.47	1.26	.96	.00	.60	+.33	.27
4	+.28	.07	.45	.98	. 96	1.45	1.29	.92	. 02	.63	+.31	.34
5	+.28	.05	.44	1.00	1.01	1.33	1.32	. 92	.01	.66	+.31	.33
6	+.25	. 03	.46	.75	1.03	1.30	1.34	.90	. 03	.70	+.29	.31
7	+.21	+.01	.51	. 62	1.05	1.26	1.34	.89	. 05	.74	+.26	.31
8	+.17	+.06	. 53	.60	1.10	1.27	1.32	.89	+.04	.74	+.20	.32
وَ	+.14	+.09	. 49	.59	1.14	1.27	1.33	.91	+.07	. 62	+.17	.36
10	+.12	+.10	. 47	.49	1.14	1.29	1.31	.91	+.06	.54	+.22	.40
11	+.07	+.08	.50	.32	1.15	1.30	1.32	.90	+.06	.49	+.18	.37
12	+.02	+.09	. 54	.30	1.18	1.31	1.34	.90	+.04	.46	+.15	.44
13	. 03	+.09	. 58	.30	1.19	1.33	1.34	.90	+.01	.45	+.11	.42
14	. 04	+.07	.61	.29	1.20	1.33	1.34	. 92	. 03	.43	+.06	.40
15	.04	+.02	. 62	.31	1.20	1.33	1.36	.99	. 04	.35	+.04	.38
16	. 08	. 05	. 62	.34	1.26	1.36	1.38	.94	. 07	.29	.00	.31
17	. 21	. 17	. 65	.38	1.26	1.34	1.38	. 97	. 10	.24	.03	.19
18	. 24	.31	.71	.41	1.28	1.36	1.38	.96	. 13	.10	. 07	.14
19	. 23	.43	.74	.47	1.31	1.37	1.34	.96	. 15	.06	. 07	. 12
20	. 22	.51	.79	.51	1.30	1.33	1.33	. 96	. 19	.09	. 12	.01
21	.22	.58	. 82	.54	1.31	1.35	1.33	.96	. 25	.09	. 16	.03
22	. 24	.43	. 81	.58	1.29	1.38	1.35	.88	. 27	.06	. 18	.08
23	. 26	.40	.80	. 62	1.34	1.37	1.36	.80	.30	.06	. 24	.04
24	. 26	.40	. 83	.66	1.33	1.38	1.37	.61	. 32	.06	. 24	.03
25	. 27	.40	. 87	.66	1.35	1.36	1.40	.50	.36	+.16		.04
26	.26	.35	. 90	.68	1.37	1.38	1.43	.43	.40	+.20		.08
27	.26	.35	. 92	.71	1.38	1.40	1.48	.24	.43	+.25		.13
28	.29		. 94	.72	1.41	1.40	1.51	. 17	.47	+.26		. 15
29	. 29	.32	. 94	.75	1.45	1.33	1.53	. 17	. 50	+.28		.18
30	. 28		. 95	.76		1.29	1.30	.20	. 55	+.27	. 29	.20
31	.26		. 95	.78		1.27		.16		+.26	. 27	
MBAN	. 05	.18	. 67	.61	1.19	1.35	1.35	.78	. 15	.26	+.06	.23

WTR YR 1992 MEAN .57 HIGHEST +.34 OCT. 1, 1991 LOWEST 1.53 APR. 28, 1992

⁺ Above land-surface datum.



182511066045401. Local number, PN-2.
LOCATION.--Lat 18°25'11, long 66°04'54", Hydrologic Unit 21010005, 1.58 mi northeast of Port Buchannan Military Res. main gate, 2.95 mi southeast of Cataño plaza, and 2.45 mi southeast of U.S. Naval Reservation in Miramar. Owner: U.S. Geological Survey, WRD, Name: La Esperanza No. 2.
AQUIPER.--Alluvium.
WELL CHARACTERISTICS - NAVAL RESERVATION OF THE PROPERTY OF THE PROPERTY

AUGIFEK.--ALIUVIUM.

WELL CHARACTERISTICS.--Drilled observation well, diameter 4 in (0.10 m), cased 4 in (0.10 m), 0-40 ft (0-12.2 m), perforated 30-40 ft ((9.15-12.2 m). Depth 40 ft (12.2 m).

INSTRUMENTATION.--Digital water level recorder--15-minute punch.

DATUM.--Elevation of land-surface datum is about 13 ft (3.96 m) above mean sea level, from topographic map.

Measuring point: Hole on well shaft, 3.17 ft (0.97 m) above land-surface datum.


REMARKS.--Recording observation well.

PERIOD OF RECORD. --July 1989 to current year.

EXTREMES FOR PERIOD OF RECORD.--Highest water level recorded, 8.07 ft (2.46 m) below land-surface datum, June 8-10, 1992; lowest water level recorded, 11.90 ft (3.63 m) below land-surface datum, July 15-16, 1991.

		WATER LEVE	L, IN FERT		Land-Surf Pantanbous				1991	TO SEPTEMBER	1992	
DAY	OCT	NOV	DEC	JAN	PRB	MAR	APR	MAY	JUN	JUL	λŪĞ	SEP
1	9.15	10.40	9.00	9.63		10.65	10.02	10.04	8.40	9.85	8.93	9.94
2	9.11	10.21	9.05	9.68		10.71	10.04	9.79	8.26	9.90	9.01	9.88
3	9.13	10.01	8.97	9.77		10.71	10.01	9.46	8.21	9.95	9.00	9.86
4	9.18	9.78	8.72	9.85		10.75	10.00	9.38	8.27	10.01	9.10	9.87
5	9.21	9.64	8.59	9.90		10.44	10.04	9.43	8.29	10.06	9.14	9.95
6	9.27	9.50	8.56	9.37		10.20	10.10	9.46	8.26	10.11	9.05	9.99
7	9.34	9.35	8.55	8.97		10.12	10.20	9.28	8.20	10.18	8.98	9.99
8	9.43	9.26	8.59	8.86		10.01	10.23	9.20	8.08	10.21	8.87	10.00
9	9.49	9.07	8.44	8.85		10.02	10.25	9.24	8.07	10.07	8.87	10.00
10	9.55	9.02	8.30	8.64		10.07	10.25	9.29	8.07	9.92	8.88	9.98
11	9.63	9.05	8.31	8.39		10.12	10.33	9.22	8.09	9.89	8.94	10.01
12	9.72	9.12	8.37	8.34		10.18	10.33	9.21	8.17	9.72	9.01	9.95
13	9.81	9.19	8.47	8.31		10.25	10.31	9.25	8.26	9.69	9.08	9.92
14	9.89	9.23	8.56	8.29		10.34	10.32	9.34	8.36	9.69	9.16	9.92
15	9.96	9.31	8.62	8.38		10.33	10.26	9.47	8.52	9.68	9.06	10.01
16	10.03	9.40	8.70	8.48		10.33	10.29	9.47	8.61	9.59	9.09	10.01
17	10.09	9.44	8.77	8.59		10.42	10.37	9.50	8.70	9.68	9.15	9.95
18	10.16	9.51	8.87	8.67		10.43	10.39	9.47	8.78	9.41	9.26	9.67
19	10.23	9.63	8.97	8.77		10.48	10.32	9.47	8.87	9.35	9.34	9.54
20	10.26	9.74	9.05	8.88		10.54	10.31	9.47	8.95	9.31	9.43	9.43
21	10.29	9.77	9.12	8.96		10.58	10.34	9.45	9.05	9.32	9.49	9.32
22	10.37	9.44	9.17	9.06		10.66	10.42	9.36	9.12	9.35	9.55	9.32
23	10.39	9.06	9.18	9.13		10.71	10.48	9.31	9.19	9.30	9.64	9.36
24	10.45	8.79	9.20		10.50	10.72	10.56	8.96	9.25	9.29	9.66	9.37
25	10.51	8.59	9.26		10.52	10.74	10.60	8.82	9.35	9.29	9.73	9.39
26	10.43	8.58	9.32		10.55	10.76	10.66	8.65	9.48	9.32	9.79	9.42
27	10.40	8.65	9.38		10.56	10.82	10.71	8.48	9.55	9.37	9.88	9.49
28	10.44	8.74	9.44		10.58	10.83	10.75	8.39	9.62	9.16	9.93	9.54
29	10.46	8.83	9.47		10.60	10.52	10.81	8.39	9.72		10.00	9.63
30	10.50	8.94	9.52			10.15	10.44	8.46	9.77	8.89	9.99	9.71
31	10.43		9.57			10.02		8.46		8.94	10.00	
MRAN	9.91	9.31	8.91	8.95	10.55	10.44	10.34	9.20	8.72	9.60	9.32	9.75

WTR YR 1992 HIGHEST 8.07 JUNE 8-10, 1992 LOWEST 10.87 MAR. 27-28, 1992 MRAN 9.53



RIO HONDO TO RIO PUERTO NUEVO BASINS

182435066052700. Local number, PN-5.
LOCATION.--Lat 18°24'35", long 66°05'27", Hydrologic Unit 21010005, 2.94 mi southeast of Catafio plaza, 0.44 mi north of Escuela Superior Gabriela Mistral, and 1.19 mi northeast of WAPA TV Radio Anthena. Owner: U.S. Geological Survey, WRD, Name: Salud Mental No. 1.
AQUIFER.--Alluvium.

MRAN

29.91

30.00

29.19

AQUIFER.--Alluvium.

WELL CHARACTERISTICS.--Drilled water-table well, diameter 4.0 in (0.10 m), cased 4.0 in (0.10 m), 0-83 ft (0-25.3 m), perforated 73-83 ft (22.2-25.3 m). Depth 83 ft (25.3 m).

INSTRUMENTATION.--Digital water level recorder--15-minute punch.

DATUM.--Elevation of land-surface datum is about 85 ft (25.9 m) above mean sea level, from topographic map. Measuring point: Hole on well shaft, 2.85 ft (0.87 m) above land-surface datum.

REMARKS.--Recording observation well.

PERIOD OF RECORD.--April 1989 to current year.


EXTREMES FOR PERIOD OF RECORD.--Highest water level recorded, 26.20 ft (7.98 m) below land-surface datum, Nov. 21-22, 1989; lowest water level recorded, 30.23 ft (9.21 m) below land-surface datum, May 21, 1992.

		WATER LE	VEL, IN FE		Land-Surf Tantanbous				BR 1991	TO SEPTEMBER	1992	
DAY	OCT	NOV	DRC	JAN	Peb	MAR	APR	MAY	JUN	JUL	AUG	SEP
1	29.94	29.99	29.75	28.92	28.43	28.98	29.77		29.71			
2	29.94	29.98	29.71	28.92	28.43	29.00	29.79	30.20	29.63			
3	29.94	29.95	29.66	28.92	28.43	29.01	29.80		29.57			
4	29.94	29.99	29.55	28.92	28.43	29.04	29.82		29.52			
5	29.93	30.01	29.55	28.93	28.43	29.05	29.83		29.40			
6	29.92	30.01	29.54	28.78	28.43	29.08	29.85		29.34			
7	29.91	30.03	29.50		28.43	29.12	29.89		29.25			
8	29.90	30.03	29.43		28.45	29.15	29.89		29.15			
9	29.89	30.02	29.37		28.46	29.19	29.90		29.08			
10	29.88	30.03	29.33		28.47	29.21	29.91		29.01			
11	29.88	30.04	29.26		28.49	29.23	29.93		28.93			
12	29.88	30.04	29.23		28.53	29.28	29.95		28.88			
13	29.88	30.04	29.20	28.74	28.56	29.32	29.97		28.81			
14	29.88	30.05	29.16	28.69	28.57	29.32	30.01		28.77			
15	29.87	30.05	29.12	28.66	28.59	29.33	30.01		28.73			
16	29.87	30.05	29.09	28.63	28.60	29.37	30.04		28.69			
17	29.87	30.05	29.04	28.61	28.63	29.39	30.06		28.64			
18	29.87	30.05	29.03	28.57	28.66	29.40	30.07		28.59			
19	29.87	30.06	29.02	28.56	28.70	29.45	30.08		28.55			
20	29.87	30.07	28.99	28.54	28.72	29.47	30.09		28.51			
21	29.88	30.09	28.98	28.53	28.74	29.50	30.12		28.49			
22	29.89	29.96	28.96	28.53	28.75	29.53	30.14	30.13	28.44			
23	29.90	29.99	28.94	28.52	28.77	29.56	30.16	30.10	28.41			
24	29.91	30.01	28.94	28.48	28.83	29.58	30.17	29.95	28.40			
25	29.91	30.01	28.94	28.46	28.83	29.60	30.18	30.07	28.39			
26	29.92	29.99	28.94	28.44	28.84	29.62	30.20	30.03	28.37			
27	29.93	29.95	28.93	28.44	28.87	29.67	30.21	29.94	28.36			
28	29.95	29.90	28.92	28.43	28.90	29.69		29.94	28.35			
29	29.96	29.86	28.92	28.44	28.92	29.69		29.94				
30	29.97	29.79	28.92	28.44		29.71		29.88				
31	29.98		28.92	28.44		29.74		29.82				

WTR YR 1992 MEAN 29.36 HIGHEST 28.35 JUNE 28, 1992 LOWEST 30.23 MAY 21, 1992

28.62

28.62



29.36

29.99

28.86

RIO HONDO TO RIO PURRTO NURVO BASINS

182445066043401. Local number, PN-6.
LOCATION.--Lat 18°24'45°, long 66°04'34°, Hydrologic Unit 21010005, 0.28 mi northeast of Escuela Dr. Pedreira, 3.52 mi southeast of Cataño plaza, and 0.53 mi south of Hiram Bithorn Stadium main gate. Owner: U.S. Geological Survey, southeast of Catafio plaza, and 0.53 mi south of Hiram Bithorn Stadium main gate. Owner: U.S. Geological Survey WRD, Name: Alsacia No. 2.

AQQIFER.--Alluvium.

WELL CHARACTERISTICS.--Drilled observation well, diameter 4 in (0.10 m), cased 4 in (0.10 m), 0-27 ft (0-8.23 m), perforated 21-27 ft (6.40-8.23 m). Depth 27 ft (8.23 m). TINSTRUMENTATION.--Digital water level recorder--15-minute punch.

DATUM.--Elevation of land-surface datum is about 10 ft (3.05 m) above mean sea level, from topographic map. Measuring point: Hole on well shaft, 3.03 ft (0.91 m) above land-surface datum.

REMARKS.--Recording observation well. Destroyed by Municipality employee with heavy equipment.

PERIOD OF RECORD.--July 1989 to November 27, 1991, temporary discontinued.

EXTREMES FOR PERIOD OF RECORD.--Highest water level recorded, 3.11 ft (0.95 m) below land-surface datum, Sept. 18, 1989; lowest water level recorded, 8.70 ft (2.65 m) below land-surface datum, Nov. 21, 1991.


MRAN

8.02

8.01

		WATER LEVEL,	IN FRET				I, WATER YEAR LION AT 1200	OCTOBER	1991	TO SEPTEMBER	1992	
DAY	OCT	NOV	DEC	JAN	FEB	MAR	APR	MAY	JUN	JUL	DUA	SEP
1	7.29	8.38										
2	7.26	8.22										
3	7.26	8.10										
4	7.33	8.04										
5	7.37	8.01										
6	7.41	7.93										
7	7.50	7.87										
8	7.54	7.77										
9	7.62	7.72										
10	7.68	7.70										
11	7.79	7.76										
12	7.89	7.78										
13	8.00	7.83										
14	8.04	7.86										
15	8.10	7.91										
16	8.11	7.99										
17	8.21	8.11										
18	8.34	8.25										
19	8.40	8.39										
20	8.34	8.54										
21	8.34	8.62										
22	8.42	8.29										
23	8.46	8.01										
24	8.49	7.80										
25	8.52	7.74										
26	8.43	7.75										
27	8.44	7.79										
28	8.51											
29	8.52											
30	8.53											
31	8.43											

WTR YR 1992 MRAN 8.01 HIGHEST 7.26 OCT. 2-3, 1991 LOWEST 8.70 NOV. 21, 1991



RIO HONDO TO RIO PUERTO NUEVO BASINS

182437066040500. Local number, PN-7.
LOCATION.--Lat 18°24'37", long 66°04'05", Hydrologic Unit 21010005, 4.03 mi southeast of Catafio plasa, 0.70 mi east of Escuela Dr. Pedreira, and 0.25 southeast of Hospital del Maestro. Owner: Name: Parque de las Fuentes No. 1.
AQUIFER.--Alluvium.

AQUIFER.--Alluvium.

WELL CHARACTERISTICS.--Drilled observation well, diameter 4 in (0.10 m), cased 4 in (0.10 m), 0-52 ft (0-15.8 m), perforated 42-52 ft (12.8-15.8 m). Depth 52 ft (15.8 m).

INSTRUMENTATION.--Digital water level recorder--15-minute punch.

DATUM.--Elevation of land-surface datum is about 23 ft (7.01 m) above mean sea level, from levels.

Measuring point: Hole on well shelter floor, 3.20 ft (0.98 m) above land-surface datum.

REMARKS.--Recording observation well. Formerly published as 182437066040501, Parque de las Fuentes No. 2, which is


another well.

PERIOD OF RECORD.--February 1989 to current year.

EXTREMES FOR PERIOD OF RECORD.--Highest water level recorded, 6.50 ft (1.98 m) below land-surface datum, Sept. 27, 1989; lowest water level recorded, 12.60 ft (3.84 m) below land-surface datum, Aug. 16-17, 1991.

		WATER LEVE	L, IN FEBT		Land-Surf Tantanbous			YEAR OCTOBER	1991 TO	SEPTEMBER	1992	
DAY	OCT	NOV	DEC	JAN	FEB	MAR	APR	MAY	JUN	JUL	AUG	SEP
1	10.69	10.71	9.13	9.74	9.45	10.72	10.34	11.64	8.31	9.57	8.65	10.01
2	10.69	10.54	9.16	9.77	9.48	10.76	10.35	11.37	8.18	9.64	8.69	9.99
3	10.76	10.37	9.16	9.83	9.62	10.78	10.36	11.12	8.16	9.72	8.72	10.00
4	10.82	10.20	8.99	9.90	9.66	10.80	10.40	11.04	8.19	9.79	8.77	10.04
5	10.85	10.10	8.90	9.95	9.69	10.45	10.47	11.15	8.18	9.87	8.81	10.08
6	10.85	10.03	8.88	9.31	9.74	10.26	10.54	11.22	8.01	9.96	8.78	10.10
7	10.89	9.92	8.89	8.97	9.78	10.15	10.60	11.21	7.93	10.04	8.74	10.07
8	11.00	9.80	8.89	8.89	9.87	10.09	10.62	11.21	7.65	10.10	8.70	10.07
9	11.09	9.67	8.84	8.87	9.96	10.09	10.65	11.28	7.59	9.94	8.69	10.07
10	11.15	9.59	8.75	8.60	10.00	10.08	10.64	11.33	7.59	9.82	8.69	10.08
11	11.30	9.58	8.72	8.35	10.05	10.10	10.66	11.33	7.59	9.72	8.69	10.10
12	11.37	9.59	8.72	8.29	10.11	10.14	10.67	11.34	7.63	9.62	8.78	10.08
13	11.37	9.58	8.79	8.26	10.16	10.20	10.69	11.38	7.75	9.62	8.89	10.07
14	11.34	9.59	8.83	8.25	10.21	10.26	10.69	11.45	7.87	9.61	8.98	10.07
15	11.41	9.62	8.92	8.27	10.23	10.26	10.69	11.29	8.02	9.59	8.97	10.09
16	11.50	9.67	8.95	8.33	10.28	10.31	10.74	11.10	8.14	9.56	9.00	10.08
17	11.65	9.73	9.02	8.41	10.34	10.38	10.78	10.82	8.21	9.52	9.08	10.03
18	11.79	9.82	9.13	8.48	10.37	10.39	10.79	10.66	8.31	9.32	9.19	9.76
19	11.84	9.92	9.18	8.57	10.41	10.43	10.77	10.54	8.36	9.24	9.27	9.65
20	11.82	9.99	9.26	8.67	10.45	10.44	10.73	10.45	8.40	9.24	9.31	9.54
21	11.86	10.03	9.32	8.75	10.49	10.48	10.73	10.39	8.53	9.21	9.38	9.50
22	11.86	9.57	9.36	8.86	10.50	10.55	10.82	10.07	8.68	9.19	9.38	9.50
23	11.59	9.20	9.37	8.95	10.49	10.60	11.16	9.87	8.78	9.16	9.47	9.53
24	11.39	8.94	9.37	9.05	10.49	10.63	11.47	9.41	8.86	9.13	9.53	9.54
25	11.19	8.83	9.43	9.15	10.52	10.65	11.69	9.26	8.93	9.09	9.64	9.58
26	11.01	8.81	9.51	9.19	10.56	10.70	11.88	9.12	9.11	9.07	9.73	9.66
27	10.92	8.81	9.55	9.22	10.59	10.75	12.02	8.62	9.18	9.15	9.79	9.74
28	10.86	8.85	9.59	9.29	10.62	10.63	12.26	8.51	9.29	8.91	9.86	9.80
29	10.83	8.93	9.62	9.34	10.65	10.48	12.38	8.47	9.38	8.72	9.93	9.89
30	10.81	9.06	9.65	9.34		10.39	11.88	8.47	9.47	8.66	9.99	9.96
31	10.75		9.68	9.41		10.36		8.47		8.64	10.02	
MRAN	11.20	9.63	9.15	8.98	10.16	10.43	10.95	10.44	8.34	9.43	9.17	9.89

WTR YR 1992 MEAN 9.81 HIGHEST 7.59 JUNE 9-12, 1992 LOWEST 12.40 APR. 29, 1992



182443066041502. Local number, PN-8c.
LOCATION.--Lat 18°24'43", long 66°04'15", Hydrologic Unit 21010005, 2.29 mi east of Port Buchannan Military Res. main gate, 3.83 mi southeast of Cataño plaza, and 0.16 mi southwest of Hospital del Maestro. Owner: U.S. Geological Survey, WRD, Name: Parque Luis Muñoz Marin 1C.
AQUIFER.--Alluvium.
WELL CHARACTERISTICS

AQUIFER.--Alluvium.

WELL CHARACTERISTICS.--Drilled observation well, diameter 4 in (0.10 m), cased 4 in (0.10), 0-33 ft (0-10.1 m), perforated 33-40 ft (10.1-12.2 m). Depth 40 ft (12.2 m).

INSTRUMENTATION.--Digital water level recorder--15-minute punch.

DATUM.--Elevation of land-surface datum is about 13 ft (3.96 m) above mean sea level, from topographic map.

Measuring point: Hole on well shaft, 3.66 ft (1.12 m) above land-surface datum.


REMARKS.--Recording observation well.

PERIOD OF RECORD.--February 1989 to current year.

EXTREMES FOR PERIOD OF RECORD.--Highest water level recorded, 10.35 ft (3.15 m) below land-surface datum, Sept. 25, 1989; lowest water level recorded, 15.46 ft (4.71 m) below land-surface datum, Apr. 28-29, 1992.

		WATER LEV	BL, IN FE		Land-Surf Antaneous			EAR OCTOB	BR 1991 1	O SEPTEMB	ER 1992	
DAY	OCT	NOV	DEC	Jan	FRB	MAR	APR	MAY	JUN	JUL	AUG	SEP
1	14.16	15.00	13.34	14.45	14.17	15.05	15.03	14.65	12.32	14.22	13.45	14.46
2	14.12	14.80	13.49	14.47	14.24	15.05	15.04	14.13	12.07	14.29	13.54	14.50
3	14.15	14.82	13.55	14.51	14.26	15.05	15.04	14.26	12.13	14.34	13.57	14.54
4	14.19	14.82	13.46	14.55	14.32	15.06	15.07	14.31	12.25	14.40	13.65	14.57
5	14.23	14.81	13.38	14.57	14.37	14.85	15.09	14.38	12.31	14.43	13.46	14.58
6	14.30	14.79	13.36	13.30	14.42	14.88	15.11	14.28	12.10	14.48	13.56	14.57
7	14.38	14.77	13.39	13.30	14.46	14.87	15.13	14.34	11.92	14.53	13.59	14.53
8	14.45	14.56	13.41	13.30	14.52	14.89	15.14	14.40	11.34	14.52	13.60	14.59
9	14.50	14.55	13.28	13.33	14.57	14.90	15.13	14.48	11.11	14.31	13.64	14.61
10	14.56	14.55	13.05	12.71	14.58	14.90	15.09	14.49	11.25	14.43	13.46	14.65
11	14.63	14.55	12.99	12.46	14.61	14.91	15.13	14.55	11.38	14.41	13.50	14.63
12	14.68	14.55	12.98	12.37	14.65	14.95	15.14	14.58	11.58	14.41	13.64	14.67
13	14.74	14.55	13.05	12.31	14.70	14.97	15.17	14.64		14.41	13.71	14.67
14	14.75	14.57	13.14	12.34	14.73	14.97	15.19	14.72		14.36	13.79	14.66
15	14.79	14.64	13.26	12.46	14.77	14.97	15.19	14.76		14.28	13.58	14.68
16	14.86	14.67	13.36	12.59	14.80	14.99	15.21	14.78		14.29	13.72	14.66
17	14.89	14.72	13.46	12.66	14.83	15.02	15.23	14.58		14.21	13.88	14.60
18	14.93	14.76	13.56	12.83	14.85	15.02	15.23	14.65		14.10	13.96	14.50
19	14.87	14.80	13.67	13.00	14.87	15.03	15.21	14.57		14.07	14.04	14.50
20	14.95	14.82	13.79	13.11	14.89	15.03	15.11	14.59		14.06	14.10	14.27
21	14.99	14.83	13.80	13.25	14.90	15.05	15.16	14.66		13.88	14.15	14.29
22	15.01	13.97	13.90	13.37	14.85	15.08	15.22	14.48		13.94	13.89	14.33
23	15.01	13.55	13.95	13.50	14.91	15.10	15.28	14.43		13.95	14.08	14.34
24	15.01	12.97	14.06	13.59	14.93	15.11	15.30	13.62		13.93	14.11	14.22
25	15.01	12.66	14.13	13.66	14.97	15.11	15.33	13.54	13.71	13.89	14.20	14.33
26	15.00	12.64	14.18	13.72	14.98	15.14	15.38	13.43	13.83	13.92	14.29	14.39
27	15.00	12.74	14.23	13.83	15.00	15.16	15.41	12.52	13.92	13.97	14.34	14.46
28	15.01	12.90	14.28	13.92	15.01	15.19	15.45	12.50	14.01	13.61	14.39	14.50
29	15.01	13.05	14.32	13.99	15.03	14.96	15.46	12.54	14.09	13.55	14.44	14.53
30	15.02	13.22	14.37	14.05		15.01	14.41	12.58	14.15	13.53	14.46	14.56
31	14.99		14.42	14.12		15.02		12.60		13.55	14.38	
MEYN	14.72	14.22	13.63	13.41	14.70	15.01	15.17	14.10	12.53	14.14	13.88	14.51

WTR YR 1992 MEAN 14.22 HIGHEST 11.04 JUNE 8-9, 1992 LOWEST 15.46 APR. 28-29, 1992



RIO HONDO TO RIO PUERTO NUEVO BASINS

182417066042700. Local number, PN-10.
LOCATION.--Lat 18°24'17", long 66°04'27", Hydrologic Unit 21010005, 3.96 mi southeast of Cataño plaza, 1.00 mi southwest of Escuela J. J. Osuna, and 2.26 mi east of WAPA TV Radio Anthena. Owner: U.S. Geological Survey, WRD, Name: Las Americas No. 1. AQUIFER.--Alluvium.

well Characteristics. -- Drilled observation well, cased 4.0 in (0.10 m), 0-80 ft (0-24.39 m), 4.0 in (0.10 m), perforated pipe 80-90 ft (24.39-27.43 m). Depth 90 ft (27.43 m).

perforated pipe 80-90 ft (24.39-27.43 m). Depth 90 ft (27.43 m).

INSTRUMENTATION. --Digital water level recorder--15-minute punch.

DATUM.--Elevation of land-surface datum is about 16 ft (4.89 m) above mean sea level, from topographic map.

Measuring point: Hole on well shaft, 3.10 ft (0.95 m) above land-surface datum.

REMARKS.--Recording observation well.


PERIOD OF RECORD.--Ctober 1989 to current year.

EXTREMES FOR PERIOD OF RECORD.--Highest water level recorded, +2.04 ft (+0.62 m) above land-surface datum, Oct. 22, 1990; lowest water level recorded, 2.48 ft (0.76 m) below land-surface datum, Oct. 26-27, 1989.

		WATER LEVE	L, IN FRET	BRLOW INST	Land-Surfa Antaneous	CE DATUM, OBSERVAT	WATER YE	ear october 00	1991	TO SEPTEMBE	R 1992	
DAY	OCT	NOA	DEC	JAN	PRB	MAR	APR	MAY	JUN	JUL	AUG	SEP
1	+.85	+.63	+.33	.01	+.12	.33	. 28	.28	+.74	+.47	+.99	+.85
2	+.85	+.65	+.31	.02	+.10	.36	. 26	.25	+.79	+.46	+1.01	+.85
3	+.86	+.69	+.30	.02	+.07	.37	. 25	.20	+.84	+.46	+1.03	+.82
4	+. 87	+.73	+.30	.02	+.02	.37	. 25	. 13	+.86	+.45	+1.05	+.80
5	+.90	+.76	+.31	.02	. 02	.34	.25	.07	+.90	+.43	+1.07	+.79
6	+.92	+.80	+.31	.03	. 06	.31	.26	.04	+.93	+.41	+1.08	+.78
7	+.93	+.82	+.32	+.02	. 08	.29	. 27	.01	+.93	+.40	+1.10	+.77
8	+.93	+.85	+.31	+.07	. 12	.27	.28	+.01	+.97	+.39	+1.13	+.77
ġ	+.93	+.88	+.30	+.09	.20	.26	.28	+.05	+1.00	+.42	+1.15	+.77
10	+.93	+.87	+.29	+.13	.22	.26	.26	+.06	+1.02	+.46	+1.15	+.76
11	+.92	+.87	+.30	+.18	. 23	.25	. 25	+.07	+1.03	+.50	+1.15	+.75
12	+.89	+.87	+.28	+.22	. 25	.25	.24	+.09	+1.04	+.52	+1.15	+.74
13	+.72	+.88	+.28	+.26	. 26	.26	.24	+.12	+1.04	+.54	+1.15	+.72
14	+.70	+.87	+.26	+.30	.26	.27	.23	+.13	+1.03	+.56	+1.14	+.71
15	+.69	+.88	+.25	+.32	. 26	.27	.23	+.13	+1.02	+.59	+1.14	+.71
16	+.67	+.87	+.23	+.33	.27	.27	.23	+.13	+.99	+.63	+1.14	+.73
17	+.64	+.82	+.21	+.33	.27	.28	.24	+.13	+.98	+.67	+1.14	+.76
18	+.60	+.73	+.19	+.33	. 27	.29	.24	+.15	+.96	+.57	+1.12	+.82
19	+.58	+.65	+.17	+.32	. 27	.29	.23	+.16	+.95	+.63	+1.10	+.88
20	+.57	+.56	+.14	+.29	.27	.29	.22	+.18	+.91	+.70	+1.09	+.91
21	+.57	+.49	+.13	+.27	.27	.29	.21	+.18	+.79	+.78	+1.08	+.94
22	+.57	+.43	+.12	+.26	. 27	.29	. 19	+.23	+.72	+.82	+1.07	+.96
23	+.59	+.39	+.12	+.24	. 27	.30	.20	+.27	+.69	+.82	+1.05	+.97
24	+.60	+.37	+.11	+.23	. 27	.31	.20	+.23	+.66	+.82	+1.03	+.99
25	+.61	+.38	+.08	+.19	. 28	.31	.20	+.30	+.62	+.83	+1.01	+.99
26	+.63	+.40	+.06	+.18	.28	.31	.21	+.39	+.59	+.83	+.95	+.99
27	+.63	+.40	+.03	+.17	.29	.31	. 23	+.45	+.56	+.83	+.92	+.97
28	+.63	+.39	+.01	+.16	. 30	.33	. 24	+.53	+.54	+.79	+.90	+.95
29	+.62	+.37	. 00	+.15	.30	.33	. 25	+.60	+.53	+.87	+.88	+.92
30	+.62	+.34	.00	+.15		.30	.28	+.64	+.50	+.92	+.87	+.89
31	+.63		.01	+.14		.29		+.69		+.96	+.85	
MEAN	+.73	+.65	+.19	+.17	. 19	.30	. 24	+.16	+.84	+.63	+1.05	+.84

HIGHEST +1.15 AUG. 9-13, 1992 LOWEST .37 MAR. 3-4, 1992 WTR YR 1992 MBAN +.38

⁺ Above land-surface datum



WATER YEAR

RIO HONDO TO RIO PUERTO NUEVO BASINS

182349066032600. Local number, PN-13.
LOCATION.--Lat 18°23'49", long 66°03'26", Hydrologic Unit 21010005, 5.15 mi southeast of Cataño plaza, 1.28 mi south of Escuela J. J. Osuna, and 0.69 mi southwest of University of Puerto Rico main gate. Owner: U.S. Geological Survey, WRD, Name: Jardin Botánico No. 1. AQUIFER, -- Alluvium.

AQUIFER.--Alluvium.

WELL CHARACTERISTICS.--Drilled water-table well, diameter 4 in (0.10 m) cased 4.0 in (0.10 m), 0-45 ft (0-13.72 m), perforated 35-45 ft (10.67-13.72 m). Depth 45 ft (13.72 m).

INSTRUMENTATION.--Digital water level recorder--15-minute punch.

DATUM.--Elevation of land-surface datum is about 32 ft (9.75 m) above mean sea level, from topographic map.

Measuring point: Hole on well shaft, 2.84 ft (0.86 m) above land-surface datum.

DEMANY ---Paccycling character well

REMARKS. -- Recording observation well.


REMARKS.--Recording observation well.

PERIOD OF RECORD.--March 1989 to current year.

EXTREMES FOR PERIOD OF RECORD.--Highest water level recorded, 8.75 ft (2.67 m) below land-surface datum, Sept. 18, 1989; lowest water level recorded, 17.08 ft (5.20 m) below land-surface datum, Apr. 16, 1992.

		WATER LEV	EL, IN F	et Below Inst	Land-Surf Antaneous	ACE DATUM OBSERVAT	, WATER Y	FEAR OCTOE	MER 1991 7	O SEPTEME	BER 1992	
DAY	OCT	Nov	DEC	JAN	FRB	MAR	APR	MAY	JUN	JUL	λŪG	SEP
1	16.52	16.82	16.58	16.72	16.57	16.93	16.93	16.21	15.83	16.46	15.94	16.43
2	16.52	16.18	16.63	16.72	16.60	16.94	16.96	15.54	15.69	16.49	15.98	16.48
3	16.59	16.69	16.57	16.75	16.53	16.93	16.95	16.13	15.78	16.51	15.94	16.51
4	16.59	16.74	16.47	16.77	16.61	16.94	16.97	16.21	15.88	16.53	15.99	16.55
5	16.52	16.81	16.49	16.78	16.62	16.87	16.99	16.29	15.88	16.52	15.39	16.53
6	16.65	16.83	16.56	15.30	16.65	16.88	17.03	15.37	15.90	16.58	15.89	16.50
7	16.69	16.82	16.61	16.26	16.66	16.87	16.98	16.23	15.89	16.64	16.00	16.46
8	16.71	16.25	16.47	16.41	16.69	16.91	16.97	16.32	15.66	16.51	15.99	16.58
9	16.70	16.74	16.56	16.39	16.72	16.92	16.94	16.40	15.64	16.20	16.03	16.59
10	16.73	16.85	16.56	15.30	16.73	16.92	16.80	16.21	15.75	16.47	15.79	16.64
11	16.74	16.91	16.59	16.11	16.74	16.92	16.85	16.37	15.87	16.38	15.85	16.64
12	16.76	16.92	16.42	16.17	16.77	16.95	16.91	16.41	15.90	16.54	16.00	16.68
13	16.77	16.93	16.61	16.06	16.78	16.95	17.03	16.48	15.92	16.55	16.05	16.68
14	16.77	16.97	16.53	16.17	16.79	16.94	17.02	16.49	15.95	16.48	16.06	16.68
15	16.77	16.98	16.65	16.20	16.79	16.95	17.05	16.54	16.02	16.39	15.88	16.70
16	16.78	16.82	16.66	16.24	16.82	16.97	17.07	16.58	16.04	16.40	16.06	16.70
17	16.81	16.96	16.65	16.18	16.81	16.94	17.03	16.31	16.08	16.15	16.17	16.58
18	16.82	16.98	16.65	16.28	16.84	16.90	17.00	16.35	16.12	16.37	16.22	16.59
19	16.65	16.99	16.69	16.34	16.80	16.95	16.99	16.28	16.14	16.44	16.24	16.69
20	16.75	16.99	16.70	16.35	16.87	16.96	16.85	16.37	16.17	16.44	16.24	16.31
21	16.78	16.98	16.52	16.40	16.88	16.96	16.93	16.42	16.13	16.24	16.27	16.44
22	16.80	16.16	16.57	16.42	16.59	17.00	17.01	16.31	16.17	16.29	15.96	16.66
23	16.79	16.45	16.57	16.45	16.86	16.96	16.99	15.97	16.21	16.39	16.22	16.66
24	16.81	16.22	16.65	16.46	16.87	17.03	16.98	15.36	16.24	16.12	16.24	16.50
25	16.81	16.47	16.67	16.39	16.87	16.99	16.99	15.88	16.28	16.27	16.31	16.59
26	16.82	16.53	16.67	16.41	16.88	16.99	17.02	15.78	16.32	16.34	16.36	16.65
27	16.81	16.53	16.62	16.45	16.90	17.01	17.04	15.32	16.34	16.31	16.37	16.67
28	16.83	16.56	16.67	16.46	16.91	17.05	17.04	15.53	16.38	16.02	16.41	16.71
29	16.85	16.59	16.67	16.47	16.92	16.85	17.05	15.61	16.41	16.08	16.43	16.70
30	16.84	16.60	16.68	16.53		16.94	15.80	15.34	16.44	16.13	16.45	16.70
31	16.76		16.71	16.56		16.94		15.69		16.13	16.27	
MRAN	16.73	16.71	16.60	16.34	16.76	16.94	16.94	16.07	16.03	16.37	16.10	16.59

WTR YR 1992 MRAN 16.51 HIGHEST 12.89 APR. 30, 1992 LOWEST 17.08 APR. 16, 1992



RIO HONDO TO RIO PUERTO NUEVO BASINS

182406066034700. Local number, PN-19.
LOCATION.--Lat 18°24'06", long 66°03'47", Hydrologic Unit 21010005, 4.65 mi southeast of Cataño plaza, 0.89 mi south of Escuela J. J. Osuna, and 0.78 mi southwest of University of Puerto Rico main gate. Owner: U.S. Geological Survey, WRD, Name: Jardin Botánico No. 3.
AQUIFER.--Alluvium.

AQUIFER.--Alluvium.

WELL CHARACTERISTICS.--Drilled water-table well, diameter 4 in (0.10 m) cased 4.0 in (0.10 m), 0-48 ft (0-14.6 m), perforated 38-48 ft (11.6-14.6 m). Depth 48 ft. (14.6 m).

INSTRUMENTATION.--Digital water level recorder--15-minute punch.

DATUM.--Elevation of land-surface datum is about 32 ft (9.75 m) above mean sea level, from topographic map. Measuring point: Hole on well shaft, 2.91 ft (0.88 m) above land-surface datum.


REMARKS.--Recording observation well.

PERIOD OF RECORD.--June 1991 to current year.

EXTREMES FOR PERIOD OF RECORD.--Highest water level recorded, 4.04 ft (1.23 m) below land-surface datum, June 9, 1992; lowest water level recorded, 8.23 ft (2.51 m) below land-surface datum, Apr. 28, 1992.

		WATER LEVEL,	IN FERT		Land-Surfa Pantaneous				1991	TO SEPTEMBER	1992	
DÄY	CCT	Nov	DBC	Jan	FEB	MAR	APR	MAY	JUN	JUL	AUG	SEP
1	6.34	7.67		7.17	6.30	7.97	7.75	6.55	4.35	6.11	4.53	6.04
2	6.33	7.65		7.20	6.40	8.03	7.77	6.01	4.21	6.20	4.52	6.09
3	6.34	7.50		7.24	6.47	8.07	7.78	5.73	4.23	6.33	4.51	6.15
4	6.42	7.45		7.34	6.52	8.11	7.79	5.69	4.31	6.40	4.52	6.19
5	6.45	7.42		7.37	6.54	7.70	7.86	5.69	4.29	6.46	4.53	6.27
6	6.47	7.42		6.61	6.59	7.65	7.93	5.71	4.21	6.55	4.37	6.29
7	6.51	7.42		6.22	6.75	7.53	8.07	5.64	4.22	6.63	4.35	6.37
8	6.58	7.42		6.11	6.92	7.50	8.09	5.63	4.05	6.61	4.31	6.42
9	6.64	7.32		6.08	6.99	7.50	8.10	5.68	4.05	6.24	4.31	6.44
10	6.71	7.29		5.77	7.03	7.53	7.89	5.72	4.09	6.11	4.33	6.49
11	6.73	7.27		5.50	7.07	7.56	7.86	5.75	4.10	6.02	4.38	6.53
12	6.84	7.27		5.39	7.14	7.67	7.84	5.80	4.15	5.95	4.52	6.58
13	6.92	7.27		5.25	7.23	7.70	7.89	5.94	4.22	5.96	4.63	6.63
14	6.97	7.24		5.20	7.32	7.79	7.90	6.13	4.31	5.97	4.72	6.66
15	7.00	7.25		5.16	7.37	7.79	7.92	6.26	4.41	5.69	4.74	6.71
16	7.02	7.25		5.20	7.41	7.82	7.98	6.40	4.54	5.60	4.77	6.74
17	7.05	7.26		5.26	7.44	7.85	8.05	6.33	4.67	5.51	4.87	6.76
18	7.11		6.62	5.31	7.49	7.92	8.09	6.29	4.74	5.20	4.98	6.67
19	7.16		6.67	5.38	7.53	7.92	7.89	6.35	4.81	5.18	5.09	6.64
20	7.23	7.37	6.72	5.47	7.62	7.92	7.86	6.36	4.96	5.19	5.15	6.57
21	7.27		6.82	5.55	7.66	7.93	7.84	6.40	5.08	5.21	5.24	6.50
22	7.34		6.83	5.61	7.68	7.98	7.90	6.00	5.13	5.20	5.32	6.48
23	7.39		6.84	5.72	7.68	8.02	7.95	5.74	5.21	5.20	5.38	6.49
24	7.42		6.87	5.79	7.69	8.10	7.97	5.21	5.29	5.21	5.47	6.48
25	7.43		6.92	5.85	7.72	8.12	8.00	5.07	5.37	5.15	5.57	6.49
26	7.46		6.98	5.90	7.79	8.14	8.09	4.94	5.49	5.12	5.67	6.51
27	7.51		6.99	6.01	7.82	8.17	8.17	4.53	5.56	5.14	5.74	6.56
28	7.59		7.01	6.08	7.86	8.20	8.22	4.42	5.66	4.80	5.80	6.62
29	7.64		7.03	6.12	7.91	7.99	8.23	4.44	5.75	4.64	5.85	6.69
30	7.66		7.06	6.18		7.78	7.00	4.53	5.98	4.55	5.97	6.74
31	7.67		7.09	6.21		7.75		4.53		4.55	5.99	
MEAN	7.01	7.37	6.89	5.98	7.24	7.86	7.92	5.66	4.71	5.63	4.97	6.49

WTR YR 1992 MEAN 6.43 HIGHEST 4.04 JUNE 9, 1992 LOWEST 8.23 APR. 28, 1992



RIO GRANDE DE LOIZA BASIN

181550065593200. Local number, 50.
LOCATION.--Lat 18°15'50", long 65°59'32", Hydrologic Unit 21010005, 1.36 mi northwest of Gurabo plaza, 0.70 mi north of Estación Experimental Agrícola, and 2.42 mi southwest of Escuela José M. Gallardo. Owner: Gurabo Agricultural

Experimental Station, Name: Gurabo.

AQUIFER.--Unconsolidated deposits of Quaternary Age.

WELL CHARACTERISTICS.--Drilled unused water-table well, diameter 13 in (0.34 m), cased 4 in (0.10 m), 0-145 ft (0-44.2 m). Depth 145 ft (44.2 m).

(0-44.2 m). Depth 145 ft (44.2 m).

INSTRUMENTATION. --Digital water level recorder--60-minute punch.

DATUM. --Elevation of land-surface datum is about 148 ft (45.1 m) above mean sea level, from topographic map.

Measuring point: Top of 12 in (0.30 m) casing, 0.80 ft (0.24 m) above land-surface datum.

REMARKS. --Observation well. Automatic digital recorder installed on September 18, 1991.


PERIOD OF RECORD. --December 1960 to March 1985, September 1991 to September 1992.

EXTREMES FOR PERIOD OF RECORD. --Highest water level measured, 12.6 ft (3.86 m) below land-surface datum, Sept. 9,

1975. lowest water level measured, 44.4 ft (13.8 m) below land-surface datum, June 18, 1975. 1975; lowest water level measured, 44.4 ft (13.5 m) below land-surface datum, June 18, 1975.

		WATER LEV	RL, IN FR	RT BELOW	LAND-SURF	ACE DATUM OBSERVAT	, WATER Y	YEAR OCTOBE	R 1991 T	O SEPTEMB	BR 1992	
				INST	ANTANBOUS	OBSERVAT.	TON AT 12	200				
DAY	OCT	NOA	DEC	JAN	FEB	MAR	APR	MAY	JUN	JUL	AUG	SEP
1	30.25	27.44	29.10	29.03	27.75	28.31	31.70	33.33	29.10	28.66	28.93	24.18
2	30.22	27.53	28.99	29.10	27.81	28.44	31.72	32.39	29.17	28.63	27.94	24.14
3	30.12	28.56	29.16	30.46	27.83	28.38	31.33	32.10	29.12	28.53	27.71	24.11
4	30.34	29.11	28.90	30.83	27.84	28.41	31.29	31.96	29.31	28.35	26.55	24.11
5	30.35	29.34	28.83	31.00	27.78	28.44	31.39	31.92	29.31	27.33	27.97	23.95
6	30.29	29.44	28.81	29.52	27.75	28.91	31.50	32.89	29.23	27.01	28.25	23.65
ž	30.21	29.34	28.89	28.76	27.78	28.61	31.61	33.00	29.27	28.03	24.42	22.71
é	30.14	29.29	28.92	28.41	27.90	28.63	31,67	33.01	29.37	28.30	23.46	22.05
9	30.06	29.14	28.91	28.28	27.96	28.64	31.72	33.02	29.31	28.42	22.87	23.06
10	29.99	29.23	28.92	28.31	27.96	28.69	32.14	32.92	25.45	28.58	22.54	23.32
				20.00	27 27	29.32	32.36	31.97	24.02	28.65	25.74	23.47
11	29.96	29.20	28.92	28.08	27.87 27.73	29.32	31.61	31.76	27.51	27.80	27.37	23.62
12	29.97	29.18	28.87	26.66	27.73	30.16	31.46	31.71	28.37	25.50	27.90	23.52
13	30.00	28.61	28.86	26.21		29.35	32.47	31.82	28.60	24.01	28.16	22.35
14	30.06	26.70	28.80	25.96	30.45		32.47	32.69	27.52	27.55	28.17	23.15
15	30.09	27.92	28.72	26.76	30.16	29.23	32.34	32.09	47.34	27.33	20.17	
16	30.13	28.58	28.77	27.17	30.12	29.25	31.74	32.81	26.39	27.90	24.92	26.03
17	30.23	28.82	28.83	27.39	30.07	29.29	31.59	31.58	26.42	28.15	23.62	26.93
18	31.34	29.02	28.86	27.52	30.07	29.35	32.43	30.85	26.96	28.28	26.97	27.48
19	30.36	29.11	28.82	27.68	30.06	29.35	32.69	31.13	26.49	28.36	23.99	27.69
20	30.23	29.10	28.86	27.75	30.07	29.89	31.92	30.97	28.18	28.39	23.09	27.82
21	30.21	29.03	28.78	27.80	30.05	30.08	32.24	29.71	26.57	28.83	22.74	27.71
22	30.17	28.99	28.76	27.83	28.58	30.22	32.72	30.24	26.11	28.56	26.58	27.76
23	29.89	29.09	28.69	27.86	28.19	30.31	33.17	30.19	25.89	28.66	26.50	27.98
24	29.71	29.10	28.72	27.83	28.06	30.40	33.69	30.11	28.28	28.72	26.59	27.70
25	29.72	29.01	28.82	27.81	28.00	30.47	33.16	29.91	28.78	28.74	27.46	27.79
			28.76	27.85	29.12	30.52	32.34	29.80	28.97	28.67	25.29	28.06
26	29.77	29.02				31.40	32.18	28.64	29.00	28.61	24.62	28.10
27	29.88	28.95	28.76	27.85	29.40	31.40	32.18	28.16	27.97	28.64	24.51	28.13
28	29.96	28.96	28.83	27.81	28.52		32.41	27.95	27.72	29.80	24.41	28.29
29	29.94	29.11	28.92	27.76	28.31	30.40	32.48	28.68	28.49	29.04	24.29	28.33
30	26.86	29.15	28.99	27.62		31.26		28.97	20.45	29.01	24.22	
31	25.97		29.16	27.68		32.19		40.7/	-	23.41	27.22	
MRAN	29.88	28.84	28.87	28.08	28.70	29.62	32.13	31.17	27.90	28.18	25.73	25.57

WTR YR 1992 MEAN 28.73 HIGHEST 22.05 SEPT. 8, 1992 LOWEST 33.99 APR. 24, 1992



RIO GRANDE DE LOIZA BASIN

182515065594100. Local number, 222.
LOCATION.--Lat 18°25'15", long 65°59'41", Hydrologic Unit 21010005, 3.56 mi northwest of Carolina plaza, 1.21 mi northwest of Escuela Extensión El Comandante, and 0.74 mi southwest of Escuela Vistamar. Owner: U.S. Geological Survey, WRD, Name: Campo Rico TW-1.
AQUIFER.--Surficial Deposits.

WELL CURPLOCREDIOSTICS --DWilled unused unter-table well disputer 4 in (0.10 m) Depth 100 ft /20 5 m)

AQUIFER.--Surficial Deposits.

WELL CHARACTERISTICS.--Drilled unused water-table well, diameter 4 in (0.10 m). Depth 100 ft (30.5 m).

INSTRUMENTATION.--Digital water level recorder--60-minute punch.

DATUM.--Elevation of land-surface datum is about 10.0 ft (3.05 m) above mean sea level, from topographic map.

Measuring point: Hole on side of casing, 0.80 ft (0.24 m) above land-surface datum. Prior July 28, 1986, top of shelter floor, 3.10 ft (0.94 m) above land-surface datum.


REMARKS.--Recording observation well.

PERIOD OF RECORD.--February 1986 to current year.

EXTREMES FOR PERIOD OF RECORD.--Highest water level recorded, 4.42 ft (1.35 m) below land-surface datum, Aug. 31, 1986; lowest water level recorded, 7.42 ft (2.26 m) below land-surface datum, Feb. 9, 1986.

		WATER LEVEL	, IN PERT	BELOW	Land-Surfa Tantaneous (DE DATUM	, WATER YE ION AT 120	LAR OCTOBER	1991	to september	1992	
DAY	OCT	NOV	DEC	JAN	FEB	MAR	APR	MAY	JUN	JUL	AUG	SEP
1	5.71	5.17	5.34	5.43	5.50	5.63	5.62	5.66	5.73	5.66	5.66	5.65
2	5.71	5.25	5.29	5.38	5.39	5.62	5.60	5.72	5.64	5.55	5.74	5.73
3	5.66	5.14	5.15	5.40	5.40	5.57	5.65	5.73	5.64	5.56	5.86	5.88
4	5.54	5.05	5.15	5.30	5.37	5.59	5.61	5.76	5.62	5.61	5.88	6.02
5	5.34	5.01	5.14	5.36	5.39	5.56	5.53	5.71	5.59	5.71	6.07	5.90
6	5.24	4.98	5.19	5.32	5.49	5.54	5.62	5.67	5.65	5.84	6.11	5.82
7	5.26	5.01	5.25	5.42	5.51	5.56	5.68	5.71	5.71	5.92	6.10	5.76
8	5.25	5.00	5.32	5.40	5.53	5.54	5.69	5.75	5.76	5.99	6.14	5.62
9	5.30	5.10	5.40	5.53	5.58	5.58	5.55	5.77	5.81	5.95	6.06	5.55
10	5.49	5.27	5.44	5.46	5.68	5.58	5.55	5.77	5.86	5.90	5.86	5.51
11		5.30	5.48	5.41	5.69	5.61	5.61	5.83	5.78	5.78	5.82	5.41
12		5.30	5.57	5.43	5.67	5.67	5.74	5.87	5.80	5.73	5.84	5.39
13		5.35	5.56	5.45	5.66	5.65	5.76	5.85	5.77	5.93	5.77	5.38
14		5.35	5.62	5.48	5.59	5.61	5.72	5.78	5.77	5.86	5.68	5.42
15		5.41	5.51	5.50	5.52	5.58	5.62	5.81	5.77	5.81	5.70	5.48
16		5.40	5.51	5.54	5.43	5.53	5.61	5.90	5.74	5.80	5.63	5.53
17		5.30	5.46	5.54	5.48	5.53	5.67	5.73	5.70	5.73	5.73	5.59
18		5.18	5.42	5.52	5.50	5.57	5.69	5.72	5.69	5.72	5.81	5.61
19		5.17	5.38	5.55	5.52	5.68	5.69	5.67	5.71	5.76	5.82	5.75
20		5.14	5.37	5.63	5.61	5.67	5.71	5.66	5.62	5.85	5.87	5.77
21		5.15	5.20	5.63	5.68	5.62	5.69	5.72	5.73	5.90	5.97	5.78
22		4.96	5.21	5.69	5.72	5.68	5.69	5.73	5.81	6.00	6.03	5.71
23		4.96	5.28	5.73	5.76	5.57	5.75	5.71	5.91	6.05	6.02	5.60
24		5.04	5.35		5.82	5.61	5.83	5.69	5.87	6.06	6.06	5.43
25		5.26	5.39	5.68	5.75	5.64	5.73	5.67	5.83	6.16	5.86	5.25
26		5.33	5.58	5.62	5.78	5.63	5.70	5.72	5.90	6.12	5.76	5.23
27		5.48	5.69	5.59	5.71	5.61	5.75	5.72	5.93	6.07	5.62	5.21
28		5.50	5.68	5.65	5.67	5.65	5.80	5.83	5.84	6.04	5.49	5.29
29		5.49	5.61	5.59	5.66	5.62	5.74	5.79	5.76	5.88	5.42	5.42
30	5.49	5.44	5.52	5.55		5.69	5.65	5.85	5.69	5.77	5.39	5.50
31	5.32		5.51	5.50		5.66		5.78		5.68	5.49	
MRAN	5.44	5.22	5.41	5.51	5.59	5.61	5.67	5.75	5.75	5.85	5.81	5.57

HIGHEST 4.74 OCT. 31, 1991 LOWEST 6.23 JULY 28, 1992 WTR YR 1992 MEAN 5.61



RIO GRANDE DE LOIZA BASIN

181513065554601. Local number, CJ-TW3B.

LOCATION.--Lat 18°15'13", long 65°55'46", Hydrologic Unit 21010005, 2.86 mi east of Gurabo plaza, 3.57 mi southwest of Hwy 186 km 4.7, and 1.39 mi southwest of Hwy 185 km 15.7. Owner: U.S. Geological Survey, WRD, Name: CJ-TW3B. AQUIFER:--Unconsolidated deposits of Quaternary Age.

WELL CHARACTERISTICS.--Drilled unused water-table well, diameter 4 in (0.10 m), cased 4 in (0.10 m), 0-38 ft (0-11.6 m) screened 25-35 ft (7.62 m). Depth 38 ft (11.6 m).

INSTRUMENTATION.--Digital water level recorder--60-minute punch.

DATUM.--Elevation of land-surface datum is about 187 ft (57.0 m) above mean sea level, from topographic map.

Measuring point: Top of casing 2.95 ft (0.90 m) above land-surface datum.

EMMARES.--Observation well. Automatic digital recorder installed on September 17, 1991.


REMARKS:--Observation well. Automatic digital recorder installed on September 17, 1991.

PERIOD OF RECORD.--September 1991 to September 1992.

EXTREMES FOR PERIOD OF RECORD.--Highest water level recorded, 13.4 ft (4.09 m) below land-surface datum, June 13-14, 1992; lowest water level recorded, 18.4 ft (5.61 m) below land-surface datum, May 1-2, 1992.

		WATER LEV	/RL, IN FRI		Land-Surf 'Antanbous				ER 1991 '	ro septemb	ER 1992	
DAY	oct	NOV	DEC	JAN	FRB	MAR	APR	MAY	JUN	JUL	λŪG	SEP
1	18.18	18.37	17.46	17.83	16.62	17.22	17.93	18.41	14.16	15.26	16.71	17.32
2	18.14	18.34	17.46	17.84	16.65	17.24	17.94	18.29	14.18	15.33	16.74	17.35
3	18.01	18.31	17.48	17.87	16.68	17.27	17.95	18.21	14.25	15.42	16.77	17.37
4	17.98	18.31	17.49	17.88	16.72	17.31	17.98	18.21	14.31	15.49	16.82	17.40
5	17.97	18.31	17.50	17.90	16.72	17.34	18.02	18.25	14.31	15.56	16.81	17.42
6	17.97	18.33	17.51	16.13	16.73	17.39	18.03	18.29	14.32	15.64	16.72	17.43
7	17.97	18.30	17.52	14.96	16.70	17.41	18.05	18.09	14.39	15.70	16.72	17.45
8	17.97	17.91	17.54	14.60	16.71	17.43	18.07	17.99	14.31	15.75	16.77	17.49
9	17.99	17.45	17.55	14.65	16.73	17.45	18.08	18.00	14.24	15.82	16.82	17.51
10	17.99	17.26	17.56	14.73	16.74	17.48	18.09	18.06	14.21	15.88	16.85	17.54
11	18.01	17.23	17.60	14.84	16.74	17.51	18.09	18.09	13.91	15.93	16.88	17.57
12	18.02	17.23	17.61	15.04	16.76	17.53	18.10	18.10	13.73	15.98	16.91	17.60
13	18.04	17.27	17.62	15.21	16.79	17.56	18.13	18.12	13.48	16.04	16.91	17.62
14	18.05	17.33	17.65	15.35	16.81	17.58	18.15	18.13	13.44	16.08	16.93	17.64
15	18.07	17.37	17.66	15.49	16.84	17.61	18.19	18.15	13.49	16.13	16.93	17.66
16	18.09	17.39	17.66	15.61	16.85	17.64	18.21	18.16	13.64	16.19	16.93	17.67
17	18.11	17.42	17.68	15.71	16.88	17.66	18.21	18.18	13.80	16.22	16.95	17.69
18	18.13	17.44	17.69	15.81	16.90	17.68	18.23	18.19	13.96	16.26	16.96	17.71
19	18.14	17.46	17.70	15.89	16.92	17.70	18.24	18.20	14.09	16.30	16.98	17.72
20	18.16	17.48	17.70	15.98	16.95	17.71	18.25	17.94	14.28	16.33	17.02	17.73
21	18.17	17.50	17.71	16.05	16.97	17.73	18.30	17.80	14.41	16.37	17.05	17.75
22	18.20	17.45	17.71	16.11	17.00	17.75	18.33	17.79	14.44	16.41	17.05	17.72
23	18.21	17.33	17.71	16.20	17.03	17.77	18.33	17.78	14.51	16.45	17.06	17.72
24	18.23	17.33	17.72	16.26	17.06	17.79	18.34	16.75	14.64	16.49	17.08	17.73
25	18.25	17.34	17.73	16.31	17.08	17.80	18.34	15.99	14.74	16.52	17.10	17.74
26	18.27	17.38	17.74	16.36	17.11	17.82	18.36	15.66	14.84	16.55	17.12	17.74
27	18.29	17.38	17.76	16.41	17.14	17.85	18.38	14.93	14.94	16.58	17.19	17.75
28	18.31	17.41	17.77	16.46	17.16	17.86	18.39	14.53	15.01	16.61	17.21	17.76
29	18.33	17.42	17.78	16.51	17.19	17.89	18.40	14.30	15.09	16.65	17.24	17.77
30	18.35	17.44	17.81	16.54		17.93	18.41	14.15	15.14	16.67	17.26	17.78
31	18.37		17.82	16.58				14.12		16.70	17.29	
mban	18.13	17.62	17.64	16.10	16.87	17.60	18.18	17.32	14.28	16.11	16.96	17.61

WTR YR 1992 MEAN 17.03 HIGHEST 13.43 JUNE 13-14, 1992 LOWEST 18.42 MAY 1-2, 1992



24.60

24.60

24.58

24.55

24.51

24.47

24.52

24.57

GROUND-WATER LEVELS

RIO GRANDE DE LOIZA BASIN

16

17

18

19

20

MRAN

24.60

24.63

24.65

24.65

24.59

23.80

23.83

23.87

23.93

24.10

181352066025300. Local number, CJ-TW19A.
LOCATION.--Lat 18°13'52", long 66°02'53", Hydrologic Unit 21010005, 0.96 mi southwest of Caguas plaza, 1.02 mi
northwest of Escuela Antonio S. Pedreira, and 0.30 mi southeast of Hwy 156 km 59.1. Owner: U.S. Geological Survey, WRD, Name: CJ-TW19A.

AQUIFER.--Unconsolidated deposits of Quaternary Age.
WELL CHARACTERISTICS.--Drilled unused water-table well, diameter 4 in (0.10 m), cased 4 in (0.10 m), 0-67 ft
(0-20.4 m), screened 50-65 ft (15.2-19.8 m). Depth 67 ft (20.4 m).
INSTRUMENTATION.--Digital water level recorder--60-minute punch.

DATUM.--Elevation of land-surface datum is about 262 ft (79.8 m) above mean sea level, from topographic map.
Measuring point: Top of casing 3.00 ft (0.91 m) above land-surface datum.
REMARKS.--Observation well drilled on September 1, 1989. Automatic digital recorder installed on September 18,

1991. Aquifer test conducted on Aug. 13, 1990.
PERIOD OF RECORD. -- to September 1992.
EXTREMES FOR PERIOD OF RECORD. -- Highest water level recorded, 114 ft (34.8 m) below land-surface datum, Apr. 24,, 1992; lowest water level recorded, 125 ft (37.1 m) below land-surface datum, Sept. 14, 1992.

WATER LEVEL, IN FRET BELOW LAND-SURFACE DATUM, WATER YEAR OCTOBER 1991 TO SEPTEMBER 1992 INSTANTANEOUS OBSERVATION AT 1200

DAY	OCT	NOV	DEC	JAN	FEB	MAR	APR	MAY	JUN	JUL	AUG	SEP
1	24.50	24.56	24.17	24.59	24.34	24.80	25.01	25.20	24.65			24.64
2	24.49	24.50	24.19	24.60	24.37	24.80	25.02	25.21	24.66			24.65
3	24.47	24.45	24.21	24.62	24.39	24.81	25.04	25.21	24.68			24.66
Ā	24.45	24.44	24.23	24.63	24.42	24.82	25.04	25.21	24.67			24.68
5	24.44	24.43	24.24	24.64	24.43	24.83	25.05	25.21	24.65			24.68
6	24.44	24.45	24.25	24.33	24.44	24.84	25.06	25.21	24.63			24.67
ž	24.45	24.43	24.26	24.13	24.47	24.85	25.08	25.23	24.61			24.66
8	24.47	24.28	24.27	24.07	24.49	24.86	25.08	25.23	24.60			24.66
9	24.49	24.07	24.29	24.06	24.51	24.87	25.09	25.23	24.56			24.63
10	24.51	23.99	24.31	24.06	24.53	24.88	25.10	25.23	24.54			24.61
11	24.52	23.92	24.33	24.07	24.53	24.89	25.10	25.23	24.51			24.59
12	24.54	23.91	24.35	24.09	24.55	24.90	25.11	25.23	24.46			24.57
13	24.55	23.93	24.37	24.10	24.57	24.91	25.12	25.23	24.39			24.57
14	24.57	23.84	24.39	24.12	24.58	24.92	25.12	25.23	24.32			24.57
15	24.58	23.81	24.40	24.15	24.60	24.93	25.12	25.25	24.29			24.59

24.94

24.96 24.97

24.97

24.96

25.13

25.14 25.14

25.15

25.15

25.12

25.25

25.25

25.22

25.19

25.17

25.09

24.28

24.26

24.26

24.26

24.29

24.46

24.43 25.15 25.15 24.32 24.52 21 24.70 24.00 24.09 24.68 24.92 24.49 24.69 24.71 24.73 25.16 25.16 25.12 25.10 24.34 24.35 ---24.53 24.37 22 24.71 24.11 24.91 24.04 24.53 24.20 24.90 23 24.70 24.03 24.49 24.13 24.90 25.16 24.37 ---24.55 24.13 24.69 24.50 24 24.04 24.16 24.57 24.90 25.16 24.89 ---24.10 24.58 24.09 24.82 24.74 24.90 25.17 26 24.68 24.07 24.52 24.22 25.18 25.18 ---24.60 24.60 24.09 24.10 27 24.76 24.92 24.74 _---24.53 24.25 24.69 24.11 ---24.69 24.67 28 24.71 24.12 24.54 24.27 24.77 24.94 ---24.61 24.12 24.96 24.98 25.18 29 24.72 24.14 24.54 24.29 24.78 ---25.19 24.66 ---24.62 24.14 24.70 24.57 24.30 24.32 30 24.15 24.60 24.58 24.99 24.65 ---24.64

24.90

MRAN 24.60 HIGHEST 23.78 NOV. 16, 1991 LOWEST 25.25 MAY 15-17, 1992 WTR YR 1992

24.59

24.18

24.14

24.08

24.08

24.08

24.23


24.41

24.43 24.45 24.46

24.39

24.61

24.63 24.64



RIO HUMACAO TO RIO SECO BASINS

175858066100200. Local number, 6.
LOCATION.--Lat 17°58'58", long 66°10'02", Hydrologic Unit 21010004, 4.23 mi northeast of Central Aguirre Church,
4.08 mi northeast of Colegio del Perpetuo Socorro Church, and 1.77 mi northwest of Hwy 3 km 144.2. Owner: Doctor Bruno, Name: Juana 5.
AQUIFER.--Alluvium of Quaternary Age.
WELL CHARACTERISTICS.--Drilled unused water-table well, diemeter 16 in (0.41 m). Depth 173 ft (52.74 m) reported,

WELL CHARACTERISTICS. -- Drilled unused water-table well, diemeter 16 in (0.41 m). Depth 173 rt (52.74 m) reported, 110 ft (33.54 m) measured.

INSTRUMENTATION. -- Digital water level recorder -- 60-minute punch.

DATUM. -- Elevation of land-surface datum is about 127 ft (38.7 m) above mean sea level, from topographic map. Measuring point: Top of shelter floor, 3.00 ft (0.91 m) above land-surface datum. After Aug. 7, 1981, top of 16 in (0.41 m) casing, 1.55 ft (0.47 m) above land-surface datum.

REMARKS. -- Recording observation well.


PERIOD OF RECORD. -- November 1960 to current year.

EXTREMENT FOR DEPTOR OF DECORD -- Highest water level recorded 26.20 ft (7.99 m) below land-surface datum. Dec. 10

EXTREMES FOR PERIOD OF RECORD. --Highest water level recorded, 26.20 ft (7.99 m) below land-surface datum, Dec. 10, 1979; lowest water level recorded, 65.95 ft (20.10 m) below land-surface datum, June 2, 1968.

		WATER LEV	EL, IN FE			ACE DATUM OBSERVAT		YEAR OCTOB	RR 1991 T	O SEPTEME	ER 1992	
DAY	OCT	NOV	DEC	Jan	FEB	MAR	APR	MAY	JUN	JUL	AUG	SEP
1	60.23	59.98	61.48	62.81	63.24	58.26	60.77	62.25	62.60	58.41	53.37	53.13
2	60.33	59.69	61.56	62.83	63.24	57.62	60.67	62.32	62.46	58.10	53.35	53.12
3	60.43	59.45	61.64	62.84	63.24	57.36	60.37	62.40	62.32	57.80	53.33	53.10
4	60.53	59.31	61.73	62.85		57.71	60.29	62.47	62.19	57.51	53.30	53.10
5	60.63	59.28	61.81	62.87		57.95	60.32	62.54	62.07	57.23	53.30	53.08
6	60.72	59.29	61.88	62.90	63.24	58.10	60.37	62.61	61.95	56.99	53.28	53.07
7	60.81	59.27	61.94	62.92	63.24	58.18	60.44	62.67	61.84	56.74	53.25	53.06
8	60.90	59.27	62.01	62.95	63.24	58.29	60.48	62.72	61.77	56.50	53.21	53.07
9	61.00	59.32	62.07	62.97	63.24	58.46	60.48	62.76	61.64	56.27	53.17	53.09
10	61.07	59.40	62.13	62.99	63.24	58.70	60.50	62.78	61.53	56.05	53.13	53.11
11	61.16	59.51	62.17	63.00	63.25	58.91	60.52	62.80	61.43	55.83	53.12	53.14
12	61.24	59.62	62.22	63.02	63.25	59.10	60.58	62.82	61.33	55.63	53.10	53.14
13	61.33	59.72	62.26	63.04	63.25	59.31	60.64	62.85	61.23	55.41	53.09	53.12
14	61.40	59.83	62.30	63.06	63.25	59.49	60.71	62.89	61.13	55.22	53.07	
15	61.49	59.94	62.35	63.08	63.25	59.65	60.80	62.91	61.03	55.03	53.05	
16	61.56	60.04	62.38	63.10	63.26	59.81	60.89	62.93	60.92	54.87	53.06	
17	61.64	60.14	62.42	63.11	63.26	59.96	60.99	62.95	60.82	54.67	53.06	53.04
18	61.71	60.24	62.46	63.13	63.26	60.10	61.09	62.98	60.72	54.49	53.07	52.93
19	61.78	60.35	62.50	63.14	63.26	60.23	61.18	63.00	60.61	54.32	53.08	52.85
20	61.85	60.44	62.53	63.15	63.25	60.33	61.27	63.04	60.50	54.19	53.11	52.77
21	61.92	60.54	62.56	63.17	63.23	60.40	61.37	63.07	60.39	54.06	53.13	52.74
22	61.99	60.64	62.59	63.18	63.15	60.46	61.47	63.09	60.27	53.95	53.27	52.72
23	62.06	60.74	62.61	63.19	63.03	60.53	61.58	63.11	60.14	53.86	53.30	52.74
24	62.12	60.83	62.64	63.21	62.96	60.61	61.67	63.13	60.01	53.77	53.31	52.77
25	62.17	60.92	62.66	63.22	62.88	60.69	61.76	63.16	59.85	53.69	53.29	52.81
26	62.14	61.02	62.68	63.22	62.28	60.78	61.85	63.16	59.67	53.62	53.28	52.83
27	61.95	61.12	62.70	63.23	61.36	60.81	61.94	63.16	59.46	53.57	53.24	52.86
28	61.62	61.21	62.72	63.23	60.21	60.73	62.02	63.11	59.22	53.52	53.22	52.90
29	61.18	61.30	62.74	63.24	59.16	60.67	62.09	63.01	58.96	53.47	53.19	52.94
30	60.72	61.39	62.77	63.24		60.67	62.17	62.89	58.71	53.43	53.17	52.99
31	60.32		62.79	63.24		60.72		62.75		53.40	53.15	
MRAN	61.29	60.13	62.30	63.07	62.84	59.50	61.04	62.85	60.89	55.21	53.20	52.97

WTR YR 1992 MEAN 59.64 HIGHEST 52.71 SEPT. 22, 1992 LOWEST 63.26 FEB. 15-20, 1992



RIO HUMACAO TO RIO SECO BASINS

180415065513900. Local number, 96.
LOCATION.--Lat 18°04'15°, long 65°51'39°, Hydrologic Unit 21010005, 2.44 mi northwest of Escuela Eugenio María de Hostos 4.67 mi southwest of Escuela Segunda Unidad Luciano, and 3.93 mi southwest of Escuela Asunción López.

Owner: P.R. Aqueduct and Sewer Authority, Name: USGS TW-2 or Yabucoa 7.

AQUIPER. -- Alluvium of Quaternary Age. AUDIFAN. --ALLUVIUM OF QUATERNARY Age.
WELL CHARACTERISTICS. --Drilled observation water-table well, diameter 16 in (0.41 m), cased 0-10 ft (0-3.05 m),
diameter 6 in (0.15 m), cased about 0-183 ft (0-55.79 m), perforated 56-81 ft (17.07-24.70 m), 102-123 ft
(31.10-37.50 m), 144-181 ft (43.90-55.18 m). Depth 181 ft (55.18 m).
INSTRUMENTATION. --Digital water level recorder--60-minute punch.
DATUM. --Elevation of land-surface datum is about 25 ft (7.62 m) above mean sea level, from topographic map.
Measuring point: Top of shelter floor, 4.00 ft (1.22 m) above land-surface.
REMARKS. --Recording observation well.

REMARKS.--Recording observation well.

PERIOD OF RECORD.--April 25, 1978 to current year.

EXTREMES FOR PERIOD OF RECORD.--Highest water level recorded, 13.10 ft (3.99 m) below land-surface datum, Dec. 2, 1987; lowest water level recorded, 28.29 ft (8.62 m) below land-surface datum, Sept. 20, 1980.

WATER LEVEL, IN FERT BELOW LAND-SURFACE DATUM, WATER YEAR OCTOBER 1991 TO SEPTEMBER 1992

INSTANTANEOUS OBSERVATION AT 1200 JUN JUL AUG SEP DAY OCT NOV JAN PRB APR MAY DRC MAR 22.62 22.48 22.43 21.82 18.25 19.42 16.36 19.70 ---------_--19.34 16.40 16.44 19.70 2 22.38 21.84 18.30 22.35 20.38 22.28 21.86 18.35 19.25 19.69 22.20 21.90 18.38 16.49 19.72 ___ ---22.19 20.39 ---------20.40 5 22.13 21.92 18.36 19.19 16.54 19.81 _---22.06 22.08 21.90 20.40 ------18.36 19.07 ---20.04 20.12 20.23 ___ 21.94 21.93 18.75 18.41 16.67 16.76 ---22.01 18.38 ---21.77 20.43 18.41 20.47 21.60 21.98 21.95 21.73 18.11 16.88 ---20.49 ------_---10 21.90 21.42 18.50 17.79 17.01 20.32 ---21.21 20.52 21.10 20.79 17.53 17.13 21.01 20.54 ---------_---12 21.76 18.63 17.31 17.25 20.48 ------20.79 20.54 ---_---21.69 21.63 20.51 18.71 18.77 17.12 16.95 17.36 17.46 20.55 20.56 20.55 ------13 14 15 20.36 ---___ 21.58 19.86 18.86 16.81 17.55 20.64 _------20.20 20.65 _---20.07 20.71 16 21.53 19.55 18.93 16.70 17.70 20.62 21.51 19.28 18.98 16.60 17.85 20.57 ------19.96 20.75 ------16.53 16.45 ---18 21.51 21.51 19.06 19.02 19.05 18.04 18.22 20.52 ------19.87 20.82 ------19.85 20.87 ---20.47 19 18.86 20 21.48 18.69 19.09 16.41 18.43 20.43 19.85 21.90 21 22 19.85 21.46 18.55 19.11 16.39 18.65 20.41 ------19.84 ------21.46 18.41 19.12 16.37 18.86 22.68 21.81 23 21.46 18.28 19.11 16.33 19.05 22.81 ------19.91 ------21.69 ___ ------24 25 21.47 18.16 19.12 16.28 19.21 23.02 ---19.97 21.56 18.04 21.35 21.50 19.15 16.24 19.34 23.23 26 27 21.22 21.55 18.02 19.23 16.21 19.43 23.31

23.28

23.25

23.15

23.07

23.00

21.15

_---

20.90

20.56

21.09

20.98

20.85

20.75

21.32

WTR YR 1992 MRAN 19.79 HIGHEST 16.20 JAN. 26-28, 1992 LOWEST 23.31 MAR. 26, 1992

19.50

19.58

19.67

17.81

16.20

16.20

16.22

16.26 16.31

17.29

19.30 19.37

19.44

19.50

19.49

18.85

21.62

21.73

21.76

21.78

21.80

21.77

28

29

30

31


MRAN

18.09

18.11

18.15

18.20



RIO SALINAS TO RIO JACAGUAS BASINS

32.75

33.09 33.62

32.98

34.10

34.24

33.86

35.33

35.31

35.80

35.50

29

30

MRAN

175829066232200. Local number, 87.
LOCATION.--Lat 17°58'29", long 66°23'22", Hydrologic Unit 21010004, 1.10 mi northeast of Santa Isabel plaza, 3.69 mi southeast of Escuela Playita Cortada, and 1.07 mi southeast of Estación Experimental Santa Isabel.

Owner: Francisco Alomar, Name: Alomar 1.

AQUIFER:--Alluvium of Quaternary Age.

WELL CHARACTERISTICS.--Drilled unused water-table well, diameter 20 in (0.51 m), iron cased. Depth 112 ft (34.14 m).

INSTRUMENTATION.--Digital water level recorder--60-minute punch.

DATUM.--Elevation of land-surface datum is 35.32 ft (10.77 m) above mean sea level.

Measuring point: Bottom of clean-out shelter door, 2.50 ft (0.76 m) above land-surface datum. Prior to August 1981, top of recorder shelter floor, 4.00 ft (1.22 m) above land-surface datum.

REMARKS.--Recording observation well.

PERIOD OF RECORD. --April 1967 to current year.

EXTREMES FOR PERIOD OF RECORD.--Highest water level recorded, 8.45 ft (2.58 m) below land-surface datum, Dec. 10, 1970; lowest water level recorded, 49.18 ft (14.99 m) below land-surface datum, July 27, 1974.

WATER LEVEL, IN FEET BELOW LAND-SURFACE DATUM, WATER YEAR OCTOBER 1991 TO SEPTEMBER 1992

	INSTANTANEOUS OBSERVATION AT 1200													
DAY	OCT	NOV	DEC	JAN	FRB	MAR	APR	MAY	JUN	JUL	AUG	SRP		
1	32.87	33.34	34.07	35.41	36.12	36.71	37.73	37.99	36.31	36.94	37.54	37.58		
2	33.14	33.06	34.61	35.60	35.98	36.83	37.71	38.04	36.43	36.89	37.47	37.65		
3	32.86	33.36	34.90	36.49	36.02	37.13	37.78	37.89	36.06	37.01	37.35	37.65		
4	32.80	33.63	35.20	35.86	36.23	37.05	37.66	37.93	36.18	36.89	37.56	37.85		
5	32.99	33.86	35.66	35.75	36.59	37.08	37.54	38.02	36.13	36.70	37.48	37.86		
6	32.52	33.54	35.83	35.32	36.34	37.13	37.67	38.20	36.30	36.87	37.29	37.74		
7	32.56	33.27	35.27	35.10	36.21	37.29	37.85	38.18	36.14	36.98	37.17	37.61		
8	32.70	33.16	34.92	34.95	36.07	37.52	37.76	38.14	36.35	37.06	37.11	37.68		
9	32.73	33.12	35.70	34.86	35.96	37.14	38.00	38.24	36.43	36.92	37.07	37.72		
10	32.42	33.09	36.07	34.82	35.99	37.36	37.97	38.05	36.59	37.06	37.15	37.68		
11	32.30	33.44	36.17	34.87	36.20	37.33	37.87	37.97	36.59	36.98	37.25	37.56		
12	32.30	33.44	36.26	34.75	36.23	37.61	37.73	38.23	36.41	36.94	37.18	37.76		
13	32.81	33.69	36.00	34.79	36.12	37.40	37.87	38.28	36.41	36.91	37.21	37.84		
14	32.46	33.71	35.46	35.38	36.43	37.32	38.13	38.44	36.29	37.16	37.39	37.79		
15	33.17	33.95	35.07	35.26	36.30	37.45	38.01	38.39	36.26	37.15	37.28	37.97		
16	33.28	34.04	35.73	35.42	36.34	37.40	38.00	38.28	36.48	37.17	37.38	37.84		
17	33.19	33.69	36.05	35.39	36.36	37.54	37.98	37.97	36.55	37.17	37.30	37.66		
18	33.28	34.00	36.38	35.34	36.49	37.59	37.88	37.92	36.68	37.12	37.39	37.56		
19	33.47	34.21	35.84	35.23	36.67	37.74	38.11	37.93	36.63	36.98	37.66	37.80		
20	33.48	34.35	35.38	35.41	36.65	37.70	37.89	38.01	36.70	37.16	37.46	37.80		
21	33.80	34.41	35.19	35.86	36.86	37.55	37.89	38.19	36.51	37.44	37.50	37.59		
22	33.67	34.38	35.22	36.14	36.69	37.42	37.82	38.09	36.36	37.29	37.51	37.49		
23	33.36	34.47		35.74	36.50	37.34	37.89	37.97	36.43	37.22	37.66	37.44		
24	33.20	34.24	35.72	35.74	36.47	37.56	37.76	37.76	36.53	37.37	37.74	37.40		
25	33.32	35.04	35.52	35.62	36.64	37.46	38.04	37.53	36.77	37.26	37.86	37.51		
26	32.76	34.60	35.27	35.67	36.90	37.51	38.00	37.18	36.65	37.15	37.92	37.38		
27	32.64	34.24	35.48	35.96	36.92	37.71	37.86	36.91	36.52	37.17	37.76	37.27		
28	32.91	34.20	35.68	36.18	36.93	37.63	38.09	36.75	36.48	37.50	37.76	37.24		

37.47

37.39

36.57

36.66

37.81

38.30

38.07

37.90

37.73

37.62

37.14

36.58

36.72

36.45

37.71

37.61 37.52

37.46

37.16

37.21

37.61

WTR YR 1992 MEAN 36.34 HIGHEST 32.27 OCT. 12, 1991 LOWEST 38.52 MAY 14, 1992


36.86

36.42

36.03

36.06

36.30



RIO SALINAS TO RIO JACAGUAS BASINS

180002066132200. Local number, HW-TW-01.

LOCATION.--Lat 18°00'02", long 66°13'22", Hydrologic Unit 21010004, 3.30 mi southwest of Cerro Guaraco, 8.71 mi southwest of Cayey plaza, and 2.80 mi southeast of Hwy 1 km 82.3 on Rabo del Buey. Owner: U.S. Geological Survey, WRD, Name: HW-TW-01.

AQUIFER.--Fractured, volcanic rock, water-table aquifer.

WELL CHARACTERISTICS.--Drilled observation well, diameter 7 in (0.18 m), 0-39.5 ft (0-12.0 m), cased 4 in (0.10 m), 0-38.2 ft (0-11.6 m), screened 32-37 ft (9.75-11.3 m). Depth 39.5 ft (12.0 m).

INSTRUMENTATION.--Digital water level recorder--60-minute punch.

DATUM --Elevation of land-surface datum is 190 ft (58.0 m) above warn see level.

DATUM.--Elevation of land-surface datum is 190 ft (58.0 m) above mean sea level.

Measuring point: Hole on side of 4 in (0.10 m) casing, 2.84 ft (0.87 m) above land-surface datum. Prior October
13, 1988, top of shelter floor, 3.48 ft (1.06 m) above land-surface datum.


REMARKS.--Recording observation well.

PERIOD OF RECORD.--April 14, 1988 to current year.

EXTREMES FOR PERIOD OF RECORD.--Highest water level recorded, 19.34 ft (5.89 m) below land-surface datum, Dec. 18, 1990 to Jan. 26, 1991; lowest water level recorded, 31.45 ft (9.58 m) below land-surface datum, May 21-22, 1992.

		WATER LEV	EL, IN FE			ACE DATUM OBSERVAT		RAR OCTOBE	R 1991 T	O SEPTEMB	ER 1992	
DAY	OCT	NOV	DBC	JAN	PRB	MAR	APR	MAY	JUN	JUL	AUG	SEP
1	26.28	27.28	28.12	28.96	29.69	30.28	27.44	27.68		24.94	25.86	26.14
2	26.32	27.32	28.14	28.98	29.72	30.30	27.44	27.69		24.95	25.89	26.16
3	26.35	27.35	28.17	29.00	29.74	30.32	27.45	27.70		24.97	25.92	26.18
4	26.39	27.38	28.21	29.03	29.76	30.33	27.46	27.71		25.00	25.94	26.21
5	26.42	27.41	28.23	29.05	29.78	30.35	27.47	27.73		25.03	25.97	26.22
6	26.45	27.44	28.25	29.08	29.80	30.37	27.48	27.75		25.07	25.99	26.24
7	26.48	27.47	28.28	29.11	29.82	30.39	27.49	27.78		25.10	25.99	26.26
8	26.52	27.50	28.30	29.14	29.84	30.40	27.50	27.79		25.13	25.99	26.28
9	26.56	27.52	28.32	29.16	29.86	30.42	27.51	27.82		25.16	25.99	26.31
10	26.59	27.52	28.35	29.18	29.88	30.44	27.52	27.85		25.19	25.98	26.33
11	26.62	27.54	28.39	29.20	29.91	30.45	27.53	27.86		25.22	25.97	26.35
12	26.66	27.57	28.42	29.23	29.93	30.47	27.54	27.88		25.2 5	25.97	26.37
13	26.69	27.60	28.46	29.25	29.95	30.49	27.56	27.93		25.28	25.96	26.39
14	26.72	27.63	28.48	29.27	29.96	30.51	27.57	27.99		25.31	25.94	26.40
15	26.74	27.66	28.50	29.30	29.99	30.53	27.57	28.01		25.34	25.93	26.43
16	26.78	27.69	28.54	29.33	30.01	30.54	27.58	28.03		25.38	25.92	26.43
17	26.82	27.72	28.57	29.35	30.03	30.56	27.59	28.03		25.41	25.92	26.42
18	26.85	27.74	28.59	29.38	30.05	30.58	27.60	28.04		25.44	25.92	26.43
19	26.87	27.78	28.62	29.40	30.07	30.59	27.61	28.04		25.47	25.92	26.44
20	26.91	27.81	28.65	29.43	30.09	30.61	27.61	28.04		25.49	25.92	26.43
21	26.94	27.84	28.68	29.45	30.11	30.63	27.63	28.04		25.52	25.93	26.43
22	26.97	27.87	28.70	29.47	30.13	30.64	27.64	28.44		25.55	25.9 5	26.43
23	27.00	27.89	28.72	29.50	30.14		27.64	28.44		25.59	25.96	26.42
24	27.03	27.92	28.74	29.53	30.16		27.64	28.44	24.82	25.63	25.97	26.42
25	27.06	27.95	28.77	29.55	30.18		27.64	28.42	24.81	25. 6 6	25.99	26.41
26	27.08	27.98	28.79	29.57	30.20		27.64		24.82	25.68	26.01	26.39
27	27.12	28.01	28.82	29.59	30.22		27.65		24.83	25.71	26.04	26.38
28	27.16	28.05	28.85	29.61	30.24		27.66		24.87	25.74	26.06	26.37
29	27.19	28.07	28.87	29.63	30.25		27.66		24.88	25.77	26.07	26.35
30	27.22	28.09	28.90	29.65			27.66		24.90	25.80	26.09	26.35
31	27.25		28.93	29.67						25.83	26.12	
MEAN	26.78	27.69	28.53	29.32	29.98	30.46	27.57	27.97	24.85	25.37	25.97	26.35

WTR YR 1992 MEAN 27.67 HIGHEST 24.81 JUNE 24-26, 1992 LOWEST 30.65 MAR. 22-23, 1992



MRAN

50.14

50.83

51.53

GROUND-WATER LEVELS

RIO SALINAS TO RIO JACAGUAS BASINS

180001066122002 Local number, HW-TW-03C.
LOCATION.--Lat 18°00'01", long 66°12'20", Hydrologic Unit 21010004, 8.27 mi southwest of Cayey plaza, 2.38 mi southwest of Cerro Garau, and 3.45 mi southeast of Hwy 1 km 82.3. Owner: U.S. Geological Survey, WRD, Name: HW-TW-03C.

AQUIFER.--Fractured, volcanic rock, water-table aquifer.
WELL CHARACTERISTICS.--Drilled observation well, diameter 7 in (0.18 m), 0-220 ft (0-67.0 m), cased 4 in (0.10 m),
0-150 ft (0-45.7 m), open hole 150-220 ft (45.7-67.0 m). Depth 220 ft (67.0 m).

INSTRUMENTATION. -- Digital water level recorder -- 60-minute punch.

DATUM. -- Elevation of land-surface datum is 270 ft (82.6 m) above mean sea level.

Measuring point: Top of shelter floor, 3.32 ft (1.01 m) above land-surface datum.

REMARKS.--Recording observation well. Aquifer test performed during May 24, 25, 26, 1989.

PERIOD OF RECORD.--December 15, 1988 to current year.

EXTREMES FOR PERIOD OF RECORD.--Highest water level recorded, 26.29 ft (8.01 m) below land-surface datum, Dec. 15, 1990; lowest water level recorded, 54.60 ft (16.6 m) helow land-surface datum, Oct. 3-4, 1990.

		WATER LE	VEL, IN F			ACE DATUM OBSERVAT		YEAR OCTOB	ER 1991	TO SEPTEME	ER 1992	
						ODDENANI						
DAY	OCT	MOA	DEC	JAN	FEB	MAR	APR	MAY	JUN	JUL	AUG	SEP
1	49.62	50.61	51.20	51.85	52.37	52.88	53.28	53.65	52.98	52.35	52.29	52.33
2	49.69	50.68	51.23	51.86	52.39	52.89	53.27	53.70	52.88	52.27	52.31	52.35
3 4	49.78	50.70	51.27	51.90	52.41	52.90	53.30	53.69	52.82	52.24	52.31	52.36
4	49.82	50.73	51.28	51.91	52.44	52.89	53.28	53.65	52.76	52.27	52.32	52.39
5	49.85	50.82	51.31	51.93	52.48	52.90	53.29	53.63	52.69	52.30	52.35	52.40
6	49.89	50.74	51.32	51.84	52.40	52.88	53.28	53.61	52.67	52.34	52.19	52.41
7	49.93	50.59	51.35	51.87	52.40	52.87	53.25	53.65	52.67	52.38	52.20	52.45
8	49.95	50.58	51.37	51.89	52.44	52.86	53.26	53.69	52.65	52.38	52.25	52.47
9	49.98	50.58	51.38	51.90	52.47	52.84	53.30	53.74	52.63	52.39	52.25	52.47
10	49.97	50.58	51.40	51.91	52.49	52.86	53.30	53.76	52.62	52.41	52.29	52.48
11	49.97	50.60	51.42	51.91	52.51	52.88	53.34	53.79	52.61	52.42	52.28	52.49
12	50.00	50.63	51.44	51.95	52.53	52.91	53.40	53.79	52.60	52.43	52.29	52.51
13	50.02	50.67	51.47	51.95	52.56	52.95	53.45	53.81	52.57	52.41	52.30	52.49
14	50.04	50.72	51.49	51.95	52.60	53.01	53.45	53.84	52.53	52.39	52.27	52.46
15	50.06	50.76	51.49	51.99	52.65	53.07	53.47	53.81	52.49	52.38	52.21	52.45
16	50.12	50.76	51.51	52.04	52.69	53.10	53.50	53.82	52.45	52.38	52.19	52.46
17	50.19	50.78	51.53	52.09	52.70	53.13	53.50	53.79	52.42	52.36	52.21	52.45
18	50.23	50.84	51.57	52.14	52.73	53.16	53.49	53.78	52.37	52.35	52.24	52.48
19	50.25	50.92	51.63	52.18	52.73	53.13	53.44	53.76	52.35	52.36	52.26	52.49
20	50.30	50.95	51.69	52.20	52.70	53.08	53.39	53.76	52.35	52.37	52.27	52.48
21	50.35	51.00	51.73	52.21	52.68	53.04	53.33	53.77	52.32	52.35	52.32	52.37
22	50.37	51.03	51.72	52.22	52.66	53.06	53.37	53.77	52.32	52.36	52.32	52.43
23	50.38	51.03	51.70	52.22	52.66	53.07	53.42	53 .77	52.32	52.39	52.35	52.45
24	50.39	51.03	51.71	52.21	52.69	53.08	53.42	53.59	52.32	52.40	52.38	52.47
25	50.40	51.02	51.71	52.21	52.74	53.09	53.41	53.62	52.35	52.41	52.43	52.48
26	50.39	51.04	51.73	52.22	52.75	53.10	53.49	53.38	52.38	52.41	52.45	52.51
27	50.38	51.09	51.74	52.24	52.78	53.12	53.56	53.28	52.39	52.44	52.48	52.50
28	50.47	51.11	51.74	52.25	52.82	53.18	53.58	53.21	52.41	52.45	52.44	52.48
29	50.49	51.13	51.76	52.27	52.83	53.23	53.59	53.16	52.41	52.42	52.42	52.50
30	50.51	51.17	51.79	52.29		53.26	53.61	53.12	52.39	52.37	52.36	52.48
31	50.55		51.83	52.33		53.27		53.06		52.32	52.34	

53.02

53.40

53.63

52.52


52.37

52.31

52.45

WTR YR 1992 MEAN 52.24 HIGHEST 49.57 OCT. 1, 1991 LOWEST 53.85 MAY 14, 1992

52.60



RIO SALINAS TO RIO JACAGUAS BASINS

175947066130601 Local number, HW-TW-05B.
LOCATION.--Lat 17°59'47", long 66°13'06", Hydrologic Unit 21010004, 2.70 mi northeast of Central Aguirre Church,
6.16 mi northwest of Escuela de Guayama, and 2.70 mi northeast of Hwy 3 km 151.3. Owner: U.S. Geological Survey, WRD, Name: HW-TW-05B.

AQUIFER.--Fractured, volcanic rock, water-table aquifer.

WELL CHARACTERISTICS.--Drilled observation well, diameter 7 in (0.18 m), 0-52 ft (0-15.8 m), cased 4 in (0.10 m),

0-51 ft (0-15.5 m), screened 41-46 ft (12.5-14.0 m). Depth 52 ft (15.8 m).

INSTRUMENTATION.--Digital water level recorder--60-minute punch.

DATUM.--Elevation of land-surface datum is 145 ft (44.2 m) above mean sea level.

Measuring point: Hole on side of casing, 3.00 ft (0.91 m) above land-surface datum. Prior October 13, 1989 top
of shelter floor, 3.47 ft (1.06 m) above land-surface datum.


REMARKS.--Recording observation well.

PERIOD OF RECORD.--April 13, 1988 to current year.

EXTREMES FOR PERIOD OF RECORD.--Highest water level recorded, 7.89 ft (2.40 m) below land-surface datum, May 26, 1992; lowest water level recorded, 22.14 ft (6.75 m) below land-surface datum, Sept. 5, 1990.

		WATER LEV	el, in fe	T BELOW	Land-Surf Antanbous	ACE DATUM	, WATER Y	EAR OCTOB	ER 1991 '	TO SEPTEMB	BR 1992	
DAY	oct	NOV	DEC	JAN	FEB	MAR	APR	мач	JUN	JUL	AUG	SEP
	13.00	13.98	13.19	14.47	14.98	15.79	16.38	16.36	11.28	13.50	14.76	14.99
1	13.00	13.98	13.19	14.49	14.98	15.79	16.38	16.38	11.50	13.50	14.80	15.04
2 3	13.02	14.05	13.25	14.54	15.01	15.84	16.38	16.42	11.70	13.59	14.81	15.05
4	13.00	14.08	13.32	14.57	15.04	15.87	16.38	16.44	11.63	13.65	14.82	15.08
5	13.12	14.10	13.32	14.60	15.10	15.90	16.39	16.48	11.97	13.70	14.89	15.10
3	13.12	14.10	13.37	14.60	15.10	13.90	10.33	10.40	11.5	23.70	24.05	
6	13.14	14.14	13.42	14.59	15.11	15.92	16.40	16.51	12.10	13.76	14.65	15.12
7	13.18	13.79	13.47	14.48	15.12	15.95	16.40	16.55	12.24	13.83	14.51	15.15
8	13.23	13.38	13.52	14.45	15.15	15.97	16.41	16.57	12.36	13.87	14.46	15.18
9	13.29	12.91	13.57	14.45	15.18	16.00	16.41	16.60	12.47	13.91	14.43	15.20
10	13.27	12.44	13.62	14.44	15.21	16.02	16.42	16.63	12.57	13.96	14.41	15.20
11	13.25	12.27	13.67	14.44	15.24	16.04	16.44	16.66	12.65	14.00	14.41	15.23
12	13.25	12.20	13.73	14.44	15.27	16.06	16.46	16.67	12.73	14.04	14.39	15.27
13	13.26	12.18	13.77	14.45	15.30	16.08	16.45	16.70	12.77	14.08	14.38	15.29
14	13.29	12.18	13.81	14.47	15.33	16.10	16.44	16.74	12.79	14.12	14.38	15.31
15	13.32	12.21	13.86	14.49	15.35	16.12	16.43	16.70	12.85	14.17	14.38	15.36
16	13.36	12.26	13.91	14.53	15.37	16.15	16.42	16.61	12.90	14.20	14.39	15.39
17	13.41	12.31	13.94	14.57	15.40	16.17	16,42	16.55	12.94	14.25	14.44	15.41
18	13.46	12.40	13.98	14.59	15.43	16.18	16.42	16.53	12.98	14.27	14.48	15.43
19	13.49	12.49	14.03	14.63	15.47	16.20	16.43	16.53	13.01	14.30	14.51	15.47
20	13.53	12.56	14.06	14.67	15.50	16.22	16.43	16.53	13.08	14.33	14.54	15.47
										44.36	14.58	15.30
21	13.59	12.64	14.11	14.69	15.53	16.22	16.35	16.56	13.14	14.36	14.50	15.13
22	13.62	12.72	14.14	14.72	15.55	16.23	16.30	16.60	13.10	14.39 14.44	14.65	15.13
23	13.66	12.78	14.17	14.75	15.58	16.26	16.28	16.61	13.10		14.71	15.04
24	13.70	12.85	14.19	14.77	15.63	16.29	16.27	15.58	13.11	14.49	14.74	15.04
25	13.73	12.89	14.24	14.80	15.65	16.29	16.26	14.34	13.16	14.51	14.74	15.03
26	13.76	12.96	14.27	14.82	15.68	16.30	16.27	7.89	13.20	14.53	14.77	15.03
27	13.79	13.03	14.30	14.87	15.70	16.32	16.31	8.83	13.26	14.58	14.81	15.03
28	13.83	13.05	14.34	14.90	15.73	16.34	16.33	9.62	13.31	14.61	14.86	15.03
29	13.87	13.09	14.37	14.92	15.76	16.35	16.33	10.20	13.38	14.64	14.90	15.04
30	13.89	13.14	14.41	14.94		16.37	16.35	10.66	13.44	14.70	14.93	15.06
31	13.94		14.45	14.95		16.38		10.98		14.73	14.97	
MRAN	13.43	12.97	13.86	14.63	15.36	16.12	16.38	15.13	12.70	14.16	14.62	15.18

WTR YR 1992 MRAN 14.54 HIGHEST 7.89 MAY 26, 1992 LOWEST 16.75 MAY, 14-15, 1992



RIO SALINAS TO RIO JACAGUAS BASINS

175957066123400 Local number, HW-TW-13.
LOCATION.--Lat 17°59'57", long 66°12'34", Hydrologic Unit 21010004, 3.11 northeast of Central Aguirre Church, 5.76 mi northwest of Escuela de Guayama, and 2.03 mi northeast of Hwy 3 km 151.3. Owner: U.S. Geological Survey, WRD,

Name: HW-TW-13.

AQUIFER.--Fractured, volcanic rock, water-table aquifer.

WELL CHARACTERISTICS.--Drilled observation well, diameter 7 in (0.18 m), 0-69 ft (0-21.0 m), cased 4 in (0.10 m), 0-69 ft (0-21.0 m), screened 4.0-69 ft (1.22-21.0 m). Depth 69 ft (21.0 m).

INSTRUMENTATION. -- Digital water level recorder -- 60-minute punch.

DATUM. -- Elevation of land-surface datum is 203 ft (61.9 m) above mean sea level.

Measuring point: Hole on side of casing, 2.33 ft (0.71 m) above land-surface datum. Prior October 14, 1988, top of shelter floor, 3.47 ft (1.06 m) above land-surface datum.


REMARKS.--Recording observation well.

PERIOD OF RECORD.--April 14, 1988 to current year.

EXTREMES FOR PERIOD OF RECORD.--Highest water level recorded, 34.39 ft (10.5 m) below land-surface datum, Oct. 27, 1990; lowest water level recorded, 47.74 ft (14.6 m) below land-surface datum, Sept. 15, 1992.

		WATER I	EVEL, IN F		Land-Sure Tantanbous				1991	TO SEPTEMBER	1992	
				142	1 AMI AMEOUS	ODSERVAI	TOR AT 1	200				
DAY	oct	NOV	DEC	JAN	FRB	MAR	APR	MAY	JUN	JUL	AUG	SEP
1	45.82	45.87	45.80	46.06	46.15	46.19	46.37	46.51				
2	45.82	45.88	45.80	46.06	46.15	46.20	46.38	46.51				
3	45.82	45.88	45.81	46.06	46.15	46.21	46.38	46.51				
4	45.83	45.88	45.81	46.06	46.15	46.21	46.38	46.52				
5	45.83	45.91	45.83	46.06	46.17	46.22	46.38	46.53				
6	45.82	45.91	45.83	46.06	46.17	46.23	46.38	46.53				
7	45.82	45.91	45.83	46.08	46.17	46.23	46.39	46.53				
8	45.83	45.91	45.84	46.08	46.17	46.25	46.40	46.50				
9	45.83	45.91	45.84	46.08	46.17	46.26	46.40	46.47				
10	45.83	45.92	45.85	46.08	46.17	46.27	46.41	46.45				
11	45.84	45.79	45.89	46.08	46.17	46.28	46.41	46.42				
12	45.84	45.70	45.90	46.08	46.17	46.28	46.42	46.39				
13	45.84	45.67	45.91	46.08	46.17	46.28	46.43	46.38				
14	45.84	45.66	45.93	46.08	46.18	46.28	46.44	46.34				
15	45.84	45.66	45.95	46.08	46.19	46.28	46.44	46.31				
16	45.84	45.66		46.09	46.19	46.29	46.44	46.28				47.66
17	45.84	45.67	45.96	46.10	46.19	46.30	46.44	46.26				47.67
18	45.83	45.70		46.10	46.19	46.31	46.44	46.22				47.68
19	45.84	45.72		46.10	46.19	46.32	46.44	46.19				47.68
20	45.84	45.73	46.00	46.10	46.19	46.32	46.44	46.17				47.71
21	45.84	45.74		46.10	46.19	46.33	46.44	46.15				47.71
22	45.84	45.75		46.10	46.19	46.33	46.44	46.13				47.72
23	45.85	45.76		46.10	46.19	46.33	46.45	46.10				47.72
24	45.85	45.77		46.12	46.19	46.36	46.45	46.10				47.70
25	45.85	45.77	46.03	46.12	46.19	46.36	46.46	46.01				47.66
26	45.85	45.78		46.12	46.19	46.37	46.46					47.65
27	45.87	45.78		46.12	46.19	46.37	46.48					47.65
28	45.87	45.79		46.13	46.19	46.37	46.50					47.67
29	45.87	45.79		46.13	46.19	46.37	46.51					47.68
30	45.86	45.80		46.13		46.37	46.51					47.70
31	45.86		46.05	46.14		46.37						
MEAN	45.84	45.79	45.94	46.09	46.18	46.29	46.43	46.34				47.68

WTR YR 1992 MEAN 46.20 HIGHEST 45.66 NOV. 14-17, 1991 LOWEST 47.74 SEPT. 15, 1992



RIO SALINAS TO RIO JACAGUAS BASINS

175946066102000 Local number, HW-TW-14.

LOCATION.--Lat 17°59'46", long 66°10'20", Hydrologic Unit 21010004, 4.42 northeast of Central Aguirre Church, 3.41 mi northwest of Escuela de Guayama, and 2.01 mi northeast of Hwy 3 km 146.3. Owner: U.S. Geological Survey, WRD,

Name: HW-TW-14.
AQUIFER.--Fractured, volcanic rock, water-table aquifer.
WELL CHARACTERISTICS.--Drilled observation well, diameter 7 in (0.18 m), 0-79 ft (0-24.4 m), cased 4 in (0.10 m), 0-79 ft (0-24.1 m), screened 71-78 ft (21.6-23.8 m). Depth 79 ft (24.1 m).

0-79 ft (0-24.1 m), screened 71-78 ft (21.6-23.8 m). Depth 79 ft (24.1 m).

INSTRUMENTATION.--Digital water level recorder--60-minute punch.

DATUM.--Elevation of land-surface datum is 205 ft (62.5 m) above mean sea level.

Measuring point: Hole on side of casing, 3.02 ft (0.92 m) above land-surface datum. Prior October 7, 1988, top of shelter floor, 3.67 ft (1.12 m) above land-surface datum.

REMARKS.--Recording Observation well. Well dry at 73.56 ft (22.42 m).


PERIOD OF RECORD.--December 1987 to current year.

PERIOD OF RECORD.--December 1987 to current year.

EXTREMES FOR PERIOD OF RECORD. --Highest water level measured, 41.1 ft (12.5 m) below land-surface datum, Dec. 17, 1987; lowest water level recorded, 75.35 ft (23.0 m) below land-surface datum, Oct. 2, 1989.

WATER LEVEL, IN FEET BELOW LAND-SURFACE DATUM, WATER YEAR OCTOBER 1991 TO SEPTEMBER 1992 INSTANTANEOUS OBSERVATION AT 1200													
DAY	OCT	NOV	DEC	JAN	PRB	MAR	APR	MAY	JUN	JUL	AUG	SEP	
1	73.61	73.61	72.49	72.93	72.03	73.79	73.81	73.81	73.76	73.76	73.76	61.86	
2	73.61	73.61	72.48	72.97	72.08	73.80	73.81	73.81	73.76	73.76	73.76	61.92	
3	73.61	73.61	72.46	73.03	72.14	73.80	73.81	73.81	73.76	73.76	73.76	62.02	
4	73.61	73.60	72.45	73.13	72.20	73.80	73.81	73.81	73.76	73.76	73.76	62.11	
5	73.61	73.60	72.42	73.20	72.24	73.80	73.81	73.81	73.76	73.76	73.76	62.18	
6	73.61	73.60	72.40	73.28	72.26	73.80	73.81	73.81	73.76	73.76	73.76	62.24	
7	73.61	73.60	72.37	73.36	72.27	73.80	73.81	73.81	73.76	73.76	73.76	62.32	
8	73.61	73.60	72.35	73.43	72.28	73.80	73.81	73.81	73.76	73.76	73.76	62.40	
9	73.61	73.60	72.33	73.44	72.28	73.80	73.81	73.81	73.76	73.76	73.76	62.46	
10	73.61	73.60	72.31	73.43	72.36	73.80	73.81	73.81	73.76	73.76	73.76	62.56	
11	73.61	73.60	72.31	73.34	72.45	73.80	73.81	73.81	73.76	73.76	73.76	62.61	
12	73.61	73.60	72.30	73.11	72.50	73.80	73.81	73.81	73.76	73.76	73.76	62.69	
13	73.61	73.60	72.29	72.85	72.54	73.80	73.81	73.81	73.76	73.76	73.76	62.76	
14	73.61	73.60	72.28	72.67	72.59	73.80	73.81	73.81	73.76	73.76	73.76	62.80	
15	73.61	73.60	72.29	72.51	72.64	73.80	73.81	73.81	73.76	73.76	73.76	62.88	
16	73.61	73.60	72.29	72.06	72.71	73.80	73.81	73.81	73.76	73.76	73.76	62.97	
17	73.61	73.61	72.29	71.96	72.79	73.80	73.81	73.81	73.76	73.76	73.76	63.06	
18	73.61	73.54	72.30	71.88	72.87	73.80	73.81	73.81	73.76	73.76	73.76	63.16	
19	73.61	73.34	72.30	71.81	72.95	73.80	73.81	73.81	73.76	73.76	73.76	63.28	
20		73.18	72.30	71.76	73.03	73.80	73.81	73.81	73.76	73.76	61.39	63.40	
21		73.06	72.33	71.73	73.10	73.80	73.81	73.81	73.76	73.76	61.37	63.52	
22		72.86	72.34	71.70	73.18	73.80	73.81	73.79	73.76	73.76	61.36	63.55	
23		72.74	72.37	71.70	73.26	73.80	73.81	73.78	73.76	73.76	61.37	63.55	
24	73.61	72.66	72.39	71.70	73.33	73.80	73.81	73.78	73.76	73.76	61.41	63.55	
25	73.61	72.61	72.45	71.71	73.42	73.80	73.81	73.78	73.76	73.76	61.44	63.53	
26	73.61	72.54	72.50	71.74	73.49	73.80	73.81	73.77	73.76	73.76	61.49	63.53	
27	73.61	72.53	72.56	71.78	73.57	73.80	73.81	73.77	73.76	73.76	61.55	63.51	
28	73.61	72.51	72.61	71.84	73.65	73.81	73.81	73.76	73.76	73.76	61.59	63.50	
29	73.61	72.50	72.66	71.88	73.73	73.81	73.81	73.76	73.76	73.76	61.65	63.49	
30	73.61	72.48	72.73	71.91		73.81	73.81	73.76	73.76	73.76	61.71	63.48	
31	73.61		72.83	71.96		73.81		73.76		73.76	61.79		
MRAN	73.61	73.26	72.41	72.45	72.76	73.80	73.81	73.80	73.76	73.76	69.02	62.90	

WTR YR 1992 MRAN 72.10 HIGHEST 61.36 AUG. 21-23, 1992 LOWEST 73.81 MAR. 27 TO MAY 22, 1992



RIO SALINAS TO RIO JACAGUAS BASINS

180206066135500. Local number, RM # 5.
LOCATION.--Lat 18°02'06", long 66°13'55", Hydrologic Unit 21010004, 6.98 mi southwest of Cayey plaza, 0.63 mi east of
Hwy 1 km 82.3 on Rabo del Buey, and 1.75 mi southeast of Capilla de Santa Marta. Owner: U.S. Geological Survey,
WRD, Name: RM # 5.

MRAN

WRD, Name: RM # 5.
AQUIFER.-Quaternary alluvium.
WELL CHARACTERISTICS.--Drilled observation water-table well, diameter 4 in (0.10 m), cased 4 in (0.10 m), 0-34 ft
 (0-10.4 m), screened 24-34 ft (7.32-10.7 m). Depth 34 ft (10.4 m).
INSTRUMENTATION.--Digital water level recorder--60-minute punch.
DATUM.--Elevation of land-surface datum is 276.35 ft (84.2 m) above mean sea level.

Measuring point: Top of shelter floor, 3.28 ft (1.0 m) above land-surface datum.
REMARKS.--Recording observation well. Pumping test performed during February 2, 7, 1990.

PERIOD OF RECORD. --March 9, 1989 to current year.

EXTREMES FOR PERIOD OF RECORD.--Highest water level recorded, 7.48 ft (2.28 m) below land-surface datum, May 26, 1992; lowest water level recorded, 19.87 ft (6.06 m) below land-surface datum, June 14, 1990.

		WATER LEV	EL, IN FE	et below Inst	Land-Surf 'Antanbous	ACE DATUM OBSERVAT	, WATER I	YEAR OCTOBE 200	R 1991	TO SEPTEMB	ER 1992	
DAY	OCT	NOV	DEC	JAN	FRB	MAR	APR	MAY	JUN	JUL	AUG	SEP
1	11.87	14.62	12.06	14.20	11.68	11.74	11.81	11.81	10.71	11.56	11.68	11.74
2	11.86	14.43	12.10	14.17	11.68	11.76	11.63	11.82	10.85	11.57	11.69	11.78
3	11.85	14.52	12.13	14.09	11.68	11.77	11.71	11.81	10.95	11.59	11.66	11.71
4	11.87	14.71	12.13	14.05	11.68	11.77	11.77	11.84	11.06	11.59	11.68	11.74
5	11.89	14.91	11.99	14.07	11.68	11.78	11.80	11.86	11.13	11.59	11.59	11.80
6	11.90	15.08	12.07	10.13	11.69	11.78	11.82	11.88	11.19	11.59	10.98	11.81
7	11.93	12.83	12.08	10.87	11.60	11.78	11.83	11.82	11.25	11.60	11.32	11.81
8	11.99	11.96	12.12	11.13	11.62	11.78	11.84	11.82	11.28	11.61	11.42	11.83
9	12.03	11.62	12.16	11.26	11.65	11.78	11.84	11.85	11.30	11.61	11.48	11.83
10	11.96	11.74	12.21	11.34	11.65	11.78	11.85	11.88	11.32	11.61	11.52	11.83
11	11.93	11.82	12.25	11.39	11.65	11.79	11.87	11.90	11.34	11.62	11.56	11.90
12	12.00	11.87	12.30	11.43	11.66	11.79	11.85	11.92	11.22	11.61	11.57	11.92
13	12.09	11.89	12.33	11.47	11.66	11.81	11.66	11.92	11.26	11.63	11.59	
14	12.17	11.96	12.34	11.50	11.67	11.81	11.72	11.93	11.28	11.63	11.62	
15	12.30	12.00	12.38	11.52	11.67	11.82	11.64	11.50	11.34	11.63	11.63	11.92
16	12.61	12.02	12.41	11.55	11.68	11.81	11.67	11.63	11.37	11.55	11.64	11.93
17	12.87	12.05	12.40	11.58	11.68	11.81	11.74	11.68	11.39	11.56	11.65	11.88
18	13.14	12.07	12.39	11.60	11.69	11.81	11.78	11.76	11.40	11.57	11.66	11.84
19	13.26	12.11	12.53	11.61	11.69	11.80	11.80	11.78	11.42	11.59	11.67	11.86
20	13.48	12.10	12.74	11.62	11.69	11.80	11.57	11.81	11.44	11.60	11.68	10.99
21	13.67	12.12	12.92	11.64	11.70	11.80	11.44	11.83	11.32	11.61	11.69	11.25
22	13.82	12.15	12.94	11.65	11.72	11.80	11.60	11.85	11.39	11.62	11.71	11.49
23	14.01	12.15	13.01	11.66	11.72	11.80	11.66	11.75	11.42	11.63	11.72	11.57
24	14.16	12.15	13.07	11.66	11.72	11.83	11.70	10.64	11.45	11.63	11.73	11.62
25	14.32	11.99	13.21	11.66	11.68	11.83	11.75	10.91	11.47	11.63	11.74	11.65
26	14.49	12.00	13.33	11.65	11.68	11.83	11.79	8.72	11.49	11.64	11.75	11.67
27	14.63	12.01	13.45	11.65	11.68	11.85	11.81	9.49	11.51	11.66	11.75	11.70
28	14.79	12.01	13.64	11.67	11.68	11.84	11.82	9.75	11.53	11.66	11.77	11.72
29	14.93	11.98	13.83	11.68	11.74	11.88	11.83	10.01	11.53	11.66	11.75	11.73
30	15.06	11.97	14.00	11.68		11.90	11.83	10.27	11.54	11.67	11.77	11.75
31	15.15		14.15	11.68		11.90		10.50		11.68	11.78	

11.75

11.35

11.30

11.61


11.63

11.72

HIGHEST 7.48 MAY 26, 1992 LOWEST 15.17 OCT. 31, 1991 WTR YR 1992 MEAN 11.92

11.68

11.90



RIO SALINAS TO RIO JACAGUAS BASINS

180104066152300. Local number, RM # 10.
LOCATION.--Lat 18°01'04", long 66°15'23", Hydrologic Unit 21010004, 8.00 mi southeast of Coamo plaza, 1.07 mi
northeast of Escuela de Coco, and 0.70 mi southwest of Escuela Sabana Llana. Owner: U.S. Geological Survey, WRD,

Name: RM # 10.

AQUIFER. --Quaternary alluvium.

Name: RM # 10.

AQUIFER. --Quaternary alluvium.

MELL CHARACTERISTICS. --Drilled observation water-table well, diameter 4 in (0.10 m), cased 4 in (0.10 m), 0-37 ft (0-11.3 m), screened 27-37 ft (8.23-11.3 m). Depth 37 ft (11.3 m).

INSTRUMENTATION. --Digital water level recorder--15-minute punch.

DATUM. --Elevation of land-surface datum is 164.13 ft (50.0 m) above mean sea level, from leveling survey.

Measuring point: Top of shelter floor, 3.62 ft (1.10 m) above land-surface datum.

REMARKS. --Recording observation well. Pumping test performed on February 8, 1990.


PERIOD OF RECORD. --March 13, 1989 to current year.

EXTREMES FOR PERIOD OF RECORD. --Highest water level recorded, 18.0 ft (5.49 m) below land-surface datum, Nov. 9, 1990; lowest water level recorded, 35.56 ft (10.8 m) below land-surface datum, Aug. 28-29, 1990.

WATI	R LEVEL,	IN	FERT	BELOW	LAND-	-Surface	DATUM,	WATER	YEAR	OCTOBER	1991	TO	September	1992
	INSTANTANEOUS OBSERVATION AT 1200													

DAY	OCT	NOV	DRC	JAN	FEB	MAR	APR	MAY	JUN	JUL	AUG	SEP
1	30.98	31.19	28.99	30.37	25.16	26.30	28.10	27.96	20.03	20.40	24.61	24.05
2	31.01	31.19	29.05	30.42	25.16	26.37	28.15	27.95	19.93	20.50	24.75	24.18
3	31.04	31.19	29.10	30.47	25.15	26.41	28.20	27.95	19.86	20.62	24.86	24.32
4	31.07	31.19	29.15	30.53	25.14	26.47	28.24	27.96	19.82	20.75	24.90	24.36
5	31.09	31.19	29.20	30.59	25.13	26.53	28.30	27.97	19.7 9	20.89	24.89	24.45
6	31.12	31.19	29.25	30.35	25.11	26.60	28.35	28.00	19.78	21.01	24.32	24.62
7	31.13	30.74	29.29	29.31	25.10	26.67	28.39	28.03	19.78	21.13	24.09	24.80
8	31.15	30.34	29.34	28.61	25.07	26.73	28.42	28.06	19.79	21.28	23.89	24.95
9	31.17	30.05	29.38	28.11	25.03	26.79	28.45	28.10	19.78	21.46	23.51	25.09
10	31.18	29.74	29.41	27.68	25.00	26.86	28.48	28.13	19.78	21.65	23.07	25.25
11	31.19	29.46	29.45	27.33	24.98	26.92	28.51	28.17	19.78	21.84	22.78	25.40
12	31.20	29.28	29.48	27.04	24.97	26.97	28.53	28.21	19.76	22.01	22.55	25.55
13	31.20	29.15	29.51	26.78	24.99	27.03	28.56	28.25	19.73	22.16	22.35	25.70
14	31.20	29.04	29.55	26.51	25.01	27.09	28.58	28.29	19.72	22.30	22.26	25.85
15	31.20	28.94	29.58	26.31	25.07	27.15	28.61	28.22	19.73	22.46	22.19	25.99
16	31.20	28.85	29.61	26.13	25.12	27.21	28.64	28.08	19.77	22.62	22.15	26.10
17	31.20	28.78	29.64	25.98	25.16	27.26	28.67	27.96	19.78	22.72	22.14	26.23
18	31.21	28.72	29.74	25.86	25.23	27.31	28.70	27.93	19.81	22.82	22.19	26.34
19	31.21	28.69	29.77	25.75	25.31	27.38	28.73	27.92	19.84	22.93	22.39	26.44
20	31.21	28.66	29.81	25.64	25.43	27.45	28.75	27.91	19.88	23.06	22.58	26.54
21	31.21	28.64	29.85	25.56	25.54	27.49	28.67	27.89	19.92	23.20	22.70	26.23
22	31.21	28.64	29.88	25.48	25.61	27.56	28.44	27.89	19.90	23.33	22.70	25.78
23	31.21	28.64	29.92	25.42	25.73	27.62	28.29	27.88	19.93	23.46	22.78	25.43
24	31.20	28.67	29.97	25.37	25.83	27.67	28.21	27.09	19.97	23.60	22.90	25.14
25	31.20	28.68	30.02	25.33	25.94	27.74	28.17	26.80	20.01	23.73	23.04	24.93
26	31.20	28.73	30.06	25.29	26.01	27.79	28.12	24.69	20.05	23.85	23.21	24.77
27	31.20	28.78	30.11	25.26	26.09	27.86	28.08	22.49	20.10	23.97	23.37	24.63
28	31.20	28.82	30.15	25.21	26.18	27.91	28.03	21.44	20.17	24.10	23.47	24.59
29	31.20	28.88	30.20	25.19	26.24	27.96	27.99	20.83	20.23	24.23	23.63	24.60
30	31.20	28.93	30.26	25.17		28.01	27.97	20.45	20.30	24.35	23.75	24.65
31	31.20		30.30	25.17		28.07		20.19		24.47	23.88	
MEAN	31.17	29.50	29.65	27.04	25.36	27.20	28.38	26.73	19.89	22.48	23.29	25.23

WTR YR 1992 MEAN 26.34 HIGHEST 19.72 JUNE 13-15, 1992 LOWEST 31.21 OCT. 17-24, 1991



RIO INABON TO RIO LOCO BASINS

180133066503300. Local number, 132.

LOCATION.--Lat 18°01'33", long 66°50'33", Hydrologic Unit 21010004, 0.90 mi southeast of Yauco plaza, 3.46 mi east of Guayanilla plaza, and 1.32 mi north of Escuela Segunda Unidad Barinas. Owner: Pittsburg Plate Glass 4, Name: Yauco 2.

Name: Yauco 2.

AQUIFER.--Limestone of Tertiary Age.

AQUIFER.--Limestone of Tertiary Age.

MELL CHARACTERISTICS.--Drilled observation well, cased 20 in (0.51 m) 0-20 ft (0-6.1 m), 12 in (0.30 m) perforated pipe 20-84 ft (6.1-25.61 m), 10 in (0.25 m) perforated pipe 84-190 ft (25.61-57.93 m). Depth 190 ft (57.93 m). INSTRUMENTATION.--Digital water level recorder--60-minute punch.

DATUM.--Elevation of land-surface datum is about 75 ft (22.87 m) above mean sea level, from topographic map.

Measuring point: Top of shelter floor, 2.35 ft (0.72 m) above land-surface datum.

REMARKS.--Recording observation well.


PERIOD OF RECORD.--July 1972 to current year.

EXTREMES FOR PERIOD OF RECORD.--Highest water level recorded, +0.12 ft (0.04 m) below land-surface datum, July 19, 1979; lowest water level recorded, 36.91 ft (11.25 m) below land-surface datum, June 27, 1974.

		WATER LE	VEL, IN FE	et Below Inst	Land-Surf Antaneous	ACE DATUM, OBSERVAT	, WATER ION AT	YRAR OCTOBRE 1200	1991	TO SEPTEMBER	1992	
DAY	OCT	NOV	DEC	JAN	PEB	MAR	APR	MAY	JUN	JUL	AUG	SEP
1	14.58	15.18	16.08	19.09	17.32	18.49	20.90	19.67	15.91	13.86		15.17
2	14.63	15.18	16.18	19.17	17.35	18.57	20.97		15.70	13.91		15.20
3	14.69	15.18	16.27	19.25	17.42	18.64	21.03		15.52	14.01		15.24
3 4	14.74	15.16	16.34	19.35	17.51	18.70	21.09		15.37	14.10		15.28
5	14.79	15.29	16.40	19.41	17.63	18.79	21.16		15.20	14.14		15.30
6	14.84	15.33	16.45		17.72	18.87	21.21	19.56	15.04	14.20		15.37
7	14.80	15.37	16.50		17.80	18.95	21.27		14.91	14.30		15.31
8	14.79	15.38	16.62	17.61	17.81	19.06	21.29		14.78	14.40		15.16
9	14.81	15.40	16.66	17.59	17.84	19.15	21.30		14.74	14.50		15.15
10	14.87	15.43	16.68	17.51	17.89	19.23	21.33		14.63	14.55		15.15
		45 40	16.82	17.44	17.93	19.37	21.39	19.90	14.54	14.62		15.15
11	14.94	15.47	16.82	17.40	17.98	19.47	21.42		14.45			15.15
12	14.98	15.53	17.04	17.31	18.00	19.55	21.48		14.29			15.15
13	15.02	15.59	17.18	17.24	18.01	19.64	21.50		14.16			15.15
14	15.08	15.66		17.19	18.01	19.71	21.54		14.04	14.68		15.14
15	15.12	15.70	17.20	17.19	18.03	13.71	21.34					
16	15.13	15.77	17.27	17.14	18.02	19.77	21.61		13.94			15.10
17	15.17	15.57		17.11	18.03	19.86	21.66		13.88			15.10
18	15.24	15.45		17.07	18.07	19.91	21.67		13.85			15.08
19	15.31	15.52		17.05	18.09	19.97	21.68		13.82			15.07
20	15.32	15.55		17.05	18.06	20.03	21.71		13.79	14.80		15.04
21	15.32	15.60		17.03	18.06	20.06	21.55		13.76	14.80	15.02	14.97
22	15.32	15.62		17.02	18.10	20.14	20.61		13.69	14.80	14.97	14.92
23	15.32	15.66		17.02	18.10	20.19	20.56		13.65	14.80	14.97	14.75
24	15.38	15.69		17.03	18.14	20.28	20.45		13.65	14.81	14.97	14.72
25	15.38	15.76		17.05	18.19	20.39	20.28		13.65	14.81	14.98	14.68
				45.00	40 05	20.47	20.14	17.52	13.62	14.82	15.02	14.36
26	15.33	15.83		17.08	18.25				13.63		15.08	14.38
27	15.30	15.89		17.14	18.29	20.54	20.00		13.67		15.12	14.38
28	15.30	15.94		17.23	18.36	20.61	19.87		13.70		15.14	14.27
29	15.31	15.97		17.29	18.42	20.71	19.79		13.78		15.15	14.27
30	15.33	16.04		17.30		20.77	19.72		13.70	_	15.16	
31	15.15		18.99	17.30		20.84		16.17			13.10	
MRAN	15.08	15.56	17.10	17.57	17.95	19.70	21.01	18.87	14.31	14.59	15.05	14.97

WTR YR 1992 MEAN 16.86 HIGHEST 13.62 JUNE 26-27, 1992 LOWEST 21.73 APR. 20-21, 1992

⁺ Above land-surface datum.



RIO INABON TO RIO LOCO BASINS

175950066354200. Local number, 141.

LOCATION.--Lat 17°59'50°, long 66°35'42°, Hydrologic Unit 21010004, 1.71 mi southeast of Plaza Degetau at Ponce, 1.31 mi southeast of the intersection between Hwy 10 and Hwy 2, and 2.60 mi notheast of Muellle de Ponce.

Owner: P.R. Aqueduct and Sewer Authority, Name: Restaurada 8A.

AQUIFER:--Alluvium of Quaternary Age.

WELL CHARACTERISTICS.--Drilled unused public supply well, diameter 16-10 in (0.41-0.25 m), cased 16 in (0.41 m) 2-20 ft (0.6-6.1 m), perforated 20-130 ft (6.10-39.6 m), 10 in (0.25 m) 128-165 ft (39.0-50.3 m), perforated. Depth 165 ft (50.3 m).

INSTRUMENTATION.--Digital water level recorder--60-minute punch.

DATUM.--Elevation of land-surface datum is about 24 ft (7.30 m) above mean sea level, from topographic map.

Measuring point: Bottom edge of hole on side of casing 1.90 ft (0.58 m) above land-surface datum, 26.2 ft (7.67 m), above mean sea level.

(7.67 m), above mean sea level.

REMARKS.--Recording observation well.


PERIOD OF RECORD.--October 1981 to March 1, 1986, discontinued, November 18, 1991 to September 1992.

EXTREMES FOR PERIOD OF RECORD.--Highest water level recorded, 11.2 ft (3.41 m) below land-surface datum, Oct. 9, 1985; lowest water level recorded, 28.6 ft (8.71 m) below land-surface datum, July 9, 1982.

WATER LEVEL, IN FEET BELOW LAND-SURFACE DATUM, WATER YEAR OCTOBER 1991 TO SEPTEMBER 1992 INSTANTANEOUS OBSERVATION AT 1200

DAY	OCT	NOV	DEC	Jan	FRB	MAR	APR	MAY	JUN	JUL	AUG	SEP
1			16.28	18.11	17.28	17.81	17.60	20.43	17.09	18.07	18.35	19.14
2			16.33	18.14	17.33	17.75	17.52	20.50	17.41	17.87	18.25	19.12
3			16.38	18.18	17.38	17.67	17.47	20.55	17.62	17.97	18.18	19.17
4			16.41	18.17	17.46	17.62	17.38	20.67	17.64	18.00	18.11	19.31
5			16.45	18.17	17.50	17.52	17.36	20.75	17.76	17.95	18.06	19.31
6			16.52	17.15	17.48	17.44	17.37	20.88	17.86	17.99	17.59	19.34
7			16.54	16.55	17.51	17.35	17.33	20.92	17.89	17.99	17.58	19.56
8			16.53	16.35	17.54	17.28	18.01	21.02	17.92	18.00	17.45	19.53
9			16.55	16.12	17.58	17.24	17.45	21.08	18.00	18.01	17.46	19.51
10			16.59	15.98	17.59	17.18	17.37	21.10	18.03	18.17	17.43	19.56
11			16.66	16.00	17.71	17.14	17.37	21.09	18.08	18.04	17.49	19.63
12			16.67	16.07	17.64	17.12	17.40	21.15	18.08	17.82	17.37	19.61
13			16.59	16.12	17.61	17.11	17.44	21.16	18.07	18.13	17.10	19.47
14			16.53	16.17	17.58	17.02	17.47	21.22	18.11	18.08	17.44	19.39
15			16.48	16.23	17.56	16.95	17.49	21.29	18.17	17.94	17.50	19.41
16			16.43	16.32	17.58	16.87	19.34	21.09	18.29	17.95	17.47	19.43
17			16.40	16.53	17.61	16.78	19.61	21.00	18.34	17.97	17.54	17.23
18		15.64	16.48	16.55	17.69	16.78	19.80	20.92	18.30	17.62	17.66	17.04
19		15.70	16.53	16.67	17.72	16.86	19.93	19.69	18.27	18.18	17.76	16.93
20		15.78	16.51	16.76	17.75	16.97	20.03	20.70	18.27	18.36	17.97	16.86
21		16.06	17.40	16.88	17.81	17.06	19.68	19.51	17.92	18.31	18.36	16.78
22		16.10	17.50	16.97	17.83	17.04	20.10	20.71	18.05	18.60	18.45	16.81
23		16.10	17.64	17.05	17.90	17.14	20.22	20.37	18.17	18.94	18.56	17.01
24		16.14	17.62	17.07	17.92	17.27	20.23	19.68	18.28	19.36	18.46	17.17
25		16.19	17.66	17.07	17.91	17.54	20.25	19.24	18.16	19.37	18.54	17.26
26		16.22	17.74	17.08	17.84	18.30	20.26	18.69	18.19	18.94	18.60	17.23
27		16.24	17.88	17.11	17.81	17.79	20.30	18.31	18.11	18.85	18.75	17.23
28		16.25	17.97	17.13	17.83	17.64	20.29	18.05	18.05	18.79	18.83	17.29
29		16.23	18.02	17.15	17.82	17.61	20.30	18.00	17.95	18.79	18.45	17.31
30		16.26	18.07	17.16		17.57	20.34	14.83	17.99	18.79	18.77	19.02
31			18.08	17.20		17.59		14.64		18.60	18.82	
MRAN		16.07	16.95	16.91	17.65	17.32	18.76	19.98	18.00	18.30	18.01	18.39

WTR YR 1992 MEAN 17.95 HIGHEST 13.9 MAY. 31, 1992 LOWEST 21.34 MAY 15, 1992



MEAN

39.40

39.39

39,42

GROUND-WATER LEVELS

RIO GUANAJIBO BASIN

180132067033800. Local number, 143.

LOCATION.--Lat 18°01'32", long 67°03'38", Hydrologic Unit 21010003, 1.86 mi south of Lajas plaza, 1.27 mi southeast of the Estación Experimental Agrícola, and 1.30 mi northwest of the intersection of Hwy 116 with Hwy 305.

Owner: Pedro P. Vivoni, Name: Vivoni, Hacienda Amistad.

AQUIFER.--Limestone of unknown age.

WELL CHARACTERISTICS.--Drilled unused irrigation well, diameter 12 in (0.30 m). Depth 200 ft (60.98 m).

INSTRUMENTATION.--Digital water level recorder--15-minute punch.

DATUM.--Elevation of land-surface datum is about 52.5 ft (16.0 m) above mean sea level, from topographic map.

MEMARKS.--Recording observation well.

REMARKS. -- Recording observation well.
PERIOD OF RECORD. -- December 1981 to current year.


EXTREMES FOR PERIOD OF RECORD.--Highest water level recorded, 37.36 ft (11.39 m) below land-surface datum, Nov. 20, 1985; lowest water level recorded, 40.0 ft (12.2 m) below land-surface datum, June 9-11, 1990.

		WATER LEV	/EL, IN FE		land-surf Antaneous				BR 1991 7	O SEPTEMB	ER 1992	
				TWS	ANTANEOUS	UBSERVAT	ION AT 12	.00				
DAY	OCT	Nov	DEC	JAN	FRB	MAR	APR	MAY	JUN	JUL	AUG	SEP
1	39.38	39.43	39.41	39.45	39.25	39.62	39.76	39.80	39.36	39.30	39.40	39.42
2	39.41	39.42	39.41	39.42	39.25	39.62	39.73	39.82	39.34	39.26	39.40	39.41
3	39.45	39.42	39.41	39.44	39.25	39.62	39.72	39.81	39.36	39.25	39.39	39.40
4	39.44	39.40	39.39	39.43	39.27	39.61	39.71	39.79	39.34	39.25	39.36	39.43
5	39.40	39.38	39.40	39.47	39.27	39.60	39.73	39.79	39.30	39.25	39.39	39.41
6	39.40	39.36	39.40	39.15	39.25	39.61	39.75	39.80	39.31	39.26	39.38	39.39
7	39.39	39.37	39.39	39.20	39.25	39.63	39.75	39.84	39.32	39.27	39.37	39.40
8	39.40	39.38	39.40	39.24	39.30	39.64	39.71	39.86	39.32	39.27	39.39	39.40
9	39.42	39.38	39.40	39.26	39.34	39.63	39.72	39.89	39.31	39.27	39.38	39.41
10	39.42	39.38	39.40	39.24	39.34	39.61	39.72	39.88	39.29	39.28	39. 37	39.44
11	39.40	39.37	39.42	39.24	39.34	39.58	39.72	39.87	39.28	39.28	39.39	39.45
12	39.41	39.37	39.43	39.25	39.36	39.60	39.76	39.85	39.29	39.31	39.43	39.45
13	39.42	39.37	39.45	39.23	39.36	39.65	39.77	39.83	39.29	39.31	39.45	39.43
14	39.39	39.3 9	39.44	39.22	39.37	39.68	39.75	39.86	39.28	39.30	39.43	39.41
15	39.37		39.44	39.22	39.38	39.68	39.73	39.88	39.28	39.30	39.42	39.40
16	39.37		39.45	39.24	39.41	39.69	39.78	39.92	39.27	39.32	39.40	39.40
17	39.40		39.47	39.25	39.41	39.73	39.77	39.89	39.27	39.32	39.43	39.38
18	39.41		39.41	39.25	39.42	39.74	39.75	39.88	39.25	39.32	39.43	39.37
19	39.39		39.42	39.25	39.42	39.71	39.74	39.86	39.23	39.31	39.41	39.37
20	39.39		39.43	39.25	39.43	39.67	39.71	39.87	39.22	39.32	39.43	39.35
21	39.42		39.47	39.24	39.43	39.65	39.69	39.87	39.27	39.31	39.44	39.38
22	39.41		39.43	39.23	39.43	39.67	39.75	39.85	39.26	39.33	39.41	39.37
23	39.40		39.40	39.23	39.45	39.69	39.76	39.59	39.26	39.36	39.41	39.33
24	39.38		39.40	39.25	39.49	39.72	39.74	39.46	39.26	39.35	39.43	39.34
25	39.37		39.42	39.25	39.49	39.70	39.72	39.47	39.27	39.37	39.45	39.35
26	39.36		39.44	39.25	39.50	39.70	39.77	39.42	39.27	39.37	39.49	39.34
27	39.37	39.37	39.44	39.26	39.53	39.73	39.81	39.41	39.27	39.40	39.52	39.35
28	39.39	39.38	39.42	39.26	39.55	39.76	39.80	39.41	39.27	39.40	39.49	39.36
29	39.38	39.38	39.42	39.25	39.56	39.77	39.78	39.41	39.29	39.40	39.47	39.36
30	39.38	39.40	39.44	39.24		39.78	39.79	39.44	39.30	39.41	39.43	39.32
31	39.40		39.45	39.25		39.76		39.40		39.40	39.43	

WTR YR 1992 MEAN 39.45 HIGHEST 39.08 JAN. 6, 1992 LOWEST 39.92 MAY 16, 1992

39.38

39.27



39.67

39.75

39.73

39.29

39.32

39.42

RIO GUANAJIBO BASIN

180627067080600. Local number, CR-TW-1.

LOCATION.-Lat 18°06'27", long 67°08'06", Hydrologic Unit 21010003, 1.48 mi north of Cabo Rojo plaza, 1.24 mi northwest of Escuela Segunda Unidad Antonio Acarón Correa, and 1.78 mi southweast of Escuela Sabana Alta.

Owner: U.S. Geological Survey, WRD, Name: CR-TW-1.

ACUIFER.--Sand and clay.

WELL CHRACTERISTICS.--Drilled unused water-table well, diameter 4 in (0.10 m), cased 4 in (0.10 m), 0-15 ft (0-4.57 m), screened 5-15 ft (1.52-4.57 m). Depth 15 ft (4.57 m).

INSTRUMENTATION.--Digital water level recorder--60-minute punch.

DATUM.--Elevation of land-surface datum is about 28.6 ft (8.72 m) above mean sea level, from topographic map. Measuring point: Hole on shelter floor 5.83 ft (1.78 m) above land-surface datum.


REMARKS.--Observation well. Drilled on Mar. 3, 1992. Automatic digital recorder installed on July 16, 1992.

EXTREMES FOR PERIOD OF RECORD.--Highest water level recorded, +3.11 ft (+0.95m) above land-surface datum, Sept. 8, 1992; lowest water level recorded, 0.34 ft (0.10 m) below land-surface datum, July 23, 1992.

		WATER LEVEL,	IN FEET	BELOW LA	nd-Surfa Taneous	CE DATUM, OBSERVATIO	WATER YEAR ON AT 1200	OCTOBER	1991	TO SEPTEMBER	1992	
DAY	OCT	NOV	DEC	Jan	FEB	MAR	APR	MAY	JUN	JUL	AUG	SEP
1											+.32	+.22
2											+.27	+.28
3											+.22	+.28
4											+.23	+.19
5											+.20	+.40
6											+.27	+.63
7		~									+.19	+2.37
8											+.15	+3.01
9											+.21	+2.44
10											+.31	+1.92
11											+.22	+1.40
12											+.16	+1.38
13											+.53	+.87
14											+.46	+2.09
15											+.34	+2.97
16											+.34	+2.43
17										.05	+.26	+1.89
18										.12	+.23	+1.44
19										.16	+.17	+.92
20										.06	+.13	+.51
21										.16	+.05	+1.91
22										.25	+.23	+1.46
23		~								.31	+.33	+1.05
24			~							+.24	+.24	+.56
25										+.18	+.19	+.44
26										+.10	+.21	+1.85
27										+.02	+.14	+1.43
28										.05	+.09	+.90
29										.13	+.03	+.80
30										.24	+.22	+.71
31										.14	+.33	
MRAN										.08	+.23	+1.29

WTR YR 1992 MEAN +.59 HIGHEST +3.11 SEPT. 8, 1992 LOWEST .34 JULY 23, 1992

⁺ Above land-surface datum.



RIO GUANAJIBO BASIN


180628067075800. Local number, CR-TW-2A.
LOCATION.--Lat 18°06'28", long 67°07'58", Hydrologic Unit 21010003, 1.56 mi northeast of Cabo Rojo plaza, 0.33 mi northwest of Hacienda La Ratina, and 1.94 mi southeast of Escuela Sabana Alta. Owner: U.S. Geological Survey, WRD, Name: CR-TW-2A.
AQUIFER.--Sand and clay.
WELL CHARACTERISTICS.--Drilled unused water-table well, diameter 4 in (0.10 m), cased 4 in (0.10 m), 0-113 ft (0-34.4 m), screened 105-113 ft (32.0-34.4 m). Depth 113 ft (34.4 m).
INSTRUMENTATION.--Digital water level recorder--60-minute punch.
DATUM.--Elevation of land-surface datum is about 28.9 ft (8.81 m) above mean sea level, from topographic map.
Measuring point: Hole on shelter floor 6.10 ft (1.86 m) above land-surface datum.
REMARKS.--Observation well. Drilled on Mar. 6, 1992. Automatic digital recorder installed on July 16, 1992.
PERTIOD OF RECORD.--July 1992 to September 1992.
EXTREMES FOR PERIOD OF RECORD.--Highest water level recorded, +2.06 ft (+0.62 m) above land-surface datum, Sept. 15, 1992; lowest water level recorded, 5.12 ft (1.56 m) below land-surface datum, July 31, 1992.

WATER LEVEL,	IN FERT	BELOW LAND-SURFACE	DATUM, WATER	YEAR OCTOBE	R 1991 TO	SEPTEMBER	1992
		THESE INCIDENTS OF	**************************************	1200			

DAY	ост	NOV	DEC	JAN	FRB	MAR	APR	MAY	JUN	JUL	AUG	SEP
1											3.21	3.29
2											3.21	3.38
3											3.33	3.47
4											3.45	3.59
5											3.61	1.92
6											3.69	1.26
7											3.49	+.76
8											3.26	+1.70
9											3.11	+1.60
10											2.83	+1.60
11											2.78	+.64
12											2.82	+.59
13											1.19	+.43
14											. 99	+1.11
15											1.03	+2.05
16											1.09	+1.98
17										3.46	1.26	+1.98
18										3.63	1.50	+1.98
19										3.85	1.69	+1.98
20										4.04	1.88	+.39
21										4.25	2.04	+1.08
22										4.46	2.05	+.82
23										4.66	1.99	+.55
24										3.84	2.04	+.45
25										3.93	2.13	+.45
26										4.12	2.20	+1.04
27										4.36	2.28	+.83
28										4.58	2.35	+.71
29										4.78	2.81	+.34
30										4.97	3.07	+.25
31										5.11	3.10	
MRAN										4.27	2.43	+.28

WTR YR 1992 MEAN 1.73 HIGHEST +2.06 SEPT. 15, 1992 LOWEST 5.12 JULY 31, 1992

⁺ Above land-surface datum.



RIO GUANAJIBO BASIN

180628067075801. Local number, CR-TW-2B.
LOCATION.--Lat 18°06'28", long 67°07'58", Hydrologic Unit 21010003, 1.56 mi northeast of Cabo Rojo plaza, 0.33 mi northwest of Hacienda La Ratina, and 1.94 mi southeast of Escuela Sabana Alta. Owner: U.S. Geological Survey, WRD, Name: CR-TW-2B.
AQUIFER.--Sand and clay

WELL CHARACTERISTICS. --Drilled unused water-table well, diameter 4 in (0.10 m), cased 4 in (0.10 m), 0-15 ft (0-4.57 m), screened 10-15 ft (3.05-4.57 m). Depth 15 ft (4.57 m).

INSTRUMENTATION. --Digital water level recorder--60-minute punch.

DATUM. -- Elevation of land-surface datum is about 28.8 ft (8.78 m) above mean sea level, from topographic map.

Measuring point: Hole on shelter floor 6.10 ft (1.86 m) above land-surface datum.

REMARKS. -- Observation well. Drilled on Mar. 10, 1992. Automatic digital recorder installed on June 3, 1992.


PRRIOD OF RECORD. -- June 1992 to September 1992.

EXTREMES FOR PERIOD OF RECORD. -- Highest water level recorded, +2.71 ft (+0.83 m) above land-surface datum, Sept. 8, 1992; lowest water level recorded, 3.60 ft (1.10 m) below land-surface datum, July 8, 1992.

WATER LEVEL, IN FEET BELOW LAND-SURFACE DATUM, WATER YEAR OCTOBER 1991 TO SEPTEMBER 1992 INSTANTANEOUS OBSERVATION AT 1200 AUG DAY OCT NOV DRC JAN FRB MAR MAY JUN JUL SRP 2.68 . 68 2.18 ---------------2.81 1.22 2.24 ---3 ---------------------2.96 1.48 2.28 . 35 2.35 ------------3.11 1.70 ------. 69 1.90 . 54 6 ------------------. 89 3.36 2.00 ------.11 ___ ---------+1.97 ------1.06 3.49 2.13 ---8 ------3.60 2.22 +2.62 1.18 ------------------------1.29 3.21 2.25 +2.03 10 ------------2.90 1.88 +.02 +1.47 11 ------------------. 08 2.94 2.05 +.96 ---------------12 ------.49 .79 3.05 3.19 +.93 2.18 13 . 39 +.41 14 ------------------------3.32 ------------15 ---1.13 1.37 .91 +2.55 16 ---------___ ___ ___ ------1.29 1.60 . 87 +2.02 ------17 ------------1.38 ------1.80 1.21 +1.44 18 ---------1.37 +.99 2.11 ---------19 ---_------20 ---------1.66 2.51 1.70 +.01 21 ---------1.73 2.71 1.85 22 23 ------------------------1.77 2.89 +1.01 ---------------1.84 3.08 1.68 +.60 ------1.92 1.29 1.79 ---------+.06 ---25 ------2.01 1.91 .03 26 1.97 ---2.10 2.11 +1.38 ---------27 ---2.19 2.43 2.06 +1.01 ------------2.67 28 ------------2.30 2.13 +.44 ---------------29 ---2.44 2.87 2.17 +.24 30 ---------3.07 2.23 ---2.56 +.14 31 ___ ------2.06 MRAN ---------1.38 2.70 1.67 +.54

WTR YR 1992 MRAN 1.32 HIGHEST +2.71 SEPT. 8, 1992 LOWEST 3.60 JULY 8, 1992

⁺ Above land-surface datum.



RIO GUANAJIBO BASIN

180628067075802. Local number, CR-TW-2C.
LOCATION.--Lat 18°06'28", long 67°07'58", Hydrologic Unit 21010003, 1.56 mi northeast of Cabo Rojo plasa, 0.33 mi northwest of Hacienda La Ratina, and 1.94 mi southeast of Escuela Sabana Alta. Owner: U.S. Geological Survey, WRD, Name: CR-TW-2C. AQUIFER.--Sand and clay.

WELL CHARACTERISTICS.-Drilled unused water-table well, diameter 4 in (0.10 m), cased 4 in (0.10 m), 0-65 ft (0-19.8 m), screened 60-65 ft (18.3-19.8 m). Depth 65 ft (19.8 m).

INSTRUMENTATION.--Digital water level recorder--60-minute punch.

DATUM.--Elevation of land-surface datum is about 28.9 ft (8.81 m) above mean sea level, from topographic map.

Measuring point: Hole on shelter floor 6.06 ft (1.85 m) above land-surface datum.

REMARKS.--Observation well. Drilled on Mar. 7, 1992. Automatic digital recorder installed on June 16, 1992.


PERIOD OF RECORD. -- June 1992 to September 1992.

EXTREMES FOR PERIOD OF RECORD. -- Highest water level recorded, +1.96 ft (+0.60 m) above land-surface datum, Sept. 15, 1992; lowest water level recorded, 6.16 ft (1.88 m) below land-surface datum, July 31, 1992.

WATER LEVEL, IN FEET BELOW LAND-SURFACE DATUM, WATER YEAR OCTOBER 1991 TO SEPTEMBER 1992 INSTANTANEOUS OBSERVATION AT 1200 NOV AUG SRP DAY OCT DEC JAN FRB MAR APR MAY JUN mr. ·--5.59 3.45 4.19 ------1 ------------------5.60 3.57 ------------3.66 3 ------5.62 4.26 3.79 4.32 ------5.62 5 ---------------2.00 5.65 1.34 6 ------------------------4.49 ------+.67 ---5.66 ---------4.19 ---8 ------------------3.89 ------------5.81 3.69 +1.37 ------------+.99 10 3.27 +.56 11 ---------------------------5.83 ------3.27 ------------------5.84 +.49 12 13 5.09 1.56 +.06 14 ---___ ___ ___ ------___ ------5.06 1.32 +1.00 ------------5.07 15 ------------+1.95 1.35 16 ---------4.76 5.07 1.42 +1.71 ---___ 17 ------------5.00 4.96 1.64 +1.71 +1.71 ---------------------5.33 18 +1.60 5.34 ------20 ------------5.48 5.51 2.07 +.08 21 22 5.67 ---------------5.50 5.51 5.84 2.13 2.04 +.72 ------------------------23 24 25 2.10 ---------------------___ 5.52 5.23 2.20 +.02 5.53 5.37 26 ---------5.54 5.56 5.56 5.76 2.33 2.40 2.97 +.75 27 ------------------------28 ------------5.90 29 ------------------5.57 +.33 30 6.07 3.23 +.27 31 ---------___ ___ ---6.16 3.28 ---

WTR YR 1992 MEAN 3.17 HIGHEST +1.96 SEPT. 15, 1992 LOWEST 6.16 JULY 31, 1992

MRAN



5.42

5.56

2.83

+.09

⁺ Above land-surface datum.

RIO GUANAJIBO BASIN

180643067080400. Local number, CR-TW-3.
LOCATION.--Lat 18°06'43°, long 67°08'04°, Hydrologic Unit 21010003, 1.75 mi northeast of Cabo Rojo plaza, 0.64 mi northwest of Hacienda La Ratina, and 1.58 mi southwest of Escuela Sabana Alta. Owner: U.S. Geological Survey, WRD, Name: CR-TW-3.
AQUIFER.--Sand and clay.

AQUIFER. --Sand and clay.

WELL CHARACTERISTICS. --Drilled unused water-table well, diameter 4 in (0.10 m), cased 4 in (0.10 m), 0-30 ft (0-9.14 m), screened 20-30 ft (6.10-9.14 m). Depth 30 ft (9.14 m).

INSTRUMENTATION. --Digital water level recorder--60-minute punch.

DATUM. --Elevation of land-surface datum is about 27.2 ft (8.29 m) above mean sea level, from topographic map.

Measuring point: Hole on shelter floor 5.56 ft (1.69 m) above land-surface datum.

REMARKS. --Observation well. Drilled on Mar. 12, 1992. Automatic digital recorder installed on July 10, 1992.

PERIOD OF RECORD. --March 1992 to September 1992.


PERIOD OF RECORD. --March 1992 to September 1992.

EXTREMES FOR PERIOD OF RECORD. --Highest water level recorded, +4.24 ft (+1.29 m) above land-surface datum, Sept. 15, 1992; lowest water level recorded, 2.03 ft (0.62 m) below land-surface datum, July 30-31, 1992.

		WATER LEVEL,	in Fe et		Land-Surfaci Antaneous o			OCTOBER	1991	TO SEPTEMBER	1992	
DAY	OCT	NOV	DEC	JAN	FRB	MAR	APR	MAY	JUN	JUL	AUG	SEP
1											.76	.24
2											. 53	.28
3											. 52	.31
4											. 56	.41
5											. 61	+.86
6											. 65	+1.31
7											. 65	+3.01
8											. 60	+3.73
9											. 52	+3.53
10										1.25	. 33	+3.23
11										1.39	.33	+2.85
12										1.58	. 39	+2.81
13										1.73	+.91	+2.35
14											+1.09	+3.37
15										.29	+.97	+4.24
16										.70	+.83	+3.86
17										. 94	+.62	+3.45
18										1.16	+.46	+3.13
19										1.31	+.30	+2.72
20										1.43	+.19	+2.32
21										1.58	+.07	+3.36
22										1.73	+.22	+3.04
23										1.87	+.31	+2.79
24										1.27	+.24	+2.39
25										1.26	+.16	+2.13
26										1.40	+.12	+3.43
27										1.57	+.05	+3.13
28										1.73	. 03	+2.70
29										1.87	. 25	+2.66
30										2.02	.22	+2.59
31										2.01	. 17	
MRAN										1.45	. 02	+2.46

HIGHEST +4.24 SEPT. 15, 1992 LOWEST 2.03 JULY 30-31, 1992 WTR YR 1992 MEAN +.50

⁺ Above land-surface datum.



RIO GUANAJIBO BASIN

180650067073700. Local number, CR-TW-4.
LOCATION.--Lat 18°06'50", long 67°07'37", Hydrologic Unit 21010003, 2.15 mi northeast of Cabo Rojo plaza, 0.68 mi northeast of Hacienda La Ratina, and 2.13 mi southeast of Escuela Sabana Alta. Owner: U.S. Geological Survey, WRD,

northeast of Hacienda La Ratina, and 2.13 mi southeast of Rscuela Sabana Alta. Owner: U.S. Geological Survey, Name: CR-TW-4.

AQUIFER: --Sand and clay.

WELL CHARACTERISTICS. --Drilled unused water-table well, diameter 4 in (0.10 m), cased 4 in (0.10 m), 0-28 ft (0-8.53 m), screened 15-25 ft (4.57-7.62 m). Depth 28 ft (8.53 m).

INSTRUMENTATION. --Digital water level recorder--60-minute punch.

DATUM. --Rlevation of land-surface datum is about 37.2 ft (11.3 m) above mean sea level, from topographic map.


Measuring point: Hole on shelter floor 3.96 ft (1.21 m) above land-surface datum.

PERIOD OF RECORD. --June 1992 to September 1992.

EXTREMES FOR PERIOD OF RECORD. --Highest water level recorded, 3.55 ft (1.08 m) below land-surface datum, Sept. 26, 1992; lowest water level recorded, 8.05 ft (2.45 m) below land-surface datum, July 5, 1992.

		WATER LEVEL,	IN FEET	BRLOW L	AND-SURFAC	E DATUM, OBSERVATI	WATER YEAR ON AT 1200	OCTOBER	1991	TO SEPTEMBER	1992	
DAY	OCT	NOV	DEC	JAN	FEB	MAR	APR	MAY	JUN	JUL	DUA	SEP
1										7.56	6.46	6.07
2										7.63	6.67	6.21
3										7.69	6.83	6.29
ă										7.74	6.90	6.46
5										8.05	6.99	5.19
6										7.95	7.01	4.75
7										8.01	7.09	4.17
8										7.88	7.15	3.97
9										7.73	7.09	4.03
10										7.73	6.62	4.12
11										7.75	6.76	4.17
12										7.82	6.90	4.09
13										7.86	5.53	4.18
14										7.41	5.47	3.90
15										7.25	5.57	3.72
16										7.34	5.67	3.80
17										7.38	5.95	3.91
18										7.46	6.12	3.92
19										7.51	6.30	4.03
20										7.59	6.49	4.09
21										7.65	6.62	3.81
22										7.73	6.25	3.87
23										7.82	5.89	3.87
24										7.11	6.07	3.96
25										7.20	6.24	3.95
26										7.32	6.24	3.56
27										7.44	6.41	3.71
28										7.55	6.54	3.82
29										7.64	6.61	3.73
30										7.73	6.53	3.72
31										7.76	5.90	
MRAN										7.62	6.42	4.30

WTR YR 1992 MRAN 6.13 HIGHEST 3.55 SEPT. 26, 1992 LOWEST 8.05 JULY 5, 1992



RIO GUANAJIBO BASIN

180557067083100. Local number, CR-TW-5.
LOCATION.--Lat 18°05'57", long 67°08'31", Hydrologic Unit 21010003, 0.75 mi northeast of Cabo Rojo plaza, 0.92 mi southeast of Hacienda La Ratina, and 1.83 mi southeast of Escuela Sabana Alta. Owner: U.S. Geological Survey, WRD,

southeast of Hacienda La Ratina, and 1.83 mi southeast of Escuela Sabana Alta. Owner: U.S. Geological Survame: CR-TW-5.
AQUIFER: --Sand and clay.
WELL CHARACTERISTICS. --Drilled unused water-table well, diameter 4 in (0.10 m), cased 4 in (0.10 m), 0-25 ft (0-7.62 m), screened 15-25 ft (4.57-7.62 m). Depth 25 ft (7.62 m).
INSTRUMENTATION. --Digital water level recorder--60-minute punch.
DATUM. --Elevation of land-surface datum is about 35.3 ft (10.8 m) above mean sea level, from topographic map.
Measuring point: Hole on shelter floor 3.88 ft (1.18 m) above land-surface datum.
REMARKS. --Observation well. Drilled on Mar. 17, 1992. Automatic digital recorder installed on July 16, 1992.
PERIOD OF RECORD. --July 1992 to September 1992.


PERIOD OF RECORD. --July 1992 to September 1992.

EXTREMES FOR PERIOD OF RECORD. --Highest water level recorded, 3.78 ft (1.15 m) below land-surface datum, Sept. 15, 1992; lowest water level recorded, 6.50 ft (1.98 m) below land-surface datum, July 23, 1992.

WATER LEVEL, IN FEET BELOW LAND-SURFACE DATUM, WATER YEAR OCTOBER 1991 TO SEPTEMBER 1992 INSTANTANEOUS OBSERVATION AT 1200

DAY	OCT	NOV	DEC	JAN	FEB	MAR	APR	MAY	JUN	JUL	AUG	SEP
1											5.94	5.69
2											5.74	5.69
3											5.69	5.67
4											5.67	5.70
5											5.75	5.54
6											5.73	5.23
7											5.72	4.60
8											5.78	3.94
9											5.79	4.02
10											5.75	4.28
11											5.79	4.60
12											5.85	4.73
13											5.38	4.88
14											5.21	4.52
15											5.25	3.84
16										6.41	5.37	3.89
17										6.40	5.50	4.16
18										6.42	5.61	4.45
19										6.42	5.65	4.68
20										6.37	5.73	4.85
21										6.38	5.81	4.61
22										6.45	5.74	4.59
23										6.48	5.67	4.73
24										6.32	5.68	4.89
25										6.30	5.72	5.01
26										6.31	5.75	4.67
27										6.34	5.80	4.65
28										6.39	5.82	4.81
29										6.41	5.84	4.87
30										6.47	5.76	4.86
31										6.47	5.69	
MBAN										6.40	5.68	4.75

WTR YR 1992 MEAN 5.47 HIGHEST 3.78 SEPT. 15, 1992 LOWEST 6.50 JULY 23, 1992



RIO GUANAJIBO BASIN

180617067083300. Local number, CR-TW-6.
LOCATION.--Lat 18°06'17", long 67°08'33", Hydrologic Unit 21010003, 1.11 mi northeast of Cabo Rojo plaza, 1.27 mi northwest of Escuela Segunda Unidad Antonio Acarón Correa, and 1.50 southeast of Escuela Sabana Alta.
Owner: U.S. Geological Survey, WRD, Name: CR-TW-6.

AQUIFER . - - Sand and clay.

WELL CHARACTERISTICS. -- Drilled unused water-table well, diameter 4 in (0.10 m), cased 4 in (0.10 m), 0-30 ft (0-9.14 m), screened 20-30 ft (6.10-10.0 m). Depth 30 ft (10.0 m).
INSTRUMENTATION. -- Digital water level recorder -- 60-minute punch.

DATUM.--Elevation of land-surface datum is about 32.9 ft (10.0 m) above mean sea level, from topographic map.

Measuring point: Hole on shelter floor 5.77 ft (1.76 m) above land-surface datum.

REMARKS.--Observation well. Drilled on Mar. 19, 1992. Automatic digital recorder installed on June 4, 1992.


PERIOD OF RECORD.--June 1992 to September 1992.

EXTREMES FOR PERIOD OF RECORD.--Highest water level recorded, 4.00 ft (1.22 m) below land-surface datum, Sept. 15, 1992; lowest water level recorded, 11.6 ft (3.54 m) below land-surface datum, July 13, 1992.

WATER LEVEL, IN FEET BELOW LAND-SURFACE DATUM, WATER YEAR OCTOBER 1991 TO SEPTEMBER 1992 INSTANTANEOUS OBSERVATION AT 1200

DAY	OCT	NOV	DEC	JAN	FRB	MAR	APR	MAY	JUN	JUL	AUG	SEP
1										10.32	10.38	9.43
2										10.51	10.04	9.14
3										10.55	10.00	9.15
4	'								7.80	10.63	9.94	9.13
5									7.53	10.66	9.83	8.23
6									7.48	10.98	9.66	8.11
7									7.66	11.16	9.66	7.38
8									7.70	11.18	9.72	6.57
9									7.90	11.23	9.91	6.06
10									7.53	11.44	9.90	5.83
11									7.31	11.43	9.94	5.71
12									7.14	11.52	9.96	5.77
13									7.15	11.59	9.24	6.08
14									7.29	11.25	9.04	5.38
15									7.34	10.33	8.89	4.03
16									7.20	10.65	8.92	4.44
17									7.42	10.88	9.16	4.70
18									7.65	11.01	9.26	4.83
19									7.52	11.01	9.29	5.06
20									7.91	10.99	9.20	5.31
21									8.20	11.01	9.31	5.23
22									8.28	11.05	9.26	5.23
23									8.53	11.07	9.30	5.27
24									8.71	10.87	9.35	5.26
25									8.80	10.86	9.34	5.34
26									8.92	10.86	9.28	4.98
27									9.10	10.94	9.31	5.07
28									9.45	10.99	9.30	5.28
29									9.57	11.06	9.55	5.22
30									10.04	11.17	9.59	5.04
31										11.17	9.56	3.04
31										11.09	3.30	
MEAN									8.04	10.98	9.52	6.08

WTR YR 1992 MEAN 8.70 HIGHEST 4.00 SEPT. 15, 1992 LOWEST 11.60 JULY 13, 1992



16.55

18.98

22.64

20.87

GROUND-WATER LEVELS

RIO GUANAJIBO BASIN

MRAN


180604067085100. Local number, CR-TW-7.
LOCATION.--Lat 18°06'04", long 67°08'51", Hydrologic Unit 21010003, 0.80 mi northwest of Cabo Rojo plaza, 1.29 mi
northwest of Escuela Segunda Unidad Antonio Acarón Correa, and 1.56 southeast of Escuela Sabana Alta. Owner: U.S. northwest of Escuela Segunda Unidad Antonio Acarón Correa, and 1.56 southeast of Escuela Sabana Alta. Owner Geological Survey, WRD, Name: CR-TW-7.
AQUIFER.--Sand and clay.
WELL CHARACTERISTICS.--Drilled unused water-table well, diameter 4 in (0.10 m), cased 4 in (0.10 m), 0-40 ft (0-12.2 m), screened 30-40 ft (9.14-12.2 m). Depth 40 ft (12.2 m).
INSTRUMENTATION.--Digital water level recorder--60-minute punch.
DATUM.--Elevation of land-surface datum is about 42.2 ft (12.9 m) above mean sea level, from topographic map.
Measuring point: Hole on shelter floor 5.69 ft (1.73 m) above land-surface datum.
REMARKS.--Observation well. Drilled on Mar. 19, 1992. Automatic digital recorder installed on June 4, 1992.
DERIOD OF RECORD.--June 1992 to Sentember 1992.

PERIOD OF RECORD. -- June 1992 to September 1992.

EXTREMES FOR PERIOD OF RECORD. -- Highest water level recorded, 14.2 ft (4.32 m) below land-surface datum, Sept. 15, 1992; lowest water level recorded, 23.4 ft (7.15 m) below land-surface datum, July 13, 1992.

		WATER LEVEL,	in feet				WATER YEAR ON AT 1200	OCTOBE	R 1991	TO SEPTEMB	BR 1992	
DAY	OCT	NOA	DEC	JAN	PRB	MAR	APR	MAY	JUN	JUL	λUG	SEP
1										21.76	22.10	20.71
2										21.97	21.60	20.37
3										22.03	21.52	20.36
4									18.79	22.11	21.42	20.32
5									18.44	22.16	21.25	19.21
6									18.35	22.56	21.07	19.09
7									18.55	22.80	21.03	18.40
8									18.57	22.82	21.11	17.56
9									18.83	22.97	21.34	16.72
10									18.46	23.26	21.35	16.31
11									18.19	23.24	21.38	16.10
12									17.95	23.37	21.41	16.16
13									17.92	23.43	20.67	16.51
14									18.10	23.04	20.31	15.75
15									18.14	21.92	20.08	14.32
16									17.93	22.24	20.11	14.60
17									18.20	22.56	20.42	14.82
18									18.45	22.70	20.52	14.93
19									18.27	22.69	20.55	15.19
20									18.70	22.67	20.43	15.51
21									19.15	22.69	20.56	15.52
22									19.22	22.74	20.49	15.43
23									19.52	22.75	20.57	15.48
24									19.74	22.55	20.62	15.42
25									19.86	22.54	20.59	15.52
26									20.01	22.52	20.55	15.17
27									20.23	22.61	20.61	15.20
28									20.67	22.67	20.56	15.43
29									20.79	22.75	20.86	15.39
30									21.41	22.90	20.91	15.15
31										22.78	20.88	

WTR YR 1992 MEAN 19.81 HIGHEST 14.19 SEPT. 15, 1992 LOWEST 23.45 JULY 13, 1992



RIO GUANAJIBO BASIN

180547067084800. Local number, CR-TW-8.
LOCATION.--Lat 18°05'47", long 67°08'48", Hydrologic Unit 21010003, 0.50 mi north of Cabo Rojo plaza, 1.10 mi
northwest of Escuela Segunda Unidad Antonio Acarón Correa, and 1.85 southeast of Escuela Sabana Alta. Owner: U.S. Geological Survey, WRD, Name: CR-TW-8.

Geological Survey, WRD, Name: CR-TW-8.
AQUIFER.--Sand and clay.

MELL CHARACTERISTICS.--Drilled unused water-table well, diameter 4 in (0.10 m), cased 4 in (0.10 m), 0-39 ft (0-11.7 m), screened 25-35 ft (7.62-10.7 m). Depth 39 ft (11.9 m).

INSTRUMENTATION.--Digital water level recorder--60-minute punch.

DATUM.--Elevation of land-surface datum is about 40.7 ft (12.4 m) above mean sea level, from topographic map.

Measuring point: Hole on shelter floor 3.94 ft (1.20 m) above land-surface datum.


REMARKS.--Observation well. Drilled on Mar. 25, 1992. Automatic digital recorder installed on July 16, 1992.

PERIOD OF RECORD.--July 1992 to September 1992.

EXTREMES FOR PERIOD OF RECORD.--Highest water level recorded, 7.02 ft (2.14 m) below land-surface datum, Sept. 25, 1992; lowest water level recorded, 14.4 ft (4.38 m) below land-surface datum, July 29, 1992.

		WATER LEVEL,	IN PERT				, WATER YEAR ION AT 1200	OCTOBER	1991	TO SEPTEMBER	1992	
DAY	OCT	NOV	DEC	JAN	FRB	MAR	APR	MAY	JUN	JUL	AUG	SEP
1											12.97	
2											12.67	
3											12.48	
4											12.37	
5											12.29	
6											12.27	
7											12.36	
8											12.36	
9											12.33	
10											12.16	
11											11.02	
12											10.55	
13											13.28	
14											13.92	
15											13.91	
16										1	13.87	
17										14.08		
18										14.13		7.64
19										14.14		7.68
20										14.16		7.86
21										14.21		7.69
22										14.28		7.61
23										14.20		7.68
24										14.14		7.30
25										14.09		7.02
26										14.13	12.70	7.29
27											3.08	7.72
28											2.96	8.11
29										14.37		8.36
30										14.13		8.33
31										13.55		
mean										14.14 1	2.61	7.71

WTR YR 1992 MEAN 11.74 HIGHEST 7.02 SEPT. 25, 1992 LOWEST 14.38 JULY 29, 1992



RIO GUANAJIBO BASIN


180628067084300. Local number, CR-TW-9A.
LOCATION.--Lat 18°06'28", long 67°08'43", Hydrologic Unit 21010003, 1.29 mi north of Cabo Rojo plaza, 1.54 mi
northwest of Escuela Segunda Unidad Antonio Acarón Correa, and 1.23 southeast of Escuela Sabana Alta. Owner: U.S. Geological Survey, WRD, Name: CR-TW-9A.

Geological Survey, WRD, Name: CR-TW-9A.
AQUIFER.--Sand and clay.
WELL CHARACTERISTICS.--Drilled unused water-table well, diameter 4 in (0.10 m), cased 4 in (0.10 m), 0-24 ft
 (0-7.32 m), screened 19-24 ft (5.79-7.32 m). Depth 24 ft (7.32 m).
INSTRUMENTATION.--Digital water level recorder--60-minute punch.
DATUM.--Elevation of land-surface datum is about 29.5 ft (8.99 m) above mean sea level, from topographic map.
 Measuring point: Hole on shelter floor 3.92 ft (1.20 m) above land-surface datum.
REMARKS.--Observation well. Drilled on Mar. 25, 1992. Automatic digital recorder installed on July 8, 1992.
EXTREMES FOR PERIOD OF RECORD.--Highest water level recorded, 1.36 ft (0.41 m) below land-surface datum, Sept. 9,
 1992; lowest water level recorded, 5.28 ft (1.61 m) below land-surface datum, July 21-22, 1992.

THE PROPERTY OF TARREST OF PARTY NAMED VEAD COMODED 1991 TO SEPTEMBER 1992

		WATER LEVEL,	IN PERT	BELOW I	Land-Surfaci Antanbous of	BSERVATI	WATER YEAR ON AT 1200	OCTOBER	1991	TO SEPTEMBER	1992	
DAY	ост	NOV	DEC	JAN	PEB	MAR	APR	MAY	JUN	JUL	AUG	SEP
1		***									3.68	3.32
2											3.70	3.48
3											3.80	2.63
ă											3.74	1.74
5											3.78	1.90
6		***									3.73	2.28
7											3.16	2.45
8										5.24	3.44	2.05
9										5.05	3.62	1.44
10										5.07	2.71	1.98
11										5.17	2.99	
12										5.21	3.04	
13										5.22	3.17	
14										4.84	3.31	
15										4.97	3.37	
16										5.06	3.45	
17										5.12	3.51	
18											3.49	2.10
19											3.30	2.28
20										5.21	3.40	2.40
21											3.50	2.12
22												2.24
23												2.18
24												2.33
25										4.97		2.24
26											3.52	1.88
27											3.59	2.09
28											3.63	2.25
29											3.67	2.17
30											3.28	2.19
31										3.58	3.33	
MEAN										4.90	3.44	2.25

HIGHEST 1.36 SEPT. 9, 1992 LOWEST 5.28 JULY 21-22, 1992 WTR YR 1992 MRAN 3.55




GROUND-WATER LEVELS

RIO GUANAJIBO BASIN

180547067073100. Local number, CR-TW-10.
LOCATION.--Lat 18°05'47", long 67°07'31", Hydrologic Unit 21010003, 1.46 mi northeast of Cabo Rojo plasa, 0.60 mi
northeast of Escuela Segunda Unidad Antonio Acarón Correa, and 2.74 southeast of Escuela Sabana Alta. Owner: U.S. northeast of Escuela Segunda Unidad Antonio Acarón Correa, and 2.74 southeast of Escuela Sabana Alta. Owner: U. Geological Survey, WRD, Name: CR-TW-10.
AQUIPER.-Sand and clay.
WELL CHARACTERISTICS.--Drilled unused water-table well, diameter 4 in (0.10 m), cased 4 in (0.10 m), 0-40 ft (0.12.2 m), screened 30-40 ft (9.14-12.2 m). Depth 40 ft (12.2 m).
INSTRUMENTATION.--Digital water level recorder--60-minute punch.
DATUM.--Elevation of land-surface datum is about 36.4 ft (11.1 m) above mean sea level, from topographic map.
Heasuring point: Hole on shelter floor 3.67 ft (1.12 m) above land-surface datum.
REMARKS.--Observation well. Drilled on May 21, 1992. Automatic digital recorder installed on July 6, 1992.
PERIOD OF RECORD.--July 1992 to September 1992.
EXTREMES FOR PERIOD OF RECORD.--Highest water level recorded, 5.17 ft (1.58 m) below land-surface datum, Sept. 15, 1992; lowest water level recorded, 21.0 ft (6.39 m) below land-surface datum, July 13, 1992.

		WATER LEVEL,	IN FEET		Land-Surfaci Antaneous of			OCTOBER	1991 '	ro sept embe r	1992	
DAY	OCT	NOV	DEC	JAN	FRB	MAR	APR	MAY	JUN	JUL	AUG	SEP
1											19.31	17.18
2											18.91	16.62
3											19.09	17.01
Ā											19.14	17.07
5											18.43	14.83
6											18.24	14.87
7										19.72	18.53	12.42
8											18.40	9.84
9											18.94	8.37
10										20.75	18.77	8.35
11											19.01	8.29
12											18.68	8.77
13											17.17	9.64
14											16.67	7.45
15										17.37	16.43	5.21
16											16.78	6.76
17											17.65	6.88
18											17.37	7.11
19											17.14	7.47
20										19.63	16.98	8.21
21											17.21	8.21
22											16.96	8.02
23											17.30	8.15
24											17.34	8.28
25										19.71	17.12	8.50
26											17.11	7.38
27											17.20	7.58
28											17.23	8.27
29											17.79	7.63
30											17.78	7.31
31										20.02	17.75	
MRAN										19.81	17.82	9.72

WTR YR 1992 MEAN 15.57 HIGHEST 5.17 SEPT. 15, 1992 LOWEST 21.0 JULY 13, 1992



RIO CULEBRINAS BASIN

182442067091700. Local number, 200.
LOCATION.--Lat 18°24'42", long 67°09'17", Hydrologic Unit 21010002, 1.40 mi south of Aguadilla plaza, 3.04 mi northeast of Aguada plaza, and 0.20 mi north of Hwy 2 km 146.4. Owner: Carmelo Sánchez, Name: Aguadilla Cement Well.
AQUIFER. -- Surficial deposits.

AQUIFER. -- Surficial deposits.

MELL CHARACTERISTICS. -- Abandoned water-table industrial well, diameter 4 in (0.10 m), cased 0-20 ft (0-6.10 m), perforated 11-20 ft (3.35-6.10 m). Depth 20 ft (6.10 m).

INSTRUMENTATION. -- Digital water level recorder -- 60-minute punch.


DATUM. -- Elevation of land-surface datum is about 10 ft (3.05 m) above mean sea level, from topographic map. Heasuring point: Shelter floor on top of 4 in (0.10 m) casing, 3.25 ft (0.99 m) above land-surface datum. REMARKS. -- Recording observation well. Water levels affected by nearby pumping well.

PERIOD OF RECORD. -- October 1985 to current year.

EXTREMES FOR PERIOD OF RECORD. -- Highest water level recorded, 2.24 ft (0.68 m) below land-surface datum, Aug 25, 1988; lowest water level recorded, 9.60 ft (2.93 m) below land-surface datum, Feb. 20, 1992.

		WATER LEVE	L, IN FEET		Land-Surfa Tantaneous			YEAR OCTOBER 1200	1991	TO SEPTEMBER	1992	
DAY	OCT	NOV	DRC	JAN	FRB	MAR	APR	MAY	JUN	JUL	λŪG	SEP
1	6.55	7.00	8.03	8.63	9.13	9.53	8.94	8.80	5.67		6.03	5.24
2	6.60	7.05	8.08	8.68	9.14	9.56	8.96	8.72	5.66		6.19	5.38
3	6.38	7.09	8.10	8.68	9.19	9.57	8.97	8.73	5.68		6.24	5.48
4	6.52	7.26	8.10	8.68	9.22	9.56	8.96	8.77	5.07		6.33	5.56
5	6.58	7.20	8.11	8.59	9.28	9.56	8.96	8.78	4.88		6.16	5.60
6	6.69	7.26	8.11	8.51	9.29	9.56	9.02	8.81	4.37		6.27	5.68
7	6.90	7.31	8.11	8.54	9.29	9.54	9.05	8.55			6.27	5.73
8	6.96	7.39	8.10	8.54	9.30	9.53	9.08	8.58	4.01		6.34	5.86
9	7.08	7.10	8.35	8.62	9.31	9.52	9.11	8.58	4.18		6.28	5.30
10	7.06	7.13	8.27	8.64	9.34	9.53	9.00	8.52	3.64		6.35	5.03
11	7.16	7.27	8.33	8.65	9.37	9.53	8.96	8.48	3.48		6.42	5.15
12	7.20	7.36	8.35	8.67	9.38	9.36	8.76	8.44	3.56		6.47	5.25
13	7.23	7.40	8.38	8.73	9.40	9.39	8.51	8.26	3.57		6.13	5.35
14	6.65	7.44	8.40	8.74	9.42	9.39	8.53	8.28	3.66		5.67	5.44
15	6.70	7.49	8.41	8.77	9.43	9.38	8.53	8.31	3.50		5.70	5.57
16	6.61	7.52	8.45	8.81	9.44	9.45	8.35	8.31	3.36		5.77	4.88
17	6.78	7.56	8.46	8.81	9.49	9.40	8.34	8.35	3.48		5.74	4.89
18	6.91	7.63	8.48	8.81	9.51	9.26	8.38	8.44	3.62		5.92	5.00
19	6.53	7.66	8.52	8.81	9.53	9.29	8.45	8.44	3.67		6.07	5.03
20	6.62	7.72	8.49	8.87	9.58	9.31	8.52	8.14			5.99	4.91
21	6.71	7.76	8.41	8.88	9.58	9.31	8.54	8.16			6.03	5.03
22	6.81	7.81	8.48	8.89	9.56	9.33	8.59	8.18			6.09	5.13
23	6.93	7.83	8.53	8.91	9.55	9.37	8.68	7.33			5.81	5.23
24	7.00	7.86	8.54	8.92	9.58	9.38	8.67	6.86				4.80
25	7.03	7.93	8.54	8.92	9.58	9.34	8.66	6.54		5.85	5.86	4.62
26	6.49	7.96	8.54	8.93	9.57	9.35	8.65	6.00		5.99	5.71	4.48
27	6.54	7.99	8.54	8.97	9.56	9.34	8.73	5.44		5.81	5.57	4.47
28	6.68	7.94	8.57	9.00	9.55	9.29	8.76	5.38		5.97	4.97	4.54
29	6.77	8.00	8.58	9.02	9.54	9.29	8.79	5.36		6.05	4.95	4.61
30	6.88	8.00	8.62	9.03		9.32	8.80	5.38		6.10	4.99	4.67
31	6.96		8.62	9.12		9.03		5.53		6.11	5.31	
mban	6.79	7.53	8.37	8.79	9.42	9.41	8.74	7.76	4.17	5.98	5.92	5.13

WTR YR 1992 MEAN 7.55 HIGHEST 3.11 JUNE 15, 1992 LOWEST 9.60 FEB. 20, 1992



THIS PAGE WAS LEFT BLANK INTENTIONALLY



ST. THOMAS, U.S. VIRGIN ISLANDS

50252000 BONNE RESOLUTION GUT AT BONNE RESOLUTION, ST. THOMAS, VI

LOCATION.--Lat 18°21'57", long 64°57'34", Hydrologic Unit 21020001, on right bank near Hull Bay Road, 0.5 mi (0.8 km) upstream from Atlantic Ocean, and 2.5 mi (4.0 km) northwest of Fort Christian, Charlotte Amalie.

DRAINAGE AREA. -- 0.49 mi 2 (1.27 km2).

WATER-DISCHARGE RECORDS

PERIOD OF RECORD.--December 1962 to February 1967, March 1979 to April 1981, May 1982 to current year.

GAGE.--Water-stage recorder and crest-stage gage. Elevation of gage is 280 ft (85 m), from topographic map.

December 1962 to February 1967 and March 1979 to April 1981 at site about 100 ft (30 m) upstream at different datum.

REMARKS. -- Records poor.

	DIS	CHARGE,	CUBIC FER		OND, WATER DAILY MEAN		TOBER 1991	L TO SEPTE	MBRR 199	2		
DAY	ост	NOV	DEC	JAN	FRB	MAR	APR	MAY	JUN	JUL	AUG	SEP
1	.03	. 02	.03	.02	.02	. 02	e.01	. 05	.03	. 02	.02	. 02
2	.06	. 02	.04	.01	.02	. 02	e.01	.05	.04	.02	.02	.02
3	.06	. 02	.03	.01	.02	.02	e.01	.02	.03	.02	.02	. 02
ă	.04	.02	.03	. 02	9.3	.02	e.01	.02	.03	.02	.02	.02
5	.04	. 02	.03	7.9	.45	. 02	e.01	. 03	.03	.02	.05	. 02
6	.04	.02	.02	2.5	.11	. 02	e.01	. 02	.02	.02	.02	. 02
7	.04	. 02	.03	. 03	.09	. 02	e.01	. 02	.03	. 02	.03	. 02
8	.02	. 14	.04	.01	.07	. 02	e.01	. 02	.03	. 02	.02	.02
9 10	.03	. 08 . 04	.03 .02	.01 .02	.07 .06	.02 .02	e.01 e.01	. 02 . 02	.10	.01 .01	.06 .03	.02 .02
11	.03	. 03	.02	. 02	.06	. 02	e.01	. 02	.04	.01	.03	.01
12	.02	. 03	.02	.01	.05	. 02	e.01	. 03	.04	.01	.03	.01
13	. 03	. 03	.01	.01	.05	.01	e.01	.02	.03	.02	.05	.01
14	.02	. 03	.01	.01	.05	.01	e.01	e.03	.03	. 07	.03	.01
15	.02	.03	.01	.01	.06	. 02	e.01	.03	.03	. 02	.03	.01
16	.02	.02	.03	.01	.06	.02	e.01	. 05	.03	.02	.03	e.01
17	.02	.02	.03	.01	.06	.02	e.01	.08	.02	. 02	.03	e.01
18	.03	.02	.02	.01	.04	. 02	e.01	. 10	.02	.02	.03	. 01
19	.06	.02	.02	.01	.03	. 01	01	.08	.02	. 02	.03	. 01
20	.07	. 02	.02	.01	.03	.01	e.01	. 03	.02	.02	.03	.01
21	.06	. 02	.02	.01	.02	.01	0.01	.03	. 02	.01	.01	.01
22	.05	.02	.03	.01	.03	.02	.03	.03	.02	.02	.02	. 01
23	.03	.03	.03	.01	.03	.01	.04	.10	.02	.02	.02	.01
24	.02	.06	.03	.01	.03	.01	. 05	5.9	.02	. 02	.02	.01
25	.02	. 03	.03	. 02	.02	.02	.06	.11	.02	. 02	.02	.01
26	.02	. 03	.03	. 02	.03	. 03	.06	. 07	.02	.02	.02	.01
27	.02	. 03	.03	. 02	.02	. 13	.04	. 05	.02	.02	.02	.01
28	.02	. 03	.02	. 02	.02	. 05	.05	.08	.02	. 02	.04	.01
29	.02	. 04	.02	.02	.02	. 04	.06	. 05	.02	. 02	.03	.01
30	.02	. 03	.02	.02		. 02	.18	. 05	.02	.01	.02	.01
31	.02		.02	. 02		e.03		.06		. 03	.02	
TOTAL	1.01	0.97	0.77	10.82	10.92	0.73	0.78	7.27	0.86	0.62	0.85	0.40
MBAN	.033	.032	.025	. 35	.38	.024	. 026	. 23	.029	.020	. 027	.013
MAX	.07	. 14	.04	7.9	9.3	.13	.18	5.9	.10	. 07	.06	. 02
MIN	.02	.02	.01	.01	.02	.01	.01	.02	.02	.01	.01	.01
AC-FT	2.0	1.9	1.5	21	22	1.4	1.5	14	1.7	1.2	1.7	. 8
CFSM	.07	. 07	.05	.71	.77	. 05	.05	.48	.06	.04	.06	.03
IN.	.08	. 07	.06	. 82	.83	. 06	.06	. 55	.07	. 05	.06	. 03
e Bs	timated											
STATIST	ICS OF MC	NTHLY M	SAN DATA F	OR WATER	YEARS 1986	- 1992,	BY WATER	YEAR (WY)				
MESS					000			5.		0.54	000	1 20
MEAN	.78	1.08	.043	.082	. 082	.078	.091	. 56	.18	.061	.082	1.38 8.91
MAX (WY)	3.09 1 986	4.22 1988	.059 1988	. 35	.38	.31	.34 1986	2.06 1987	.89 1987	.18 1988	.23 1988	1989
MIN	.033	.016	.010	1992 .016	1992 .009	1987 .024	.012	.016	.023	.013	.012	.013
(WY)	1992	1990	1990	1986	1986	1992	1989	1989	1989	1991	1991	1992
SUMMARY	STATISTI	cs	FOR	1991 CALE	INDAR YEAR	P	OR 1992 W	ATER YEAR		WATER Y	BARS 1963	- 1992
annual Annual Highest		ŒAN		11.4	16 931		36.00 .09			.3		1989
Lowest	ANNUAL ME	RAN								.0		1964
	DAILY ME				2 Jun 30		9.3			160		8 1963
	DAILY MEA				1 May 14			1 Dec 13		.0		1 1980
	SEVEN-DAY			.0	1 May 19		.0:			.0		1 1980
	'ANEOUS PE						342			1650		8 1983
	ANBOUS PE		S .					7 Feb 4		7.0	u Aprl	8 1983
	ANEOUS LC							1 Oct 31		224		
	RUNOFF (A			23	164		71	n		.6	2	
	RUNOFF (C) 6 4 37		. 20 2. 7:			8.5		
	RUNOFF (I			. 0			. 01			.1		
	ENT BACKE			.0			. 0:			.0		
	ENT EXCE			.0			.0:			.0		
JU FARC					•		. 0.	•			-	

ST. THOMAS, U.S. VIRGIN ISLANDS

50276000 TURPENTINE RUN AT MARIENDAL, ST. THOMAS, VI

LOCATION.--Lat 18°19'48", long 64°52'58", Hydrologic Unit 21020001, on right bank, at Mariendal, 1.0 mi (1.6 km) upstream from mouth, and 3.3 mi (5.3 km) southeast of Fort Christian, Charlotte Amalie.

DRAINAGE AREA. -- 2.97 mi2 (7.69 km2).

WATER-DISCHARGE RECORDS

PERIOD OF RECORD.--January 1963 to April 1969, October 1978 to September 1980, June 1982 to July 1986, July 1986 to current year (high-water discharges only).

GAGE.--Crest-stage gage. Elevation of gage is 40 ft (12 m), from topographic map.

REMARKS. -- Records poor, peak discharges only.

AVERAGE DISCHARGES.--10 years (1964-68, 1979-80, 1983-85), 1.22 ft 3 /s (0.034 m 3 /s), 5.58 in/yr (142 mm/yr), 884 acre-ft/yr (1.09 hm 3 /yr); median of yearly mean discharges, 0.54 ft 3 /s (0.015 m 3 /s), 390 acre-ft/yr (0.48 hm 3 /yr).

EXTREMES FOR PERIOD OF RECORD.--Maximum discharge, 9,710 ft³/s (275 m³/s), Apr. 18, 1983, gage height, 11.09 ft (3.380 m), from floodmark, from rating curve extended above 500 ft³/s (14.2 m³/s) on basis of slope area measurement and step-backwater analysis; no flow many days from 1963 to 1969, and in 1984.

EXTREMES FOR CURRENT YEAR.--Maximum discharge, 384 ft³/s (10.9 m³/s), Jan. 5, gage-height 4.09 ft (1.247 m).

ST. JOHN, U.S. VIRGIN ISLANDS

50295000 GUINEA GUT AT BETHANY, ST. JOHN, VI

LOCATION.--Lat 18°19'55", long 64°46'50", Hydrologic Unit 21020001, 600 ft (183 m) southeast of Bethany Church, and 1.0 mi (1.6 km) east of Government House at Cruz Bay.

DRAINAGE AREA. -- 0.37 mi * (0.96 km *).

WATER-DISCHARGE RECORDS

PERIOD OF RECORD. -- January 1963 to October 1967, September 1982 to current year.

GAGE.--Water-stage recorder and concrete control. Elevation of gage is 260 ft (79 m), from topographic map. Prior to September 1982, at datum 1.00 ft (0.30 m) higher.

REMARKS.--Records poor. Gage-height and precipitation satellite telemetry at station.

		DISCHAR	SE, CUBIC	FEET PER			YEAR OCTOBER VALUES	1991 TO	sep temb er	1992		
DAY	OCT	NOA	DEC	JAN	FEB	MAF	R APR	MAY	JUN	JOL	AUG	SEP
1	.00	.00	.00	.00	.00	. 00	.00	.01	.04	.01	.01	.00
2	.00	.00	.00	.00	.00	. 00		.49	.03	.01	.01	.00
3	.00	.00	.00	.00	.00	. 00		.06	.03	.01	.02	.00
4	.00	.00	.00	.00	.00	. 00	.00	.02	.03	.01	.02	.00
5	.00	.00	.00	.00	.00	.00	.00	.01	.03	.01	.02	.00
6	.00	. 00	.00	.00	.00	.00	.00	. 00	.03	.01	.02	.00
7	.00	.00	.00	.00	.00	. 00		.00	.01	.01	.02	.00
8	.00	.00	.00	.00	.00	. 00	.06	.00	.01	.01	.02	. 00
9	.00	.00	.00	.00	.00	.00	.00	.00	.01	.01	.01	.00
10	.00	.00	.00	.00	.00	.00	.00	.00	.01	.01	.01	.00
11	.00	.00	.00	.00	.00	.00	.00	.00	.01	.01	e.01	.00
12	.00	.00	.00	.00	.00	.00		.00	.01	.01	e.01	.00
13	.00	.00	.00	.00	.00	. 00		.00	.01	.01	e.01	. 00
14	.00	.00	.00	.00	.00	. 00		.00	.01	.01	e.00	.00
15	.00	.00	.00	.00	.00	. 00	.00	.00	.01	.01	e.00	.00
16	.00	.00	.00	.00	.00	.00	.00	.00	.01	.01	e.00	.00
17	.00	.00	.00	.00	.00	. 00	.00	.00	.01	.01	e.00	.00
18	.00	.00	.00	.00	.00	. 01	L .00	.00	.01	.01	e.00	.02
19	.00	.00	.00	.00	.00	. 01	L .00	.00	.01	.01	.00	.01
20	.00	.00	.00	.00	.00	.01	L .00	.00	.01	.01	.00	.01
21	.00	.00	.00	.00	.00	. 01	L .00	.00	.01	.01	.00	.01
22	.00	.00	.00	.00	.00	. 00		.00	.01	.01	.00	.01
23	.00	.00	.00	.00	.00	. 00		.01	.01	.01	.00	.01
24	.00	.00	.00	.00	.00	. 00		7.5	.01	.01	.00	.01
25	.00	.00	.00	.00	.00	.00	.00	. 94	.01	.01	.00	.01
26	.00	.00	.00	. 00	.00	. 00	.00	. 37	.01	.01	.00	. 02
27	.00	.00	.00	. 00	.00	. 00		. 19	.01	.01	.00	. 02
28	.00	.00	.00	. 00	.00	. 00		.08	.01	.01	.00	. 02
29	.00	.00	.00	.00	.00	.00		. 06	.01	.01	.00	.02
30	.00	.00	.00	.00		. 00	.01	.05	.01	.01	.00	.02
31	.00		.00	.00		.00)	.04		.01	.00	
TOTAL	0.00	0.00	0.00	0.00	0.00	0.04	0.01	9.83	0.43	0.31	0.19	0.19
MEAN	.000	.000	.000	.000	.000	.001		. 32	.014	.010	.006	.006
MAX	.00	.00	.00	.00	.00	. 01	.01	7.5	.04	.01	.02	.02
MIN	.00	.00	.00	.00	.00	.00	.00	.00	.01	.01	.00	.00
AC-FT	.00	.00	.00	.00	.00	. 08		19	. 9	. 6	.4	.4
CFSM	.00	.00	.00	.00	.00	. 00		. 86	.04	. 03	. 02	. 02
IN.	.00	.00	.00	.00	.00	.00	.00	.99	.04	. 03	.02	. 02
e Es	timated											
STATIST	ICS OF MC	NTHLY MEA	N DATA FO	R WATER Y	BARS 1984	- 199	2, BY WATER	YBAR (WY))			
MRAN	.069	a c	022	016	005	005		4.4	.011	.010	.012	. 34
MAX	.23	.45 2.52	.027	.016 .044	.006 .017	.005		. 14 . 89	.011	.010	.026	2.35
(WY)	1986	1985	1989	1989	1989	1985		1986	1987	1990	1988	1989
MIN	.000	.000	.000	.000	.000	.000		.003	.000	.000	.000	.000
(WY)	1992	1992	1987	1992	1992	1986		1988	1991	1987	1991	1991
SUMMARY	STATISTI	cs	FOR 1	991 CALEN	DAR YRAR		FOR 1992 WAY	TER YEAR		WATER Y	EARS 1963	- 1992
ANNUAL				0.50			11.00			.0:	0.6	
ANNUAL		(DAM		.00	1		. 03	U		.3		1983
	ANNUAL M									.0		1967
	ANNUAL ME			0.3	Apr 8		7.5	May 24		110		7 1983
	DAILY MEA				Jan 21			Oct 1		.0		5 1983
	SEVEN-DAY				Jan 21			Oct 1		.0	Peb 1	6 1984
	ANEOUS PE						31			946		8 1983
	ANBOUS PE							May 24		5.3		8 1983
	RUNOFF (A			1.0			22			62		
	RUNOFF (C			.00			.08			.2		
	RUNOFF (I			.05			1.11			3.1		
	ENT EXCEE			.01			.01			.0		
	ENT EXCEE			.00			.00			.0		
30 PERC	ENT EXCEE	เบธ		.00			.00			.0	U	

ST. JOHN, U.S. VIRGIN ISLANDS

50295500 CRUZ BAY GUT AT CRUZ BAY, ST. JOHN, VI

LOCATION.--Lat 18°19'42", long 64°45'53", Hydrologic Unit 21020001, 0.40 mi (0.64 km) east of Government House at Cruz Bay, 0.45 mi (0.72 km) west of Bethany Church and 0.40 mi (0.64 km) Southwest of Caneel Hill.

DRAINAGE AREA. -- 0.09 mi 2 (0.23 km2).

WATER-STAGE RECORDS

PERIOD OF RECORD. -- April to September 1992 (gage-height only).

GAGE. -- Water-stage recorder. Elevation of gage is 120 ft (37 m), from topographic map.

REMARKS.--Gage-height and precipitation satellite telemetry at station. All gage-heights of 1.36 ft or lower are considered zero flow.

EXTREMES FOR CURRENT PERIOD. -- Maximum gage-height, 2.87 ft (0.875 m), May 24; minimum, 1.32 ft (0.402 m), Apr. 18-20.

GAGE HEIGHT, FEET, WATER YEAR OCTOBER 1991 TO SEPTEMBER 1992 DAILY MEAN VALUES

DAY	OCT	NOA	DEC	JAN	FRB	MAR	APR	MAY	JUN	JUL	AUG	SEP
1								1.36	1.36	1.36	1.36	1.36
2								1.83	1.35	1.36	1.36	1.36
2 3 4								1.36	1.35	1.36	1.36	1.36
4								1.36	1.35	1.35	1.36	1.36
5								1.36	1.35	1.36	1.36	1.36
6								1.36	1.36	1.35	1.36	1.36
7								1.36	1.35	1.35	1.36	1.36
6 7 8 9								1.35	1.36	1.35	1.36	1.36
9								1.36	1.36	1.35	1.36	1.36
10								1.36	1.36	1.35	1.36	1.36
11								1.36	1.36	1.35	1.36	1.36
12								1.36	1.36	1.35	1.36	1.36
13								1.36	1.36	1.35	1.36	1.36
14								1.35	1.36	1.36	1.36	1.36
15								1.35	1.36	1.35	1.36	1.36
16								1.35	1.36	1.35	1.36	1.36
17								1.35	1.36	1.35	1.36	1.36
18								1.35	1.36	1.35	1.36	1.36
19							1.32	1.35	1.36	1.35	1.36	1.36
20							1.33	1.35	1.36	1.36	1.36	1.36
21							1.33	1.34	1.36	1.35	1.36	1.36
22							1.34	1.34	1.35	1.36	1.36	1.36
23							1.34	1.34	1.36	1.36	1.36	1.36
24							1.35	2.18	1.36	1.36	1.36	1.36
25							1.35	1.83	1.36	1.36	1.36	1.36
26							1.35	1.69	1.36	1.36	1.36	1.36
27							1.35	1.45	1.36	1.36	1.36	1.36
28							1.36	1.35	1.36	1.36	1.36	1.36
29							1.36	1.35	1.36	1.36	1.36	1.36
30							1.36	1.35	1.36	1.35	1.36	1.36
31								1.35		1.36	1.36	
MEAN								1.42	1.36	1.35	1.36	1.36
MAX								2.18	1.36	1.36	1.36	1.36
MIN												

50332000 RIVER GUT AT RIVER, ST. CROIX, VI

LOCATION.--Lat 17°44'32", long 64°48'52", Hydrologic Unit 21020002, 0.20 mi (0.32 km) North from Quarry, 0.72 mi (1.16 km) northwest from Holly Cross church on route 72, 0.80 mi (1.29 km) southwest from top of Mt. Pleasant.

DRAINAGE AREA. -- 1.42 mi 2 (3.68 km2).

WATER-STAGE RECORDS

PERIOD OF RECORD. -- November 1991 to September 1992 (gage-height only).

GAGE.--Water-stage recorder. Datum of gage is 155 ft (47 m), from topographic map.

REMARKS.--Gage-height and precipitation satellite telemetry at station. All gage-heights of 29.60 ft or lower are considered zero flow.

GAGE HEIGHT, FEET, WATER YEAR OCTOBER 1991 TO SEPTEMBER 1992

EXTREMES FOR CURRENT PERIOD. -- Maximum gage-height, 35.81 ft (10.915 m), May 24; minimum, 26.51 ft (8.080 m), many days.

					DAIL	y mean va	LUES			
AY	OCT	NOV	DBC	JAN	FEB	MAR	APR	MAY	JUN	

DAY	OCT	NOV	DBC	Jan	FEB	MAR	APR	MAY	JUN	JUL	AUG	SEP
1			30.87	29.95	29.93	29.46	28.89	29.35	30.62	29.99	29.53	28.62
2			30.91	29.88	29.89	29.42	28.87	28.68	30.59	29.94	29.49	28.68
3			30.93	29.82	29.88	29.40	28.89	28.62	30.61	29.90	29.44	28.66
4			30.96	29.79	29.87	29.37	28.89	28.58	30.57	29.87	29.44	28.65
5		29.78	30.86	29.73	29.88	29.36	28.92	28.59	30.57	29.84	29.56	28.67
6		29.79	30.95		29.91	29.35	28.95	28.55	30.57	29.79	29.53	28.57
7 8 9		29.86	30.86		29.94	29.32	29.02	28.53	30.56	29.73	29.49	28.47
8		29.99	30.90		29.86	29.30	29.08	28.53	30.56	29.73	29.47	28.51
		29.99	30.95	30.20	29.80	29.31	29.21	28.50	30.56	29.71	29.45	28.57
10		29.98	30.92	30.31	29.79	29.32	29.25	28.54	30.57	29.68	29.40	28.51
11		29.96	30.88	30.35	29.76	29.28	29.27	28.51	30.57	29.66	29.39	28.50
12		29.93	30.85	30.38	29.76	29.25	29.31	28.93	30.57	29.62	29.34	28.53
13		29.92	30.80	30.44	29.76	29.24	29.33	29.29	30.57	29.61	29.31	28.62
14		29.91	30.68	30.44	29.72	29.23	29.36	29.32	30.56	29.61	29.28	28.62
15		29.89	30.66	30.44	29.69	29.19	29.35	29.31	30.55	29.61	29.25	28.54
16		29.87	30.53	30.46	29.66	29.18	29.33	29.70	30.54	29.59	29.16	28.44
17		29.84	30.47	30.46	29.64	29.19	29.32	29.78	30.54	29.60	29.10	28.47
18		29.82	29.90	30.41	29.63	29.12	29.30	29.61	30.53	29.59	29.08	28.52
19		29.80	29.39	30.36	29.63	29.13	29.75	29.56	30.52	29.61	29.06	28.51
20		29.77	29.28	30.32	29.64	29.06	30.10	29.56	30.50	29.60	28.99	28.47
21		29.81	30.26	30.29	29.62	29.01	29.94	29.57	30.48	29.58	28.89	28.47
22		29.93	30.28	30.19	29.59	29.05	29.84	29.56	30.46	29.62	28.88	28.76
23		29.93	30.24	30.18	29.56	29.06	29.76	29.56	30.44	29.63	28.90	29.14
24		30.46	30.25	30.12	29.54	29.00	29.72	31.51	30.42	29.65	28.84	29.13
25		30.76	30.24	30.17	29.53	28.94	29.68	30.86	30.40	29.65	28.77	29.12
26		30.77	30.25	30.25	29.53	28.86	29.66	30.74	30.36	29.65	28.72	29.11
27		30.78	30.26	30.16	29.52	29.00	29.66	30.70	30.32	29.65	28.81	29.08
28		30.82	30.23	30.06	29.50	28.89	29.65	30.68	30.22	29.65	28.76	29.07
29		30.80	30.16	30.03	29.48	28.88	29.63	30.60	30.12	29.62	28.72	30.31
30		30.77	30.11	29.99		28.89	29.60	30.71	30.05	29.58	28.75	30.83
31			30.02	29.95		28.91		30.72		29.54	28.68	
MEAN			30.48		29.71	29.16	29.38	29.52	30.48	29.68	29.14	28.80
MAX			30.96		29.94	29.46	30.10	31.51	30.62	29.99	29.56	30.83
MIN			29.28		29.48	28.86	28.87	28.50	30.05	29.54	28.68	28.44

50333500 RIVER GUT NEAR GOLDEN GROVE, ST. CROIX, VI

LOCATION.--Lat 17°42'46°, long 64°47'58°, Hydrologic Unit 21020002, on right bank, 0.4 mi (0.6 km) from Experimental Station, 0.9 mi (1.4 km) from intersection of Highway 66 and road 64, 0.3 mi (0.5 km) from University of the U.S. Virgin Islands (UVI).

DRAINAGE AREA. -- 5.40 mi 2 (9.14 km2).

WATER-DISCHARGE RECORDS

PERIOD OF RECORD. -- August 1990 to current year.

GAGE. -- Water-stage recorder. Elevation of gage is mean sea level.

REMARKS. -- Records poor. Gage-height and precipitation satellite telemetry at station.

		DISCHARG	R, CUBI	C FEET PER	SECOND, I	WATER YEA		1991 TO	September	1992		
DAY	oct	NOV	DEC	JAN	PEB	MAR	APR	MAY	JUN	JUL	AUG	SEP
1	.00	. 00	.00	. 00	.00	.00	.00	.00	.00	.00	.00	.00
2	.00	.00	.00	.00	.00	.00	.00	.00	.00	.00	.00	. 00
3	.00	. 00	.00	.00	.00	.00	.00	.00	.00	.00	.00	.00
4 5	.00	.00	.00	. 00	.00	. 00	.00	.00	.00	.00	.00 .00	.00 .00
	.00	.00	.00	.00	.00	.00	.00	.00				
6 7	.00 .00	.00	.00 .00	. 00 . 00	.00	. 00 . 00	.00 .00	.00 .00	.00	.00	.00 .00	.00 .00
8	.00	.00	.00	.00	.00	.00	.00	.00	.00	. 00	.00	. 00
ğ	.00	. 00	.00	.00	.00	. 00	.00	.00	.00	.00	.00	.00
10	.00	.00	.00	.00	.00	.00	.00	.00	.00	.00	.00	.00
11	.00	. 00	.00	. 00	.00	.00	.00	.00	.00	.00	.00	.00
12	.00	. 00	.00	. 00	.00	. 00	.00	. 00	.00	.00	.00	. 00
13 14	.00	. 00 . 00	.00	. 00 . 00	.00	. 00 . 00	.00 .00	.00 .00	.00 .00	.00 .00	.00 .00	.00 .00
15	.00	.00	.00	.00	.00 .00	. 00	.00	.00	.00	.00	.00	.00
16	.00	.00	.00	.00	.00	.00	.00	.00	.00	.00	.00	.00
17	.00	.00	.00	. 00	.00	. 00	.00	.00	.00	.00	.00	.00
18	.00	.00	.00	.00	.00	. 00	.00	. 00	.00	.00	.00	.00
19 20	.00 .00	.00 .00	.00 .00	. 00 . 00	.00 .00	. 00 . 00	.00	.00 .00	.00	.00 .00	.00	.00
21	.00	. 00	.00	.00	.00	.00	.00	.00	.00	.00	.00	. 00
22	.00	. 00	.00	. 00	.00	.00	.00	.00	.00	.00	.00	.00
23	.00	.00	.00	.00	.00	. 00	.00	.00	.00	.00	.00	.00
24	.00	. 00	.00	. 00	.00	.00	.00	.00	.00	. 00	.00	. 00
25	.00	. 00	.00	. 00	.00	.00	.00	83	.00	.00	.00	.00
26 27	.00 .00	.00	.00	. 00	.00	. 00	.00 .00	. 27	.00 .00	.00 .00	.00	.00 . 0 0
28	.00	. 00 . 00	.00	.00 .00	.00 .00	.00	.00	.00 .00	.00	.00	.00	.00
29	.00	.00	.00	.00	.00	.00	.00	. 00	.00	. 00	.00	.00
30	.00	.00	.00	. 00		.00	.00	.00	.00	.00	.00	.00
31	.00		.00	.00		. 00		.00		.00	.00	
TOTAL	0.00	0.00	0.00	0.00	0.00	0.00	0.00	83.27	0.00	0.00	0.00	0.00
MBAN	.000	.000	.000	.000	.000	.000	. 000	2.69	.000	.000	.000	.000
MAX MIN	.00	.00 .00	.00	. 00	.00	. 00	.00	83	.00 .00	.00 .00	.00	.00 .00
AC-FT	.00 .00	.00	.00 .00	.00 .00	.00 .00	.00 .00	.00	.00 165	.00	.00	.00	.00
CFSM	.00	. 00	.00	. 00	.00	.00	.00	.50	. 0 0	.00	.00	.00
IN.	.00	.00	.00	.00	.00	.00	.00	. 57	.00	.00	.00	.00
STATIST	TICS OF MC	NTHLY MEAN	DATA F	OR WATER	TEARS 1990	- 1992,	BY WATER	YEAR (WY)				
MEAN	6.79	.43	.005	.000	.000	.000	.000	1.34	.000	.000	.000	.001
MAX	13.6	. 85	.009	.000	.000	.000	.000	2.69	. 000	.000	.000	.003
(WY)	1991	1991	1991	1991	1991	1991	1991	1992	1991	1991	1991	1990
MIN (WY)	.000 1992	.000 1992	.000 1992	.000 1991	.000 1991	.000 1991						
SUMMARY	(STATIST)	(CS	FOR	1991 CALE	NDAR YBÀR	P	OR 1992 WA	TER YEAR		WATER YE	LARS 1990	- 1992
ANNUAL		-					83.27					
annual Highest Lowest		BAN					. 23			.73 1.22 .23 169	2 3	1991 1992 26 1990
	DAILY ME			.0	0 Jan 1			Oct 1		.00) Aug	30 1990
ANNUAL	SEVEN-DAY	MINIMUM			Jan 1		.00	Oct 1		.00) Aug :	30 1990
	ANEOUS PE						742	May 25		860		26 1990
	ANEOUS PE							May 25		49.03	Oct :	26 1990
	RUNOFF (165 .04	2		52 5	,	
	RUNOFF (. 57			1.87		
	ENT EXCE			.0	0		. 00			.00		
50 PERC	CENT EXCE	BD\$.0	0		.00			.00		
90 PERC	CENT EXCE	BDS		.0	0		.00			. 00	0	

50333700 RIVER GUT AT HWY 66 AT FAIRPLAINS, ST. CROIX, VI

LOCATION.--Lat 17°42'31", long 64°47'16", Hydrologic Unit 21020002, 1.00 mi (1.61 km) southeast from Experimental Station, 1.10 mi (1.77 km) southeast from Hwy 70 and Hwy 64 intersection, 0.50 mi (0.80 km) west from Anguilla ruins.

DRAINAGE AREA. -- 5.89 mi 2 (15.26 km2).

WATER-STAGE RECORDS

PERIOD OF RECORD. -- May 1990 to current year (gage-height only).

GAGE.--Water-stage recorder. Elevation of gage is 20 ft (6 m), from topographic map.

 $\label{eq:REMARKS.--Gage-height and precipitation satellite telemetry at station. \\$

EXTREMES FOR CURRENT PERIOD.--MAY TO SEPTEMBER 1990: Maximum gage-height during period, 10.56 ft (3.219 m); minimum, 10.46 ft (3.188 m), many days, but could be lower.

WATER YEAR 1991: Maximum gage-height, 13.87 ft (4.228 m), Oct. 14; minimum, 10.46 ft (3.188 m), many days, but could be lower.

WATER YEAR 1992: Maximum gage-height, 15.34 ft (4.676 m), May 25; minimum, 10.46 ft (3.188 m), many days, but could be lower.

GAGE HEIGHT, FERT, WATER YEAR OCTOBER 1989 TO SEPTEMBER 1990 DAILY MEAN VALUES

DAY	OCT	NOV	DBC	JAN	PEB	MAR	APR	MAY	JUN	JUL	AUG	SEP
1									10.46	10.46	10.46	10.46
2									10.46	10.46	10.46	10.46
2 3									10.46	10.46	10.46	10.46
4								10.47	10.46	10.46	10.46	10.46
5								10.46	10.46	10.46	10.46	10.46
								20120	10.10	20120	20.11	
6 7								10.47	10.46	10.46	10.46	10.46
7								10.46	10.46	10.46	10.46	10.46
8								10.46	10.46	10.46	10.46	10.46
9								10.46	10.46	10.46	10.46	10.46
10								10.46	10.46	10.46	10.46	10.46
11								10.46	10.46	10.46	10.46	10.46
12								10.46	10.46	10.46	10.46	10.46
13								10.46	10.46	10.46	10.46	10.46
14								10.46	10.46	10.46	10.46	10.47
15												10.46
13								10.46	10.46	10.46	10.46	10.46
16								10.46	10.46	10.46	10.46	10.47
17								10.46	10.46	10.46	10.46	10.46
18								10.46	10.46	10.46	10.46	10.46
19								10.46	10.46	10.46	10.46	10.46
20								10.46	10.46	10.46	10.46	10.46
21								10.46	10.46	10.46	10.46	10.46
22								10.46	10.46	10.46	10.46	10.46
23								10.46	10.46	10.46	10.46	10:46
24								10.46	10.46	10.46	10.46	10.46
25								10.46	10.46	10.46	10.46	10.46
43								10.46	10.46	10.46	10.46	10.46
26								10.46	10.46	10.46	10.46	10.46
27								10.46	10.46	10.46	10.46	10.46
28								10.46	10.46	10.46	10.46	10.46
29								10.46	10.46	10.46	10.46	10.46
30								10.46	10.46	10.46	10.46	10.46
31								10.46		10.46	10.46	
MBAN									10.46	10.46	10.46	10.46
MAX									10.46	10.46	10.46	10.46
MIN									10.46	10.46	10.46	10.47
MIT M									10.46	10.46	10.46	10.46

ST. CROIX, U.S. VIRGIN ISLANDS

50333700 RIVER GUT AT HWY 66 AT FAIRPLAINS, ST. CROIX, VI--Continued

GAGE HEIGHT, FRET, WATER YEAR OCTOBER 1990 TO SEPTEMBER 1991 DAILY MEAN VALUES

						D.1.1.1	at theodo					
DAY	OCT	NOV	DEC	JAN	PRB	MAR	APR	MAY	JUN	JUL	AUG	SEP
1	10.46	10.46	10.46	10.46	10.46	10.47	10.46	10.47	10.46	10.46	10.46	10.46
2	10.46	10.46	10.46	10.46	10.46	10.48	10.46	10.47	10.46	10.46	10.46	10.46
3	10.46	10.46	10.46	10.46	10.46	10.48	10.46	10.47	10.46	10.46	10.46	10.46
4	10.46	10.46	10.46	10.46	10.46	10.47	10.46	10.47	10.46	10.46	10.46	10.46
5	10.46	10.46	10.46	10.46	10.46	10.46	10.46	10.47	10.46	10.46	10.46	10.46
6	10.46	10.46	10.46	10.46	10.46	10.46	10.46	10.47	10.46	10.46	10.46	10.46
7	10.46	10.46	10.46	10.46	10.46	10.46	10.46	10.47	10.46	10.46	10.46	10.46
8	10.46	10.46	10.46	10.46	10.46	10.46	10.46	10.47	10.46	10.46	10.46	10.46
9	10.46	10.46	10.46	10.46	10.46	10.46	10.46	10.47	10.46	10.46	10.46	10.46
10	10.81	10.46	10.46	10.46	10.46	10.46	10.46	10.47	10.46	10.46	10.46	10.46
11	11.23	10.46	10.46	10.46	10.46	10.46	10.46	10.47	10.46	10.46	10.46	10.46
12	10.75	10.46	10.46	10.46	10.46	10.46	10.46	10.47	10.46	10.46	10.46	10.46
13	10.46	10.46	10.46	10.46	10.47	10.46	10.46	10.47	10.46	10.46	10.46	10.46
14	11.33	10.46	10.46	10.46	10.47	10.46	10.46	10.47	10.46	10.46	10.46	10.46
15	10.48	10.46	10.46	10.46	10.46	10.46	10.46	10.47	10.46	10.47	10.46	10.46
16	10.98	10.46	10.46	10.46	10.46	10.46	10.46	10.47	10.46	10.47	10.46	10.46
17	10.67	10.46	10.46	10.46	10.46	10.46	10.46	10.47	10.46	10.46	10.46	10.46
18	10.46	10.46	10.46	10.46	10.46	10.46	10.46	10.47	10.46	10.46	10.46	10.46
19	10.46	10.46	10.46	10.46	10.46	10.46	10.46	10.47	10.46	10.46	10.46	10.46
20	10.46	10.46	10.46	10.46	10.47	10.46	10.46	10.47	10.47	10.46	10.46	10.46
21	10.46	10.46	10.46	10.46	10.47	10.46	10.46	10.47	10.46	10.46	10.46	10.46
22	10.46	10.46	10.46	10.46	10.47	10.46	10.46	10.47	10.46	10.46	10.46	10.46
23	10.46	10.46	10.46	10.46	10.47	10.46	10.46	10.47	10.46	10.46	10.46	10.46
24	10.46	10.46	10.46	10.46	10.47	10.46	10.46	10.47	10.46	10.46	10.46	10.46
25	10.48	10.46	10.46	10.46	10.47	10.46	10.46	10.47	10.46	10.46	10.46	10.46
26	11.86	10.46	10.46	10.46	10.47	10.46	10.47	10.47	10.46	10.46	10.46	10.46
27	10.46	10.46	10.46	10.46	10.47	10.46	10.47	10.47	10.46	10.46	10.46	10.46
28	10.46	10.46	10.46	10.46	10.47	10.46	10.47	10.47	10.46	10.46	10.46	10.46
29	10.46	10.46	10.46	10.46		10.46	10.47	10.47	10.46	10.46	10.46	10.48
30	10.46	10.46	10.46	10.46		10.46	10.47	10.47	10.46	10.46	10.46	10.47
31	10.46		10.46	10.46		10.46		10.47		10.46	10.46	
MEAN	10.60	10.46	10.46	10.46	10.46	10.46	10.46	10.47	10.46	10.46	10.46	10.46
MAX	11.86	10.46	10.46	10.46	10.47	10.48	10.47	10.47	10.47	10.47	10.46	10.48
MIN	10.46	10.46	10.46	10.46	10.46	10.46	10.46	10.47	10.46	10.46	10.46	10.46

ST. CROIX, U.S. VIRGIN ISLANDS

50333700 RIVER GUT AT HWY 66 AT FAIRPLAINS, ST. CROIX, VI--Continued

GAGE HEIGHT, FEET, WATER YEAR OCTOBER 1991 TO SEPTEMBER 1992 DAILY MEAN VALUES

DAY	OCT	VON	DEC	JAN	FRB	MAR	APR	MAY	JUN	JUL	AUG	SEP
1	10.46	10.47	10.46	10.46	10.46	10.46	10.46	10.46	10.46	10.46	10.46	10.46
2	10.47	10.46	10.47	10.46	10.46	10.46	10.46	10.46	10.46	10.46	10.46	10.46
3	10.46	10.47	10.46	10.46	10.46	10.46	10.46	10.46	10.46	10.46	10.46	10.46
4	10.47	10.47	10.46	10.46	10.46	10.46	10.46	10.46	10.46	10.46	10.46	10.46
5	10.46	10.47	10.47	10.46	10.46	10.46	10.46	10.46	10.46	10.46	10.46	10.46
6	10.47	10.47	10.46	10.46	10.46	10.46	10.46	10.46	10.46	10.46	10.46	10.46
7	10.47	10.46	10.46	10.46	10.46	10.46	10.46	10.46	10.46	10.46	10.46	10.46
8	10.46	10.47	10.46	10.46	10.46	10.46	10.46	10.46	10.46	10.46	10.46	10.46
9	10.46	10.47	10.46	10.46	10.46	10.46	10.46	10.46	10.46	10.46	10.46	10.46
10	10.47	10.47	10.46	10.46	10.46	10.46	10.46	10.46	10.46	10.46	10.46	10.46
11	10.46	10.47	10.46	10.46	10.46	10.46	10.46	10.46	10.46	10.46	10.46	10.46
12	10.46	10.47	10.46	10.46	10.46	10.46	10.46	10.46	10.46	10.46	10.46	10.46
13	10.46	10.47	10.46	10.46	10.46	10.46	10.46	10.46	10.46	10.46	10.46	10.46
14	10.47	10.47	10.46	10.46	10.46	10.46	10.46	10.46	10.46	10.46	10.46	10.46
15	10.46	10.47	10.46	10.46	10.46	10.46	10.46	10.46	10.46	10.46	10.46	10.46
16	10.47	10.47	10.46	10.46	10.46	10.46	10.46	10.46	10.46	10.46	10.46	10.46
17	10.47	10.47	10.46	10.46	10.46	10.46	10.46	10.46	10.46	10.46	10.46	10.46
18	10.47	10.47	10.46	10.46	10.46	10.46	10.46	10.46	10.46	10.46	10.46	10.46
19	10.46	10.46	10.46	10.46	10.46	10.46	10.46	10.46	10.46	10.46	10.46	10.46
20	10.46	10.46	10.46	10.46	10.46	10.46	10.46	10.46	10.46	10.46	10.46	10.46
21	10.47	10.46	10.46	10.46	10.46	10.46	10.46	10.46	10.46	10.46	10.46	10.46
22	10.46	10.47	10.46	10.46	10.46	10.47	10.46	10.46	10.46	10.46	10.46	10.46
23	10.47	10.47	10.46	10.46	10.46	10.46	10.46	10.46	10.46	10.46	10.46	10.46
24	10.47	10.47	10.46	10.46	10.46	10.46	10.46	10.46	10.46	10.46	10.46	10.46
25	10.47	10.46	10.46	10.46	10.46	10.46	10.46	11.15	10.46	10.46	10.46	10.46
26	10.47	10.46	10.46	10.46	10.46	10.46	10.46	10.64	10.46	10.46	10.46	10.46
27	10.46	10.46	10.46	10.46	10.46	10.47	10.46	10.46	10.46	10.46	10.46	10.46
28	10.47	10.46	10.46	10.46	10.46	10.46	10.46	10.46	10.46	10.46	10.46	10.46
29	10.47	10.46	10.46	10.46	10.46	10.46	10.46	10.46	10.46	10.46	10.46	10.46
30	10.46	10.46	10.46	10.46		10.46	10.46	10.46	10.46	10.46	10.46	10.46
31	10.47		10.46	10.46		10.46		10.46		10.46	10.46	
MEAN	10.47	10.47	10.46	10.46	10.46	10.46	10.46	10.49	10.46	10.46	10.46	10.46
MAX	10.47	10.47	10.47	10.46	10.46	10.47	10.46	11.15	10.46	10.46	10.46	10.46
MIN	10.46	10.46	10.46	10.46	10.46	10.46	10.46	10.46	10.46	10.46	10.46	10.46

50334500 BETHLEHEM GUT AT HWY 66 AT FAIRPLAINS, ST.CROIX, VI

LOCATION.--Lat 17°42'31", long 64°47'15", Hydrologic Unit 21020002, 1.00 mi (1.61 km) southeast from Experimental Station, 1.10 mi (1.77 km) southeast from Hwy 70 and Hwy 64 intersection, 0.50 mi (0.80 km) west from Anguilla ruins.

DRAINAGE AREA. -- 4.11 mi 2 (10.64 km2).

WATER-STAGE RECORDS

PERIOD OF RECORD. -- 1963 to 1969 monthly measurements only, May 1990 to current year (gage-height only). Prior to 1990 published as Bethlehem Gut at upper Bethlehem.

GAGE .- Water-stage recorder. Elevation of gage is 20 ft (6 m), from topographic map.

REMARKS.--Gage-height and precipitation satellite telemetry at station.

EXTREMES FOR CURRENT PERIOD. -- MAY TO SEPTEMBER 1990: Maximum gage-height during period, 14.00 ft (4.267 m), Sept. 16; minimum, 11.45 ft (3.490 m), many days, but could be lower.

WATER YEAR 1991: Maximum gage-height, 18.33 ft (5.587 m), Oct. 26; minimum, 11.45 ft (3.490 m), many days, but could be lower.

WATER YEAR 1992: Haximum gage-height, 19.28 ft (5.876 m), May 25; minimum, 11.45 ft (3.490 m), many days, but could be lower.

GAGE HEIGHT, FEET, WATER YEAR OCTOBER 1989 TO SEPTEMBER 1990 DAILY MEAN VALUES

DAY	OCT	NOA	DEC	JAN	FRB	MAR	APR	MAY	JUN	JUL	AUG	SEP
1									11.45	11.45	11.45	11.45
1 2									11.45	11.45	11.45	11.45
3									11.45	11.45	11.45	11.45
3 4 5								11.45	11.45	11.45	11.45	11.45
5								11.45	11.45	11.45	11.45	11.45
6								11.45	11.45	11.45	11.45	11.45
7								11.45	11.45	11.45	11.45	11.45
7 8								11.45	11.45	11.45	11.45	11.45
9								11.45	11.45	11.45	11.45	11.45
10								11.45	11.45	11.45	11.45	11.45
11								11.45	11.45	11.45	11.45	11.45
12								11.45	11.45	11.45	11.45	11.45
13								11.45	11.45	11.45	11.59	11.45
14								11.45	11.46	11.45	11.56	11.45
15								11.45	11.46	11.45	11.45	11.45
16								11.45	11.46	11.45	11.45	12.46
17								11.45	11.45	11.45	11.45	11.70
18								11.45	11.45	11.45	11.45	11.71
19								11.45	11.45	11.45	11.45	11.60
20								11.45	11.45	11.45	11.45	11.46
21								11.45	11.45	11.45	11.45	11.45
22								11.45	11.45	11.45	11.45	11.45
23								11.45	11.45	11.45	11.45	11.45
24								11.45	11.46	11.45	11.45	11.76
25								11.45	11.45	11.45	11.45	11.95
26								11.45	11.45	11.45	11.45	11.74
27								11.45	11.45	11.45	11.45	11.61
28								11.45	11.45	11.45	11.45	11.51
29								11.45	11.45	11.45	11.45	11.64
30								11.45	11.45	11.45	11.45	11.87
31								11.45		11.45	11.45	
MBAN									11.45	11.45	11.46	11.57
MAX									11.46	11.45	11.59	12.46
MIN									11.45	11.45	11.45	11.45
									11.43	11.43	11.43	11.43

ST. CROIX, U.S. VIRGIN ISLANDS

50334500 BETHLEHEM GUT AT HWY 66 AT FAIRPLAINS, ST. CROIX, VI--Continued

GAGE HEIGHT, FEET, WATER YEAR OCTOBER 1990 TO SEPTEMBER 1991 DAILY MEAN VALUES

DAY	OCT	NOV	DEC	JAN	PRB	MAR	APR	MAY	JUN	JUL	AUG	SEP
1	12.03	12.21	11.48	11.45	11.45	11.45	11.45	11.45	11.45	11.45	11.45	11.45
2	11.77	12.11	11.49	11.45	11.45	11.45	11.45	11.45	11.45	11.45	11.45	11.45
3	11.70	12.03	11.54	11.45	11.45	11.45	11.45	11.45	11.45	11.45	11.45	11.45
4	11.61	12.64	11.51	11.45	11.45	11.45	11.45	11.45	11.45	11.45	11.45	11.45
5	11.53	12.40	11.47	11.45	11.45	11.45	11.45	11.45	11.45	11.45	11.45	11.45
-	11.30	12.40	11.47	11.45	11.45	11.45	11.45	11.45	11.45	11.43	11.43	11.43
6	11.46	12.19	11.45	11.45	11.45	11.45	11.45	11.45	11.45	11.45	11.45	11.45
7	11.45	12.09	11.45	11.45	11.45	11.45	11.45	11.45	11.45	11.45	11.45	11.45
8	11.45	11.96	11.45	11.45	11.45	11.45	11.45	11.46	11.45	11.45	11.45	11.45
9	12.22	11.87	11.45	11.45	11.45	11.45	11.45	11.45	11.45	11.45	11.45	11.45
10		11.79	11.45	11.45	11.45	11.45	11.45	11.45	11.45	11.45	11.45	11.45
11		11.70	11.45	11.45	11.45	11.45	11.45	11.45	11.45	11.45	11.45	11.45
12		11.61	11.45	11.45	11.45	11.45	11.45	11.45	11.45	11.45	11.45	11.45
13		11.52	11.45	11.45	11.45	11.45	11.45	11.45	11.45	11.45	11.45	11.45
14		11.48	11.45	11.45	11.45	11.45	11.45	11.45	11.45	11.45	11.45	11.45
15		11.45	11.45	11.45	11.45	11.45	11.45	11.45	11.45	11.45	11.45	11.45
16		11.45	11.45	11.45	11.45	11.45	11.45	11.45	11.45	11.45	11.45	11.45
17		11.45	11.45	11.45	11.45	11.45	11.45	11.45	11.45	11.45	11.45	11.45
18		11.45	11.45	11.45	11.45	11.45	11.45	11.45	11.45	11.45	11.45	11.45
19		11.45	11.45	11.45	11.45	11.45	11.45	11.45	11.45	11.45	11.45	11.45
20		11.91	11.45	11.45	11.45	11.45	11.45	11.45	11.45	11.45	11.45	11.45
21		12.15	11.45	11.45	11.45	11.45	11.45	11.45	11.45	11.45	11.45	11.45
22		12.00	11.45	11.45	11.45	11.45	11.45	11.45	11.45	11.45	11.45	11.45
23		11.90	11.45	11.45	11.45	11.45	11.45	11.45	11.45	11.45	11.45	11.45
24		11.82	11.45	11.45	11.45	11.45	11.45	11.45	11.45	11.45	11.45	11.45
25		11.77	11.45	11.45	11.45	11.45	11.45	11.45	11.45	11.45	11.45	11.45
26		44 70					44 45					11 45
27		11.70	11.45	11.45	11.45	11.45	11.45	11.45	11.45	11.45	11.45	11.45
28	12.45	11.63 11.56	11.45	11.45	11.45	11.45	11.45	11.45	11.45	11.45	11.45	11.45
29	12.45		11.45	11.45	11.45	11.45	11.45	11.45	11.45	11.45	11.45	11.45
30		11.45	11.45	11.45		11.45	11.45	11.45	11.45	11.45	11.45	11.45
	12.31	11.47	11.45	11.45		11.45	11.45	11.45	11.45	11.45	11.45	11.45
31	12.27		11.45	11.45		11.45		11.45		11.45	11.45	
MEAN		11.81	11.46	11.45	11.45	11.45	11.45	11.45	11.45	11.45	11.45	11.45
MAX		12.64	11.54	11.45	11.45	11.45	11.45	11.46	11.45	11.45	11.45	11.45
MIN		11.45	11.45	11.45	11.45	11.45	11.45	11.45	11.45	11.45	11.45	11.45
		11.43	11.43	11.43	11.43	11.43	11.43	11.43	14.43	11.43	11.43	11.43

ST. CROIX, U.S. VIRGIN ISLANDS

50334500 BETHLEHEM GUT AT HWY 66 AT FAIRPLAINS, ST. CROIX, VI--Continued

GAGE HEIGHT, FEET, WATER YEAR OCTOBER 1991 TO SEPTEMBER 1992 DAILY MEAN VALUES

DAY	ОСТ	NOV	DEC	jan	FEB	MAR	APR	MAY	JUN	JUL	AUG	SRP
1	11.45	11.45	11.45	11.45	11.46	11.45	11.46	11.45	11.88	11.45	11,45	11.45
2	11.45	11.45	11.45	11.45	11.45	11.45	11.46	11.45	11.82	11.45	11.45	11.45
3	11.45	11.45	11.45	11.45	11.46	11.45	11.46	11.45	11.76	11.45	11.45	11.45
4	11.45	11.45	11.45	11.45	11.45	11.45	11.46	11.45	11.70	11.45	11.45	11.45
5	11.45	11.45	11.45	11.45	11.45	11.45	11.46	11.45	11.63	11.45	11.45	11.45
6	11.45	11.45	11.45	11.45	11.45	11.45	11.46	11.45	11.57	11.45	11.45	11.45
7	11.45	11.45	11.45	11.45	11.45	11.45	11.46	11.45	11.51	11.45	11.45	11.45
8	11.45	11.45	11.45	11.45	11.45	11.45	11.46	11.45	11.46	11.45	11.45	11.45
9	11.45	11.45	11.45	11.45	11.45	11.45	11.46	11.45	11.45	11.45	11.45	11.45
10	11.45	11.45	11.45	11.45	11.45	11.45	11.46	11.45	11.45	11.45	11.45	11.45
11	11.45	11.45	11.45	11.45	11.45	11.45	11.46	11.45	11.45	11.45	11.45	11.45
12	11.45	11.45	11.45	11.45	11.45	11.45	11.46	11.45	11.45	11.45	11.45	11.45
13	11.45	11.45	11.45	11.45	11.45	11.45	11.46	11.45	11.45	11.45	11.45	11.45
14	11.45	11.45	11.45	11.45	11.45	11.45	11.46	11.45	11.45	11.45	11.45	11.45
15	11.45	11.45	11.45	11.45	11.45	11.45	11.46	11.45	11.45	11.45	11.45	11.45
16	11.45	11.45	11.45	11.45	11.45	11.45	11.46	11.45	11.45	11.45	11.45	11.45
17	11.45	11.45	11.45	11.45	11.45	11.45	11.46	11.45	11.45	11.45	11.45	11.45
18	11.45	11.45	11.45	11.45	11.45	11.45	11.46	11.45	11.45	11.45	11.45	11.45
19	11.45	11.45	11.45	11.45	11.45	11.45	11.47	11.45	11.45	11.45	11.45	11.45
20	11.45	11.45	11.45	11.45	11.45	11.45	11.46	11.45	11.45	11.45	11.45	11.45
21	11.45	11.45	11.45	11.45	11.45	11.45	11.46	11.45	11.45	11.45	11.45	11.45
22	11.45	11.45	11.45	11.45	11.45	11.45	11.46	11.45	11.45	11.45	11.45	11.45
23	11.45	11.45	11.45	11.45	11.45	11.45	11.46	11.45	11.45	11.45	11.45	11.45
24	11.45	11.45	11.46	11.45	11.45	11.45	11.46	11.92	11.45	11.45	11.45	11.45
25	11.45	11.45	11.46	11.45	11.45	11.45	11.46	13.09	11.45	11.45	11.45	11.45
26	11.45	11.45	11.46	11.45	11.45	11.45	11.46	12.77	11.45	11.45	11.45	11.45
27	11.45	11.45	11.46	11.45	11.45	11.45	11.46	12.43	11.45	11.45	11.45	11.45
28	11.45	11.45	11.45	11.45	11.45	11.46	11.46	12.23	11.45	11.45	11.45	11.45
29	11.45	11.45	11.45	11.45	11.45	11.46	11.45	12.11	11.45	11.45	11.45	11.45
30	11.45	11.45	11.45	11.45		11.46	11.45	12.03	11.45	11.45	11.45	11.45
31	11.45		11.45	11.46		11.46		11.96		11.45	11.45	
MEAN	11.45	11.45	11.45	11.45	11.45	11.45	11.46	11.67	11.51	11.45	11.45	11.45
MAX	11.45	11.45	11.46	11.46	11.46	11.46	11.47	13.09	11.88	11.45	11.45	11.45
MIN	11.45	11.45	11.45	11.45	11.45	11.45	11.45	11.45	11.45	11.45	11.45	11.45

503375000 GUT 4.5 AT CAME VALLEY, ST. CROIX, VI

LOCATION.--Lat 17°43'25", long 66°51'01", Hydrologic Unit 21020002, 2.1 mi (3.4 km) northeast from St. Patricks School at Frederiksted, 1.6 mi (2.6 km) northeast from Zion Church on Centerline road and 1.25 mi (2.0 km) from Mother of Perpetual Help Church near Monpedlier road 76.

DRAINAGE AREA. -- 0.21 mi2 (0.54 km2).

WATER-STAGE RECORDS

PERIOD OF RECORD. -- October 1991 to September 1992 (gage-height only).

GAGE. -- Water-stage recorder. Elevation of gage is 300 ft (91 m), from topographic map.

REMARKS.--Gage-height and precipitation satellite telemetry at station. All gage-height of 49.28 ft or lower are considered zero flow.

EXTREMES FOR CURRENT YEAR. -- Maximum gage height, 50.65 ft (15.438 m) May 24; minimum, 49.27 ft (15.017 m), many days.

GAGE HEIGHT, FEET, WATER YEAR OCTOBER 1991 TO SEPTEMBER 1992 DAILY MEAN VALUES

DAY	OCT	NOV	DEC	JAN	PEB	MAR	APR	MAY	JUN	JOL	AUG	SEP
1	49.28	49.28	49.28	49.28	49.28	49.28	49.27	49.27	49.29			49.28
2	49.28	49.28	49.28	49.28	49.28	49.28	49.27	49.27	49.29			49.28
3	49.28	49.28	49.28	49.28	49.28	49.28	49.27	49.27	49.29			49.28
4	49.27	49.28	49.28	49.28	49.28	49.28	49.27	49.27	49.29			49.28
5	49.27	49.28	49.28	49.28	49.28	49.28	49.27	49.27	49.29			49.28
6	49.27	49.30	49.28	49.28	49.28	49.28	49.27	49.27	49.29			49.28
7	49.27		49.28	49.28	49.28	49.28	49.27	49.27	49.29			49.28
8	49.27		49.28	49.28	49.28	49.28	49.27	49.27	49.29			49.28
9	49.27	49.28	49.28	49.28	49.28	49.28	49.27	49.27	49.29			49.28
10	49.27	49.28	49.28	49.28	49.28	49.28	49.28	49.27	49.29			49.28
11	49.27	49.28	49.28	49.28	49.28	49.28	49.27	49.27	49.29			49.28
12	49.27	49.28	49.28	49.28	49.28	49.28	49.27	49.27				49.28
13	49.27	49.28	49.28	49.28	49.28	49.28	49.27	49.27				49.28
14	49.27	49.28	49.28	49.28	49.28	49.28	49.27	49.27				49.28
15	49.27	49.28	49.28	49.28	49.28	49.28	49.27	49.28				49.28
16	49.27	49.28	49.28	49.28	49.28	49.28	49.27	49.28				49.28
17	49.27	49.28	49.28	49.28	49.28	49.28	49.27	49.28				49.28
18	49.27	49.28	49.28	49.28	49.28	49.28	49.27	49.28		~		49.28
19	49.27	49.28	49.28	49.28	49.28	49.28	49.27	49.28		~ ~ ~		49.28
20	49.27	49.28	49.28	49.28	49.28	49.28	49.27	49.28				49.28
21	49.27	49.28	49.28	49.28	49.28	49.28	49.27	49.28				49.28
22	49.27	49.28	49.28	49.28	49.28	49.28	49.27	49.28				49.28
23	49.27	49.28	49.28	49.28	49.28	49.28	49.27	49.28				49.28
24	49.27	49.28	49.28	49.28	49.28	49.28	49.27	49.81				49.28
25	49.28	49.28	49.28	49.28	49.28	49.28	49.27	49.76				49.28
26	49.28	49.28	49.28	49.28	49.28	49.28	49.27	49.45				49.28
27	49.28	49.28	49.28	49.28	49.28	49.27	49.27	49.27				49.28
28	49.28	49.28	49.28	49.28	49.28	49.27	49.27	49.29			49.28	49.28
29	49.28	49.28	49.28	49.28	49.28	49.27	49.27	49.29			49.28	49.50
30	49.28	49.28	49.28	49.28		49.27	49.27	49.29			49.28	49.33
31	49.28		49.28	49.28		49.27		49.29			49.28	
MEAN	49.27		49.28	49.28	49.28	49.28	49.27	49.31				49.29
MAX	49.28		49.28	49.28	49.28	49.28	49.28	49.81				49.50
MIN	49.27		49.28	49.28	49.28	49.27	49.27	49.27				49.28

50345000 JOLLY HILL GUT AT JOLLY HILL, ST. CROIX, VI

LOCATION.--Lat 17°44'00", long 64°51'47", Hydrologic Unit 21020002, on Mahogany Road at Jolly Hill, 1.8 mi (2.9 km) northeast of Frederiksted.

DRAINAGE AREA. -- 2.10 mi 2 (5.44 km2).

WATER-DISCHARGE RECORDS

PERIOD OF RECORD. -- January 1963 to December 1968. Monthly measurements, 1962-69. October 1982 to current year.

GAGE.--Water-stage recorder, crest-stage gage and sharp-crested concrete control. Elevation of gage is 140 ft (43 m), from topographic map.

REMARKS.--Records poor. Low-water diversions upstream from station. Gage-height and precipitation satellite telemetry at station.

		DISCHAR	GR, CUBIC	PBBT PRR			YEAR OCTOBER VALUES	1991 TO	SEPTEMBER	1992		
DAY	OCT	NOV	DEC	JAN	FRB	MAR	APR	MAY	JUN	JUL	AUG	SEP
1	.00	.00	.00	.00	.00	. 00	.35	.00	.24	.00	e.00	.00
2	.00	.00	.00	.00	.00	.00		.00	.31	.00		. 00
3	.00	.00	.00	. 00	.00	.00		.00	.31	. 00	e.00	. 00
4	.00	. 00	.00	. 00	.00	, 00		.00	.29	.00	e.00	.00
5	.00	.00	.00	.00	.00	. 00		.00	.29	.00	e.00	.00
6	.00	.00	.00	. 00	.00	. 00	.00	. 00	.29	.00	e.00	. 00
7	.00	.00	.00	. 00	.00	. 00		.00	.25	.00	e.00	.00
8	.00	. 00	.00	. 00	.00	. 00		.00	.24	.00	e.00	.00
9	.00	. 00	.00	. 00	.00	. 00		. 00	.23	.00	e.00	.00
10	.00	.00	.00	.00	.00	. 00		.00	.25	.00	e.00	.00
11	.00	.00	.00	.00	.00	. 00	.00	e.00	.22	.00	e.00	.00
12	.00	.00	.00	. 00	.00	. 00		.00	.22	.00	e.00	.00
13	.00	.00	.00	.00	.00	. 00	.00	.00	.21	.00	e.00	.00
14	.00	.00	.00	.00	.00	. 00		.00	.20	.00	e.00	.00
15	.00	.00	.00	. 00	.00	.00	.00	.00	.19	.00	e.00	.00
16	.00	.00	.00	.00	.00	. 00	.00	.00	.23	.00	e.00	.00
17	.00	.00	.00	. 00	.00	. 00		. 00	.20	.00	e.00	.00
18	.00	.00	.00	.00	.00	. 00	.00	.00	.15	.00	e.00	.00
19	.00	.00	.00	.00	.00	. 00	.00	.00	.14	.00	e.00	.00
20	.00	.00	.00	. 00	.00	. 00	.00	.00	.13	.00	.00	. 04
21	.00	.00	.00	.00	.00	. 00	.00	. 00	.12	.00	.00	. 12
22	.00	. 00	.00	.00	.00	. 00		.00	.11	.00	.00	.00
23	.00	. 00	.00	. 00	.00	. 00		.00	.11	.00	.00	.01
24	.00	.00	.00	.00	.00	. 00		12	.09	. 18	.00	.00
25	.00	.00	.00	.00	.00	. 00		. 51	.08	.00	.00	.00
26	.00	.00	.00	.00	.00	. 00	.00	.33	.07	.00	.00	.00
27	.00	.00	.00	.00	.00	. 00		.30	.06	.00	.00	.00
28	.00	.00	.00	. 00	.00	. 00		. 29	.09	.00	.00	.00
29	.00	. 00	.00	. 00	.00	.00		. 29	.06	.00	.00	. 66
30	.00	.00	.00	.00		. 00		. 32	.02	e.00	.00	2.8
31	.00		.00	.00		.00		.28		e.00	.00	
TOTAL	0.00	0.00	0.00	0.00	0.00	0.00	0.35	14.32	5.40	0.18	0.00	3.63
MEAN	.000	.000	.000	.000	.000	.000		.46	.18	.006	.000	.12
MAX	.00	.00	.00	.00	.00	.00		12	.31	. 18	.00	2.8
MIN	.00	. 00	.00	. 00	.00	. 00		. 00	.02	.00	.00	.00
AC-PT	.00	. 00	.00	.00	.00	. 00		28	11	. 4	.00	7.2
CFSM	.00	.00	.00	. 00	.00	. 00		. 22	.09	.00	.00	.06
IN.	.00	. 00	.00	. 00	.00	.00		.25	.10	.00	.00	.06
e Rs	timated											
STATIST	ICS OF MC	NTHLY ME	N DATA FO	OR WATER Y	EARS 1986	- 199	2, BY WATER	YEAR (WY)			
										000	0.4.0	25
mban Max	.69 2.14	1.00	.66	. 33	.20	. 11		.14	.28	.096	.040	.35
(WY)	1991	2.33 1988	2.34 1988	.88 1988	.55 1988	.34 1990		.46 1992	1.43 1987	.52 1987	.18 1987	2.15 1989
MIN	.000	.000	.000	.000	.000	.000		.000	.000	.000	.000	.000
(WY)	1987	1992	1992	1992	1989	1989		1989	1989	1989	1989	1991
SUMMARY	STATISTI	cs	FOR	1991 CALEN	DAR YRAR		FOR 1992 WA	TER YEAR		WATER Y	'EARS 1963 -	1992
ANNUAL												2004
ANNUAL				17.68 .04			23.88 .06			.1	.9	
	ANNUAL M	(RAN		,,,	•			•		.5		1988
LOWEST ANNUAL MEAN										003	1965	
HIGHEST DAILY MEAN			.33	Jan 2		12	May 24		22	Nov 27		
	DAILY MEA				Jun 14			Oct 1		.0	0 Oct 1	
ANNUAL SEVEN-DAY MINIMUM					Jun 14		.00	Oct 1		. 0	0 Sep 4	
instantaneous peak flow							118	May 24		430	Nov 27	
INSTANTANEOUS PRAK STAGE							May 24		4.1		1987	
	RUNOFF (A			35			47			140		
	RUNOFF (C			.02			. 03			.0		
	RUNOFF (I			.31			.42			1.2		
	ENT EXCES			.20			. 10			. 8		
50 PERC	ENT EXCES	SUS		.00			.00			. 0	•	

ST. CROIX, U.S. VIRGIN ISLANDS

50348000 SALT RIVER AT CANNAN, ST. CROIX, VI

LOCATION.--Lat 17°45'40", long 64°47'53", Hydrologic Unit 21020002, 6.20 mi (9.98 km) northwest from Cristianted Government House, 4.15 mi (6.68 km) north from Alexander Hamilton Airport main building, 3.10 mi (4.99 km) northeast from St. Lukes church at Grove Place.

DRAINAGE AREA. -- 0.36 mi 2 (0.93 km2).

WATER-STAGE RECORDS

PERIOD OF RECORD. -- September 1991 to September 1992 (gage-height only).

GAGE.--Water-stage recorder. Datum of gage is 315 ft (96 m), from topographic map.

REMARKS. -- Gage-height and precipitation satellite telemetry at station. All gage-heights of 49.02 ft or lower are considered zero flow.

EXTREMES FOR CURRENT YEAR. -- Maximum gage-height, 51.20 ft (15.606 m), May 24; minimum recorded, 48.98 ft (14.929 m), June 11-15.

GAGE HEIGHT, FEET, WATER YEAR OCTOBER 1991 TO SEPTEMBER 1992

DAILY MEAN VALUES												
DAY	ост	NOV	DEC	JAN	FRB	MAR	APR	MAY	JUN	ஶ	AUG	SEP
1	49.03	48.99	49.00	49.02		49.02	49.03	49.02	49.03			49.02
2	49.03	49.00	49.00	49.01		49.02	49.03	49.02	49.03			49.02
3	49.02	49.00	49.00			49.02	49.03	49.02	49.02			49.02
4	49.02	49.01	49.00			49.02	49.03	49.02	49.02			49.02
5	49.01	49.01	49.00			49.02	49.03	49.02	49.02			49.02
6	49.01	49.02	49.01			49.02	49.03	49.02	49.02			49.02
7	49.01	49.02	49.01			49.02	49.03	49.02	49.02			49.02
8	49.01	49.02	49.01			49.02	49.03	49.02	49.02			49.02
9	49.01	49.00	49.01			49.02	49.03	49.02	49.02			49.02
10	49.00	49.00	49.01			49.02	49.03	49.02	49.02			49.02
11	49.00	49.00	49.01		48.99	49.02	49.02	49.02	49.00			49.02
12	49.00	49.00	49.01		49.01	49.02	49.02	49.02	48.98			49.02
13	49.00	49.00	49.01		49.01	49.02	49.02	49.02	48.98			49.02
14	49.01	49.00	49.01		49.01	49.02	49.02	49.02	48.98			49.02
15	49.01	49.00	49.02		49.02	49.02	49.02	49.03	48.98			49.02
16	49.01	49.00	49.02		49.02	49.02	49.02	49.03				49.02
17	49.01	49.00	49.02		49.03	49.02	49.02	49.03				49.02
18	49.01	49.00	49.02		49.02	49.02	49.02	49.03				49.02
19	49.01	49.00	49.02		49.02	49.02	49.02	49.03				49.02
20	49.01	49.00	49.02		49.02	49.02	49.02	49.03				49.02
21	49.01	49.00	49.02		49.02	49.02	49.02	49.03				49.02
22	49.01	49.00	49.02		49.02	49.02	49.02	49.03				49.02
23	49.01	49.00	49.02		49.02	49.02	49.02	49.03				49.02
24	49.03	49.00	49.02		49.02	49.02		49.53				49.02
25	49.02	49.00	49.02		49.02	49.02		49.15				49.02
26	49.02	49.00	49.02		49.02	49.02		49.07				49.02
27	49.02	49.00	49.02		49.02	49.02		49.04			49.01	49.02
28	49.02	49.00	49.02		49.02	49.03	49.02	49.04			49.02	49.02
29	49.02	49.00	49.02		49.02	49.03	49.02	49.04			49.02	49.02
30	49.02	49.00	49.02			49.03	49.02	49.06			49.02	49.02
31	48.99		49.02			49.03		49.03			49.02	
MEAN	49.01	49.00	49.01			49.02		49.05				49.02
MAX	49.03	49.02	49.02			49.03		49.53				49.02
MIN	48.99	48.99	49.00			49.02		49.02				49.02

50349000 GUT 10 NEAR ALTONA, ST. CROIX, VI

LOCATION.--Lat 17°44'00", long 64°41'30", Hydrologic Unit 21020002, 1.3 mi (2.1 km) southeast of Christiansted, 0.95 mi (1.53 km) west of Prospect Hill and 1.0 mi (1.6 km) north of junction of Highways 62 and 85.

DRAINAGE ARRA. -- 0.13 mi 2 (0.34 km2).

WATER-STAGE RECORDS

PERIOD OF RECORD. -- November 1991 to September 1992 (gage-height only).

GAGE. -- Water-stage recorder. Rlevation of gage is 210 ft (64 m), from topographic map.


REMARKS.--Gage-height and precipitation satellite telemetry at station. All gage-height of 49.57 ft or lower are considered zero flow.

EXTREMES FOR CURRENT PERIOD. -- Maximum gage height, 50.80 ft (15.484 m) May 25; minimum, 49.50 ft (15.088 m), Dec. 12,22.

GAGE HEIGHT, FRET, WATER YEAR OCTOBER 1991 TO SEPTEMBER 1992 DAILY MEAN VALUES

DAY	OCT	NOV	DEC	JAN	FEB	MAR	APR	MAY	JUN	JUL	AUG	SEP
1		49.59	49.56	49.59	49.57	49.57	49.57	49.57	49.57	49.57	49.57	49.57
2 3		49.59	49.56	49.59	49.57	49.57	49.57	49.57	49.57	49.57	49.57	49.57
3		49.59	49.56	49.58	49.57	49.57	49.57	49.57	49.57	49.57	49.57	49.57
4		49.59	49.56	49.57	49.57	49.57	49.57	49.57	49.57	49.57	49.57	49.57
5		49.59	49.56	49.57	49.57	49.57	49.57	49.57	49.57	49.57	49.57	49.57
6		49.59	49.55	49.56	49.57	49.57	49.57	49.57	49.57	49.57	49.57	49.57
7 8		49.59	49.55	49.56	49.57	49.57	49.57	49.57	49.57	49.57	49.57	49.57
8		49.59	49.53	49.56	49.57	49.57	49.57	49.57	49.57	49.57	49.57	49.57
9		49.59	49.53	49.57	49.57	49.57	49.57	49.57	49.57	49.57	49.57	49.57
10		49.59	49.53	49.57	49.57	49.57	49.57	49.57	49.57	49.57	49.57	49.57
11		49.59	49.53	49.57	49.57	49.57	49.57	49.57	49.57	49.57	49.57	49.57
12		49.59	49.52	49.57	49.57	49.57	49.57	49.57	49.57	49.57	49.57	49.57
13		49.59	49.53	49.57	49.57	49.57	49.57	49.57	49.57	49.57	49.57	49.57
14		49.59	49.53	49.57	49.57	49.57	49.57	49.57	49.57	49.57	49.57	49.57
15		49.59	49.53	49.57	49.57	49.57	49.57	49.57	49.57	49.57	49.57	49.57
16		49.59	49.53	49.57	49.57	49.57	49.57	49.57	49.57	49.57	49.57	49.58
17		49.59	49.53	49.57	49.57	49.57	49.57	49.57	49.57	49.57	49.57	49.59
18		49.59	49.53	49.57	49.57	49.57	49.57	49.57	49.57	49.57	49.57	49.59
19		49.59	49.53	49.57	49.57	49.57	49.57	49.57	49.57	49.57	49.57	49.59
20		49.57	49.52	49.57	49.57	49.57	49.57	49.57	49.57	49.57	49.57	49.59
21		49.57	49.53	49.57	49.57	49.57	49.57	49.57	49.57	49.57	49.57	49.59
22		49.56	49.53	49.57	49.57	49.57	49.57	49.57	49.57	49.57	49.57	49.59
23		49.56	49.53	49.57	49.57	49.57	49.57	49.57	49.57	49.57	49.57	49.59
24		49.56	49.53	49.57	49.57	49.57	49.57	49.57	49.57	49.57	49.57	49.57
25		49.57	49.53	49.57	49.57	49.57	49.57		49.57	49.57	49.57	49.59
26		49.56	49.54	49.57	49.57	49.57	49.57	49.57	49.57	49.57	49.57	49.59
27		49.56	49.58	49.57	49.57	49.57	49.57	49.57	49.57	49.57	49.57	49.59
28		49.56	49.59	49.57	49.57	49.57	49.57	49.57	49.57	49.57	49.57	49.59
29		49.56	49.59	49.57	49.57	49.57	49.57	49.57	49.57	49.57	49.57	49.59
30		49.56	49.59	49.57		49.57	49.57	49.57	49.57	49.57	49.57	49.59
31			49.59	49.57		49.57		49.57		49.57	49.57	
MEAN		49.58	49.55	49.57	49.57	49.57	49.57		49.57	49.57	49.57	49.58
MAX		49.59	49.59	49.59	49.57	49.57	49.57		49.57	49.57	49.57	49.59
MIN		49.56	49.52	49.56	49.57	49.57	49.57		49.57	49.57	49.57	49.57

THIS PAGE WAS LEFT BLANK INTENTIONALLY



ST. CROIX, U.S. VIRGIN ISLANDS

174225064471900. Local number, 1.

LOCATION.--Lat 17°42'25", long 64°47'19", Hydrologic Unit 21020002, 6 mi southwest of Christiansted Plaza, 1.00 mi southeast of the Experimental Station, and 0.50 mi northeast of the Alexander Hamilton Airport entrance on Hwy 64. Owner: U.S. Virgin Islands Government, Name: Fairplains 6 (FP6).

AQUIFER . - - Alluvium and marl .

WELL CHARACTERISTICS. -- Observation drilled public supply water-table well, diameter 6 in (0.15 m), cased 6 in (0.15 m).

INSTRUMENTATION. -- Monthly measurement with chalked steel tape by USGS personnel.

DATUM.--Elevation of land-surface datum is about 20.0 ft (6.10 m) above mean sea level, from topographic map. Measuring point: Top of pump concrete base, 2.20 ft (0.67 m) above land-surface datum.

REMARKS .-- Observation well. Water levels affected by pumping.

PERIOD OF RECORD. -- March 1982 to current year.


EXTREMES FOR PERIOD OF RECORD.--Highest water level measured, 15.64 ft (4.77 m) below land-surface datum, Mar. 25, 1982; lowest water level measured, a59.26 ft (18.1 m) below land-surface datum, Apr. 25, 1990.

WATER LEVEL, IN FRET BELOW LAND-SURFACE DATUM, WATER YEAR OCTOBER 1991 TO SEPTEMBER 1992 INSTANTANEOUS OBSERVATIONS

Date	Water level	Date	Water level	Date	Water level	Date	Water level
Oct. 23 Dec. 3	20.22 20.70	Feb. 4 Mar. 12	20.96 20.78	May 28 July 1	18.14 17.76	July 27 Sept. 14	18.75 17.95
Jan. 7	19.80	Apr. 30	19.29	ouly 1	17.70	ocpt. 14	1,.,,

WATER YEAR 1992 HIGHEST 17.76 JULY 1, 1992 LOWEST 20.96 FEB. 4, 1992

a Pumping.




WATER YEAR

174225064472000. Local number, 2.
LOCATION.--Lat 17°42'25", long 64°47'20", Hydrologic Unit 21020002, 0.90 mi southeast of the Experimental Station,
0.6 mi southwest of Christiansted Plaza, and 0.18 mi northeast of the Alexander Hamilton Airport entrance on
Hwy 64. Owner: U.S. Virgin Islands Government, Name: USGS-10, Fairplains 2 (FP2).
AQUIFER.--Alluvium and marl.
WELL CHRACTERISTICS.--Drilled unused water-table well, diameter 6 in (0.15 m), cased 6 in (0.15 m).
INSTRUMENTATION.--Digital water level recorder--60-minute punch.
DATUM.--Elevation of land-surface datum is about 20 ft (6.10 m) above mean sea level, from topographic map.
Measuring point: Top of 0.5 in (0.01 m) hole at concrete base wall, 3.00 ft (0.91 m) above land-surface datum.
REMARKS.--Recording observation well. Nearby pumping well.
PERIOD OF RECORD.--June 1983 to current year.
EXTREMES FOR PERIOD OF RECORD.--Highest water level recorded, 19.45 ft (5.93 m) below land-surface datum, Nov. 4,
1989, lowest water level recorded, 26.46 ft (8.06 m) below land-surface datum, Aug. 25, 1990.

		WATER	LEVEL, IN	FRET BELOW INS	Land-Sure Tantanbous	ACE DATUM OBSERVAT	, WATER ION AT 1	YEAR OCTOE 1200	ER 1991	TO SEPTEME	ER 1992	
DAY	OCT	NO	V DE	C JAN	FRB	MAR	APR	MAY	JUN	JUL	AUG	SEP
1	24.11	24.1	0 24.3	4 24.46	24.63		25.07	24.53	23.46	23.32	23.46	23.79
2	24.09	24.0	8 24.4	4 24.51	24.73		25.05	24.49	23.50	23.24	23.46	23.69
3	24.07	24.0	7 24.4	3 24.50	24.64		25.07	24.47	23.30	23.30	23.40	23.58
4	24.16	24.0			24.79		25.08	24.42	23.45	23.14	23.52	23.73
5	24.15	24.1	7 24.4	0 24.51	24.80		25.13	24.48	23.42	23.17	23.46	23.62
6	24.12	24.3	6 24.3	8 24.53	24.83		25.03	24.45	23.45	23.17	23.52	23.57
7	24.16	24.3			24.93		25.09	24.40	23.39	23.31	23.52	23.50
8	24.12	24.3	1 24.3	5 24.50	24.84		25.10	24.70	23.31	23.25	23.48	23.46
9	24.09	24.3	0 24.3	2 24.51	24.92		25.09	24.62	23.42	23.40	23.47	23.50
10	24.07	24.2	6 24.3	1 24.56	24.81		25.05	24.64	23.30	23.33	23.51	23.49
11	24.15	24.2	8 24.3	2 24.55	24.83		25.26	24.66	23.38	23.40	23.51	23.48
12	23.98	24.3			24.83		25.06	24.72	23.38	23.35	23.69	23.40
13	24.07	24.3	4 24.3	5 24.54	24.96		25.22	24.57	23.35	23.35	23.70	23.39
14	24.01	24.3	3 24.5	2 24.58	24.90		25.14	24.52	23.32	23.49	23.67	23.37
15	24.00	24.3	4 24.5	8 24.59	24.89		24.95	24.76	23.29	23.48	23.76	23.40
16	24.14	24.3	3 24.5	9 24.63	24.97		24.69	24.72	23.24	23.48	23.97	23.32
17	24.15	24.3	1 24.5	6 24.65	24.53		24.58		23.29	23.39	23.93	23.28
18	24.13	24.2	9 24.5	1 24.65	24.38		24.67	24.77	23.24	23.47	23.85	23.21
19	24.11	24.3	0 24.5	1 24.64	24.36		24.40		23.23	23.41	23.82	23.40
20	24.07	24.3	2 24.6	2 24.65			24.41	24.82	23.30	23.36	23.95	23.48
21	24.02	24.3	2 24.5	3 24.65			24.34		23.22	23.44	24.02	23.47
22	24.01	24.3				~	24.31		23.28	23.52	23.87	23.53
23	24.04	24.3					24.21		23.35	23.51	23.96	23.53
24	24.02	24.3					24.35		23.33	23.46	23.96	23.57
25	24.19	24.3	3 24.4	3 24.71			24.16	24.28	23.23	23.44	23.83	23.64
26	24.10	24.3					24.22		23.31	23.43	23.96	23.61
27	24.07	24.3					24.09		23.28	23.55	23.88	23.67
28	24.10	24.3					24.04		23.26	23.54	24.02	23.56
29	24.14	24.2					24.23		23.32	23.46	23.93	23.66
30	24.11	24.2				25.03	24.32		23.21	23.47	23.88	23.67
31	24.11		- 24.5	2 24.77		25.01		23.59		23.56	23.70	
MBAN	24.09	24.2	9 24.4	4 24.61	24.77	25.02	24.71	24.47	23.33	23.39	23.73	23.52

WTR YR 1992 MEAN 24.11 HIGHEST 23.10 JULY 4, 1992 LOWEST 25.26 APR. 11, 1992



174243064475100. Local number, 3.
LOCATION.--Lat 17°42'43", long 64°47'51", Hydrologic Unit 21020002, 0.75 mi northwest of the Alexander Hamilton Airport entrance on Rwy 64, 6.45 mi southwest of Christiansted Plaza, and 0.57 mi southwest of the Experimental Station. Owner: U.S. Virgin Islands Government, Name: Golden Grove - 6 (PW6).

30.00

30.03

29.80

30.67

30.68

30.48

31.06

31.08

31.11

30.87

29

30

MRAN

AQUIFER.--Alluvium and marl.

WELL CHARACTERISTICS.--Drilled unused water-table well, diameter 8 in (0.20 m), cased 8 in (0.20 m).

INSTRUMENTATION.--Digital water level recorder--60-minute punch.

DATUM.--Elevation of land-surface datum is about 40 ft (12.2 m) above mean sea level, from topographic map.

Measuring point: Upper edge of hole at 8 in (0.20 m) casing, 4.20 ft (1.28 m) above land-surface datum. REMARKS. -- Recording observation well. PERIOD OF RECORD. -- March 1982 to current year.

EXTREMES FOR PERIOD OF RECORD. -- Highest water level recorded, 12.99 ft (3.96 m) below land-surface datum, Nov. 10, 1990; lowest water level recorded, 34.46 ft (10.5 m) below land-surface datum, May 27-28 1992.

WATER LEVEL, IN FEET BELOW LAND-SURFACE DATUM, WATER YEAR OCTOBER 1991 TO SEPTEMBER 1992

INSTANTANEOUS OBSERVATION AT 1200												
DAY	OCT	NOA	DBC	JAN	FEB	MAR	APR	MAY	JUN	JUL	AUG	SEP
1	29.51	30.07	30.69	31.13	31.49	32.19	32.92	33.47	30.93	30.85	31.94	33.01
2	29.52	30.11	30.71	31,14	31.52	32.23	32.95	33.49	30.55	30.88	31.97	33.05
2 3	29.54	30.14	30.72	31.15	31.55	32.24	32.98	33.51	30.21	30.93	31.99	33.08
4	29.56	30.19	30.73	31.17	31.57	32.27	32.99	33.53	29.97	30.97	32.01	33.11
5	29.57	30.22	30.75	31.19	31.59	32.30	33.01	33.59	29.78	31.01	32.05	33.14
6	29.60	30.25	30.77	31.21	31.61	32.34	33.03	33.63	29.64	31.05	32.07	33.17
7	29.63	30.30	30.79	31.22	31.63	32.37	33.05	33.67	29.52	31.09	32.10	33.18
8	29.66	30.32	30.81	31.23	31.65	32.39	33.08	33.71	29.46	31.13	32.12	33.19
9	29.69	30.35	30.83	31.24	31.67	32.41	33.10	33.73	29.42	31.16	32.16	33.20
10	29.70	30.39	30.83	31.23	31.69	32.44	33.11	33.78	29.42	31.19	32.20	33.22
11	29.72	30.42	30.83	31.24	31.72	32.48	33.13	33.83	29.44	31.23	32.26	33.23
12	29.75	30.44	30.84	31.26	31.75	32.51	33.14	33.86	29.47	31.27	32.30	33.24
13	29.76	30.46	30.84	31.28	31.77	32.54	33.16	33.89	29.52	31.31	32.33	33.25
14	29.79	30.50	30.83	31.29	31.78	32.57	33.17	33.96	29.61	31.33	32.38	33.26
15	29.81	30.54	30.85	31.30	31.79	32.59	33.18	33.99	29.70	31.37	32.41	33.28
16	29.83	30.57	30.85	31.32	31.81	32.65	33.20	34.05	29.76	31.42	32.46	33.30
17	29.85	30.59	30.83	31.33	31.82	32.68	33.23	34.09	29.85	31.46	32.52	33.32
18	29.87	30.62	30.84	31.34	31.84	32.70	33.25	34.14	29.93	31.49	32.56	33.34
19	29.89	30.64	30.86	31.35	31.87	32.71	33.26	34.17	30.00	31.52	32.60	33.36
20	29.91	30.66	30.88	31.37	31.86	32.73	33.26	34.19	30.08	31.54	32.67	33.38
21	29.92	30.65	30.90	31.39	31.87	32.74	33.28	34.23	30.19	31.63	32.70	33.40
22	29.92	30.64	30.92	31.40	31.89	32.77	33.31	34.30	30.27	31.68	32.72	33.41
23	29.92	30.64	30.93	31.40	31.90	32.78	33.32	34.33	30.33	31.72	32.75	33.43
24	29.93	30.64	30.96	31.40	31.92	32.80	33.34	34.39	30.44	31.74	32.77	33.45
25	29.93	30.65	30.98	31.41	31.96	32.82	33.36	34.42	30.51	31.76	32.79	33.47
26	29.94	30.66	31.01	31.41	32.01	32.85	33.37	34.44	30.56	31.79	32.85	33.49
27	29.95	30.67	31.02	31.42	32.02	32.86	33.39	34.45	30.62	31.81	32.88	33.52
28	29.98	30.66	31.04	31.42	32.11	32.88	33.41	34.45	30.70	31.85	32.91	33.54
												~~

32.91

32.92

32.89

32.60

WTR YR 1992 MEAN 31.76 HIGHEST 29.39 JUNE 10, 1992 LOWEST 34.46 MAY 27-28, 1992

32.14


31.79

31.43

31.44

31.46

31.31



33.45

32.31 31.53

33.83

30.77

30.81

30.05

31.87

31.90

31.92

31.42

32.94

32.96

32.97

32.46

33.57

33.57

33.31

33.43

33.45

33.20

ST. CROIX, U.S. VIRGIN ISLANDS

174245064475800. Local number, 4.

LOCATION.--Lat 17°42'45", long 64°47'58", Hydrologic Unit 21020002, 5.40 mi east of Fort Frederick at Frederickstead, 0.80 mi northeast of Envy, and 1.52 mi southeast of Holy Cross Church. Owner: U.S. Virgin Islands Government, Name: Golden Grove - 1 (PW1).

ACTIFER. -- Alluvium and marl

WELL CHARACTERISTICS. -- Observation drilled production water-table well, diameter 6 in (0.15 m), cased 6 in (0.15 m), 0-104 ft (0-31.70 m), perforated 64-104 ft (19.51-31.70 m). Depth 104 ft (31.70 m).

INSTRUMENTATION .-- Monthly measurement with chalked steel tape by USGS personnel.

DATUM.--Elevation of land-surface datum is about 40 ft (12.2 m) above mean sea level, from topographic map.

Measuring point: Lower edge of 1 in. (0.02 m) pipe at pump base, 3.40 ft (1.04 m) above land-surface datum.

REMARKS. -- Observation well. Water levels affected by pumping.


PERIOD OF RECORD. -- January 1983 to current year.

EXTREMES FOR PERIOD OF RECORD: Highest water level measured, 19.08 ft (5.81 m) below land-surface datum, Nov. 26, 1990; lowest water level measured, a58.30 ft (17.77 m) below land-surface datum, September 27, 1983.

WATER LEVEL, IN FEET BELOW LAND-SURFACE DATUM, WATER YEAR OCTOBER 1991 TO SEPTEMBER 1992 INSTANTANEOUS OBSERVATIONS

Date	Water level	Date	Water level	Date	Water level	Date	Water level
Jan. 8	a33.20	Mar. 13	35.38	May 27	34.99	July 28	34.41
Feb. 5	a33.72	Apr. 30	36.30	June 26	33.85	Sept. 15	35.72

WATER YEAR 1992 HIGHEST 33.20 JAN. 8, 1992 LOWEST 35.72 SEPT. 15, 1992



WATER YEAR

ST. CROIX, U.S. VIRGIN ISLANDS

174303064484400. Local number, 6.

LOCATION.--Lat 17°43'03", long 64°48'44", Hydrologic Unit 21020002, 4.95 mi northeast of Fort Frederick at Frederickstead, 1.10 mi southwest of Holy Cross Church, and 0.40 mi northwest of Adventure ruins. Owner: U.S. Virgin Islands Government, Name: Adventure 28.

AQUIFER.--Alluvium of Pleistocene age and marl of Oligocene age.

WELL CHARACTERISTICS. -- Drilled unused water-table well, diameter 4 in (0.10 m), cased 4 in (0.10 m). Depth 97 ft

(29.6 m).

INSTRUMENTATION. --Monthly measurement with chalked steel tape by USGS personnel.

DATUM. --Elevation of land-surface datum is about 80 ft (24.39 m) above mean sea level, from topographic map.

Measuring point: Upper edge of hole at 4 in (0.10 m) casing, 2.00 ft (0.61 m) above land-surface datum. Prior

June 20, 1983, top of 4 in (0.10 m) casing, 0.90 ft (0.27 m) above land-surface datum.


REMARKS.--Recording observation well.

PERIOD OF RECORD.--August 1973 to March 1974, discontinued. March 1982 to current year.

EXTREMES FOR PERIOD OF RECORD.--Highest water level measured, 22.80 ft (6.95 m) below land-surface datum, Feb. 13, 1991; lowest water level recorded, 40.18 ft (12.25 m) below land-surface datum, Aug. 5, 1984.

WATER LEVEL, IN FRET BELOW LAND-SURFACE DATUM, WATER YEAR OCTOBER 1991 TO SEPTEMBER 1992 INSTANTANEOUS OBSERVATIONS

Dat	e		Water level	Date			Water level	Date	Water level	Date	Water level
Oct. Nov.			34.18 34.56	Dec. Jan.			34.88 33.87	Feb. 20 Mar. 30	33.36 36.89	May 14 July 22	37.39 39.84
WATER	YEAR	1992	HIGHEST	33.36	FEB.	20,	1992	LOWEST 39.84	JULY 22, 1992		



ST. CROIX, U.S. VIRGIN ISLANDS

174525064460600. Local number, 7.

LOCATION.--Lat 17°45'25", long 64°46'06", Hydrologic Unit 21020002, 4.35 mi northwest of Christiansted Plaza, 4.25 mi northwest of the Alexander Hamilton Airport entrance on Hwy 64, and 0.45 mi southeast of Windsor Ruins. Owner: U.S. Virgin Islands Government, Name: Concordia 14.

AOUIFER . - - Sand and gravel .

WELL CHARACTERISTICS. -- Observation drilled production water-table well, diameter 6 in (0.15 m), cased 6 in (0.15 m). Depth 85 ft (25.91 m).

INSTRUMENTATION . -- Monthly measurement with chalked steel tape by USGS personnel.

DATUM.--Elevation of land-surface datum is about 40 ft (12.2 m) above mean sea level, from topographic map. Measuring point: Top of 0.50 in (0.01 m) pipe on top of pump concrete base, 2.30 ft (0.70 m) above land-surface datum.

REMARKS. -- Observation well. Water levels affected by pumpage.


PERIOD OF RECORD. -- March 1982 to current year.

EXTREMES FOR PERIOD OF RECORD.--Highest water level measured, 10.07 ft (3.07 m) below land-surface datum, Mar. 4, 1989; lowest water level measured, a48.20 ft (a14.7 m) below land-surface datum, Aug. 24, 1990.

WATER LEVEL, IN FEET BELOW LAND-SURFACE DATUM, WATER YEAR OCTOBER 1991 TO SEPTEMBER 1992 INSTANTANEOUS OBSERVATIONS

Date	Water level	Date	Water level	Date	Water level
July 2	a46.46	July 29	a41.61	Sept. 16	a47.28

WATER YEAR 1992 HIGHEST a41.61 JULY 29, 1992 LOWEST a47.28 SEPT. 16, 1992



WATER YEAR

ST. CROIX, U.S. VIRGIN ISLANDS

174527064460100. Local number, 8.

LOCATION.--Lat 17°45'27", long 64°46'01", Hydrologic Unit 21020002, 4.35 mi northeast of the Alexander Hamilton Airport entrance on Hwy 64, 4.15 mi northwest of Christiansted Plaza, and 0.50 mi southeast of Windsor Ruins. Owner: U.S. Virgin Islands Government, Name: Concordia 1 (Main pump house).

AQUIFER. -- Limestone of Tertiary Age.

WELL CHARACTERISTICS. -- Observation drilled production water-table well, diameter 6 in (0.15 m), cased 6 in (0.15 m). Depth 82 ft (25.0 m).

INSTRUMENTATION .-- Monthly measurement with chalked steel tape by USGS personnel.

DATUM.--Elevation of land-surface datum is about 40 ft (12.2 m) above mean sea level, from topographic map. Measuring point: Top of 6 in (0.15 m) casing, 2.20 ft (0.67 m) above land-surface datum.


REMARKS. -- Observation well. Water levels affected by pumpage.

PERIOD OF RECORD. -- March 1982 to current year.

EXTREMES FOR PERIOD OF RECORD.--Highest water level measured, 14.03 ft (4.28 m) below land-surface datum, Jan. 19, 1988; lowest water level measured, a49.34 ft (a15.4 m) below land-surface datum, May 4. 1992.

WATER LEVEL, IN FEET BELOW LAND-SURFACE DATUM, WATER YEAR OCTOBER 1991 TO SEPTEMBER 1992 INSTANTANEOUS OBSERVATIONS

Date	Water level	Da t e	Water level	Date	Water level	Da te	Water level
Jan. 7 Mar. 13	a48.52 a48.74	May 1 May 29	a49.34 a47.29	July 2 July 29	a47.63 a47.38	Sept. 16	a48.37
WATER YEAR	1992 HIGHEST	a47.29 MAY	29, 1992	LOWEST a49.34	MAY 1, 1992		



ST. CROIX, U.S. VIRGIN ISLANDS

174532064460300. Local number, 9.

LOCATION.--Lat 17°45'32", long 64°46'03", Hydrologic Unit 21020002, 4.20 mi northwest of Christiansted Plaza, 4.32 mi northeast of Alexander Hamilton Airport entrance on Hwy 64, and 0.40 mo southeast of Windsor Ruins. Owner: U.S. Virgin Islands Government, Name: Concordia 7.

AQUIFER . - - Limestone of Tertiary Age.

WELL CHARACTERISTICS. -- Observation drilled production water-table well, diameter 6 in (0.15 m), cased 0-81 ft (0-24.7 m). Depth 81 ft (24.7 m).

INSTRUMENTATION .-- Monthly measurement with chalked steel tape by USGS personnel.

DATUM.--Elevation of land-surface datum is 35 ft (10.7 m) above mean sea level, from topographic map.

Measuring point: Hole in pump base, 2.20 ft (0.67 m) above land-surface datum. Previous to Mar. 25, 1982,
hole in pump base 2.50 ft (0.76 m) above land-surface datum.

REMARKS .-- Observation well. Water levels affected by pumping.


PERIOD OF RECORD. -- June 1962 to October 1968, discontinued. March 1982 to current year.

EXTREMES FOR PERIOD OF RECORD.--Highest water level measured, 1.75 ft (0.53 m) below land-surface datum, May 11, 1966; lowest water level measured, 57.40 ft (17.5 m) below land-surface datum, Mar. 5, 1964.

WATER LEVEL, IN FEET BELOW LAND-SURFACE DATUM, WATER YEAR OCTOBER 1991 TO SEPTEMBER 1992 INSTANTANEOUS OBSERVATIONS

Date	Water level	Date	Water level	Date	Water level	Date	Water level
Mar. 13 May 1	17.47 a37.26	May 29 July 2	a20.51 13.40	July 29	14.70	Sept. 16	a37.10

WATER YEAR 1992 HIGHEST 13.40 JULY 2, 1992 LOWEST a37.26 MAY 1, 1992



WATER YEAR

ST. CROIX, U.S. VIRGIN ISLANDS

174329064454700. Local number, 10.

LOCATION.--Lat 17°43'29", long 64°45'47", Hydrologic Unit 21020002, 4.05 mi southwest of Christiansted plaza, 2.40 mi northeast of the Experimental Station, and 2.75 mi northeast of the Alexander Hamilton Airport entrance on Hwy 64. Owner: U.S. Virgin Islands Government, Name: Barren Spot 5 (PWD-5).

AQUIFER . -- Alluvium and marl .

WELL CHARACTERISTICS.--Drilled production water-table well, diameter 6 in (0.15 m), cased 0-130 ft (0-39.63 m), perforated 71-130 ft (21.64-39.63 m). Depth 130 ft (39.63 m).

INSTRUMENTATION .-- Monthly measurement with chalked steel tape by USGS personnel.

DATUM.--Elevation of land-surface datum is about 75 ft (22.86 m) above mean sea level, from topographic map.
Measuring point: Hole on top of pump base, 2.00 ft (0.61 m) above land-surface datum.

REMARKS. -- Observation well. Water levels affected by pumping.


PERIOD OF RECORD .-- March 1982 to current year.

EXTREMES FOR PERIOD OF RECORD.--Highest water level measured, 61.86 ft (18.86 m) below land-surface datum, Mar. 26, 1982; lowest water level measured, a79.81 ft (a24.33 m) below land-surface datum, June 25, 1990.

WATER LEVEL, IN FEET BELOW LAND-SURFACE DATUM, WATER YEAR OCTOBER 1991 TO SEPTEMBER 1992 INSTANTANEOUS OBSERVATIONS

Date	Water level	Date	Water level	Date	Water level	Date	Water level
Oct. 22 Nov. 25	a77.43 a77.66	Feb. 4 Mar. 12	a77.49 a78.33	May 28 July 1	a79.05 a78.62	July 27 Sept. 14	68.10 a78.52
.Tam G	-78 08	Ann 27	-70 OF				

WATER YEAR 1992 HIGHEST 68.10 JULY 27, 1992 LOWEST a79.05 MAY 28, 1992



ST. CROIX, U.S. VIRGIN ISLANDS

174303064481100. Local number, 11.
LOCATION.--Lat 17°43'03", long 64°18'11", Hydrologic Unit 21020002, 5.20 mi east of Fort Frederick at Frederickstead, 1.20 mi southeast of Holy Cross Church, and 0.45 mi northeast of Adventure Ruins. Owner: U.S. Virgin Islands Water and Power Authority, Name: WAPA-02 at Adventure well field.

and Power Authority, Name: WAPA-02 at Adventure well field.
AQUIFER.--Alluvium and Kingshill Limestone.
WELL CHARACTERISTICS.--Drilled observation well, diameter 4 in (0.10 m), cased 0-60 ft (0-18.3 m), screened
20-40 ft (6.09-12.2 m). Open hole 60-100 ft (18.3-30.5 m). Depth 100 ft (30.5 m).
INSTRUMENTATION.--Digital water level recorder--60-minute punch.
DATUM.--Elevation of land-surface datum is about 50 ft (15.2 m) above mean sea level, from topographic map.
Measuring point: Top of shelter floor, 2.00 ft (0.61 m) above land-surface datum.

17.03

18.53

REMARKS.--Recording obeservation well.

PERIOD OF RECORD.--February 27, 1990 to current year.

EXTREMES FOR PERIOD OF RECORD.--Highest water level recorded, 9.75 ft (2.97 m) below land-surface datum, Oct. 26-27, 1990; lowest water level recorded, 27.68 ft (8.44 m) below land-surface datum, Sept. 19-23, 1992


		WATER LEV	EL, IN FR		LAND-SURF. 'ANTANEOUS			EAR OCTOB	BR 1991 T	O SEPTEMB	ER 1992	
DAY	OCT	NOA	DBC	JAN	PEB	MAR	APR	MAY	JUN	JUL	AUG	SRP
1	16.14	18.19	16.57	18.95	20.96	22.61	23.53	23.82	22.67	24.66	26.04	27.09
2	16.27	18.25	16.43	19.06	21.02	22.67	23.57	23.72	22.79	24.70	26.07	27.11
3	16.40	18.31	16.31	19.16	21.12	22.78	23.61	23.66	22.89	24.74	26.09	27.14
4	16.09	18.38	16.21	19.24	21.25	22.83	23.65	23.56	23.16	24.78	26.11	27.16
5	16.12	18.51	16.16	19.34	21.25	22.90	23.68	23.53	23.51	24.83	26.14	27.20
6	16.22	18.69	16.04	19.44	21.28	22.97	23.63	23.56	23.77	24.90	26.16	27.24
7	16.30	18.76	15.93	19.49	21.33	23.01	23.57	23.61	23.93	24.95	26.18	27.27
8	16.45	18.78	15.85	19.56	21.36	23.00	23.65	23.68	24.01	25.02	26.20	27.29
9	16.81	18.77	15.78	19.63	21.41	23.00	23.76	23.74	24.09	25.13	26.22	27.30
10	16.82	18.81	15.75	19.69	21.46	23.04	23.85	23.80	24.12	25.21	26.25	27.33
11	16.98	18.85	15.71	19.77	21.53	23.03	23.92	23.83	24.14	25.29	26.26	27.34
12	16.84	18.90	15.67	19.84	21.59	23.03	24.01	23.87	24.16	25.36	26.28	27.37
13	16.77	18.96	15.68	19.88	21.67	23.05	24.08	23.94	24.17	25.42	26.30	27.41
14	16.76	19.04	15.64	19.97	21.73	23.07	24.14	24.01	24.17	25.48	26.32	27.45
15	16.77	19.11	15.51	20.04	21.78	23.12	24.21	24.07	24.17	25.53	26.34	27.50
16	16.92	19.26	15.46	20.13	21.82	23.17	24.30	24.11	24.18	25.56	26.35	27.55
17	17.09	19.33	15.65	20.19	21.88	23.24	24.41	24.13	24.19	25.60	26.37	27.60
18	17.21	19.37	16.05	20.25	21.94	23.32	24.52	24.13	24.19	25.66	26.40	27.64
19	17.29	19.43	16.29	20.31	22.03	23.43	24.61	24.15	24.20	25.69	26.43	27.67
20	17.29	19.50	16.50	20.37	22.06	23.51	24.64	24.18	24.21	25.72	26.48	27.68
21	17.32	19.46	16.72	20.42	22.11	23.53	24.65	24.23	24.24	25.75	26.53	27.68
22	17.38	19.12	16.92	20.47	22.17	23.54	24.67	24.27	24.27	25.76	26.58	27.68
23	17.47	18.64	17.19	20.49	22.22	23.54	24.59	24.33	24.30	25.80	26.63	27.67
24	17.53	18.20	17.54	20.55	22.28	23.53	24.47	24.40	24.33	25.85	26.68	27.65
25	17.61	17.78	17.84	20.61	22.34	23.53	24.34	24.01	24.36	25.89	26.73	27.61
26	17.68	17.50	18.09	20.67	22.40	23.53	24.25	22.97	24.40	25.91	26.79	27.49
27	17.71	17.32	18.29	20.74	22.45	23.53	24.16	22.46	24.46	25.93	26.86	27.33
28	17.78	17.12	18.45	20.81	22.50	23.53	24.07	22.31	24.50	25.95	26.91	27.19
29	17.92	16.93	18.60	20.96	22.55	23.53	23.99	22.32	24.54	25.97	26.97	27.09
30	18.03	16.76	18.74	20.98		23.56	23.90	22.43	24.60	25.99	27.03	27.03
31	18.08		18.85	20.97		23.49		22.54		26.01	27.07	

WTR YR 1992 MEAN 22.35 HIGHEST 15.42 DEC. 17, 1991 LOWEST 27.68 SEPT. 19-23, 1992

21.78

20.06

16.66



23.21

24.08

23.66

24.02

26.44

27.39

ST. CROIX, U.S. VIRGIN ISLANDS

174308064482800. Local number, 12.

LOCATION.--Lat 17º43'08", long 64º48'28", Hydrologic Unit 21020002, 4.95 mi east of Fort Frederick at Frederickstead, 1.10 mi south of Holy Cross Church, and 0.40 mi northeast of Adventure Ruins. Owner: U.S. Virgin Islands Water and Power Authority, Name: WAPA-03 at Adventure well field.

AQUIFER.--Kingshill Limestone.

WELL CHARACTERISTICS.--Drilled observation well, diameter 4 in (0.10 m), cased 0-110 ft (0-33.5 m), screened 50-90 ft (15.2-27.4 m). Depth 110 ft (33.5 m).

INSTRUMENTATION.--Digital water level recorder--60-minute punch.

DATUM.--Elevation of land-surface datum is about 60 ft (18.3 m) above mean sea level, from topographic map.

Measuring point: Top of shelter floor, 3.00 ft (0.91 m) above land-surface datum.


REMARKS.--Recording observation well.

PERIOD OF RECORD.--February 28, 1990 to current year.

RXTREMES FOR PERIOD OF RECORD.--Highest water level recorded, 16.13 ft (4.92 m) below land-surface datum, Feb. 25, 1991; lowest water level recorded, 36.39 ft (11.1 m) below land-surface datum, Sept. 30, 1992.

		WATER LEV	ARI. IN FR	RT BELOW	LAND-SURF	ACE DATUM	, WATER Y	BAR OCTOB	ER 1991 T	O SEPTEMB	BR 1992	
		MAILE		INST	RUDBUATUA	OBSERVAT	ION AT 12	:00				
		NOV	DEC	JAN	FRB	MAR	APR	MAY	JUN	JUL	λŪG	SEP
DAY	OCT	MOA	DEC	UAN	FBD							
1	28.26	29.71	30.20	29.62	29.93	30.04	32.23	32.63	33.82	34.39	30.28	36.02
2	28.47	29.68	30.24	29.67	30.44	30.42	32.23	32.72	33.82	34.44	30.21	36.04
3	28.62	29.65	30.23	29.80	28.44	30.69	32.23	32.78	33.84	34.46	30.15	36.05
3	28.75	29.65	30.20	29.81	27.03	30.89	32.23	32.86	33.83	34.47	31.73	36.06
5	28.79	29.70	30.14	29.85	26.49	30.95	32.23	32.92	33.82	34.50	32.70	36.07
•	20.73	23.70	30.11									
6	28.82	29.69	30.07	29.92	26.13	28.37	32.23	32.96	33.89	34.54	33.26	36.09
7	28.79	29.79	29.99	29.96	25.93	27.06	32.23	33.02	33.92	34.56	33.74	36.10
8	28.50	29.81	29.97	29.99	25.93	26.65	32.23	33.14	33.92	34.57	34.07	36.11
9	28.63	29.81	29.88	30.00	25.78	29.81	31.49	33.22	33.93	34.62	34.30	36.12
10	28.80	29.86	29.83	30.03	25.65	30.55	31.79	33.28	33.96	34.68	34.52	36.13
10	20.90	27.00	-,,,,,									
11	28.89	29.86	29.86	30.14	25.63	30.98	30.88	33.34	33.99	34.72	34.68	36.15
12	28.96	29.87	29.72	30.17	25.55	31.15	30.32	33.38	33.99	34.76	34.82	36.16
	29.03	29.90	29.68	30.19	25.57	31.28	30.59	33.37	34.00	34.77	34.92	36.17
13	29.03	29.96	29.62	30.25	25.67	31.36	30.51	33.32	34.02	34.81	35.02	36.18
14	29.02	29.96	29.48	30.32	25.58	31.43	30.92	33.34	34.06	34.83	35.10	36.20
15	29.00	49.90	27.49	30.32	-3.30	02						
• •	29.03	30.01	29.33	30.40	25.50	31.51	31.69	33.41	34.07	34.11	35.21	36.21
16	29.03	30.01	26.69	30.43	25.50	31.56	32.05	33.46	34.06	33.08	35.27	36.22
17		30.09	25.04	30.54	25.44	31.64	32.25	33.52	34.06	32.30	35.31	36.23
18	29.19	30.09	28.02	30.56	25.40	31.71	32.23	33.56	34.11	31.72	35.32	36.24
19	29.23	30.09	28.65	30.58	25.36	31.76	32.23	33.63	34.14	31.28	35.34	36.26
20	29.21	30.09	20.00	30.56	23.30	31170	55.55					
		30.11	28.87	30.60	25.43	31.82	32.31	33.68	34.15	31.03	35.56	36.27
21	29.30	30.11	28.99	30.63	25.36	31.92	32.22	33.72	34.16	30.84	35.67	36.28
22	29.28		29.05	28.18	25.39	31.97	32.22	33.76	34.17	30.74	35.75	36.29
23	29.31	30.14	29.05	29.87	25.42	32.03	29.06	33.38	34.20	30.71	35.81	36.31
24	29.36		29.19	30.36	25.44	32.07	28.53	33.71	34.23	30.63	35.88	36.32
25	29.40	30.15	29.25	30.36	23.44	32.07	•0.50					
		20.20	29.30	30.55	25.45	32.15	30.85	33.84	34.26	30.50	35.91	36.33
26	29.51		29.46	30.73	25.47	32.19	31.71	33.86	34.31	30.38	35.96	36.34
27	29.49	30.29		30.73	25.51	32.24	32.11	33.86	34.32	30.28	35.97	36.36
28	29.47		29.48 29.51	30.92	29.35	32.27	32.35	33.88	34.35	30.20	35.99	36.37
29	29.51		29.55	30.90	29.33	32.33	32.50	33.86	34.38	30.18	36.00	36.38
30	29.54					32.32		33.84		30.27	36.01	
31	29.69		29.59	28.95		34.34		55.04				
MRAN	29.06	29.97	29.33	30.15	26.20	31.07	31.62	33.40	34.06	32.82	34.53	36.20

MEAN 31.55 HIGHEST 24.85 DEC. 18, 1991 LOWEST 36.39 SEPT. 30, 1992 WTR YR 1992




ST. CROIX, U.S. VIRGIN ISLANDS

174316064480800. Local number, 13.
LOCATION.--Let 17*43'16*, long 64*48'08*, Hydrologic Unit 21020002, 5.25 mi east of Fort Frederick at Frederickstead, 0.95 mi southeast of Holy Cross Church, and 0.65 mi northeast of Adventure Ruine. Owner: U.S. Virgin Islands Water and Power Authority, Name: WAPA-17 at Adventure well field.
AQUIFER.--Ringshill Limestone.

AGUIFER.--Ringshil Limestone.
WELL CHARACTERISTICS.--Drilled observation well, diameter 4 in (0.10 m), cased 0-95 ft (0-29.8 m), screened 10-40 ft (3.05-12.2 m). Depth 95 ft (29.0 m).
INSTRUMENTATIOM.--Digital water lever recorder--60-minute punch.
DATUM.--Elevation of land-surface datum is about 75 ft (22.9 m) above mean sea level, from topographic mmp.
Measuring point: Top of shelter floor, 2.33 ft (8.71 m) above land-surface datum.
REMARES.--Recording observation well.
PERIOD OF RECORD.--February 28, 1990 to current year.
EXTREMES FOR PERIOD OF RECORD.--Righest water level recorded, 4.66 ft (1.43 m) below land-surface datum, Oct. 14
1990; lowest water level recorded, 21.36 ft (6.51 m) below land-surface datum, Mmy 23, 1992

		WATER LEV	RL, IN PR	PT BELOW INS	Land- Suri Pantanbou	ACE DATUM OBSERVAT	I, WATER ! PIOM AT 1:	ybar octob 200	ER 1991 T	O SEPTEME	iik 1992	
DAY	OCT	WOV	DEC	Jam	723	MAR	APR	MAY	JUN	JUL	AUG	SE?
1	14.42	15.50	16.51	17.48	18.32	19.33	20.17	20.35	15.25	15.98	15.63	17.09
2 3	14.48	15.53	16.53	17.54	18.39	19.37	20.07	20.35	15.53	15.88	15.90	17.12
	14.54	15.57	16.56	17.56	18.44	19.41	19.99	20.35	15.86	15.06	15.94	17.13
4	14.54	15.61	16.60	17.59	18.48	19.44	19.92	20.35	16.08	15.65	15.99	17.17
5	14.58	15.64	16.64	17.63	18.52	19.48	19.88	20.44	16.21	15.84	16.01	17.20
6	14.62	15.68	16.67	17.63	18.56	19.51	19.90	28.60	16.30	15.84	16.01	17.23
7	14.65	15.72	16.70	17.66	18.61	19.54	20.04	20.68	16.35	15.84	16.05	17.26
•	14.68	15.76	16.73	17.70	18.65	19.58	20.14	20.76	16.39	15.83	16.18	17.30
,	14.68	15.78	16.76	17.73	18.68	19.60	20.22	20.83	16.42	15.83	16.14	17.33
10	14.70	15.61	16.78	17.77	18.72	19.64	20.25	20.69	16.42	15.84	16.18	17.37
11	14.73	15.84	16.82	17.80	18.76	19.66	20.31	20.95	16.48	15.84	16.23	17.41
12	14.75	15.87	16.85	17.84	18.80	19.70	20.34	21.01	16.38	15.85	16.27	17.46
13	14.78	15.92	16.89	17.87	18.83	19.74	20.35	21.06	16.35	15.86	16.31	17.50
14	14.83	15.96	16.92	17.90	18.87	19.78	20.36	21.10	16.32	15.88	16.35	17.53
15	14.86	16.02	16.95	17.93	18.89	19.81	20.38	21.15	16.29	15.88	16.39	17.59
16	14.89	16.06	16.98	17.96	18.93	19.85	20.42	21.19	16.26	15.89	16.44	17.60
17	14.93	16.11	16.99	17.99	18.96	19.88	20.47	28.96	16.23	15.91	16.58	17.62
18	14.97	16.15	17.02	18.03	18.99	19.92	20.53	21.01	16.28	15.91	16.54	17.64
19	15.02	16.20	17.05	18.05	19.02	19.94	20.59	21.13	16.17	15.92	16.59	17.66
20	15.06	16.24	17.08	18.08	19.06	19.97	20.49	21.20	16.14	15.92	16.64	17.66
21	15.09	16.28	17.12	18.12	19.08	20.00	20.53	21.24	16.12	15.93	16.69	17.59
22	15.13	16.30	17.14	18.15	19.13	20.02	20.60	21.28	16.09	15.94	16.74	17.60
23	15.16	16.33	17.17	18.11	19.16	20.04	20.59	21.33	16.06	15.93	16.78	17.58
24	15.19	16.36	17.21	18.09	19.18	20.07	20.54	19.54	16.03	15.87	16.84	17.54
25	15.23	16.38	17.24	18.17	19.23	20.10	20.48	11.43	16.01	15.82	16.89	17.61
26	15.26	16.42	17.27	18.20	19.26	20.14	20.44	12.01	15.97	15.78	16.93	17.66
27	15.29	16.38	17.30	18.25	19.27	20.15	20.41	12.80	15.94	15.75	16.95	17.71
28	15.33	16.41	17.34	18.29	19.25	20.16	20.39	13.69	15.93	15.73	16.99	17.74
29	15.37	16.45	17.37	18.33	19.29	20.19	20.37	14.30	15.92	15.71	17.01	17.77
30	15.42	16.48	17.41	18.38		20.22	20.36	14.69	15.91	15.70	17.03	17.77
31	15.46		17.45	18.37		20.24		15.00		15.75	17.07	
MEAN	14.92	16.03	16.97	17.94	18.87	19.82	20.32	19.15	16.12	15.85	16.46	17.48

WTR YR 1992 MEAN 17.49 HIGHEST 11.15 MAY 25, 1992 LOWEST 21.36 MAY 23, 1992



ST. CROIX, U.S. VIRGIN ISLANDS

174247064475701. Local number, 14.

LOCATION.--Lat 17°42'47", long 64°47'57", Hydrologic Unit 21020002, 0.80 mi northwest of the Alexander Hamilton Airport entrance on Hwy 64, 0.53 mi south of the Experimental Station, and 6.65 mi southwest of Christiansted Plaza. Owner: U.S. Virgin Islands Water and Power Authority, Name: WAPA-21a at Golden Grove well field.

AQUIPER.--Alluvial, Kingshill Limestone.

AQUIFER.--Alluvial, Kingshill Limestone.

WELL CHARACTERISTICS.--Drilled observation well, diameter 4 in (0.10 m), cased 0-70 ft (0-21.3 m), screened 15-70 ft (4.57-21.3 m). Depth 100 ft (30.5 m), well collapsed to 70 ft (21.3 m).

INSTRUMENTATION.--Digital water level recorder--60-minute punch.

DATUM.--Elevation of land-surface datum is about 52 ft (15.8 m) above mean sea level, from topographic map. Measuring point: Top of shelter floor, 3.25 ft (0.99 m) above land-surface datum.


REMARKS.--Recording observation well. Water levels affected by nearby pumping well.

PERIOD OF RECORD.--February 28, 1990 to current year.

EXTREMES FOR PERIOD OF RECORD.--Highest water level measured, 14.19 ft (4.32 m) below land-surface datum, Nov. 3, 1990; lowest water level recorded, 43.26 ft (13.2 m) below land-surface datum, Apr. 22, 1992

		WATER	LEVEL, IN			FACE DATUM S OBSERVAT		YEAR OCTOBER 1200	1991	TO SEPTEMBER	1992	
DAY	ост	NO	V DEC	c jan	FEB	MAR	APR	MAY	JUN	JUL	AUG	SEP
1	37.41	39.2	.7	- 37.03		42.32	42.76				39.72	
2	37.41	39.9	0	- 37.16	37.46	42.34	42.75				39.78	
3	37.40	39.9	1	- 37.04	37.46	42.33	42.74				39.79	
4	37.42	39.9	3	- 37.22	37.44	42.42	42.73				39.81	
5	37.46	39.9	4 36.2	0 37.15	37.63	42.42	42.75				39.82	
6	37.57	39.9	6 36.2	4 37.03	37.63	42.41	42.75				40.54	
7	37.69	39.9	7 36.2	2 36.79	37.63	42.41	42.75				37.38	
8	37.60	40.0	36.2	6 36.82	37.63	42.40	42.74				40.64	
9	37.63	40.0	0 35.8	36.81	37.71	42.40	42.76				40.77	
10	37.43	40.1	.8 35.3	5 36.31	37.60	42.39	42.75				40.86	
11	37.78	40.1	9 35.3	2 36.74	37.81	42.38	42.74				40.94	
12	37.85	40.1	9 35.3	0 36.83	37.77	42.38	42.73		-		40.97	
13	37.98	40.1	9 34.7	1 36.91	37.77	42.37	42.73				41.02	
14	38.23	40.2	4 35.1	0 36.87	37.58	42.37	42.72				41.03	
15	38.24	40.3	35.1	4 36.90	37.81	42.36	42.71				41.08	
16	38.43	40.3			37.78	42.51	42.71				41.12	
17	38.41	40.3	34.8	1 36.50	37.73	42.51	42.70				41.14	
18	38.48	40.3	8 34.9	8 36.87	37.73	42.50	42.69				41.14	
19	38.46	40.3	8 36.1	4 36.95	37.79	42.50	42.68				41.21	
20	38.37	40.4	4 36.2	2 37.41	37.88	42.49	42.68				41.21	
21	38.06				38.37	42.48	42.67			39.57	41.21	
22	38.05				38.88	42.48	42.66			39.59	40.78	
23	38.01				39.38	42.47				39.66	40.66	
24	38.03				39.91	42.47				39.67	40.62	
25	38.04		- 36.7	7	42.08	42.46				39.69	41.25	
26	38.06				42.29	42.45				39.70	41.36	
27	38.06				42.33	42.45				39.73	41.36	
28	38.27				42.34	42.44					41.36	
29	38.48				42.33	42.53				39.76	40.94	
30	38.51		- 36.9	2						39.78	36.74	41.66
31	38.53		- 37.1	2		42.76				39.69		
MEAN	37.98	40.1	10 36.0	4 36.91	38.71	42.44	42.72			39.69	40.54	41.66

WTR YR 1992 MEAN 39.46 HIGHEST 34.70 DEC. 16-17, 1991 LOWEST 43.26 APR. 22, 1992



ST. CROIX, U.S. VIRGIN ISLANDS

174319064454401. Local number, 15.

LOCATION.--Lat 17943'19*, long 64°45'44*, Hydrologic Unit 21020002, 2.55 mi northeast of the Alexander Hamilton Airport entrance on Hwy 64, 4.00 mi southwest of Christiansted Plaxa, and 2.30 mi northeast of the Experimental Station. Owner: U.S. Virgin Islands Water and Power Authority, Name: WAPA-23a at Barren Spot well field.

AQUIFER.--Post Kingshill Limestone.

WELL CHARACTERISTICS.--Drilled observation well, diameter 4 in (0.10 m), cased 0-110 ft (0-33.5 m), screened 70-110 ft (21.3-33.5 m). Depth 110 ft (33.5 m).

INSTRUMENTATION.--Digital water level recorder--60-minute punch.


DATUM.--Blevation of land-surface datum is about 65 ft (19.8 m) above mean sea level, from topographic map.

Measuring point: Top of shelter floor, 3.50 ft (1.07 m) above land-surface datum.

REMARKS FOR PERIOD OF RECORD. -- Highest water level recorded, 55.29 ft (16.8 m) below land-surface datum, Oct. 1, 1991; lowest water level recorded, 69.68 ft (21.3 m) below land-surface datum, Sept. 29, 1991.

		WATER LEVI	EL, IN FE		Land-Surf Pantaneous			YEAR OCTOB 200	BR 1991 1	O SEPTEME	ER 1992	
DAY	OCT	Nov	DBC	JAN	FEB	MAR	APR	MAY	JUN	JUL	AUG	SEP
1	55.29	60.37		60.69	58.93	60.64	60.20	60.63	60.65	60.38	60.29	60.34
2	59.30	60.01		60.72	60.01	60.69	60.20	60.64	60.65	59.12	60.32	60.44
3	59.36	59.96		60.72	59.78	60.71	59.40	60.64	60.62	60.12	60.34	60.43
4	59.34	59.94		60.72	60.07	60.72	59.98	60.65	60.58	60.15	60.30	60.43
5	59.34	60.15	60.53	60.72	60.35	60.72	60.05	60.66	60.58	60.12	60.29	60.38
6	59.29	59.57	60.55	60.68	60.47	60.72	60.08	60.66	60.58	60.11	60.29	60.42
7	59.29		60.50	60.69	60.51	60.73	60.11	60.68	60.58	60.11	59.30	60.43
8	59.29		60.56	60.70	60.61	59.92	60.12	60.70	60.58	60.11	59.94	59.55
9	59.29		60.57	60.70	60.61	60.55	60.16	60.71	60.57	60.11	59.99	60.38
10	59.31		59.49	60.69	59.57	60.64	60.16	60.72	60.50	60.11	60.01	60.41
11	59.32		59.46	60.67	59.00	60.67	60.16	60.73	60.52	60.11	60.13	60.41
12	59.34		59.45	60.66	60.39	60.59	60.16	60.70	60.51	60.11	60.14	60.41
13	59.35		59.44	60.64	60.54	60.52	60.16	60.65	60.54	60.11	60.16	60.41
14	59.35		59.43	60.64	59.36	60.49	60.16	60.63	60.54	60.09	60.16	60.41
15	59.35		59.43	60.62	60.37	60.48	60.12	60.63	60.55	60.07	60.16	60.41
16	59.35		59.40	60.62	60.47	60.46	60.12	60.52	60.52	60.08	60.18	60.39
17	59.35		60.10	60.62	60.58	60.44	60.12	60.58	60.52	60.06	60.20	60.40
18	59.35		60.40	60.62	60.64	60.43	60.12	60.61	60.52	60.06	60.18	60.40
19	59.28		60.50	60.62	60.65	60.34	58.40	60.63	60.52	60.06	60.20	60.34
20	59.23		60.54	60.62	60.67	59.35	59.90	59.64	60.48	60.05	59.05	60.37
21	59.22		60.57	60.62	60.70	60.25	59.99	60.57	60.55	60.04	58.25	60.39
22	59.16		60.60	60.62	60.47	60.25	60.19	60.65	60.49	60.07	59.57	60.39
23	59.14		60.58	60.62	60.63	60.25	60.3 0	60.72	58.61	60.05	60.16	60.39
24	59.14		60.62	60.62	59.37	60.25	60.32	60.46	58.24	60.05	60.27	60.39
25	59.14		60.64	60.65	58.67	60.25	60.44	60.57	60.00	60.05	60.33	60.39
26	59.20		60.64	60.63	59.75	60.25	60.47	60.62	60.19	60.05	60.38	60.39
27	59.25		60.64	60.60	60.31	60.23	60.49	60.62	60.27	60.05	60.40	60.37
28	59.33		60.65	60.29	60.48	60.17	60.56	60.64	60.32	60.05	60.42	60.35
29	59.33		60.66	60.19	60.56	60.18	60.59	60.58	60.34	60.14	60.42	58.89
30	60.26		60.67	60.18		60.18	60.62	60.63	60.36	60.21	59.89	60.05
31	60.34		60.67	60.17		60.20		60.64		60.25	60.27	
MRAN	59.22	60.00	60.27	60.60	60.16	60.40	60.13	60.60	60.35	60.07	60.06	60.31

WTR YR 1992 MEAN 60.19 HIGHEST 55.29 OCT. 1, 1991 LOWEST 60.75 MAY 10-11, 1992



ST. THOMAS, U.S. VIRGIN ISLANDS

182050064580400. Local number, 1.

LOCATION.--Let 18°20'50", long 64°58'04", Hydrologic Unit 21020001, 2.18 mi northwest of Charlotte Amalia, 0.68 mi northeast of Harry S. Truman Airport entrance on Hwy 302, and 0.97 mi southwest of Dorothea. Owner: Mr. Michael Dudovick, Name: Thach Farm.

AQUIFER .-- Volcanic rocks of Cretaceous age.

WELL CHARACTERISTICS. -- Drilled water-table production well, diameter 6 in (0.15 m), cased 6 in (0.15 m) 0-25 ft (0-7.62 m), open hole 25-80 ft (7.62-24.4 m). Depth 80 ft (24.4 m).

INSTRUMENTATION .-- Monthly measurement with chalked steel tapo by USGS personnel.

DATUM.--Elevation of land-surface datum is 80 ft (24.4 m) above mean sea level, from topographic map.
Measuring point: Top of 6 in (0.15 m) casing, 2.50 ft (0.76 m) above land-surface datum. Frior to Mar. 23,
1982, top of 6 in (0.15 m) casing, 1.30 ft (0.40 m) above land-surface datum.


REMARKS. -- Non-potable public-water supply and observation well.

PERIOD OF RECORD .-- October 1963 to August 1969, discontinued. March 1982 to current year.

EXTREMES FOR PERIOD OF RECORD. -- Highest water level measured, 2.33 ft (0.71 m) below land-surface datum, Mov. 20, 1984; lowest water level measured, a60.99 ft (18.60 m) below land-surface datum, Cet. 7, 1991.

WATER LEVEL, IN FEET BELOW LAND-SURFACE DATUM, WATER YEAR OCTOBER 1991 **10** SEPTEMBER 1992 INSTANTANEOUS OBSERVATIONS

					-		
Date	Water level	Date	Water level	Date	Water level	Date	Water level
Oct. 7 Nov. 5	a60.99 59.01	Dec. 9 Jan. 7	59.80 a60.21	Peb. 10 May. 18	a59.55 a60.70	Sept. 8	a60.60
	utauret	50 61 WW	5. 1991 TO	MRST 60.99 OCT	. 7. 1991		



ST. THOMAS, U.S. VIRGIN ISLANDS

182138064543100. Local number, 2.

LOCATION.--Let 18°21'38°, long 64°54'31°, Hydrologic Unit 21020001, 2.25 mi northeast of Charlotte Amalie, 0.84 mi north of Winterberg Peak, and 0.93 mi northeast of Canaan. Owner: Mahogany Run Resort, Mame: Mahogany 15.

AQUIPER . - - Fractured rocks .

WHILL CHARACTERISTICS. -- Drilled public supply water-table well, diameter 6 in (0.15 m), cased 6 in (0.15 m). Depth 145 ft (44.21 m).

INSTRUMENTATION .-- Monthly measurement with chalked steel tape by USGS personnel.

DATUM.--Elevation of land-surface datum is 100 ft (30.5 m) above mean sea level, from topographic map. Prior to this report, elevation used was 120 ft (36.6 m). Measuring point: Top of 6 in (6.15 m) casing, 0.10 ft (0.03 m) helow land-surface datum. Prior September 16, 1991, 0.00 ft (0.00 m), prior May 31, 1991, 1.30 ft (0.40 m), and prior March 4, 1991, 1.20 ft (0.36 m) helow land-surface datum.

REMARKS. -- Observation well. Water levels affected by pumpage.


PERIOD OF RECORD. -- March 1982 to current year.

EXTREMES FOR PERIOD OF RECORD. -- Highest water level measured, 12.45 ft (3.79 m) below land-surface datum, July 1, 1986; lowest water level measured, a120.92 ft (36.9 m) helow land-surface datum, Aug. 15, 1991.

WATER LEVEL, IN FRET BELOW LAND-SURFACE DATUM, WATER YEAR OCTOBER 1991 TO SEPTEMBER 1992 INSTANTANEOUS OBSERVATIONS

Date	Water level	Date	Water level	Date	Water level	Date	Water level
Nov. 6	a66.57	Jan. 7	46.73	May 19	a116.42	July 14	a93.75

WATER YEAR 1992 HIGHEST a43.76 FEB. 10, 1992 LOWEST a116.4 MAY 19, 1992



ST. THOMAS, U.S. VIRGIN ISLANDS

182138064542500. Local number, 3.

LOCATION.--Lat 18°21'38", long 64°54'25", Hydrologic Unit 21020001, 2.50 mi northeast of Charlotte Amalie, 0.82 mi north of Winterberg Peak, and 0.97 mi northeast of Canaan. Owner: Mahogany Run Resort, Name: Mahogany 16.

AQUIFER . - - Fractured rocks .

WELL CHARACTERISTICS. -- Drilled water-table production well, diameter 6 in (0.15 m), cased 6 in (0.15 m).
Depth 145 ft (44.21 m).

INSTRUMENTATION .-- Monthly measurement with chalked steel tape by USGS personnel.

DATUM.--Elevation of land-surface datum is 100 (30.5 m) above mean sea level, from topographic map. Prior to this report, elevation used was 130 ft (39.6 m). Measuring point: Top of 6 in (0.15 m) casing, 1.30 ft (0.40 m) below land-surface datum.

REMARKS. -- Water levels affected by nearby pumping well.


PERIOD OF RECORD. -- March 1982 to current year.

EXTREMES FOR PERIOD OF RECORD.--Highest water level measured, 10.25 ft (3.12 m) below land-surface datum Jan. 21, 1988; lowest water level measured, a103.85 ft (31.65 m) below land-surface datum, Oct. 4, 1984.

WATER LEVEL, IN FEET BELOW LAND-SURFACE DATUM, WATER YEAR OCTOBER 1991 TO SEPTEMBER 1992 INSTANTANEOUS OBSERVATIONS

Date	Water level	Date	Water level	Date	Water level	Date	Water level
Nov. 16 Dec. 9	49.20 48.74	Jan. 7 Feb. 10	47.57 45.19	May 16 July 14	54.39 50.49	Sept. 8	54.53

WATER YEAR 1992 HIGHEST 45.19 FEB. 10, 1992 LOWEST 54.53 SEPT. 8, 1992



ST. THOMAS, U.S. VIRGIN ISLANDS

182136064541900. Local number, 4.

LOCATION.--Lat 18°21'36", long 64°54'19", Hydrologic Unit 21020001, 2.75 mi northeast of Charlotte Amalie, 0.81 mi north of Winterberg Peak, and 0.99 mi northeast of Canaan. Owner: Mahogany Run Resort, Name: Mahogany 17.

ACUIFER . - - Fractured rock

WELL CHARACTERISTICS.--Drilled water-table production well, diameter 6 in (0.15 m), cased 6 in (0.15 m).

Depth 145 ft (44.21 m).

INSTRUMENTATION . -- Monthly measurement with chalked steel tape by USGS personnel.

DATUM.--Elevation of land-surface datum is 110 ft (33.5 m) above mean sea level, from topographic map. Prior to this report, elevation used was 140 ft (42.7 m). Measuring point: Top of 6 in (0.15 m) casing at land-surface datum.

REMARKS.--Public water supply. Water levels affected by nearby pumping well.

PERIOD OF RECORD .-- March 1982 to current year.


EXTREMES FOR PERIOD OF RECORD.--Highest water level measured, 17.49 ft (5.33 m) below land-surface datum, Dec. 11 1985; lowest water level measured, a60.40 ft (18.41 m) below land-surface datum, Sept. 10, 1982.

WATER LEVEL, IN FEST BELOW LAND-SURFACE DATUM, WATER YEAR OCTOBER 1991 TO SEPTEMBER 1992 INSTANTANEOUS OBSERVATIONS

Date	Water level	Date	Water level	Date	Water level	Date	Water level
Nov. 6	42.14	Jan. 7	42.67 41.49	May 19 July 14	45.36 43.50	Sept. 8	45.26

WATER YEAR 1992 HIGHEST 41.49 PEB. 10, 1992 LOWEST 45.36 MAY 19, 1992

a Pumping.



ST. THOMAS, U.S. VIRGIN ISLANDS

182038064550300. Local number, 6.
LOCATION.--Let 18°20'38", long 64°55'03", Hydrologic Unit 21020001, 1.12 mi east of Charlotte Amalie, 0.75 mi southwest of Winterberg Peak, and 1.08 mi southeast of Canaan. Owner: U.S. Virgin Islands Government, Mame: Grade School 3.
AQUIFER.--Volcanic breccia.

WELL CHARACTERISTICS .- Drilled unused water-table well, diameter 6 in (0.15 m), cased 6 in (0.15 m). Depth 70 ft (21.3 m).

(21.3 m).

INSTRUMENTATION.--Digital water level recorder--60-minute punch.

DATUM.--Elevation of land-surface datum is about 60 ft (18.3 m) above mean sea leval, from topographic map.

Measuring point: Top of 0.5 in (0.01 m) hole at 6 in (0.15 m) casing, 1.30 ft (0.40 m) above land-surface datum. Prior to June 27, 1983, top of 6 in (0.15 m) casing, 2.90 ft (0.88 m) above land-surface datum.


PERIOD OF RECORD.--March 1982 to current year.

EXTREMES FOR PERIOD OF RECORD.--Eighest water level recorded, 1.53 ft (0.47 m) below land-surface datum, Oct. 1, 1989; lowest water level recorded, 35.38 ft (10.73 m) below land-surface datum, July 21, 1982.

WATER LEVEL, IN FEET BELOW LAND-SUFFACE DATUM, WATER YEAR OCTOBER 1991 TO SEPTEMBER 1992 INSTANTANEOUS OBSERVATION AT 1200

DAY	OCT	MOV	DEC	jan	713	MAR	APR	MAY	JUN	JUL	AUG	SEP
1	29,37	28.77	28.03		27.53	30.37	31.51	32.36	26.58	30.55	31.95	30.26
2	28.97	28.95	28.10	29.68	27.79	30.44	31.50	32.26	26.65	30.65	32.02	30.33
	28.32	29.06	28.16	29.79	28.04	30.53	31.54	32.15	26.62	30.69	32.09	30.27
4	27.82	29.17	28.21	29.88	28.26	30.62	31.56	32.01	26.60	30.74	32.03	30.25
5	27.51	29.30	28.22	29.96	28.37	30.65	31.58	31.92	26.66	30.83	31,90	30.20
6	27.42	29.41	28.24	29.05	28.19	30.64	31.60	31.90	26.79	30.96	31.66	30.10
7	27.41	29.54	28.27	25.97	28.09	30.60	31.61	31.89	26.92	31.11	31.39	30.24
•	27.50	29.63	28.31	24.66	28.07	30.61	31.59	31.90	27.09	31.22	31.19	30.35
•	27.56	29.29	28.37	24.15	28.07	30.60	31.61	31.66	27.27	31.20	30.94	30.31
10	27.42	28.97	28.39	23.92	28.09	30.79	31.63	31.54	27.42	31.34	30.72	30.19
11	27.19	28.78	28.41	23.76	28.17	30.89	31.66	31.44	27.54	31.47	30.53	30.16
12	27.10	28.70	28.45	23.73	28.30	30.95	31.70	31.39	27.59	31.61	30.40	30.20
13	27.11	28.65	38.51	23.79	28.45	30.98	31.72	31.35	27.55	31.70	30.33	30.12
14	27.16	28.56	28.59	23.89	28.61	31.00	31.74	31.39	27.48	31.77	30.19	30.02
15	27.18	28.59	28.67	24.04	28.79	31.84	31.76	31.50	27.51	31.05	29.84	29.95
16	27.26	28.60	28.77	24.27	28.94	31.12	31.90	31.59	27.61	31.97	29.60	29.92
17	27.35	28.58	28.84	24.51	29.06	31.20	31.87	31.63	27.75	31.84	29.53	29.93
18	27.46	28.58	28.91	24.77	29.16	31,29	31.96	31.64	27.92	31.80	29.53	29.85
19	27.50	28.61	28.93	25.04	29.25	31.37	32.05	31.69	28.09	31.76	29.50	29.81
20	27.44	28.67	28.92	25.32	29.39	31.46	32.08	31.79	28.29	31.76	29.58	29.86
21	27.39	28.75	28.91	25.61	29.54	31.54	32.00	31.91	20.51	31.77	29.57	30.05
22	27.44	28.82	28.91	25.92	29.66	31,59	32.10	32.03	28.72	31.76	29.52	30.03
23	27.54	28.88	29.04	26.19	29.80	31,60	33,15	32.14	28.94	31.68	29.56	29.84
24	27.67	28.92	29.17	26.37	29.94	31.57	32.30	32.19	29.16	31.57	29.66	29.66
25	27.76	28.63	29.20	26.53	30.10	31.54	33.10	30.87	29.40	31.49	29.71	29.57
26	27.85	28.35	29.23	26.67	30.26	31.54	32.12	29.33	29.64	31.43	29.74	29.46
27	27.96	28.18	29.28	26.76	30.37	31.50	33,13	28.44	29.86	31.43	29.87	29.35
28	28.08	28.07	29.33	26.84	30.40	31.63	32.21	27,78	30.05	31.53	29.98	29.34
29	28.20	28.01	29.37	26.93	30.35	31.63	32.30	27.00	30.24	31.65	30.09	29.41
30	28.35	28.00		27.07		31.59	32.36	26.75	30.41	31.76	30.11	29.36
31	28.53			27.28	***	31.56		36.59		31.07	30.13	
MEAN	27.70	28.77	28.68	26.08	28.93	31.12	31.06	30,96	29.03	31.44	39.42	29.95

WTR YR 1992 MEAN 29.51 HIGHEST 23.70 JAN. 12, 1992 LOWEST 32.40 APR. 30, MAY 1, 1992



ST. THOMAS, U.S. VIRGIN ISLANDS

182036064545200. Local number, 7.

LOCATION.--Lat 18°20'36°, long 64°54'52°, Hydrologic Unit 21020001, 1.33 mi east of Charlotte Amalie, 0.55 mi southwest of Winterberg Peak, and 1.20 mi southeast of Canaan. Owner: U.S. Virgin Islands Water and Rower Authority, Name: St. Thomas Hospital, VIEO-1.

AQUIFER.--Fractured, volcanic rock, water-table aquifer.

MELL CHARACTERISTICS.--Drilled observation water-table well, diameter 7 in (0.18 m), cased 4 in (0.10 m), 0-165 ft (0-44.2 m), screened 100-145 ft (30.5-44.2 m). Depth 145 ft (44.2 m).

INSTRUMENTATION.--Digital water level recorder-60-minute punch.

DATUM.--Elevation of land-surface datum is about 85 ft (25.9 m) above mean sea level, from topographic map.

Measuring point: Top of shelter floor, 3.20 ft (0.97 m) above land-surface datum.


REMARKS.--Observation well. Drilled on Pebruary 1991. Automated digital recorder installed on May 1991. Pumping test performed during May 22-24, 1991.

PERIOD OF RECORD.--May 1991 to current year.

EXTREMES FOR PERIOD OF RECORD.--Highest water level recorded, 68.23 ft (20.8 m) below land-surface datum, Feb. 11, 1992; lowest water level recorded, 74.17 ft (22.6 m) below land-surface datum, Sept. 22-23, 1991.

		WATER	LHVEL, IN		i land-sur Stantaniscu			YEAR OCTOR 1200	ER 1991	to septem	WR 1992	
DAY	OCT	390	W DE	c jan	723	MAR	APR	MAY	JUN	JUL	λŪG	SEP
1	73.35	72.0	3 71.3	8 71.90	68.51	69.27	71.21	71.10	70.33	70.19	70.83	71.44
2	73.19	72.1	1 71.1	6 71.08	68.50	69.33	71.25	71.03	70.36	70.17	70.90	71.52
3	72.99	72.1			68.47	69.37	71.34	70.88	70.37	70.26	70.92	71.58
4	72.79	72.2			68.43	69.43	71.42	70.80	70.37	70.37	70.95	71.63
5	72.67	72.2	3 70.9	3 71.69	68.39	69.52	71.53	70.73	70.36	70.42	71.80	71.67
6	72.59	72.3	9 71.0	7 71.54	68.34	69.62	71.61	70.66	70.39	70.44	70.98	71.71
7	72.56	72.4			68.33	69.75	71.64	70.60	70.48	70.44	70.98	71.57
8	72.54	72.3			68.34	69.84	71.66	70.55	70.52	70.45	70.95	71.00
9	72.53	72.0			68.34	69.91	71.67	70.52	70.54	70.45	70.96	70.42
10	72.47	71.8	1 71.4	9 70.01	68.31	69.96	71.64	70.46	70.51	70.45	70.93	70.06
11	72.37	71.6			68.26	70.03	71.57	70.40	70.49	70.47	70.92	69.86
12	72.29	71.6			68.28	70.11	71.48	70.36	70.45	70.50	70.91	69.79
13	72.12	71.6			68.36	70.20	71.37	70.35	70.39	70.56	70.89	69.80
14	71.96	71.6			68.43	70.29	71.24	70.42	70.34	70.59	70.83	69.82
15	71.88	71.5	5 71.7	7 69.29	68.49	70.36	71.17	70.50	70.31	70.66	70.78	69.92
16	71.72	71.4			68.51	70.42	71.14	70.59	70.30	70.71	70.75	70.01
17	71.54	71.4			68.51	70.48	71.16	70.63	70.33	70.74	70.74	69.95
18	71.45	71.5			68.48	70.54	71.15	70.71	70.40	70.71	70.73	69.90
19	71.46	71.4			68.45	70.57	71.15	70.76	70.44	70.58	70.73	69.93
20	71.53	71.3	7 71.9	1 69.14	68.44	70.62	71.14	70.81	70.46	70.50	70.73	70.00
21	71.61	71.4			68.44	70.70	71.14	70.88	70.51	70.58	70.80	70.08
22	71.63	71.6			68.52	70.82	71.13	71.00	70.48	70.67	70.83	70.18
23	71.65	71.7			68.61	70.89	71.13	71.09	70.49	70.81	70.89	70.26
24	71.70	71.8			68.71	70.97	71.12	71.17	70.48	70.89	70.94	70.37
25	71.70	71.7	2 72.1	0 68.70	68.81	71.05	71.21	70.94	70.52	70.95	71.03	70.43
26	71.70	71.5			68.93	71.14	71.33	70.69	70.52	70.94	71.13	70.32
27	71.70	71.6			69.01	71.22	71.35	70.58	70.48	70.88	71.20	70.29
28	71.79	71.6			69.08	71.28	71.28	70.46	70.43	70.82	71.24	70.26
29	71.82	71.7			69.17	71.29	71.21	70.35	70.35	70.75	71.26	70.30
30	71.87	71.6				71.26	71,15	70.29	70.26	70.75	71.31	70.33
31	71.95		- 71.9	2 68.52		71.21	*	70.30		70.77	71.38	
MEAN	72.10	71.7	9 71.6	6 69.75	68.53	70.37	71.32	70.66	70.42	70.60	70.95	70.48

WTR YR 1992 MEAN 70.73 HIGHEST 68.23 FEB. 11, 1992 LOWEST 73.43 OCT. 1, 1991



ST. THOMAS, U.S. VIRGIN ISLANDS

182038064580000. Local number, 8.

LOCATION.--Lat 18°20'38", long 64°58'00", Hydrologic Unit 21020001, 2.08 mi northwest of Charlotte Amalie, 0.50 mi northeast of Harry S. Truman Airport entrance on Hwy 302, and 1.15 mi southwest of Dorothea. Owner: U.S. Virgin Islands Water and Power Authority, Name: Kirwan Terrace, VIEO-6.

AQUIFER.--Alluvial deposits, volcanic rock.

WELL CHARACTERISTICS.--Drilled observation well, diameter 4 in (0.10 m), cased 0-56 in (0-17.1 m), screened 56-76 ft (17.1-23.2 m). Depth 76 ft (23.2 m).

INSTRUMENTATION.--Digital water level recorder--60-minute punch.

INSTRUMENTATION. --Digital water level recorder --60-minute punch.

DATUM. --Elevation of land-surface datum is about 35 ft (10.7 m) above mean sea level, from topographic map.

Measuring point: Top of shelter floor, 3.00 ft (0.91 m) above land-surface datum.

REMARKS. --Observation well. Drilled on July 1, 1991. Automated digital recorder installed on October 2, 1991.


PERIOD OF RECORD. --October 1991 to September 1992.

EXTREMES FOR PERIOD OF RECORD. --Highest water level recorded, 23.27 ft (7.09 m) below land-surface datum, Oct. 14, 1991; lowest water level recorded, 26.35 ft (8.03 m) below land-surface datum, Apr. 29, 1992.

WATER LEVEL, IN FEET BELOW LAND-SURFACE DATUM, WATER YEAR OCTOBER 1991 TO SEPTEMBER 1992 INSTANTANEOUS OBSERVATION AT 1200

DAY	ост	NOV	DEC	JAN	FRB	MAR	APR	MAY	JUN	JUL	AUG	SEP
1		23.62	25.29	26.16	24.64	24.32	24.68	25.53	23.65	24.38	25.47	25.39
2	23.38	23.53	25.31	26.18	24.60	24.31	24.70	25.24	23.67	24.66	25.43	25.43
3	23.35	23.43	25.33	26.22	24.56	24.30	24.74	25.13	23.68	24.89	25.36	25.45
4	23.34	23.36	25.35	26.25	24.53	24.30	24.79	25.06	23.69	25.00	25.35	25.47
5	23.34	23.30	25.38	26.27	24.49	24.32	24.86	24.99	23.71	25.02	25.32	25.50
6	23.35	23.46	25.41	25.90	24.47	24.28	24.90	24.89	23.91	25.02	25.30	25.51
7	23.37	24.00	25.44	25.46	24.43	24.30	24.95	24.82	23.89	25.05	25.28	25.50
8	23.39	24.27	25.48	25.17	24.40	24.33	24.99	24.73	23.84	25.10	25.26	25.50
9	23.39	24.36	25.50	25.01	24.37	24.35	25.05	24.62	23.94	25.12	25.23	25.50
10	23.39	24.44	25.52	24.91	24.34	24.40	25.07	24.71	23.74	25.14	25.20	
11	23.36	24.51	25.60	24.86	24.32	24.41	25.13	24.65	23.62	25.15	25.12	
12	23.32	24.59	25.67	24.85	24.32	24.45	25.20	24.87	23.62	25.17	25.07	
13	23.30	24.65	25.72	24.84	24.33	24.49	25.27	24.95	23.67	25.18	25.00	
14	23.29	24.72	25.77	24.83	24.34	24.53	25.35	24.88	23.69	25.27	24.93	
15	23.31	24.79	25.79	24.82	24.37	24.55	25.43	24.87	23.67	25.29	24.85	
16	23.35	24.84	25.80	24.82	24.44	24.57	25.51	24.86	23.71	25.32	24.81	
17	23.53	24.89	25.82	24.80	24.44	24.60	25.61	24.85	23.63	25.33	24.78	
18	23.78	24.94	25.85	24.80	24.43	24.62	25.66	24.86	23.43	25.32	24.79	
19	23.99	25.00	25.87	24.78	24.50	24.63	25.66	24.95	23.32	25.34	24.84	
20	24.27	25.05	25.90	24.72	24.51	24.66	25.71	24.95	23.90	25.31	24.89	
21	24.50	25.10	25.93	24.68	24.73	24.69	25.75	24.98	24.22	25.30	24.91	
22	24.69	25.16	25.94	24.69	24.45	24.73	25.73	24.98	24.38	25.33	24.94	
23	24.84	25.19	25.96	24.70	24.39	24.76	25.74	25.00	24.48	25.36	24.95	
24	24.92	25.20	25.99	24.66	24.36	24.81	25.76	24.41	24.56	25.37	24.99	
25	24.83	25.18	26.02	24.65	24.34	24.85	25.76	23.95	24.58	25.40	25.01	
26	24.64	25.20	26.04	24.67	24.35	24.86	25.79	23.78	24.61	25.41	25.04	
27	24.40	25.23	26.07	24.70	24.34	24.81	25.81	23.67	24.61	25.43	25.13	
28	24.20	25.23	26.10	24.72	24.30	24.71	25.81	23.64	24.51	25.46	25.18	
29	24.01	25.24	26.10	24.72	24.30	24.69	26.22	23.66	24.47	25.49	25.23	
30	23.87	25.26	26.12	24.72		24.67	25.73	23.70	24.44	25.51	25.30	
31	23.74		26.18	24.70		24.68		23.68		25.50	25.36	
MRAN	23.81	24.59	25.75	25.07	24.43	24.55	25.38	24.64	23.96	25.21	25.11	25.47

WTR YR 1992 MEAN 24.80 HIGHEST 23.27 OCT. 14, 1991 LOWEST 26.35 APR. 29, 1992



WATER YEAR

ŭ

GROUND-WATER LEVELS

ST. THOMAS, U.S. VIRGIN ISLANDS

181917064524600. Local number, 9.

LOCATION.--Lat 18°19'17*, long 64°52'46*, Hydrologic Unit 21020001, 0.20 mi southwest of Nadir, 1.25 mi northeast of Bolongo Bay Resort, and 1.95 mi southwest of the National Park Service Visitors Information Center at Red Hook.

Owner: U.S. Virgin Islands Water and Power Authority, Name: Race Track, VIBO-9.

AQUIFER.--Alluvial deposits, volcanic rock.

WELL CHARACTERISTICS.--Drilled observation well, diameter 4 in (0.10 m), cased 0-6 in (0-1.83 m), screened 6-35 ft (1.83-10.7 m). Depth 35 ft (10.7 m).

INSTRUMENTATION.--Digital water level recorder--60-minute punch.

DATUM.--Elevation of land-surface datum is about 15 ft (4.57 m) above mean sea level, from topographic map.

Measuring point: Top of shelter floor, 3.00 ft (0.91 m) above land-surface datum.

REMARKS.--Observation well. Drilled on July 10, 1991. Automated digital recorder installed on October 3, 1991.

PERIOD OF RECORD.--October 1991 to September 1992.

EXTREMES FOR PERIOD OF RECORD.--Highest water level recorded, 2.37 ft (0.72 m) below land-surface datum, Jan. 6, 1992; lowest water level recorded, 5.49 ft (1.67 m) below land-surface datum, Apr. 18, 1992.

		WATER LEVEL,	IN FEET		LAND-SURFAC ANTANBOUS C				1991 T	O SEPTEMBER	1992		
DAY	OCT	NOA	DEC	JAN	FRB	MAR	APR	MAY	JUN	JUL	AUG	SEP	K.
1		4.70	4.47	5.20	4.28	4.81	5.23	5.05	4.06	4.85	5.30	5.05	
2		4.73	4.42	5.21	4.27	4.80	5.32	4.38	2.67	4.91	5.25	5.04	
3		4.67	4.47	5.27	4.31	4.77	5.29	4.76	3.08	4.91	5.19	5.05	
4	3.58	4.62	4.51	5.26	4.33	4.80	5.27	4.82	3.29	4.97	5.17	2	ž
5	3.71	4.67	4.59	5.26	4.33	4.85	5.30	4.89	3.45	4.98	5.09	5.04	2
6	3.82	4.67	4.64	2.46	4.37	4.87	5.29	4.93	3.63	4.99	5.08		Ģ.
7	3.93	4.51	4.69	2.85	4.37	4.94	5.30	4.96	3.74	5.02	5.07		ş.e.
8	4.01	3.65	4.74	3.10	4.48	5.01	5.27	5.03	3.86	5.11	4.86	4.98	da d
9	4.09	3.99	4.77	3.33	4.53	5.01	5.28	5.07	3.97	5.10	4.90	4.98	£ .
10	4.13	4.04	4.80	3.43	4.57	5.01	5.37	5.10	4.06	5.12	4.87	4.99	ůi
11	4.19	4.09	4.82	3.53	4.67	5.03	5.36	5.08	4.08	5.14	4.91	2.00	2.2
12	4.24	4.14	4.83	3.72	4.77	5.08	5.39	5.16	4.14	5.15	4.92	3.00	12
13	4.28	4.19	4.86	3.70	4.78	5.09	5.36	5.16	4.23	5.10	4.86	3.00	-13 -13
14	4.31	4.26	4.90	3.78	4.79	5.13	5.39	5.20	4.30	5.12	4.86	3.04	3.P.
15	4.32	4.30	4.91	3.86	4.79	5.14	5.39	5.17	4.33	5.11	4.90	5.04	43
16	4.34	4.37	4.87	3.95	4.80	5.01	5.39	5.24	4.40	5.09	4.89	J. UU ,	e Z
17	4.35	4.41	4.86	4.05	4.84	5.14	5.45	5.20	4.42	5.04	4.92		1.2
18	4.39	4.42	4.92	4.09	4.90	5.16	5.42	5.23	4.41	5.00	4.94	=.,,	3.
19	4.46	4.49	4.89	4.11	4.95	5.17	5.42	5.25	4.47	5.02	4.98		
20	4.48	4.55	4.94	4.17	4.94	5.16	5.40	5.30	4.45	5.08	5.07	4.99	· £
21	4.48	4.60	4.92	4.21	4.97	5.21	5.34	5.27	4.49	5.08	5.11	,,	45
22	4.51	4.51	4.97	4.28	4.95	5.23	5.32	5.23	4.41	5.11	5.13		e iz
23	4.51	4.54	5.00	4.29	4.99	5.19	5.36	5.15	4.54	5.16	5.16		1. E
24	4.53	3.54	5.05	4.30	4.99	5.22	5.37	2.77	4.61	5.16	5.13	#10#	·蒙 李蒙
25	4.57	3.99	5.08	4.21	4.93	5.23	5.40	2.99	4.66	5.19	5.07	4.62	78
26	4.61	4.16	5.07	4.13	4.92	5.21	5.39	3.27	4.69	5.24	5.06		ů¥ ***
27	4.64	4.28	5.08	4.16	4.88	5.22	5.37	3.31	4.73	5.25	5.06		4
28	4.64	4.35	5.12	4.20	4.88	5.24	5.47	3.52	4.82	5.23	5.04	4.31	海龙 水 3-
29	4.66	4.38	5.12	4.23	4.86	5.23	5.41	3.68	4.82	5.23	5.05	4.00	\$\$ 5.00
30	4.66	4.45	5.11	4.25		5.16	5.44	3.85	4.86	5.20	5.05	/	्र
31	4.70		5.17	4.25		5.22		3.97		5.22	5.01		3 €
MRAN	4.33	4.34	4.86	4.09	4.70	5.08	5.36	4.64	4.19	5.09	5.03	4.89	多数高
WTR YR	1992	MEAN 4.72	HIGHEST 2	.37 JAN	1. 6, 1992	LOWEST	5.49 APR.	18, 1992				34% E	神州

WATER LEVEL, IN FEET BELOW LAND-SURFACE DATUM 2 724 Charles and 4 WALLES TORS 6 SEPT OCT NOV DEC JAN FEB MAR APR MAY JUNE JULY AUG 1992 WATER YEAR

ST. THOMAS, U.S. VIRGIN ISLANDS

21.07

20.58

21.96

192131064541000. Local number, 10.

LOCATION.--Lat 18°21'31°, long 66°54'10°, Hydrologic Unit 21020001, 2.35 mi northeast of Charlotte Amalie, 0.92 mi northeast of Winterberg Peak, and 1.22 mi southeast of Canaan. Owner: U.S. Virgin Islands Water and Power Authority, Name: Highway 42 dead end, VIEO-10.

ACOIFER.--Alluvial deposits, volcanic rock.

WELL CHARACTERISTICS.--Drilled observation well, diameter 4 in (0.10 m), cased 0-27 in (0-0.23 m), screened 27-53 ft (8.23-16.2 m). Depth 53 ft (16.2 m).

INSTRUMENTATION.--Digital water level recordar--60-minute punch.

DATUM.--Elevation of land-surface datum is about 155 ft (47.2 m) above mean sea level, from topographic map.

Measuring point: Top of shelter floor, 3.00 ft (0.91 m) above land-surface datum.

REMARKS.--Observation well. Drilled on July 15, 1991. Automated digital recorder installed on October 3, 1991.

PERIOD OF RECORD.--Cotober 1991 to September 1992.


ENTREMES FOR PERIOD OF RECORD.--Highest water level recorded, 16.67 ft (5.00 m) below land-surface datum, Jan. 6, 1992; lowest water level recorded, 23.43 ft (7.14 m) below land-surface datum, Sept. 16, 1992.

WATER LEVEL, IN FEET BELOW LAND-SURFACE DATUM, WATER YEAR OCTOBER 1991 TO SEPTEMBER 1992 INSTANTAMEOUS OBSERVATION AT 1200 DAY OCT NOV SEP DEC JAN MAY JUL AUG 21.51 21.08 22.70 22.73 22.11 21.69 21.42 19.58 22.55 22.57 22.86 21.30 ------21.12 ---21.62 21.42 21.47 ---21.21 21.15 22.97 3 ---21.11 22.77 ---21.10 21.06 ___ 20.21 22.40 23.03 20.91 21.70 21.22 22.80 ---21.22 21.97 ---20.69 21.51 22.57 23.11 21.76 22.83 21.14 21.34 ---21.57 23.10 21.25 22.06 21.43 20.97 21.05 21.11 6 21.34 21.11 21.45 17.02 ---21.29 22.15 22.21 ---21.62 21.08 21.91 20.51 21.51 21.55 ... 19.52 ---21.33 21.37 21.68 21.72 22.07 22.45 22.63 21.65 21.60 20.20 21.64 21.73 22.17 22.25 9 19.55 19.33 ------21.41 ---21.09 21.79 22.10 21.72 22.76 10 ------21.79 ---22.36 20.12 21.04 22.00 20.03 19.77 19.45 20.03 20.46 21.97 11 21.85 ... ---21.09 22.99 22.41 12 21.92 22.45 22.49 22.53 20.55 ---21.52 21.56 21.93 22.00 22.14 23.10 23.20 ---13 21.16 ---20.48 ---14 21.32 20.10 22.04 ---21.60 ---20.69 22.03 20.51 22.37 21.45 20.41 22.10 ---20.55 22.56 ---23.35 21.58 20.64 21.09 20.59 20.79 22.47 23.41 22.60 21.92 21.90 21.00 21.46 21.44 20.04 21.02 21.17 22.01 21.84 21.97 20.62 20.67 20.70 21.72 21.76 21.00 22.64 22.68 22.71 22.30 22.73 22.90 17 21.69 21.77 ------20.83 22.57 10 ------20.07 22.65 22.72 20 21.30 21.31 22.06 ---20.74 22.73 20.94 22.00 23.05 21.03 19.91 20.69 20.95 19.69 21 22 23 21.44 21.53 21.60 10.12 22.12 20.78 22.77 23.30 23.33 21.00 21.64 21.78 22.25 22.95 21.86 22.19 22.27 22.34 21.90 21.93 23.11 ---20.82 22.61 21.03 22.47 ---20.86 23.36 21.89 22.61 22.71 22.83 21.00 24 22.35 ---21.96 ---21.11 25 20.44 19.96 22.41 20.94 22.00 20.76 22.00 22.01 26 20.70 20.50 22.47 20.97 22.04 21.32 21.17 22.17 22.09 20.09 20.89 20.35 22.52 ---20.76 21.21 21.26 22.25 22.96 21.73 21.01 ---21.96 28 21.05 21.10 20.55 22.50 ---21.04 21.03 ---20.76 22.32 23.03 22.10 ---29 22.62 21.08 21.93 ---20.65 21.20 22.39 23.00 22.33 30 21.31 20.94 22.64 ---21.33 22.51 22.00 31 21.43 ---21.28 22.71 22.07

WTR YR 1992 MEAN 21.65 HIGHEST 16.67 JAM. 6, 1992 LOWEST 23.43 SEPT. 16, 1992

20.78

21.60



21.64

22.40

20.07

21.86

21.54

22.46

22.69

ST. THOMAS, U.S. VIRGIN ISLANDS

182035064550200. Local nember, 11.

LOCATION.--Lat 18°20'35°, long 64°55'02°, Hydrologic Unit 21020001, 0.05 mi east of Fort Christian in Charlotte Amalie town, 0.10 mi north of HNY 310 on Pearson Gardens area, and 0.72 mi southwest of Winterberg Peak.

Owner: U.S. Virgin Islands Water and Fower Authority, Name: Lockhart School, VIBO-11.

AGUIFER.--Alluvial deposits, volcanic rock.

WELL CHARACTERISTICS.--Drilled observation well, diameter 4 in (0.10 m), cased 0-90 in (0-27.4 m), screened 90-110 ft (27.4-33.5 m). Depth 110 ft (33.5 m).

INSTRUMENTATION.--Digital water level recorder--60-minute punch.

DATUM.--Elevation of land-surface datum is about 40 ft (12.2 m) above mean sea level, from topographic map.

Measuring point: Top of shelter floor, 2.50 ft (0.76 m) above land-surface datum.


REMARKS.--Observation well. Drilled on July 23, 1991. Automated digital recorder installed on Movember 19, 1991.

PERIOD OF RECORD.--November 1991 to September 1992.

EXTREMES FOR PERIOD OF RECORD.--Eighest water level recorded, 31.78 ft (9.69 m) below land-surface datum, Peb. 12, 1992; lowest water level recorded, 35.42 ft (10.8 m) below land-surface datum, Dec. 31, 1991.

		WATER LEV	/RL, IN PR		Land-Suri Tantanbous			YHAR OCTOBI 1200	IR 1991 1	ro septemb	ER 1992	
DAY	OCT	MOA	Dac	Jan	723	MAR	APR	MAY	JUN	JUL	AUG	SRP
1			34.25	35.21	32.27	33.30	34.05	34.09	32.91	33.65	34.04	33.83
2			34.19	34.99	32.76	32.79	34.56	33.97	33.10	33.16	33.99	33.99
3			33.78	35.02	32.08	32.75	34.65	34.52	32.09	33.90	33.91	33.70
4			34.06	35.06	32.26	32.93	34.91	34.45	32.00	33.69	33.43	33.93
5			33.93	34.80	32.56	32.92	34.90	34.02	32.91	33.31	33.69	34.41
6			34.20	34.12	32.47	32.98	34.46	33.79	33.49	33.57	33.33	34.06
7			34.40	33.64	32.35	33.70	34.91	33.91	33.59	33.26	33.33	34.19
8			33.73	33.34	32.57	33.19	34.79	34.41	33.39	33.74	33.36	33.82
9			33.83	33.17	32.23	33.27	34.94	34.14	32.98	33.29	33.41	32.92
10			34.12	32.53	31.92	33.40	34.39	33.95	32.89	33.60	33.25	33.00
11			34.47	33.19	31.87	33.29	34.91	34.15	32.87	33.74	33.27	32.82
12			34.00	32.92	31.86	33.63	34.70	33.71	33.37	33.36	33.14	33.35
13			34.00	32.20	32.13	33.99	34.90	33.65	33.34	33.37	33.18	33.25
14			34.39	32.15	31.96	33.92	34.17	33.65	33.26	33.81	33.61	33.42
15			35.00	32.76	32.26	34.12	34.17	34.17	32.80	33.74	33.67	33.49
16			34.54	32.19	32.64	34.00	34.80	34.44	32.91	33.84	33.59	32.93
17			34.29	32.29	32.74	33.76	34.16	34.54	32.74	33.25	33.59	32.88
18			34.60	32.81	32.15	33.65	34.83	34.59	32.96	33.66	33.18	33.04
19			34.74	32.90	32.15	33.71	34.89	34.03	32.92	33.73	33.24	33.27
20		34.02	34.76	32.82	32.16	33.68	34.89	33.97	33.55	33.21	33.01	33.56
21		34.42	35.00	32.15	32.47	34.32	34.69	34.43	33.58	33.63	33.28	33.05
22		34.24	35.12	32.08	32.89	34.47	34.18	34.17	33.48	33.76	33.79	33.05
23		34.71	35.19	32.16	32.95	34.01	34.20	34.26	33.11	33.32	33.92	32.94
24		34.71	34.75	32.02	32.39	34.00	34.90	34.25	33.17	33.74	33.47	33.08
25		33.96	34.58	32.25	32.40	33.96	34.82	34.11	33.26	34.07	33.66	33.65
26		33.92	35.27	32.60	32.34	34.06	34.95	33.96	33.32	33.87	33.74	33.40
27		33.87	35.22	32.30	32.58	34.04	34.32	33.20	33.77	33.34	33.54	33.61
28		33.90	35.00	32.31	32.86	34.67	34.91	32.95	33.30	33.47	33.61	32.96
29		34.33	35.11	32.62	32.78	34.62	34.27	32.98	33.17	33.82	34.13	33.11
30		34.38	35.23	32.02		34.13	34.84	33.49	33.14	33.37	34.26	33.30
31			35.33	32.54		34.39		33.20		33.41	33.73	
MEAN		34.21	34.56	33.01	32.30	33.73	34.63	33.97	33.16	33.57	33.56	33.40

WTR YR 1992 MEAN 33.63 HIGHEST 31.78 PRB. 12, 1992 LOWEST 35.42 DEC. 31, 1991



ST. JOHN, U.S. VIRGIN ISLANDS

182010064472600. Local number, 1.

LOCATION. - Location 1 19220430", long 64°47'26", Hydrologic Unit 21020001, 0.40 mi sotheast from Cruz Bay plaza, 0.30 mi southwest of Caneel Hill, and 0.32 mi northeast of the Government House at Cruz Bay. Owner: U.S. Virgin Islands Government, National Park Services, Name: NPS-2 (Cruz Bay).

গ্ৰী উঠা এই জনজন্ম াত্ৰ AQUIFER.--Volcanic rocks of Cretaceous Age.

WELL CHARACTERIGRET - Drilled unused water-table well, diameter 6 in (0.15 m), 4 in (0.10 m) cased, 0-20 ft (0-6.10 m), open hole 20-99 ft (6.10-30.2 m). Depth 99 ft (30.2 m).

INSTRUMENTATION. -- Monthly measurement with chalked steel tape by USGS personnel.

DATUM.--Elevation of land-surface datum is 60 ft (18.3 m) above mean sea level, from topographic map.

Measuring point: Top of 4 in (0.10 m) casing, 4.10 ft (1.25 m) above old land-surface datum after 1.40 ft (0.43 m) landefield and 2.70 ft (0.82 m) casing extension occurred. Prior to June 29, 1983, top of 4 in (0.10 m) casing, 1.40 ft (0.43 m) above land-surface datum.

REMARKS. -- Observation well. Water levels affected by pumping nearby well.


PERIOD OF RECORD # May 1964, discontinued. June 30, 1983 to current year.

EXTERMES FOR PRINGO OF RECORD. -- Highest water level measured, +1.41 ft (0.43 m) above land-surface datum, May 1, 1986, 10 west water level measured, 42.56 ft (12.98 m) below land-surface datum, Aug. 30, 1967.

WATER LEVEL, IN FEET BELOW LAND-SURFACE DATUM, WATER YEAR OCTOBER 1991 TO SEPTEMBER 1992 26.04 28. **8**1 INSTANTANEOUS OBSERVATIONS 传点。在它 Water Date : Water Water Water Level Date level Date level Date level 36 E& 34.14 99.5 Oct. 21.90 Feb. 13 28.61 25.40 July 17 31.40 Jan. 18 ₹8.34.12 0.42 Nov. May

경우, 원인 중국 원인 WATER (文章) 1992 - REGHEST 0.42 JAN. 9, 1992 LOWEST 34.14 OCT. 8, 1991

+ Above land-surface datum.



ST. JOHN, U.S. VIRGIN ISLANDS

182109064460300. Local number, 2.

LOCATION. -- Lat 18°21'09", long 64°46'03", Hydrologic Unit 21020001, 2.28 mi northeast of Cruz Bay Plaza, 2.20 mi northeast of the Government House at Cruz Bay, and 0.10 mi south of entrance to Trunk Bay on Hwy 20. Owner: U.S. Virgin Islands Government, National Park Service, Name: NPS-5 (Trunk Bay).

AQUIFER .-- Volcanic rocks of Cretaceous Age.

WELL CHARACTERISTICS.--Drilled water-table production well, diameter 6 in (0.15 m), cased 0-12 ft (0-3.66 m), open hole 12-60 ft (3.66-18.3 m). Depth 60 ft (18.3 m).

INSTRUMENTATION .-- Monthly measurement with chalked steel tape by USGS personnel.

DATUM.--Elevation of land-surface datum is 60 ft (18.3 m) above mean sea level, from topographic map.

Measuring point: Top of 6 in (0.15 m) casing, 0.70 ft (0.21 m) above land-surface datum. Prior to Mar. 24,
1982 top of 6 in (0.15 m) casing, 1.00 ft (0.30 m) above land-surface datum.

REMARKS .-- Active water supply well for recreation facilities at Trunk Bay.


PERIOD OF RECORD .-- August 1964 to December 1969, discontinued. March 1982 to current year.

EXTREMES FOR PERIOD OF RECORD. --Highest water level measured, 12.83 ft (3.91 m) below land-surface datum, Jan. 24, 1985; lowest water level measured, a57.29 ft (17.47 m) below land-surface datum, Nov. 27, 1968.

WATER LEVEL, IN FEBT BELOW LAND-SURFACE DATUM, WATER YEAR OCTOBER 1991 TO SEPTEMBER 1992 INSTANTANEOUS OBSERVATIONS

Dat	e	Water level	Date	Water level	Date	Water level	Date	Water level
Oct. Nov.	8 7	a47.50 41.68	Dec. 11 Jan. 10	a50.18 a48.86	Feb. 13 May 18	42.53 36.24	July 16	34.40

WATER YEAR 1992 HIGHEST 34.40 JULY 16, 1992 LOWEST a50.18 DEC. 11, 1991



ST. JOHN, U.S. VÍNGIM ISLANDS1

102116064451000. Local number, 3.

LOCATION.--Lat 10°21'16°, long 64°45'10°, Hydrologic Unit 21020001, 3.08 mi northeast of Crus Bay plaza, 2.62 mi northwest of Coral Bay, and 0.95 mi northwest of Mamey Péak. Owner: U.S. Virgin Islands Government, Mational Park Service, Name: MPS-6 (Cinnanon Bay).

AQUIFER.--Volcanic rocks of Cretaceous Age.

MELL CHARACTERISTICS.--Drilled water-table abandoned production well, diameter 6-in (0.15 m), cased 0-51 ft (0-15.55 m), open hole 51-70 ft (15.55-21.34 m). Depth 70 ft (21.34 m).

INSTRUMENTATION.--Digital water level recorder--60-minute punch.

DATUM.--Elevation of land-surface datum is about 60 ft (16.3 m) above mean sea level, from topographic map.

Measuring point: Hole on 6 in (0.15 m) casing, 2.00 ft (0.61 m) above land-surface datum. Prior to June 29, 1963, top of 6 in (0.15 m) casing at land-surface datum.

REMARKS.--Recording observation well.


PERIOD OF RECORD.--August 1964 to December 1969, discontinued. March 1982 to current year.

EXTREMES FOR PERIOD OF RECORD.--Highest water level recorded, 41.12 ft (12.56 m) below land-surface datum, Aug. 15, 1969; lowest water level recorded, 63.15 ft (19.25 m) below land-surface datum, July 1, 1969.

WATER LEVEL. IN FEET BELOW LAND-SURFACE DATUM, WATER YEAR OCTOBER 1991 TO SEPTEMBER 1992

		MATER AND	YBL, IN FE			US OBSERV			MR 1771 1	O SEPTEM	MK 1776	
DAY	OCT	MOV	DBC	Jan	753	MAR	APR	MAY	JUN	JUL	YOG	SEP
1	56.67	58.16	57.53	50.62	56.60	59.65	59.94	59.71	50.11	59.71	59.75	60.21
2	56.61	58.16	57.53	56.62	58.75	5 9 .71	59.94	59.54	56.14	59.67	59.71	60.24
3	56.54	50.16	57.64	58.60	50.63	59.73	59.94	59.26	50.21	59.71	59.63	60.26
4	56.49	50.15	57.77	56.57	56.67	59.73	59.95	59.01	56.24	59.68	59.57	60.30
5	56.43	56.17	57.69	56.53	50.66	59.72	60.00	58.97	56.26	59.71	59.51	60.34
6	58.34	56.24	57.96	50.45	50.66	59.72	60.04	50.97	50.35	59.70	59.45	60.36
7	56.29	56.19	56.09	56.27	50.00	59.74	60.06	58.97	56.45	59.63	59.41	60.36
•	50.26	56.11	56.16	56.16	56.91	59.76	60.07	59.01	50.52	59.70	59.36	60.37
•	56.22	50.06	56.24	56.07	58.96	59.69	60.05	59.07	56.60	59.75	59.36	60.33
10	50.20	56.01	58.24	56.12	56.67	59.59	60.01	59.14	56.69	59.79	59.34	60.30
11	58.16	57.94	58.20	56.17	58.62	59.60	59.99	59.22	50.76	59.85	59.41	60.27
12	56.13	57.69	56.19	58.22	56.79	59.65	59.98	59.29	58.86	59.91	59.48	€0.25
13	56.10	57.65	56.20	56.26	58.66	59.74	60.04	59.36	56.95	59.66	59.55	60.25
14	56.06	57.63	50.19	56.30	56.94	59.77	60.06	59.42	56.97	59.79	59.61	60.26
15	58.06	57.77	58.26	50.35	59.01	59.60	60.11	59.46	50.96	59.76	59.69	60.26
16	50.06	57.73	58.33	58.43	59.07	59.62	60.14	59.54	50.95	59.79	59.74	60.26
17	56.05	57.70	58.27	56.49	59.16	59.85	60.17	59.59	58.94	59.67	59.76	60.18
16	56.05	57.67	58.24	56.56	59.24	59.65	60.18	59.64	50.93	59.69	59.66	60.07
19	56.04	57.66	56.22	58.62	59.32	59.82	60.19	59.62	59.05	59.91	59.93	59.96
20	58.02	57.65	58.26	56.54	59.40	59.79	60.20	59.70	59.16	59.63	59.96	59.66
21	56.00	57.64	58.26	56.49	59.46	59.76	60.22	59.73	59.23	59.63	60.02	59.77
22	57. 9 7	57.64	58.23	58.48	59.52	59.78	60.28	59.72	59.31	59.91	60.06	59.71
23	57.94	57.63	58.25	56.45	59.59	59.79	60.20	59.64	59.39	59.96	60.10	59.73
24	57.92	57.63	56.26	58.55	59.54	59.76	60.14	59.52	59.46	60.04	60.13	59.74
25	57.90	57.61	58.33	58.64	59.50	59.77	60.15	59.16	59.53	60.06	60.17	59.74
26	57.90	57.58	58.37	56.71	59.47	59.77	60.12	56.60	59.60	60.11	60.19	59.75
27	57.89	57.58	58.43	50.66	59.44	59.79	60.05	56.57	59.68	68.07	60.21	59.74
28	57.69	57.58	50.50	56.61	59.51	59.60	59.99	56.42	59.73	60.02	60.16	59.73
29	56.01	57.56	58.55	58.57	59.59	59.83	59.92	58.27	59.77	59.97	60.15	59.73
30	56.11	57.54	56.61	58.66		59.66	59.62	56.21	59.75	59.91	60.16	59.73
31	50.16		50.50	58.74		59.93		56.16		59.62	60.21	
MEAN	58.14	57.84	58.19	58.47	59.13	59.76	60.06	59.18	58.95	59.85	59.80	60.07

WTR YR 1992 MEAN 59.12 HIGHEST 57.52 DEC. 2, 1991 LOWEST 60.38 SEPT. 6-6, 1992



ST. JOHN, U.S. VIRGIN ISLANDS

192042064454500. Local number, 5.
LOCATION.--Lat 10°20'42", long 64°45'45", Hydrolegid Unit 21020001, 2.30 mi northwest of Crus Bay plaza, 0.30 mi south of Peter Peek, and 0.65 mi east of Susannaberg em Center Line road. Owner: U.S. Virgin Islands Government, Mane: DPW-6. (Susannahorg)
AQUIPER.--Louisenhoj Permation.
WELL CHARACTERISTICS.--Drilled water-table well, diameter 6 in (0.15 m), cased 6 in (0.15 m). Sounded depth

WELL CHARACTERISTICS. -- Drilled water-table well, diameter 6 in (0.15 m), cased 6 in (0.15 m). Sounded depth 70 ft (21.3 m).

INSTRUMENTATION. -- Digital water level recorder -- 60-minute punch, discontinued on April 9, 1992. Monthly measurement with chelked steel tape by USGS personnel.

DATUM. -- Elevation of land-surface datum is about 660 ft (195 m) above mean see level, from topographic map. Measuring point: Top of 6 in (0.15 m) casing, 1.60 ft (0.49 m) above land-surface datum. Prior to June 20, 1993, top of 6 in (0.15 m) casing, 1.30 ft (0.40 m) above land-surface datum.

REMARKS. -- Recording observation well. Automatic digital recorder discontinued on April 9, 1992.


PERIOD OF RECORD. -- September 1982 to current year.

EXTREMES FOR FERIOD OF RECORD. -- Sighest water level recorded, 1.33 ft (0.60 m) below land-surface datum, May 10, 1996; lowest water level recorded, 24.05 ft (7.57 m) below land-surface datum, Nov. 8, 1991.

WATER LEVEL,	IN	PEST	BELOW	LAND-	SURFACE	DATUM,	WATER	YEAR	OCTOBER	1991	TO	SEPTEMBER	1992
			II	MATANT	BUOGHA!	OBSERVA	TION AT	1200)				

DAY	OCT	MOV	DBC	Jan	783	MAR	APR	MAY	JUN	JUL	AUG	SEP
1	24.61	24.79	20.07	22.16	20.64	22.35	23.60					
2	24.59	24.90	20.97	22.20	20.73	22.40	23.71					
3	24.50	24.92	20.90	22.26	20.79	22.45	23.75					
4	24.57	24.83	20.92	22.30	20.84	22.50	23.79					
5	24.56	24.84	20.95	22.34	20.91	22.55	23.83					
6	24.55	24.05	20.96	9.19	20.97	22.62	22.07					
7	24.53	24.85	20.90	17.61	21.01	22.66	23.91					
•	24.51	24.04	21.04	19.37	21.08	22.72	23.94					
9	24.50	24.94	21.09	19.50	21.14	22.77						
10	24.50	21.06	21.14	19.67	21.20	22:78						
11	24.50	23.92	21.23	19.65	21.26	22.94						
12	24.50	23.85	21.33	19.59	21.33	22.99	***					
13	24.50	23.60	21.39	19.51	21.39	22.95						
16	24.50	23.36	21.44	19.46	21.45	22.99						
15	24.51	23.16	21.50	19.42	21.52	23.03						
16	24.54	23.00	21.56	19.40	21.60	23.06						
17	24.57	22.85	21.60	19.40	21.66	23.10				20.93		
19	24.57	22.76	21.64	19.43	21.74	23.13		21.70				
19	24.59	22.69	21.67	19.52	21.79	23.16						
20	24.61	22.65	21.73	19.64	21.84	23.19						
21	24.61	22.65	21.77	19.75	21.90	23.22						
22	24.65	22.65	21.90	19.96	21.95	23.26						
23	24.66	22.65	21.93	19.97	22.01	23.31						
24	24.67	11.21	21.97	20.06	22.06	23.34						
25	24.69	21.32	21.90	20.13	22.10	23.37						
26	24.70	21.24	21.94	20.23	22.14	23.40					•-•	
27	24.73	21.16	21.99	20.31	22.19	23.44						
20	24.74	21.05	22.01	20.38	22.24	23.50						
29	24.75	20.95	22.05	20.47	22.29	23.54						
30	24.76	20.88	22.10	20.55		23.59						
31	24.76		22.13	20.60		23.64						
MEAN	24.60	22.74	21.49	19.00	21.51	23.02	23.81					

WTR YR 1992 MEAN 22.27 HIGHEST 6.24 JAN. 6, 1992 LOWEST 24.85 NOV. 9, 1991



ST. JOHN, U.S. VIRGIN ISLANDS

182044064454600. Local number, 6.

LOCATION.--Lat 18°20'44", long 64°45'46", Hydrologic Unit 21020001, 2.27 mi northeast of Cruz Bay plaza, 0.28 mi southwest of Peter Peak, and 0.58 mi northeast of Susannaberg on Center Line road. Owner: U.S. Virgin Islands Government, Name: DPW-5.

AQUIFER . -- Louisenhoj Formation.

WELL CHARACTERISTICS. -- Drilled public supply water-table well, diameter 6 in (0.15 m), cased 6 in (0.15 m). Sounded depth 145 ft (44.2 m).

INSTRUMENTATION .-- Monthly measurement with chalked steel tape by USGS personnel.

DATUM.--Elevation of land-surface datum is about 640 ft (195 m) above mean sea level, from topographic map.

Measuring point: Top of 6 in (0.15 m) casing, 1.80 ft (0.55 m) above land-surface datum. Prior May 18, 1992,
top of 6 in (0.15 m) casing, 1.50 ft (0.46 m) above land-surface datum. Prior Oct. 23, 1990, top of 6 in (0.15 m)
casing, 1.40 ft (0.43 m) above land-surface datum.

REMARKS. -- Observation well. Water levels affected by pumping.


PERIOD OF RECORD. -- September 1982 to current year.

EXTREMES FOR PERIOD OF RECORD.--Highest water level measured, 18.85ft (5.74m) below land-surface datum, July 2, 1986; lowest water level measured, a108.6 ft (33.1 m) below land-surface datum, Oct. 8, 1991.

WATER LEVEL, IN FRET BELOW LAND-SURFACE DATUM, WATER YEAR OCTOBER 1991 TO SEPTEMBER 1992 INSTANTANEOUS OBSERVATIONS

Date	Water level	Date	Water level	Date	Water level	Date	Water level
Oct. 8 Nov. 8	a108.65 a105.98	Dec. 11 Jan. 9	56.31 53.66	Feb. 14 May 18	54.20 52.09	July 17	48.87

WATER YEAR 1992 HIGHEST 48.87 JULY 17, 1992 LOWEST a108.6 OCT. 8, 1991



ST. JOHN, U.S. VIRGIN ISLANDS

182044064454800. Local number, 7.

LOCATION. -- Lat 18°20'44, long 64°45'48", Hydrologic Unit 21020001, 2.18 mi northeast of Cruz Bay plaza, 0.31 mi southwest of Peter Peak, and 0.48 mi northeast of Susannaberg on Ceter Line road. Owner: U.S. Virgin Islands Government, Name: DPW-4.

AQUIFER .-- Louisenhoj Formation.

WELL CHARACTERISTICS. -- Drilled public supply water-table well, diameter 6 in (0.15 m), cased 6 in (0.15 m). Sounded depth 60 ft (18.3 m).

INSTRUMENTATION. -- Monthly measurement with chalked steel tape by USGS personnel.

DATUM.--Elevation of land-surface datum is about 640 ft (195 m) above mean sea level, from topographic map.

Measuring point: Top of 6 in (0.15 m) casing, 1.30 ft (0.40 m) above land-surface datum. Prior May 18, 1992, top
of 6 in (0.15 m) casing, 0.60 ft (0.18 m) above land-surface datum.

REMARKS. -- Observation well.


PERIOD OF RECORD. -- September 1982 to current year.

EXTREMES FOR PRRIOD OF RECORD.--Highest water level measured, 14.48 ft (4.41 m) below land-surface datum, July 2, 1986; lowest water level measured, 52.45 ft (15.98 m) below land-surface datum, Nov. 8, 1991.

WATER LEVEL, IN FEET BELOW LAND-SURFACE DATUM, WATER YEAR OCTOBER 1991 TO SEPTEMBER 1992 INSTANTANEOUS OBSERVATIONS

Date	Water level	Date	Water level	Date	Water level	Date	Water level
Oct. 8 Nov. 8	50.32 52.45	Dec. 11 Jan. 9	48.45 43.22	Feb. 14 May 18	a50.90 40.03	July 17	37.91

WATER YEAR 1992 HIGHEST 37.91 JULY 17, 1992 LOWEST 52.45 NOV. 8, 1992



WATER YEAR

ST. JOHN, U.S. VIRGIN ISLANDS

182044064454900. Local number, 8.

LOCATION.--Lat 18°20'44", long 64°45'49", Hydrologic Unit 21020001, 2.15 mi northeast of Crus Bay plaza, 0.35 mi southwest of Peter Peak, and 0.45 mi northeast of Susannaberg on Center Line road. Owner: U.S. Virgin Islands Government, Name: DPW-3.

AQUIPER .-- Louisenhoj Formation.

WELL CHARACTERISTICS.--Drilled public supply water-table well, diameter 6 in (0.15 m), cased 6 in (8.15 m). Sounded depth 110 ft (33.5 m).

INSTRUMENTATION. -- Monthly measurement with chalked steel tape by USGS personnel.

DATUM.--Elevation of land-surface datum is about 620 ft (189 m) above mean sea level, from topographic map. Prior to this report, elevation used was 640 ft (195 m). Measuring point: Top of 6 in (0.15 m) casing, 1.80 ft (0.55 m) above land-surface datum.

REMARKS. -- Observation well.


PERIOD OF RECORD. -- September 1982 to current year.

EXTREMES FOR PERIOD OF RECORD. -- Highest water level measured, 12.17ft (3.71 m) bolow land-surface datum, July 2, 1986; lowest water level measured, 69.58 ft (21.21 m) below land-surface datum, Feb. 27, 1986.

WATER LEVEL, IN FRET BELOW LAND-SURFACE DATUM, WATER YEAR OCTOBER 1991 TO SEPTEMBER 1992 INSTANTANEOUS OBSERVATIONS

Date	Water level	Date	Water level	Date	Water level	Date	Water level
Nov. 9	a40.58	Jan. 9	38.18	May 18	35.44	July 17	33.30

WATER YEAR 1992 HIGHEST 33.30 JULY 17, 1992 LOWEST 42.72 DEC. 11, 1991



ST. JOHN, U.S. VIRGIN ISLANDS

182044064455000. Local number, 9.

LOCATION.--Lat 18°20'44°, long 64°45'50°, Hydrologic Unit 21020001, 2.05 mi northeast of Cruz Bay plass, 0.41 mi southwest of Peter Peak, and 0.38 mi east of Susannabery on Center Line road. Owner: U.S. Virgin Islands Government, Hame: DPW-2.

AQUIFER .-- Louisenhoj Formation.

WELL CHARACTERISTICS. -- Drilled public supply water-table well, diameter 6 in (0.15 m), cased 6 in (0.15 m). Sounded depth 65 ft (19.8 m).

INSTRUMENTATION .- - Nonthly measurement with chalked steel tape by USGS personnel.

DATOM. --Elevation of land-surface datum is about 620 ft (189 m) above mean sea level, from topographic map. Prior to this report, elevation used was 640 ft (195 m). Measuring point: Top of 6 in (0.15 m) casing, 2.00 ft (8.61 m) above land-surface datum.

REMARKS. -- Observation well.


PERIOD OF RECORD. -- September 1982 to current year.

EXTREMES FOR PERIOD OF RECORD. -- Highest water level measured, 14.93 ft (4.55 m) below land-surface datum, Dec. 19, 1989; lowest water level measured, a55.67 ft (a16.9 m) below land-surface datum, Feb. 14, 1992.

MATER LEVEL, IN FEST BELOW LAND-SURFACE DATUM, WATER YEAR OCTOBER 1991 TO SEPTEMBER 1992 INSTANTANEOUS OBSERVATIONS

Date	Water level	Date	Water level	Date	Water level	Date	Water level
Oct. 8 Nov. 8	455.31 455.35	Dec. 11 Jan. 9	43.88 42.55	Feb. 14 May 18	a55.67 43.54	July 17	41.34

WATER YEAR 1992 HIGHEST 41.34 JULY 17, 1992 LOWEST a55.67 FEB. 14, 1992



ST. JOHN, U.S. VIRGIN ISLANDS

182044064455200. Local number, 10.

LOCATION.--Lat 18°20'44", long 64°45'52", Hydrologic Unit 21020001, 2.00 mi northeast of Cruz Bay plaza, 0.46 mi southwest of Peter Peak, and 0.35 mi east of Susannaberg on Center Line road. Owner: U.S. Virgin Islands Government, Name: DPW-1.

AQUIFER . - - Louisenhoj Formation.

WELL CHARACTERISTICS.--Drilled public supply water-table well, diameter 6 in (0.15 m), cased 6 in (0.15 m). Sounded depth 60 ft (18.3 m).

INSTRUMENTATION. -- Monthly measurement with chalked steel tape by USGS personnel.

DATUM.--Elevation of land-surface datum about 610 ft (186 m) above mean sea level. Prior to this report, elevation used was 640 ft (195 m). Measuring point: Top of 6 in (0.15 m) casing, 2.00 ft (0.61 m) above land-surface datum.

REMARKS. -- Observation well. Water levels affected by pumping.


PERIOD OF RECORD. -- September 1982 to current year.

EXTREMES FOR PERIOD OF RECORD.--Highest water level measured, 13.54 ft (4.13 m) below land-surface datum, Dec. 19, 1989; lowest water level measured, 39.42 ft (12.01 m) below land-surface datum, Nov. 8, 1991.

WATER LEVEL, IN FEET BELOW LAND-SURFACE DATUM, WATER YEAR OCTOBER 1991 TO SEPTEMBER 1992 INSTANTANEOUS OBSERVATIONS

Date	Water level	Date	Water level	Date	Water level	Date	Water level
Oct. 8 Nov. 8	39.05 39.42	Dec. 11	38.30 37.81	Feb. 14	a38.50	July 17	37.07

WATER YEAR 1992 HIGHEST 37.07 JULY 17, 1992 LOWEST 39.42 DEC. 11, 1991



ST. JOHN, U.S. VIRGIN ISLANDS

181956064464500. Local number, 11.
LOCATION.--Lat 18°19'56", long 64°46'45", Hydrologic Unit 21020001, 1.05 mi southeast of Cruz Bay plaza, 0.25 mi southeast of Bethany Church, and 0.48 mi southeast of Margaret Hill. Owner: U.S. Virgin Islands Government,

Name: Guinea Gut Well.

AQUIFER.--Louisenhoj Formation (Donnelly, 1959).

WELL CHARACTERISTICS.--Drilled unused water-table well, diameter 6 in (0.15 m), cased 6 in (0.15 m). Depth 85 ft

(25.9 m).

INSTRUMENTATION.--Digital water level recorder--60-minute punch.

DATUM.--Rlevation of land-surface datum is about 280 ft (85.36 m) above mean sea level, from topographic map.

Measuring point: Bottom of 0.5 in (0.01 m) hole at 6 in (0.15 m) casing, 1.50 ft (0.46 m) above land-surface datum. Prior to June 28, 1983, top of 6 in (0.15 m) casing, 1.80 ft (0.55 m) above land-surface datum.


REMARKS.--Recording observation well.

PERIOD OF RECORD.--March 1982 to current year.

EXTREMES FOR PERIOD OF RECORD.--Highest water level recorded, 2.71 ft (0.79 m) below land-surface datum, Jan. 3, 1990; lowest water level recorded, 25.25 ft (7.70 m) below land-surface datum, Oct. 2, 1985.

		WATER LEV	EL, IN FE	ET BELOW	LAND-SURF	ACE DATUM	, WATER Y	RAR OCTOBER	1991	TO SEPTEMB	BR 1992	
		*		Inst	antaneous	OBSERVAT	ION AT 12	200				
DAY	ост	NOV	DBC	JAN	FEB	MAR	APR	MAY	JUN	JUL	AUG	SEP
1	23.29	23.53	13.04	17.61	15.40	19.32	22.29	24.13			20.64	23.00
2	23.29	23.57	13.21	17.73	15.53	19.44	22.38	22.85			20.75	23.05
3	23.27	23.61	13.34	17.88	15.66	19.55	22.46	18.58			20.82	23.08
4	23.25	23.65	13.44	18.02	15.80	19.67	22.54	17.48			20.89	23.12
5	23.24	23.69	13.58	18.13	15.91	19.80	22.61	17.94			20.98	23.16
6	23.22	23.73	13.72	17.33	16.04	19.92	22.70	18.19			21.04	23.19
7	23.21	23.74	13.87	13.88	16.11	20.04	22.78	18.42			21.11	23.22
8	23.21	23.70	14.04	12.65	16.31	20.16	22.84	18.60			21.18	23.24
9	23.21	23.69	14.18	12.69	16.49	20.27	22.91	18.79			21.25	23.27
10	23.20	19.82	14.34	12.77	16.66	20.34	22.99	18.90			21.32	23.31
11	23.19	16.88		12.88	16.81	20.43	23.07	19.02			21.41	23.34
12	23.18	16.61	14.86	13.00	16.98	20.55	23.14	19.12			21.48	23.38
13	23.18	17.00	15.06	13.06	17.14	20.66	23.20	19.22			21.56	23.43
14	23.18	17.23	15.22	13.15	17.25	20.77	23.28	19.31			21.63	23.49
15	23.21	17.41	15.39	13.26	17.40	20.86	23.36	19.43			21.69	23.55
16	23.23	17.57	15.55	13.38	17.55	20.96	23.44	19.53			21.76	23.59
17	23.25	17.71	15.69	13.51	17.70	21.06	23.51	19.56		19.08	21.84	23.62
18	23.27	17.86	15.85	13.62	17.85	21.13	23.58	19.59		19.14	21.92	23.66
19	23.27	17.99	15.98	13.76	18.01	21.19	23.65	19.66		19.22	21.99	23.68
20	23.27	18.10	16.11	13.89	18.14	21.25	23.70	19.74		19.31	22.08	23.70
21	23.28	18.20	16.27	14.01	18.27	21.33	23.73	19.79		19.39	22.15	23.72
22	23.29	18.28	16.37	14.16	18.39	21.42	23.77	19.85		19.50	22.22	23.75
23	23.31	18.37	16.49	14.32	18.50	21.50	23.81			19.63	22.31	23.77
24	23.32	17.06	16.64	14.49	18.59	21.58	23.84			19.74	22.39	23.81
25	23.33	12.99	16.77	14.60	18.72	21.66	23.87			19.86	22.47	23.85
26	23.36	11.86	16.90	14.71	18.84	21.75	23.94			19.97	22.56	23.89
27	23.38	12.03	17.02	14.85	18.96	21.84	23.97			20.07	22.63	23.92
28	23.40	12.31	17.10	14.96	19.08	21.94	24.01			20.18	22.71	23.95
29	23.43	12.59	17.21	15.08	19.18	22.03	24.05			20.29	22.80	23.97
30	23.46	12.84	17.35	15.21		22.11	24.11			20.40	22.88	23.98
31	23.49		17.49	15.31		22.22				20.53	22.95	
MEAN	23.28	18.45	15.40	14.64	17.35	20.86	23.32	19.44		19.75	21.79	23.52

WTR YR 1992 MEAN 19.83 HIGHEST 11.82 NOV. 26, 1991 LOWEST 24.14 MAY 1-2, 1992



ST. JOHN, U.S. VIRGIN ISLANDS

182110064430000. Local number, 12.

LOCATION.--Let 10°21'10°, long 64°43'80°, Hydrologic Unit 21020001, 0.20 mi morthwest of Goral Ray Church, 1.05 mi southeast of King Hill, and 8.50 mi west of road 10. Owner: U.S. Virgin Islands Water and Power Authority, Name: WAPA, Coral Bay, VIBO-2.

AQUIFER.--Fractured, volcanic rock, water-table aguifer.

WHILL CHARACTERISTICS.--Drilled observation water-table well, diameter 7 in (0.18 m), 0-70 ft (9-21.3 m), cased 4 in (8.18 m), 0-66 ft (9-20.1 m), screened 26-66 ft (7.26-20.1 m). Depth 66 ft (20.1 m).

IMSTRUMENTATION.--Digital water level recorder--68-minuto punch.

DATUM.--Elevation of land-surface datum is about 30 ft (9.14 m) above mean sea level, from topographic wap.

Measuring point: Top of shelter floor, 3.10 ft (0.94 m) above land-surface datum.

REMARKS.--Recording observation wall. Drilled on February 1991.


PERIOD OF RECORD.--May 1991 to current year.

PERIOD OF RECORD. --May 1991 to current year.

EXTREMES FOR PERIOD OF RECORD.--Highest water level recorded, 21.47 ft (6.54 h) below land-surface datum, June 5-8, 1992; lowest water level recorded, 24.11 ft (7.35 m) below land-surface datum, Apr. 18-19, 1992.

		WATER LE	vel, in pe		land- Surf Pantaneous				IR 1991 '	ro supremo	ER 1992	
DAY	OCT	NOA	DIRC	JAN	713	MAR	APR	MAY	JUN	JUL	AUG	52 7
1	23.53	23.49	23.28	23.72	23.43	23.83	24.07	23.93	21.95	22.73	23.66	23.90
2	23.50	23.47	23.22	23.74	23.44	23.85	24.03	23.58	21.89	22.70	23.60	23.98
3	23.47	23.48	23.23	23.76	23.46	23.86	24.02	23.09	21.80	22.81	23.68	24.00
4	23.45	23.49	23.21	23.78	23.46	23.87	24.03	22.86	21.58	22.85	23.69	24.03
5	23.43	23.51	23.23	23.70	23.46	23.88	24.03	22.73	21.49	22.89	23.71	24.87
6	23.41	23.54	23.25	23.58	23.48	23.88	24.04	22.65	21.47	22.92	23.70	24.08
7	23.40	23.58	23.28	23.37	23.47	23.89	24.84	22.60	21.47	22.97	23.70	24.07
	23.39	23.46	23.30	23.29	23.47	23.90	24.04	22.56	21.48	23.00	23.70	24.05
•	23.41	23.41	23.31	23.24	23.48	23.91	24.04	22.55	21.52	23.04	23.70	24.04
10	23.39	23.35	23.33	23.21	23.48	23.91	24.05	22.55	21.57	23.88	23.71	23.99
11	23.37	23.31	23.35	23.19	23.49	23.91	24.87	22.55	21.64	23.12	23.73	23.96
12	23.36	23.28	23.40	23.19	23.51	23.92	24.07	22.56	21.71	23.16	23.73	23.95
13	23.36	23.25	23.42	23.17	23.52	23.94	24.08	22.50	21.70	23.19	23.75	23.95
14	23.36	23.22	23.45	23.17	23.53	23.95	24.00	22.62	21.04	23.23	23.76	23.96
15	23.36	23.20	23.47	23.16	23.53	23.95	24.09	22.65	21.90	23.27	23.77	23.97
16	23.35	23.19	23.50	23.16	23.54	23.97	24.09	22.71	21.96	23.32	23.79	23.97
17	23.38	23.19	23.50	23.10	23.56	23.98	24.10	22.78	22.02	23.32	23.01	23.97
10	23.40	23.19	23.51	23.19	23.50	23.96	24.10	22.74	22.06	23.32	23.03	23.94
19	23.41	23.28	23.52	23.21	23.60	23.94	24.10	22.76	22.12	23.34	23.85	23.92
20	23.40	23.21	23.53	23.22	23.61	23.94	24.06	22.80	22.19	23.36	23.86	23.89
21	23.41	23.23	23.56	23.23	23.64	23.95	24.03	22.02	22.23	23.30	23.80	23.89
22	23.43	23.23	23.59	23.25	23.67	23.96	24.02	22.84	22.20	23.42	23.89	23.89
23	23.43	21.25	23.61	23.27	23.70	23.96	24.00	22.86	22.32	23.44	23.91	23.08
24	23.44	23.23	23.63	23.28	23.71	23.97	24.00	22.64	22.30	23.46	23.92	23.86
25	23.45	23.21	23.64	23.29	23.73	23.90	24.01	22.07	22.43	23.49	23.93	23.83
26	22.47	23.19	23.66	23.30	23.75	23.99	24.03	21.87	22.50	23.51	23.94	23.91
27	23.40	23.19	23.66	23.32	23.77	24.01	24.04	21.79	22.53	23.54	23.94	23.70
28	23.50	23.17	23.66	23.35	23.79	24.82	24.06	21.75	22.58	23.56	23.95	23.76
29	23.51	23.17	23.60	23.37	23.81	24.03	24.80	21.75	22.64	23.50	23.97	23.75
30	23.51	23.10	23.68	23.39		24.05	24.05	21.77	22.69	23.62	23.97	23.74
31	23.51		23.78	23.41		24.06		21.79		23.64	23.99	
MEAN	23.43	23.30	23.46	23.35	23.57	23.94	24.05	22.57	22.00	23.24	23.81	23.93

WTR YR 1992 MEAN 23.39 HIGHEST 21.47 JUNE 5-9, 1992 LOWEST 24.11 APR. 18-19, 1992



ST. JOHN, U.S. VIRGIN ISLANDS

181950064422300. Local number, 13.

LOCATION.--Lat 18°19'50°, long 64°42'23°, Hydrologic Unit 21020001, 1.47 mi southeast of Coral Bay Church, 0.68 mi northeast of Minna Hill, and 0.10 mi west of Hwy 107 at Calabash Boom. Owner: U.S. Virgin Islands Water and Power Authority, Hame: WAPA, Calabash Boom, VIBO-3.

AUGIFER.--Fractured, volcanic rock, water-table aquifer.

WELL CHARACTERISTICS.--Drilled observation water-table well, diameter 7 in (0.18 m), 0-110 ft (8-33.5 m), cased 4 in (0.10 m), 0-10 ft (0-33.5 m), servened 50-110 ft (15.2-33.5 m). Hepth 110 ft (33.5 m).

INSTRUMENTATION.--Digital water level recorder--60-minute punch.

DATUM.--Elevation of land-surface datum is about 55 ft (16.0 m) above mean sea level, from topographic map.

Measuring point: Top of shelter floor, 2.80 ft (0.85 m) above land-surface datum.


REMARKS.--Recording Observation well. Dyilled on Pebruary 1991.

PERIOD OF RECORD.--May 1991 to current year.

EXTREMES FOR PERIOD OF RECORD.--Highest water level 52.84 ft (15.9 m) below land-surface datum, Dec. 3-5, 1991; lowest water level recorded, 52.05 ft (16.1 m) below land-surface datum, Aug. 27-20, 1992.

		WATER	LEVEL, IN	PRET BELOW	Land-Suri Tantaneous	ACE DATOR	I, WATEN Y	THE OCTOR	ER 1991 T		ER 1992	
DAY	OCT	300	W DE		723	MAR	¥2B.	MAY	JUN6	JUL	AUG	SE?
DAI	· ·	-				-	-,					
1	52.21	52.1	4 52.0	5 52.33	52.33	52.53	52.64	52.64	52.58	52.49	52.76	52.01
1 2	52.19	52.1			52.34	52.54	52.64	52.64	52.56	52.49	52.76	52.81
3	52.18	52.1	4 52.0		52.34	52.54	52.64	52.62	52.56	52.49	52.76	52.81
4	52.17	52.1	14 52.0		52.35	52.54	52.64	52.62	52.55	52.50	52.76	52.01
5	52.15	52.1	4 52.0	5 52.36	52.35	52.54	52.64	52.61	52.53	52.50	52.76	52.80
6	52.13	52.1	52.0	5 52.36	52.35	52.54	52.64	52.61	52.51	52.51	52.77	52.79
ž	52.12	52.1			52.35	52.54	52.64	52.61	52.49	52.52	52.79	52.79
ė	52.12	52.3			52.35	52.54	52.64	52.61	52.47	52.53	52.79	52.77
j	52.14	52.1			52.35	52.54	52.64	52,61	52.45	52.56	52.79	52.75
10	52.13	52.1			52.35	52.54	52.65	52.61	52.44	52.58	52.79	52.75
11	52.13	52.1	14 52.0	8 52.31	52.36	52.54	52.66	52.61	52.44	52.59	52.81	52.74
12	52.13	52.1		0 52.31	52.30	52.54	52.67	52.61	52.43	52.61	52.81	52.71
13	52.13	52.1			52.39	52.54	52.68	52.61	52.43	52.62	52.81	52.70
14	52.13	52.1			52.39	52.55	52.68	52.61	52 -43	52.63	52.81	52.78
15	52.13	52.0			52.40	52.56	52.68	52.61	52.42	52.65	52.81	52.69
16	52.13	52.0	52.1	4 52.27	52.42	52.56	52.69	52.60	52.42	52,66	52.81	52.69
17	52.12	52.0			52.42	52.56	52.69	52.60	52.42	52,66	52.01	52.69
18	52.12	52.0			52.43	52.58	52.69	52.60	52.42	52.66	52.82	52.69
19	52.12	52.0			52.43	52.58	52.69	52.60	52.42	52.66	52.02	52.69
20	52,13	52.0			52.43	52.59	52.69	52.60	52.42	52.66	52.82	52.67
21	52.13	52.0			52.45	52.59	52.69	52.60	52.42	52.67	52.82	52.66
22	52.12	52.0			52.45	52.59	52.69	52.61	52.42	52.68	52.83	52.65
23	52.12	52.0			52.46	52.59	52.69	52.62	52.42	52.70	52.83	52.64
24	52.11	52.0			52.47	52.59	52.69	52.63	52.42	52.70	52.83	52.64 52.63
25	52.11	52.0	06 52.2	4 52.27	52.40	52.59	52.69	52.63	52.43	52.71	52.84	
26	52.11	52.0	06 58.2	5 52.28	52.50	52.59	52.69	52.62	52.44	52.72	52.84	52.63
27	52.11	52.0		6 52.29	52.51	52.60	52.68	52.62	52.45	52.72	52.05	52.63
28	52.12	52.			52.52	52.60	52.67	52.60	52.46	52.74	52.85	52.63
29	52.12	52.0			52.52	52.61	52.65	52.59	52.47	52.75	52.83	52.63
30	52.12	52.0	06 \$2,2	52.32		52.62	52,65	52.59	52.48	52.76	52.83	52.63
31	52.14		\$3,3	\$ 52.33		52.63		52.59		52.76	52.81	
MEAN	52.13	52.	10 52.1	5 52.30	52.41	52.57	52.67	52.61	52.46	52.63	52.81	52.71

WTR YR 1992 MEAN 53.46 HIGHEST 52.04 PMC. 3-5, 1991 LOWEST 52.05 AUG. 27-28, 1992



WATER YEAR

ST. JOHN, U.S. VIRGIN ISLANDS

182048064430400. Local number, 14.

LOCATION.--Lat 1820'48", long 64043'04", Hydrologic Unit 21020001, 0.27 mi southwest of Coral Bay Church, 1.05 mi southeast of King Hill, and 0.08 mi west of Hwy 107 in Carolina area. Owner: U.S. Virgin Islands Water and Power Authority, Name: WAPA, Coral Bay, VIEO-4.

AQUIFER.--Fractured, volcanic rock, water-table aquifer.

AQUIFER.--Fractured, volcanic rock, water-table aquifer.
WELL CHARACTERISTICS.--Drilled observation water-table well, diameter 7 in (0.18 m), 0-50 ft (0-15.2 m), cased 6 in (0.15 m), 0-50 ft (0-15.2 m), screened 20-50 ft (6.09-15.2 m). Depth 50 ft (15.2 m).

INSTRUMENTATION.--Digital water level recorder--60-minute punch.

DATUM.--Elevation of land-surface datum is about 13 ft (3.96 m) above mean sea level, from topographic map.

Measuring point: Top of shelter floor, 3.10 ft (0.94 m) above land-surface datum.

REMARKS.--Recording observation well. Drilled on February 1991. Water levels affected by nearly pumping well.

PERIOD OF RECORD.--May 1991 to current year.

EXTREMES FOR PERIOD OF RECORD.--Highest water level recorded, 9.95 ft (3.03 m) below land-surface datum, June 5, 1992; lowest water level recorded, 12.06 ft (3.68 m) below land-surface datum, Sept. 4, 1992

		WATER LEV	RL, IN FR	ET BELOW	LAND-SURF	ACE DATUM	, WATER Y	TRAR OCTOB	BR 1991 T	O SEPTEMB	BR 1992	
				inst	antaneous	OBSERVAT	ION AT 12	200				
DAY	OCT	NOV	DEC	JAN	PEB	MAR	APR	MAY	JUN	JOL	λŪG	SEP
1	10.60	10.49	10.47	10.89	10.82	11.04	11.04	10.86	10.29	10.55	10.95	10.96
2	10.58	10.50	10.48	10.89	10.79	11.04	11.03	10.48	10.19	10.55	10.92	11.75
3	10.50	10.50	10.44	10.88	10.77	11.01	11.04	10.44	10.10	10.53	10.95	11.94
4	10.59	10.50	10.46	10.86	10.76	11.03	11.02	10.44	10.06	10.55	10.96	12.05
5	10.54	10.53	10.47	10.84	10.77	11.04	11.04	10.42	10.04	10.56	10.93	11.27
•	10.54	10.55	20.47	20.00	20							
6	10.51	10.50	10.48	10.53	10.79	11.03	11.05	10.40	10.05	10.60	10.95	11.07
7	10.51	10.42	10.52	10.53	10.75	11.05	11.05	10.41	10.07	10.65	10.97	11.00
8	10.46	10.37	10.53	10.54	10.77	11.04	11.02	10.41	10.14	10.69	10.98	10.97
و	10.45	10.36	10.56	10.57	10.82	11.03	11.02	10.43	10.16	10.73	10.98	10.89
10	10.44	10.37	10.58	10.58	10.81	11.00	11.03	10.43	10.19	10.77	10.97	10.87
											40.00	10.83
11	10.47	10.38	10.61	10.60	10.85	10.99	11.01	10.45	10.21	10.78	10.96	10.84
12	10.51	10.35	10.68	10.61	10.80	11.00	11.06	10.47	10.23	10.80	10.99	
13	10.54	10.33	10.69	10.59	10.81	11.00	11.10	10.47	10.26	10.82	10.96	10.84
14	10.56	10.34	10.74	10.60	10.80	11.00	11.13	10.45	10.28	10.83	10.95	10.84
15	10.57	10.38	10.73	10.61	10.79	11.04	11.12	10.48	10.29	10.81	10.98	10.86
					40.70	** **	11.12	10.56	10.28	10.80	10.95	10.88
16	10.59	10.40	10.69	10.63	10.78	11.04	11.12	10.52	10.29	10.72	10.98	10.82
17	10.63	10.38	10.69	10.63	10.83	11.05		10.52	10.29	10.74	11.02	10.82
18	10.63	10.37	10.69	10.62	10.87	10.99	11.11 10.99	10.55	10.23	10.75	11.03	10.85
19	10.62	10.38	10.68	10.62	10.90	11.02		10.55	10.31	10.80	11.06	10.82
20	10.58	10.39	10.71	10.65	10.94	11.06	11.00	10.54	10.20	10.00	11.00	20.02
21	10.56	10.43	10.74	10.67	10.98	11.06	10.99	10.56	10.33	10.83	11.08	10.84
22	10.50	10.42	10.80	10.71	10.99	11.07	10.97	10.59	10.36	10.86	11.10	10.85
23	10.47	10.42	10.81	10.74	11.02	11.00	11.01	10.58	10.41	10.89	11.09	10.83
24	10.47	10.36	10.85	10.75	11.03	11.06	11.07	10.36	10.42	10.90	11.11	10.75
25	10.47	10.41	10.85	10.76	11.04	11.05	11.05	10.26	10.45	10.94	11.08	10.71
23	10.47	20.41	10.03	10.70	11.00							
26	10.48	10.42	10.83	10.75	11.05	11.05	11.01	10.25	10.48	10.98	11.03	10.65
27	10.52	10.44	10.83	10.81	11.03	11.03	11.04	10.27	10.51	10.97	10.99	10.63
28	10.53	10.45	10.87	10.83	11.04	11.07	11.08	10.28	10.54	11.00	10.98	10.64
29	10.53	10.46	10.85	10.84	11.06	11.08	11.08	10.28	10.55	10.97	10.95	10.67
30	10.54	10.47	10.84	10.85		11.11	10.88	10.30	10.57	11.55	10.95	10.72
31	10.52		10.88	10.83		11.10		10.31		10.96	10.93	

WTR YR 1992 MEAN 10.73 HIGHEST 9.95 JUNE 5, 1992 LOWEST 12.06 SEPT. 4, 1992

10.88


10.70

10.68

10.53

MEAN

10.42



11.04

10.45

10.29

10.95

10.99

10.80

Page	Page
A	
Access to WATSTORE data	Blanca at El Jagual, Quebrada
Acre-foot, definition of	Blanco at La Torre, Río
Adenosine triphosphate, definition of	Blanco basin, Río, gaging station
Adjuntas, Lago Garzas No. 1 near	records in
dam near	Blasina near Carolina, Quebrada 208,209
Adjuntas, Río Grande de Arecibo near 60,61	Blue-green algae, definition of
Adjuntas, Río Guilarte near	Bonne Resolution Gut at Bonne
Agua at Playa de Ponce, Quebrada del	Resolution, St. Thomas, VI
Aguada, Río Culebra near	Borinquen, Río Turabo above
Aguada, Río Culebrinas near	Bottom material, definition of
Aguada, Río Ingenio near	Bucaná at Highway 14 bridge near
Aguas Buenas, Río Caguitas near	Ponce, Río
Aguas Buenas, Río de Bayamón near	at Ponce
Aguas Verdes basin, Quebrada,	Bucaná basin, Río, gaging station
ground-water records in	records in
Algae growth potential, definition of	water-quality records in
water-quality partial-record	Bucarabones near Las Marías, Río
stations in Puerto Rico	Ducatabolics iicai Las Maitas, No
Annual 7-day minimum, definition of	C
Añasco Arriba, Río Grande de Añasco at	· ·
Añasco, Río Dagüey near	Cabo Rojo, Río Viejo near
Añasco, Río Grande de Añasco near	Caguas, Lago Loíza No. 4 near mouth
Aquifer, definition of	near
Arecibo, Río Grande de Arecibo above 70,71	Caguas, Río Bairoa near
Arenas at Las Marías, Río	Caguas, Río Caguitas at Highway 30 at 290,291
Artesian, definition of	Caguas, Río Caguitas at Villa Blanca at 278-289
Artificial substrate, definition of	Caguas, Río Grande de Loíza at
Ash mass, definition of	Caguitas at Highway 30 at Caguas, Río
Ausubo near Ponce, Quebrada	at Villa Blanca at Caguas
n	near Aguas Buenas
В	Caín near San Germán, Río
Bacteria, definition of	Campo Rico, Río Canóvanas near
Bahía de San Juan No. 5 at San Juan	Camuy basin, Río, gaging station
Bairoa at Bairoa, Río	records in
near Caguas	Camuy near Bayaney, Río
Balboa, Río Yagüez at	at Tres Pueblos Sinkhole
Baños de Coamo, Río Coamo at	near Hatillo
Bauta near Orocovis, Río96	Canal Principal de Diversiones at
Bayagán near Ponce, Río	Lago de Guajataca
Bayamón at Flood Channel at Bayamón,	Canóvanas near Campo Rico, Río 340,341
Río de	Cañas at Magueyes, Río 460
near Aguas Buenas	at Río Cañas
near Bayamón	at Río Cañas Abajo
Bayamón basin, Río de, gaging station	at Río Cañas Arriba
records in	downstream from Las Américas Ave
water-quality records in	near Juana Díaz
Bayamón below Lago Cidra, Río de	near Santa Isabel
near Bayamón 180 Bayamón, Río Guaynabo near 181,182	Cañas basin, Río, low-flow partial- record stations in
Bayaney, Río Camuy near	Caonillas above Lago Caonillas near
Bed material, definition of	Jayuya, Río
Bed load, definition of	Caonillas, Lago Caonillas at
Bed load discharge, definition of	Carolina, Quebrada Blasina near
Bethlehem Gut at Hwy 66 at Fairplains,	Carolina, Río Grande de Loíza at
St. Croix, VI	Casei near Mayagüez, Río
Biochemical oxygen demand, definition	Castañer, Lago Guayo near
of	Cataño, Río Hondo at Flood Channel
Biomass, definition of	near 164,165

Page	Page
Cayaguas at Cerro Gordo, Río	Color unit, definition of
Cayey, Lago Carite No. 1 near dam	Comerío, Río de La Plata at
near	Comerío, Río de la Plata near
Cayey, Lago Carite No. 3 on Río de	Contents, definition of
la Plata near	Control, definition of
Ceiba, Río Tallaboa near Quebrada	Control structure, definition of
Cells/volume, definition of	Cooperation
Central Cambalache, Río Grande de	Corozal, Río Cibuco below
Arecibo at	Cruces near Sabana Grande, Río
Central Guamaní, Río Seco near	Cruz Bay Gut at Cruz Bay, St. John, VI
Central Rufina, Río Guayanilla at	Cubic foot per second, definition of
Central Rufina, Río Guayanilla near	Cubic foot per second-day, definition of
Cerrillos above Lago Cerrillos near	Cubic feet per second per square mile,
Ponce, Río	definition of
near Ponce	Culebra basin, Río, low-flow partial-
upstream from Lago Cerrillos	record stations in
Cerro Gordo, Quebrada Cerro Gordo	
near	Culebra, Drainage Canal at Culebra Airport
Cerro Gordo, Río Cayaguas at	Culebra near Aguada, Río
Charico Hondo, Río Tanamá at	Culebra, Quebrada Resaca near Monte
Chemical oxygen demand, definition of	Resaca
Chico at Providencia, Río,	Culebrinas at Highway 404 near Moca,
Chico basin, Río, water-quality	Río
records in	near Aguada
Chiquito at Portugués, Río	near San Sebastián
near Ponce	Culebrinas basin, Río, gaging
Chlorophyll, definition of	station records in
Ciales, Río Cialitos at Highway 649	ground-water records in
at	water-quality records in
Ciales, Río Grande de Manatí at97	Cupeyes near San Germán, Río
Ciales, Río Grande de Manatí at	Cuyón at La Guava, Río
Highway 149 at	near Coamo
Cialitos at Highway 649 at Ciales,	_
Río 100,101	D
Cibuco at Vega Baja, Río	- · · · · · · · · · · · · · · · · · · ·
below Corozal	Dagüey near Affasco, Río
Cibuco basin, Río, gaging-station	Damsite, Lago El Guineo at
records in	Damsite, Lago Loíza at
ground-water records in	Damsite, Lago La Plata at
water-quality records in	Damsite, Lago Lucchetti at
Cidra, Lago de Cidra at Damsite near	Damsite, Lago Matrullas at
Cimarrona near Jobos, Quebrada	Definition of terms 30-39
Coamo basin, Río, low-flow partial-	Descalabrado basin, Río, gaging
record stations in	station records in
water-quality records in	low-flow partial-record stations in
Coamo at Baños de Coamo, Río	Descalabrado at Las Ollas, Río
at Cosmo	near Los Llanos
near Coamo	near Sanja Blanca
near Pasto	near Santa Isabel
near Santa Isabel	Diatoms, definition of
Coamo, Quebrada Monteria near	Discharge at low-flow partial-record
Coamo, Río Cuyón near	stations
Coamo, Río de la Mina at	Discharge, definition of
Coamo, Río de la Mina near	Dissolved, definition of
Coamo, Río del Pasto near	Dissolved-solids concentration, definition of
Cofresi Tributary near Isabel II,	Diversity index, definition of
Quebrada (Vieques)	Drainage area, definition of
Collores, Quebrada Indalecia at	Drainage basin, definition of
Collores, Río Guayo near	Drainage Canal at Culebra Airport,
Collores, Río Guayo upstream from	Culebra
Diversion at	Dry mass, definition of

Page	Page
Duey at Duey, Río	Grande de Loíza at Caguas, Río
E	at Quebrada Arenas
El Espino, Río Grande de Añasco at	Grande de Loíza basin, Río, gaging
El Espino, Río Humata near	station records in
El Mangó, Río Gurabo below	ground-water records in
El Señorial, Río Piedras at	water-quality partial-record
El Verde, Quebrada Sonadora near	stations, analyses of samples
El Verde, Quebrada Toronja at	collected at
El Verde, Río Grande near	water-quality records in
Espíritu Santo basin, Río, gaging	Grande de Manatí at Ciales, Río
station records in	at Highway 2 near Manatí
water-quality records in	at Highway 149 at Ciales
Espíritu Santo near Río Grande, Río 348-350	near Morovis 91-93
Explanation of records	Grande de Manatí basin, Río, gaging
	station records in 86-102
F	ground-water records in
	water-quality records in 89-105
Fajardo below Fajardo, Río	Grande de Patillas near Patillas, Río 378,379
near Fajardo	Grande de Patillas basin, Río,
Fajardo basin, Río, gaging station	water-quality records in
records in	Grande near Rincon, Río
water-quality records in,	near El Verde
Fecal coliform bacteria, definition of	near Sabana Grande
Fecal streptococcal bacteria,	Grande near Lago Lucchetti Damsite,
definition of	Quebrada
Flores near Sabana Grande, Río	Grande upstream from Lago Loco,
Florida, Río Grande de Arecibo below	Quebrada
Lago Dos Bocas near	Graphs:
	Ground-water levels at selected
G	wells in Puerto Rico and the
	U.S. Virgin Islands
Gage-height, definition of	Monthly-mean discharge of selected
Gaging station, definition of	streams in Puerto Rico
Grande basin, Río, low-flow partial-	Green algae, definition of
record stations in	Grid showing system for numbering
Grande de Añasco basin, Río, gaging	wells and miscellaneous sites
station records in	(latitude and longitude)
low-flow partial-record stations in	Ground-water level, records of
water-quality records in	Ground-water quality, records of 28,29
Grande de Añasco at Añasco Arriba, Río	Ground-water records for Puerto Rico
at El Espino 466	Ground-water records for U.S. Virgin
near Añasco	Islands 555-592
near Lares	Ground-water station, definition of
near Las Marías	Ground-water stations in Puerto Rico,
near San Sebastián	map showing location of
Grande de Arecibo at Central	Ground-water stations in U.S. Virgin
Cambalache, Río	Islands, map showing location of
above Arecibo	Guaba near Las Marías, Río
below Lago Dos Bocas near Florida 68,69	near Maricao
near Adjuntas 60,61	Guadiana at Guadiana, Río
near Utuado	near Naranjito
Grande de Arecibo basin, Río, gaging	Guajataca above mouth near
station records in	Quebradillas, Río 51,52
ground-water records in	at Lares
water-quality partial-record	Guajataca basin, Río, gaging station
stations, analyses of samples	records in
collected at	ground-water records in
water-quality records in	

Page	Page
water-quality partial-record stations,	Hormigueros, Río Rosario at Hwy 2
analyses of samples collected at	near 464
water-quality records in	Hormigueros, Río Rosario near 417-425,464
Guanábana near Juana Díaz, Quebrada	Humacao at Highway 3 at Humacao, Río 367,368
Guanajibo at Highway 119 at San Germán,	at Las Piedras
Río 414	Humacao basin, Río, gaging station
at La Pica	records in
below San Germán	water-quality records in
near Hormigueros	Humata near El Espino, Río
near San Germán	Hydrologic Bench-Mark Network,
Guanajibo basin, Río, gaging station	definition of
records in	Hydrologic conditions, summary of
ground-water records in	Hydrologic unit, definition of
low-flow partial-record stations	Try alonogic diat, definition of the triangle of triangle of the triangle of the triangle of trian
in	I
water-quality records in	•
Guanajibo, Quebrada Maga near	Icacos near Naguabo, Río
Guanajibo, Río Hondo near	Identification numbers, stations
Guánica, Rio Loco at	Inabón at Real Abajo, Río
Guayanés above mouth at Playa de	Inabón at Real Anón, Río
Guayanés, Río	Inabón basin, Río, gaging station
at Yabucoa	records in
near Peñuelas	low-flow partial-record stations in
Guayanés basin, Río, water-quality	•
records in	Indalecia at Collores, Quebrada
Guayanilla at Central Rufina, Río	Indiera Alta, Río Prieto at
at Pasto	Ingenio at Jagüey, Río
··-	near Aguada
near Central Rufina	Ingenio basin, Río, low-flow partial-
near Guayanilla	record stations in
Guayanilla basin, Río, gaging	Instantaneous discharge, definition of
station records in	Introduction
low-flow partial-record stations in	T
water-quality records in	J
Guaynabo near Bayamón, Río	Income at Image Dian Big
Guayo at Guayo, Río 465 near Collores 459	Jacaguas at Juana Díaz, Río
	at Villaba
upstream from Diversion at Collores	Jacaguas basin, Río, gaging station records in
Guilarte near Adjuntas, Río	low-flow partial-record stations in
Guinea Gut at Bethany, St. John, VI	•
Gurabo at Gurabo, Río	water-quality records in
below El Mangó	Jagual, Quebrada Blanca at El
near Gurabo	Jagüey, Río Ingenio at
Gurabo, Quebrada Mamey near	Jajome at Jajome, Río
Gut 4.5 at Cane Valley, St. Croix, VI	Jayuya, Río Caonillas above Lago
Gut 10 near Altona, St. Croix, VI	Caonillas near
77	Jayuya, Río Saliente at Coabey near
Н	Jauca, Río Jueyes near
TI I I I C C C	Jobos, Quebrada Cimarrona near
Hardness, definition of	Jobos, Quebrada Melania near
Hatillo, Río Camuy near	Jolly Hill Gut at Jolly Hill,
Hato Rey, Río Piedras at	St. Croix, VI
Hoconuco (Duey) near San Germán, Río	Juana Díaz, Quebrada Guanábana near
Hoconuco near San Germán, Río	Juana Díaz, Río Cañas near
Hondo at Flood Channel near Cataño, Río	Juana Díaz, Río Jacaguas at
near Guanajibo	Jueyes at Río Jueyes, Río
Hondo basin, Río, low-flow partial-	near Jauca
record stations in	Jueyes basin, Río, low-flow partial-
water-quality records in 164,165	record stations in
Hormigueros, Río Guanajibo near	Juncos, Río Valenciano near

Page Page L La Plata basin, Río de, gaging No. 3 on Río de la Plata near Cayey 470-472 water-quality partial-record Lago Cerrillos, Río Cerrillos stations, analyses of samples Lago Cerrillos, Río San Patricio Lares, Río Grande de Añasco near 433,434,465 Lago de Cidra at Damsite near Cidra 166 Lago de Guajataca, Canal Principal Las Américas Ave., Río Cañas No. 1 near dam near Quebradillas 473-479 No. 3 near mouth near Quebradillas 470-472 Lago Dos Bocas No. 1 near dam near No. 3 at west branch near Utuado 470-472 Las Marías, Río Grande de Añasco near 466 Lago Garzas No. 1 near dam near Lago La Plata No. 3 near dam near Levels for Puerto Rico, ground water 481-535 No. 5 near mouth near Naranjito 470-472 Levels for U.S. Virgin Islands, Lago Loco, Quebrada Grande Loco basin, Río, low-flow Lago Lucchetti Damsite, Quebrada Lago Lucchetti Damsite, Río Naranjo Low-flow partial-record stations, Lago Lucchetti Damsite, Río Yauco Low-flow partial-record in Southwest Puerto Rico, map Lago Matrullas at Damsite95 Lago Toa Vaca, Río Toa Vaca M Laguna Tortuguero basin, water Macaná basin, Río, low-flow Laguna Tortuguero outlet near Maga basin, Quebrada, low-flow La Mina near Esperanza, Quebrada (Vieques) 451,452 Maga near Hormigueros, Quebrada 464 Magueyes, Río Cañas at 460 La Plata at Provecto La Plata, Río de 117-119 Majada basin, Río, Mameyes basin, Río, gaging station

rage	
Mameyes near Sabana, Río	Mayagüecilla at Las Marías, Río
Manatí, Río Grande de Manatí at	Mayagüez, Quebrada Sábalos near
Highway 2 near	Mayagüez, Río Casei near
Maps:	Mayagüez, Río Yagüez near
Location of surface-water stations	Mean concentration, definition of
in Puerto Rico	Mean discharge, definition of
Location of ground-water stations	Measuring point, definition of
in Puerto Rico	Melanía basin, low-flow
Location of ground-water stations	partial-record stations in
in the U.S. Virgin Islands	Melanía near Jobos, Quebrada
Location of low-flow partial-record	Metamorphic stage, definition of
stations in Southwest Puerto Rico	
Location of maximum concentration	Methylene blue active substances, definition of
of fecal coliform bacteria at	Micrograms per gram, definition of
sample sites	Micrograms per liter, definition of
Location of maximum concentration	Milligrams of carbon per area or
of fecal streptococci bacteria	volume per unit time or
at sample sites	periphyton and macrophytes and
Location of surface-water stations	for phytoplankton, definition of
in the U.S. Virgin Islands	Milligrams of oxygen per area or
Location of surface-water stations in	volume per unit time for
Vieques and Culebra Islands	periphyton and macrophytes and
Location of water-quality stations	for phytoplankton, definition of
in Puerto Rico	Milligrams per liter, definition of
Río Camuy basin	Mina at Coamo, Río de la
Río Cibuco basin	near Coamo
Río Culebrinas basin	Moca, Río Culebrinas at Highway 404
Río Grande de Arecibo basin	near 444
Río Grande de Loíza basin	Monteria near Coamo, Quebrade
Río Grande de Manatí basin	Morovis, Río Grande de Manatí near 91-93
Río Guajataca basin	
Río Guanajibo basin	N
Río Herrera to the Río Antón Ruiz	
basins	
	Naguabo, Río Icacos near
Río Hondo to the Río Puerto	Naguabo, Río Icacos near
Río Hondo to the Río Puerto	Naranjito, Lago La Plata No. 3 near dam near
Río Hondo to the Río Puerto 163 Nuevo basins 163 Río Humacao to the Río Seco basins 365	Naranjito, Lago La Plata No. 3 near dam near
Río Hondo to the Río Puerto 163 Nuevo basins 163 Río Humacao to the Río Seco basins 365 Río Inabón to the Río Loco basins 395	Naranjito, Lago La Plata No. 3 near dam near
Río Hondo to the Río Puerto 163 Nuevo basins 163 Río Humacao to the Río Seco basins 365 Río Inabón to the Río Loco basins 395 Río de la Plata basin 115	Naranjito, Lago La Plata No. 3 near dam near
Río Hondo to the Río Puerto 163 Nuevo basins 163 Río Humacao to the Río Seco basins 365 Río Inabón to the Río Loco basins 395 Río de la Plata basin 115 Río Salinas to the Río Jacaguas basins 381	Naranjito, Lago La Plata No. 3 473-479 near dam near 473-479 Naranjito, Lago La Plata No. 5 470-472 near mouth near 470-472 Naranjito, Río Guadiana near 141,142 Naranjo near Lago Lucchetti Damsite, Río 462
Río Hondo to the Río Puerto 163 Nuevo basins 163 Río Humacao to the Río Seco basins 365 Río Inabón to the Río Loco basins 395 Río de la Plata basin 115 Río Salinas to the Río Jacaguas basins 381 Río Yagüez and the Río Grande de	Naranjito, Lago La Plata No. 3 473-479 near dam near 473-479 Naranjito, Lago La Plata No. 5 470-472 near mouth near 470-472 Naranjito, Río Guadiana near 141,142 Naranjo near Lago Lucchetti Damsite, Río 462 National Stream-Quality Accounting
Río Hondo to the Río Puerto 163 Nuevo basins 163 Río Humacao to the Río Seco basins 365 Río Inabón to the Río Loco basins 395 Río de la Plata basin 115 Río Salinas to the Río Jacaguas basins 381 Río Yagüez and the Río Grande de 429	Naranjito, Lago La Plata No. 3 473-479 near dam near 473-479 Naranjito, Lago La Plata No. 5 470-472 near mouth near 470-472 Naranjito, Río Guadiana near 141,142 Naranjo near Lago Lucchetti Damsite, Río 462 National Stream-Quality Accounting 34 Network, definition of 34
Río Hondo to the Río Puerto 163 Nuevo basins 163 Río Humacao to the Río Seco basins 365 Río Inabón to the Río Loco basins 395 Río de la Plata basin 115 Río Salinas to the Río Jacaguas basins 381 Río Yagüez and the Río Grande de 429 Maricao at Maricao, Río 464	Naranjito, Lago La Plata No. 3 473-479 near dam near 473-479 Naranjito, Lago La Plata No. 5 470-472 near mouth near 470-472 Naranjito, Río Guadiana near 141,142 Naranjo near Lago Lucchetti Damsite, Río 462 National Stream-Quality Accounting 34 Network, definition of 34 National Trends Network, definition of 34
Río Hondo to the Río Puerto Nuevo basins 163 Río Humacao to the Río Seco basins 365 Río Inabón to the Río Loco basins 395 Río de la Plata basin 115 Río Salinas to the Río Jacaguas basins 381 Río Yagüez and the Río Grande de 429 Maricao at Maricao, Río 464 Maricao, Río Guaba near 466	Naranjito, Lago La Plata No. 3 473-479 near dam near 473-479 Naranjito, Lago La Plata No. 5 470-472 near mouth near 470-472 Naranjito, Río Guadiana near 141,142 Naranjo near Lago Lucchetti Damsite, Río 462 National Stream-Quality Accounting 34 Network, definition of 34 National Trends Network, definition of 34 Natural substrate, definition of 37
Río Hondo to the Río Puerto Nuevo basins 163 Río Humacao to the Río Seco basins 365 Río Inabón to the Río Loco basins 395 Río de la Plata basin 115 Río Salinas to the Río Jacaguas basins 381 Río Yagüez and the Río Grande de 429 Maricao at Maricao, Río 464 Maricao, Río Guaba near 466 Maricao, Río Lajas near 465	Naranjito, Lago La Plata No. 3 473-479 near dam near 473-479 Naranjito, Lago La Plata No. 5 470-472 near mouth near 470-472 Naranjito, Río Guadiana near 141,142 Naranjo near Lago Lucchetti Damsite, Río 462 National Stream-Quality Accounting 34 Network, definition of 34 National Trends Network, definition of 34
Río Hondo to the Río Puerto Nuevo basins 163 Río Humacao to the Río Seco basins 365 Río Inabón to the Río Loco basins 395 Río de la Plata basin 115 Río Salinas to the Río Jacaguas basins 381 Río Yagüez and the Río Grande de 429 Añasco basins 429 Maricao at Maricao, Río 464 Maricao, Río Guaba near 466 Maricao, Río Lajas near 465 Marisol, Quebrada de Los Plátanos at 465	Naranjito, Lago La Plata No. 3 473-479 near dam near 470-472 Naranjito, Lago La Plata No. 5 470-472 near mouth near 141,142 Naranjito, Río Guadiana near 141,142 Naranjo near Lago Lucchetti Damsite, Río 462 National Stream-Quality Accounting 34 Network, definition of 34 National Trends Network, definition of 34 Natural substrate, definition of 37 Networks and programs, special 9
Río Hondo to the Río Puerto Nuevo basins 163 Río Humacao to the Río Seco basins 365 Río Inabón to the Río Loco basins 395 Río de la Plata basin 115 Río Salinas to the Río Jacaguas basins 381 Río Yagüez and the Río Grande de 429 Maricao at Maricao, Río 464 Maricao, Río Guaba near 466 Maricao, Río Lajas near 465 Marisol, Quebrada de Los Plátanos at 465 Matilde basin, Río, low-flow	Naranjito, Lago La Plata No. 3 473-479 near dam near 473-479 Naranjito, Lago La Plata No. 5 470-472 near mouth near 470-472 Naranjito, Río Guadiana near 141,142 Naranjo near Lago Lucchetti Damsite, Río 462 National Stream-Quality Accounting 34 Network, definition of 34 National Trends Network, definition of 34 Natural substrate, definition of 37
Río Hondo to the Río Puerto Nuevo basins 163 Río Humacao to the Río Seco basins 365 Río Inabón to the Río Loco basins 395 Río de la Plata basin 115 Río Salinas to the Río Jacaguas basins 381 Río Yagüez and the Río Grande de 429 Añasco basins 429 Maricao at Maricao, Río 464 Maricao, Río Guaba near 466 Maricao, Río Lajas near 465 Marisol, Quebrada de Los Plátanos at 465 Matilde basin, Río, low-flow 460,461	Naranjito, Lago La Plata No. 3 near dam near
Río Hondo to the Río Puerto Nuevo basins 163 Río Humacao to the Río Seco basins 365 Río Inabón to the Río Loco basins 395 Río de la Plata basin 115 Río Salinas to the Río Jacaguas basins 381 Río Yagüez and the Río Grande de 429 Añasco basins 429 Maricao at Maricao, Río 464 Maricao, Río Guaba near 466 Maricao, Río Lajas near 465 Marisol, Quebrada de Los Plátanos at 465 Matilde basin, Río, low-flow 460,461 Matilde at Ponce, Río 461	Naranjito, Lago La Plata No. 3 near dam near
Río Hondo to the Río Puerto Nuevo basins 163 Río Humacao to the Río Seco basins 365 Río Inabón to the Río Loco basins 395 Río de la Plata basin 115 Río Salinas to the Río Jacaguas basins 381 Río Yagüez and the Río Grande de 429 Añasco basins 429 Maricao at Maricao, Río 464 Maricao, Río Guaba near 465 Maricao, Río Lajas near 465 Marisol, Quebrada de Los Plátanos at 465 Matilde basin, Río, low-flow 460,461 Matilde at Ponce, Río 461 Maunabo at Lizas, Río 373	Naranjito, Lago La Plata No. 3 473-479 near dam near 470-472 Naranjito, Lago La Plata No. 5 470-472 near mouth near 470-472 Naranjito, Río Guadiana near 141,142 Naranjo near Lago Lucchetti Damsite, Río 462 National Stream-Quality Accounting 34 Network, definition of 34 National Trends Network, definition of 34 Natural substrate, definition of 37 Networks and programs, special 9 O Organic mass, definition of 31 Organism, definition of 34
Río Hondo to the Río Puerto Nuevo basins 163 Río Humacao to the Río Seco basins 365 Río Inabón to the Río Loco basins 395 Río de la Plata basin 115 Río Salinas to the Río Jacaguas basins 381 Río Yagüez and the Río Grande de 429 Añasco basins 429 Maricao at Maricao, Río 464 Maricao, Río Guaba near 465 Maricao, Río Lajas near 465 Marisol, Quebrada de Los Plátanos at 465 Matilde basin, Río, low-flow 461 Matilde at Ponce, Río 461 Maunabo at Lizas, Río 373 at Maunabo 374,375	Naranjito, Lago La Plata No. 3 473-479 near dam near 470-472 Naranjito, Lago La Plata No. 5 470-472 near mouth near 470-472 Naranjito, Río Guadiana near 141,142 Naranjo near Lago Lucchetti Damsite, Río 462 National Stream-Quality Accounting 34 Network, definition of 34 National Trends Network, definition of 34 Natural substrate, definition of 37 Networks and programs, special 9 O O Organic mass, definition of 31 Organism, definition of 34 Organism count/area, definition of 34
Río Hondo to the Río Puerto Nuevo basins 163 Río Humacao to the Río Seco basins 365 Río Inabón to the Río Loco basins 395 Río de la Plata basin 115 Río Salinas to the Río Jacaguas basins 381 Río Yagüez and the Río Grande de 429 Añasco basins 429 Maricao at Maricao, Río 464 Maricao, Río Guaba near 465 Maricao, Río Lajas near 465 Marisol, Quebrada de Los Plátanos at 465 Matilde basin, Río, low-flow 461 Matilde at Ponce, Río 461 Maunabo at Lizas, Río 373 at Maunabo 374,375 Maunabo basin, Río, gaging stations	Naranjito, Lago La Plata No. 3 near dam near
Río Hondo to the Río Puerto Nuevo basins 163 Río Humacao to the Río Seco basins 365 Río Inabón to the Río Loco basins 395 Río de la Plata basin 115 Río Salinas to the Río Jacaguas basins 381 Río Yagüez and the Río Grande de 429 Añasco basins 429 Maricao at Maricao, Río 464 Maricao, Río Guaba near 465 Maricao, Río Lajas near 465 Marisol, Quebrada de Los Plátanos at 465 Matilde basin, Río, low-flow partial-record stations in 460,461 Matilde at Ponce, Río 461 Maunabo at Lizas, Río 373 at Maunabo 374,375 Maunabo basin, Río, gaging stations 373	Naranjito, Lago La Plata No. 3 473-479 near dam near 470-472 Naranjito, Lago La Plata No. 5 470-472 near mouth near 470-472 Naranjito, Río Guadiana near 141,142 Naranjo near Lago Lucchetti Damsite, Río 462 National Stream-Quality Accounting 34 Network, definition of 34 National Trends Network, definition of 34 Natural substrate, definition of 37 Networks and programs, special 9 O O Organic mass, definition of 34 Organism count/area, definition of 34 Organism count/volume, definition of 34 Orocovis, Río Bauta near 96
Río Hondo to the Río Puerto Nuevo basins 163 Río Humacao to the Río Seco basins 365 Río Inabón to the Río Loco basins 395 Río de la Plata basin 115 Río Salinas to the Río Jacaguas basins 381 Río Yagüez and the Río Grande de 429 Añasco basins 429 Maricao at Maricao, Río 464 Maricao, Río Guaba near 465 Maricao, Río Lajas near 465 Marisol, Quebrada de Los Plátanos at 465 Matilde basin, Río, low-flow partial-record stations in 460,461 Matilde at Ponce, Río 461 Maunabo at Lizas, Río 373 at Maunabo 374,375 Maunabo basin, Río, gaging stations 374,375 water-quality records in 374,375	Naranjito, Lago La Plata No. 3 473-479 near dam near 470-472 Naranjito, Lago La Plata No. 5 470-472 near mouth near 470-472 Naranjito, Río Guadiana near 141,142 Naranjo near Lago Lucchetti Damsite, Río 462 National Stream-Quality Accounting 34 Network, definition of 34 National Trends Network, definition of 34 Natural substrate, definition of 37 Networks and programs, special 9 O O Organic mass, definition of 34 Organism count/area, definition of 34 Organism count/volume, definition of 34 Orocovis, Río Bauta near 96 Orocovis, Río Orocovis at 86-88
Río Hondo to the Río Puerto Nuevo basins 163 Río Humacao to the Río Seco basins 365 Río Inabón to the Río Loco basins 395 Río de la Plata basin 115 Río Salinas to the Río Jacaguas basins 381 Río Yagüez and the Río Grande de 429 Añasco basins 429 Maricao at Maricao, Río 464 Maricao, Río Guaba near 465 Maricao, Río Lajas near 465 Marisol, Quebrada de Los Plátanos at 465 Matilde basin, Río, low-flow partial-record stations in 460,461 Matilde at Ponce, Río 461 Maunabo at Lizas, Río 373 at Maunabo 374,375 Maunabo basin, Río, gaging stations 373 records in 373 water-quality records in 374,375 Maximum concentrations of fecal	Naranjito, Lago La Plata No. 3 473-479 near dam near 470-472 Naranjito, Lago La Plata No. 5 470-472 near mouth near 470-472 Naranjito, Río Guadiana near 141,142 Naranjo near Lago Lucchetti Damsite, Río 462 National Stream-Quality Accounting 34 Network, definition of 34 National Trends Network, definition of 34 Natural substrate, definition of 37 Networks and programs, special 9 O O Organic mass, definition of 34 Organism count/area, definition of 34 Organism count/volume, definition of 34 Orocovis, Río Bauta near 96
Río Hondo to the Río Puerto Nuevo basins 163 Río Humacao to the Río Seco basins 365 Río Inabón to the Río Loco basins 395 Río de la Plata basin 115 Río Salinas to the Río Jacaguas basins 381 Río Yagüez and the Río Grande de 464 Añasco basins 429 Maricao at Maricao, Río 464 Maricao, Río Guaba near 465 Maricao, Río Lajas near 465 Marisol, Quebrada de Los Plátanos at 465 Matilde basin, Río, low-flow partial-record stations in 460,461 Matilde at Ponce, Río 461 Maunabo at Lizas, Río 373 at Maunabo 374,375 Maunabo basin, Río, gaging stations records in 373 water-quality records in 374,375 Maximum concentrations of fecal coliform bacteria at sampled	Naranjito, Lago La Plata No. 3 473-479 near dam near 470-472 Naranjito, Lago La Plata No. 5 470-472 near mouth near 470-472 Naranjito, Río Guadiana near 141,142 Naranjo near Lago Lucchetti Damsite, Río 462 National Stream-Quality Accounting 34 Network, definition of 34 National Trends Network, definition of 34 Natural substrate, definition of 37 Networks and programs, special 9 O O Organic mass, definition of 34 Organism count/area, definition of 34 Organism count/volume, definition of 34 Orocovis, Río Bauta near 96 Orocovis, Río Orocovis at 86-88 Orocovis, Río Orocovis near 89,90
Río Hondo to the Río Puerto Nuevo basins 163 Río Humacao to the Río Seco basins 365 Río Inabón to the Río Loco basins 395 Río de la Plata basin 115 Río Salinas to the Río Jacaguas basins 381 Río Yagüez and the Río Grande de 464 Añasco basins 429 Maricao at Maricao, Río 464 Maricao, Río Guaba near 465 Maricao, Río Lajas near 465 Marisol, Quebrada de Los Plátanos at 465 Matilde basin, Río, low-flow partial-record stations in 460,461 Matilde at Ponce, Río 461 Maunabo at Lizas, Río 373 at Maunabo 374,375 Maunabo basin, Río, gaging stations records in 373 water-quality records in 374,375 Maximum concentrations of fecal coliform bacteria at sampled sites, map showing location of 10	Naranjito, Lago La Plata No. 3 473-479 near dam near 470-472 Naranjito, Lago La Plata No. 5 470-472 near mouth near 441,142 Naranjito, Río Guadiana near 141,142 Naranjo near Lago Lucchetti Damsite, Río 462 National Stream-Quality Accounting 34 Network, definition of 34 National Trends Network, definition of 34 Natural substrate, definition of 37 Networks and programs, special 9 O O Organic mass, definition of 34 Organism count/area, definition of 34 Organism count/volume, definition of 34 Orocovis, Río Bauta near 96 Orocovis, Río Orocovis at 86-88
Río Hondo to the Río Puerto Nuevo basins 163 Río Humacao to the Río Seco basins 365 Río Inabón to the Río Loco basins 395 Río de la Plata basin 115 Río Salinas to the Río Jacaguas basins 381 Río Yagüez and the Río Grande de 464 Añasco basins 429 Maricao at Maricao, Río 464 Maricao, Río Guaba near 466 Maricao, Río Lajas near 465 Marisol, Quebrada de Los Plátanos at 465 Matilde basin, Río, low-flow partial-record stations in 460,461 Matilde at Ponce, Río 461 Maunabo at Lizas, Río 373 at Maunabo 374,375 Maunabo basin, Río, gaging stations records in 373 water-quality records in 374,375 Maximum concentrations of fecal coliform bacteria at sampled sites, map showing location of 10 Maximum concentrations of fecal 10	Naranjito, Lago La Plata No. 3 near dam near
Río Hondo to the Río Puerto Nuevo basins 163 Río Humacao to the Río Seco basins 365 Río Inabón to the Río Loco basins 395 Río de la Plata basin 115 Río Salinas to the Río Jacaguas basins 381 Río Yagüez and the Río Grande de Añasco basins 429 Maricao at Maricao, Río 464 Maricao, Río Guaba near 466 Maricao, Río Guaba near 465 Marisol, Quebrada de Los Plátanos at 465 Matilde basin, Río, low-flow partial-record stations in 460,461 Matilde at Ponce, Río Maunabo at Lizas, Río 373 at Maunabo 374,375 Maunabo basin, Río, gaging stations records in 373 water-quality records in 373 mater-quality records in 374,375 Maximum concentrations of fecal coliform bacteria at sampled sites, map showing location of 10 Maximum concentrations of fecal streptococci bacteria at	Naranjito, Lago La Plata No. 3 near dam near
Río Hondo to the Río Puerto Nuevo basins 163 Río Humacao to the Río Seco basins 365 Río Inabón to the Río Loco basins 395 Río de la Plata basin 115 Río Salinas to the Río Jacaguas basins 381 Río Yagüez and the Río Grande de 464 Añasco basins 429 Maricao at Maricao, Río 464 Maricao, Río Guaba near 466 Maricao, Río Lajas near 465 Marisol, Quebrada de Los Plátanos at 465 Matilde basin, Río, low-flow partial-record stations in 460,461 Matilde at Ponce, Río 461 Maunabo at Lizas, Río 373 at Maunabo 374,375 Maunabo basin, Río, gaging stations records in 373 water-quality records in 374,375 Maximum concentrations of fecal coliform bacteria at sampled sites, map showing location of 10 Maximum concentrations of fecal 10	Naranjito, Lago La Plata No. 3 near dam near

Page	rag
Partial record station,	Portugués basin, Río, gaging
definition of	station records in
Partial-record stations in Puerto Rico,	low-flow partial-record
Discharge at	stations in
Partial-record stations in Southwest Puerto	water-quality records in
Rico, map showing location of low-flow	Portugués, Río Chiquito at
Partial record station in Puert	Prieto at Indiera Alta, Río
Rico, Water quality at	at Pezuela
Particle size, definition of	at Río Prieto
Particle-size classification,	Primary productivity, definition of
definition of	Programs, special networks and
Pastillo near Ponce, Río	Providencia, Río Chico at
Pastillo, Río Pastillo at	Proyecto La Plata, Río de La Plata at
Pasto near Coanto, Río del	Publications on techniques of
Pasto, Río Coamó near	water-resources investigations
Pasto, Río Gustýánilla at	Puerto Nuevo basin, Río, gaging station records in
Patillas, Río Grande de Patillas near	
Pedro García; Río Toa Vaca at	water-quality records in
Peñuelas, Río Guayanés near	
Peñuelas, Río Macaná near	Q
Peñuelas, Río Taliaboa at	On the of many mands for Breats
Percent composition, definition of	Quality of water records for Puerto Rico, surface- and
Perchas, Quebrada Las Cañas at	- · · · · · · · · · · · · · · · · · · ·
Periphyton, definition of	Quebrada Aguas Verdes basiñ, ground-water records in
	Quebrada Arenas, Río Grande de
Pezuela, Río Prieto at	Loíza at
Picocurie, definition of	Quebradillas, Lago Guajataca No. 1
Piedras at Hato Rey, Río	near dam near
at El Señorial	Quebradillas, Lago Guajataca No. 3
Pilón at Colonia Puerto Real, Quebrada	near mouth near
(Vieques)	Quebradillas, Río Guajataca above
at Río Piedras	mouth near
near Río Piedras	
Plankton, definition of	R
Playa de Guayanés, Río Guayanés	•
above mouth at	Rabo del Buey, Río Lapas near
Playa de Ponce, Quebrada del Agua at	Rabo del Buey, Río Majada at
Plena, Río Majada at La	Radiochemical program, definition of
Polychlorinated biphenyls,	Real Abajo, Río Inabón at
definition of	Real Anón, Río Inabón at
Ponce, Quebrada Ausubo near	Records, explanation of
Ponce, Río Bayagán near	Records of ground-water levels
Ponce, Río Bucaná at	Records of ground-water quality 28,29
Ponce, Río Bucaná at Highway 14 near	Records of stage and water discharge 19-24
Ponce, Río Cerrillos above Lago	Records of surface-water quality
Cerrillos near	Recoverable from bottom material.
Ponce, Río Cerrillos near	definition of
Ponce, Río Chiquito near	Resaca near Monte Resaca, Quebrada
Ponce, Río Matilde at	(Culebra)
Ponce, Río Pastillo near	Return period, definition of
Ponce, Río Portugués at	Rincón, Río Grande near
Ponce, Río Portugués at Hwy 2	Río Cañas Abajo, Río Cañas at
By-Pass at 460	Río Cañas Arriba, Río Cañas at
Ponce, Río Portugués near	Río Cañas, Río Cañas at
Portugués at Highway 2 By-Pass at Ponce, Río	Río Grande, Río Espíritu Santo near
at Ponce	Río Piedras, Río Piedras at
near Ponce	Río Piedras, Río Piedras near
near Tibes	Río Prieto at Río Prieto

Page	Page
River Gut at Highway 66 at Fairplains,	Stage-discharge relation,
St. Croix, VI	definition of
at River	Station identification numbers
near Golden Grove	St. Croix, VI, Bethlehem Gut at Highway 66
Rosario at Highway 2 near Hormigueros, Río 464	at Fairplains
at Las Vegas	St. Croix, VI, Gut 4.5 at Cane Valley 550
near Hormigueros	St. Croix, VI, Gut 10 near Altona 553
Rosario, Río Duey near	St. Croix, VI, Jolly Hill Gut at
Runoff, in inches, definition of	Jolly Hill
	St. Croix, VI, River Gut at Hwy 66 at
S	Fairplains
Sébales basis Arabanda Janu Sam	St. Croix, VI, River Gut at River
Sábalos basin, Quebrada, low-flow	
partial-record stations in	St. Croix, VI, Salt River at Canaan
Sabana basin, Río, gaging station	St. John, VI, Guinea Gut at Bethany
records in	Streamflow, definition of
at Sabana	St. Thomas, VI, Bonne Resolution
Sabana Grande, Río Cruces near	Gut at Bonne Resolution
Sabana Grande, Río Flores near	St. Thomas, VI, Turpentine Run
Sabana Grande, Río Grande near	at Mariendal
Sabana, Río Mameyes near	Substrate, definition of
Saliente at Coabey near Jayuya, Río	Summary of hydrologic conditions
Salinas at Salinas, Río	Surface and quality-of-water records
Salinas basin, Río, gaging station records in 382,383	for Puerto Rico
low-flow partial-record	Surface area, definition of
stations in	Surface-water quality, records of
Salt River at Canaan, St. Croix, VI	Surface-water records for
Salvatierra near San Lorenzo,	U.S. Virgin Islands
Quebrada	Surface-water stations in Puerto
San Germán, Río Caín near	Rico, map showing location of
San Germán, Río Cupeyes near	Surface-water stations in U.S.
San Germán, Río Guanajibo at Hwy 119 at 414	Virgin Islands, map showing
San Germán, Río Guanajibo near	location of
San Germán, Río Guanajibo below	Surface-water stations in Vieques and
San Germán, Río Hoconuco near	Culebra Islands, map showing
San Germán, Río Hoconuco (Duey) near	location of
Sanja Blanca, Río Descalabrado near	Surficial bed material,
San Juan, Bahía de San Juan No. 5 at	definition of
San Juan, Laguna San José No. 2 at	Suspended, definition of
San Lorenzo, Quebrada Salvatierra near	Suspended-recoverable, definition of
San Lorenzo, Río Grande de Loíza at	Suspended sediment, definition of
Highway 183 near	Suspended-sediment concentration,
San Patricio upstream from Lago	definition of
Cerrillos, Río	Suspended-sediment discharge, definition of
San Sebastián, Río Grande de Añasco	Suspended-sediment load,
near	definition of
Santa Isabel, Río Cañas near	Suspended-total, definition of
Santa Isabel, Río Coamo near	Susua at Palomas, Quebrada
Santa Isabel, Río Descalabrado near	Dubba ar Latorias, Queeraou IIIIIIIIIIIIIIIIIIIIIIIIIIIIIIIIIIII
Seco basin, Río, low-flow	T
partial-record stations in	<u>-</u>
Seco near Central Guamaní, Río	Tanamá at Charco Hondo, Río
Sediment, definition of	near Utuado
7-day 10-year low flow, definition of	Tallaboa basin, Río, low-flow
Sodium-adsorption-ratio, definition of	partial-record stations in
Solute, definition of	Tallaboa at Peñuelas, Río
Sonadora near El Verde, Quebrada 344,345	at Tallaboa
Special network and programs 9	near Quebrada Ceiba
Specific conductance, definition of	Taxonomy, definition of

Page	Page
Techniques of water-resources	Water-quality stations in Puerto
investigations, publications on 40-42	Rico, map showing location of
Terms, definition of	Water-resources investigations,
Thermograph, definition of	publications on techniques of
Tibes, Río Portugués near	Water year, definition of
Time-weighted average, definition of	WATSTORE data, Access to 29,30
Toa Alta, Río de La Plata at	WDR, definition of
Highway 2 near	Weighted average, definition of
Toa Vaca above Lago Toa Vaca, Río	Wells - Puerto Rico:
at Pedro García	Cibuco basin, Río
upstream from Lago Toa Vaca	Well 70 - Sabana Hoyos
Tons per acre-foot, definition of	Well 211 - Rosario No. 3
Tons per day, definition of	Well 212 - Ponderosa TW-1 490
Toronja at El Verde, Quebrada	Well 213 - Pampano No. 2
Total, definition of	Culebrinas basin, Río
Total coliform bacteria, definition of	Well 200 - Aguadilla Cement north
Total discharge, definition of	Grande de Arecibo basin, Río
Total organism count, definition of	Well 204 - Gilberto Rivera
Total-recoverable, definition of	Grande de Loíza basin, Río
Total sediment discharge,	Well 50 - USGS #50 Experimental Gurabo 506
definition of	Well 222 - Campo Rico TW
Total-sediment load, definition of	Well CJ-TW-3B - Gurabo Oeste 508 Well CJ-TW-19A - Bonneville 509
Tres Pueblos Sinkhole, Río Camuy at	
Tritium network, definition of	Grande de Manatí basin, Río Well 206 - Plazuela No. 2
Trujillo Alto, Lago Loíza No. 7 near dam near	Well 207 - Cantito La Luisa
Trujillo Alto, Río Grande de Loíza below	Well 210 - Gelo Martínez
Turabo above Borinquen, Río	Guajataca basin, Río
Turpentine Run at Mariendal,	Well 165 - Mateo Pérez, Bo. Salto 482
St. Thomas, VI	Well 202 - Carmelo Barreto-García
St. Homas, vi	Guanajibo basin, Río
U	Well 143 - Vivoni, Hacienda Amistad
U	Well CR-TW-1 - Bajura #1
Utuado, Lago Dos Bocas No. 1 near	Well CR-TW-2A - Bajura #2A
dam near	Well CR-TW-2B - Bajura #2B
Utuado, Lago Dos Bocas No. 3 at	Well CR-TW-2C - Bajura #2C
west branch near	Well CR-TW-3 - Bajura #3
Utuado, Río Grande de Arecibo near	Well CR-TW-4 - Bajura #4
Utuado, Río Tanamá near	Well CR-TW-5 - Bajura #5
	Well CR-TW-6 - Bajura #6
V	Well CR-TW-7 - Bajura #7 531
	Well CR-TW-8 - Bajura #8
Valenciano near Juncos, Río	Well CR-TW-9A - Bajura #9A
Vega Baja, Laguna Tortuguero outlet near 106	Well CR-TW-10 - Bajura #10 534
Vega Baja, Río Cibuco at	Hondo to Río Puerto Nuevo basins, Río
Viejo near Cabo Rojo, Río	Well 218 - Levittown No. 7
Vieques, Quebrada Cofresí Tributary	Well 219 - Fort Buchanan No. 1 496
near Isabel II	Well 220 - Parque San Luis Rey
Vieques, Quebrada La Mina near Esperanza	Well PN-2
Vieques, Quebrada Pilón at Colonia Puerto	Well PN-5
Real	Well PN-6
Villalba, Río Jacaguas at	Well PN-7
	Well PN-8c
W	Well PN-10
	Well PN-13
Water-discharge, records of stage and 19-24	Well PN-19 505
Water-quality partial-record	Humacao to Río Seco basins, Río
stations in Puerto Rico,	Well 6 - Juana 5
analyses of samples	Well 96 - USGS TW-2 or Yabucoa 7
as No standart 460, 470	

Page	Page
Inabón to Río Loco basins, Río	Well 8 - DPW-3586
Well 132 - Yauco 2	Well 9 - DPW-2 587
Well 141 - Restaurada 8A	Well 10 - DPW-1
La Plata basin, Río de	Well 11 - Guinea Gut Well
Well 214 - Dorado Beach No. 7 492	Well 12 - VIEO-2 590
Well 216 - Pozo Navy - Campanillas 493	Well 13 - VIEO-3 591
Well 217 - Monserrate TW - 2	Well 14 - VIEO-4 592
Salinas to Río Jacaguas basins, Río	St. Thomas
Well - 87 Alomar 1 512	Well 1 - USGS-8 (Thatch Farm Dudovick) 570
Well HW-TW-01	Well 2 - Mahogany 15 571
Well HW-TW-03C	Well 3 - Mahogany 16 572
Well HW-TW-05B	Well 4 - Mahogany 17 573
Well HW-TW-13516	Well 6 - Grade School 3
Well HW-TW-14 517	Well 7 - VIEO-1 575
Well RM - 05	Well 8 - VIEO-6 576
Well RM - 10	Well 9 - VIEO-9 577
Wells - U.S. Virgin Islands:	Well 10 - VIEO-10
St. Croix	Well 11 - VIEO-11
Well 1 - Fairplains 6 (FP6)	Wet mass, definition of
Well 2 - USGS-10, Fairplains 2 (FP2)	WSP, definition of
Well 3 - Golden Grove 6 (PW6)	
Well 4 - Golden Grove 1 (PW1)	Y
Well 6 - Adventure 28	
Well 7 - Concordia 14	Yabucoa, Río Guayanés at
Well 8 - Concordia 1 (main pump house) 562	Yagüez at Balboa, Río
Well 9 - Concordia 7	near Mayagüez
Well 10 - Barren Spot 5 (PWD-5)	Yagüez basin, Río, low-flow
Well 11 - WAPA - 02	partial-record stations in
Well 12 - WAPA - 03	water-quality records in
Well 13 - WAPA - 17	Yahuecas, Río Limani near
Well 14 - WAPA - 21a	Yauco basin, Río, gaging station
Well 15 - WAPA - 23a 569	records in
St. John	low-flow partial-record stations in
Well 1 - NPS-2 (Cruz Bay)	Yauco near Lago Lucchetti Damsite, Río
Well 2 - NPS-5 (Trunk Bay)	-
Well 3 - NPS-6 (Cinnamon Bay)	2
Well 5 - DPW-6	
Well 6 - DPW-5	Zooplankton, definition of
Well 7 - DPW-4 585	•

FACTORS FOR CONVERTING INCH-POUND UNITS TO INTERNATIONAL SYSTEM UNITS (SI)

The following factors may be used to convert the inch-pound units published herein to the International System of Units (SI).

Multiply inch-pound units	Ву	To obtain SI units
	Length	
inches (in)	2.54x10 ¹	millimeters (mm)
C (C)	2.54x10 ⁻²	meters (m)
feet (ft)	3.048x10 ⁻¹	meters (m)
miles (mi)	1.609x10°	kilometers (km)
	Area	
acres	4.047×10^3	square meters (m ²)
40103	4.047x10 ⁻¹	square hectometers (hm²)
	4.047x10 ⁻³	square kilometers (km²)
square miles (mi ²)	2.590x10°	square kilometers (km²)
	Volume	
gallons (gal)	3.785x10°	liters (L)
Barrons (Rai)	3.785x10°	cubic decimeters (dm ³)
	3.785x10 ⁻³	cubic meters (m ³)
million gallons	3.785×10^{3}	cubic meters (m ³)
8	3.785x10 ⁻³	cubic hectometers (hm³)
cubic feet (ft ³)	2.832x101	cubic decimeters (dm ³)
	2.832x10 ⁻²	cubic meters (m ³)
cfs-days	2.447x10 ³	cubic meters (m ³)
	2.447x10 ⁻³	cubic hectometers (hm³)
acre-feet (acre-ft)	1.233x10 ³	cubic meters (m ³)
	1.233x10 ⁻³	cubic hectometers (hm³)
	1.233x10 ⁻⁶	cubic kilometers (km³)
	Flow	
cubic feet per second (ft ³ /s)	2.832x101	liters per second (L/s)
the section for second (it 13)	2.832x101	cubic decimeters per second (dm ³ /s)
	2.832x10 ⁻²	cubic meters per second (m³/s)
gallons per minute (gal/min)	6.309x10 ⁻²	liters per second (L/s)
(8-4)	6.309x10 ⁻²	cubic decimeters per second (dm ³ /s)
	6.309x10 ⁻⁵	cubic meters per second (m³/s)
million gallons per day	4.381x101	cubic decimeters per second (dm ³ /s)
,	4.381x10 ⁻²	cubic meters per second (m³/s)
	Mass	
tons (short)	9.072x10 ⁻¹	megagrams (Mg) or metric tons
1171200000000	13471271155V	0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0

U.S. DEPARTMENT OF THE INTERIOR U.S. Geological Survey P.O. Box 364424 San Juan, Puerto Rico 00936-4424